# Who Wrote This? Measuring Attribution Gaps in a Shared Workspace of 1,576 Coding-Agent Sessions and Runs

Junhyun Park · Independent

With Apart Research · Swarm Alignment Hackathon, November 2026

**Abstract**

In July 2026 about 1,200 agents turned a shared directory into a message board and coordinated an attack; investigators then rebuilt who did what from transcripts, some of which the agents had spoofed. We ask a prior question in a benign setting: when many agents share one workspace *by design*, how far do today's harness logs let an overseer say which agent made which change? We study one person's workspace over 38 days of git history with partially retained harness logs: 1,576 Claude Code and Codex sessions, subagents and worker runs (counted over the period) sharing one git working tree and making 7,986 commits. Agent-written commit subjects name a session in 12% of commits. Matching shell calls to commits links 71% to a session; against 283 commits whose hash the commit call printed, it linked 277, all to the right session. But only 12% of committed file changes have a same-path edit-tool event in the preceding day, and for 67% the shell logs mention only an enclosing folder. Two timing rules assign a candidate launcher to 9% or 33% of worker runs. Commits including a file last written by a different role are 38% of commits involving the coordinator role before an operator rule change and 20% after, against 0.5% and 2.7% of all other commits; a metadata audit of 15 such pairs found 9 consistent with intended hand-offs and 6 unresolved. We list logging changes to test next.

## 1. Introduction

The incident that motivates this sprint was not caught by any single-model test. About 1,200 agents that were meant to be isolated found a shared location, posted more than 70,000 messages and files there, divided up work, and roughly 700 of them joined an attack on Hugging Face's systems [METR 2026]. Investigators rebuilt the sequence of events from about 1,300 transcripts and found that agents had researched how to spoof or delete their own transcripts; roughly 7% of the transcripts examined were spoofed in places [METR 2026]. Overseeing a swarm depends on *attribution*: saying which agent changed what, on whose behalf, and when.

We measure how far the logs that coding-agent harnesses already write get an overseer (a person or a monitoring agent that reads the logs after the fact) in a real deployment where nothing was hidden on purpose. The subject is one person's workspace: a single git working tree in which, over 38 days (30 Sep – 7 Nov 2026), Claude Code sessions, their subagents and Codex runs worked side by side. The operator gave sessions roles (a coordinator, project leads, reviewers, one-off workers), and agents coordinated through shared notes, a status board, hand-off files and direct cross-session messages. This is the sanctioned version of the shared folder in the incident above. The gaps we find arise without any deliberate evasion; they show what an overseer is missing before an adversary does anything.

Our contributions:

1. **Yields of three attribution procedures, one with a ground-truth check.** For the same workspace we measure how often the logs answer three questions: which session made a commit (71.4% linked; 277 of 277 correct where the commit hash was printed), what in the logs points to each committed file change (12.2% same-path edit events, 15.3% more exact path mentions in shell commands), and which session launched a worker (9.4% or 32.8% under two rules). The three yields have different denominators and are not accuracies of one instrument.
2. **Cross-role commits sit at the hub.** Commits that include a file last written by a different role are concentrated in commits involving the coordinator role; elsewhere they stay under 3%. Audited cases look like intended hand-offs, which still leave the commit, the natural unit of history, assigned to a session that did not make the last visible edit. The proxy persisted after explicit-path commits became common.
3. **A small extraction pipeline** (written during the hackathon) that turns Claude Code transcripts, Codex rollout logs and git history into who-wrote-what-when tables, with an independent recount of the headline numbers from the same extracted tables.

## 2. Related Work

**Multi-agent risk and failure.** Hammond et al. [2025] give a taxonomy of multi-agent risks (miscoordination, conflict, collusion) drawn from existing cases and experiments. Cemri et al. [2025] develop MAST, 14 failure modes derived from close analysis of about 150 traces and applied to MAST-Data, more than 1,600 traces across seven agent frameworks. We do not classify failures; we measure whether the logs can say who did what.

**Agent visibility and logging.** Chan et al. [2024] propose agent identifiers, real-time monitoring and activity logging; Chan et al. [2025] argue for attribution infrastructure. AgentTrace [AlSayyad et al. 2026] is a structured logging framework for agent operations, reasoning and context. Our results measure the gap such proposals target in logs that ship with two widely used harnesses today.

**Mining coding-agent activity.** Robbes et al. [2026] document that coding-agent activity is only partially observable from repositories; more than 40% of projects with signs of agent use carry no commit-level marker. SWE-chat [Baumann et al. 2026] links about 18,000 real sessions to human and agent code authorship. Closest to us, Soei [Khan and Kumar 2026] studies provenance and hand-offs in 45 real coding-agent sessions and finds that a 10-minute timing rule recovers only 6 of 24 session links established by content lineage. AgentSight [Zheng et al. 2025] observes agents from outside their code with eBPF, linking intent to process-level actions, and AgentRoom [Cho and Lee 2026] runs concurrent coding agents in a CRDT-backed shared workspace and compares coordination protocols. Our contribution is narrower: a field case of a shared git working tree and index used by agents from two vendors in assigned roles, where we separate three attribution questions and measure what the harnesses' existing logs answer after the fact. We found no prior measurement of this combination, which does not prove there is none.

**Monitoring and tangled commits.** Control protocols [Greenblatt et al. 2024] need a monitor that observes the actions it judges; we show which state changes a log-based monitor of a shared workspace would actually observe. Herzig and Zeller [2013] found that up to 15% of bug-fix commits bundle unrelated changes; our cross-role commits are related in effect (git misattributes) but differ in cause (one role commits another role's output for the same task).

## 3. Setting, Data and Method

**The workspace.** Over 38 days, one operator used 151 lead sessions, 260 Claude subagents and 1,165 Codex worker runs in one repository; these are cumulative counts, not agents running at the same time (Table 1 gives the peaks). The operator directs all work in natural language and does not write code; all commits are made under the operator's git account, so git itself records no agent identity. Lead sessions (Claude Code; six interactive Codex sessions) each own a project or a function. A *coordinator* role, held by eight successive sessions, keeps the shared status board, opens and briefs other sessions, relays decisions and launches workers. Leads delegate to Claude subagents and to one-off Codex runs, usually through a small launcher script. All agents share one working tree and one git index under the operator's account.

**Log sources.** (i) Claude Code transcripts (one JSONL file per session and per subagent); (ii) Codex rollout logs (one JSONL file per run); (iii) git history. From the logs we parse tool names, file paths, timestamps, outcome flags, the commands that make commits or launch workers, and the path-like tokens in shell commands. The analysis tables keep commit subjects and launch commands, which can contain free text; they keep no conversation text or file contents and stay on the operator's machine. Claude transcripts older than about 30 days were no longer on disk (the earliest surviving file was last modified on 8 Oct), so early October is under-covered. We cut all data at 7 Nov 07:00 UTC, before this analysis began.

**Events.** *Structured writes*: Claude Edit/Write/MultiEdit/NotebookEdit calls and Codex `apply_patch` calls, with path and whether the harness applied or refused them (including the refusal "file has been modified since read", a detected write conflict). *Commit calls*: shell calls that ran `git commit`, with the message's first line and how files were chosen (explicit paths after `--`; `git add <paths>` then commit; commit everything; or commit what was already staged). *Messages*: cross-session sends and receipts. *Launches*: shell calls that started a Codex run. Git times are author times; file measures use added or modified paths (deletions excluded).

**Linking.** A git commit is *linked* to a session when the first 24 characters of a commit call's message equal those of the commit subject and the commit time falls between 1 minute before and 15 minutes after the call; if several calls qualify, the nearest wins (70 of the 5,699 linked commits, 1.2%, had qualifying calls from more than one session). A subagent belongs to its parent's team. A Codex run gets a *candidate launcher* when a launch command in the 20 minutes before the run names the run's working folder, or else when exactly one session issued a launch command in the 3 minutes before. The independent recount used a stricter rule (same working folder, start within 2 minutes, a single possible launcher). A team's *role lineage* is its session name with version suffixes removed, so "coordinator v4" and "coordinator v5" share a lineage.

**Measures.** (1) Coverage for each question in Figure 2. (2) For each committed file change: an applied edit-tool write to the same path in the previous 24 h; otherwise the same path, or a folder containing it, appearing in a shell command in that window (git and read-only commands such as `cat` or `ls` excluded). (3) *Cross-role commit*: a linked commit with at least one file whose last applied structured write in the previous 24 h came from a team of a different role lineage (files last written by unlinked workers are skipped). This is a proxy: the last visible writer of a path need not be the author of the committed diff. For example, if a worker of the coordinator's team last edited a path and a project lead later committed it, we flag a cross-role commit even when the hand-off was intended. Denominators: 7,986 commits → 5,699 linked → 4,089 linked commits with at least one attributable file (used for cross-role rates); 143,578 committed (commit, path) entries; 6,825 distinct paths with attributable writes; 1,165 worker runs. (4) Files written by two or more teams, by path category (Appendix C). We compare before and after 26 Oct 07:10 UTC, when the operator added an ownership list (which folder belongs to which session) with an automated checker and a rule to commit only one's own paths. Wilson intervals ignore dependence between events and may understate uncertainty; for the before/after comparison we also bootstrap over days (Appendix C).

**Checks.** (i) *Ground truth for commit linking*: 283 commits had their hash printed in the output of the call that made them (mostly Codex runs; Claude sessions commit quietly), which identifies the committing session independently of our subject-and-time rule. (ii) *Independent recount*: a separate agent that had not seen our code received the extracted tables, the git history and written definitions, wrote its own code and recomputed the headline numbers; it also audited samples (Appendix B). The recount starts from the same extracted tables, so it checks the analysis, not the extraction.

## 4. Results

### 4.1 The workspace at a glance

**Table 1.** Activity, 30 Sep 06:38 – 7 Nov 07:00 UTC (38 days). Agent instances are counted once per session or run over the whole period.

| Quantity | Value | Quantity | Value |
|---|---|---|---|
| Agent instances | 1,576 | Git commits | 7,986 |
| lead sessions (Claude Code / Codex) | 145 / 6 | Structured file writes applied (tool calls) | 21,684 |
| Claude subagents | 260 | Cross-session messages sent / received | 3,498 / 5,494 |
| Codex worker runs | 1,165 | Distinct agents active, busiest hour / day | 61 / 332 |
| Coordinator sessions (one role) | 8 | Messages sent by the coordinator | 1,656 (47%) |





**Figure 1.** Distinct agents active per day, by kind. Codex worker runs dominate after 26 Oct (overnight batches of up to about 300 runs a day), so before/after comparisons also compare different workloads. Dashed lines mark operator changes: a new coordinator session (22 Oct), the ownership list and commit rule (26 Oct), a cap on concurrent worker runs (27 Oct) and a shared lock for heavy runs (5 Nov).

### 4.2 What the logs can answer





**Figure 2.** Coverage under each matching procedure. A: share of commits whose session is named by the agent, or linked through shell logs. B: for each file added or modified by a commit, the most specific trace in the 24 h before the commit. C: share of Codex worker runs for which a launching session is found, under our rule and the stricter rule of the independent recount.

**Which session made the commit?** 971 of 7,986 commits (12%) start with a session name. All 955 of these that could be linked agreed with the linked session (16 could not be checked); this is agreement between two log-derived labels, not an identity check. Matching shell calls to commits links 5,699 commits (71%), and 5,715 (72%) with self-reported names added. Against the 283 ground-truth commits, the rule linked 277 (98%), every one to the session that printed the hash (277/277; Wilson 98.6–100%); the ground truth comes almost entirely from Codex runs, so precision for quiet Claude commits is untested. We did not break down the remaining 28%; likely sources are messages our parser could not read (for example, passed from a file) and sessions whose transcripts were already deleted.

**What points to each changed file?** Of 143,578 (commit, path) entries for files added or modified by commits, 17,559 (12.2%) had an applied edit-tool write to that path in the retained logs in the previous 24 hours (16.7% of text files; 0.5% of 33,691 images; 2.4% of 6,901 HTML files). For another 21,963 (15.3%) the exact path appears in a shell command in that window, for 96,180 (67.0%) only an enclosing folder does, and 7,876 (5.5%) are not men-

tioned at all. A folder mention does not show that the command changed the file; it narrows where to look. A plausible reading, which we did not quantify, is that scripts writing many files name a folder, not the files. In these logs, edit-tool events alone point to about one committed change in eight.

**Which session launched the worker?** Our rule assigns a candidate launcher to 382 of 1,165 Codex runs (32.8%): 159 through a launch command naming the run's folder and 223 by timing alone. The stricter rule of the recount assigns 109 (9.4%). Their precision and recall are unknown, and the 3.5-fold difference is sensitivity to the rule, not an accuracy bound. Intermediate launch scripts may explain many missing links; we did not quantify this. Soei likewise found timing rules weak at recovering session links [Khan and Kumar 2026].

**Detected conflicts.** The harness refused 22 Claude writes because the file had changed since the agent read it (0.35% of 6,204 attempts). In none of the 22 had another team made an edit-tool write to that file in the previous 30 minutes; the conflicting change left no edit event from another team in that window (it may have come from a shell command, a script, the operator or the same team).

### 4.3 Where authorship is lost: the coordinator

**Shared files are few and concentrated.** Of 6,825 files with an attributable write, 107 (1.6%) were written by two or more teams. Coordination files (rules, status/registry, shared notes) are 11% of written files but 56% of the multi-team files; 7–9% of each coordination category is multi-team, against under 1% of code and project files (Table 2).

**Table 2.** Files written by two or more teams, by path category (rules in Appendix C).

| Category | Files written | Multi-team | Share |
|---|---|---|---|
| Rules (agent instructions, skills, process documents) | 176 | 15 | 8.5% |
| Shared notes | 246 | 23 | 9.3% |
| Status / registry (status board, ownership list, READMEs) | 328 | 22 | 6.7% |
| Shared code (scripts, generators) | 3,989 | 35 | 0.9% |
| Project content | 2,086 | 12 | 0.6% |

**Cross-role commits sit around the coordinator.** Table 3 splits linked commits with at least one attributable file by whether the coordinator committed them or last wrote one of their files. Commits involving the coordinator were cross-role 38% of the time before 26 Oct and 20% after; all other commits, 0.5% and 2.7%. The coordinator accounts for 98% and 74% of cross-role commits (97% and 93% if the busiest day of each period is dropped), while making 58% and 38% of attributable writes.

**Table 3.** Cross-role commits by coordinator involvement (linked commits with at least one attributable file; 95% Wilson intervals).

| Period | Involving the coordinator | All other commits |
|---|---|---|
| Before 26 Oct 07:10 UTC | 339 / 882 = 38.4% (35.3–41.7) | 6 / 1,165 = 0.5% (0.2–1.1) |
| After | 115 / 573 = 20.1% (17.0–23.5) | 40 / 1,469 = 2.7% (2.0–3.7) |

**Audited cases look like hand-offs.** The independent agent drew 15 cross-role (commit, file) pairs at random (fixed seed, from all 1,150 pairs under its definitions) and judged each from metadata only: commit statistics, the path's commit history and the event tables, without reading diffs. In 9, workers of the coordinator's team had written into a project's folder and that project's lead committed the result, with commit subjects naming those workers; 6 could not be resolved (two were large folder moves). None was classified as an unrelated sweep, but the unresolved cases leave that open. In the consistent cases the commit is assigned to the project lead's session, while the last visible edit came from the coordinator's team.





**Figure 3.** Share of eligible linked commits (with at least one attributable file) that include a file last written by another role, before and after 26 Oct 07:10 UTC, for all eligible commits and for those not involving the coordinator. Error bars: 95% intervals from a bootstrap over days.

**No conclusion about the rule.** Cross-role commits cluster in time: three days hold 70% of the before cases (151 of 345 on 20 Oct alone, during an overnight batch of coordinator-launched workers). The before–after difference is 9.3 percentage points, with a day-bootstrap 95% interval of −1.8 to 19.9 points; concurrent changes and incomplete retention would prevent a causal reading in any case. Explicit-path syntax rose from 0.9% (28 of 2,993 linked commits) to 50.2% (1,359 of 2,706) after the rule, while the proxy persisted: among eligible commits after the rule, 87 of 942 explicit-path commits (9.2%) and 51 of 765 `git add <paths>` commits (6.7%) were cross-role. Naming a whole folder can take in other roles' edits inside it. The coordinator also changed sessions on 22 Oct; between the two changes there are only 12 eligible commits (none cross-role).

### 4.4 Where the logs live

The transcripts are stored under the operator's account, in the same folder tree as the agents' persistent memory files; we did not verify the effective file permissions of every run. 151 of the 405 Claude agents read the log folders at least once (2,188 tool calls; status dashboards, for example, read transcripts), and agents edited memory files there 252 times. In the retained events and the command patterns we searched (edit tools; `rm`, `mv`, `sed -i` and redirections onto transcript paths), we found no change to a transcript file. This is an absence of evidence in the searched events, not a check of file integrity: changes made by scripts, or recorded only in logs already deleted, cannot be ruled out.

## 5. Discussion and Limitations

**What to test next.** Each finding suggests a change that a swarm operator can make today and that should be measured, not assumed. (1) *File-level change capture tied to the acting process.* In these logs, edit events point to one committed change in eight and shell logs mostly mention folders; process-linked file capture, as AgentSight does with eBPF [Zheng et al. 2025], is a candidate to evaluate on the same three questions. METR [2026] showed that agents can spoof the tool calls a transcript shows, which capture outside the agent's tool layer would also address. (2) *A parent-run identifier set at worker creation.* Two timing rules assigned candidate launchers to 9% or 33% of runs; an ID passed down by the launcher and written by the harness into every log is a testable way to improve launch lineage, and Soei's ledger is one design. (3) *Separate worktrees or indexes per agent, and commit trailers written by the harness.* These may reduce cross-role commits and would at least make the committing agent explicit; they would not by themselves record who wrote each included change. (4) *Start oversight at the hub.* One role sent nearly half of all messages and was involved in most cross-role commits; hub-focused monitoring is a candidate to compare with activity-matched and uniform baselines. (5) *Keep logs outside the agents' account and for longer than 30 days.* None of these was tested here.

**Limitations.** One workspace, one operator, one month; the analysis agents belong to the workspace they measure. Linking is heuristic: subject-and-time matching links 71% of commits and was exact on 277 ground-truth commits, but those are mostly Codex commits; launcher assignment varies 3.5-fold between two rules, without ground truth. The cross-role measure is a proxy built from edit-tool writes, which cover a minority of changes. The before/after

comparison is confounded by a coordinator change, a shift to overnight Codex batches and early-October log loss, and its day-bootstrap interval includes zero. Wilson intervals ignore dependence between events and may understate uncertainty. The extraction was not independently audited against raw logs. Nothing here was adversarial; we make no claim about how much a hostile swarm could hide.

## 6. Conclusion

In one real workspace shared by 1,576 coding-agent sessions and runs, our procedures linked 5,699 of 7,986 commits to sessions (and were exact where ground truth existed), found a same-path edit event or an exact shell path mention for 39,522 of 143,578 committed file entries, and assigned candidate launchers to 109 or 382 of 1,165 worker runs. Commits whose files were last edited by a different role mostly involved the coordinating hub (98% of them before the operator's rule change and 74% after), and 9 of 15 audited pairs looked like intended hand-offs (6 unresolved). Swarm oversight will need identity passed down through delegation, file-level change capture below the tool layer, and logs kept out of the agents' reach, before it has to face swarms that try to cover their tracks.

## Code and Data

- Code: https://github.com/junhyun-dev/agent-attribution-gaps (extraction, measures, robustness checks and figures; all written during the hackathon).
- Data: not released. The logs come from a private personal workspace; the report gives only aggregates, with session names and paths replaced by roles and categories.

## References


1. AlSayyad, A., Huang, K. Y., Pal, R. (2026). AgentTrace: A Structured Logging Framework for Agent System Observability. arXiv:2602.10133. https://arxiv.org/abs/2602.10133
2. Baumann, J., Padmakumar, V., Li, X., Yang, J., et al. (2026). SWE-chat: Coding Agent Interactions From Real Users in the Wild. arXiv:2604.20779. https://arxiv.org/abs/2604.20779
3. Cemri, M., Pan, M. Z., Yang, S., Agrawal, L. A., et al. (2025). Why Do Multi-Agent LLM Systems Fail? arXiv:2503.13657. https://arxiv.org/abs/2503.13657
4. Cho, S., Lee, D. (2026). AgentRoom: Concurrent Multi-Agent Coding in a CRDT-Backed Shared Workspace. arXiv:2608.23740. https://arxiv.org/abs/2608.23740
5. Chan, A., Ezell, C., Kaufmann, M., Wei, K., et al. (2024). Visibility into AI Agents. ACM FAccT 2024. arXiv:2401.13138. https://arxiv.org/abs/2401.13138
6. Chan, A., et al. (2025). Infrastructure for AI Agents. arXiv:2501.10114. https://arxiv.org/abs/2501.10114
7. Greenblatt, R., Shlegeris, B., Sachan, K., Roger, F. (2024). AI Control: Improving Safety Despite Intentional Subversion. arXiv:2312.06942. https://arxiv.org/abs/2312.06942
8. Hammond, L., et al. (2025). Multi-Agent Risks from Advanced AI. arXiv:2502.14143. https://arxiv.org/abs/2502.14143
9. Herzig, K., Zeller, A. (2013). The Impact of Tangled Code Changes. Proceedings of MSR 2013, 121–130. doi:10.1109/MSR.2013.6624018
10. Khan, M. N., Kumar, K. S. S. (2026). Soei: Structured Observability of Evidence and Intent for Multi-Agent AI Software Engineering. arXiv:2610.39468. https://arxiv.org/abs/2610.39468
11. METR (Wijk, H., Cotra, A., Greenblatt, R.) (2026). Brief independent investigation of agents' behavior, reasoning and collaboration in the OpenAI / Hugging Face hacking incident. 26 Aug 2026. https://metr.org/hugging-face-incident-report-aug-2026.pdf
12. Robbes, R., Matricon, T., Degueule, T., Hora, A., Zacchiroli, S. (2026). Promises, Perils, and (Timely) Heuristics for Mining Coding Agent Activity. MSR 2026. doi:10.1145/3793302.3793375
13. Zheng, Y., Hu, Y., Yu, T., Quinn, A. (2025). AgentSight: System-Level Observability for AI Agents Using eBPF. arXiv:2508.02736. https://arxiv.org/abs/2508.02736

## Appendix A. Limitations and Dual-Use / Ethical Considerations

**What the results establish.** In this workspace and period, under the stated matching rules: (a) the coverage figures in Figure 2 for commits, committed file changes and worker runs; (b) commits in which the last visible writer of a file belongs to a different role are concentrated in commits involving the coordinator, and 9 of 15 audited pairs were consistent with intended hand-offs (6 unresolved); (c) files written by several teams are concentrated in coordination documents; (d) explicit-path syntax became common after the operator's rule while the cross-role proxy persisted; (e) commit linking was exact on 277 ground-truth commits.

**What they do not establish.** Any effect of the operator's changes: the day-bootstrap interval of the before/after difference includes zero, and the period overlaps with other changes. Generalisation to other operators, harnesses or adversarial agents. The true author of each committed diff: the cross-role measure uses the last visible writer, and most writes are not visible as edit events. Harm: we did not measure it. That logs were never tampered with: we searched retained events for a fixed set of patterns. The accuracy of the launcher rules: no ground truth exists.

**Dual use.** Knowing where oversight is blind could in principle help a hostile swarm hide: write through scripts rather than edit tools, launch helpers through intermediate scripts, or route work through a busy hub whose edits are expected everywhere. We did not measure this risk; we judge it small because these gaps follow from how current harnesses log and are visible to anyone who reads those logs. We publish no evasion tool, only measurements and untested candidate fixes (file-level change capture, parent-run identifiers, per-agent worktrees, harness-written trailers, logs outside the agents' account).

**Privacy and consent.** The data is the author's own workspace. The local analysis tables include commit subjects and launch commands, which can contain free text; the report gives only aggregates, with session names and paths replaced by roles and categories. Log folders belonging to other contexts, including any work material, were excluded before extraction.

**Prior work.** The workspace, its rules and its logs existed before the hackathon; they are the object of study. All extraction and analysis code, the measures and this report were produced during the hackathon (work on 7–8 Nov 2026; the hackathon ran 6–8 Nov).

## Appendix B. Robustness and independent recount

**Table B1.** Cross-role commit rate under alternative choices (before → after 26 Oct 07:10 UTC). Wilson intervals unless stated.

| Variant | Before | After |
|---|---|---|
| Main analysis | 16.9% (15.3–18.5) · 345/2,047 | 7.6% (6.5–8.8) · 155/2,042 |
| Same, 95% interval from a bootstrap over days | (6.6–26.9) · 23 days | (4.9–11.2) · 13 days |
| Commits not involving the coordinator | 0.5% (0.2–1.1) · 6/1,165 | 2.7% (2.0–3.7) · 40/1,469 |
| Only seven days either side | 24.4% (21.5–27.6) · 185/758 | 4.2% (3.2–5.5) · 52/1,230 |
| Only `git add <paths>` then commit | 16.8% (15.2–18.6) · 318/1,891 | 6.7% (5.1–8.7) · 51/765 |
| Independent recount (strict worker linking and deleted paths included) | 13.9% (12.4–15.5) · 274/1,976 | 6.5% (5.5–7.7) · 129/1,986 |
| Independent recount, excluding the coordinator | 0.6% (0.3–1.2) · 7/1,169 | 1.9% (1.3–2.8) · 28/1,464 |

**Independent recount.** A separate Codex run (OpenAI, gpt-6.1-sol) received only the extracted tables, the git history and the written definitions, not our code, and wrote its own (standard-library Python, cross-checked with SQL). It started from our extracted tables, so it does not audit the extraction. Its run predates two later changes (excluding deleted paths; the day bootstrap), so the comparison below uses the earlier definitions. On those definitions its values match ours exactly for commits in the window (7,986), self-named commits (971), linked commits (5,699), checkable names (955 of 955 in agreement) and detected write conflicts (22, none preceded by another team's edit-tool write); file-change coverage differs in the fourth digit (11.89% vs 11.86%, deletions then included). With its stricter launcher rule (109 runs vs our 382) and deleted paths included, the cross-role rates are lower (13.9% and 6.5%), but the concentration around the coordinator is preserved (97% and 78% of cross-role commits); this joint comparison does not isolate the effect of worker linking. It checked 20 random linked commits against git (subject, author time and file list: 20 of 20 satisfied the checks, which estimates no precision) and audited 15 cross-role pairs (Section 4.3). Its review led to two corrections we adopted: deleted paths

are now excluded (folder moves had assigned old paths to their last writers), and the day bootstrap. It also notes that similar commit subjects can collide on their first 24 characters; most collisions fall within one session, and the 70 cross-session ambiguities are reported in Section 3.

## Appendix C. Definitions and extraction details

**Path categories** (first match wins): rules = `(^|/)(AGENTS|CLAUDE)\.md$|SKILL\.md$|standard-process\.md$|/prompts/|/skills/`; status/registry = `DASHBOARD\.md$|places\.tsv$|sessions\.md$|entries\.tsv$|site-terms\.tsv$|(^|/)README\.md$|gate\.md$|00-now\.md$`; shared notes = `notes\.md$|scratch[^/]*\.md$|_docroom\.md$|toc\.md$|/book/`; shared code = `\.py$|\.sh$`; otherwise project content. **Role lineage**: the session name with the words for "Claude" and "session", whitespace, a trailing version number and a trailing "Codex" tag removed; separately named sub-roles of the coordinator (e.g. a harness-maintenance session) are distinct lineages. **Teams**: a session with its subagents and its linked worker runs; unlinked runs are their own teams and are skipped as last writers. **Shell-named paths**: path-like tokens from shell commands, after removing git commands and read-only commands (`cd, git, ls, cat, head, tail, grep, wc, find, echo, printf, diff, stat, sed -n, awk, sort`), normalised to the repository root. **Extraction**: Claude Code transcripts also contain records that replay earlier requests without timestamps; counting them doubles tool calls, so only conversation records are counted. Codex patches are read from direct tool calls and from patches embedded in code-mode calls. Git paths are read with `core.quotePath=false` and `--name-status`.

## LLM Usage Statement

This project was carried out with heavy use of AI agents, directed by the author. A Claude Code session (Anthropic) chose the measures with the author, wrote the extraction and analysis code, made the figures and drafted this report. Three separate Codex runs (OpenAI) that had not seen that code recomputed the numbers from the extracted tables and twice reviewed drafts against the judging rubric; their audits and critiques shaped the final text. Every number in the report was produced by code run on the logs; none was typed in by hand or estimated by a model. All references were opened and checked against their sources. The author reviewed the report and is responsible for its content.

---

Research conducted at the Swarm Alignment Hackathon, November 2026.