

Contextual Typing

Xu Xue and Bruno C. d. S. Oliveira

The University of Hong Kong

Type Inference and what we believe ...

Type Inference and what we believe ...

- Let **type annotations** be reasonable and meaningful;

Type Inference and what we believe ...

- Let **type annotations** be reasonable and meaningful;
 - unambitious in complete type inference;
 - the places to put the annotations should be easy to predict;

Type Inference and what we believe ...

- Let **type annotations** be reasonable and meaningful;
- Type information propagation is **local**;

Type Inference and what we believe ...

- Let **type annotations** be reasonable and meaningful;
- Type information propagation is **local**;
 - better error report;
 - better performance;
 - etc.

Type Inference and what we believe ...

- Let **type annotations** be reasonable and meaningful;
- Type information propagation is **local**;
- **Guidelines** are easy to follow;

Type Inference and what we believe ...

- Let **type annotations** be reasonable and meaningful;
- Type information propagation is **local**;
- **Guidelines** are easy to follow;
 - for language designers;
 - and programmers;

Type Inference and what we believe ...

- Let **type annotations** be reasonable and meaningful;
- Type information propagation is **local**;
- **Guidelines** are easy to follow;
- **Scalability** is necessary;

Type Inference and what we believe ...

- Let **type annotations** be reasonable and meaningful;
- Type information propagation is **local**;
- **Guidelines** are easy to follow;
- **Scalability** is necessary;
- **Implementation** can be easily derived.

Bidirectional Typing

- Merge type inference and type checking by two modes;

Bidirectional Typing

- Merge type inference and type checking by two modes;
 - Inference mode: $\Gamma \vdash e \Rightarrow A$

Bidirectional Typing

- Merge type inference and type checking by two modes;
 - Inference mode: $\Gamma \vdash e \Rightarrow A$
 - Checking mode: $\Gamma \vdash e \Leftarrow A$

Bidirectional Typing

- Merge type inference and type checking by two modes;
 - Inference mode: $\Gamma \vdash e \Rightarrow A$
 - Checking mode: $\Gamma \vdash e \Leftarrow A$
- Mode-correct bidirectional type systems can be directly implemented;

Bidirectional Typing

- Merge type inference and type checking by two modes;
 - Inference mode: $\Gamma \vdash e \Rightarrow A$
 - Checking mode: $\Gamma \vdash e \Leftarrow A$
- Mode-correct bidirectional type systems can be directly implemented;

`infer :: Env → Term → Type`

`check :: Env → Term → Type → Bool`

Bidirectional Typing

- Merge type inference and type checking by two modes;
 - Inference mode: $\Gamma \vdash e \Rightarrow A$
 - Checking mode: $\Gamma \vdash e \Leftarrow A$
- Mode-correct bidirectional type systems can be directly implemented;

`infer :: Env → Term → Type`

`check :: Env → Term → Type → Bool`

- Types are propagated to neighbouring expressions;

Bidirectional Typing: Problems

- Trade-off between expressive power and backtracking;
 - more expressive, less syntax-directness;
 - all-or-nothing inference strategy;
- Unclear annotatability and rule duplication;
- Inexpressive subsumption.

Our Proposal: Contextual Typing

- Quantitative Type Assignment Systems (QTASs);
 - as a specification for programmers;
 - tells you where the annotations are needed;
 - parametrised with a counter: $\Gamma \vdash_n e : A$
- Syntax-directed Algorithmic Type Systems;
 - is decidable;
 - parametrised with a context: $\Gamma \vdash \Sigma \Rightarrow e \Rightarrow A$

Soundness

Soundness

If $\Gamma \vdash \Box \Rightarrow e \Rightarrow A$, then $\Gamma \vdash_0 e : A$.

Soundness

If $\Gamma \vdash \Box \Rightarrow e \Rightarrow A$, then $\Gamma \vdash_0 e : A$.

If $\Gamma \vdash A \Rightarrow e \Rightarrow A$, then $\Gamma \vdash_\infty e : A$.

Soundness

If $\Gamma \vdash \Box \Rightarrow e \Rightarrow A$, then $\Gamma \vdash_0 e : A$.

If $\Gamma \vdash A \Rightarrow e \Rightarrow A$, then $\Gamma \vdash_\infty e : A$.

Completeness

Soundness

If $\Gamma \vdash \Box \Rightarrow e \Rightarrow A$, then $\Gamma \vdash_0 e : A$.

If $\Gamma \vdash A \Rightarrow e \Rightarrow A$, then $\Gamma \vdash_\infty e : A$.

Completeness

If $\Gamma \vdash_0 e : A$, then $\Gamma \vdash \Box \Rightarrow e \Rightarrow A$.

Soundness

If $\Gamma \vdash \Box \Rightarrow e \Rightarrow A$, then $\Gamma \vdash_0 e : A$.

If $\Gamma \vdash A \Rightarrow e \Rightarrow A$, then $\Gamma \vdash_\infty e : A$.

Completeness

If $\Gamma \vdash_0 e : A$, then $\Gamma \vdash \Box \Rightarrow e \Rightarrow A$.

If $\Gamma \vdash_\infty e : A$, then $\Gamma \vdash A \Rightarrow e \Rightarrow A$.

Recap

- Contextual typing is a lightweight approach to type inference
 - that exploits partially known contextual information;
- It enables several improvements over bidirectional typing

Code Block

```
infer :: Int → Int → Int
```

```
infer n1 n2 = n1 + n2
```