CONTEXTUAL TYPING

Xu Xue, HKUPLG ICFP'24

TYPE INFERENCE AND WHAT WE BELIEVE

- → Having reasonable and meaningful annotations is good.
- → Local information is good.
- → Having guidelines for langauge designers and programmers is good.
- → Scalabilities are necessary.
- → Implementation can be easily derived.

→ Merge type inference and type checking by two modes;

- → Merge type inference and type checking by two modes;
 - \rightarrow Inference mode: $\Gamma \vdash e \Rightarrow A$

- → Merge type inference and type checking by two modes;
 - \rightarrow Inference mode: $\Gamma \vdash e \Rightarrow A$
 - \rightarrow Checking mode: $\Gamma \vdash e \Leftarrow A$

- → Merge type inference and type checking by two modes;
 - \rightarrow Inference mode: $\Gamma \vdash e \Rightarrow A$
 - \rightarrow Checking mode: $\Gamma \vdash e \Leftarrow A$
- → Types are propogated to neighbouring expressions;

BIDIRECTIONAL TYPING: PROBLEMS STATEMENT

- → Trade-off between expressive power and backtracking;
 - → more expressive, less syntax-directness;
 - → all-or-nothing inference strategy;
- → Unclear annotatability and rule duplication;
- → Inexpressive subsumption.

BALLOON

exclaim True

```
exclaim :: Show a \Rightarrow a \rightarrow String exclaim x = show x ++ "!"
```

→ Quantitative Type Assignment Systems (QTASs)

→ Quantitative Type Assignment Systems (QTASs)

$$\rightarrow \Gamma \vdash_n e : A$$

Counter: quantifies how much information we know from the context

- → Quantitative Type Assignment Systems (QTASs)
 - $\rightarrow \Gamma \vdash_n e : A$

Counter: quantifies how much information we know from the context

→ Algorithmic Type System

→ Quantitative Type Assignment Systems (QTASs)

$$\rightarrow \Gamma \vdash_n e : A$$

Counter: quantifies how much information we know from the context

→ Algorithmic Type System

$$\rightarrow \Gamma \vdash \Sigma \Rightarrow e \Rightarrow A$$

Context: precisely captures the information of surrounding context