Contextual Typing

Xu Xue Bruno C. d. S. Oliveira

Type Inference and what we believe ...

- Having reasonable and meaningful annotations is good;
- Local information is good;
- Having guidelines for language designers and programmers is good;
- Scalability is necessary;
- Implementation can be easily derived.

• Merge type inference and type checking by two modes;

- Merge type inference and type checking by two modes;
 - \circ Inference mode: $\Gamma \vdash e \Rightarrow A$

- Merge type inference and type checking by two modes;
 - \circ Inference mode: $\Gamma \vdash e \Rightarrow A$
 - \circ Checking mode: $\Gamma \vdash e \Leftarrow A$

- Merge type inference and type checking by two modes;
 - \circ Inference mode: $\Gamma \vdash e \Rightarrow A$
 - \circ Checking mode: $\Gamma \vdash e \Leftarrow A$
- Types are propogated to neighbouring expressions;

Bidirectional Typing: Problems Statement

- Trade-off between expressive power and backtracking;
 - more expressive, less syntax-directness;
 - o all-or-nothing inference strategy;
- Unclear annotatability and rule duplication;
- Inexpressive subsumption.

Our Proposal: Contextual Typing

- Quantitative Type Assignment Systems;
 - as a specification for programmers;
 - tells you where the annotations are needed;
 - \circ parametrised with a counter: $\Gamma \vdash_n e : A$
- Syntax-directed algorithmic Type Systems
 - is decidable;
 - \circ parametrised with a context: $\Gamma \vdash \Sigma \Rightarrow e \Rightarrow A$

If $\Gamma \vdash \Box \Rightarrow e \Rightarrow A$, then $\Gamma \vdash_0 e : A$.

If
$$\Gamma \vdash \Box \Rightarrow e \Rightarrow A$$
, then $\Gamma \vdash_0 e : A$.

If
$$\Gamma \vdash A \Rightarrow e \Rightarrow A$$
, then $\Gamma \vdash_{\infty} e : A$.

If
$$\Gamma \vdash \Box \Rightarrow e \Rightarrow A$$
, then $\Gamma \vdash_0 e : A$.

If
$$\Gamma \vdash A \Rightarrow e \Rightarrow A$$
, then $\Gamma \vdash_{\infty} e : A$.

Completeness

If
$$\Gamma \vdash \Box \Rightarrow e \Rightarrow A$$
, then $\Gamma \vdash_0 e : A$.

If
$$\Gamma \vdash A \Rightarrow e \Rightarrow A$$
, then $\Gamma \vdash_{\infty} e : A$.

Completeness

If
$$\Gamma \vdash_0 e : A$$
, then $\Gamma \vdash \Box \Rightarrow e \Rightarrow A$.

If
$$\Gamma \vdash \Box \Rightarrow e \Rightarrow A$$
, then $\Gamma \vdash_0 e : A$.

If
$$\Gamma \vdash A \Rightarrow e \Rightarrow A$$
, then $\Gamma \vdash_{\infty} e : A$.

Completeness

If
$$\Gamma \vdash_0 e : A$$
, then $\Gamma \vdash \Box \Rightarrow e \Rightarrow A$.

If
$$\Gamma \vdash_{\infty} e : A$$
, then $\Gamma \vdash A \Rightarrow e \Rightarrow A$.

Recap

- Contextual typing is a lightweight approach to type inference
 - o that exploits partially known contextual information;
- It enables several improvements over bidirectional typing