



Structure, Inference, and Optimization in Complex Networks

Tzu-Chi Yen, Dissertation Defense, June 29th, 2023


Graph 101



Graph 101



Graph 101



Graph 101

Input, raw

DATA

Paper : Authors
 $p_1 : a_1, a_2$
 $p_2 : a_2, a_4$
 $p_3 : a_1, a_2, a_3$
 $p_4 : a_3, a_4$

Papers	Authors			
	a_1	a_2	a_3	a_4
p_1	■	■		
p_2		■		■
p_3	■	■	■	
p_4			■	■

$$V = \{a_1, a_2, \dots, a_4\}$$

QUESTION

Has this pair of authors
written together?

FRAMEWORK



REPRESENTATION



Pick any 2 nodes as an edge

Output, processed
Data

Graph 101

Input, raw

DATA

Paper : Authors
 $p_1 : a_1, a_2$
 $p_2 : a_2, a_4$
 $p_3 : a_1, a_2, a_3$
 $p_4 : a_3, a_4$

Papers	Authors			
	a_1	a_2	a_3	a_4
p_1	■	■		
p_2		■		■
p_3	■	■	■	
p_4			■	■

$$V = \{a_1, a_2, \dots, a_4\}$$

QUESTION

Has this pair of authors
written together?

FRAMEWORK

Graph

REPRESENTATION

Pick any 2 nodes as an edge

Output, processed
Data

Graph 101

Input, raw

DATA

Paper : Authors
 $p_1 : a_1, a_2$
 $p_2 : a_2, a_4$
 $p_3 : a_1, a_2, a_3$
 $p_4 : a_3, a_4$

Papers	Authors			
	a_1	a_2	a_3	a_4
p_1	■	■		
p_2			■	■
p_3	■	■	■	
p_4			■	■

$$V = \{a_1, a_2, \dots, a_4\}$$

QUESTION

Has this pair of authors
written together?


FRAMEWORK

Graph



Pick any 2 nodes as an edge

REPRESENTATION



Output, processed
Data

Graph 101

Input, raw

DATA

Paper : Authors
 $p_1 : a_1, a_2$
 $p_2 : a_2, a_4$
 $p_3 : a_1, a_2, a_3$
 $p_4 : a_3, a_4$

Papers	Authors			
	a_1	a_2	a_3	a_4
p_1	■	■		
p_2				■
p_3	■	■		
p_4			■	■

$$V = \{a_1, a_2, \dots, a_4\}$$

QUESTION


Has this pair of authors
written together?

FRAMEWORK

Graph

Pick any 2 nodes as an edge

REPRESENTATION



Output, processed
Data

$$G = (V, \{e\})$$

$$\{e\} = \{(1, 2), (2, 4), (1, 2), (1, 3), (2, 3), (3, 4)\}$$

Graph 101

Input, raw

DATA

Paper : Authors

$p_1 : a_1, a_2$

$p_2 : a_2, a_4$

$p_3 : a_1, a_2, a_3$

$p_4 : a_3, a_4$


Authors

$a_1 \quad a_2 \quad a_3 \quad a_4$

Papers	p_1	p_2	p_3	p_4
p_1	■			
p_2		■		■
p_3	■	■	■	
p_4			■	■


For studying complex systems

Ecological systems



Connectomics

Contact networks



websites


Google
Wikipedia
SIAM

subway stops


Bank
London Bridge
Waterloo

Sequential behaviors

Network analysis uses graph abstractions




Higher-order analysis uses richer representations




Output, processed
Data

$$G = (V, \{e\})$$

$$\{\boldsymbol{e}\} = \{(1, 2), (2, 4), (1, 2), (1, 3), (2, 3), (3, 4)\}$$





Outline

1. Context & motivation (chapter 1)



2. Aspiration of prestige in institutional peer selection (chapter 5)



3. Community detection in bipartite networks (chapter 2)



4. Regularized methods for efficient ranking (chapter 3)



5. A detour in higher-order structures (chapter 4)

6. Conclusions & future research (chapter 6)

Outline

1. Context & motivation (chapter 1)



2. Aspiration of prestige in institutional peer selection (chapter 5)

3. Community detection in bipartite networks (chapter 2)

4. Regularized methods for efficient ranking (chapter 3)

5. A detour in higher-order structures (chapter 4)


6. Conclusions & future research (chapter 6)

Outline

1. Context & motivation (chapter 1)



2. Aspiration of prestige in institutional peer selection (chapter 5)



3. Community detection in bipartite networks (chapter 2)

4. Regularized methods for efficient ranking (chapter 3)

5. A detour in higher-order structures (chapter 4)

6. Conclusions & future research (chapter 6)



Motivation (Structure vs. Psychology)

Social hierarchy. directional bias in interactions, observed interactions tend to point from higher-ranked individuals to lower-ranked ones

Motivation (Structure vs. Psychology)

Social hierarchy. directional bias in interactions, observed interactions tend to point from higher-ranked individuals to lower-ranked ones

U.S. academic system. strong self-reinforcing hierarchy of status and signaling.

Motivation (Structure vs. Psychology)

Social hierarchy. directional bias in interactions, observed interactions tend to point from higher-ranked individuals to lower-ranked ones

Prestige drives epistemic inequality in the diffusion of scientific ideas

Allison C. Morgan , Dimitrios J. Economou, Samuel F. Way & Aaron Clauset

EPJ Data Science 7, Article number: 40 (2018) | [Cite this article](#)

U.S. academic system. strong self-reinforcing hierarchy of status and signaling.

Motivation (Structure vs. Psychology)

Social hierarchy. directional bias in interactions, observed interactions tend to point from higher-ranked individuals to lower-ranked ones

U.S. academic system. strong self-reinforcing hierarchy of status and signaling.

Labor advantages drive the greater productivity of faculty at elite universities

SAM ZHANG , K. HUNTER WAPMAN , DANIEL B. LARREMORE , AND AARON CLAUSET  [Authors Info & Affiliations](#)

SCIENCE ADVANCES • 18 Nov 2022 • Vol 8, Issue 46 • DOI: 10.1126/sciadv.abq7056

Prestige drives epistemic inequality in the diffusion of scientific ideas

Allison C. Morgan , Dimitrios J. Economou, Samuel F. Way & Aaron Clauset

[EPJ Data Science](#) 7, Article number: 40 (2018) | [Cite this article](#)

Motivation (Structure vs. Psychology)

Social hierarchy. directional bias in interactions, observed interactions tend to point from higher-ranked individuals to lower-ranked ones

U.S. academic system. strong self-reinforcing hierarchy of status and signaling.

Labor advantages drive the greater productivity of faculty at elite universities

SAM ZHANG , K. HUNTER WAPMAN , DANIEL B. LARREMORE , AND AARON CLAUSSET  [Authors Info & Affiliations](#)

SCIENCE ADVANCES • 18 Nov 2022 • Vol 8, Issue 46 • DOI: 10.1126/sciadv.abq7056

Prestige drives epistemic inequality in the diffusion of scientific ideas

[Allison C. Morgan](#) , [Dimitrios J. Economou](#), [Samuel F. Way](#) & [Aaron Clauset](#)

[EPJ Data Science](#) 7, Article number: 40 (2018) | [Cite this article](#)

Quantifying hierarchy and dynamics in US faculty hiring and retention

[K. Hunter Wapman](#) , [Sam Zhang](#), [Aaron Clauset](#) & [Daniel B. Larremore](#) 

[Nature](#) 610, 120–127 (2022) | [Cite this article](#)

Motivation (Structure vs. Psychology)

Social hierarchy. directional bias in interactions, observed interactions tend to point from higher-ranked individuals to lower-ranked ones

U.S. academic system. strong self-reinforcing hierarchy of status and signaling.

Aspiration behavior. individuals routinely aim “higher” and judge themselves to be peers of those of higher status.

Labor advantages drive the greater productivity of faculty at elite universities

SAM ZHANG , K. HUNTER WAPMAN , DANIEL B. LARREMORE , AND AARON CLAUSSET  [Authors Info & Affiliations](#)

SCIENCE ADVANCES • 18 Nov 2022 • Vol 8, Issue 46 • DOI: 10.1126/sciadv.abq7056

Prestige drives epistemic inequality in the diffusion of scientific ideas

Allison C. Morgan , Dimitrios J. Economou, Samuel F. Way & Aaron Clauset

[EPJ Data Science](#) 7, Article number: 40 (2018) | [Cite this article](#)

Quantifying hierarchy and dynamics in US faculty hiring and retention

K. Hunter Wapman , Sam Zhang, Aaron Clauset & Daniel B. Larremore 

[Nature](#) 610, 120–127 (2022) | [Cite this article](#)

Motivation (Structure vs. Psychology)

Social hierarchy. directional bias in interactions, observed interactions tend to point from higher-ranked individuals to lower-ranked ones

U.S. academic system. strong self-reinforcing hierarchy of status and signaling.

Aspiration behavior. individuals routinely aim “higher” and judge themselves to be peers of those of higher status.

SCIENCE ADVANCES | RESEARCH ARTICLE

SOCIAL SCIENCES

Aspirational pursuit of mates in online dating markets

Elizabeth E. Bruch^{1,2*} and M. E. J. Newman^{2,3}

Labor advantages drive the greater productivity of faculty at elite universities

SAM ZHANG , K. HUNTER WAPMAN , DANIEL B. LARREMORE , AND AARON CLAUSSET  [Authors Info & Affiliations](#)

SCIENCE ADVANCES • 18 Nov 2022 • Vol 8, Issue 46 • DOI: 10.1126/sciadv.abq7056

Prestige drives epistemic inequality in the diffusion of scientific ideas

Allison C. Morgan , Dimitrios J. Economou, Samuel F. Way & Aaron Clauset

[EPJ Data Science](#) 7, Article number: 40 (2018) | [Cite this article](#)

Quantifying hierarchy and dynamics in US faculty hiring and retention

K. Hunter Wapman , Sam Zhang, Aaron Clauset & Daniel B. Larremore 

[Nature](#) 610, 120–127 (2022) | [Cite this article](#)

Motivation (Structure vs. Psychology)

Social hierarchy. directional bias in interactions, observed interactions tend to point from higher-ranked individuals to lower-ranked ones

U.S. academic system. strong self-reinforcing hierarchy of status and signaling.

Aspiration behavior. individuals routinely aim “higher” and judge themselves to be peers of those of higher status.

SCIENCE ADVANCES | RESEARCH ARTICLE

SOCIAL SCIENCES

Aspirational pursuit of mates in online dating markets

Elizabeth E. Bruch^{1,2*} and M. E. J. Newman^{2,3}

Labor advantages drive the greater productivity of faculty at elite universities

SAM ZHANG , K. HUNTER WAPMAN , DANIEL B. LARREMORE , AND AARON CLAUSSET  [Authors Info & Affiliations](#)

SCIENCE ADVANCES • 18 Nov 2022 • Vol 8, Issue 46 • DOI: 10.1126/sciadv.abq7056

Prestige drives epistemic inequality in the diffusion of scientific ideas

Allison C. Morgan , Dimitrios J. Economou, Samuel F. Way & Aaron Clauset

EPJ Data Science 7, Article number: 40 (2018) | [Cite this article](#)

Quantifying hierarchy and dynamics in US faculty hiring and retention

K. Hunter Wapman , Sam Zhang, Aaron Clauset & Daniel B. Larremore 



Nature 610, 120–127 (2022) | [Cite this article](#)

Friendship networks and social status



Published online by Cambridge University Press: 15 April 2013

BRIAN BALL and M.E.J. NEWMAN



Peer institutions (dataset to study the *psychology* behind structure)



Peer institutions (dataset to study the *psychology* behind structure)



Peer institutions (dataset to study the *psychology* behind structure)



Method (data collection)

Code	Type of Institutions	<i>N</i>
15 (R1)	Doctoral Universities: Highest Research Activity	125
16 (R2)	Doctoral Universities: Higher Research Activity	114
17 (R3)	Doctoral Universities: Moderate Research Activity	30
18 (M:Large)	Master's Colleges & Universities: Larger Programs	18
19 (M:Med)	Master's Colleges & Universities: Medium Programs	2
20 (M:Small)	Master's Colleges & Universities: Small Programs	1
21 (B:A&S)	Baccalaureate Colleges: Arts & Sciences Focus	6
26 (S:Health)	Special Focus Four-Year: Other Health Professions Schools	1
27 (S:Engineer)	Special Focus Four-Year: Engineering Schools	1
		total = 298

Aspiration: Peer institutions survey (IPEDS, 2020–21). Of the 1179 institutions and 18817 nominations collected, we matched the names with the faculty hiring dataset & restricted to Ph.D.-granting ones, resulting in 298 institutions.

Institutional prestige: Faculty hiring dataset (existing, 2011–12). Each institution is annotated by a data-driven estimate of its “prestige” within the faculty hiring system. Proxy for an institution’s ability to place its graduates as faculty at other institutions.

Method (data collection)


Code	Type of Institutions	N
15 (R1)	Doctoral Universities: Highest Research Activity	125
16 (R2)	Doctoral Universities: Higher Research Activity	114
17 (R3)	Doctoral Universities: Moderate Research Activity	30
18 (M:Large)	Master's Colleges & Universities: Larger Programs	18
19 (M:Med)	Master's Colleges & Universities: Medium Programs	2
20 (M:Small)	Master's Colleges & Universities: Small Programs	1
21 (B:A&S)	Baccalaureate Colleges: Arts & Sciences Focus	6
26 (S:Health)	Special Focus Four-Year: Other Health Professions Schools	1
27 (S:Engineer)	Special Focus Four-Year: Engineering Schools	1
		total = 298

Aspiration: Peer institutions survey (IPEDS, 2020–21). Of the 1179 institutions and 18817 nominations collected, we matched the names with the faculty hiring dataset & restricted to Ph.D.-granting ones, resulting in 298 institutions.

Institutional prestige: Faculty hiring dataset (existing, 2011–12). Each institution is annotated by a data-driven estimate of its “prestige” within the faculty hiring system. Proxy for an institution’s ability to place its graduates as faculty at other institutions.

Method (quantifying prestige/desirability via SpringRank)


Each directed edge $u \rightarrow v$ implies
PhD from u becomes faculty at v



Computer science faculty hiring network; <http://tuvalu.santafe.edu/~aaronc/facultyhiring/>. See also: *Sci. Adv.* 1(1), e1400005, 2015.


Method (quantifying prestige/desirability via SpringRank)

Each directed edge $u \rightarrow v$ implies
PhD from u becomes faculty at v




Computer science faculty hiring network; <http://tuvalu.santafe.edu/~aaronc/facultyhiring/>. See also: *Sci. Adv.* 1(1), e1400005, 2015.

Each directed edge $u \rightarrow v$ implies
institution u selects institution v




Method (quantifying prestige/desirability via SpringRank)

Each directed edge $u \rightarrow v$ implies
PhD from u becomes faculty at v



Computer science faculty hiring network; <http://tuvalu.santafe.edu/~aaronc/facultyhiring/>. See also: *Sci. Adv.* 1(1), e1400005, 2015.



Each directed edge $u \rightarrow v$ implies
institution u selects institution v




SpringRank: Let $\mathbf{A} = \{A_{ij}\}$ be the adjacency matrix of a directed multigraph.
The SpringRank Model finds the ranking \mathbf{s}^* of the nodes by solving:

$$\underset{\mathbf{s} \in \mathbb{R}^N}{\text{minimize}} \frac{1}{2} \sum_{ij} A_{ij} (s_i - s_j - 1)^2 .$$


Institutions name higher prestige institutions as their peers




Institutions name higher prestige institutions as their peers



Institutions name higher prestige institutions as their peers



Institutions name higher prestige institutions as their peers




Method (logistic regression with LASSO and Laplacian regularization*)

$$\underset{\beta \in \mathbb{R}^p}{\text{minimize}} \ell(\mathbf{y}, \boldsymbol{\beta}^\top \mathbf{x}) + \frac{\lambda \|\boldsymbol{\beta}\|_1}{\text{LASSO } (\ell_1 \text{ regularization})}$$

↑ ↑ ↑


(logistic) loss actual data predicted data



Institutional features (nodal features)	Type	Total features	Total derived features (one for each edge)
Historically black?	binary	2	4
Sector (public or private)	categorical	2	4
Carnegie Classification	categorical	9	78
Two-letter state abbreviation	categorical	50	2494
Avg enrollment of full-time students	numeric	1	2
Graduation rates	numeric	1	2
Admission rates	numeric	1	2
Prestige rank	numeric	1	2

Method

(logistic regression with LASSO and Laplacian regularization*)



$$\underset{\beta \in \mathbb{R}^p}{\text{minimize}} \ell(\mathbf{y}, \boldsymbol{\beta}^\top \mathbf{x}) + \frac{\lambda \|\boldsymbol{\beta}\|_1}{\text{LASSO } (\ell_1 \text{ regularization})}$$


use when #features / #samples ~ 1

↑
(logistic) loss
↑
actual data
↑
predicted data

Institutional features (nodal features)	Type	Total features	Total derived features (one for each edge)
Historically black?	binary	2	4
Sector (public or private)	categorical	2	4
Carnegie Classification	categorical	9	78
Two-letter state abbreviation	categorical	50	2494
Avg enrollment of full-time students	numeric	1	2
Graduation rates	numeric	1	2
Admission rates	numeric	1	2
Prestige rank	numeric	1	2

Method

(logistic regression with LASSO and Laplacian regularization*)



$$\underset{\beta \in \mathbb{R}^p}{\text{minimize}} \ell(\mathbf{y}, \boldsymbol{\beta}^\top \mathbf{x}) + \frac{\lambda \|\boldsymbol{\beta}\|_1}{\text{LASSO } (\ell_1 \text{ regularization})}$$

use when #features / #samples ~ 1

↑
(logistic) loss
↑
actual data
↑
predicted data




$$\begin{aligned} & \underset{\boldsymbol{\beta}_{\text{high}}, \boldsymbol{\beta}_{\text{low}} \in \mathbb{R}^p}{\text{minimize}} \ell(\mathbf{y}_{\text{high}}, \boldsymbol{\beta}_{\text{high}}^\top \mathbf{x}) + \lambda \|\boldsymbol{\beta}_{\text{high}}\|_1 \\ & + \ell(\mathbf{y}_{\text{low}}, \boldsymbol{\beta}_{\text{low}}^\top \mathbf{x}) + \lambda \|\boldsymbol{\beta}_{\text{low}}\|_1 \\ & + \lambda_L \|\boldsymbol{\beta}_{\text{high}} - \boldsymbol{\beta}_{\text{low}}\|_2^2 \end{aligned}$$

Institutional features (nodal features)	Type	Total features	Total derived features (one for each edge)
Historically black?	binary	2	4
Sector (public or private)	categorical	2	4
Carnegie Classification	categorical	9	78
Two-letter state abbreviation	categorical	50	2494
Avg enrollment of full-time students	numeric	1	2
Graduation rates	numeric	1	2
Admission rates	numeric	1	2
Prestige rank	numeric	1	2

Idea: Parameters in adjacent strata should be similar.
Plus, parameters are encouraged to be zero (not used).


Rich peer decision patterns (categorical features)

- ▷ : higher prestige
- △ : lower prestige





Rich peer decision patterns (categorical features)

- ▷ : higher prestige
- △ : lower prestige




HBCU tends (slightly) to choose other HBCUs.





Rich peer decision patterns (categorical features)

- ☒ : higher prestige
- ☐ : lower prestige




HBCU tends (slightly) to choose other HBCUs.

Private schools don't choose public schools (vv).



Rich peer decision patterns (categorical features)



- ☒ : higher prestige
- ☐ : lower prestige



HBCU tends (slightly) to choose other HBCUs.


Private schools don't choose public schools (vv).

R1 chooses other R1, but **not R2**.



Rich peer decision patterns (categorical features)

- ▷ : higher prestige
- △ : lower prestige





HBCU tends (slightly) to choose other HBCUs.


Private schools don't choose public schools (vv).

R1 chooses other R1, but **not R2**.

R2 chooses other R2, but also chooses R1.




Prestige determines peer decision (numeric features)




$i \rightarrow j$	Adm	Size	Grad	Prestige
Similarity (unsigned) $(x_j - x_i)^2$	\emptyset	\emptyset	\emptyset	\emptyset
Difference (signed) $x_j - x_i$	\emptyset	✓	✓	✓


Prestige determines peer decision (numeric features)




$i \rightarrow j$	Adm	Size	Grad	Prestige
Similarity (unsigned) $(x_j - x_i)^2$	\emptyset	\emptyset	\emptyset	\emptyset
Difference (signed) $x_j - x_i$	\emptyset	✓	✓	✓



Prestige determines peer decision (numeric features)




$i \rightarrow j$	Adm	Size	Grad	Prestige
Similarity (unsigned) $(x_j - x_i)^2$	\emptyset	\emptyset	\emptyset	\emptyset
Difference (signed) $x_j - x_i$	\emptyset	✓	✓	✓




Outcome: Aspiration for a higher prestige rank is a significant predictive variable (for the elite institutions)


Wait... What about other schools?





Wait... What about other schools?



Wait... What about other schools?



Wait... What about other schools?




Method (clustering via the bipartite stochastic block model)

Conventional.

Bipartite network. of conferences and authors.

Nonnegative matrix factorization. Clustering who attend what conference.

Problems. How many groups to choose? Sometimes just outputs 1 group (e.g., scarce data) 😭



Lin et al., SIAM Conference on Data Mining (2010)

Method

(clustering via the bipartite stochastic block model)

Conventional.

Bipartite network. of conferences and authors.

Nonnegative matrix factorization. Clustering who attend what conference.

Problems. How many groups to choose? Sometimes just outputs 1 group (e.g., scarce data) 😭

Novel.

Nonparametric Bayesian modeling. Probabilistic generative model that detects communities. 😎




Communities with statistical validation

(e.g., description length, posterior likelihood)

Known: The bipartite structure, i.e., which node is of which type. Edges are given (measurement is perfect).

Unknown: Of which group should a node be assigned to.



SBMs formalize the concept of “large-scale structure”





Image credit: Aaron Clauset

Bipartite stochastic block model

$$P(\mathbf{A}, \mathbf{k}, \mathbf{e}, \mathbf{b}) = P(\mathbf{A} \mid \mathbf{k}, \mathbf{e}, \mathbf{b})P(\mathbf{k} \mid \mathbf{e}, \mathbf{b})P(\mathbf{e} \mid \mathbf{b})P(\mathbf{b})$$

Likelihood Prior



Bipartite stochastic block model

$$P_{\text{bi}}(A, k, e, b) = \frac{\prod_i k_i! \prod_{r < s} e_{rs}!}{\prod_r e_r! \prod_{i < j} A_{ij}!} \prod_r \frac{\prod_k \eta_k^r!}{n_r!} \frac{1}{q(e_r, n_r)} \binom{B_I B_{II}}{E}^{-1} \frac{\prod_r n_r!}{N_I! N_{II}!} \left(\frac{N_I - 1}{B_I - 1}\right)^{-1} \left(\frac{N_{II} - 1}{B_{II} - 1}\right)^{-1} \frac{1}{N_I N_{II}}.$$

$$P(A, k, e, b) = P(A | k, e, b) P(k | e, b) P(e | b) P(b)$$

Likelihood Prior

Bipartite stochastic block model

$$P_{\text{bi}}(A, k, e, b) = \frac{\prod_i k_i! \prod_{r < s} e_{rs}!}{\prod_r e_r! \prod_{i < j} A_{ij}!} \prod_r \frac{\prod_k \eta_k^r!}{n_r!} \frac{1}{q(e_r, n_r)} \binom{B_I B_{II}}{E}^{-1} \frac{\prod_r n_r!}{N_I! N_{II}!} \left(\frac{N_I - 1}{B_I - 1}\right)^{-1} \left(\frac{N_{II} - 1}{B_{II} - 1}\right)^{-1} \frac{1}{N_I N_{II}}.$$

$$P(A, k, e, b) = P(A | k, e, b) P(k | e, b) P(e | b) P(b) = P(A, \{b_i\})$$

Likelihood Prior



Optimized with Markov chain Monte Carlo
(Metropolis-Hastings)

Bipartite stochastic block model

$$P_{\text{bi}}(A, k, e, b) = \frac{\prod_i k_i! \prod_{r < s} e_{rs}!}{\prod_r e_r! \prod_{i < j} A_{ij}!} \prod_r \frac{\prod_k \eta_k^r!}{n_r!} \frac{1}{q(e_r, n_r)} \left(\begin{array}{c} B_{\text{I}} B_{\text{II}} \\ E \end{array} \right)^{-1} \frac{\prod_r n_r!}{N_{\text{I}}! N_{\text{II}}!} \left(\begin{array}{c} N_{\text{I}} - 1 \\ B_{\text{I}} - 1 \end{array} \right)^{-1} \left(\begin{array}{c} N_{\text{II}} - 1 \\ B_{\text{II}} - 1 \end{array} \right)^{-1} \frac{1}{N_{\text{I}} N_{\text{II}}}.$$

$$P(A, k, e, b) = P(A \mid k, e, b)P(k \mid e, b)P(e \mid b)P(b) = P(A, \{b_i\})$$

Likelihood Prior



Optimized with Markov chain Monte Carlo
(Metropolis-Hastings)

Enhanced model sensitivity: More detailed prior (e.g., we know *a priori* that the network is bipartite) gives more sensitive model to detect structure.

Bipartite stochastic block model

$$P_{\text{bi}}(A, \boldsymbol{k}, \boldsymbol{e}, \boldsymbol{b}) = \frac{\prod_i k_i! \prod_{r < s} e_{rs}!}{\prod_r e_r! \prod_{i < j} A_{ij}!} \prod_r \frac{\prod_k \eta_k^r!}{n_r!} \frac{1}{q(e_r, n_r)} \left(\begin{array}{c} B_{\text{I}} B_{\text{II}} \\ E \end{array} \right)^{-1} \frac{\prod_r n_r!}{N_{\text{I}}! N_{\text{II}}!} \left(\begin{array}{c} N_{\text{I}} - 1 \\ B_{\text{I}} - 1 \end{array} \right)^{-1} \left(\begin{array}{c} N_{\text{II}} - 1 \\ B_{\text{II}} - 1 \end{array} \right)^{-1} \frac{1}{N_{\text{I}} N_{\text{II}}}.$$

$$P(A, k, e, b) = P(A \mid k, e, b)P(k \mid e, b)P(e \mid b)P(b) = P(A, \{b_i\})$$


Likelihood Prior




Enhanced model sensitivity: More detailed prior (e.g., we know *a priori* that the network is bipartite) gives more sensitive model to detect structure.

New algorithm comes with the new prior: Prior may introduce new variables, hence a new algorithm is needed.

Use dynamic programming
to navigate the landscape



Testing performance: bipartite priors & search matter



Comparison with hierarchical SBM


Table I. Results for 24 empirical networks. Number of nodes n_I , n_{II} , mean degree $\langle k \rangle$, number of type-I groups B_I , and number of type-II groups B_{II} , and description length per edge Σ/E . Superscripts: b-biSBM, g-SBM, h-hSBM. L indicates the number of levels found by the hSBM. Reported values indicate best of 100 independent runs. Unless otherwise noted, data are accessible from the Colorado Index of Complex Networks (ICON) [52]. The confidence level is marked with asterisks^a.

Dataset	N_I	N_{II}	$\langle k \rangle$	(B_I^b, B_{II}^b)	(B_I^g, B_{II}^g)	(B_I^h, B_{II}^h)	$\langle L+1 \rangle$	Σ^b/E	Σ^h/E
Southern women interactions [53]	18	14	5.56	(1, 1)	(1, 1)	(1, 1)	2.0	2.15*	2.26
Joern plant-herbivore web [54]	22	52	4.97	(2, 2)	(1, 1)	(1, 1)	2.0	2.64*	2.74
Swingers and parties [55]	57	39	4.83	(1, 1)	(1, 1)	(1, 1)	2.0	2.92*	2.97
McMullen pollination web [56]	54	105	2.57	(2, 2)	(2, 2)	(1, 1)	2.0	2.87*	3.02
Ndrangheta criminals [57]	156	47	4.48	(3, 4)	(3, 3)	(3, 4)	2.87	3.44*	3.49
Abu Sayyaf kidnappings ^b [58]	246	105	2.28	(2, 2)	(1, 1)	(1, 1)	2.0	4.50*	4.54
Virus-host interactome [59]	53	307	2.52	(2, 2)	(1, 1)	(1, 1)	2.0	3.78*	3.81
Clements-Long plant-pollinator [60]	275	96	4.98	(1, 1)	(1, 1)	(1, 1)	2.0	3.45*	3.47
Human musculoskeletal system [61]	173	270	4.30	(7, 8)	(5, 5)	(8, 8)	4.01	3.94	3.94
Mexican drug trafficking ^b [62]	765	10	16.1	(12, 8)	(8, 7)	(10, 6)	3.11	1.26*	1.29
Country-language network [63]	254	614	2.89	(4, 5)	(2, 2)	(4, 3)	2.11	4.53*	4.56
Malaria gene similarity [44]	297	806	5.38	(15, 16)	(6, 6)	(25, 20)	4.95	4.73	4.67*
Protein complex-drug [64]	739	680	5.20	(20, 22)	(14, 14)	(35, 39)	5.06	3.65	3.50**
Robertson plant-pollinator [65]	456	1428	16.2	(20, 18)	(11, 11)	(20, 19)	4.0	3.10*	3.10
Human gene-disease network [66]	1419	516	4.06	(13, 14)	(9, 9)	(35, 36)	5.04	5.02	4.80**
Food ingredients-flavors web [67]	1525	1107	27.9	(27, 69)	(20, 29)	(42, 130)	4.91	2.55	2.51**
Wikipedia doc-word network [68]	63	3140	24.8	(22, 206)	(18, 23)	(29, 71)	4.17	1.58	1.51**
Foursquare check-ins [69]	2060	2876	11.0	(65, 66)	(40, 40)	(244, 248)	5.2	5.92	5.09**
Ancient metabolic network [70]	5651	5252	4.22	(18, 22)	(5, 5)	(17, 21)	4.26	5.68**	5.82
Marvel Universe characters [71]	6486	12942	9.95	(68, 72)	(67, 62)	(365, 314)	6.24	4.70	4.42***
Reuters news stories [72]	19757	38677	33.5	(396, 440)	(87, 108)	(294, 463)	6.25	4.22	4.16***
IMDb movie-actor dataset ^c	53158	39768	6.49	(91, 92)	(69, 68)	(264, 265)	6.22	7.40	7.30***
YouTube group memberships [73]	94238	30087	4.72	(62, 66)	(37, 38)	(221, 238)	5.9	7.07**	7.13
DBpedia writer network [74]	89355	46213	2.13	(22, 26)	(2, 3)	(2, 3)	2.16	10.32**	10.41

^a Via the posterior odds ratio: * : $\Lambda < 10^{-2}$; ** : $\Lambda < 10^{-100}$; *** : $\Lambda < 10^{-10000}$.

^b Temporal data with timestamps are aggregated, making a multigraph.

^c Data available at <http://www.imdb.com/interfaces>. IMDb copyright permits redistribution of data only in unaltered form.



Comparison with hierarchical SBM

Table I. Results for 24 empirical networks. Number of nodes n_I , n_{II} , mean degree $\langle k \rangle$, number of type I groups (B_I^b, B_{II}^b) , type II groups (B_I^g, B_{II}^g) , type III groups (B_I^h, B_{II}^h) , number of levels $\langle L+1 \rangle$, description length per edge Σ/E . Superscripts: b-biSBM, g-SBM, h-hSBM. L indicates the number of levels found by the hSBM. Reported values indicate best of 100 independent runs. Unless otherwise noted, data are accessible from the Additional files section of the International Complex Networks and their Applications Conference (ICON) [52]. The confidence level is marked with asterisks^a.


Dataset	N_I	N_{II}	$\langle k \rangle$	(B_I^b, B_{II}^b)	(B_I^g, B_{II}^g)	(B_I^h, B_{II}^h)	$\langle L+1 \rangle$	Σ^b/E	Σ^h/E
Southern women interactions [53]	18	14	5.56	(1, 1)	(1, 1)	(1, 1)	2.0	2.15*	2.26
Joern plant-herbivore web [54]	22	52	4.97	(2, 2)	(1, 1)	(1, 1)	2.0	2.64*	2.74
Swingers and parties [55]	57	39	4.83	(1, 1)	(1, 1)	(1, 1)	2.0	2.92*	2.97
McMullen pollination web [56]	54	105	2.57	(2, 2)	(2, 2)	(1, 1)	2.0	2.87*	3.02
Ndrangheta criminals [57]	156	47	4.48	(3, 4)	(3, 3)	(3, 4)	2.87	3.44*	3.49
Abu Sayyaf kidnappings ^b [58]	246	105	2.28	(2, 2)	(1, 1)	(1, 1)	2.0	4.50*	4.54
Virus-host interactome [59]	53	307	2.52	(2, 2)	(1, 1)	(1, 1)	2.0	3.78*	3.81
Clements-Long plant-pollinator [60]	275	96	4.98	(1, 1)	(1, 1)	(1, 1)	2.0	3.45*	3.47
Human musculoskeletal system [61]	173	270	4.30	(7, 8)	(5, 5)	(8, 8)	4.01	3.94	3.94
Mexican drug trafficking ^b [62]	765	10	16.1	(12, 8)	(8, 7)	(10, 6)	3.11	1.26*	1.29
Country-language network [63]	254	614	2.89	(4, 5)	(2, 2)	(4, 3)	2.11	4.53*	4.56
Malaria gene similarity [44]	297	806	5.38	(15, 16)	(6, 6)	(25, 20)	4.95	4.73	4.67*
Protein complex-drug [64]	739	680	5.20	(20, 22)	(14, 14)	(35, 39)	5.06	3.65	3.50**
Robertson plant-pollinator [65]	456	1428	16.2	(20, 18)	(11, 11)	(20, 19)	4.0	3.10*	3.10
Human gene-disease network [66]	1419	516	4.06	(13, 14)	(9, 9)	(35, 36)	5.04	5.02	4.80**
Food ingredients-flavors web [67]	1525	1107	27.9	(27, 69)	(20, 29)	(42, 130)	4.91	2.55	2.51**
Wikipedia doc-word network [68]	63	3140	24.8	(22, 206)	(18, 23)	(29, 71)	4.17	1.58	1.51**
Foursquare check-ins [69]	2060	2876	11.0	(65, 66)	(40, 40)	(244, 248)	5.2	5.92	5.09**
Ancient metabolic network [70]	5651	5252	4.22	(18, 22)	(5, 5)	(17, 21)	4.26	5.68**	5.82
Marvel Universe characters [71]	6486	12942	9.95	(68, 72)	(67, 62)	(365, 314)	6.24	4.70	4.42***
Reuters news stories [72]	19757	38677	33.5	(396, 440)	(87, 108)	(294, 463)	6.25	4.22	4.16***
IMDb movie-actor dataset ^c	53158	39768	6.49	(91, 92)	(69, 68)	(264, 265)	6.22	7.40	7.30***
YouTube group memberships [73]	94238	30087	4.72	(62, 66)	(37, 38)	(221, 238)	5.9	7.07**	7.13
DBpedia writer network [74]	89355	46213	2.13	(22, 26)	(2, 3)	(2, 3)	2.16	10.32**	10.41

^a Via the posterior odds ratio: * : $\Lambda < 10^{-2}$; ** : $\Lambda < 10^{-100}$; *** : $\Lambda < 10^{-10000}$.

^b Temporal data with timestamps are aggregated, making a multigraph.

^c Data available at <http://www.imdb.com/interfaces>. IMDb copyright permits redistribution of data only in unaltered form.

Avg. description length,
the lower the better



Comparison with hierarchical SBM

Table I. Results for 24 empirical networks. Number of nodes n_I , n_{II} , mean degree $\langle k \rangle$, number of type I groups (B_I^b, B_{II}^b) , type II groups (B_I^g, B_{II}^g) , type III groups (B_I^h, B_{II}^h) , average number of levels $\langle L+1 \rangle$, description length per edge Σ/E . Superscripts: b-biSBM, g-SBM, h-hSBM. L indicates the number of levels found by the hSBM. Reported values indicate best of 100 independent runs. Unless otherwise noted, data are accessible from the Additional files section of the International Complex Networks and their Applications Conference (ICON) [52]. The confidence level is marked with asterisks^a.


Dataset	N_I	N_{II}	$\langle k \rangle$	(B_I^b, B_{II}^b)	(B_I^g, B_{II}^g)	(B_I^h, B_{II}^h)	$\langle L+1 \rangle$	Σ^b/E	Σ^h/E
Southern women interactions [53]	18	14	5.56	(1, 1)	(1, 1)	(1, 1)	2.0	2.15*	2.26
Joern plant-herbivore web [54]	22	52	4.97	(2, 2)	(1, 1)	(1, 1)	2.0	2.64*	2.74
Swingers and parties [55]	57	39	4.83	(1, 1)	(1, 1)	(1, 1)	2.0	2.92*	2.97
McMullen pollination web [56]	54	105	2.57	(2, 2)	(2, 2)	(1, 1)	2.0	2.87*	3.02
Ndrangheta criminals [57]	156	47	4.48	(3, 4)	(3, 3)	(3, 4)	2.87	3.44*	3.49
Abu Sayyaf kidnappings ^b [58]	246	105	2.28	(2, 2)	(1, 1)	(1, 1)	2.0	4.50*	4.54
Virus-host interactome [59]	53	307	2.52	(2, 2)	(1, 1)	(1, 1)	2.0	3.78*	3.81
Clements-Long plant-pollinator [60]	275	96	4.98	(1, 1)	(1, 1)	(1, 1)	2.0	3.45*	3.47
Human musculoskeletal system [61]	173	270	4.30	(7, 8)	(5, 5)	(8, 8)	4.01	3.94	3.94
Mexican drug trafficking ^b [62]	765	10	16.1	(12, 8)	(8, 7)	(10, 6)	3.11	1.26*	1.29
Country-language network [63]	254	614	2.89	(4, 5)	(2, 2)	(4, 3)	2.11	4.53*	4.56
Malaria gene similarity [44]	297	806	5.38	(15, 16)	(6, 6)	(25, 20)	4.95	4.73	4.67*
Protein complex-drug [64]	739	680	5.20	(20, 22)	(14, 14)	(35, 39)	5.06	3.65	3.50**
Robertson plant-pollinator [65]	456	1428	16.2	(20, 18)	(11, 11)	(20, 19)	4.0	3.10*	3.10
Human gene-disease network [66]	1419	516	4.06	(13, 14)	(9, 9)	(35, 36)	5.04	5.02	4.80**
Food ingredients-flavors web [67]	1525	1107	27.9	(27, 69)	(20, 29)	(42, 130)	4.91	2.55	2.51**
Wikipedia doc-word network [68]	63	3140	24.8	(22, 206)	(18, 23)	(29, 71)	4.17	1.58	1.51**
Foursquare check-ins [69]	2060	2876	11.0	(65, 66)	(40, 40)	(244, 248)	5.2	5.92	5.09**
Ancient metabolic network [70]	5651	5252	4.22	(18, 22)	(5, 5)	(17, 21)	4.26	5.68**	5.82
Marvel Universe characters [71]	6486	12942	9.95	(68, 72)	(67, 62)	(365, 314)	6.24	4.70	4.42***
Reuters news stories [72]	19757	38677	33.5	(396, 440)	(87, 108)	(294, 463)	6.25	4.22	4.16***
IMDb movie-actor dataset ^c	53158	39768	6.49	(91, 92)	(69, 68)	(264, 265)	6.22	7.40	7.30***
YouTube group memberships [73]	94238	30087	4.72	(62, 66)	(37, 38)	(221, 238)	5.9	7.07**	7.13
DBpedia writer network [74]	89355	46213	2.13	(22, 26)	(2, 3)	(2, 3)	2.16	10.32**	10.41

^a Via the posterior odds ratio: * : $\Lambda < 10^{-2}$; ** : $\Lambda < 10^{-100}$; *** : $\Lambda < 10^{-10000}$.

^b Temporal data with timestamps are aggregated, making a multigraph.

^c Data available at <http://www.imdb.com/interfaces>. IMDb copyright permits redistribution of data only in unaltered form.

Avg. description length,
the lower the better



For smaller networks,
bipartite SBM is better.

Comparison with hierarchical SBM

Table I. Results for 24 empirical networks. Number of nodes n_I , n_{II} , mean degree $\langle k \rangle$, number of type I groups (B_I^b, B_{II}^b) , type II groups (B_I^g, B_{II}^g) , type III groups (B_I^h, B_{II}^h) , average number of levels $\langle L+1 \rangle$, description length per edge Σ/E . Superscripts: b-biSBM, g-SBM, h-hSBM. L indicates the number of levels found by the hSBM. Reported values indicate best of 100 independent runs. Unless otherwise noted, data are accessible from the Additional files section of the International Complex Networks and their Applications Conference (ICON) [52]. The confidence level is marked with asterisks^a.


Dataset	N_I	N_{II}	$\langle k \rangle$	(B_I^b, B_{II}^b)	(B_I^g, B_{II}^g)	(B_I^h, B_{II}^h)	$\langle L+1 \rangle$	Σ^b/E	Σ^h/E
Southern women interactions [53]	18	14	5.56	(1, 1)	(1, 1)	(1, 1)	2.0	2.15*	2.26
Joern plant-herbivore web [54]	22	52	4.97	(2, 2)	(1, 1)	(1, 1)	2.0	2.64*	2.74
Swingers and parties [55]	57	39	4.83	(1, 1)	(1, 1)	(1, 1)	2.0	2.92*	2.97
McMullen pollination web [56]	54	105	2.57	(2, 2)	(2, 2)	(1, 1)	2.0	2.87*	3.02
Ndrangheta criminals [57]	156	47	4.48	(3, 4)	(3, 3)	(3, 4)	2.87	3.44*	3.49
Abu Sayyaf kidnappings ^b [58]	246	105	2.28	(2, 2)	(1, 1)	(1, 1)	2.0	4.50*	4.54
Virus-host interactome [59]	53	307	2.52	(2, 2)	(1, 1)	(1, 1)	2.0	3.78*	3.81
Clements-Long plant-pollinator [60]	275	96	4.98	(1, 1)	(1, 1)	(1, 1)	2.0	3.45*	3.47
Human musculoskeletal system [61]	173	270	4.30	(7, 8)	(5, 5)	(8, 8)	4.01	3.94	3.94
Mexican drug trafficking ^b [62]	765	10	16.1	(12, 8)	(8, 7)	(10, 6)	3.11	1.26*	1.29
Country-language network [63]	254	614	2.89	(4, 5)	(2, 2)	(4, 3)	2.11	4.53*	4.56
Malaria gene similarity [44]	297	806	5.38	(15, 16)	(6, 6)	(25, 20)	4.95	4.73	4.67*
Protein complex-drug [64]	739	680	5.20	(20, 22)	(14, 14)	(35, 39)	5.06	3.65	3.50**
Robertson plant-pollinator [65]	456	1428	16.2	(20, 18)	(11, 11)	(20, 19)	4.0	3.10*	3.10
Human gene-disease network [66]	1419	516	4.06	(13, 14)	(9, 9)	(35, 36)	5.04	5.02	4.80**
Food ingredients-flavors web [67]	1525	1107	27.9	(27, 69)	(20, 29)	(42, 130)	4.91	2.55	2.51**
Wikipedia doc-word network [68]	63	3140	24.8	(22, 206)	(18, 23)	(29, 71)	4.17	1.58	1.51**
Foursquare check-ins [69]	2060	2876	11.0	(65, 66)	(40, 40)	(244, 248)	5.2	5.92	5.09**
Ancient metabolic network [70]	5651	5252	4.22	(18, 22)	(5, 5)	(17, 21)	4.26	5.68**	5.82
Marvel Universe characters [71]	6486	12942	9.95	(68, 72)	(67, 62)	(365, 314)	6.24	4.70	4.42***
Reuters news stories [72]	19757	38677	33.5	(396, 440)	(87, 108)	(294, 463)	6.25	4.22	4.16***
IMDb movie-actor dataset ^c	53158	39768	6.49	(91, 92)	(69, 68)	(264, 265)	6.22	7.40	7.30***
YouTube group memberships [73]	94238	30087	4.72	(62, 66)	(37, 38)	(221, 238)	5.9	7.07**	7.13
DBpedia writer network [74]	89355	46213	2.13	(22, 26)	(2, 3)	(2, 3)	2.16	10.32**	10.41

^a Via the posterior odds ratio: * : $\Lambda < 10^{-2}$; ** : $\Lambda < 10^{-100}$; *** : $\Lambda < 10^{-10000}$.

^b Temporal data with timestamps are aggregated, making a multigraph.

^c Data available at <http://www.imdb.com/interfaces>. IMDb copyright permits redistribution of data only in unaltered form.

Avg. description length,
the lower the better



For smaller networks,
bipartite SBM is better.

For larger+sparser networks,
bipartite SBM is better.

Implications

Bayesian framework. data becomes a part of the model, algorithm becomes data-dependent, i.e., **some data may be harder to fit** (opportunities for improvement).


Always choose a simpler model. If not possible to attain (e.g., no good definition of “simple-ness”), choose a more **flexible** one.

A handful of groups explain most nomination behaviors

Type-I nodes: feature pair tags, to cluster as B_I groups

Type-II nodes: nominations, to cluster as B_{II} groups

feature pair tags nominations




Bipartite expanded
feature network

A handful of groups explain most nomination behaviors

Type-I nodes: feature pair tags, to cluster as B_I groups

Type-II nodes: nominations, to cluster as B_{II} groups



Code	Type of Institutions	N	N_I	N_{II}	E	B_I	B_{II}	Σ/E
15	Doctoral Universities: Highest Research Activity	117	946	1956	13692	5	2	2.45
16	Doctoral Universities: Higher Research Activity	112	833	1757	12299	8	2	2.67
17	Doctoral Universities: Moderate Research Activity	102	596	1815	12705	11	3	2.68
18	Master's Colleges & Universities: Larger Programs	251	958	4118	28825	16	3	2.73
19	Master's Colleges & Universities: Medium Programs	129	656	2082	14574	14	3	2.71
20	Master's Colleges & Universities: Small Programs	78	502	1169	8183	6	2	2.70
21	Baccalaureate Colleges: Arts & Sciences Focus	176	778	3105	21735	4	2	2.48
22	Baccalaureate Colleges: Diverse Fields	144	698	2129	14903	12	3	2.69
23	Baccalaureate/Associate's Colleges: Mixed Baccalaureate/Associate's	126	32	232	1624	4	2	2.45
24	Special Focus Four-Year: Faith-Related Institutions	1	9	2	14	1	1	1.31
26	Special Focus Four-Year: Other Health Professions Schools	5	53	42	293	1	1	2.55
27	Special Focus Four-Year: Engineering Schools	3	45	24	168	1	1	2.53
28	Special Focus Four-Year: Other Technology-Related Schools	3	53	38	266	1	1	2.37
29	Special Focus Four-Year: Business & Management Schools	6	47	122	854	1	1	2.27
30	Special Focus Four-Year: Arts, Music & Design Schools	18	138	196	1372	1	1	2.41
32	Special Focus Four-Year: Other Special Focus Institutions	2	38	30	209	1	1	2.34


Bipartite expanded
feature network

total = 1179

A handful of groups explain most nomination behaviors

Type-I nodes: feature pair tags, to cluster as B_I groups

Type-II nodes: nominations, to cluster as B_{II} groups




Code	Type of Institutions	N	<i>N</i> _I	<i>N</i> _{II}	E	<i>B</i> _I	<i>B</i> _{II}	Σ/E
15	Doctoral Universities: Highest Research Activity	117	946	1956	13692	5	2	2.45
16	Doctoral Universities: Higher Research Activity	112	833	1757	12299	8	2	2.67
17	Doctoral Universities: Moderate Research Activity	102	596	1815	12705	11	3	2.68
18	Master's Colleges & Universities: Larger Programs	251	958	4118	28825	16	3	2.73
19	Master's Colleges & Universities: Medium Programs	129	656	2082	14574	14	3	2.71
20	Master's Colleges & Universities: Small Programs	78	502	1169	8183	6	2	2.70
21	Baccalaureate Colleges: Arts & Sciences Focus	176	778	3105	21735	4	2	2.48
22	Baccalaureate Colleges: Diverse Fields	144	698	2129	14903	12	3	2.69
23	Baccalaureate/Associate's Colleges: Mixed Baccalaureate/Associate's	126	32	232	1624	4	2	2.45
24	Special Focus Four-Year: Faith-Related Institutions	1	9	2	14	1	1	1.31
26	Special Focus Four-Year: Other Health Professions Schools	5	53	42	293	1	1	2.55
27	Special Focus Four-Year: Engineering Schools	3	45	24	168	1	1	2.53
28	Special Focus Four-Year: Other Technology-Related Schools	3	53	38	266	1	1	2.37
29	Special Focus Four-Year: Business & Management Schools	6	47	122	854	1	1	2.27
30	Special Focus Four-Year: Arts, Music & Design Schools	18	138	196	1372	1	1	2.41
32	Special Focus Four-Year: Other Special Focus Institutions	2	38	30	209	1	1	2.34

total = 1179

A handful of groups explain most nomination behaviors

Type-I nodes: feature pair tags, to cluster as B_I groups

Type-II nodes: nominations, to cluster as B_{II} groups



Code	Type of Institutions	N	<i>N</i> _I	<i>N</i> _{II}	E	<i>B</i> _I	<i>B</i> _{II}	Σ/E
15	Doctoral Universities: Highest Research Activity	117	946	1956	13692	5	2	2.45
16	Doctoral Universities: Higher Research Activity	112	833	1757	12299	8	2	2.67
17	Doctoral Universities: Moderate Research Activity	102	596	1815	12705	11	3	2.68
18	Master's Colleges & Universities: Larger Programs	251	958	4118	28825	16	3	2.73
19	Master's Colleges & Universities: Medium Programs	129	656	2082	14574	14	3	2.71
20	Master's Colleges & Universities: Small Programs	78	502	1169	8183	6	2	2.70
21	Baccalaureate Colleges: Arts & Sciences Focus	176	778	3105	21735	4	2	2.48
22	Baccalaureate Colleges: Diverse Fields	144	698	2129	14903	12	3	2.69
23	Baccalaureate/Associate's Colleges: Mixed Baccalaureate/Associate's	126	32	232	1624	4	2	2.45
24	Special Focus Four-Year: Faith-Related Institutions	1	9	2	14	1	1	1.31
26	Special Focus Four-Year: Other Health Professions Schools	5	53	42	293	1	1	2.55
27	Special Focus Four-Year: Engineering Schools	3	45	24	168	1	1	2.53
28	Special Focus Four-Year: Other Technology-Related Schools	3	53	38	266	1	1	2.37
29	Special Focus Four-Year: Business & Management Schools	6	47	122	854	1	1	2.27
30	Special Focus Four-Year: Arts, Music & Design Schools	18	138	196	1372	1	1	2.41
32	Special Focus Four-Year: Other Special Focus Institutions	2	38	30	209	1	1	2.34

total = 1179

A handful of groups explain most nomination behaviors (cont.)

Type	Top feature pairs	Group 1	Group 2	
R1	non-HBCU to non-HBCU, to higher admission rate, to other R1		10.4% 36.8%	
	78.9% intrastate, 93.5% interstate, non-HBCU to HBCU, to similar enrollment size, to R2 or to M:Large	2.5%	22.1%	
	Public to Public/Private, to lower grad rate	0%	13.2%	
	5.3% intrastate, to higher grad rate, to similar admission rate	3.9%	6.1%	
	15.8% intrastate, 6.5% interstate, Private to Public/Private	4.9%	0.1%	
R2	non-HBCU to non-HBCU, to higher admission rate, to R1, to M:Large		28.4% 12.7%	
	to lower enrollment size, to higher graduation rate, to similar admission rate, to other R2		19.7% 4.7%	
	69.6% intrastate, 90.7% interstate, HBCU to HBCU/non-HBCU, non-HBCU to HBCU, to M:Small, to Bacc. Colleges (diverse fields), Private to Public/Private for-profit		11.5% 1.3%	
	Public to Public		9.6% 0%	
	to higher admission rate, to R3		1.9% 2.1%	
R3	Private to Private		0% 3.7%	
	17.4% intrastate, 4% interstate, to M:Med, S:Engineer,		0.6% 1.8%	
	Public to Private			
	13% intrastate, 5.3% interstate, to B:A&S, to Special Focus Four-Year (Arts/Music/Design)		0% 1.9%	

A handful of groups explain most nomination behaviors (cont.)

Type	Top feature pairs	Group 1	Group 2
R1	non-HBCU to non-HBCU, to higher admission rate, to other R1		10.4% 36.8%
	78.9% intrastate, 93.5% interstate, non-HBCU to HBCU, to similar enrollment size, to R2 or to M:Large	2.5%	22.1%
	Public to Public/Private, to lower grad rate	0%	13.2%
	5.3% intrastate, to higher grad rate, to similar admission rate	3.9%	6.1%
	15.8% intrastate, 6.5% interstate, Private to Public/Private	4.9%	0.1%
R2	non-HBCU to non-HBCU, to higher admission rate, to R1, to M:Large		28.4% 12.7%
	to lower enrollment size, to higher graduation rate, to similar admission rate, to other R2		19.7% 4.7%
	69.6% intrastate, 90.7% interstate, HBCU to HBCU/non-HBCU, non-HBCU to HBCU, to M:Small, to Bacc. Colleges (diverse fields), Private to Public/Private for-profit		11.5% 1.3%
	Public to Public		9.6% 0%
	to higher admission rate, to R3		1.9% 2.1%
	Private to Private		0% 3.7%
	17.4% intrastate, 4% interstate, to M:Med, S:Engineer,		0.6% 1.8%
	Public to Private		
	13% intrastate, 5.3% interstate, to B:A&S, to Special Focus Four-Year (Arts/Music/Design)		0% 1.9%

Homophily. In R1 (47.2%) and R2 schools (24.4%), but R2 shows more aspiration to R1 (41.1%).

A handful of groups explain most nomination behaviors (cont.)

Type	Top feature pairs	Group 1	Group 2
R1	non-HBCU to non-HBCU, to higher admission rate, to other R1		10.4% 36.8%
	78.9% intrastate, 93.5% interstate, non-HBCU to HBCU, to similar enrollment size, to R2 or to M:Large	2.5%	22.1%
	Public to Public/Private, to lower grad rate	0%	13.2%
	5.3% intrastate, to higher grad rate, to similar admission rate	3.9%	6.1%
	15.8% intrastate, 6.5% interstate, Private to Public/Private	4.9%	0.1%
R2	non-HBCU to non-HBCU, to higher admission rate, to R1, to M:Large		28.4% 12.7%
	to lower enrollment size, to higher graduation rate, to similar admission rate, to other R2		19.7% 4.7%
	69.6% intrastate, 90.7% interstate, HBCU to HBCU/non-HBCU, non-HBCU to HBCU, to M:Small, to Bacc. Colleges (diverse fields), Private to Public/Private for-profit		11.5% 1.3%
	Public to Public	9.6%	0%
	to higher admission rate, to R3	1.9%	2.1%
	Private to Private	0%	3.7%
	17.4% intrastate, 4% interstate, to M:Med, S:Engineer,		0.6% 1.8%
	Public to Private		
	13% intrastate, 5.3% interstate, to B:A&S, to Special Focus Four-Year (Arts/Music/Design)	0%	1.9%

Homophily. In R1 (47.2%) and R2 schools (24.4%), but R2 shows more aspiration to R1 (41.1%).

Public schools. Tend to endorse others with a higher admission rate (R1: 13.2%; R2: 9.6%).

A handful of groups explain most nomination behaviors (cont.)

Type	Top feature pairs	Group 1	Group 2
R1	non-HBCU to non-HBCU, to higher admission rate, to other R1		10.4% 36.8%
	78.9% intrastate, 93.5% interstate, non-HBCU to HBCU, to similar enrollment size, to R2 or to M:Large	2.5%	22.1%
	Public to Public/Private, to lower grad rate	0%	13.2%
	5.3% intrastate, to higher grad rate, to similar admission rate	3.9%	6.1%
	15.8% intrastate, 6.5% interstate, Private to Public/Private	4.9%	0.1%
R2			
	non-HBCU to non-HBCU, to higher admission rate, to R1, to M:Large		28.4% 12.7%
	to lower enrollment size, to higher graduation rate, to similar admission rate,		19.7% 4.7%
	to other R2		
	69.6% intrastate, 90.7% interstate, HBCU to HBCU/non-HBCU, non-HBCU to HBCU, to M:Small, to Bacc. Colleges (diverse fields), Private to Public/Private for-profit		11.5% 1.3%
	Public to Public	9.6%	0%
	to higher admission rate, to R3	1.9%	2.1%
	Private to Private	0%	3.7%
	17.4% intrastate, 4% interstate, to M:Med, S:Engineer,		0.6% 1.8%
	Public to Private		
	13% intrastate, 5.3% interstate, to B:A&S, to Special Focus Four-Year (Arts/Music/Design)	0%	1.9%

Homophily. In R1 (47.2%) and R2 schools (24.4%), but R2 shows more aspiration to R1 (41.1%).

Public schools. Tend to endorse others with a higher admission rate (R1: 13.2%; R2: 9.6%).

Niche effect. R1 wants to increase grad rate than other intrastate R1s; R2 aspires the same, but be fitter (lower enrollment size).

Implications

Implications

All institutions. Name higher prestige institutions as their peers.

Implications


All institutions. Name higher prestige institutions as their peers.

Elite institutions. Particularly aspire prestige.

Implications

All institutions. Name higher prestige institutions as their peers.

Elite institutions. Particularly aspire prestige.




Implications

All institutions. Name higher prestige institutions as their peers.

Elite institutions. Particularly aspire prestige.

Others. Explainable by a handful of feature groups.



Outline

1. Context & motivation (chapter 1)
2. Aspiration of prestige in institutional peer selection (chapter 5)
3. Community detection in bipartite networks (chapter 2)
-  4. Regularized methods for efficient ranking (chapter 3)
5. A detour in higher-order structures (chapter 4)
6. Conclusions & future research (chapter 6)

Outline

Structure and inference in annotated networks

M. E. J. Newman  & Aaron Clauset 

Nature Communications 7, Article number: 11863 (2016)

Network Structure, Metadata, and the Prediction of Missing Nodes
and Annotations

Darko Hric, Tiago P. Peixoto, and Santo Fortunato
Phys. Rev. X 6, 031038 – Published 12 September 2016

1. Context & motivation (chapter 1)
2. Aspiration of prestige in institutional peer selection (chapter 5)
3. Community detection in bipartite networks (chapter 2)
4. Regularized methods for efficient ranking (chapter 3)
5. A detour in higher-order structures (chapter 4)
6. Conclusions & future research (chapter 6)



Outline

Structure and inference in annotated networks

M. E. J. Newman [✉](#) & Aaron Clauset [✉](#)

Nature Communications 7, Article number: 11863 (2016)

Network Structure, Metadata, and the Prediction of Missing Nodes and Annotations


Darko Hric, Tiago P. Peixoto, and Santo Fortunato
Phys. Rev. X 6, 031038 – Published 12 September 2016

1. Context & motivation (chapter 1)
2. Aspiration of prestige in institutional peer selection (chapter 5)
3. Community detection in bipartite networks (chapter 3)
4. Regularized methods for efficient ranking (chapter 2)
5. A detour in higher-order structures (chapter 4)
6. Conclusions & future research (chapter 6)




SpringRank

Each directed edge $u \rightarrow v$ implies
PhD from u becomes faculty at v



Computer science faculty hiring network; <http://tuvalu.santafe.edu/~aarong/facultyhiring/>. See also: *Sci. Adv.* 1(1), e1400005, 2015.

Each directed edge $u \rightarrow v$ implies institution u selects institution v




SpringRank: Let $A = \{A_{ij}\}$ be the adjacency matrix of a directed multigraph. The SpringRank Model finds the ranking s^* of the nodes by solving:

$$\underset{s \in \mathbb{R}^N}{\text{minimize}} \frac{1}{2} \sum_{ij} A_{ij} (s_i - s_j - 1)^2 .$$


SpringRank

Each directed edge $u \rightarrow v$ implies
PhD from u becomes faculty at v



Computer science faculty hiring network; <http://tuvalu.santafe.edu/~aaronc/facultyhiring/>. See also: *Sci. Adv.* 1(1), e1400005, 2015.

Each directed edge $u \rightarrow v$ implies
institution u selects institution v



When the input data is **erroneous**, **time-varying**, or with **node attributes**

SpringRank: Let $\mathbf{A} = \{A_{ij}\}$ be the adjacency matrix of a directed multigraph.
The SpringRank Model finds the ranking \mathbf{s}^* of the nodes by solving:

$$\underset{\mathbf{s} \in \mathbb{R}^N}{\text{minimize}} \frac{1}{2} \sum_{ij} A_{ij} (s_i - s_j - 1)^2 .$$


Motivation

Math PhD Exchange Dataset: Proxy for university i hiring a graduate from university j at a time near t . We view this as an **endorsement** by j that graduates of t are of high quality.



PhD, Computer Science
University of Chicago

$$w > 1$$





$$t = 2023$$

Assistant Professor
University of Colorado

Tzu-Chi, Maya, & Michael graduate (👉)



Motivation

Math PhD Exchange Dataset: Proxy for university i hiring a graduate from university j at a time near t . We view this as an **endorsement** by j that graduates of i are of high quality.



Motivation

Math PhD Exchange Dataset: Proxy for university i hiring a graduate from university j at a time near t . We view this as an **endorsement** by j that graduates of i are of high quality.



Idea: Optimization with Sparsity-Inducing Penalties

Sparsity through the ℓ_1 norm: a number of coefficients of w^* , depending on the strength of the regularization, will be exactly equal to zero.

Idea: Optimization with Sparsity-Inducing Penalties

Sparsity through the ℓ_1 norm: a number of coefficients of w^* , depending on the strength of the regularization, will be exactly equal to zero.

Sparsity through the ℓ_1/ℓ_q norm (group norm): sometimes coefficients of w^* are naturally partitioned in subsets, or groups, of variables. Through regularization, some groups of coefficients will be exactly equal to zero.


Idea: Optimization with Sparsity-Inducing Penalties

Sparsity through the ℓ_1 norm: a number of coefficients of w^* , depending on the strength of the regularization, will be exactly equal to zero.


Sparsity through the ℓ_1/ℓ_q norm (group norm): sometimes coefficients of w^* are naturally partitioned in subsets, or groups, of variables. Through regularization, some groups of coefficients will be exactly equal to zero.

Sparsity through overlapping groups: groups can even overlap, resulting in more exotic structures to be selected.

example group setup



example coefficients selected



Idea: Optimization with Sparsity-Inducing Penalties


Sparsity through the ℓ_1 norm: a number of coefficients of w^* , depending on the strength of the regularization, will be exactly equal to zero.

Sparsity through the ℓ_1/ℓ_q norm (group norm): sometimes coefficients of w^* are naturally partitioned in subsets, or groups, of variables. Through regularization, some groups of coefficients will be exactly equal to zero.


Sparsity through overlapping groups: groups can even overlap, resulting in more exotic structures to be selected.

Examples. Regression, graphical modeling, de-noising, dictionary learning, etc.
 (common theme: convex optimization!)

example group setup



example coefficients selected



Specific regularizations (1/3)

Regularize time dependency: apply ℓ_1 or ℓ_2 norm to the rank gradient in adjacent time window

$$\Omega_1(\mathbf{s}) := \sum_t \|\mathbf{s}_t - \mathbf{s}_{t-1}\|_1$$

$$\Omega_2(\mathbf{s}) := \sum_t \|\mathbf{s}_t - \mathbf{s}_{t-1}\|_2^2$$

Specific regularizations (1/3)

Regularize time dependency: apply $\ell 1$ or $\ell 2$ norm to the rank gradient in adjacent time window

$$\Omega_1(s) := \sum_t \|s_t - s_{t-1}\|_1$$

$$\Omega_2(s) := \sum_t \|s_t - s_{t-1}\|_2^2$$

$\ell 2$ encourages $s_t \approx s_{t-1}$


$\ell 1$ encourages $s_t = s_{t-1}$ (sparsity in ranking difference)

Result (1/3): Ranking over time

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

Benefits. Reduce the S/N-ratio to reveal the trends (through ℓ_2), and possibly also reveal “specific events” (through ℓ_1).


For smaller schools (lacking data), we can assign non-zero ranks.



Specific regularizations (2/3)

Robust to outliers: substitute the quadratic loss with the Huber loss

$$\text{huber}(s) = \begin{cases} (1/2)s^2 & |s| \leq 1 \\ |s| - (1/2) & |s| > 1 \end{cases}.$$



Regularize time dependency: apply ℓ_1 or ℓ_2 norm to the rank gradient in adjacent time window

$$\Omega_1(\mathbf{s}) := \sum_t \|\mathbf{s}_t - \mathbf{s}_{t-1}\|_1$$

$$\Omega_2(\mathbf{s}) := \sum_t \|\mathbf{s}_t - \mathbf{s}_{t-1}\|_2^2$$

Result (2/3): Robust ranking

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

Result (2/3): Robust ranking



$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

“Single-point mutation” style noise: A random node receives edges $|E|$ pointed from other nodes.

Result (2/3): Robust ranking

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$


“Single-point mutation” style noise: A random node receives edges $|E|$ pointed from other nodes.



Result (2/3): Robust ranking

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

“Single-point mutation” style noise: A random node receives edges $|E|$ pointed from other nodes.




Other forms of noise: Randomly added/removed edges

Result (2/3): Robust ranking

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

“Single-point mutation” style noise: A random node receives edges $|E|$ pointed from other nodes.



Other forms of noise: Randomly added/removed edges

Benefits: Huber loss is less sensitive to outliers in the data.

Solution method

Generic form: two regularization functions, one makes the objective strongly convex (easier to solve), the other encourages certain structure.

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

$$\underset{s \in \mathbb{R}^N}{\text{minimize}} \underbrace{\frac{1}{2} \sum_{ij} A_{ij}(s_i - s_j - 1)^2}_{\mathcal{L}_{\text{quad}}} + \alpha \sum_{i=1}^N s_i^2$$

$$\text{huber}(s) = \begin{cases} (1/2)s^2 & |s| \leq 1 \\ |s| - (1/2) & |s| > 1 \end{cases} .$$

$$\Omega_1(s) := \sum_t \|s_t - s_{t-1}\|_1$$

$$\Omega_2(s) := \sum_t \|s_t - s_{t-1}\|_2^2$$

Solution method

Generic form: two regularization functions, one makes the objective strongly convex (easier to solve), the other encourages certain structure.

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

$$\underset{s \in \mathbb{R}^N}{\text{minimize}} \underbrace{\frac{1}{2} \sum_{ij} A_{ij} (s_i - s_j - 1)^2}_{\mathcal{L}_{\text{quad}}} + \alpha \sum_{i=1}^N s_i^2$$

$$\text{huber}(s) = \begin{cases} (1/2)s^2 & |s| \leq 1 \\ |s| - (1/2) & |s| > 1 \end{cases}$$

$$\Omega_1(s) := \sum_t \|s_t - s_{t-1}\|_1$$

$$\Omega_2(s) := \sum_t \|s_t - s_{t-1}\|_2^2$$

Solution method

Generic form: two regularization functions, one makes the objective strongly convex (easier to solve), the other encourages certain structure.

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

$$\underset{s \in \mathbb{R}^N}{\text{minimize}} \underbrace{\frac{1}{2} \sum_{ij} A_{ij} (s_i - s_j - 1)^2}_{\mathcal{L}_{\text{quad}}} + \alpha \sum_{i=1}^N s_i^2$$

$$\text{huber}(s) = \begin{cases} (1/2)s^2 & |s| \leq 1 \\ |s| - (1/2) & |s| > 1 \end{cases}$$

$$\Omega_1(s) := \sum_t \|s_t - s_{t-1}\|_1$$

$$\Omega_2(s) := \sum_t \|s_t - s_{t-1}\|_2^2$$

Solution method

Generic form: two regularization functions, one makes the objective strongly convex (easier to solve), the other encourages certain structure.

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

$$\underset{s \in \mathbb{R}^N}{\text{minimize}} \underbrace{\frac{1}{2} \sum_{ij} A_{ij} (s_i - s_j - 1)^2}_{\mathcal{L}_{\text{quad}}} + \alpha \sum_{i=1}^N s_i^2$$

Solvable by existing tools. e.g., CVXPY, which uses generic solvers.

$$\text{huber}(s) = \begin{cases} (1/2)s^2 & |s| \leq 1 \\ |s| - (1/2) & |s| > 1 \end{cases}.$$

$$\Omega_1(s) := \sum_t \|s_t - s_{t-1}\|_1$$

$$\Omega_2(s) := \sum_t \|s_t - s_{t-1}\|_2^2$$

Solution method

Generic form: two regularization functions, one makes the objective strongly convex (easier to solve), the other encourages certain structure.

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

$$\underset{s \in \mathbb{R}^N}{\text{minimize}} \underbrace{\frac{1}{2} \sum_{ij} A_{ij} (s_i - s_j - 1)^2}_{\mathcal{L}_{\text{quad}}} + \alpha \sum_{i=1}^N s_i^2$$

Solvable by existing tools. e.g., CVXPY, which uses generic solvers.

Issue. Graph is sparse. Need to exploit sparsity to avoid memory and computational issues for large problems.

$$\text{huber}(s) = \begin{cases} (1/2)s^2 & |s| \leq 1 \\ |s| - (1/2) & |s| > 1 \end{cases}$$

$$\Omega_1(s) := \sum_t \|s_t - s_{t-1}\|_1$$

$$\Omega_2(s) := \sum_t \|s_t - s_{t-1}\|_2^2$$

Solution method

Generic form: two regularization functions, one makes the objective strongly convex (easier to solve), the other encourages certain structure.

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

Solvable by existing tools. e.g., CVXPY, which uses generic solvers.

Issue. Graph is sparse. Need to exploit sparsity to avoid memory and computational issues for large problems.

Krylov methods. if we can cast the objective into a sum-of-squares form, we can use a sparse iterative solver (e.g., bi-conjugate gradient stabilized method*)

$$\underset{s \in \mathbb{R}^N}{\text{minimize}} \underbrace{\frac{1}{2} \sum_{ij} A_{ij} (s_i - s_j - 1)^2}_{\mathcal{L}_{\text{quad}}} + \alpha \sum_{i=1}^N s_i^2$$

$$\text{huber}(s) = \begin{cases} (1/2)s^2 & |s| \leq 1 \\ |s| - (1/2) & |s| > 1 \end{cases} .$$

$$\Omega_1(s) := \sum_t \|s_t - s_{t-1}\|_1$$

$$\Omega_2(s) := \sum_t \|s_t - s_{t-1}\|_2^2$$

Solution method

Generic form: two regularization functions, one makes the objective strongly convex (easier to solve), the other encourages certain structure.

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

Solvable by existing tools. e.g., CVXPY, which uses generic solvers.

Issue. Graph is sparse. Need to exploit sparsity to avoid memory and computational issues for large problems.

Krylov methods. if we can cast the objective into a sum-of-squares form, we can use a sparse iterative solver (e.g., bi-conjugate gradient stabilized method*)

First-order methods. we may turn to generalizations of gradient decent

$$\underset{s \in \mathbb{R}^N}{\text{minimize}} \underbrace{\frac{1}{2} \sum_{ij} A_{ij} (s_i - s_j - 1)^2}_{\mathcal{L}_{\text{quad}}} + \alpha \sum_{i=1}^N s_i^2$$

$$\text{huber}(s) = \begin{cases} (1/2)s^2 & |s| \leq 1 \\ |s| - (1/2) & |s| > 1 \end{cases} .$$

$$\Omega_1(s) := \sum_t \|s_t - s_{t-1}\|_1$$

$$\Omega_2(s) := \sum_t \|s_t - s_{t-1}\|_2^2$$

Dual-based proximal gradient methods


$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

Dual-based proximal gradient methods

Composite model: requires that f has a nice gradient and g has a easy-to-compute proximal operator

$$\underset{\mathbf{x} \in \mathbb{R}^n}{\text{minimize}} \{F(\mathbf{x}) \equiv f(\mathbf{x}) + g(\mathbf{x})\}$$

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$




Dual-based proximal gradient methods

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$

Composite model: requires that f has a nice gradient and g has an easy-to-compute proximal operator

$$\underset{x \in \mathbb{R}^n}{\text{minimize}} \{F(x) \equiv f(x) + g(x)\}$$



Dual-based proximal gradient methods

Composite model: requires that f has a nice gradient and g has an easy-to-compute proximal operator

$$\underset{\mathbf{x} \in \mathbb{R}^n}{\text{minimize}} \{F(\mathbf{x}) \equiv f(\mathbf{x}) + g(\mathbf{x})\}$$


Dual problem: easier to solve, as the linear operator L goes to the part that relies on the gradient.

(Primal)

$$\underset{\mathbf{s} \in \mathbb{R}^N}{\text{minimize}} f(\mathbf{s}) + g(L\mathbf{s})$$


(Dual)

$$\underset{\mathbf{v} \in \mathcal{K}}{\text{minimize}} f^*(-L^*\mathbf{v}) + g^*(\mathbf{v})$$



$$f^*(s) = \max_x \langle s, x \rangle - f(x)$$

$$\underset{\mathbf{s}}{\text{minimize}} \mathcal{L}(\mathbf{s}) + \alpha \|\mathbf{s}\|_2^2 + \lambda \Omega(L\mathbf{s})$$



The Proximal Gradient Method

Initialization: pick $\mathbf{x}^0 \in \text{int}(\text{dom}(f))$.

General step: for any $k = 0, 1, 2, \dots$ execute the following steps:


(a) pick $L_k > 0$;

(b) set $\mathbf{x}^{k+1} = \text{prox}_{\frac{1}{L_k}g} \left(\mathbf{x}^k - \frac{1}{L_k} \nabla f(\mathbf{x}^k) \right)$.

Specific regularizations

Robust to outliers: substitute the quadratic loss with the Huber loss

$$\text{huber}(s) = \begin{cases} (1/2)s^2 & |s| \leq 1 \\ |s| - (1/2) & |s| > 1 \end{cases}.$$



Regularize time dependency: apply ℓ_1 or ℓ_2 norm to the rank gradient in adjacent time window

$$\Omega_1(\mathbf{s}) := \sum_t \|\mathbf{s}_t - \mathbf{s}_{t-1}\|_1$$

$$\Omega_2(\mathbf{s}) := \sum_t \|\mathbf{s}_t - \mathbf{s}_{t-1}\|_2^2$$

Same node category, same mean ranking: encourage “no bias across categories” unless necessary


$$\Omega_{\text{group}}(\mathbf{s}) := \sum_{z(i) \neq z(j)} w_{ij} |\langle s_i \rangle - \langle s_j \rangle|$$

Result (3/3): Ranking to learn group-dependent phenomena

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$


Result (3/3): Ranking to learn group-dependent phenomena

$$\underset{s}{\text{minimize}} \mathcal{L}(s) + \alpha \|s\|_2^2 + \lambda \Omega(Ls)$$



Benefits: By encouraging nodes of different groups to have the same, mean ranking, we select the groups that are special, or biased.

Result (3/3): Ranking to learn group-dependent phenomena



Benefits: By encouraging nodes of different groups to have the same, mean ranking, we select the groups that are special, or biased.

Caveats: *Is this a better model?* Not always. We use a cross-validated model to predict out-of-sample edge directions (worse) and compare their likelihoods (better) with the vanilla SpringRank. But “better” is subjective. We expect the model to outperform for **smaller categories** though.

Implications

Implications

$$\underset{\mathbf{s} \in \mathbb{R}^N}{\text{minimize}} \underbrace{\frac{1}{2} \sum_{ij} A_{ij}(s_i - s_j - 1)^2}_{\mathcal{L}_{\text{quad}}} + \alpha \sum_{i=1}^N s_i^2$$

Mix-and-match losses with regularizations allow new modeling capabilities.

$$\text{huber}(s) = \begin{cases} (1/2)s^2 & |s| \leq 1 \\ |s| - (1/2) & |s| > 1 \end{cases}$$

$$\Omega_1(\mathbf{s}) := \sum_t \|\mathbf{s}_t - \mathbf{s}_{t-1}\|_1$$

$$\Omega_2(\mathbf{s}) := \sum_t \|\mathbf{s}_t - \mathbf{s}_{t-1}\|_2^2$$

$$\Omega_{\text{group}}(\mathbf{s}) := \sum_{z(i) \neq z(j)} w_{ij} |(\langle s_i \rangle - \langle s_j \rangle)|$$


Implications

Mix-and-match losses with regularizations allow new modeling capabilities.

SpringRank can now select group-dependent (multi-modal) ranking distributions. Other fancier choice models do the same (e.g., contextual repeated selection model), but not conventional ones (e.g., Bradley-Terry-Luce model & vanilla SpringRank).

$$\underset{s \in \mathbb{R}^N}{\text{minimize}} \underbrace{\frac{1}{2} \sum_{ij} A_{ij}(s_i - s_j - 1)^2}_{\mathcal{L}_{\text{quad}}} + \alpha \sum_{i=1}^N s_i^2$$

$$\begin{aligned} \text{huber}(s) &= \begin{cases} (1/2)s^2 & |s| \leq 1 \\ |s| - (1/2) & |s| > 1 \end{cases} \\ \Omega_1(s) &:= \sum_t \|s_t - s_{t-1}\|_1 \\ \Omega_2(s) &:= \sum_t \|s_t - s_{t-1}\|_2^2 \\ \Omega_{\text{group}}(s) &:= \sum_{z(i) \neq z(j)} w_{ij} |(\langle s_i \rangle - \langle s_j \rangle)| \end{aligned}$$



Implications


Mix-and-match losses with regularizations allow new modeling capabilities.

SpringRank can now select group-dependent (multi-modal) ranking distributions. Other fancier choice models do the same (e.g., contextual repeated selection model), but not conventional ones (e.g., Bradley-Terry-Luce model & vanilla SpringRank).

Limitations. No natural way to apply to numeric groups (think: how does admission rate relate to the hierarchy?); Cross-validating >2 hyperparameters is slow.


$$\underset{s \in \mathbb{R}^N}{\text{minimize}} \underbrace{\frac{1}{2} \sum_{ij} A_{ij}(s_i - s_j - 1)^2}_{\mathcal{L}_{\text{quad}}} + \alpha \sum_{i=1}^N s_i^2$$

$$\begin{aligned} \text{huber}(s) &= \begin{cases} (1/2)s^2 & |s| \leq 1 \\ |s| - (1/2) & |s| > 1 \end{cases} \\ \Omega_1(s) &:= \sum_t \|s_t - s_{t-1}\|_1 \\ \Omega_2(s) &:= \sum_t \|s_t - s_{t-1}\|_2^2 \\ \Omega_{\text{group}}(s) &:= \sum_{z(i) \neq z(j)} w_{ij} |(\langle s_i \rangle - \langle s_j \rangle)| \end{aligned}$$




Outline

1. Context & motivation (chapter 1)
2. Aspiration of prestige in institutional peer selection (chapter 5)
3. Community detection in bipartite networks (chapter 2)
4. Regularized methods for efficient ranking (chapter 3)
-  5. A detour in higher-order structures (chapter 4)
6. Conclusions & future research (chapter 6)




Edges. These 2 authors have written a paper together.

Graph




Edges. These 2 authors have written a paper together.

Graph




“Higher-order” graph

Edges. These 3 authors have worked together (and wrote >1 papers).



Edges. These 2 authors have written a paper together.



“Higher-order” graph

Edges. These 3 authors have worked together (and wrote >1 papers).



PHYSICAL REVIEW E 104, L042303 (2021)

Letter


Construction of simplicial complexes with prescribed degree-size sequences

Tzu-Chi Yen *

Department of Computer Science, University of Colorado, Boulder, Colorado 80309, USA




(Received 31 May 2021; accepted 30 September 2021; published 28 October 2021)



Edges. These 2 authors have written a paper together.

Graph



“Higher-order” graph

Edges. These 3 authors have worked together (and wrote >1 papers).

NP-completeness. Do not give up if a problem is NP-hard, sometimes a simple algorithm exists!



PHYSICAL REVIEW E 104, L042303 (2021)

Letter


Construction of simplicial complexes with prescribed degree-size sequences

Tzu-Chi Yen ^{ID}*


Department of Computer Science, University of Colorado, Boulder, Colorado 80309, USA



(Received 31 May 2021; accepted 30 September 2021; published 28 October 2021)

**Graph**

Edges. These 2 authors have written a paper together.

**“Higher-order” graph**

Edges. These 3 authors have worked together (and wrote >1 papers).

NP-completeness. Do not give up if a problem is NP-hard, sometimes a simple algorithm exists!

Null models. Configuration model for **graphs** vs. for **higher-order graphs**



PHYSICAL REVIEW E 104, L042303 (2021)

Letter


Construction of simplicial complexes with prescribed degree-size sequences

Tzu-Chi Yen *


Department of Computer Science, University of Colorado, Boulder, Colorado 80309, USA



(Received 31 May 2021; accepted 30 September 2021; published 28 October 2021)

**Graph**

Edges. These 2 authors have written a paper together.

**“Higher-order” graph**

Edges. These 3 authors have worked together (and wrote >1 papers).

NP-completeness. Do not give up if a problem is NP-hard, sometimes a simple algorithm exists!

Null models. Configuration model for **graphs** vs. for **higher-order graphs**

Applied topology. How does #holes in a higher-order graph scale?



PHYSICAL REVIEW E 104, L042303 (2021)

Letter


Construction of simplicial complexes with prescribed degree-size sequences

Tzu-Chi Yen *


Department of Computer Science, University of Colorado, Boulder, Colorado 80309, USA



(Received 31 May 2021; accepted 30 September 2021; published 28 October 2021)



Edges. These 2 authors have written a paper together.



“Higher-order” graph

Edges. These 3 authors have worked together (and wrote >1 papers).

NP-completeness. Do not give up if a problem is NP-hard, sometimes a simple algorithm exists!

Null models. Configuration model for **graphs** vs. for **higher-order graphs**

Applied topology. How does #holes in a higher-order graph scale?



PHYSICAL REVIEW E 104, L042303 (2021)

Letter



Construction of simplicial complexes with prescribed degree-size sequences

Tzu-Chi Yen *


Department of Computer Science, University of Colorado, Boulder, Colorado 80309, USA

(Received 31 May 2021; accepted 30 September 2021; published 28 October 2021)








What makes a school aspirational?




What makes a school aspirational?






What makes a school aspirational?


What structure can we infer from a network?






What makes a school aspirational?

What structure can we infer from a network?








What makes a school aspirational?

What structure can we infer from a network?

How can metadata help?







Future research

Future research

Mix-and-match. Network science + ☐☐☐☐☐.

Future research

Mix-and-match. Network science + ☐☐☐☐☐.

Structure is mundane, psychology is alive.

- Directed edge. Action verbs.
- Metadata. Show intent.

Future research

Mix-and-match. Network science + ☐☐☐☐☐.

Structure is mundane, psychology is alive.

- Directed edge. Action verbs.
- Metadata. Show intent.

Reproducible results. Statistically grounded methodologies.

Statistical inference links data and theory in network science

[Leto Peel](#)✉, [Tiago P. Peixoto](#)✉ & [Manlio De Domenico](#)✉

Nature Communications **13**, Article number: 6794 (2022) | [Cite this article](#)

Future research

Mix-and-match. Network science + ☐☐☐☐☐.

Structure is mundane, psychology is alive.

- Directed edge. Action verbs.
- Metadata. Show intent.

Reproducible results. Statistically grounded methodologies.

Exploiting sparsity. Combinatorial problems often admits a natural (convex) relaxation.

Statistical inference links data and theory in network science

[Leto Peel](#)✉, [Tiago P. Peixoto](#)✉ & [Manlio De Domenico](#)✉

[Nature Communications](#) **13**, Article number: 6794 (2022) | [Cite this article](#)

A unified perspective on convex structured sparsity:
Hierarchical, symmetric, submodular norms and beyond

Guillaume Obozinski
Université Paris-Est
Laboratoire d'Informatique Gaspard Monge
Groupe Imagine, Ecole des Ponts - ParisTech
Marne-la-Vallée, France
guillaume.obozinski@enpc.fr

Francis Bach
INRIA - Sierra project-team
Département d'Informatique
de l'Ecole Normale Supérieure
Paris, France
francis.bach@ens.fr

December 8, 2016



Thanks!

