

Structure of the 16-digit order number for standard motors 1LE0.

1.	2.	3.	Motor type
1	L	E	Standard low voltage motors

4.	Motor series
0	IEC motor line
8	IEC line second generation

5.	Housing material
0	Cast iron housing - Basic Line
3	Aluminium

10.	Number of poles
A	2-pole
B	4-pole
C	6-pole
D	8-pole

11.	Construction length
	(0-8) core length encoded, usually more than one core length exists for one frame size, please see the table for examples

Digit	1.	2.	3.	4.	5.	6.	7.	-	8.	9.	10.	11.	12.	-	13.	14.	15.	16.	Option
Order number	1	L	E	0	3	0	3	-	1	C	A	1	2	-	2	A	B	4	- Z

6.	Versions
0	Standard IEC motors
2	Simotics FL - old line
4	Simotics FL - new line

7.	Efficiency class
3	Motors with IE3 Premium Efficiency

8.	9.	Frame size
0	D	80
0	E	90
1	A	100
1	B	112
1	C	132
1	D	160
1	E	180
2	A	200
2	B	225
2	C	250
2	D	280
3	A	315
3	B	355

12.	13.	Voltage code
0	4	400 VΔ 50Hz, 460 VΔ 60Hz
2	1	220 VΔ / 380 VY 50Hz, 440 VY 60Hz
2	2	230 VΔ / 400 VY 50Hz, 460 VY 60Hz
2	3	240 VΔ / 415 VY 50Hz, 480 VY 60Hz
3	3	380 VΔ / 660 VY 50Hz, 440 VΔ 60Hz
3	4	400 VΔ / 690 VY 50Hz, 460 VΔ 60Hz
3	5	415 VΔ 50Hz, 480 VΔ 60Hz
9	0	Other (typically 60 Hz, 87 Hz or non-standard), must be specified by option code Mxx

16.	Terminal box position
4	Terminal box top
5	Terminal box right-hand side
6	Terminal box left-hand side

14.	Type of construction
A	IM B3 / IM1001
C	IM V5 / IM1011
D	IM V6 / IM1031
F	IM B5 / IM3001
G	IM V1 / IM3011
H	IM V3 / IM3031
J	IM B35 / IM2001
K	IM B14 / IM3601
L	IM V19 / IM3631
M	IM V18 / IM3611
N	IM B34 / IM2101
T	IM B6 / IM1051
U	IM B7 / IM1061
V	IM B8 / IM1071
W	IM V15 / IM2011
Y	IM V35 / IM 2031

Table of digits 8-11, assigned to power ratings of motors in IE3 efficiency class				
	2-pole	4-pole	6-pole	8-pole
0.55 kW	0DB2	0DC3		
0.63 kW	0DB2	0DC3		
0.75 kW	0DA2	0DB3	0EC0	
0.86 kW	0DA2	0DB3	0EC0	
1.1 kW	0DA3	0EB0	0EC4	
1.3 kW	0DA3	0EB0	0EC4	
1.5 kW	0EA0	0EB4	1AC4	
1.75 kW	0EA0	0EB4	1AC4	
2.2 kW	0EA4	1AB4	1BC2	1CD0
2.55 kW	0EA4	1AB4	1BC2	1CD0
3 kW	1AA4	1AB5	1CC0	1CD2
3.45 kW	1AA4	1AB5	1CC0	1CD2
4 kW	1BA2	1BB2	1CC2	1DD2
4.6 kW	1BA2	1BB2	1CC2	1DD2
5.5 kW	1CA0	1CB0	1CC3	1DD3
6.3 kW	1CA0	1CB0	1CC3	1DD3
7.5 kW	1CA1	1CB2	1DC2	1DD4
8.6 kW	1CA1	1CB2	1DC2	1DD4
11 kW	1DA2	1DB2	1DC4	1ED4
12.6 kW	1DA2	1DB2	1DC4	1ED4
15 kW	1DA3	1DB4	1EC4	2AD5
17.3 kW	1DA3	1DB4	1EC4	2AD5
18.5 kW	1DA4	1EB2	2AC4	2BD0
21.3 kW	1DA4	1EB2	2AC4	2BD0
22 kW	1EA2	1EB4	2AC5	2BD2
24.5 kW	1EA2	1EB4	2AC5	2BD2
30 kW	2AA4	2AB4	2BC2	2CD2
33.5 kW	2AA4	2AB4	2BC2	2CD2
37 kW	2AA5	2BB0	2CC2	2DD0
41.5 kW	2AA5	2BB0	2CC2	2DD0
45 kW	2BA2	2BB2	2DC0	2DD2
51 kW	2BA2	2BB2	2DC0	2DD2
55 kW	2CA2	2CB2	2DC2	3AD0
62 kW	2CA2	2CB2	2DC2	3AD0
75 kW	2DA0	2DB0	3AC0	3AD2
84 kW	2DA0	2DB0	3AC0	3AD2
90 kW	2DA2	2DB2	3AC2	3AD5
101 kW	2DA2	2DB2	3AC2	3AD5
110 kW	3AA0	3AB0	3AC5	3AD6
123 kW	3AA0	3AB0	3AC5	3AD6
125 kW				3AD6
132 kW	3AA2	3AB2	3AC6	3BD2
				3AD6
148 kW	3AA2	3AB2	3AC6	3BD2
155 kW				3AD7
160 kW	3AA5	3AB5	3BC2	3BD3
				3AC6
180 kW	3AA5	3AB5	3BC2	3BD3
				3AC1
185 kW	3AA6	3AB6	3BC3	3BD5
				3AC1
200 kW	3AA7	3AB7	3BC4	3BD6
				3AC7
207 kW	3AA6	3AB6	3BC3	3BD5
				3AC3
220 kW	3BA2	3BB2	3BC5	3BD7
	3AA3	3AB3	3AC3	
224 kW	3AA7	3AB7	3BC4	3BD6
245 kW				3AC8
246 kW	3BA2	3BB2	3BC5	
250 kW	3BA3	3BB3	3BC6	3BD1
	3AA6	3AB6	3AC8	
280 kW	3BA5	3BB5	3BC6	3BD8
	3BA3	3BB3	3BC8	
	3AA8	3AB8		
314 kW	3BA5	3BB5		
315 kW	3BA6	3BB6	3BC2	3BD2
	3AA7	3AB7		
340 kW				3BC3
353 kW	3BA6	3BB6		
355 kW	3BA3	3BB3	3BC3	
380 kW				3BC4
400 kW	3BA4	3BB4	3BC4	
450 kW	3BA7	3BB7		
485 kW	3BA5	3BB5		
500 kW	3BA5	3BB5		
Valid in general for the following motors, when they exist in the relevant frame size, pole number and efficiency class: 1LE000, 1LE002, 1LE004 1LE032, 1LE800, 1LE803 Individual exceptions also occur. For details please see the catalog.				

Published by
Siemens AG
Digital Industries
Motion Control
P.O. Box 31 80
91050 Erlangen, Germany

Article No, DIMC-Y10067-00-7600
Dispo 21400
© Siemens 2022

Special Series
DI MC LVM EU PPM 3

www.siemens.com/simotics
www.siemens.com/mymotor

This flyer provides general information about the motor order number structure. However, it does not cover all possible combinations and it does not define which digits and the combinations that are applicable for each product. To select a specific product, please refer to the catalog or the configuration tools (LV Easy, Drive Technology Configurator). The best way to understand the MLFB structure and the motor parameters is to have access to a real motor. You can then scan the QR code printed on the motor rating plate using the SIDRIVE IQ Twin app on your smartphone or tablet.

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they expressly agreed upon in the concluded contact.

All product designations may be trademarks or other rights of Siemens AG, its affiliated companies or other companies whose use by third parties for their own purposes could violate the rights of the respective owner.

Structure of the 16-digit order number for hazardous areas motors 1MB0.

1.	2.	3.	Motor type	4.	Motor series	5.	Housing material	more than one core length exists for one frame size, please see the table for examples							winding - 3 wire (18 terminals)					
1	M	B	Motors for hazardous areas	0	IEC motor line	0	Cast iron housing - Basic Line								Z	Other (NTC, bimetal etc.), must be specified by option code Qxx				

Digit	1.	2.	3.	4.	5.	6.	7.	-	8.	9.	10.	11.	12.	-	13.	14.	15.	16.	Option
Order number	1	M	B	0	0	6	3	-	1	C	A	1	2	-	2	A	B	4	- Z

6.	Versions
6	Explosion proof line
7.	Efficiency class
3	Motors with IE3 Premium Efficiency

8.	9.	Frame size
0	D	80
0	E	90
1	A	100
1	B	112
1	C	132
1	D	160
1	E	180
2	A	200
2	B	225
2	C	250
2	D	280
3	A	315
3	B	355

10.	Number of poles
A	2-pole
B	4-pole
C	6-pole
D	8-pole

16.	Terminal box position
4	Terminal box top

14.	Type of construction
A	IM B3 / IM1001
C	IM V5 / IM1011
D	IM V6 / IM1031
F	IM B5 / IM3001
G	IM V1 / IM3011
H	IM V3 / IM3031
J	IM B35 / IM2001
K	IM B14 / IM3601
L	IM V19 / IM3631
M	IM V18 / IM3611
N	IM B34 / IM2101
T	IM B6 / IM1051
U	IM B7 / IM1061
V	IM B8 / IM1071
W	IM V15 / IM2011

12.	13.	Voltage code
0	1	230 VΔ 50Hz
2	1	220 VΔ / 380 VY 50Hz, 440 VY 60Hz
2	2	230 VΔ / 400 VY 50Hz, 460 VY 60Hz
2	3	240 VΔ / 415 VY 50Hz, 480 VY 60Hz
3	3	380 VΔ / 660 VY 50Hz, 440 VΔ 60Hz
3	4	400 VΔ / 690 VY 50Hz, 460 VΔ 60Hz
3	5	415 VΔ 50Hz, 480 VΔ 60Hz
9	0	Other (typically 60 Hz, 87 Hz or non-standard), must be specified by option code Mxx

15.	Motor protection
A	without (Standard)
B	1 or 3 PTC thermistor - for tripping (2 terminals)
C	2 or 6 PTC thermistors - for alarm and tripping (4 terminals)
H	3 resistance thermometers PT100 (6 terminals)
J	6 resistance thermometers PT100 (12 terminals)
K	1 Pt1000 resistance thermometer(2 terminals)
L	2 Pt1000 resistance thermometers(4 terminals)
Q	3 resistance thermometers PT100 in stator winding - 3 wire (9 terminals)
R	6 resistance thermometers PT100 in stator winding - 3 wire (18 terminals)
Z	Other (NTC, bimetal etc.), must be specified by option code Qxx

Table of digits 8-11, assigned to power ratings of motors in IE3 efficiency class

	2-pole	4-pole	6-pole	8-pole
0,55 kW		0DB2	0DC3	
0,75 kW	0DA2	0DB3	0EC0	
1,1 kW	0DA3	0EB0	0EC4	
1,5 kW	0EA0	0EB4	1AC4	
2,2 kW	0EA4	1AB4	1BC2	1CD0
3 kW	1AA4	1AB5	1CC0	1CD2
4 kW	1BA2	1BB2	1CC2	1DD2
5,5 kW	1CA0	1CB0	1CC3	1DD3
7,5 kW	1CA1	1CB2	1DC2	1DD4
11 kW	1DA2	1DB2	1DC4	1ED4
15 kW	1DA3	1DB4	1EC4	2AD5
18,5 kW	1DA4	1EB2	2AC4	2BD0
22 kW	1EA2	1EB4	2AC5	2BD2
30 kW	2AA4	2AB4	2BC2	2CD2
37 kW	2AA5	2BB0	2CC2	2DD0
45 kW	2BA2	2BB2	2DC0	2DD2
55 kW	2CA2	2CB2	2DC2	3AD0
75 kW	2DA0	2DB0	3AC0	3AD2
90 kW	2DA2	2DB2	3AC2	3AD5
110 kW	3AA0	3AB0	3AC5	3AD6
132 kW	3AA2	3AB2	3AC6	3BD2
160 kW	3AA5	3AB5	3BC2	3BD3
185 kW	3AA6	3AB6	3BC3	3BD5
200 kW	3AA7	3AB7	3BC4	3BD6
220 kW	3BA2	3BB2	3BC5	
250 kW	3BA3	3BB3	3BC6	
280 kW	3BA5	3BB5		
315 kW	3BA6	3BB6		

Valid in general for the following motors, when they exist in the relevant frame size, polenumber and efficiency class:
1MB0063

Individual exceptions also occur. For details please see the catalog.

Published by
Siemens AG
Digital Industries
Motion Control
P.O. Box 31 80
91050 Erlangen, Germany

Article No. DIMC-Y10067-00-7600
Dispo 21400
© Siemens 2022

Special Series
DI MC LVM EU PPM 3

www.siemens.com/simotics
www.siemens.com/mymotor

This flyer provides general information about the motor order number structure. However, it does not cover all possible combinations and it does not define which digits and the combinations that are applicable for each product. To select a specific product, please refer to the catalog or the configuration tools (LV Easy, Drive Technology Configurator). The best way to understand the MLFB structure and the motor parameters is to have access to a real motor. You can then scan the QR code printed on the motor rating plate using the SIDRIVE IQ Twin app on your smartphone or tablet.

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they expressly agreed upon in the concluded contact.

All product designations may be trademarks or other rights of Siemens AG, its affiliated companies or other companies whose use by third parties for their own purposes could violate the rights of the respective owner.

Structure of the 16-digit order number for standard motors 1LE8 in China.

1.	2.	3.	Motor type
1	L	E	Standard low voltage motors

4.	5.	Housing material
8	0	IEC motor series for China, Cast iron housing

8.	9.	Frame size
3	A	315
3	B	355

11.	Construction length
	(0-8) core length encoded, usually more than one core length exists for one frame size, please see the table for examples

14.	Type of construction
A	IM B3 / IM1001
C	IM V5 / IM1011
D	IM V6 / IM1031
G	IM V1 / IM3011
J	IM B35 / IM2001
T	IM B6 / IM1051
U	IM B7 / IM1061
V	IM B8 / IM1071
W	IM V15 / IM2011
Y	IM V35 / IM 2031

16.	Terminal box position
4	Terminal box top
5	Terminal box right-hand side
6	Terminal box left-hand side

Digit	1.	2.	3.	4.	5.	6.	7.	-	8.	9.	10.	11.	12.	-	13.	14.	15.	16.	Option
Order number	1	L	E	8	0	0	3	-	3	A	A	2	0	-	4	A	B	4	- Z

6.	Versions
0	IEC line second generation
3	IEC line second generation

7.	Efficiency class
3	Motors with IE3 Premium Efficiency

10.	Number of poles
A	2-pole
B	4-pole
C	6-pole
D	8-pole

12.	13.	Voltage code
0	4	400 VΔ 50Hz, 460 VΔ 60Hz
0	6	690 VY 50 Hz
3	3	380 VΔ / 660 VY 50Hz, 440 VΔ 60Hz
3	4	400 VΔ / 690 VY 50Hz, 460 VΔ 60Hz
3	5	415 VΔ 50Hz, 480 VΔ 60Hz
4	0	500 VΔ 50Hz, 575 VΔ 60Hz
9	0	Other (typically 60 Hz, 87 Hz or non-standard), must be specified by option code Mxx

15.	Motor protection
A	without (Standard)
B	1 or 3 PTC thermistor - for tripping (2 terminals)
C	2 or 6 PTC thermistors - for alarm and tripping (4 terminals)
H	3 resistance thermometers PT100 (6 terminals)
J	6 resistance thermometers PT100 (12 terminals)
K	1 Pt1000 resistance thermometer(2 terminals)
L	2 Pt1000 resistance thermometers(4 terminals)
Q	3 resistance thermometers PT100 in stator winding - 3 wire (9 terminals)
R	6 resistance thermometers PT100 in stator winding - 3 wire (18 terminals)

Table of digits 8-11, assigned to power ratings of motors in IE3 efficiency class

	2-pole	4-pole	6-pole	8-pole
125 kW				3AD6
132 kW				3AD6
155 kW			3AC6	3AD7
160 kW			3AC6	3AD7
180 kW			3AC1	
185 kW			3AC1	3AD1
190 kW			3AC7	
200 kW			3AC7	3AD8
215 kW			3AC3	
220 kW	3AA3	3AB3	3AC3	3BD7
245 kW			3AC8	
250 kW	3AA6	3AB6	3AC8	3BD1
280 kW	3AA8	3AB8	3BC8	3BD8
315 kW	3AA7	3AB7	3BC2	3BD2
340 kW			3BC3	
355 kW	3BA3	3BB3	3BC3	
380 kW			3BC4	
400 kW	3BA4	3BB4	3BC4	
450 kW	3BA7	3BB7		
480 kW		3BB5		
485 kW	3BA5			
500 kW	3BA5	3BB5		

Valid in general for the following motors, when they exist in the relevant frame size, polenumber and efficiency class: 1LE8003, 1LE8033

Individual exceptions also occur. For details please see the catalog.

Published by
Siemens AG
Digital Industries
Motion Control
P.O. Box 31 80
91050 Erlangen, Germany

Article No, DIMC-Y10067-00-7600
Dispo 21400
© Siemens 2022

Special Series
DI MC LVM EU PPM 3

www.siemens.com/simotics
www.siemens.com/mymotor

This flyer provides general information about the motor order number structure. However, it does not cover all possible combinations and it does not define which digits and the combinations that are applicable for each product. To select a specific product, please refer to the catalog or the configuration tools (LV Easy, Drive Technology Configurator). The best way to understand the MLFB structure and the motor parameters is to have access to a real motor. You can then scan the QR code printed on the motor rating plate using the SIDRIVE IQ Twin app on your smartphone or tablet.

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they expressly agreed upon in the concluded contact.

All product designations may be trademarks or other rights of Siemens AG, its affiliated companies or other companies whose use by third parties for their own purposes could violate the rights of the respective owner.