

Class10: Halloween mini project

Junlin Ruan (PID: A17839687)

Table of contents

Background	1
Data Export	1
Quick overview of the dataset	4
Overall Candy Ranking	10
Winpercent and Pricepercent	15
Exploring the correlation structure	17
Principal Component Analysis	18

Background

As it is nearly Halloween and the half way point in the quarter let's do a mini project that help us figure out the best candy!

Our data come from the 538 website and is available as a CSV file:

Data Export

```
candy <- read.csv("candy-data.txt", row.names = 1)
head(candy)
```

	chocolate	fruity	caramel	peanutyalmondy	nougat	crispedricewafer
100 Grand	1	0	1	0	0	1
3 Musketeers	1	0	0	0	1	0
One dime	0	0	0	0	0	0
One quarter	0	0	0	0	0	0
Air Heads	0	1	0	0	0	0
Almond Joy	1	0	0	1	0	0

	hard	bar	pluribus	sugarpercent	pricepercent	winpercent
100 Grand	0	1	0	0.732	0.860	66.97173
3 Musketeers	0	1	0	0.604	0.511	67.60294
One dime	0	0	0	0.011	0.116	32.26109
One quarter	0	0	0	0.011	0.511	46.11650
Air Heads	0	0	0	0.906	0.511	52.34146
Almond Joy	0	1	0	0.465	0.767	50.34755

```
library(flextable)
flextable::flextable(head(candy, 10))
```

chocolate	fruity	caramel	peanut	almond	ynougat	crisped	ricewafer	hard	bar	pluribus s
1	0	1	0	0	0	1	0	0	1	0
1	0	0	0	0	1	0	0	0	1	0
0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0
0	1	0	0	0	0	0	0	0	0	0
1	0	0	1	0	0	0	0	0	1	0
1	0	1	1	1	1	0	0	0	1	0
0	0	0	1	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	0	0	1
0	1	1	0	0	0	0	0	0	0	0

Q1. How many different candy types are in this dataset?

```
nrow(candy)
```

```
[1] 85
```

```
candy |>
  nrow()
```

```
[1] 85
```

```
library(tidyverse)
```

```
-- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
v dplyr      1.1.4      v readr      2.1.5
v forcats    1.0.1      v stringr    1.5.2
v ggplot2    4.0.0      v tibble     3.3.0
v lubridate  1.9.4      v tidyr      1.3.1
v purrr      1.1.0
```

```
-- Conflicts ----- tidyverse_conflicts() --
```

```
x purrr::compose() masks flextable::compose()
```

```
x dplyr::filter()  masks stats::filter()
```

```
x dplyr::lag()     masks stats::lag()
```

```
i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become
```

```
candy %>%
  nrow()
```

```
[1] 85
```

Q2. How many fruity candy types are in the dataset?

```
sum(candy$fruity)
```

```
[1] 38
```

My favorite winpercent

```
library(dplyr)
```

```
candy |>
  filter(rownames(candy) == "Almond Joy") |>
  select(winpercent)
```

```
      winpercent
Almond Joy 50.34755
```

```
candy["Twix", ]$winpercent
```

```
[1] 81.64291
```

Q3. What is your favorite candy in the dataset and what is it's winpercent value?

```
candy["Air Head", ]$winpercent
```

```
[1] 52.34146
```

Q4. What is the winpercent value for “Kit Kat”?

```
candy["Kit Kat", ]$winpercent
```

```
[1] 76.7686
```

Q5. What is the winpercent value for “Tootsie Roll Snack Bars”?

```
candy["Toostie Roll Snack Bars", ]$winpercent
```

```
[1] NA
```

Quick overview of the dataset

```
library("skimr")  
skimr::skim(candy)
```

Table 2: Data summary

Name	candy
Number of rows	85
Number of columns	12
Column type frequency:	
numeric	12
Group variables	None

Variable type: numeric

skim_variable	n_missing	complete_rate	mean	sd	p0	p25	p50	p75	p100	hist
chocolate	0	1	0.44	0.50	0.00	0.00	0.00	1.00	1.00	
fruity	0	1	0.45	0.50	0.00	0.00	0.00	1.00	1.00	
caramel	0	1	0.16	0.37	0.00	0.00	0.00	0.00	1.00	
peanutyalmondy	0	1	0.16	0.37	0.00	0.00	0.00	0.00	1.00	
nougat	0	1	0.08	0.28	0.00	0.00	0.00	0.00	1.00	
crispedricewafer	0	1	0.08	0.28	0.00	0.00	0.00	0.00	1.00	
hard	0	1	0.18	0.38	0.00	0.00	0.00	0.00	1.00	
bar	0	1	0.25	0.43	0.00	0.00	0.00	0.00	1.00	
pluribus	0	1	0.52	0.50	0.00	0.00	1.00	1.00	1.00	
sugarpercent	0	1	0.48	0.28	0.01	0.22	0.47	0.73	0.99	
pricepercent	0	1	0.47	0.29	0.01	0.26	0.47	0.65	0.98	
winpercent	0	1	50.32	14.71	22.45	39.14	47.83	59.86	84.18	

Q6. Is there any variable/column that looks to be on a different scale to the majority of the other columns in the dataset?

The winpercent is on a 0-100 scale the rest are 0-1 scale


Q7. What do you think a zero and one represent for the candy\$chocolate column?

That the candy does not contain chocolate

Q8. Plot a histogram of winpercent values


```
library(ggplot2)

ggplot(candy) +
  aes(winpercent) +
  geom_histogram(bins = 20)
```



Q9. Is the distribution of winpercent values symmetrical?

```
ggplot(candy) +  
  aes(winpercent) +  
  geom_density()
```



Q10. Is the center of the distribution above or below 50%?

```
mean(candy$winpercent)
```

```
[1] 50.31676
```

```
summary(candy$winpercent)
```

Min.	1st Qu.	Median	Mean	3rd Qu.	Max.
22.45	39.14	47.83	50.32	59.86	84.18

Q11. On average is chocolate candy higher or lower ranked than fruit candy?

```
# 1. Find all chocolate candy in the data set
# 2. Find their winpercent values
# 3. Calculate the mean of these values

# 4-6. Do the same for fruity candy
# 7. Compare mean winpercents of chocolate vs fruity
# 8. Pick the highest as the winner

choc.inds <- candy$chocolate == 1
```

```
choc.win <- candy[choc.inds, ]$winpercent
choc.mean <- mean(choc.win)
choc.mean
```

```
[1] 60.92153
```

```
mean(candy[candy$chocolate==1,]$winpercent)
```

```
[1] 60.92153
```

```
mean(candy[candy$fruity==1,]$winpercent)
```

```
[1] 44.11974
```

```
frut.ind <- candy$fruity==1
frut.win <- candy[frut.ind,]$winpercent
frut.mean <- mean(frut.win)
frut.mean
```

```
[1] 44.11974
```

```
candy |>
  filter(chocolate==1) |>
  select(winpercent)
```

	winpercent
100 Grand	66.97173
3 Musketeers	67.60294
Almond Joy	50.34755
Baby Ruth	56.91455
Charleston Chew	38.97504
Hershey's Kisses	55.37545
Hershey's Krackel	62.28448
Hershey's Milk Chocolate	56.49050
Hershey's Special Dark	59.23612
Junior Mints	57.21925
Kit Kat	76.76860
Peanut butter M&M's	71.46505

M&M's	66.57458
Milk Duds	55.06407
Milky Way	73.09956
Milky Way Midnight	60.80070
Milky Way Simply Caramel	64.35334
Mounds	47.82975
Mr Good Bar	54.52645
Nestle Butterfinger	70.73564
Nestle Crunch	66.47068
Peanut M&Ms	69.48379
Reese's Miniatures	81.86626
Reese's Peanut Butter cup	84.18029
Reese's pieces	73.43499
Reese's stuffed with pieces	72.88790
Rolo	65.71629
Sixlets	34.72200
Nestle Smarties	37.88719
Snickers	76.67378
Snickers Crisper	59.52925
Tootsie Pop	48.98265
Tootsie Roll Juniors	43.06890
Tootsie Roll Midgies	45.73675
Tootsie Roll Snack Bars	49.65350
Twix	81.64291
Whoppers	49.52411

Q12. Is this difference statistically significant?

```
t.test(choc.win, frut.win)
```

Welch Two Sample t-test

```
data:  choc.win and frut.win
t = 6.2582, df = 68.882, p-value = 2.871e-08
alternative hypothesis: true difference in means is not equal to 0
95 percent confidence interval:
 11.44563 22.15795
sample estimates:
mean of x mean of y
 60.92153  44.11974
```

Overall Candy Ranking

Q13. What are the five least liked candy types in this set?

```
candy |>
  arrange(winpercent) |>
  head(5)
```

	chocolate	fruity	caramel	peanut	almond	nougat
Nik L Nip	0	1	0		0	0
Boston Baked Beans	0	0	0		1	0
Chiclets	0	1	0		0	0
Super Bubble	0	1	0		0	0
Jawbusters	0	1	0		0	0

	crisped	rice	wafer	hard	bar	pluribus	sugar	percent	price	percent
Nik L Nip				0	0	0	1	0.197		0.976
Boston Baked Beans				0	0	0	1	0.313		0.511
Chiclets				0	0	0	1	0.046		0.325
Super Bubble				0	0	0	0	0.162		0.116
Jawbusters				0	1	0	1	0.093		0.511

	winpercent
Nik L Nip	22.44534
Boston Baked Beans	23.41782
Chiclets	24.52499
Super Bubble	27.30386
Jawbusters	28.12744

```
x <- c(5,1,10,4)
#sort(x)
order(x)
```

```
[1] 2 4 1 3
```

```
#order(candy$winpercent)
```

```
ord.ind <- order(candy$winpercent)
head(candy[ord.ind,], 5)
```

	chocolate	fruity	caramel	peanut	almond	nougat
Nik L Nip	0	1	0		0	0

Boston Baked Beans	0	0	0	1	0
Chiclets	0	1	0	0	0
Super Bubble	0	1	0	0	0
Jawbusters	0	1	0	0	0

	crispedrice	wafer	hard	bar	pluribus	sugarpercent	pricepercent
Nik L Nip		0	0	0	1	0.197	0.976
Boston Baked Beans		0	0	0	1	0.313	0.511
Chiclets		0	0	0	1	0.046	0.325
Super Bubble		0	0	0	0	0.162	0.116
Jawbusters		0	1	0	1	0.093	0.511

	winpercent
Nik L Nip	22.44534
Boston Baked Beans	23.41782
Chiclets	24.52499
Super Bubble	27.30386
Jawbusters	28.12744

Q14. What are the top 5 all time favorite candy types out of this set?

```
candy |>
  arrange(winpercent) |>
  tail(5)
```

	chocolate	fruity	caramel	peanut	almond	nougat
Snickers	1	0	1		1	1
Kit Kat	1	0	0		0	0
Twix	1	0	1		0	0
Reese's Miniatures	1	0	0		1	0
Reese's Peanut Butter cup	1	0	0		1	0

	crispedrice	wafer	hard	bar	pluribus	sugarpercent
Snickers		0	0	1	0	0.546
Kit Kat		1	0	1	0	0.313
Twix		1	0	1	0	0.546
Reese's Miniatures		0	0	0	0	0.034
Reese's Peanut Butter cup		0	0	0	0	0.720

	pricepercent	winpercent
Snickers	0.651	76.67378
Kit Kat	0.511	76.76860
Twix	0.906	81.64291
Reese's Miniatures	0.279	81.86626
Reese's Peanut Butter cup	0.651	84.18029

```
candy |>
  arrange(-winpercent) |>
  head(5)
```


	chocolate	fruity	caramel	peanut	almondy	nougat
Reese's Peanut Butter cup	1	0	0		1	0
Reese's Miniatures	1	0	0		1	0
Twix	1	0	1		0	0
Kit Kat	1	0	0		0	0
Snickers	1	0	1		1	1

	crisped	rice	wafer	hard	bar	pluribus	sugar	percent
Reese's Peanut Butter cup		0	0	0		0		0.720
Reese's Miniatures		0	0	0		0		0.034
Twix		1	0	1		0		0.546
Kit Kat		1	0	1		0		0.313
Snickers		0	0	1		0		0.546

	price	percent	winpercent
Reese's Peanut Butter cup	0.651		84.18029
Reese's Miniatures	0.279		81.86626
Twix	0.906		81.64291
Kit Kat	0.511		76.76860
Snickers	0.651		76.67378


Q15. Make a first barplot of candy ranking based on winpercent values.

```
ggplot(candy) +
  aes(winpercent, rownames(candy)) +
  geom_col()
```



Q16. This is quite ugly, use the `reorder()` function to get the bars sorted by winpercent?

```
ggplot(candy) +  
  aes(x = winpercent,  
      y = reorder(rownames(candy), winpercent)) +  
  geom_col()
```




Add some color based on the “type” of candy

```
my_cols <- rep("black", nrow(candy))
my_cols[as.logical(candy$chocolate)] <- "chocolate"
my_cols[as.logical(candy$fruity)] <- "pink"
my_cols[as.logical(candy$bar)] <- "brown"
my_cols
```

```
[1] "brown"    "brown"    "black"    "black"    "pink"     "brown"
[7] "brown"    "black"    "black"    "pink"     "brown"    "pink"
[13] "pink"     "pink"     "pink"     "pink"     "pink"     "pink"
[19] "pink"     "black"    "pink"     "pink"     "chocolate" "brown"
[25] "brown"    "brown"    "pink"     "chocolate" "brown"    "pink"
[31] "pink"     "pink"     "chocolate" "chocolate" "pink"     "chocolate"
[37] "brown"    "brown"    "brown"    "brown"    "brown"    "pink"
[43] "brown"    "brown"    "pink"     "pink"     "brown"    "chocolate"
[49] "black"    "pink"     "pink"     "chocolate" "chocolate" "chocolate"
[55] "chocolate" "pink"     "chocolate" "black"    "pink"     "chocolate"
[61] "pink"     "pink"     "chocolate" "pink"     "brown"    "brown"
[67] "pink"     "pink"     "pink"     "pink"     "black"    "black"
[73] "pink"     "pink"     "pink"     "chocolate" "chocolate" "brown"
[79] "pink"     "brown"    "pink"     "pink"     "pink"     "black"
[85] "chocolate"
```

```
ggplot(candy) +
  aes(winpercent, reorder(rownames(candy), winpercent)) +
  geom_col(fill=my_cols)
```



Q17. What is the worst ranked chocolate candy?


Sixlets > Q18. What is the best ranked fruity candy?

Starburst

Winpercent and Pricepercent


A plot with both variables/columns winpercent and pricepercent

```
my_cols[as.logical(candy$fruity)] <- "red"
ggplot(candy) +
  aes(x = winpercent,
      y = pricepercent,
      label = rownames(candy)) +
  geom_point(col=my_cols) +
  geom_text()
```



```
library(ggrepel)
my_cols[as.logical(candy$fruity)] <- "red"
ggplot(candy) +
  aes(x = winpercent,
      y = pricepercent,
      label = rownames(candy)) +
  geom_point(col=my_cols) +
  geom_text_repel(max.overlaps = 7)
```

Warning: ggrepel: 68 unlabeled data points (too many overlaps). Consider increasing max.overlaps



Q19. Which candy type is the highest ranked in terms of winpercent for the least money - i.e. offers the most bang for your buck?

Reese's Miniatures > Q20. What are the top 5 most expensive candy types in the dataset and of these which is the least popular?

```
ord <- order(candy$pricepercent, decreasing = TRUE)
head(candy[ord, c(1, 11, 12)], n = 5)
```

	chocolate	pricepercent	winpercent
Nik L Nip	0	0.976	22.44534
Nestle Smarties	1	0.976	37.88719
Ring pop	0	0.965	35.29076
Hershey's Krackel	1	0.918	62.28448
Hershey's Milk Chocolate	1	0.918	56.49050


Exploring the correlation structure

Now that we've explored the dataset a little, we'll see how the variables interact with one another. We'll use correlation and view the results with the `corrplot` package to plot a correlation matrix.

```
library(corrplot)
```

corrplot 0.95 loaded

```
cij <- cor(candy)  
corrplot(cij)
```



Q22. Examining this plot what two variables are anti-correlated (i.e. have minus values)?

fruity and chocolate > Q23. Similarly, what two variables are most positively correlated?

winpercent and chocolate

Principal Component Analysis

The function to use is called `prcomp()` with an optional `scale=T/F` argument.

```
pca <- prcomp(candy, scale = TRUE)  
summary(pca)
```


Importance of components:

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
Standard deviation	2.0788	1.1378	1.1092	1.07533	0.9518	0.81923	0.81530
Proportion of Variance	0.3601	0.1079	0.1025	0.09636	0.0755	0.05593	0.05539
Cumulative Proportion	0.3601	0.4680	0.5705	0.66688	0.7424	0.79830	0.85369
	PC8	PC9	PC10	PC11	PC12		
Standard deviation	0.74530	0.67824	0.62349	0.43974	0.39760		
Proportion of Variance	0.04629	0.03833	0.03239	0.01611	0.01317		
Cumulative Proportion	0.89998	0.93832	0.97071	0.98683	1.00000		

Our main PCA result figure


```
ggplot(pca$x) +
  aes(PC1, PC2, label = rownames(pca$x)) +
  geom_point(col = my_cols) +
  geom_text_repel(col = my_cols)
```

Warning: ggrepel: 48 unlabeled data points (too many overlaps). Consider increasing max.overlaps



We should also examine the variable “loading” or contributions of the original variables to the new PCs

```
ggplot(pca$rotation) +
  aes(PC1, rownames(pca$rotation)) +
  geom_col()
```



```
p <- ggplot(pca$x) +
  aes(PC1, PC2, label = rownames(pca$x)) +
  geom_point(col = my_cols) +
  geom_text_repel(col = my_cols)
```

Interactive plots that can be zoomed on and “brushed” over can be made with the **plotly** package. Its output is interactive and will not render to PDF :-)

```
library(plotly)
```

Attaching package: 'plotly'

The following object is masked from 'package:ggplot2':

last_plot

The following objects are masked from 'package:flextable':

`highlight, style`

The following object is masked from 'package:stats':

`filter`

The following object is masked from 'package:graphics':

`layout`

```
#ggplotly(p)
```

Q24. What original variables are picked up strongly by PC1 in the positive direction? Do these make sense to you?

PC1 picked up “fruity”, “hard”, “pluribus” in the positive direction. It makes sense as it picks up candies that fall into these categories.