

## Homework 2: Huffman Coding and Vector Quantization

M10907324 吳俊逸

Problem 1:

Implementation of Huffman Coding

Participants can do simple implementation for alphabets with any probability vector as presented in the class.

Code :

Basic program structure :

Coding: Count the number of occurrences-->Probability-->Create codebook--

>Replace text with codebook content

Decoding: count a few 1-->do all 1 processing-->get the index of each code-->replace the codebook content with text

```
clc;clear all;close all;

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%           input English and space only           %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

String_input ="a pig in my room";

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%           coding start           %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

eng_list=["a","b","c","d","e","f","g","h","i","j","k","l","m","n","o",
,"p","q","r","s","t","u","v","w","x","y","z"," "];
count_val=0;                                     % Word counter
count_zero=0;                                    % Has 0 counter
count_coding=0;                                  % Calculate the coding
number counter

for i=1:1:27
    n(2,i) = count(String_input, eng_list(1,i));    % Count the
number of occurrences of each letter
    count_val=count_val+n(2,i);                      % Count the total
```

```

number of words
end

for i=1:1:27
    n(3,i) = n(2,i) / count_val; % Calculate the
probability of each letter
    pa(1,i)=n(3,i);
end

[B,I]=sort(pa); % Sort B = Probability
of occurrence I = Index after sorting

for i=1:1:27
    if B(1,i)==0
        count_zero=count_zero+1; % Count a few zeros
    end
end

for i=1:1:27
    if B(1,i)~=0
        sort_num(1,i-count_zero)=eng_list(1,I(1,i)); % Sort after
removing zero, index-->symbol
    end
end
count_coding=27-count_zero;
k=0;
for i=1:1:count_coding
    for j = 1:1:i-1
        k=k*10+1;
    end
    if i ~= count_coding
        coding_num1(1,i)=k*10;
    else
        coding_num1(1,i)=k;
    end
    k=0;
end
end

```

```

coding_Ans=String_input;
for j=1:1:count_coding

coding_Ans=strrep(coding_Ans,sort_num(1,j),int2str(coding_num1(1,j)))
; %Letters are converted into huffman coding
end

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%                                %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%                                %
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%

decoding_val=findstr(coding_Ans, '0');
%Found 0 address
decoding_sub(1,1)=decoding_val(1,1);
%To know the address difference between two adjacent zeros, first
fill in the prime minister, because the array does not have the
zeroth item
a=0;b=0;
for i=2:1:length(decoding_val)
    decoding_sub(1,i)=decoding_val(1,i)-decoding_val(1,i-1);
end

for i=2:1:length(decoding_val)
    if decoding_sub(1,i) > (count_coding-1)
%If the subtracted number is greater than the code length of the
largest codebook content

        a=a+1; %Know
that this is the code length greater than the largest codebook
content
        index(1,a)=i;
%Store its index item

```

```

        sub_val(1,a)=fix(decoding_sub(1,i)/(count_coding-1));
%How many older
        mod_val(1,a)=mod(decoding_sub(1,i),(count_coding-1));
%The last yard left

        for k=1:1:sub_val(1,a)
            add(1,k)=count_coding;
%Combine the codes to be replaced (all ones)
        end

        if mod_val(1,a) ~= 0
            add(1,sub_val(1,a)+1)=mod_val(1,a);
%Combine the code to be replaced (the last code)
        else
            add(1,sub_val(1,a))=count_coding-1;
%Combine the code to be replaced (the last code)
        end

        if a==1
            decoding= [decoding_sub(1:index(1,1)-1) add(1,1:end)
decoding_sub(index(1,1)+1:end)];%Put the first code to be replaced
into
        else
            decoding= [decoding(1:index(1,a)-1+b) add(1,1:end)
decoding(index(1,a)+1+b:end)];%Put other codes to be replaced into
        end

        b=b+length(add)-1; %Calculate the value of index to be
inserted into the array
        add=[];%Empty storage
    end
end
decoding_Ans=decoding; %Copy the data to another array
for i=1:1:length(decoding)

decoding_Ans=strrep(decoding_Ans,decoding(1,i),sort_num(1,decoding(1,
i)));%huffman coding into letters
end

```



[illegible]

```
String_input
```

coding\_Ans

```
result after Huffman encoding
```

decoded text

example :

```
String_input =
```

```
coding_Ans =
```

```
decoding_Ans =
```

```
String_input =
```

```
coding_Ans =
```

```
decoding_Ans =
```

## Problem 2:

Linde-Buzo-Gray (LBG) algorithm to perform Vector Quantization or any variants of LBG can also be considered for implementation.

Participants can work on any image data-sets (even for a single image is fine) for training and implementation.

I prepare two methods

### 1. Compress the image directly

The codebook CB is obtained through the LBG () classification method. CB is composed of N k-dimensional codewords ( $N=256$ ,  $k=16$ ),  $i=1,2,3,\dots,N-1$ . Compressed image: Suppose a grayscale image T of size T is divided into image blocks B of size. Then find the index table Gi through optimization. Image decompression: A compressed image can be generated according to the index table and CW.

Code :

```
clc;clear all;close all;
%%
tic;
a=4;
b=a*a;
input=imread('lena.bmp');
I=double(imread('lena.bmp'));
B=im2col(I,[a,a],'distinct');% Decompose the image into a
16*(128*128) matrix
[m,n]=size(B);
N=256;
CB=zeros(m,N);
CW=zeros(1,n);
rng(999);
CB_cnt=randperm(n);
CB=B(:,CB_cnt(1:N));
for x=1:10%10 iterations
    for y=1:n%training
        p=B(1:b,y)*ones(1,N);
        [~,yy]=min(sum((p-CB).^2));
        CW(y)=yy;
    end
end
```

```

        for z=1:N%Select
            v=find(CW==z);
            for k=1:m
                nv=sum(B(k,v))/numel(v);
                CB(k,z)=nv;
            end
        end
    end
    toc
    DE=zeros(m,n);
    for i=1:n
        DE(:,i)=CB(:,CW(i));
    end
    img_4=col2im(DE,[a,a],[512,512],'distinct');

%%
tic;
a=8;
b=a*a;
input=imread('lena.bmp');
I=double(imread('lena.bmp'));
B=im2col(I,[a,a],'distinct');% Decompose the image into a 64*(64*64)
matrix
[m,n]=size(B);
N=256;
CB=zeros(m,N);
CW=zeros(1,n);
rng(999);
CB_cnt=randperm(n);
CB=B(:,CB_cnt(1:N));
for x=1:10%10 iterations
    for y=1:n%training
        p=B(1:b,y)*ones(1,N);
        [~,yy]=min(sum((p-CB).^2));
        CW(y)=yy;
    end
    for z=1:N%Select

```

```

        v=find(CW==z);
        for k=1:m
            nv=sum(B(k,v))/numel(v);
            CB(k,z)=nv;
        end
    end
end
toc
DE=zeros(m,n);
for i=1:n
    DE(:,i)=CB(:,CW(i));
end
img_8=col2im(DE,[a,a],[512,512],'distinct');

%%
tic;
a=16;
b=a*a;
input=imread('lena.bmp');
I=double(imread('lena.bmp'));
B=im2col(I,[a,a],'distinct');% Decompose the image into a 256*(32*32)
matrix
[m,n]=size(B);
N=256;
CB=zeros(m,N);
CW=zeros(1,n);
rng(999);
CB_cnt=randperm(n);
CB=B(:,CB_cnt(1:N));
for x=1:10%10 iterations
    for y=1:n%training
        p=B(1:b,y)*ones(1,N);
        [~,yy]=min(sum((p-CB).^2));
        CW(y)=yy;
    end
    for z=1:N%Select
        v=find(CW==z);
        for k=1:m

```



```

        nv=sum(B(k,v))/numel(v);
        CB(k,z)=nv;
    end
end
end
toc
DE=zeros(m,n);
for i=1:n
    DE(:,i)=CB(:,CW(i));
end
img_16=col2im(DE,[a,a],[512,512],'distinct');

%%
subplot(221);
imshow(input);title('Input Image');
subplot(222);
imshow(uint8(img_4));title('VQ-16*(128*128) matrix');
subplot(223);
imshow(uint8(img_8));title('VQ-64*(64*64) matrix');
subplot(224);
imshow(uint8(img_16));title('VQ-256*(32*32) matrix');

```

Results of the code :



2.

Code1 → Codebook training, take codebook=256 as an example :

Basic program structure :

--> Take the two adjacent points in the photo as a group and send it to the codebook to evaluate the distance

--> rank the results after evaluation and take the first index

--> add this group of data to code\_avg, and calculate the number of times in code\_time Medium

--> Calculate the average of all points closer to the node

--> Replace the result in the original codebook

--> The preset number of training is ten times, which means that the above actions are repeated ten times

--> The final codebook Save in txt

--> END

```
clc;clear all;close all;
```

```
A2=[27 107 13 39 133 194 164 39 167 148 223 108 112 70 113
180 169 192 203 104 116 240 218 37 160 23 89 4 213 127 100
117 218 64 0 65 156 189 122 53 100 165 153 33 23 226 116
74 99 196 170 48 54 17 168 162 119 81 140 86 44 208 108
102 166 222 177 175 84 174 248 96 154 132 233 239 163 80
```

```

172 157 55 221 106 95 91 63 12 137 26 164 85 52 136 218
158 7 90 203 88 163 160 223 140 236 144 231 198 93 24 15
80 15 17 191 90 228 64 18 6 54 72 116 155 199 93 250 237
226 ;
91 27 13 37 127 117 164 165 47 148 221 103 129 71 192 180
250 119 194 217 181 163 102 159 28 228 226 118 125 58 52
160 121 244 97 91 149 226 62 106 163 226 144 225 114 240 78
150 137 97 97 0 166 194 97 30 76 7 3 201 205 222 163 50
66 64 196 132 158 59 44 165 40 26 90 25 1 252 230 80 81
149 30 236 144 82 60 86 109 173 208 198 240 142 152 107 77
193 202 166 238 77 30 14 155 201 90 188 242 160 199 22 230
45 114 79 145 15 246 43 188 36 121 88 85 215 78 215
]; %Codebook after taking random random numbers

for i=1:1:10
    code_avg=[0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 ;
        0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0];
    code_time=[0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 ;
        0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0];
    data=double(imread("./imgdata/cameraman.tif"));
    nx=256;
    ny=256;
    for i = 1:1:nx
        for j=1:2:ny%Throw the two points in the picture as a group
into the codebook to evaluate the distance
            for k = 1:1:16

```

```

        sub(1,k)=(data(i,j)-A2(1,k))^2+(data(i,j+1)-
A2(2,k))^2;%Calculate the distance between each point and the node
    end

    [B,I]=sort(sub);%"B" is the look after sorting, "I" is the
index of the original position before sorting

    code_avg(1,I(1,1))=code_avg(1,I(1,1))+data(i,j);%Add the
points closest to the node into the variable code_avg
    code_avg(2,I(1,1))=code_avg(2,I(1,1))+data(i,j+1);
    code_time(1,I(1,1))=code_time(1,I(1,1))+1;%Calculate the
accumulation times in code_time
    end
end
for j=1:1:2
    for i = 1:1:128
        code_avg(j,i)=code_avg(j,i)/code_time(1,i);%Average the
points near the node
        if(uint8(code_avg(j,i))~=0)
            A2(j,i)=uint8(code_avg(j,i));%Write the changed data
into the codebook variable
        end
    end
end
end
fid=fopen(['./','codebook_256.txt'],'w');%Write file path
[r,c]=size(A2);% Get the number of rows and columns of the matrix
for i=1:r
    for j=1:c
        fprintf(fid,'%f\t',uint8(A2(i,j)));%Write data to txt file
    end
    if(i==1)
        fprintf(fid,';\n');%Matlab notation for conversion to 2-
dimensional matrix reduction
    else
        fprintf(fid,'\n');
    end
end
fclose(fid);

```

Code2→Use self-built codebook to apply to VQ compression :

```
clc;clear all;close all;
ccc=512;
input=imread('lena.bmp');

A_16=[27 70 110 113 149 153 169 180 183 188 192 215 223 228 240 248];
aaa_16=imread('lena.bmp');
for i=1:1:ccc
    for j = 1:1:ccc
        aaa_16(i,j);
        for k=1:1:16
            if(aaa_16(i,j)>A_16(1,k))
                sub_16(1,k)=aaa_16(i,j)-A_16(1,k);%Calculate the distance
between each point and the node
            else
                sub_16(1,k)=A_16(1,k)-aaa_16(i,j);%Calculate the distance
between each point and the node
            end
        end
        [B,I]=sort(sub_16);%"B" is the look after sorting, "I" is the
index of the original position before sorting
        aaa_16(i,j)=A_16(I(1,1));
    end
end
```

```
A_64=[5 12 13 19 20 23 24 27 39 41 46 47 51 53 55 59 61 64 65 72 74
76 81 82 91 92 99 106 107 110 111 114 115 118 121 136 146 148 149
152 155 156 157 160 163 169 173 174 177 179 182 183 185 187 205 210
215 222 224 228 232 242 246 254];
aaa_64=imread('lena.bmp');
for i=1:1:ccc
    for j = 1:1:ccc
        aaa_64(i,j);
        for k=1:1:64
            if(aaa_64(i,j)>A_64(1,k))
                sub_64(1,k)=aaa_64(i,j)-A_64(1,k);%Calculate the distance
between each point and the node
            end
        end
    end
end
```

```

        else
            sub_64(1,k)=A_64(1,k)-aaa_64(i,j);%Calculate the distance
between each point and the node
        end
    end

    [B,I]=sort(sub_64);%"B" is the look after sorting, "I" is the
index of the original position before sorting
    aaa_64(i,j)=A_64(I(1,1));
end
end

A_256=[27 107 13 39 133 194 164 39 167 148 223 108 112 70
113 180 169 192 203 104 116 240 218 37 160 23 89 4 213 127
100 117 218 64 0 65 156 189 122 53 100 165 153 33 23 226
116 74 99 196 170 48 54 17 168 162 119 81 140 86 44 208
108 102 166 222 177 175 84 174 248 96 154 132 233 239 163
80 172 157 55 221 106 95 91 63 12 137 26 164 85 52 136 218
158 7 90 203 88 163 160 223 140 236 144 231 198 93 24 15
80 15 17 191 90 228 64 18 6 54 72 116 155 199 93 250 237
226 ;
91 27 13 37 127 117 164 165 47 148 221 103 129 71 192 180
250 119 194 217 181 163 102 159 28 228 226 118 125 58 52
160 121 244 97 91 149 226 62 106 163 226 144 225 114 240 78
150 137 97 97 0 166 194 97 30 76 7 3 201 205 222 163 50
66 64 196 132 158 59 44 165 40 26 90 25 1 252 230 80 81
149 30 236 144 82 60 86 109 173 208 198 240 142 152 107 77
193 202 166 238 77 30 14 155 201 90 188 242 160 199 22 230
45 114 79 145 15 246 43 188 36 121 88 85 215 78 215 ];
aaa_256 = imread('lena.bmp');
nx=256;
ny=256;
for i = 1:1:nx
    for j=1:2:ny%Throw the two points in the picture as a group into
the codebook to evaluate the distance
        for k = 1:1:16
            sub(1,k)=(aaa_256(i,j)-A_256(1,k))^2+(aaa_256(i,j+1)-
A_256(2,k))^2;%Calculate the distance between each point and the node
        end
    end
end

```

```
[B,I]=sort(sub);%"B" is the look after sorting, "I" is the index  
of the original position before sorting
```

```
aaa_256(i,j)=A_256(1,I(1,1));
```

```
aaa_256(i,j+1)=A_256(2,I(1,1));
```

```
end
```

```
end
```

```
%%
```

```
subplot(221);
```

```
imshow(input);title('Input Image');
```

```
subplot(222);
```

```
imshow(uint8(aaa_16));title('VQ-Use 16 codebooks');
```

```
subplot(223);
```

```
imshow(uint8(aaa_64));title('VQ-Use 64 codebooks');
```

```
subplot(224);
```

```
imshow(uint8(aaa_256));title('VQ-Use 256 codebooks');
```

Results of the code :

