Informatica® Intelligent Data Management Cloud

October 2026

Secure Agent Services

Informatica Intelligent Data Management Cloud Secure Agent Services
October 2026

© Copyright Informatica LLC 2021, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices and AI assistant acknowledgements are included with the product.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-10-16

Table of Contents

Preface 6

Informatica Resources 6

- Informatica Documentation 6
- IDMC web site 6
- IDMC Communities 6
- IDMC Marketplace 6
- Data Integration connector documentation 7
- Informatica Knowledge Base 7
- IDMC Trust Center 7
- IDMC Pulse Dashboard 7
- Informatica Global Customer Support 7

Chapter 1: Secure Agent services 8

Setting custom environment variables 10

Configuring a restart schedule 10

Chapter 2: API Microgateway Service 12

Editing the API Microgateway Service properties 13

Enabling the API Microgateway Service in a Secure Agent or a Secure Agent group 14

Chapter 3: CMI Streaming Agent 15

CMI Streaming Agent properties 15

Chapter 4: Common Integration Components 18

Common Integration Components properties 18

Chapter 5: Connector Service 21

Connector Service properties 21

Chapter 6: Data Access Management Agent service 22

Data Access Management Agent service properties 22

Chapter 7: Data Access Management Proxy service 27

Database drivers 27

Data Access Management Proxy service properties 28

Chapter 8: Database Ingestion service 30

Database Ingestion service properties 30

Database Ingestion Agent environment variables 34

Chapter 9: Data Integration Server 35
Data Integration Server resiliency 35
Data Integration Server properties 36
Creating the OSProfileUserMappingFile 40
Setting the OSProfileScriptForTaskExecution 42
Data Integration Server upgrades 43

Chapter 10: DV Processor 45

Chapter 11: Elastic Server 46
Elastic Server properties 46
Elastic Server concurrency 48

Chapter 12: File Integration Service 50

Chapter 13: GitRepoConnectApp 51
Local repository base directory 51
GitRepoConnectApp properties 52

Chapter 14: IDMC Data Gateway Service 54
IDMC Data Gateway Service properties 54

Chapter 15: Mass Ingestion (Files) 60

Chapter 16: Metadata Foundation Application 64
Metadata Foundation Application properties 64

Chapter 17: Metadata Platform Service 69
Metadata Platform Service properties 69

Chapter 18: Process Server 75
Process Server properties 75
Default connection database properties 81
Logging levels 82
Configuring a separate logging data source 82
Process Server sizing recommendations 83
Communication with the Secure Agent 85
Secure Agent configurations for Process Server 86
Deploy to a single Secure Agent 87
Deploy to a Secure Agent group 87
Prerequisites for PostgreSQL database installation and upgrade 90
Managing the PostgreSQL database on Windows 90

Backing up the PostgreSQL database on Windows. . . . 91
Restoring the PostgreSQL database on Windows. . . . 91
Resetting the PostgreSQL database on Windows. . . . 91
Starting the PostgreSQL server on Windows. . . . 92
Stopping the PostgreSQL server on Windows. . . . 92
Getting the PostgreSQL server status on Windows. . . . 92
Vacuuming the PostgreSQL database on Windows. . . . 92
Reindexing the PostgreSQL database on Windows. . . . 93
Resetting transaction logs on Windows. . . . 93
Managing the PostgreSQL database on Linux. . . . 93
Backing up the PostgreSQL database on Linux. . . . 94
Restoring the PostgreSQL database on Linux. . . . 94
Resetting the PostgreSQL database on Linux. . . . 94
Starting the PostgreSQL server on Linux. . . . 95
Stopping the PostgreSQL server on Linux. . . . 95
Getting the PostgreSQL server status on Linux. . . . 95
Vacuuming the PostgreSQL database on Linux. . . . 95
Reindexing the PostgreSQL database on Linux. . . . 96
Resetting transaction logs on Linux. . . . 96
Upgrading the PostgreSQL database. . . . 96
Upgrading the PostgreSQL database using the replication technique. . . . 97
PostgreSQL configuration files. . . . 100
Configuring PostgreSQL log rotation. . . . 100
Configuring public certificates and private keys for Process Server. . . . 101
Configuring thread pool profile to improve throughput. . . . 102
Overriding properties in the platform.yaml file. . . . 104
Creating a custom user-platform.yaml file. . . . 104
Troubleshooting. . . . 105
Rolling upgrades. . . . 106
Rolling upgrade error handling. . . . 106

Chapter 19: SecretManagerApp. . . . 107

Chapter 20: Customer Managed Data Integration Service. . . . 108

Customer Managed Data Integration Service properties. . . . 108

Chapter 21: ResilientManagerApp. . . . 110

Chapter 22: Taskflow Service. . . . 112

Chapter 23: Configuring Secure Agent service properties. . . . 113

Index. . . . 115

Preface

Use *Secure Agent Services* to learn about the microservices that the IDMC℠ Secure Agent uses for data processing. Learn how to configure service properties.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

IDMC web site

You can access the Informatica® Intelligent Data Management Cloud™ (IDMC) web site at http://www.informatica.com/cloud.

IDMC Communities

Use the IDMC Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the IDMC Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

IDMC Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

IDMC Trust Center

The IDMC Trust Center provides information about Informatica security, compliance, and privacy practices.

You can access the trust center at https://trust.informatica.com/.

IDMC Pulse Dashboard

The IDMC Pulse Dashboard provides system status and upgrade information for all PODs and services across IDMC.

Follow the services you use and subscribe to alerts to receive notifications about upgrades, maintenance, production incidents, and upcoming releases. The IDMC Pulse Dashboard displays the production status of all the IDMC products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single service or all IDMC services. Subscribing to all services is the best way to be certain you never miss an update.

For more information, see the Service Status and Communications guide.

Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the IDMC Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

Secure Agent services

Secure Agent services are pluggable microservices that the Secure Agent uses for data processing. For example, the Secure Agent uses the Data Integration Server to run data integration jobs and Process Server to run application integration and process orchestration jobs. Each Secure Agent service runs independently of the other services that run on the agent.

The independent services architecture provides the following benefits:

- The Secure Agent does not restart when you add a connector or package.
- Services are not impacted when another service restarts. For example, process orchestration jobs continue to run when the Data Integration Server restarts.
- Downtime during upgrades is minimized. The upgrade process installs a new version of the Secure Agent, updates connector packages, and applies configuration changes for the Data Integration Server and Database Ingestion agent service. To minimize downtime, the old agent remains available and continues to run data integration jobs during the upgrade. The new version of the Secure Agent runs jobs that start after the upgrade process completes.

The services that run on a Secure Agent vary based on your organization's licenses and the IDMC services that are enabled for the Secure Agent group.

The following table describes the Secure Agent services that can run on an agent and the IDMC services that use them:

Secure Agent service	Description	Used by...
API Microgateway Service	Manages Application Integration processes that run on the Secure Agent.	Application Integration
B2B Processor	Runs B2B Gateway inbound and outbound process flows. **Note:** Do not change the values of the service properties unless Informatica Global Customer Support instructs you to do so.	B2B Gateway
CIH Processor	Runs Cloud Integration Hub publications and subscriptions for organizations that use a private publication repository.	Cloud Integration Hub
CMI Streaming Agent	Runs streaming ingestion and replication jobs in the Data Ingestion and Replication service.	Data Ingestion and Replication
Common Integration Components	Runs the shell scripts or batch commands in a Command Task step of a taskflow.	Data Integration
Connector Service	Enables connectivity and data integration with various external systems.	Data Integration, Data Ingestion and Replication

Secure Agent service	Description	Used by...
Data Access ManagementAgent	Implements, configures, or enforces data access policies regarding access to data.	Data Governance and Catalog, Data Integration
Data Access ManagementProxy	Enables you to query data through a data access policy-enforcement flow. Specifically, you submit a SQL query through the JDBC client driver.	Data Governance and Catalog, Data Marketplace
Database Ingestion	Runs application ingestion and replication jobs and database ingestion and replication jobs in the Data Ingestion and Replication service.	Data Ingestion and Replication
Data Integration Server	Runs data integration jobs such as mapping, task, and taskflow instances.	B2B Gateway, Cloud Integration Hub, Data Integration, Data Profiling
Domain Management App	Connects on-premises CDI-PC domains with IDMC and handles backend domain update tasks.	Cloud Data Integration for PowerCenter (CDI-PC)
DV Processor	Checks data integrity, accuracy, and consistency across two different data sets.	Data Validation
EDC Search Agent	Discovers Enterprise Data Catalog data assets for data catalog discovery in Data Integration. **Note:** Do not change the values of the service properties unless Informatica Global Customer Support instructs you to do so.	Data Integration
Elastic Server	Manages an advanced cluster and the jobs that run on the cluster.	Data Integration
File Integration Service	Uses file transfer protocols such as HTTPS, AS2, and SFTP to receive files from a remote server or to send files to a remove server, or both.	B2B Gateway, Data Integration
GitRepoConnectApp	Manages communication between IDMC and the source control repository when your organization uses an on-premises source control repository.	All IDMC that use source control
IDMC Data Gateway Service	Enables you to perform data exploration tasks in CLAIRE GPT. You can explore source data, preview a sample of the data set, see the SQL code used to fetch the sample data, and save the sample data in a CSV file for future reference.	CLAIRE GPT
Mass Ingestion	Runs file ingestion and replication tasks and file listener jobs. **Note:** Do not change the values of the service properties unless Informatica Global Customer Support instructs you to do so.	Data Ingestion and Replication
Metadata Foundation Application	Extracts metadata from the configured source systems in your organization, and uploads the extracted metadata to Metadata Command Center through the Secure Agent.	Data Governance and Catalog, Metadata Command Center

Secure Agent service	Description	Used by...
Metadata Platform Service	Performs profiling activities for the jobs that you run in Metadata Command Center. **Note:** Profiling fails if there is no active Metadata Platform Service present in the runtime environment of Metadata Command Center.	Data Governance and Catalog, Metadata Command Center
OI Data Collector	Runs the Operational Insights data collectors that collect the operational data and domain-related metadata from PowerCenter, Data Engineering Integration, and Data Quality. **Note:** Do not change the values of the service properties unless Informatica Global Customer Support instructs you to do so.	Operational Insights
Process Server	Runs application integration processes, connectors, and connections.	Application Integration, Application Integration Console
SecretManagerApp	Manages communication between IDMC and your secrets manager when your organization uses an external secrets manager like AWS Secrets Manager or Azure Key Vault.	Data Integration

Each Secure Agent service has a unique set of configuration properties, such as Tomcat and Tomcat JRE settings. You might need to configure a service or change the service properties to optimize performance or if you are instructed to do so by Informatica Global Customer Support. You configure a Secure Agent service independently from other services that run on the agent.

Setting custom environment variables

You can customize your environment by adding scripts or variables to the `custom_env_settings.sh` script.

If you need to set custom environment variables for any of the services, add them to a script file named `custom_env_settings.sh` and place this file in the directory where the Secure Agent is installed.

For example, the following script ensures that your custom variables are automatically set up after you upgrade the agent:

```
$ pwd
/apps/cloudagent/apps/Data_Integration_Server/65.0.3.1/.lcm
$ ls lcm-env.sh
lcm-env.sh
```

Configuring a restart schedule

Some Secure Agent services, such as Process Server, might need to be restarted after they are upgraded. You can configure a restart schedule for some of these services after a minor upgrade such as a monthly upgrade or a patch release. Configure the restart schedule on the **Settings** page.

When you configure a restart schedule, you select the day of the week and time in which to restart the services. For example, you might schedule the restarts for Sundays at 00:00 GMT.

You can configure a restart schedule for the Process Server service. To configure the restart schedule, perform the following steps:

1. In Administrator, select **Settings**.
2. Click **Edit** in the **Upgrade Settings for Secure Agent Services** area.
3. Select a day and time.
4. Click **Save**.

If you do not configure a restart schedule, by default, the Process Server service is automatically restarted 7 days after your Point of Deployment (POD) is upgraded.

CHAPTER 2

API Microgateway Service

The API Microgateway Service manages Application Integration processes that run on the organization's on-premises Secure Agent. Use the API Microgateway Service to expose managed APIs as API Microgateway proxies.


You can use the following methods to control access to managed APIs that you publish with the API Microgateway Service:

- IP filtering policy
- Rate limit policy
- Basic authentication or OAuth 2.0 authentication

The API Microgateway Service provides REST APIs to create and deploy API Microgateway proxies. API consumers access the managed APIs deployed as API Microgateway proxies on the organization's on-premises environment. The Application Integration processes expose REST Service URL and SOAP Service URL endpoints.

Use the API Microgateway Service to build an API Microgateway proxy to an API endpoint to manage. The API Microgateway Service builds an API Microgateway as an immutable Docker image on the organization's Secure Agent machine. You then use the API Microgateway Service to deploy the Docker image in a container on the Secure Agent Docker runtime environment for API access. The API Microgateway applies the API access policies that you configure before forwarding the requests to Application Integration endpoints.

The following diagram shows the API Microgateway Service and API Microgateway components exposing a managed API in the on-premises environment:



The Secure Agent Docker runtime environment hosts the Docker images using the blue-green deployment strategy to provide zero downtime during updates of the API Microgateway component.

Editing the API Microgateway Service properties

Edit the API Microgateway Service properties in Administrator.

The following image shows the API Microgateway Service properties you can edit in the **System Configuration Details** area:

▼ System Configuration Details

Service: API Microgateway Service

Type: All Types

Type	Name	Value
AGENT_RUNTIME_SETTINGS	project-name	'project1'
AGENT_RUNTIME_SETTINGS	docker-registry-name	'infa.agent.apimgw'
DOCKER_CONTAINER_SETTINGS	blue	http-port: '16090' https-port: '16095'
DOCKER_CONTAINER_SETTINGS	green	http-port: '17090' https-port: '17095'
DOCKER_CONTAINER_SETTINGS	haproxy	http-port: '6090' https-port: '6095'

The following table describes the API Microgateway Service configurations:

Type	Name	Description
AGENT_RUNTIME_SETTINGS	project-name	Name of the project that stores the API configurations. You can change the name as per requirement, for example when you create a new project. **Note:** Project name must not contain the characters `/` or `/0`. If a project name includes restricted characters, the project creation fails.
AGENT_RUNTIME_SETTINGS	docker-registry-name	Name of the local Docker registry that contains all the named and tagged API Microgateway Docker images on the Secure Agent machine. **Note:** Docker image and tag names must not contain the following characters: `- _ , .` If a Docker image or tag name includes restricted characters, the image build fails.
DOCKER_CONTAINER_SETTINGS	blue	First Docker image container that deploys on the Secure Agent machine, alternates with green. You can change the following ports of the blue container: - http-port. The default value is: 16090 - https-port. The default value is: 16095
DOCKER_CONTAINER_SETTINGS	green	Second Docker image container that deploys on the Secure Agent machine, alternates with blue. You can change the following ports of the green container: - http-port. The default value is: 17090 - https-port. The default value is: 17095
DOCKER_CONTAINER_SETTINGS	haproxy	Router of the Docker image containers on the Secure Agent machine. Switches traffic between blue and green containers. You can change the following ports of the haproxy container: - http-port. The default value is: 6090 - https-port. The default value is: 6095

Note: To stop the API Microgateway, stop all three Docker image containers.

Enabling the API Microgateway Service in a Secure Agent or a Secure Agent group

If you want to change the Secure Agent that runs the API Microgateway Service, enable the API Microgateway Service for a Secure Agent or a Secure Agent group in Administrator. When you enable API Microgateway Service for a Secure Agent group, it is enabled for all the Secure Agents in the group and for any Secure Agent that you later add to the group.

1. Navigate to the **Runtime Environments** page and select **Enable or Disable Services, Connectors** from the **Actions** menu of a Secure Agent or a Secure Agent group.

   The **Enable/Disable Components in Agent** window appears.

2. Select **API Microgateway** from the list of services and click **Save**.

   API Microgateway Service is enabled for the Secure Agent or the Secure Agent group.

CHAPTER 3

CMI Streaming Agent

Use the CMI Streaming Agent to define and deploy streaming ingestion and replication tasks. You configure streaming ingestion and replication tasks in the Data Ingestion and Replication service.

A CMI Streaming Agent runs on an on-premise system and works in conjunction with the Streaming Ingestion and Replication. In an on-premise system, the CMI Streaming Agent runs the jobs deployed by Streaming Ingestion and Replication. The agent provides status and statistics updates of each job.


On Linux, the CMI Streaming Agent does not start if the agent installation directory name contains a space. The agent returns a connection timeout status. After a few restart attempts, the agent goes into the error state.

CMI Streaming Agent properties

To change or optimize the behavior of the CMI Streaming Agent, configure agent properties for your run-time environment. Configure CMI Streaming Agent properties in the **System Configuration Details** area when you edit a Secure Agent.

You can configure Engine, Agent, and Script properties of a CMI Streaming Agent.

The following image shows some of the CMI Streaming Agent properties:



System Configuration Details

Service: CMI Streaming Agent

Type: All Types

Type	Name	Value
Engine	MaxLogFileSize	'5MB'
Engine	LogLevel	'DEBUG'
Agent	DataflowPullInterval	60
Agent	JVM	'-Xms256M -Xmx256M'
Agent	LogLevel	'DEBUG'
Agent	MaxLogFileSize	'10MB'
Agent	MaxNumberOfBackups	5
Scripts	LogLevel	'DEBUG'
Scripts	MaxFileSize	'5MB'
Scripts	MaxBackupIndex	5

You can configure the following CMI Streaming Agent properties:

Type	Property Name	Description
Engine	MaxLogFileSize	The maximum size of the log file that the engine can create. Default is 5 MB.
Engine	LogLevel	The log level for the engine.
Agent	DataflowPullInterval	The time interval after which the agent checks for updates in the task. Default is 60 seconds.
Agent	JVM	List of JVM properties for the agent. For example: `[-Xms256M -Xmx256M]`
Agent	LogLevel	The log level for the agent.
Agent	MaxLogFileSize	Maximum size of the log files that an agent can create. Default is 10 MB.

Type	Property Name	Description
Agent	MaxNumberOfBackups	Maximum number of backup log files for the agent. Default is 5.
Scripts	LogLevel	The log level of the scripts.
Scripts	MaxFileSize	The maximum file size after which the log rolls over and creates a new file. Default is 10 MB.
Scripts	MaxBackupIndex	Maximum number of backup files maintained after rolling over. Default is 5.

CHAPTER 4

Common Integration Components

The Common Integration Components service is the Secure Agent service that runs the commands specified in a Command Task step of a taskflow.

You can optimize the performance of the Common Integration Components service by configuring some of its service properties. You can change service properties when you edit the Secure Agent.

All the requests that Common Integration Components service processes are logged in the following directory:

```
<Secure Agent installation directory>\apps\Common_Integration_Components\logs\<version>
```

You can view the log file for each command task in the following directory:


```
<Secure Agent installation directory>\apps\Common_Integration_Components\logs\command
\<Command_job ID>
```

In a serverless runtime environment, the Secure Agent pushes the log file for each command task to Amazon S3.

Common Integration Components properties

To change or optimize the behavior of the Common Integration Components service, configure its properties in the **System Configuration Details** section when you edit a Secure Agent.

The following image shows some of the Common Integration Components service properties:



You can configure the following Common Integration Components service properties:

Type	Name	Description
Tomcat	JRE_OPTS	JRE VM options for the Apache Tomcat process.
Platform	LCM_JRE_OPTS	JRE options to start, stop, or get the status of the Apache Tomcat process. **Note:** Do not change the value of this property unless Informatica Global Customer Support instructs you to do so.
SYSTEM_CFG	HTTP_CONNECTION_TIMEOUT_SECONDS	The maximum amount of time, in seconds, that the Secure Agent waits to set up an HTTP connection to communicate with IDMC. Default is 60. **Note:** Do not change the value of this property unless Informatica Global Customer Support instructs you to do so.
SYSTEM_CFG	HTTP_SOCKET_TIMEOUT_SECONDS	The maximum amount of idle time, in seconds, during the data packet transfer over an HTTP connection between the Secure Agent and IDMC. Default is 60. **Note:** Do not change the value of this property unless Informatica Global Customer Support instructs you to do so.

Type	Name	Description
COMMAND_CFG	MaximumConcurrentJobs	The maximum number of concurrent command tasks that can be executed by a single Secure Agent. The default value is 10 for each Secure Agent in a Secure Agent group. For example, if there are 3 Secure Agents in a Secure Agent group, the maximum number of concurrent command tasks that the service can handle is 30. Any command execution requests beyond the maximum limit are queued and are executed when a Secure Agent is available.
Note: Do not change the values of other Common Integration Components service properties unless Informatica Global Customer Support instructs you to do so.		

CHAPTER 5

Connector Service

The Connector Service enables connectivity and data integration with various external systems, applications, databases, platforms, and cloud services.


The Connector Service lets you connect to different data sources and targets, supporting ETL operations by managing protocols, drivers, and APIs. It handles communication, authentication, and data exchange.

When you configure the Connector Service, you can configure the Java VM options and set debug options. You can configure Connector Service properties when you edit the Secure Agent.

Connector Service properties

Configure Connector Service properties in the **System Configuration Details** area when you edit a Secure Agent.

The following image shows the Connector Service properties:



You can configure the following Data Integration Server properties:

Type	Name	Description
JAVA_CFG	JAVA_VM_OPTIONS	Options to configure the Java virtual machine. Default is '-Xms32m -Xmx512m -XX:MaxPermSize=128m -DNON OSGI ENABLED=true' For more information, see INFA_MEMORY and JVM options in the Data Integration Performance Tuning guide.
JAVA_CFG	DEBUG_OPTIONS	Options to configure debugging mode. Informatica Global Customer Support will help you set the debugging options as necessary.

CHAPTER 6

Data Access Management Agent service

The Data Access Management Agent service implements, configures, or enforces policies regarding access to data.

Put a compatible JDBC driver in the following location: <install>/ext/connectors/thirdparty/ where "<install>" represents the directory in which you installed the Secure Agent. You only need to provide these drivers for accessing Snowflake and Databricks cloud data platforms. You can download compatible JDBC drivers from the vendors' websites.

Note: When you change any of the drivers, restart the Data Access Management Agent service so that the service can acquire the drivers.


Data Access Management Agent service properties

To set up the Data Access Management Agent service for the first time, specify a user name from the tenant that has the "read Connection" privilege and the "read Secure Agent Group and Secure Agent" privilege. The Secure Agent uses this user name to retrieve the required connection configuration and credentials in the runtime service.

Note: If your organization enables permissions on either the runtime environment or the connection, the user referenced as the usernameWithConnectionPrivileges requires the same permissions.

To optimize the behavior of the Data Access Management Agent service, configure its properties in the **System Configuration Details** section when you edit a Secure Agent.

The following image shows the Data Access Management Agent service properties:



You can configure the following system properties of the Data Access Management Agent service in the **System Configuration Details** section:

Type	Name	Description	Sample Value	Default Value
AGENT	enableFileBasedAudit	Set to true to generate audit logs. Leave as false to prevent audit log generation.	true	false
AGENT	customFileBasedAuditPath	You can specify a directory where the Secure Agent writes audit logs. The default path is the path in which you installed the Secure Agent.	log/audit/	not set
AGENT	dataAccessManagementSecretName	Name of the secret used for the hashing data de-identification technique used in Secret Key Mode.	my_secret	DATA_ACCESS_MANAGEMENT_SECRET

Type	Name	Description	Sample Value	Default Value
AGENT	usernameWithConnectionPrivileges	**Required**. Specify a user name from the tenant that has the "read Connection" privilege and the "read Secure Agent Group and Secure Agent" privilege. The Secure Agent uses this user name to retrieve the required connection configuration and credentials in the runtime service.	jdoe **Note:** The Data Access Management Agent service doesn't start without a valid value for the usernameWithConnectionPrivileges property.	not set
AGENT	pullChangesBatchSize	The maximum number of updates in a batch to process.	50	100
AGENT	pollingPeriod	The period for polling for new updates.	1h	5m
AGENT	pingPeriod	How often to ping the runtime service to indicate that the agent is still up and consuming updates.	45s	1m
AGENT	plugin.databricks.default.useIsAccountGroupMember plugin.databricks.<connection-id>.useIsAccountGroupMember	Grants data access based on group membership. plugin.databricks.default.useIsAccountGroupMember applies to all connections of type Databricks. plugin.databricks.<connection-id>.useIsAccountGroupMember applies only to the connection specified. The connection-specific setting overrides the default.	true **Note:** Set this to true if plugin.databricks.default.useIsMember is set to false. Both can be true.	false

Type	Name	Description	Sample Value	Default Value
AGENT	plugin.databricks.default.useIsMember plugin.databricks.<connection-id>.useIsMember	Grants data access based on local workspace group membership. plugin.databricks.default.useIsMember applies to all connections of type Databricks. plugin.databricks.<connection-id>.useIsMember applies only to the connection specified. The connection-specific setting overrides the default.	false **Note:** Set this to true if plugin.databricks.default.useIsAccountGroupMember is set to false. Both can be true.	true
AGENT	plugin.fabric-warehouse.default.schema	**Note:** The default Microsoft Fabric Data Warehouse schema name that Data Access Management uses to manage data filter policies is CDAM_INTERNAL_STATE. If this name does not comply with your organization's schema naming convention, use the plugin.fabric-warehouse.default.schema property to give the schema another name.	MY_SCHEMA	CDAM_INTERNAL_STATE

Type	Name	Description	Sample Value	Default Value
AGENT	plugin.redshift.default.namespace plugin.redshift.<connection-id>.namespace	**Note:** If your organization uses an identity provider (IdP) and pushes data access policies to Amazon Redshift, add a custom property to the Data Access Management Agent service for the namespace that Amazon Redshift requires. With the custom property, the Secure Agent maps the IDMC user groups in the data access policies to the IdP-based roles created in a namespace in Amazon Redshift. plugin.redshift.default.namespace applies to all connections of type Amazon Redshift. plugin.redshift.<connection-id>.namespace applies only to the connection specified. The connection-specific setting overrides the default.	my_namespace	not set
AGENT	datasourceChangesParallelism	The maximum number of data source updates to process in parallel.	3	4
AGENT	maxShutdownTime	How long to wait for a graceful shutdown to complete before invoking a forced shutdown.	45s	1m

CHAPTER 7

Data Access Management Proxy service

The Data Access Management Proxy service enables you to query data through a policy-enforcement flow.

Two types of JDBC drivers relate to the Data Access Management Proxy service:

The driver for your database management tool.

Examples of these tools include DBeaver and SQuirreL SQL client. Informatica provides this driver. Download the driver from Informatica Marketplace. Register it with your database management tool so that you can create a new database connection using the driver. Do not put this driver in the Secure Agents. Use this connection to access data in a Data Marketplace order.

To learn more about which sources to use, see *Catalog Source Quick Reference* in the Data Governance and Catalog help.

The source drivers for the Secure Agents.

Your database vendors supply these drivers. Put these source drivers in the following location in all Secure Agents: /ext/connectors/thirdparty/. For example, to access PostgreSQL databases, add the latest PostgreSQL driver to the following location in the Secure Agent: /ext/connectors/thirdparty/.

To learn more about which drivers to use with your databases, see "Database drivers" on page 27.

Note: When you change any of the drivers, restart the Data Access Management Proxy service for the service to acquire the drivers.

Database drivers

Use the following database drivers with the Data Access Management Agent service and the Data Access Management Proxy service.

Database Vendor	Database Version	Driver Version
Apache Hive	3.1.2+	hive-jdbc 2.3.7
Microsoft SQL Server	15+	11.2.3
MySQL	8+	8.0.27

Database Vendor	Database Version	Driver Version
Oracle	19+	ojdbc8-19.8.0.0
PostgreSQL	13+	42.6.0


Data Access Management Proxy service properties

To set up the Data Access Management Proxy service for the first time, specify a user name from the tenant that has the "read Connection" privilege and the "read Secure Agent Group and Secure Agent" privilege. The Secure Agent uses this user name to retrieve the required connection configuration and credentials in the runtime service.

Note: If your organization enables permissions on the connection, the user referenced as the userWithConnectionPrivileges requires the same permissions.

To change or optimize the behavior of the Data Access Management Proxy service, configure its properties in the **System Configuration Details** section when you edit a Secure Agent.

The following image shows the Data Access Management Proxy service properties:



You can configure the following system properties of the Data Access Management Proxy service in the **System Configuration Details** section:

Type	Name	Description	Sample Value	Default Value
DATA_PROXY	enableFileBasedAudit	Set to true to generate audit logs. Leave as false to prevent audit log generation.	true	false
DATA_PROXY	customFileBasedAuditPath	You can specify a directory where the Secure Agent writes audit logs. The default path is the path in which you installed the Secure Agent.	log/audit/	not set
DATA_PROXY	userWithConnectionPrivileges	For the proxy to be accessible, specify a user name from the tenant that has the "read Connection" privilege. The Secure Agent uses this user name to retrieve the required connection configuration and credentials in the runtime service.	jdoe **Note:** The Data Access Management Proxy service will not start without a valid value for the userWithConnectionPrivileges property.	not set
DATA_PROXY	jdbc_port	Port exposed by the proxy for querying the proxy.	3306	51320
DATA_PROXY	jdbc_host	The network interface this connector binds to as an IP address or a hostname. If null or 0.0.0.0, then bind to all interfaces.	127.0.0.1	0.0.0.0

CHAPTER 8

Database Ingestion service

Both Application Ingestion and Replication and Database Ingestion and Replication use the Database Ingestion agent service to run jobs.

After you download the Secure Agent to your runtime environment and enable the Database Ingestion service, the Database Ingestion packages are pushed to the on-premises system where the Secure Agent runs. You can then optionally configure properties for the Database Ingestion service that runs on the Secure Agent.

Database Ingestion service properties

To change or optimize the behavior of the Database Ingestion service that your Secure Agent group uses, you can configure Database Ingestion agent configuration properties for your runtime environment.

To configure the properties, open a Secure Agent in your runtime environment and click **Edit**. Under **System Configuration Details**, select **Database Ingestion** as the service and **DBMI_AGENT_CONFIG** or **LOCAL_TASK_CONFIG** as the type.

The following table describes the Database Ingestion agent service properties for the **DBMI_AGENT_CONFIG** type:

Property	Description
maxTaskUnits	The maximum number of application ingestion and replication task units and database ingestion and replication task units that can run concurrently on an on-premises machine where the Secure Agent is running. Task units are not related to the capacity and availability of your hardware or software. You can configure maxTaskUnits to precisely control CPU usage. Valid values are 1 to 2000000000 (2 billion). To calculate a reasonable number of task units for your Secure Agent machine, Informatica recommends that you divide the number of cores by 3 or 4. For example, if you have an 8-core machine, you could set this property to 2. Then monitor CPU usage and adjust the property value as needed to tune performance. During initial load processing, this property determines the number of tables that can be unloaded simultaneously. Remaining tables are queued and start unload processing when resources become available. **Note:** A single job can process many tables. The total number of tables that can be processed is limited only by available memory. On the average, 25 MB of RAM is required per table for an initial load task based on a 1 KB row size. During incremental load processing, this property determines the number of application ingestion and replication and database ingestion and replication jobs that can run simultaneously. Setting this property to a value greater than the number of cores on the Secure Agent machine can increase parallelism for task execution but also cause performance bottlenecks at task execution time.
serviceLogRetentionPeriod	The number of days to retain each internal Database Ingestion service log file after the last update is written to the file. When this retention period elapses, the log file is deleted. The default value is 7 days. Service logs are retained on the Secure Agent host where they are created: `<infaagent>/apps/Database_Ingestion/logs`. **Note:** This property is applicable to both Application Ingestion and Replication and Database Ingestion and Replication.
taskLogRetentionPeriod	The number of days to retain each job log file after the last update is written to the file. When this retention period elapses, the log file is deleted. The default value is 7 days.
ociPath	For Oracle sources and targets, the path to the Oracle Call Interface (OCI) directory that contains the oci.dll or libclntsh.so file. By default, Oracle uses $ORACLE_HOME/lib on Linux or %ORACLE_HOME%\bin on Windows. The OCI library is used by database ingestion CDC tasks to connect to Oracle. For a DBMI agent that is running, this value is appended to the PATH environment variable value on Windows or to the LD_LIBRARY_PATH environment variable value on Linux. This property is not required if you already included the OCI path in the PATH or LD_LIBRARY_PATH environment variable. **Note:** This property is applicable only to Database Ingestion and Replication.
serviceUrl	The URL that the Database Ingestion service uses to connect to the IDMC cloud. **Note:** This property is applicable to both Application Ingestion and Replication and Database Ingestion and Replication.

Property	Description
logLevel	The level of detail to include in the logs that the Database Ingestion service produces. Options are: - TRACE - DEBUG - INFO - WARN - ERROR The default value is TRACE. **Note:** This property is applicable to both Application Ingestion and Replication and Database Ingestion and Replication.
taskExecutionHeapSize	The maximum heap size, in gigabytes, for the Task Execution service. This heap size is used for the single Java process that hosts all application ingestion and replication tasks and database ingestion and replication tasks that run in the common Container service. You might need to increase this value if you run a large number of tasks or process a large volume of data. Enter the property value followed by "g" for gigabytes. The default value is '8g'. **Note:** This property is applicable to both Application Ingestion and Replication and Database Ingestion and Replication.
useProxy	Set this property to true to force the Database Ingestion agent service (DBMI Agent) to use the proxy settings from the Secure Agent proxy configuration when connecting to sources and targets. When set to false, proxy information might still be used. The DBMI Agent allows the JDBC drivers to fall back to their own default proxy usage behavior, which can be triggered by other proxy-related environment variable settings. Default is false. **Note:** This property is applicable to both Application Ingestion and Replication and Database Ingestion and Replication.
intermediateStorageDirectory	For incremental load and combined initial and incremental load jobs, the local root directory under which intermediate files that contain data are stored when the **Enable Persistent Storage** option is selected in the associated task definitions. This directory must reside on a safe, highly accurate, and high-performance device, as the stored data is critical to the product success and operational accuracy. **Note:** This property is applicable only to Database Ingestion and Replication.
storageBackupDirectory	For incremental load and combined initial and incremental load jobs, the path to the directory that stores backup files when the **Enable Persistent Storage** option is selected in the associated task definitions. This directory must reside on a safe, highly accurate, and high-performance device, as the stored data is critical to the product success and operational accuracy. **Note:** This property is applicable only to Database Ingestion and Replication.

Property	Description
storageProperties	For incremental load and combined initial and incremental load jobs, a comma-separated list of key=value pairs that is used when the **Enable Persistent Storage** option is selected in the associated task definitions. Specify this property only at the direction of Informatica Global Customer Support. **Note:** This property is applicable only to Database Ingestion and Replication.
supportedLoadTypes	For application ingestion and replication jobs and database ingestion and replication jobs, the load types that the Database Ingestion agent service can process. You can enter one or more of the following values, separated by a comma (,): - INITIAL. Initial load jobs or the initial load phase of combined initial and incremental load jobs. - INCREMENTAL. Incremental load jobs or the incremental phase of combined initial and incremental load jobs, which write to your target. - INCREMENTAL_STAGING. CDC staging tasks of incremental load or combined load jobs. Default is INITIAL,INCREMENTAL,INCREMENTAL_STAGING, which indicates all load types. **Notes:** - If multiple Database Ingestion agent services are configured to support the same load types, the jobs use the agent with the most available task units. - If the Database Ingestion agent service where a combined load job is running does not support the initial load type, the initial load phase of the combined load job is directed to another agent in the Secure Agent group where the initial load type enabled.

The following table describes the Database Ingestion agent service properties for the **LOCAL_TASK_CONFIG** type:

Property	Description
taskExecutionHeapSize	The maximum heap size, in gigabytes, available for running a single task, such as the CDC Staging Task, in its own Java Virtual Memory (JVM). You might need to increase this size if the task processes a large volume of data. Enter the property value followed by "g" for gigabytes. The default value is '2g'.
taskStartTimeoutSeconds	The number of seconds that must elapse before an attempt to start a task in its own JVM times out. The default value is 120.

Database Ingestion Agent environment variables

To change or optimize the behavior of the Database Ingestion agent service, you can define environment variables:

To configure environment variables, open a Secure Agent in your runtime environment and click **Edit**. Under **System Configuration Details** or **Custom Configuration Details**, select **Database Ingestion** as the service and **DBMI_AGENT_ENV** as the type.

Environment Variable	Description
DBMI_REPLACE_UNSUPPORTED_CHARS	For Microsoft Azure Synapse Analytics targets, controls whether an application ingestion and replication job or database ingestion and replication job replaces characters in character data that the target cannot process correctly. To enable character replacement, set this environment variable to true. `DBMI_REPLACE_UNSUPPORTED_CHARS=true` Application Ingestion and Replication or Database Ingestion and Replication then uses the character that is specified in the DBMI_UNSUPPORTED_CHARS_REPLACEMENT environment variable to replace unsupported characters.
DBMI_UNSUPPORTED_CHARS_REPLACEMENT	If the DBMI_REPLACE_UNSUPPORTED_CHARS environment variable is set to true, specifies the character that replaces the characters in source data that a Microsoft Azure Synapse Analytics target cannot process correctly. Default value: ? (question mark) **Note:** Define this environment variable only for Database Ingestion and Replication.
DBMI_WRITER_CONN_POOL_SIZE	Indicates the number of connections that an application ingestion and replication job or database ingestion and replication job uses to propagate the change data to the target. The default value is 8. Valid values are 4 through 8.
DBMI_WRITER_RETRIES_MAX_COUNT	If a network issue occurs while a database ingestion and replication job is loading source data to an Amazon S3 or Microsoft Azure Data Lake Storage Gen2 target, indicates the maximum number of times that the job retries a request to continue the initial load or incremental load. If all of the retries fail, the job fails. The default value is 5.
DBMI_WRITER_RETRIES_INTERVAL_IN_MILLIS	Specifies the time interval, in milliseconds, that a database ingestion and replication job waits before retrying the request to continue the initial load or incremental load to an Amazon S3 or Microsoft Azure Data Lake Storage Gen2 target if a network issue occurs. The default value is 1000.

Note: After you define or change an environment variable, restart the Database Ingestion Agent for the changes to take effect.

CHAPTER 9

Data Integration Server

The Data Integration Server is the Secure Agent service that runs data integration jobs such as mapping, task, and taskflow instances.

If an advanced cluster processes data logic in a mapping in advanced mode, the Data Integration Server defers the advanced cluster subtask to the Elastic Server.

You can optimize performance of the Data Integration Server by configuring some of its service properties. For example, you might want to change the network resiliency settings or the connection timeout period for the Secure Agent. You can change service properties when you edit the Secure Agent.

Data Integration Server resiliency

During temporary network issues, data integration tasks can continue to run while the Secure Agent tries to reestablish a connection. You can configure network resiliency properties for the Data Integration Server.

The following Data Integration Server properties determine how the Secure Agent tries to reestablish a connection:

NetworkTimeoutPeriod

Determines the length of time that the Secure Agent tries to reestablish communication with IDMC. If communication is not established at the end of the time period, data integration tasks that were in progress stop running. The default value is 300 seconds.

NetworkRetryInterval


Determines the frequency with which the Secure Agent tries to contact IDMC within the specified timeout period. The default value is five seconds.

For example, with the default settings, if the network is down, the Secure Agent tries to reestablish communication with IDMC for 300 seconds. During the 300-second period, the Secure Agent tries to contact IDMC every five seconds. If the Secure Agent reestablishes communication within the 300-second period, data integration tasks that are in progress are not affected. If the Secure Agent is unable to reestablish communication within the 300-second period, the Secure Agent stops all data integration tasks that are in progress.

Data Integration Server properties

To change or optimize behavior of the Data Integration Server, configure the Data Integration Server properties. Configure Data Integration Server properties in the **System Configuration Details** area when you edit a Secure Agent.

The following image shows some of the Data Integration Server properties:



You can configure the following Data Integration Server properties:

Type	Name	Description
Tomcat	NetworkTimeoutPeriod	Amount of time, in seconds, that the Secure Agent tries to reestablish communication with IDMC. Default is 300.
Tomcat	NetworkRetryInterval	Frequency, in seconds, in which the Secure Agent tries to contact IDMC within the specified timeout period. Default is 5.
Tomcat	INFA_DTM_STAGING_ENABLED_CONNECTORS	Applies to certain Cloud Data Warehouse connectors. Enables the Data Integration Server to optimize staging target data in a local flat file before loading the data to the target. To optimize staging, set this property to the plugin ID of the connector. For more information, see the help for the appropriate connector.

Type	Name	Description
Tomcat	INFA_DTM_RDR_STAGING_ENABLED_CONNECTORS	Applies to certain Cloud Data Warehouse connectors. Enables the Data Integration Server to optimize the staging of source data in a local flat file after reading the data from the source. To optimise staging, set this property to the plugin ID of the connector. For more information, see the help for the appropriate connector.
Tomcat	INFA_DTM_LKP_STAGING_ENABLED_CONNECTORS	Applies to certain Cloud Data Warehouse connectors. Enables the Data Integration Server to optimize the staging of lookup data in a local flat file after reading the data from the lookup object. To optimize staging, set this property to the plugin ID of the connector. For more information, see the help for the appropriate connector.
Tomcat JRE	JRE_OPTS	JRE VM options for the Apache Tomcat process.
Tomcat JRE	INFA_MEMORY	JRE VM options that are set for virtual machine memory for the Apache Tomcat process.
DTM	AgentConnectionTimeout	Number of seconds that the Secure Agent communication requests to wait before it times out. Default is 5.

Type	Name	Description
DTM	JVMOption1 - JVMOption5	JVM options that configure advanced properties for the Data Integration Server such as the maximum and minimum JVM heap size, the maximum record size for Intelligent Structure Discovery, or proxy settings for certain connectors. For example, to change the maximum JVM heap size from the default value of 512 MB to 2048 MB, you might set JVMOption1 to `'-Xmx2048m'`. By default, you can configure up to five advanced properties using JVMOption1 through JVMOption5. To configure additional properties, you can add custom DTM properties for the Data Integration Server named JVMOption6, JVMOption7, etc. Ensure that the option numbers are sequential and that you do not skip numbers. For information about the JVM options that you can set, see the Data Integration help, the help for the appropriate connector, or the Knowledge Base on Informatica Network.
ELASTIC_RUNTIME	resources_requests_cpu	Number of cores to reserve for the Data Integration Server in an elastic runtime environment. Enter an integer or decimal, or an integer followed by m for millicores. Enclose the value in single quotes. For example: '1', '4.5', or '1000m'.
ELASTIC_RUNTIME	resources_requests_memory	Amount of memory to reserve for the Data Integration Server in an elastic runtime environment. Enter an integer followed by Ei, Pi, Ti, Gi, Mi, or Ki. Enclose the value in single quotes. For example: '2Gi' or '512Mi'.
ELASTIC_RUNTIME	dtm_container_resources_requests_cpu	Number of cores to reserve for a job that runs on the Data Integration Server in an elastic runtime environment. Jobs run faster on more cores, and parallel processing improves. Use fewer cores for light jobs. Default is '1000m', or 1 core. Enter an integer or decimal, or an integer followed by m for millicores. Enclose the value in single quotes. For example: '1', '4.5', or '1000m' . You can override this value by specifying a different number of cores in the mapping task properties.

Type	Name	Description
ELASTIC_RUNTIME	dtm_container_resources_requests_memory	Amount of memory to reserve for a job that runs on the Data Integration Server in an elastic runtime environment. Larger memory improves transformations that use a cache to perform lookups, joins, and aggregations. It also decreases disk I/O bottlenecks. Use less memory for light jobs. Default is '2Gi', or 2 GB. Enter an integer followed by Ei, Pi, Ti, Gi, Mi, or Ki. Enclose the value in single quotes. For example: '2Gi' or '512Mi'. You can override this value by specifying a different amount of memory in the mapping task properties.
ELASTIC_RUNTIME	replicaCount	Number of Data Integration Server applications to run in an elastic runtime environment. When you run a job, the applications distribute the workload. Running more than one application enables high availability.
OS_PROFILE	EnableOSProfileForTaskExecution	Enables or disables the OS Profile functionality. Values are true or false. Default is false. **Note:** The OS Profile functionality is only available on Linux. By default, tasks run with the same operating user as the Secure Agent. When you enable the OS Profile functionality, you can run tasks with a different operating system user. For example, you have different departments using the same IDMC installation and you need isolation. **Tip:** You can view the name of the OS Profile user in the session log for completed tasks.
OS_PROFILE	FailTasksForMissingOsProfileMapping	If the OS Profile functionality is enabled, this property fails a task if the mapping to the operating system user for a given task is missing. Values are true or false. Default is true. Set this property to false to not fail the task in this scenario and instead run the task with the Secure Agent's operating system user.

Type	Name	Description
OS_PROFILE	ShareSystemDirectories	Shares the system directories that were created for the Secure Agent user with the operating system user. Values are true or false. Default is false. Enable sharing if you want to share information such as user parameters. However, for improved isolation and reduced possibility of errors, don't share these directories. The default behavior creates new system directories for the operating system user under `Data_Integration_Server/data/osprofiles_filesystem/<profile_name>` The system directories save mapping information, sessions logs, and user parameters.
OS_PROFILE	OSProfileUserMappingFile	Location of the YAML file that contains mapping information between the Secure Agent user or location and the operating system user. Changes to the mapping file apply automatically, without needing to restart the Secure Agent. For more information about this property, see "Creating the OSProfileUserMappingFile" on page 40.
OS_PROFILE	OSProfileScriptForTaskExecution	Location of the script file that will be used for task execution. For more information about this property, see "Setting the OSProfileScriptForTaskExecution" on page 42.
Note: Do not change the values of other Data Integration Server properties unless Informatica Global Customer Support instructs you to do so.		

Creating the OSProfileUserMappingFile

When defining OS_PROFILE properties, you need to create a YAML file that contains mapping information between the Secure Agent user or location and the operating system user. This is set in the OSProfileUserMappingFile property in the Data Integration Server service.

Create a YAML file using the following example as a template:

```
- profileName: userprofile1
  profileType: USER
  systemNames:
  - osp_idmc_1
  osMapping:
    osUser: osprofileuser1
    pmVariables:
      PMRootDir: /home/osprofileuser1/pmdata
      PMSessionLogDir: /mnt/shared/Vadi/osprofile
      PMBadFileDir: /home/osprofileuser1/pmbadfile
```

```
        PMCacheDir: /home/osprofileuser1/pmcache
        PMTargetFileDir: /home/osprofileuser1/pmtrgtfile
        PMSourceFileDir: /home/osprofileuser1/pmsrcfile
        PMExtProcDir: /home/osprofileuser1/pmextproc
        PMTempDir: /home/osprofileuser1/pmtemp
        PMLookupFileDir: /home/osprofileuser1/pmlookupfile
        PMStorageDir: /data/agent/userparam
      envVariables:
       - envVariable:
           name: name1
           value: ":value1:"
           addToExisting: suffix
       - envVariable:
           name: name2
           value: value2
       - envVariable:
           name: LD_LIBRARY_PATH
           value: ":abcd:"
           addToExisting: prefix
  - profileName: userprofile2
    profileType: USER
    systemNames:
    - osp_idmc_2
    osMapping:
      osUser: osprofileuser2
  - profileName: locationprofile1
    profileType: LOCATION
    systemNames:
    - osprofilefoldertest1
    - osprofiletestfolder2
    osMapping:
      osUser: osprofileuser1
  - profileName: locationprofile2
    profileType: LOCATION
    systemNames:
    - osprofilefoldertest1\test
    - osprofiletestfolder\test
    osMapping:
      osUser: osprofileuser2
```

The following table describes each property in the YAML file:

Property	Description
profileName	Name of the profile. Must be unique. This property is required.
profileType	Describes whether this mapping is based on the Secure Agent user or location. Valid values are USER or LOCATION. **Note:** If both User and Location profile types are specified for the same task, then User has the higher precedence.
systemNames	This section contains a list of IDMC system names. - If profileType = USER, then the system names are a list of IDMC users. - If profileType = LOCATION, then the system names are a list of IDMC location names. Use the absolute path for every location.
osMapping	This section contains a mapping to the operating system.
osUser	The operating system user.

Property	Description
pmVariables	A list of the PM variables to override. The following variables can be overridden: - PMRootDir - PMSessionLogDir - PMBadFileDir - PMCacheDir - PMTargetFileDir - PMSourceFileDir - PMExtProcDir - PMTempDir - PMLookupFileDir **Note:** The override directories must be accessible by both Secure Agent and operating system users. To ensure this, add both the Secure Agent and operating system users to the profile OS user group.
envVariables	This section defines the OS environment variables for each OS_PROFILE mapping. Define one or more `envVariable` entries with the following properties: - name. Name of the environment variable. - value. Value of the environment variable. - addToExisting. Optional. Set to either **prefix** or **suffix** to indicate whether the entry should be added before or after an existing variable. Use this property to add information to environment variables like PATH or LD_LIBRARY_PATH. The existing environment variable being prefixed or suffixed is from the OS User for the Secure Agent. When you add a prefix or suffix, it gets applied to the environment variable that is set in the user account where the Secure Agent is installed.

Setting the OSProfileScriptForTaskExecution

When defining OS_PROFILE properties, you need to define a script that will be used for task execution. This is set in the OSProfileScriptForTaskExecution property in the Data Integration Server service.

Choose one of the following methods to create your OS profile script:

- Configure the `pmimpprocess` executable. This is the recommended method because it is more secure.
- Use the default script provided by Informatica.

Use the following table to help you decide which method to use:

Method	Advantage	Disadvantage
Use pmimpprocess (recommended)	More secure, with the one time sticky bit set as root.	More difficult to customize, as pmimpprocess is an executable. The sole purpose of this executable is to switch users.
Use default script	Easily customizable. For example, you need to configure Kerberos.	Requires the Secure Agent user to be able to sudo, which means adding the user to /etc/sudoer. Once this is done, the user assumes near root-user privileges, which is less secure.

Configuring the pmimpprocess

To configure the OS profile script using `pmimpprocess`, perform the following steps:

1. Locate the `pmimpprocess` process in the following location:

   ```
   <Secure Agent installation directory/downloads/package-
   ICSAgentRuntime.<latest_version>/package/ICS/main/bin/rdtm
   ```

2. Copy `pmimpprocess` to the Secure Agent.
   For example:

   ```
   <Secure Agent installation directory>/apps/Data_Integration_Server/ext/pmimpprocess
   ```

3. Run the following command to change the permissions of `pmimpprocess`:

   ```
   chmod 755 pmimpprocess
   ```

4. Log in as the root user or sudo as root.

5. Run the following command to change the ownership and access permissions of `pmimpprocess`:

   ```
   chown root:root pmimpprocess
   chmod u+s pmimpprocess
   ```

6. Enter the location of `pmimpprocess` for the value of the OSProfileScriptForTaskExecution property in "Data Integration Server properties" on page 36.
   For example:

   ```
   <Secure Agent installation directory>/apps/Data_Integration_Server/ext/pmimpprocess
   ```

Using the default script

If you prefer to use the script method, locate the script in the following location:

```
Data_Integration_Server/ext/infa-osprofile-dtm.sh
```

Note: The script method is intended for advanced technical users only.

The following illustration shows the default script:

```
#!/bin/sh
input_args="$@"
env_var_file=$(mktemp)
chmod +r "${env_var_file}"
printenv | sed 's/\(^[^=]*\)=\(.*\)/export \1="\2"/'>"${env_var_file}"
echo "sudo su - ${ENV_INFA_DTM_OSPROFILE_USER} -c . ${env_var_file}; cd ${PWD}; $
{input_args}" >/tmp/xx
sudo su - ${ENV_INFA_DTM_OSPROFILE_USER} -c ". ${env_var_file}; cd ${PWD}; ${input_args}"
exit_code=$?
rm "${env_var_file}"
exit "${exit_code}"
```

Update the script as appropriate to meet your needs.

Data Integration Server upgrades

The Data Integration Server upgrades automatically when a new version is available.

Data Integration Server upgrades are automatic and don't require any user intervention. When an upgrade is available, a new version of the Data Integration Server starts up and the old version stops after processing all jobs. If there are long-running jobs such as CDC continuous extraction jobs, the upgrade process terminates the job on the old version of the Data Integration Server and restarts them as new jobs on the upgraded version.

When this happens, the original job shows as a failed status with the following message on the My Jobs page:

```
Job stopped for Data Integration Server upgrade and will resume as a new job on the upgraded service.
```

The original job is replaced by a new job with a different instance name.

For more information about configuring mapping tasks for CDC continuous extraction, see the help for the appropriate connector in the online help.

CHAPTER 10

DV Processor

DV Processor is the Secure Agent service that runs data validation test cases. DV Processor compares two data sets and generates reports to verify the accuracy and completeness of data integration operations.

DV Processor processes each test case report and provides a comprehensive summary along with detailed views, including job details, sampling data, total records, match results, row count, and column matching status. It specifies the data type, precision, and scale for each column. You can also download reports for successful jobs.

You don't need to configure any properties for the DV Processor service as it works with default settings. The DV Processor service automatically uses the latest available TLS version for improved security. Always keep your Secure Agent updated to leverage the latest security protocols and performance improvements.

Benefits of using DV Processor

- Ensures only accurate data proceeds to analytics, reporting, or downstream processes.
- Detects issues early, minimizing errors.
- Automates repetitive validation tasks, reducing manual effort and human error.
- Provides comprehensive logs and validation evidence, assisting in regulatory compliance and audits.

In Administrator, you can configure the **purge-period** value that DV Processor must use. It defines the number of days to store the log data. By default, no purge period is set, so DV Processor keeps all the log data. To edit the purge period, enter a valid integer from 0 through 2147483647.

You can start and stop the DV Processor from the Administrator page.

CHAPTER 11

Elastic Server

The Elastic Server is the Secure Agent service that manages an advanced cluster and the jobs that run on the cluster.


You can configure service properties to specify details about the cloud platform that hosts the advanced cluster, such as the cluster operator role and the Secure Agent role in an AWS environment. You can also configure properties to specify access to parameter files, the level of detail that the Elastic Server writes to log files, and concurrency settings.

For more information about advanced clusters, see *Advanced Clusters*.

Elastic Server properties

To change the behavior of the Elastic Server, configure the Elastic Server properties in the **System Configuration Details** area when you edit a Secure Agent.

The following image shows the Elastic Server properties:



You can configure the following Elastic Server properties:

Type	Name	Description
PARAMFILE_CFG	parameterfile_access_flag	Indicates whether developers can download parameter files that are stored on the Secure Agent machine. Default is 'true.'
PARAMFILE_CFG	parameterfile_access_directory	List of directories on the Secure Agent machine that allow parameter file download. Developers can download parameter files from any of the specified directories or subdirectories. Default is '/$AGENT_HOME/apps/data/userparameters, /$AGENT_HOME/apps/Data_Integration_Server/data/userparameters.'
LOG4J_CFG	log4j_app_log_level	Level of detail that the Elastic Server writes to log files. Enter the logging level as a string, such as 'INFO.' As the logging level increases, the messages that the Elastic Server writes to log files include the messages in the prior logging levels. For example, if the logging level is INFO, the log contains FATAL, ERROR, WARNING, and INFO code messages. The following values are valid: - FATAL. Includes nonrecoverable system failures that cause the service to shut down or become unavailable. - ERROR. Includes connection failures, failures to save or retrieve metadata, and service errors. - WARNING. Includes recoverable system failures or warnings. - INFO. Includes system and service change messages. - TRACE. Logs user request failures. - DEBUG. Logs user request logs.
AWS_CFG	agent_role_external_id_key	External ID that the Secure Agent specifies when the agent attempts to assume the cluster operator role. Required if you configure an external ID in the trust relationship of the cluster operator role. This property takes effect only in an AWS environment.
AWS_CFG	privileged_role_arn_key	ARN of the cluster operator role. Required when you set up separate cluster operator and Secure Agent roles in an AWS environment. This property takes effect only in an AWS environment.
AWS_CFG	role_session_duration_secs_key	Session duration of the AWS AssumeRole API in seconds. By default, the session duration is 1800 seconds (30 minutes). Overrides the maximum CLI/API session duration that is configured for the cluster operator role. If the session duration configured for the Elastic Server is longer than session duration for the cluster operator role, the Secure Agent might fail to assume the cluster operator role. This property takes effect only in an AWS environment.

Type	Name	Description
AZURE_CFG	azure_agent_role_identity_client_id	Client ID of the managed identity `agent_identity`. Required when `agent_identity` is a user-assigned managed identity and the Secure Agent machine has at least one other managed identity. This property takes effect only in an Azure environment.
CONCURRENCY_CFG	allow_queuing	Indicates whether the Elastic Server queues Spark tasks. Default is true.
CONCURRENCY_CFG	max_concurrent_jobs	Maximum number of concurrent Spark tasks that the Elastic Server can process.
Tomcat JRE	INFA_MEMORY	Minimum and maximum heap size. For the Elastic Server, the default is `'-Xms256M -Xmx2048M'`, with 256MB minimum memory and 2048MB maximum memory. For more information, see *Data Integration Performance Tuning* and the following Knowledge Base article: FAQ: What are the guidelines and best practices to increase Java heap size and other memory attributes of the Informatica Cloud Secure Agent?

Elastic Server concurrency

The Elastic Server can process Spark tasks concurrently and queue additional Spark tasks. You can configure concurrency properties to enable or disable queuing and set the maximum number of concurrent Spark tasks.

The following Elastic Server properties define queuing and concurrency:

allow_queuing

Allows the Elastic Server to queue Spark tasks. The default value is set to true.

If this property is set to false, the Elastic Server processes all submitted Spark tasks concurrently. If you set the maximum number of concurrent tasks on the Elastic Server to a value that is higher than the default concurrency, increase the Java heap size accordingly. Otherwise, the Secure Agent process might crash.

The Elastic Server processes data preview and SQL ELT optimization jobs immediately without queuing them.

max_concurrent_jobs

Maximum number of concurrent Spark tasks that the Elastic Server can process. When the Elastic Server reaches the maximum number of concurrent Spark tasks, additional Spark tasks can be queued.

By default, the maximum number of concurrent Spark tasks depends on the cloud platform. The Elastic Server uses the following defaults for fully-managed and self-service clusters:

- 500 concurrent Spark tasks per 2 GB of Java heap space on AWS
- 375 concurrent Spark tasks per 2 GB of Java heap space on Google Cloud
- 250 concurrent Spark tasks per 2 GB of Java heap space on Microsoft Azure

A local cluster can run 15 concurrent Spark tasks, and the concurrency can't be changed.

Note that the Java heap size is set to 2 GB by default. If you set the maximum number of concurrent tasks to a value that is higher than the default, increase the Java heap size using the default ratios.

For example, if you want to run 500 concurrent Spark tasks on Microsoft Azure, increase the Java heap size to 4 GB. If the Java heap size remains at 2 GB, the Elastic Server will process a maximum of 250 concurrent Spark tasks and the remaining 250 Spark tasks can be queued.

The Elastic Server uses an upper bound of 1,000 Spark tasks per 2 GB of Java heap space. If you set the maximum number of concurrent tasks to a value that is higher than 1,000 without increasing the Java heap size above 2 GB, the Elastic Server fails to start.

The memory available for the Java heap size is set by the **INFA_MEMORY** property under the type **Tomcat JRE**. For more information about this property, see "Elastic Server properties" on page 46.

For more information about Secure Agent machine sizing, see *Data Integration Performance Tuning*.

CHAPTER 12

File Integration Service

Use the File Integration Service to transfer files between your organization and remote file servers.

The File Integration Service is a Secure Agent service that the agent uses to run advanced file transfer protocols such as AS2.

You must configure file servers before your organization can receive files from remote partners. Configure your organization's file server associated with the File Integration Service on the File Servers page in Administrator. Configuration includes properties such as file server details, encryption methods, and allowed file types.

To stop or start the File Integration Service, you stop or start the file server that uses the service.

For information about configuring file servers, see *File Servers*.

To configure the File Integration Service, you must be assigned the Admin role.

CHAPTER 13

GitRepoConnectApp

When your organization uses an on-premises source control repository, the GitRepoConnectApp service manages the communication between IDMC and the source control repository.

The Secure Agent uses the GitRepoConnectApp service when it creates the local copy of the remote source control repository on the Secure Agent machine. It also uses the service to get information about source control operations from the remote repository.

Local repository base directory

If your source control repository is on-premises, the Secure Agent creates a local copy of the repository branch that stores IDMC assets. You can configure the local repository location on the Secure Agent machine.

By default, the Secure Agent creates the local repository in the following directory:

```
<Secure Agent installation directory>/apps/GitRepoConnectApp/<base directory>/<client URL>/
<organization ID>/<branch>/<remote repository name>
```

In this file path, the base directory is controlled by the **git_local_repository_path** property of the GitRepoConnectApp service.

By default, **git_local_repository_path** is set to `../data/git_repository/`. Therefore, the Secure Agent creates the local Git repository in the following directory:

```
<Secure Agent installation directory>/apps/GitRepoConnectApp/data/git_repository/<client
URL>/<organization ID>/<branch>/<remote repository name>
```

You can change the base directory by editing the **git_local_repository_path** property. For example, if you set this property to `../MYREPO/PROD`, the Secure Agent creates the local Git repository in the following directory:

```
<Secure Agent installation directory>/apps/GitRepoConnectApp/MYREPO/PROD/<client URL>/
<organization ID>/<branch>/<remote repository name>
```

To specify a base directory that contains a backslash character (`\`), escape it with another backslash character.

Use the following guidelines when you set the **git_local_repository_path** property:

- If you omit the parent directory (..) when you set this property, the Secure Agent creates a subdirectory for the version of the GitRepoConnectApp service. The local copy of the repository is then stored in the following directory:


  ```
  <Secure Agent installation directory>/apps/GitRepoConnectApp/<GitRepoConnectApp version>/
  <base directory>/<client URL>/<organization ID>/<branch>/<remote repository name>
  ```

  In this case, the Secure Agent creates a new local repository directory each time the GitRepoConnectApp service is updated, which can consume large amounts of disk space on the Secure Agent machine.
- Do not configure this property in such a way that the local repository directory is shared by multiple agents. Each Secure Agent machine must have its own local copy of the repository.

GitRepoConnectApp properties

To change or optimize behavior of the GitRepoConnectApp service, configure the service properties. Configure the service properties in the **System Configuration Details** area when you edit a Secure Agent.

The following image shows the GitRepoConnectApp properties:



System Configuration Details

Service: GitRepoConnectApp

Type: All Types

Type	Name	Value
LOG4J	rootLogger	'INFO'
GIT_REPO_CONNECT_APP_CONF	host	'localhost'
GIT_REPO_CONNECT_APP_CONF	address	'127.0.0.1'
GIT_REPO_CONNECT_APP_CONF	git_local_repository_path	'../data/git_repository/'
GIT_REPO_CONNECT_APP_CONF	JVM_MIN_MEMORY	'32m'
GIT_REPO_CONNECT_APP_CONF	JVM_MAX_MEMORY	'256m'

You can configure the following service properties:

Type	Name	Description

GIT_REPO_CONNECT_APP_CONF	git_local_repository_path	Base directory for the local Git repository on the Secure Agent machine.
		The base directory is created in the following directory:
		`<Secure Agent installation directory>/apps/GitRepoConnectApp/`
		Default is `../data/git_repository/`. Therefore, the Secure Agent creates the local Git repository in the following directory:
		`<Secure Agent installation directory>/apps/GitRepoConnectApp/data/git_repository/<client URL>/<organization ID>/<branch>/<remote repository name>`

GIT_REPO_CONNECT_APP_CONF	JVM_MIN_MEMORY	Amount of memory allocated for the GitRepoConnectApp service when the service starts. Default is 32 MB.
GIT_REPO_CONNECT_APP_CONF	JVM_MAX_MEMORY	Maximum memory allocated for the GitRepoConnectApp service. Default is 256 MB.
Note: Do not change the values of other GitRepoConnectApp properties unless Informatica Global Customer Support instructs you to do so.		

CHAPTER 14

IDMC Data Gateway Service

The IDMC Data Gateway Service enables you to perform data exploration tasks in CLAIRE GPT. You can explore source data, preview a sample of the data set, see the SQL code used to fetch the sample data, and save the sample data in a CSV file for future reference. To perform data exploration tasks in CLAIRE GPT, ensure that the IDMC Data Gateway Service is up and running on your Secure Agent.

You can optimize the performance of the IDMC Data Gateway Service by configuring the service properties.

IDMC Data Gateway Service properties

To change or optimize the behavior of the IDMC Data Gateway Service, configure its properties in the **System Configuration Details** section when you edit a Secure Agent.

The following image shows the IDMC Data Gateway Service properties:



You can configure the following system properties of the IDMC Data Gateway Service in the **System Configuration Details** section:

Type	Name	Description	Sample Value	Default Value
APP_CFG	idmc_dgs_agentMaxRetryAttempts	-	3	5
APP_CFG	idmc_dgs_agentShutdownWaitTimeMillis	-	30000	60000

Type	Name	Description	Sample Value	Default Value
APP_CFG	idmc_dgs_connectionPoolMaxSize	The maximum number of data source connections cached for a Secure Agent.	Minimum is 10. Maximum is 1000.	100
APP_CFG	idmc_dgs_connectionPoolCacheExpiryDuration	The maximum duration for which the connection with a data source is kept open when it is unused. **Note:** The value of the parameter should be in minutes.	Minimum is 10. Maximum is 120.	30 minutes
APP_CFG	idmc_dgs_minHeapSize	Option to modify the minimum heap size of JVM. **Note:** The value of the parameter should be within single quotes.	'128m'	'128m'
APP_CFG	idmc_dgs_maxHeapSize	Option to modify the maximum heap size of JVM. **Note:** The value of the parameter should be within single quotes.	'512m'	'1024m'
APP_CFG	idmc_dgs_JVM_ARGS	Option to add debug parameters or modify the JVM memory configuration parameters.	-Xms32m -Xmx512m	-XX:+UseG1GC
APP_CFG	idmc_dgs_queryExecutionTimeout	The maximum duration for which a database query is run on a data source. **Note:** The value of the parameter should be in seconds.	Minimum is 1 There is no maximum value.	60 seconds

Type	Name	Description	Sample Value	Default Value
APP_LOG4J	name	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'AppLogPropertiesConfig'	'AppLogPropertiesConfig'
APP_LOG4J	rootLogger_level	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'warn'	'info'
APP_LOG4J	rootLogger_appenderRefs	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'applog'	'applog'
APP_LOG4J	rootLogger_appenderRefs_applog_ref	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'LOGFILE'	'LOGFILE'
APP_LOG4J	appenders	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'applog'	'applog'
APP_LOG4J	appender_applog_type	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'RollingFile'	'RollingFile'

Type	Name	Description	Sample Value	Default Value
APP_LOG4J	appender_applog_name	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'LOGFILE'	'LOGFILE'
APP_LOG4J	appender_applog_filePattern	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'%d{MM-dd-yy-HH-mm-ss}-%i'	'%d{MM-dd-yy-HH-mm-ss}-%i'
APP_LOG4J	appender_applog_layout_type	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'PatternLayout'	'PatternLayout'
APP_LOG4J	appender_applog_layout_pattern	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'%d %d{z} %p [%c] - %m%n'	'%d %d{z} %p [%c] - %m%n'
APP_LOG4J	appender_applog_policies_type	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'Policies'	'Policies'
APP_LOG4J	appender_applog_policies_size_type	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'SizeBasedTriggeringPolicy'	'SizeBasedTriggeringPolicy'

Type	Name	Description	Sample Value	Default Value
APP_LOG4J	appender_applog_policies_size_size	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'5MB'	'10MB'
APP_LOG4J	appender_applog_strategy_type	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'DefaultRolloverStrategy'	'DefaultRolloverStrategy'
APP_LOG4J	appender_applog_strategy_max	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'5'	'5'
APP_LOGBACK	logback_log_file_pattern	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'{yyyy-ww}'	'{yyyy-ww}'
APP_LOGBACK	logback_log_max_file_size	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'5MB'	'10MB'

Type	Name	Description	Sample Value	Default Value
APP_LOGBACK	logback_log_max_history	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'20'	'10'
APP_LOGBACK	logback_root_level	Common property for all Secure Agent applications. **Note:** The value of the parameter should be within single quotes.	'DEBUG'	'INFO'

Note: APP_CFG refers to application configuration properties, APP_LOG4J refers to logging related application properties, and APP_LOGBACK refers to log file rotation related application properties.

CHAPTER 15

Mass Ingestion (Files)

To change or optimize the behavior of File Ingestion and Replication that your Secure Agent group uses, configure Mass Ingestion agent service properties for your runtime environment in Administrator.

You can configure the following properties:

Type	Name	Description
AGENT_RUNTIME_SETTINGS	file-listener-snapshot-dir	A directory where the snapshots of a new file listener components are added. You can add the following directory paths: - A path relative to the `MassIngestionRuntime` directory. For example, `../data/monitor`. - The absolute path. For example, `<Secure agent installation directory>/apps/MassIngestionRuntime/data/monitor` where *Secure agent installation directory* is the name of the directory where the secure agent is installed. **Note:** Use the snapshot directory shared with all agents when multiple Secure Agents are present in a group.
AGENT_RUNTIME_SETTINGS	mi-task-workspace-dir	A directory in the agent that file ingestion and replication tasks use as an intermediate staging area when transferring files to a target. The directory is a custom location in the agent. The path can be a shared location, mounted location, or a location apart from the default location in the agent.
AGENT_RUNTIME_SETTINGS	mi-task-project-dir	A directory where the file ingestion and replication task stores the project files. The directory is a custom location in the agent. The path can be a shared location, mounted location, or a location apart from the default location in the agent.
AGENT_RUNTIME_SETTINGS	mi-task-logs-dir	A directory where the file ingestion and replication task stores the task logs files. The directory is a custom location in the agent. The path can be a shared location, mounted location, or a location apart from the default location in the agent.

Type	Name	Description
AGENT_RUNTIME_SETTINGS	mi-task-quarantine-dir	A directory where the file ingestion and replication task stores the infected files detected when you run a virus scan. The directory is a custom location in the agent. The path can be a shared location, mounted location, or a location apart from the default location in the agent. For example, userdata\quarantine **Note:** To automatically clean up the quarantine directory, set the agent property for the quarantine location to a system temporary files location such as `/tmp/informatica/fmi/quarantine`.
AGENT_RUNTIME_SETTINGS	agent-dedup-repository	The information about skipped duplicate files is saved in IDMC. To save the skipped duplicate files information in the Secure Agent, set the property to `true`. Default is `false`. For more information about saving the skipped duplicate information, see the *File Ingestion and Replication* guide.
AGENT_RUNTIME_SETTINGS	mi-dedup-snapshot-dir	Enter the path to store the information about skipped duplicate files in the Secure Agent. Applies only when the **agent-dedup-repository** property is set to `true`.
AGENT_RUNTIME_SETTINGS	file-listener-max-pool-size	The maximum number of threads to execute the file listener. Default is 20.
AGENT_RUNTIME_SETTINGS	file-listener-core-pool-size	The total number of threads. Default is 20.
AGENT_RUNTIME_SETTINGS	fmi-task-max-pool-size	The maximum number of threads to execute the file ingestion and replication task. Default is 50.
AGENT_RUNTIME_SETTINGS	fmi-task-core-pool-size	The initial or minimum number of threads. Default is 20.
AGENT_RUNTIME_SETTINGS	ftp-receive-socket-buffer-size	The buffer size for FTP inbound packets. Default is 16 bytes.
AGENT_RUNTIME_SETTINGS	ftp-send-socket-buffer-size	The buffer size for FTP outbound packets. Default is 16 bytes.
AGENT_RUNTIME_SETTINGS	http-client-timeout	The timeout duration in seconds for Agent requests to IDMC. Default is 30 seconds.

Type	Name	Description
PGP_SETTINGS	public-keyring-path	The directory to store the public key ring. You can add the following directory paths: - A path relative to the directory where Data Ingestion and Replication is installed. For example, `../data/pubring.pkr` where *pubring.pkr* is the name of the file where you store the public key ring. - The absolute path. For example, `<Secure agent installation directory>/apps/MassIngestionRuntime/data/pubring.pkr` where *pubring.pkr* is the name of the file where you store the public key ring and *Secure agent installation directory* is the name of the directory where the agent is installed.
PGP_SETTINGS	secret-keyring-path	The directory to store the secret key ring. You can add the following directory paths: - A path relative to the directory where Data Ingestion and Replication is installed. For example, `../data/secring.pkr` where *secring.pkr* is the name of the file where you store the secret key ring. - The absolute path. For example, `<Secure agent installation directory>/apps/MassIngestionRuntime/data/secring.pkr` where *secring.pkr* is the name of the file where you store the secret key ring and *Secure Agent installation directory* is the name of the directory where the agent is installed.
JVM_SETTINGS	app-heap-size	The minimum and maximum heap sizes of the File Ingestion and Replication application. Default is -Xms256m -Xmx2048m.
JVM_SETTINGS	lcm-heap-size	The minimum and maximum heap sizes of life-cycle management scripts. Default is -Xms32m -Xmx128m.

You can configure the following properties in the **Custom Configuration Details** area when you edit a Secure Agent:

Type	Name	Description
AGENT_RUNTIME_SETTINGS	ComplexFileDisableWriteChecksum	Set the value to **True** to ignore the `crc` file. The job runs successfully with Hadoop Files V2 as source and Snowflake Cloud Data Warehouse V2 as the target.

Guidelines to specify the folder path

A folder path can be a shared location, mounted location, or a location apart from the default location in the Secure Agent.

The following table lists the use of slashes around the source folder path:

Source	Folder Path
Windows	<folder path> For example, `C:\temp`
Linux	/<folder path>/ For example, `/root/path`
Windows shared location	<folder path> with additional slashes (\) For example, the path `\\INV12B2B01\Shared\path`, is specified as `\\\\INV12B2B01\\Shared\\path`

Network security

MassIngestionRuntime uses internal service ports. These ports bind to the local host (127.0.0.1), so only processes running on the same machine as the Secure Agent can connect to them.

CHAPTER 16

Metadata Foundation Application


The Metadata Foundation Application service enables you to extract metadata from the configured source systems in your organization, and uploads the extracted metadata to Metadata Command Center through the Secure Agent

You can optimize the performance of the Metadata Foundation Application service by configuring some of its service properties.

Metadata Foundation Application properties

To change or optimize the behavior of the Metadata Foundation Application service, configure its properties in the **System Configuration Details** section when you edit a Secure Agent.

The following image shows some of the Metadata Foundation Application service properties:



You can configure the following Metadata Foundation Application service properties:

Type	Name	Description	Sample Value	Default Value
APP_CFG	mfa_maxParallelTasks	Number of concurrent running tasks in the Secure Agent.	5	4
APP_CFG	mfa_agentMaxRetryAttempts	-	3	5
APP_CFG	mfa_agentInitialBackoffInterval	-	500	100
APP_CFG	mfa_agentMaxBackoffInterval	-	20000	35000
APP_CFG	mfa_agentShutdownWaitTimeMillis	-	30000	60000
APP_CFG	mfa_JVM_ARGS	Option to add debug parameters or modify the JVM memory configuration parameters.	agentlib:jdwp=transport=dt_socket,address=8084,server=y,suspend=y	-
PLUGIN_CFG	plugin_JVM_ARGS	Option to add debug parameters or modify the JVM memory configuration parameters.	agentlib:jdwp=transport=dt_socket,address=8083,server=y,suspend=y	-
TRANSFER_SVC_CFG	transfer_svc_JVM_ARGS	Option to add debug parameters or modify the JVM memory configuration parameters.	agentlib:jdwp=transport=dt_socket,address=8085,server=y,suspend=y	-
TRANSFER_SVC_CFG	transfer_svc_batchSize	Number of content files that can be processed in a batch. Use this option to optimize the generation of CSV files that are uploaded using the upload service.	4	1

Type	Name	Description	Sample Value	Default Value
TRANSFER_SVC_CFG	transfer_svc_stagingMaxRetry	Number of retries in case of failure while staging the content.	5	3
TRANSFER_SVC_CFG	transfer_svc_parallelTaskExecutorsSize	Number of concurrent running tasks.	5	4
TRANSFER_SVC_CFG	transfer_svc_contentBatchExecutorsSize	Number of concurrent content uploads using the upload service.	5	4
TRANSFER_SVC_CFG	transfer_svc_stagingBatchExecutorsSize	Number of concurrent content staging tasks.	5	4
TRANSFER_SVC_CFG	transfer_svc_contentWorkersBean	Transfer service beans that do the staging, ingestion and log transfer. To disable staging, specify only ingest and log transfer.	ingestion,log	ingestion,staging,log
TRANSFER_SVC_CFG	transfer_svc_ingestionMaxRetry	Number of retries for upload and bulk ingestion in case of failure.	5	3
TRANSFER_SVC_CFG	transfer_svc_contentMaxRetentionTimeInMin	Option to retain or delete the metadata extraction results after upload. The default behavior is to delete the results.	600	0

Type	Name	Description	Sample Value	Default Value
TRANSFER_SVC_CFG	transfer_svc_postDriverCompletionMaxWaitTimeInSec	Number of seconds after which long running or unresponsive ingestion tasks will be terminated. The default behavior is to not terminate any long running or unresponsive ingestion task.	10	-1
APP_LOG4J	name	Common property for all Secure Agent applications.	AppLogPropertiesConfig	AppLogPropertiesConfig Xmx2048m
APP_LOG4J	rootLogger_level	Common property for all Secure Agent applications.	warn	info
APP_LOG4J	rootLogger_appenderRefs	Common property for all Secure Agent applications.	applog	applog
APP_LOG4J	rootLogger_appenderRefs_applog_ref	Common property for all Secure Agent applications.	LOGFILE	LOGFILE
APP_LOG4J	appenders	Common property for all Secure Agent applications.	applog	applog
APP_LOG4J	appender_applog_type	Common property for all Secure Agent applications.	RollingFile	RollingFile
APP_LOG4J	appender_applog_name	Common property for all Secure Agent applications.	LOGFILE	LOGFILE
APP_LOG4J	appender_applog_filePattern	Common property for all Secure Agent applications.	%d{MM-dd-yy-HH-mm-ss}-%i	%d{MM-dd-yy-HH-mm-ss}-%i

Type	Name	Description	Sample Value	Default Value
APP_LOG4J	appender_applog_layout_type	Common property for all Secure Agent applications.	PatternLayout	PatternLayout
APP_LOG4J	appender_applog_layout_pattern	Common property for all Secure Agent applications.	%d %d{z} %p [%c] - %m%n	%d %d{z} %p [%c] - %m%n
APP_LOG4J	appender_applog_policies_type	Common property for all Secure Agent applications.	Policies	Policies
APP_LOG4J	appender_applog_policies_size_type	Common property for all Secure Agent applications.	SizeBasedTriggeringPolicy	SizeBasedTriggeringPolicy
APP_LOG4J	appender_applog_policies_size_size	Common property for all Secure Agent applications.	5MB	10MB
APP_LOG4J	appender_applog_strategy_type	Common property for all Secure Agent applications.	DefaultRolloverStrategy	DefaultRolloverStrategy
APP_LOG4J	appender_applog_strategy_max	Common property for all Secure Agent applications.	5	5
APP_LOGBACK	logback_log_file_pattern	Common property for all Secure Agent applications.	{yyyy-ww}	{yyyy-ww}
APP_LOGBACK	logback_log_max_file_size	Common property for all Secure Agent applications.	5MB	10MB
APP_LOGBACK	logback_log_max_history	Common property for all Secure Agent applications.	20	10
APP_LOGBACK	logback_root_level	Common property for all Secure Agent applications.	DEBUG	INFO

CHAPTER 17

Metadata Platform Service

The Metadata Platform Service enables you to perform profiling activities for the jobs that you run in Metadata Command Center. Profiling fails if there is no active Metadata Platform Service present in the runtime environment of Metadata Command Center.

You can optimize the performance of the Metadata Platform Service by configuring some of its service properties.

Metadata Platform Service properties

To change or optimize the behavior of the Metadata Platform Service, configure its properties in the **System Configuration Details** section when you edit a Secure Agent.

The following image shows some of the Metadata Platform Service properties:

System Configuration Details

Service: Metadata Platform Service

Type: All Types

Type	Name	Value
APP_CFG	mps_maxParallelTasks	4
APP_CFG	mps_agentMaxRetryAttempts	5
APP_CFG	mps_agentInitialBackoffInterval	100
APP_CFG	mps_agentMaxBackoffInterval	35000
APP_CFG	mps_agentShutdownWaitTimeMillis	60000
APP_CFG	mps_profileResultRetention	false
APP_CFG	mps_maxDeploymentBatchSize	100

You can configure the following Metadata Platform Service properties:

Type	Name	Description	Sample Value	Default Value
APP_CFG	mps_maxParallelTasks	The maximum number of batch profiling sub tasks that can run at the same time.	3	4
APP_CFG	mps_agentMaxRetryAttempts	-	3	5
APP_CFG	mps_agentInitialBackoffInterval	-	500	100
APP_CFG	mps_agentMaxBackoffInterval	-	20000	35000
APP_CFG	mps_agentShutdownWaitTimeMillis	-	30000	60000
APP_CFG	mps_profileResultRetention	-	false	false
APP_CFG	mps_maxDeploymentBatchSize	The maximum number of objects that a batch profiling sub-task can contain.	50	100 **Note:** The value of the deployment batch size parameter should be 1 or greater than 1.
APP_CFG	mps_metadataComputeProfile	Defines the load type.	-	'Small:core.DataElement=1000;Medium:core.DataElement-10000;'
APP_CFG	mps_previewFileRetentionInDays	The maximum number of days when files associated with a catalog source job for the profiling capability are stored. For example, Data Preview results.	5	7
APP_CFG	mps_JVM_ARGS	Option to add debug parameters or modify the JVM memory configuration parameters.	-Xms32m -Xmx512m	-

Type	Name	Description	Sample Value	Default Value
TRANSFER_SVC_CFG	transfer_svc_batchSize	Number of content files that can be processed in a batch. Use this option to optimize the generation of CSV files that are uploaded using the upload service.	4	1
TRANSFER_SVC_CFG	transfer_svc_stagingMaxRetry	Number of retries in case of failure while staging the content.	5	3
TRANSFER_SVC_CFG	transfer_svc_parallelTaskExecutorsSize	Number of concurrent running tasks.	5	4
TRANSFER_SVC_CFG	transfer_svc_contentBatchExecutorsSize	Number of concurrent content uploads using the upload service.	5	4
TRANSFER_SVC_CFG	transfer_svc_stagingBatchExecutorsSize	Number of concurrent content staging tasks.	5	4
TRANSFER_SVC_CFG	transfer_svc_contentWorkersBean	Transfer service beans that do the staging, ingestion and log transfer. To disable staging, specify only ingest and log transfer.	ingestion,log	ingestion,staging,log
TRANSFER_SVC_CFG	transfer_svc_ingestionMaxRetry	Number of retries for upload and bulk ingestion in case of failure.	5	3

Type	Name	Description	Sample Value	Default Value
TRANSFER_SVC_CFG	transfer_svc_contentMaxRetentionTimeInMin	Option to retain or delete the metadata extraction results after upload. The default behavior is to delete the results.	600	0
TRANSFER_SVC_CFG	transfer_svc_postDriverCompletionMaxWaitTimeInSec	Number of seconds after which long running or unresponsive ingestion tasks will be terminated. The default behavior is to not terminate any long running or unresponsive ingestion task.	10	-1
APP_LOG4J	name	Common property for all Secure Agent applications.	AppLogPropertiesConfig	AppLogPropertiesConfig
APP_LOG4J	rootLogger_level	Common property for all Secure Agent applications.	warn	info
APP_LOG4J	rootLogger_appenderRefs	Common property for all Secure Agent applications.	applog	applog
APP_LOG4J	rootLogger_appenderRefs_applog_ref	Common property for all Secure Agent applications.	LOGFILE	LOGFILE
APP_LOG4J	appenders	Common property for all Secure Agent applications.	applog	applog
APP_LOG4J	appender_applog_type	Common property for all Secure Agent applications.	RollingFile	RollingFile

Type	Name	Description	Sample Value	Default Value
APP_LOG4J	appender_applog_name	Common property for all Secure Agent applications.	LOGFILE	LOGFILE
APP_LOG4J	appender_applog_filePattern	Common property for all Secure Agent applications.	%d{MM-dd-yy-HH-mm-ss}-%i	%d{MM-dd-yy-HH-mm-ss}-%i
APP_LOG4J	appender_applog_layout_type	Common property for all Secure Agent applications.	PatternLayout	PatternLayout
APP_LOG4J	appender_applog_layout_pattern	Common property for all Secure Agent applications.	%d %d{z} %p [%c] - %m%n	%d %d{z} %p [%c] - %m%n
APP_LOG4J	appender_applog_policies_type	Common property for all Secure Agent applications.	Policies	Policies
APP_LOG4J	appender_applog_policies_size_type	Common property for all Secure Agent applications.	SizeBasedTriggeringPolicy	SizeBasedTriggeringPolicy
APP_LOG4J	appender_applog_policies_size_size	Common property for all Secure Agent applications.	5MB	10MB
APP_LOG4J	appender_applog_strategy_type	Common property for all Secure Agent applications.	DefaultRolloverStrategy	DefaultRolloverStrategy
APP_LOG4J	appender_applog_strategy_max	Common property for all Secure Agent applications.	5	5
APP_LOGBACK	logback_log_file_pattern	Common property for all Secure Agent applications.	{yyyy-ww}	{yyyy-ww}
APP_LOGBACK	logback_log_max_file_size	Common property for all Secure Agent applications.	5MB	10MB

Type	Name	Description	Sample Value	Default Value
APP_LOGBACK	logback_log_max_history	Common property for all Secure Agent applications.	20	10
APP_LOGBACK	logback_root_level	Common property for all Secure Agent applications.	DEBUG	INFO

CHAPTER 18

Process Server

Process Server is the Secure Agent service that executes Application Integration processes, connectors, and connections.

When you deploy Application Integration assets to the Secure Agent, you deploy them to Process Server. When you run an asset, Process Server executes it.

The PostgreSQL database comes with the Process Server service of the Secure Agent and stores the metadata that Process Server collects and generates.

Find the PostgreSQL directory in the following location on your system:

```
<Secure Agent installation directory>\apps\process-engine\data\PostGreSql
```

Informatica includes a PostgreSQL database with the Process Server package. However, you can also connect a different PostgreSQL database version to the Process Server. You can also migrate the existing cluster database dump to the PostgreSQL database. For more information, see *Configure* in the How-To library section on the documentation portal.

Process Server properties

To change or optimize the behavior of Process Server, configure Process Server properties. You can configure the server, Secure Agent group, Java Virtual Machine, connector, database, and logging properties.

The following image shows some Process Server properties:

You can configure the following server properties:

Name	Communication Method	Description
host-name	Secure Agent Channel	The host name of the Process Engine server.
shutdown-port	Secure Agent Channel	Process Server Tomcat shutdown port.
key-alias	HTTPS	The identifier of the keystore record that contains security keys for HTTPS communication.

Name	Communication Method	Description
key-store	HTTPS	The path and file name of the key store file that Application Integration uses for HTTPS communication. When you install the Secure Agent, you can find the key store in the following default location: <Secure Agent installation directory>/apps/process-engine/conf/ae.keystore You can also enter a relative path. For example, if the current working directory is the Secure Agent installation directory, enter the following value to point to the ae.keystore file: ../conf/ae.keystore **Note:** The file path can contain only forward slashes (/).
key-store-password	HTTPS	The key store password. Default is **password**.
trust-store	HTTPS	The path and file name of the trust store file that Application Integration uses for HTTPS communication. When you install the Secure Agent, you can find the trust store in the default location: <Secure Agent installation directory>/apps/process-engine/conf/ae.cacerts You can also enter a relative path. For example, if the current working directory is the Secure Agent installation directory, enter the following value to point to the ae.cacerts file: ../conf/ae.cacerts **Note:** The file path can contain only forward slashes (/). If you want to import public certificates for service endpoint authentication, place them in the following location: <Secure Agent installation directory>/apps/process-engine/conf/certs
trust-store-password	HTTPS	The trust store password. Default is **changeit**. You can change the password.
ldap-enabled-realm	HTTP/HTTPS	Set this property to true if you want to use an LDAP provider for authentication. Use the LDAP provider as a centralized form of authentication when you have clustered Secure Agents.
ldap-properties	HTTP/HTTPS	The LDAP properties that you need to configure. Edit the existing properties to suit your LDAP provider. **Note:** Your LDAP password does not appear on screen. The value of $(pe.ldap.password) is taken from the PE_LDAP_PASSWORD environment variable.

Name	Communication Method	Description
ssl-enabled-protocols	HTTPS	The TLS protocol to use. TLSv1.2 is the default protocol. You can add version TLSv1.3 for a faster TLS handshake and to use secure cipher methods. The TLSv1.3 protocol supports the following additional cipher suites for improved security: - TLS_AES_128_GCM_SHA256 - TLS_AES_256_GCM_SHA384 For more information about supported ciphers, see the Change in Cipher Suites for IDMC Knowledge article. **Note:** The TLSv1.0 and TLSv1.1 protocols are no longer supported.
ephemeral-DH-key-size	HTTPS	The key length of the secure algorithm. Default is **2048**. Change this value only if you face compatibility issues.
use-secure-ciphers-only	HTTPS	Limits the set of ciphers used during a call to the endpoint to secure ciphers only. Default is **true**. Change this value to false only if you face compatibility issues.
fips-enabled	HTTPS	Set this property to `true` to enable the Federal Information Processing Standard (FIPS) mode on a Secure Agent. When you enable the FIPS mode, Windows uses the FIPS validated cryptographic algorithms. Default is **false**.

You can configure the following Secure Agent group ('cluster' on the UI) properties:

Name	Communication Method	Description
name	HTTP/HTTPS	The name of the Secure Agent group.
primary-node	HTTP/HTTPS	Set this property to `true` if you want the Secure Agent to be the master agent. When you select a master agent, you create a Secure Agent cluster. In a cluster, all Secure Agents share the postgreSQL database of the master Secure Agent.
load-balance-url	HTTP/HTTPS	The load balancer URL that you can use to invoke the process deployed to the Secure Agent. Applicable if you have a load balancer.

You can configure the following Java Virtual Machine properties:

Name	Communication Method	Description
min-heap	Secure Agent Channel	The minimum heap memory that Process Server allocates to the Tomcat JVM.
max-heap	Secure Agent Channel	The maximum heap memory that Process Server allocates to the Tomcat JVM.
additional-properties	Secure Agent Channel	A custom system property that you can add to the Tomcat JVM set. For example, you can set the custom property –Dsun.net.inetaddr.ttl=60

You can configure the following connector properties:

Name	Communication Method	Description
http-port	HTTP	The HTTP port to which the Secure Agent sends data. The default port is 7080. You can leave this property empty to disable non-secure connections. After this configuration, when you invoke an Application Integration process using the HTTP endpoint URL, an error occurs. For more information about the construction of REST and SOAP endpoint URLs, see the Application Integration help.
http-maxThreads	HTTP	The maximum number of connections that Process Server creates with Application Integration over HTTP.
http-connectionTimeout	HTTP	The maximum time, in milliseconds, that Process Server waits for an HTTP connection to reply.
https-port	HTTPS	The HTTPS port to which the Secure Agent sends data. You must enter a value in this property for the Secure Agent to successfully establish a connection. The default port is 7443. For more information about the construction of REST and SOAP endpoint URLs, see the Application Integration help.
https-maxThreads	HTTPS	The maximum number of connections that Process Server creates with Application Integration over HTTPS.
https-connectionTimeout	HTTPS	The maximum time, in milliseconds, that Process Server waits for an HTTPS connection to reply.
secure-channel maxThreads	Secure Agent Channel	The maximum number of connections that Process Server creates with Application Integration.
secure-channel-connectionTimeout	Secure Agent Channel	The maximum time, in milliseconds, that Process Server waits for a connection to reply.

You can configure the following database properties:

Name	Communication Method	Description
`type`	Secure Agent Channel	The database type that Process Server runs on. **Important:** Do not change this setting. The Application Integration Secure Agent does not support other databases.
`driver`	Secure Agent Channel	The database driver that Process Server runs on. **Important:** Do not change this setting. The Informatica Cloud Secure Agent does not support other databases.
`URL`	Secure Agent Channel	URL at which Process Server accesses the database. **Important:** Do not change this setting. The Informatica Cloud Secure Agent does not support other databases.
`maxActive`	Secure Agent Channel	The maximum number of active connections allocated to the Process Server database at the same time.
`maxIdle`	Secure Agent Channel	The maximum number of connections that can remain idle at a time in the Process Server database. Process Server releases connections if the number of idle connections crosses this number.
`maxWait`	Secure Agent Channel	The maximum time that the Process Server database waits for a connection if none are available.
`connection-properties`	Secure Agent Channel	Key-value pairs of database connection properties. Some keys are available by default. Do not delete the default keys. However, you can change the values of these keys. You can add other key-value pairs. For example, you can add the following key-value pair: key: `autoReconnect` value: `true`

If you created a separate logging data source and want to redirect the process logging from the existing database to the data source, configure the following properties:

Name	Communication Method	Description
`logUrl`	Secure Agent Channel	The URL at which the Process Server accesses the logging data source to redirect the process logging data. Default is `jdbc:postgresql://localhost:5432/activevos`.
`logMaxActive`	Secure Agent Channel	The logs for the maximum number of active connections allocated to the Process Server database at the same time. Default is **50**.
`logMaxIdle`	Secure Agent Channel	The logs for the maximum number of connections that remained idle at a time in the Process Server database. Default is **5**.

Name	Communication Method	Description
logMaxWait	Secure Agent Channel	The logs for the maximum time that the Process Server database waited for a connection if none was available. Default is **30000**.

logConnection-properties	Secure Agent Channel	The key-value pairs of the logging database connection properties. The following keys are available by default:
		`- key: timeBetweenEvictionRunsMillis`
		`  value: 300000`
		`- key: testOnBorrow`
		`  value: true`
		`- key: testWhileIdle`
		`  value: true`
		Do not delete the default keys. However, you can change the values of these keys.
		You can add other key-value pairs. For example, you can add the following key-value pair:
		`- key: autoReconnect`
		`  value: true`

For more information about configuring a separate logging data source on a Secure Agent, see "Configuring a separate logging data source " on page 82.

You can configure the following logging properties:

Name	Communication Method	Description
org_apache_catalina_core_ContainerBase_Catalina_localhost_level	Secure Agent Channel	The level of logging in the `localhost.log` file when you host Tomcat on a virtual machine. Default is **INFO**.
org_apache_catalina_core_ContainerBase_Catalina_localhost_manager_level	Secure Agent Channel	The level of logging in the `manager.log` file when you host Tomcat on a virtual machine. Default is **INFO**.
org_apache_catalina_core_ContainerBase_Catalina_localhost_host-manager_level	Secure Agent Channel	The level of logging in the `host-manager.log` file when you host Tomcat on a virtual machine. Default is **INFO**.
log4j2_root_level	Secure Agent Channel	The logging level of the ROOT logger. Default is **INFO**.

additional-logging	Secure Agent Channel	The name-level of logging pair for a specific class.
		Default is:
		`- name: org.apache.camel.component.file.remote.SftpOperations`
		`  level: ERROR`

You can configure the following custom properties in the **Custom Configuration Details** section:

Name	Type	Description
`https-clientAuth`	connectors	Set this property to `true` to enable mutual authentication after upgrading the Process Server. For more information about configuring this property, see " Enable mutual authentication for Process Server" on page 101.
`replication_upgrade`	db	Set this property to `true` to enable the replication upgrade of the PostgreSQL database for a Secure Agent. For more information about configuring this property, see "Upgrading the PostgreSQL database using the replication technique" on page 97.
`ssl-implementation`	server	Set this property to override the class name of the ssl implementation to be used in Tomcat. Default is `org.apach.tomcat.util.net.jsse.JSSEImplementation`.
`useDynamicDispatchService`	server	If Process Server runs on a Secure Agent, set this property to `true` to enable the dispatch service to dynamically create dispatch queue configurations and avoid deadlocks. A dynamic dispatch queue manages and limits the number of requests Process Server can handle.
`server.metadata_complete`	server	Controls the `metadata-complete` attribute in `web.xml`. Set to `true` to disable annotation scanning and enforce explicit servlet configurations for CIS Benchmark 10.18 compliance. Restart the Process Server for changes to take effect. Default is `false`.

After adding or editing a custom property, you must restart the Process Server for the change to take effect.

For more information about adding a custom property, see Chapter 23, "Configuring Secure Agent service properties" on page 113.

Default connection database properties

The following table describes the default keys that are available for the `connection-properties` database property:

Key	Description
`timeBetweenEvictionRuns`	The number of milliseconds that Process Server waits in-between runs of the idle object evictor thread.
`testOnBorrow value`	Process Server validates objects before borrowing objects from the pool. If Process Server cannot validate the object, it drops the object from the pool. Then, Process Server tries to borrow another object.
`testWhileIdle`	Process Server validates objects by the idle object evictor (if one exists). If Process Server cannot validate the object, it drops the object from the pool.
`validationQuery value`	The SQL query that validates connections from this pool before returning them to the caller. If you specify this property, the query must be an SQL SELECT statement that returns at least one row.

Logging levels

The following table describes the levels that you can configure for Process Server **logging** properties:

Level	Description
SEVERE	Logs errors.
WARNING	Logs potentially harmful situations.
INFO	Logs informational events that show the high-level progress of the application.
CONFIG	Logs informational events in more detail than at the INFO level.
FINE	Logs fine-grained informational events that you can use to debug an application.
FINER	Logs fine-grained informational events in more detail than at the FINE level.
FINEST	Logs all events.

Configuring a separate logging data source

The logs are stored in the activevos database, by default. To reduce the load on the existing database, you can create a separate logging data source and redirect process logging.

To create a separate logging data source in a dedicated schema on a Secure Agent, perform the following steps:

1. Create a separate database and a schema within the database.
2. To use a separate schema, execute the following Data Definition Language (DDL) statement to create a structure for the AeProcessLogData table and the index within the schema:

```
CREATE TABLE AeProcessLogData
(
   ProcessId BIGINT NOT NULL,
   SequenceId BIGINT NOT NULL,
   PlanId BIGINT NOT NULL,
   TenantContextId VARCHAR(32),
   LocationPath TEXT NOT NULL,
   InstanceLocationId INT NOT NULL,
   DefLocationId INT NOT NULL,
   CorrelationId INT NOT NULL,
   EventId INT NOT NULL,
   SessionId INT NOT NULL,
   SourceId INT NOT NULL,
   FaultName VARCHAR(255),
   AncillaryStr TEXT,
   AncillaryInt INT,
   EventTime BIGINT NOT NULL,
   DataDocument TEXT,
   PRIMARY KEY (ProcessId, SequenceId)
);
CREATE INDEX AeLogDataPidInsId ON AeProcessLogData(PlanId, ProcessId,
InstanceLocationId);
```

3. Create a user, for example, logdbuser, with the following privileges:

```
CREATE ROLE username WITH
NOLOGIN
NOSUPERUSER
NOCREATEDB
NOCREATEROLE
```

```
INHERIT
NOREPLICATION
NOBYPASSRLS
CONNECTION LIMIT -1
PASSWORD 'xxxxxx';
GRANT pg_read_all_data, pg_write_all_data TO username;
```

4. Create a system environment variable with the user name and password for the log database user role you created as follows:

   `PE_DB_LOG_USERNAME`

   `PE_DB_LOG_PASSWORD`

5. Configure the following logging data source properties in the Process Server properties:
   - logUrl
   - logMaxActive
   - logMaxIdle
   - logMaxWait
   - logConnection-properties

   For more information about configuring the logging data source properties, see "Process Server properties" on page 75.

6. Restart the Secure Agent for the changes to take effect.

Process Server sizing recommendations

Configure the Process Server service of the Secure Agent according to your workload.

Use the following sizing recommendations to optimize resources:


Recommendation	Small	Medium	Large
Process Count	75	175	350
Resource Cache (MB)	75	175	350
Work Manager Thread Pool Min	50	100	150
Work Manager Thread Pool Max	250	500	750
JVM Min Heap (MB)	Default	768	1024
JVM Max Heap (MB)	Default	Default	4096

The default JVM Min Heap is 512 MB, and the default JVM Max Heap is 1536 MB.

For example, to configure the Process Count, Resources Cache, Work Manager Thread Pool Min, and Work Manager Thread Pool Max related properties, perform the following steps:

1. In Application Integration Console, click **Server Configuration**.
2. On the **Server Configuration** page, select a Secure Agent.
3. Click the **Server Settings** tab.

4. Update the Process Count, Resource Cache, Work Manager Thread Pool Min, and Work Manager Thread Pool Max related property values as shown in the following image:




5. Click **Save**.
6. Restart the Process Server for the changes to take effect.

For more information about the Process Server configuration properties in Application Integration Console, see Process Server properties.

To configure the JVM Min Heap and JVM Max Heap, perform the following steps:

1. In Administrator, click **Runtime Environments**.
2. On the **Runtime Environments** page, click the name of the Secure Agent.
   You might have to expand the Secure Agent group to see the list of Secure Agents within the group.
3. Click the **Details** tab.
4. In the upper right corner, click **Edit**.
5. Scroll down to the **System Configuration Details** section.
6. Select the service as **Process Server**.

7. Select the configuration property type as **jvm**.
8. In the row that contains the **jvm min-heap** and **jvm max-heap** properties, click the **Edit Agent Configuration** icon and update the property values.
   The following image shows the **jvm min-heap** and **jvm max-heap** properties:



9. Click **Save**.
10. Restart the Process Server for the changes to take effect.

For more information about the Process Server properties in Administrator, see "Process Server properties" on page 75.

Communication with the Secure Agent

IDMC sends data from the Secure Agent to the Process Server through the Secure Agent Channel or a through a direct HTTP or HTTPS link.

The Secure Agent communicates with Process Server in two ways:

The Secure Agent Channel


A secure channel that creates tunnels between each connected Secure Agent and Process Server.

HTTP or HTTPS

A protocol over which the Secure Agent directly sends data to Process Server. If you use this communication method, IDMC validates your credentials against the authentication provider.

For more information about the communication method that each Process Server property uses, see the Process Server Properties on page 75.

The following image shows the two methods of communication between the Secure Agent and Process Server:



Secure Agent configurations for Process Server

Deploy an asset to a single Secure Agent or a Secure Agent group based on your business needs. If the Process Server uses the Secure Agent group, you can use the Secure Agent load balanced configuration or a Secure Agent Cluster configuration based on your requirements.

When you deploy Application Integration processes, connections, or service connectors to a Secure Agent, you deploy the assets to the Process Server service of the Secure Agent. All Secure Agents with the Process Server service use a PostgreSQL database.

You can deploy an asset to the following Secure Agent configurations:

Single Secure Agent

A single Secure Agent might be the only agent in a group, or one of many agents on a group.

For more information, see "Deploy to a single Secure Agent" on page 87.

Secure Agent group

A Secure Agent group can contain multiple agents.

You can use Secure Agent groups to deploy Process Server services using the following Secure Agent configurations:

Secure Agent load balancing

When you deploy an asset to a Secure Agent group, IDMC performs load balancing. Use the Secure Agent load balanced configuration to distribute requests if you process stateless requests or use the Secure Agent only to serve OData requests.

Secure Agent Cluster

A Secure Agent Cluster is an agent group that has a master Secure Agent. Use the Secure Agent Cluster configuration when you want all Process Servers to receive information about process execution activity.

For more information, see Deploy to a Secure Agent groupon page 87.

The following table summarizes the process execution of the Secure Agent in different scenarios:

	Single Secure Agent	Secure Agent Group	
		Secure Agent Load Balancing	Secure Agent Cluster
Agent Available	Process executes.	Process executes.	Process executes.
Agent Unavailable	Process does not execute.	Process executes on any available Secure Agent.	Process executes on any available Secure Agent.
Agent Stops Mid-Execution	Process does not execute.	Process stops when the Secure Agent stops.	Process continues to execute on another Secure Agent.


For more information about Process Server load balancing and clustering on a Secure Agent, see Knowledge Base article DOC-17437.

Deploy to a single Secure Agent

You can deploy an asset directly to one agent in a group.

When you deploy an asset to a single Secure Agent, no other Process Server in the Secure Agent group receives the asset definitions.

The following image shows a sample configuration where process X is deployed directly to Secure Agent 1:



Only Secure Agent 1 can execute Process X. If Secure Agent 1 is unavailable, the process does not execute.

Deploy to a Secure Agent group

A Secure Agent group contains multiple agents. You can deploy an asset to a Secure Agent group.

Depending on the business requirements, you can use the Secure Agent groups to deploy Process Server services using the following Secure Agent configurations:

Secure Agent load balanced configuration

Use the Secure Agent load balanced configuration to distribute requests if you process stateless requests or use the Secure Agent only to serve OData requests.


When you deploy an asset to a Secure Agent group, you use a load balanced configuration. IDMC performs the load balancing. You can add multiple Secure Agents to a group to balance the distribution of tasks across

Process Servers. At run time, IDMC dispatches incoming requests to available Secure Agents in a round-robin manner.

You can also use a custom load balancer by setting the `load-balance-url` Process Server property. For more information, see Process Server Propertieson page 75.

All Secure Agents in a group use individual PostgreSQL databases. When you deploy an asset to a Secure Agent group, all Process Servers within the group receive details about new or updated asset definitions. However, the other Process Servers in the group do not receive details about the execution activity of an asset. For example, if a Secure Agent within the group fails during process execution, the process does not continue to execute on another Secure Agent within the group.

The following image shows a sample configuration where process X is deployed to Secure Agent group A:



If you modify and re-publish process X, all three Secure Agents receive the updated definition. Any Secure Agent can execute the process.

For example, if the process is invoked and Secure Agent 1 and Secure Agent 2 are unavailable, the load balanced configuration ensures that Secure Agent 3 executes process X. However, Secure Agent 1 and Secure Agent 2 do not receive information about whether the process has faulted or completed successfully. If Secure Agent 3 stops while executing the process X, the process does not execute further.


Secure Agent Cluster configuration

Use the Secure Agent Cluster configuration if you are processing long-running processes and need to perform recovery of payload processing from one node to another. A clustered configuration shares a single database server with all the cluster nodes.

A Secure Agent Cluster is an agent group with a master Secure Agent. You can deploy an asset to a Secure Agent Cluster.

When you deploy an asset to a Secure Agent Cluster, all Process Servers receive information about process execution activity. The master Secure Agent receives information and informs the other Secure Agents. If a Secure Agent fails during process execution, the process continues to execute on another Secure Agent within the cluster.


To enable the cluster configuration for a Process Server, click the **Runtime Environments** tab in Administrator. In the **System Configuration Details** section, set the `cluster-enabled` Process Server property value to `true` as shown in the following image:



All Process Servers in a cluster share the PostgreSQL database of the master agent.

To define the master Secure Agent, use the `primary-node` Process Server property. For more information, see Process Server Propertieson page 75.

The following image shows a sample configuration where process X is deployed to Secure Agent Cluster A:



If Secure Agent 3 starts executing process X but stops midway, either Secure Agent 1 or Secure Agent 2 continues to execute the process.

Note: Each Secure Agent cluster name must be unique at the organization level.

For more information about Secure Agent groups, see *Runtime Environments*.

Prerequisites for PostgreSQL database installation and upgrade

Before you install or upgrade the PostgreSQL database, ensure that the following prerequisites are met:

- You have sufficient free disk space. Informatica recommends that you have a minimum free disk space that is twice the size of the `Data` folder in the following directory:
  `<Secure Agent installation directory>\apps\process-engine\data\PostGreSql\Data`
- The user who runs scripts to install or upgrade the PostgreSQL database must have read, write, and modify permissions for the folders within the following directory:
  `<Secure Agent installation directory>\apps\process-engine\data`
- Stop the PostgreSQL database and Process Server. If the Secure Agent is associated with an advanced cluster, you must stop Process Server on all nodes.

  Note: This step is required when you run the db_upgrade script with the upgrade command line option. However, it is optional when you run the db_upgrade script with the check command line option. Therefore, you can run the db_upgrade script with the check command line option without any downtime.
- On Linux operating systems, the operating system user's locale must use the UTF-8 encoding to match the encoding of the PostgreSQL database. Otherwise, Process Server fails to start.
- PostgreSQL 18.4 binaries require glibc 2.27 or later. On Linux operating systems, verify that the GNU C (GLIBC) library file is of version 2.27 or later. To find the version number, run the following command: `ldd --version`. Run the Secure Agent only on a Linux distribution that includes glibc 2.27 or later. The Secure Agent does not support hosts with an older glibc version.
- If the Secure Agent runs on Windows, install Microsoft Visual C++ Redistributable (x64) version 14.44 or later.

Managing the PostgreSQL database on Windows

Use binaries and utility scripts to manage the PostgreSQL database.

Important: To manage the PostgreSQL database, you must log in as a user who does not have system administrator rights. A system administrator will be unable to run PostrgreSQL binaries and utility scripts.

Informatica has created some utility scripts based on PostgreSQL binaries. These utility scripts make it easier for you to manage the PostgreSQL database.

The following directories contain files for the PostgreSQL database:

- PostgreSQL binaries: `<Secure Agent installation directory>\apps\process-engine\data\db\postgresql-windows-x64-binaries\pgsql\bin`
- PostgreSQL utility scripts: `<Secure Agent installation directory>\apps\process-engine\data\db\util`
- PostgreSQL logs: `<Secure Agent installation directory>\apps\process engine\logs\PostGreSql\postgresql.log`
- PostgreSQL data: `<Secure Agent installation directory>\apps\process engine\data\PostGreSql\Data`

For more information about PostgreSQL scripts, see the PostgreSQL help at https://www.postgresql.org/docs/current/static/index.html.

Some of the following sections contain sample commands that use these default values:

- Default database name: activevos
- Default database user name: bpeluser
- Default database password: bpel

Backing up the PostgreSQL database on Windows

Use the script `db_backup.bat` to back up the PostgreSQL database.

To back up the PostgreSQL database, perform the following steps:

1. Go to `<Secure Agent installation directory>\apps\process-engine\data\db\util`.
2. Run the following command:
   `db_backup.bat <dbusername> <dbpassword> <path to backup file along with name of backup file with a ".dump" extension> <dbport>`

For example, the Secure Agent creates the backup file '`BackupFile1.dump`' in the location `C:\postgre\backup` if you run the following command:

```
db_backup.bat bpeluser bpel "C:\postgre\backup\BackupFile1.dump" 6432
```

Note: The dbport argument is optional. Specify the dbport argument if you use a port that is different from the default port, 5432.

Restoring the PostgreSQL database on Windows

Use the command `db_restore.bat` to restore the PostgreSQL database from a backup file.

To restore the PostgreSQL database file from a backup file, perform the following steps:

1. Go to `<Secure Agent installation directory>\apps\process-engine\data\db\util`.
2. Run the following command:
   `db_restore.bat <dbusername> <dbpassword> <path to dump file> <dbport>`

For example, you use the file `BackupFile1.dump` to restore the PostgreSQL database if you run the following command:

```
db_restore.bat bpeluser bpel "C:\postgre\backup\BackupFile1.dump" 6432
```

Note: The dbport argument is optional. Specify the dbport argument if you use a port that is different from the default port, 5432.

Resetting the PostgreSQL database on Windows

Shut down the PostgreSQL database and then use the command `db_reset.bat` to reset it.

To reset the PostgreSQL database to its original state, perform the following steps:

1. Go to `<Secure Agent installation directory>\apps\process-engine\data\db\util`
2. To shut down the server, run the following command:
   `server_stop.bat`
3. To reset the PostgreSQL database, run the following command:
   `db_reset.bat`

Starting the PostgreSQL server on Windows

To start the PostgreSQL server on Windows, perform the following steps:

1. Go to `<Secure Agent installation directory>\apps\process-engine\data\db\util`.
2. Run the following script:
   `server_start.bat`

   Note: If you do not use the default 5432 port, you must pass the port number as an argument as follows:
   `server_start.bat <port_number>`

   For example, `server_start.bat 6789`

Stopping the PostgreSQL server on Windows

To stop the PostgreSQL server on Windows, perform the following steps:

1. Go to `<Secure Agent installation directory>\apps\process-engine\data\db\util`.
2. Run the following script:
   `server_stop.bat`.

Getting the PostgreSQL server status on Windows

To get the status of the PostgreSQL server on Windows, perform the following steps:

1. Go to `<Secure Agent installation directory>\apps\process-engine\data\db\util`.
2. Run the following script:
   `server_status.bat`

   Note: If you do not use the default 5432 port, you must pass the port number as an argument as follows:
   `server_status.bat <port_number>`

   For example, `server_status.bat 6789`

Vacuuming the PostgreSQL database on Windows

Vacuum the PostgreSQL database to delete obsolete tuples and gain space. You use the script `db_maintenance.bat` to vacuum the PostgreSQL database.

By default, the PostgreSQL database autovacuums. If you want to manually vacuum the database, perform the following steps:

1. Go to `<Secure Agent installation directory>\apps\process-engine\data\db\util`.
2. To vacuum the entire database, run the following command:
   `db_maintenance.bat <dbusername> <dbpassword> <dbport> vacuum`
3. To vacuum a single table, run the following command:
   `db_maintenance.bat <dbusername> <dbpassword> <dbport> vacuum <tablename>`

For example, you vacuum the 'aeprocesslogdata' table if you run the following command:

```
db_maintenance.bat bpeluser bpel 5432 vacuum aeprocesslogdata
```

Note: The dbport argument is required even if you use the default port, 5432.

Reindexing the PostgreSQL database on Windows

Use the reindexing option to clean the index and free up space after you vacuum data on PostgreSQL. You use the script `db_maintenance.bat` to reindex the PostgreSQL database.

To reindex the PostgreSQL database, perform the following steps:

1. Go to `< Secure Agent installation directory>\apps\process-engine\data\db\util`.
2. To reindex the entire database, run the following command:
   `db_maintenance.bat <dbusername> <dbpassword> <dbport> reindex`
3. To reindex a single table, run the following command:
   `db_maintenance.bat <dbusername> <dbpassword> <dbport> reindex <tablename>`

For example, you reindex the 'aeprocesslogdata' table if you run the following command:

```
db_maintenance.bat bpeluser bpel 5432 reindex aeprocesslogdata
```

Note: The dbport argument is required even if you use the default port, 5432.

Resetting transaction logs on Windows

If the PostgreSQL server does not start because of corruption of the control information, use the command `pg_resetxlog.exe` to reset the control information.

To reset the PostgreSQL database control information, perform the following steps:

1. Go to `<Secure Agent installation directory>\apps\process-engine\data\db\postgresql-windows-x64-binaries\pgsql\bin`.
2. Run the following command:
   `pg_resetxlog.exe -D <path to postgreSQL data directory>`

For example, you reset transactions logs in the 'Data' directory if you run the following command:

```
pg_resetxlog.exe -D "C:\postgre\apps\process-engine\data\PostGreSql\Data"
```

Managing the PostgreSQL database on Linux

Use binaries utility scripts to manage the PostgreSQL database.

Important: To manage the PostgreSQL database, you must log in as a user who does not have root access. A root user will be unable to run PostrgreSQL binaries and utility scripts.

Informatica has created some utility script based on PostgreSQL binaries. These utility scripts make it easier for you to manage the PostgreSQL database.

The following directories contain files for the PostgreSQL database:

- PostgreSQL binaries: `<Secure Agent installation directory>/apps/process-engine/data/db/postgresql-linux-x64-binaries/pgsql/bin`
- PostgreSQL utility scripts: `<Secure Agent installation directory>/apps/process-engine/data/db/util`
- PostgreSQL logs: `<Secure Agent installation directory>/apps/process-engine/logs/PostGreSql/postgresql.log`

- PostgreSQL data: `<Secure Agent installation directory>/apps/process-engine/data/PostGreSql/Data`

For more information about PostgreSQL scripts, see the PostgreSQL help at https://www.postgresql.org/docs/current/static/index.html.

Some sections contain sample commands that use the following default values:

- Default database name: activevos
- Default database user name: bpeluser
- Default database password: bpel

Backing up the PostgreSQL database on Linux

Use the script `db_backup.sh` to back up the PostgreSQL database.

To back up the PostgreSQL database, perform the following steps:

1. Go to `<Secure Agent installation directory>/apps/process-engine/data/db/util`.
2. Run the following command:
   `db_backup.sh <dbusername> <dbpassword> <path to backup file along with name of backup file>.dump <dbport>`

For example, the Secure Agent creates the backup file `backupfile1.dump` in the location `/home/data/myfolder/` if you run the following command:

```
db_backup.sh bpeluser bpel "/home/data/myfolder/backupfile1.dump" 6432
```

Note: The dbport argument is optional. Specify the dbport argument if you use a port that is different from the default port, 5432.

Restoring the PostgreSQL database on Linux

Use the script `db_restore.sh` to restore the PostgreSQL database from a backup file.

To restore the PostgreSQL database file from a backup file, perform the following steps:

1. Go to `<Secure Agent installation directory>/apps/process-engine/data/db/util`.
2. Run the following command:
   `db_restore.sh <dbusername> <dbpassword> <path to dump file> <dbport>`

For example, you use the file `backupfile1.dump` to restore the PostgreSQL database if you run the following command:

```
db_restore.sh bpeluser bpel "/home/data/myfolder/backupfile1.dump" 6432
```

Note: The dbport argument is optional. Specify the dbport argument if you use a port that is different from the default port, 5432.

Resetting the PostgreSQL database on Linux

You first shut down the PostgreSQL database and then use the script `db_reset.sh` to reset it.

To reset the PostgreSQL database to its original state, perform the following steps:

1. Go to `<Secure Agent installation directory>/apps/process-engine/data/db/util`
2. To shut down the server, run the following script:

```
server_stop.sh
```

3. To reset the PostgreSQL database, run the following script:
   ```
   db_reset.sh
   ```

Starting the PostgreSQL server on Linux

To start the PostgreSQL server on Linux, perform the following steps:

1. Go to `<Secure Agent installation directory>/apps/process-engine/data/db/util`.
2. Run the following script:
   ```
   server_start.sh
   ```
   Note: If you do not use the default 5432 port, you must pass the port number as an argument as follows:
   ```
   server_start.sh <port_number>
   ```
   For example, `server_start.sh 6789`

Stopping the PostgreSQL server on Linux

To stop the PostgreSQL server, perform the following steps:

1. Go to `<Secure Agent installation directory>/apps/process-engine/data/db/util`.
2. Run the following script:
   `server_stop.sh`.

Getting the PostgreSQL server status on Linux

To get the status of the PostgreSQL server on Linux, perform the following steps:

1. Go to `<Secure Agent installation directory>/apps/process-engine/data/db/util`.
2. Run the following script:
   ```
   server_status.sh
   ```
   Note: If you do not use the default 5432 port, you must pass the port number as an argument as follows:
   ```
   server_status.sh <port_number>
   ```
   For example, `server_status.sh 6789`

Vacuuming the PostgreSQL database on Linux

Vacuum the PostrgeSQL database to delete obsolete tuples and gain space. You use the script `db_maintenance.sh` to vacuum the PostgreSQL database.

By default, the PostgreSQL database auto vacuums. If you want to manually vacuum the database, perform the following steps:

1. Go to `<Secure Agent installation directory>/apps/process-engine/data/db/util`.
2. To vacuum the entire database, run the following command:
   ```
   db_maintenance <dbusername> <dbpassword> <dbport> vacuum
   ```
3. To vacuum a single table, run the following command:
   ```
   db_maintenance.sh <dbusername> <dbpassword> <dbport> vacuum <tablename>
   ```

For example, you vacuum the 'aeprocesslogdata' table if you run the following command:

```
db_maintenance.sh bpeluser bpel 5432 vacuum aeprocesslogdata
```

Note: The dbport argument is required even if you use the default port, 5432.

Reindexing the PostgreSQL database on Linux

Use the reindexing option to clean the index and free up space after you vacuum data on PostgreSQL. You use the script `db_maintenance.sh` to reindex the PostgreSQL database.

To reindex the PostgreSQL database, perform the following steps:

1. Go to `<Secure Agent installation directory>/apps/process-engine/data/db/util`.
2. To reindex the entire database, run the following command:
   `db_maintenance <dbusername> <dbpassword> <dbport> reindex`
3. To reindex a single table, run the following command:
   `db_maintenance.sh <dbusername> <dbpassword> <dbport> reindex <tablename>`

For example, you reindex the 'aeprocesslogdata' table if you run the following command:

```
db_maintenance.sh bpeluser bpel 5432 reindex aeprocesslogdata
```

Note: The dbport argument is required even if you use the default port, 5432.

Resetting transaction logs on Linux

If the PostgreSQL server does not start because of corruption to the control information, use the command `pg_resetxlog` to reset the control information.

To reset the control information of the PostgreSQL database, perform the following steps:

1. Go to `<Secure Agent installation directory>/apps/process-engine/data/db/postgresql-linux-x64-binaries/pgsql/bin .`
2. Run the following command:
   `pg_resetxlog -D <path to postgreSQL data directory>`

For example, you reset the transactions logs in the `Data` directory, if you run the following command:

```
pg_resetxlog -D "home/apps/process engine/data/PostGreSql/Data"
```

Upgrading the PostgreSQL database

You can upgrade the PostgreSQL database from version 12.4, 12.6, 3.5 or 14.6 to version 18.4. Version 18.4 offers improved security, performance, and scalability.

You can choose to upgrade at your own convenience by manually running scripts provided by Informatica. The scripts take a backup of the existing database version so that you can restore to the old database version in case of any upgrade issue.

For more information about upgrading the PostgreSQL database, see the following community article:

https://knowledge.informatica.com/s/article/DOC-18945

Upgrading the PostgreSQL database using the replication technique

If your Process Server PostgreSQL database version is earlier than version 18.4, you can upgrade the database to version 18.4 with minimal downtime by using the replication technique. The upgrade involves verifying host requirements, restarting the Process Server, and enabling the replication upgrade.

To upgrade the database, complete the following tasks:

1. Verify the host requirements.
2. Restart the Process Server.
3. Configure the synchronization workers
4. Enable the replication upgrade.
5. Check the replication progress.
6. Complete the switchover.

Note: You can't upgrade the PostgreSQL database by using the replication technique on a Secure Agent cluster.

Prerequisites

- Since PostgreSQL 18.4 doesn't support glibc versions earlier than 2.27, the Secure Agent must run on a Linux distribution that includes glibc 2.27 or later. The Secure Agent does not support hosts with an earlier glibc version.
- If the Secure Agent runs on Windows, install Microsoft Visual C++ Redistributable (x64) version 14.44 or later.
- Restart the Process Server before you enable the replication upgrade.
- For a replication upgrade, ensure that the host has free disk space equal to at least 2 times the current database size.

Restart the Process Server

1. Open the Administrator service and select **Runtime Environments**.
2. On the **Runtime Environments** page, click the name of the Secure Agent.

   Note: You might have to expand the Secure Agent group to see the list of Secure Agents within the group.
3. In the **Agent Service Details** section, hover over the row that contains the Process Server service and click the **Stop Service** icon.
4. Click the **Start Service** icon in the row to restart the Process Server service. After the service starts, the status changes to **Up and Running**. If the service fails to start, check the audit log on the **Monitor** tab to find the cause of the error.

Configure the synchronization workers

Configure the maximum number of synchronization workers for each subscription to control how many tables the replication copies in parallel. The default value is 2. Set the value based on your replication load, as shown in the following table:

Load	Data size	Recommended value
Low	<10 GB	2 (default)

Load	Data size	Recommended value
Medium	10-100 GB	4
High	100+ GB	6-8

1. On the Secure Agent machine, go to the following directory:

   ```
   <Secure Agent installation directory>\apps\process-engine\data\PostGreSql\Data
   ```

2. Open the `user.conf` file.
3. To set the number of synchronization workers, add the following property with a value that suits your replication load:

   ```
   max_sync_workers_per_subscription = <value>
   ```

4. Save the `user.conf` file.
5. To apply the change without restarting the database, connect to the database and run the following query:

   ```
   SELECT pg_reload_conf();
   ```

   If the configuration reloads, the query returns `t`.
6. To verify the new value, run the following query:

   ```
   SHOW max_sync_workers_per_subscription;
   ```

7. To close the database session, run `\q`.

Note: Close the database session before you enable the replication upgrade. An open session can cause the replication to fail.

Enable the replication upgrade

1. On the Secure Agent machine, open a command prompt and go to the following directory:

   ```
   <Secure Agent installation directory>/apps/process-engine/data/db/util
   ```

   Run the database upgrade script with the `enable_replication` option.

   - For Linux. `./db_upgrade.sh enable_replication`
   - For Windows. `db_upgrade.bat enable_replication`

2. Restart the Process Server to start the replication upgrade. In the Process Server logs, confirm that the replication started by looking for the following entries:

   - Starting replication
   - Replication has started successfully

   Wait for the data replication from the earlier PostgreSQL version to the newer PostgreSQL version to finish. Replication is complete when all the tables are copied to the newer version.

   Note: The time replication takes to complete depends on the size of the database.

3. After replication completes, restart the Process Server to complete the switchover to the newer PostgreSQL version. To confirm that the switchover has started, check the Process Server logs for the following entry:

   ```
   Replication is completed. Starting Switchover.
   ```

   The Process Server runs on PostgreSQL version 18.4.

Check the replication progress

Optionally, check the replication progress before you restart the Process Server to complete the switchover.

1. To confirm that a switchover is pending, check for the readyForSwitchover marker file in the following directory:

   ```
   <Secure Agent installation directory>\apps\process-engine\data\readyForSwitchover
   ```

2. Open the file to view the replica details, for example:

   ```
   port = 58795
   name = postgre-replica-v33
   version = 33
   ```

   If the file exists, replication is set up and a switchover is pending.

   Note: The port is assigned per run and changes each time. Note the port value for step 4.

3. Browse to the `psql` folder of the replica. If the version differs, replace `postgre-replica-v33` with the name in the marker file.

   ```
   cd "<Secure Agent installation directory>\apps\process-engine\data\postgre-
   replica-v33\db\postgresql-<windows or linux>-x64-binaries\pgsql\bin"
   ```

4. To connect to the replica database, run the following command with the replica port from step 2. Do not use the default port 5432, which is the source database. Enter the database password when prompted.

   Note: Replication status is visible only on the replica instance. If you connect to the source database, the query returns 0 rows.

   - For Windows.

     ```
     psql -U bpeluser -h <DB_HOST> -p <replica_port> -d activevos
     ```

   - For Linux.

     ```
     ./psql -U bpeluser -h <DB_HOST> -p <replica_port> -d activevos
     ```

5. At the `activevos=#` prompt, run the following completeness check:

   ```
   SELECT count(*) AS total,
          count(*) FILTER (WHERE srsubstate IN ('r','s')) AS ready,
          count(*) FILTER (WHERE srsubstate NOT IN ('r','s')) AS pending
   FROM pg_subscription_rel;
   ```

   Replication is complete when `ready = total` and `pending = 0`.

6. To close the database session, run `\q`. Then close the command prompt window.

   Note: An open connection to the replica database can block the switchover.

Complete the switchover

1. To complete the switchover to the newer PostgreSQL version, restart the Process Server after the replication completes.
2. To confirm that the switchover started, check the Process Server logs for the following entry:

   ```
   Replication is completed. Starting Switchover
   ```

   The Process Server runs on PostgreSQL version 18.4

When you restart the Process Server for the first time, the database starts replicating data from your existing database version. Each time you restart the Process Server, the database verifies the replication status. After replication finishes, the earlier PostgreSQL version shuts down and the newer version starts automatically. This process eliminates the need to manually upgrade the Process Server PostgreSQL database by running the scripts provided by Informatica.

PostgreSQL configuration files

When you install the PostgreSQL database, the `postgresql.conf` file is automatically created in the following directory:

```
<Secure Agent installation directory>\apps\process-engine\data\PostGreSql\Data
```

The configuration parameters in the `postgresql.conf` file define the default values of the server properties related to auditing, authentication, encryption, and other behaviors.

The `postgresql.conf` file is overwritten every time you install or upgrade to a new version of the PostgreSQL database. Do not update the `postgresql.conf` file for any customized behavior, because the changes are lost when the file is overwritten.

Use the `user.conf` file to override the default values that are defined in the `postgresql.conf` file.

If the `user.conf` file does not already exist, create the file in the same directory as the `postgresql.conf` file, and override the values. Changes take effect after you restart the PostgreSQL database.

Configuring PostgreSQL log rotation

The PostgreSQL log contains logging information for the PostgreSQL database that is packaged with the Secure Agent.

The PostgreSQL log is available in the following directory:

```
<Secure Agent installation directory>\apps\process-engine\logs\PostGreSql\postgresql.log
```

The PostgreSQL log can become very large and difficult to manage over time. You can configure log rotation to reduce the file size and manage the file easily. You can configure log rotation based on time or file size.

1. Create a file named `user.conf` in the following location if it does not already exist:

   ```
   <Secure Agent installation directory>\apps\process-engine\data\PostGreSql\Data
   ```

   The `user.conf` file overrides the values defined in the `postgresql.conf` file.
2. Perform one of the following steps:
   - To rotate the logs based on time, add the following properties to the `user.conf` file:

     ```
     log_filename = 'postgresql-%Y-%m-%d_%H%M%S.log'
     log_rotation_age=<value in minutes>
     ```

     For example, if you set the value of the log_rotation_age property to 1440, the log file will be rotated every day.
   - To rotate the logs based on file size, add the following properties to the `user.conf` file:

     ```
     log_filename = 'postgresql-%Y-%m-%d_%H%M%S.log’
     log_rotation_size=<value in kilobytes>
     log_truncate_on_rotation=on
     ```

     For example, if you set the value of the log_rotation_size property to 10240, the log file will be rotated when the file size exceeds 10 MB.
3. Save the `user.conf` file.
4. Restart the PostgreSQL database for the change to take effect.

Configuring public certificates and private keys for Process Server

When you use Application Integration processes and connections to connect to an SSL-enabled endpoint, you must have public certificates and/or private keys. You must import the public certificates and private keys for the processes and connections to the Secure Agent.

After configuring public certificates and private keys for Process Server, enable mutual authentication for Process Server,

Import public certificates and private keys for processes and connections

To connect to an SSL-enabled endpoint, such as a web service, queue, or a JDBC connection, you need a public certificate and/or a private key.

You must import the certificates to the Secure Agent machine where the process or connection is published in order for the process or connection to establish SSL-enabled connections to these endpoints.

To import the public certificates and/or private keys, perform the following steps:

- For public certificates, place the cert file in the following location and restart the Secure Agent:

  `<Secure Agent installation directory>/apps/process-engine/conf/certs`
- For private keys, import the keys to the `ae.keystore` file in the following location and restart the Secure Agent:

  `<Secure Agent installation directory>/apps/process-engine/conf`

You must import and place the public cert file in `x509` format in the `certs` folder mentioned above. You must import the certificates and keys in the same locations to ensure ease of use and compatibility with upgrades.

Additionally, to import a secret private key within the Informatica Keystore, the secret key must have the same keystore format, that is, PKCS12 "`.p12`". For example, if the secret key is provided in the "`.pfx`" format, you must convert it to "`.p12`". You can verify this with the certificate provider.

To connect to the Secure Agent through the domain name and not the localhost, you can generate the certificate based on the domain name that you want to connect to and copy the certificate into the `certs` folder.

Enable mutual authentication for Process Server


After upgrading the Process Server with the latest package, enable mutual authentication for Process Server using one of the following methods:

- Enable mutual authentication from Administrator.
- Manually update the `server.xml.mustache` file.

To enable mutual authentication from Administrator, perform the following steps:

1. In Administrator, select **Runtime Environments**.
2. On the **Runtime Environments** page, click the name of the Secure Agent.
   You might have to expand the Secure Agent group to see the list of Secure Agents within the group.
3. Click the **Details** tab.
4. In the upper right corner, click **Edit**.
5. Scroll down to the **Custom Configuration Details** area.
6. If there are custom properties already configured, click the **Add** icon to add a new property row.
7. Select the service as **Process Server**.
8. Select the configuration property type as **connectors**.

9. Enter the property name as **https-clientAuth** and the value as **true** as shown in the following image:



10. Click **Save**.
    The status of the Process Server service shows up as **Restart Required**.
11. Restart the Process Server for the change to take effect.

To manually update the `server.xml.mustache` file, perform the following steps:

1. Log in to the Secure Agent machine.
2. Go to the following directory:

   ```
   <Secure Agent installation directory>/downloads/package-process-engine.<latest_version>/package/app/conf/
   ```

3. Edit the `server.xml.mustache` file and change the value of the `clientAuth` property from `want` to `true`.
4. Save the `server.xml.mustache` file.
5. Restart the Secure Agent for the change to take effect.

Note: The default keystore is `ae.keystore` and it is installed with a localhost certificate.

For more information about the Process Server keystore and truststore configurations, see the attachment in Knowledge Base article 611562.

Configuring thread pool profile to improve throughput

When you use event-based connectors such as AMQP and Kafka, you can increase the number of threads by increasing the thread pool size in the default thread pool profile. To increase the thread pool size, update the `aeEngineConfig.xml.mustache` file on the Secure Agent machine.

By default, the thread pool size is limited to 10 threads and a maximum of 10 messages can be processed concurrently by the connections. Informatica recommends that you increase the thread pool size only if you want to increase throughput, because additional threads occupy some resources, and too large pools are not recommended. The thread pool size applies to all event-based connections.

You can also configure the thread pool profile settings on the **Server Configuration** page in Application Integration Console. When you configure the thread pool profile settings on both the **Server Configuration** page and the `aeEngineConfig.xml.mustache` file on the Secure Agent machine, the properties configured on the **Server Configuration** page take precedence. For more information about the thread pool profile settings on the **Server Configuration** page, see Server Properties.

To configure the thread pool profile, perform the following steps:

1. Log in to the Secure Agent machine.
2. Go to the following directory:

   `<Secure Agent installation directory>/downloads/package-process-engine.<latest_version>/package/app/webapps/process-engine/WEB-INF/classes`
3. Open the `aeEngineConfig.xml.mustache` file in a text editor and search for the following entry:

   `<entry name="IAeESBManager">...</entry>`
4. Within the `IAeESBManager` entry, search for the subentry named `camelContext`.

   Based on the status of the `cluster.enabled` option, you will find the following entries:

   - If the `cluster.enabled` option is disabled, edit the following `camelContext` entry:

     ```
     <entry name="Class" value="com.activee.rt.camel.AeCamelIntegrationManager"/>
     <entry name="camelContext">
      <entry name="Class" value="com.activee.rt.camel.core.AeDefaultCamelContext"/>
     </entry>
     ```
   - If the `cluster.enabled` option is enabled, edit the following `camelContext` entry:

     ```
     <entry name="Class"
     value="com.activee.rt.cluster.AeClusterDistributedCamelManager"/>
      <entry name="camelContext">
         <entry name="Class"
     value="com.activevos.socrates.connectors.camel.AeSocratesCamelContext"/>
      </entry>
     ```
5. Append a new `threadpoolProfile` subentry within the `camelContext` entry.

   If the `cluster.enabled` option is disabled, add the following lines:

   ```
   <entry name="camelContext">
    <entry name="Class" value="com.activee.rt.camel.core.AeDefaultCamelContext"/>
    <!-- New subentry -->
    <entry name="threadpoolProfile">
      <entry name="PoolSize" value="<PoolSizeValue>"/>
      <entry name="MaxPoolSize" value="<MaxPoolSizeValue>"/>
      <entry name="MaxQueueSize" value="<MaxQueueSizeValue>"/>
      <entry name="KeepAliveTime" value="<KeepAliveTimeValue>"/>
      <entry name="TimeUnit" value="SECONDS"/>
      <entry name="AllowCoreThreadTimeout" value="true"/>
      <entry name="RejectedPolicy" value="CallerRuns"/>
    </entry>
   </entry>
   ```

   If the `cluster.enabled` option is enabled, add the following lines:

   ```
   <entry name="camelContext">
    <entry name="Class"
   value="com.activevos.socrates.connectors.camel.AeSocratesCamelContext"/>
    <!-- New subentry -->
    <entry name="threadpoolProfile">
      <entry name="PoolSize" value="<PoolSizeValue>"/>
      <entry name="MaxPoolSize" value="<MaxPoolSizeValue>"/>
      <entry name="MaxQueueSize" value="<MaxQueueSizeValue>"/>
      <entry name="KeepAliveTime" value="<KeepAliveTimeValue>"/>
      <entry name="TimeUnit" value="SECONDS"/>
      <entry name="AllowCoreThreadTimeout" value="true"/>
      <entry name="RejectedPolicy" value="CallerRuns"/>
    </entry>
   </entry>
   ```

6. Increase the thread pool size as required.

   Note: The pool is used by all the running event-based connections on the Secure Agent.

7. Save the `aeEngineConfig.xml.mustache` file.
8. Restart the Secure Agent for the change to take effect.

Overriding properties in the platform.yaml file

You can override the default values for properties that the Process Server uses to get the configuration details related to Application Integration and communicate with the Secure Agent services.

To do this, you create a copy of the `platform.yaml` file and update the property values, name the file as `user-platform.yaml`, and save it in the following directory:

```
<Secure Agent installation directory>\apps\process-engine\conf
```

The `platform.yaml` file is available in the following directory:

```
<Secure Agent installation directory>\apps\process-engine\<latest_process_engine_version>
\conf
```

When the Process Server is up and running, if a property is specified in the `user-platform.yaml` file, the Process Server uses that specific value. Otherwise, Process Server uses the values defined in the `platform.yaml` file.

When the Secure Agent is upgraded to a new version, the properties in the `user-platform.yaml` file are unchanged.

Creating a custom user-platform.yaml file

You can create a custom `user-platform.yaml` file with the required properties and their custom values to override the properties in the `platform.yaml` file on the Secure Agent.

You must have the same level of access permissions as the `platform.yaml` file to create and edit the `user-platform.yaml` file.

To create a custom `user-platform.yaml` file, perform the following steps:

1. Log in to the Secure Agent machine.
2. Create a file named `user-platform.yaml` in the following directory:
   `<Secure Agent installation directory>\apps\process-engine\conf`
3. Copy the properties that you want to customize from the `platform.yaml` file that is available in the following directory to the `user-platform.yaml` file and override the values, as required:
   `<Secure Agent installation directory>\apps\process-engine\<latest_process_engine_version>\conf`

   For example, consider that you need to override the values of the `cacheExpiryMillis` and `lockTimeoutMillis` properties.

   These properties are available in the IDs section in the default `platform.yaml` file as shown in the following sample:

```
serviceHosts:
    ids:
        context: /identity-service/api/v1/
```

```
agentContext : /identity-service/agent/api/v1/
cache:
   enabled: true
   maxCacheItems: 2500
   cacheExpiryMillis: 60000
   lockTimeoutMillis: 30000
   refreshAheadEnabled: true
   queueCapacity: 500
   corePoolSize: 1
   maxPoolSize: 5
   keepAliveSec: 120
   timeToRefreshSec: 15
   evictOnLoadMiss: false
clientPool:
   socketTimeout : 60000
   connectionTimeout : 60000
   poolMaxTotal : 40
   poolMaxPerRoute : 30
hystrix:
   executionTimeoutInMilliseconds : 60000
   fallbackEnabled: false
```

Copy these properties from the `platform.yaml` file and update the values in the `user-platform.yaml` file as shown in the following sample:

```
serviceHosts:
    ids:
        context: /identity-service/api/v1/
        agentContext : /identity-service/agent/api/v1/
        cache:
           cacheExpiryMillis: 200000
           lockTimeoutMillis: 150000
```

Note: You must ensure that you follow the same hierarchy and syntax as the default `platform.yaml` file.

4. Save the `user-platform.yaml` file.
5. Restart the Process Server for the changes to take effect.

When the Process Server is up and running, the properties specified in the `user-platform.yaml` file override the properties in the `platform.yaml` file.

Troubleshooting

When overriding the properties, if the `user-platform.yaml` file contains incorrect properties or values when compared to the `platform.yaml` file, you might encounter unexpected behavior.

For example, consider the following scenarios where you do not get the expected result because of manual intervention:

- The `agentContext` property is used to fetch the IDS-SESSION-ID. If the value for the `agentContext` property in the `platform.yaml` file is `/identity-service/agent/api/`**`v1`**`/` and you entered the value as `/identity-service/agent/api/`**`v2`**`/` in the `user-platform.yaml` file, Process Server fails to fetch the IDS-SESSION-ID because of the invalid endpoint. Therefore, the Secure Agent uses the basic authentication mechanism.
- The `cacheExpiryMillis` property value is expected to be numeric. However, if you enter an alphanumeric value, the value will be treated as a string without any error.

Rolling upgrades

Process Server supports rolling upgrades. In a rolling upgrade, Process Server services that run on the agents within a Secure Agent group are upgraded sequentially. Therefore, while Process Server is being upgraded on one agent, the service remains available on other agents in the group.

Other services that run on the agents within a Secure Agent group are upgraded on each agent simultaneously. Therefore, they are unavailable while the agents in the group are being upgraded. They become available again when all agents in the group have been successfully upgraded.

Example

Your organization uses the following runtime environments:

- Secure Agent group A:

  Agent A1 runs Data Integration Server and Process Server.

  Agent A2 runs Data Integration Server, Mass Ingestion, and Process Server.

- Secure Agent group B:

  Agent B1 runs Data Integration Server, Mass Ingestion, and Process Server.

  Agent B2 runs Data Integration Server, Mass Ingestion, and Process Server.

When your organization is upgraded, Secure Agent groups A and B are upgraded simultaneously. Within each Secure Agent group, Process Server is upgraded sequentially. Therefore, while Process Server is being upgraded on agents A1 and B1, it remains up and running on agents A2 and B2. When the upgrade finishes on agents A1 and B1, Process Server is upgraded on agents A2 and B2.

Data Integration Server and Mass Ingestion do not support rolling upgrades. In groups A and B, Data Integration Server is upgraded on each agent simultaneously. In group B, Mass Ingestion is upgraded on agents B1 and B2 simultaneously.

Rolling upgrade error handling

If Process Server encounters an error during an upgrade, you can specify whether to continue or stop upgrading the service. Configure the error handling behavior on the **Settings** page.

You can select either of the following options:

In case of error, flag error and continue with upgrade

If an error occurs while a service is being upgraded, the service stops with an error on the agent in which it encountered the error. The upgrade then continues on the other agents within the group.

Warning: If you enable this option and the error occurs on all agents in the group, the service stops running on the Secure Agent group. This can cause job interruptions.

In case of error, stop upgrade

If an error occurs while a service is being upgraded, the service stops with an error on the agent in which it encountered the error. Upgrade of the service stops for all other agents in the group that have not already been upgraded. The agents that have not been upgraded continue to run the previous version of the service.

This is the default option.

To configure the error handling behavior, click **Edit** in the Upgrade Settings for Secure Agent Services area, select the appropriate option, and click **Save**.


CHAPTER 19

SecretManagerApp

The SecretManagerApp service is the Secure Agent service that manages communication between IDMC and your secrets manager when your organization uses an external secrets manager like AWS Secrets Manager or Azure Key Vault.

To change or optimize the behavior of the SecretManagerApp service, configure its properties in the System Configuration Details section when you edit a Secure Agent.

The following image shows some of the SecretManagerApp service properties:



You can configure the following SecretManagerApp service properties:

Type	Name	Description
SECRET_MANAGER_APP_CONF	JVM_MIN_MEMORY	Amount of memory allocated for the SecretManagerApp service when the service starts. Default is 32 MB.
SECRET_MANAGER_APP_CONF	JVM_MAX_MEMORY	Maximum memory allocated for the SecretManagerApp service. Default is 256 MB.
Note: Do not change the values of other SecretManagerApp service properties unless Informatica Global Customer Support instructs you to do so.		

CHAPTER 20

Customer Managed Data Integration Service

The Customer Managed Data Integration Service is the Secure Agent service that allows Secure Agents to operate in environments with limited connectivity to IDMC.

In a Customer Managed runtime environment, users have complete control over what information and upgrades are pushed to Secure Agents.


You can configure the minimum and maximum amount of memory for the JVM and you can specify the logging level.

For more information about Customer Managed runtime environments, see *Runtime Environments*.

Customer Managed Data Integration Service properties

To change or optimize the behavior of the Customer Managed Data Integration service, configure its properties in the **System Configuration Details** area when you edit a Secure Agent.

The following image shows the Customer Managed Data Integration Service properties:



You can configure the following Customer Managed Data Integration service properties:

Type	Name	Description
OFFLINE_CDI_CONF	JVM_MIN_MEMORY	Amount of memory allocated for the Customer Managed Data Integration service when the service starts. Default is 512 MB.
OFFLINE_CDI_CONF	JVM_MAX_MEMORY	Maximum memory allocated for the Customer Managed Data Integration service. Default is 2048 MB.
OFFLINE_CDI_CONF	JDK_DISABLED_SCHEMES	
Note: Do not change the values of other Customer Managed Data Integration service properties unless Informatica Global Customer Support instructs you to do so.		


CHAPTER 21

ResilientManagerApp

The Resilient Manager app lets your Secure Agent keep working without a connection to IDMC. It handles the essential services the agent needs to run on its own, such as authentication, securing data, and running scheduled jobs.

To change or optimize the behavior of the ResilientManagerApp service, configure its properties in the Service Configuration page when you edit a Customer Managed runtime environment.

The following image shows some of the ResilientManagerApp service properties:



You can configure the following ResilientManagerApp service properties:

Type	Name	Description
RESILIENT_MANAGER_APP_CONF	port	Network port the Resilient Manager app listens on. Change this if the default port is already in use on the machine or your network rules require a different port. Default is 9443.
RESILIENT_MANAGER_APP_CONF	JVM_MIN_MEMORY	Amount of memory allocated for the ResilientManagerApp service when the service starts. Specify a number followed by 'm' (megabytes) or 'g' (gigabytes). Default is 512m.
RESILIENT_MANAGER_APP_CONF	JVM_MAX_MEMORY	Maximum memory allocated for the ResilientManagerApp service. Specify a number followed by 'm' (megabytes) or 'g' (gigabytes). Default is 2048m.
RESILIENT_MANAGER_APP_CONF	log_level	Amount of detail the app writes to its log files. Valid values are ERROR, WARN, INFO, and DEBUG. Use DEBUG for more detail when troubleshooting. Default is INFO
LOG4J	rootLogger	Default amount of detail written to the logs by libraries and components other than those owned by Informatica. Valid values are ERROR, WARN, INFO, and DEBUG. Default is INFO
Note: Do not change the values of other ResilientManagerApp service properties unless Informatica Global Customer Support instructs you to do so.		

CHAPTER 22

Taskflow Service

The Taskflow service is the Secure Agent service that runs taskflows on a Customer Managed Secure Agent group without an IDMC connection. The service processes taskflows the same way IDMC does.

Prerequisites

Before you use the Taskflow service, verify the following prerequisites:

- You have the Customer Managed Runtime license. The service package is taskflow-engine-offline.
- You installed a Customer Managed Runtime environment. For more information, see *Runtime Environments* in the Administartor help.
- Enable the Taskflow Service. To enable the Taskflow Service, contact the Global Customer Support (GCS) and request it for your organization. After GCS enables the service, it starts running on the Secure Agent.

The agent runs, schedules, and monitors taskflows without an IDMC connection. The Secure Agent buffers job logs and license usage until it reconnects to IDMC. Monitoring pages, such as **My Jobs** and **Monitor** pages display the jobs after synchronization completes.

The Taskflow service uses default settings, so you don't need to configure service properties.

When the Customer Managed Secure Agent group contains more than one agent, the service distributes taskflow runs randomly across the agents.

CHAPTER 23

Configuring Secure Agent service properties

To configure Secure Agent service properties, open the **Runtime Environments** page and edit the Secure Agent. You can change, mask, and reset Secure Agent service property values. You can add and remove custom properties for a service. You can also change the Secure Agent name.

Custom properties are specific to connectors. For more details about custom properties, see the help for the appropriate connector.

Warning: Do not configure agent-level Secure Agent service property settings for an agent in a Secure Agent group that uses group-level property settings. If you want to configure agent-level property settings, delete the group-level property settings before you configure the agent properties. For more information about group-level property settings, see "Runtime Environments" in the *REST API Reference*.

1. On the **Runtime Environments** page, click the name of the Secure Agent.

   You might have to expand the Secure Agent group to see the list of Secure Agents within the group.
2. Click the **Details** tab.
3. In the upper right corner, click **Edit**.
4. To change the Secure Agent name, enter a new name in the **Agent Name** field.
5. To edit a service property, perform the following steps:
   a. In the **System Configuration Details** area, select a service.
   b. Select the configuration property type.
   c. In the row that contains the property that you want to edit, click the **Edit Agent Configuration** icon.
   d. To change the property value, enter the new property value.

      If the property is a sensitive property, the existing value will be cleared when you edit the property.
   e. If the property contains sensitive data and you want to mask the value on the Secure Agent details page, enable the **Sensitive** option.

      When you enable the sensitive option, the value you enter is masked. If the field is a multi-line text field, the value is masked after you save the changes.
   f. To reset the property to the system default value, click the **Reset Agent Configuration to system default** icon.

6. To add a custom property for a service, perform the following steps:
   a. Scroll down to the **Custom Configuration Details** area.

      The following image shows the **Custom Configuration Details** area:

   b. If there are custom properties already configured, click the **Add** icon to add a new property row.
   c. Select the service that you want to configure.
   d. Select a configuration property type.
   e. If the configuration property type has a sub-type, select the appropriate sub-type.

      For example, to determine the logging level, choose INFO or DEBUG as the sub-type.
   f. Enter the property name and value.
   g. If the property contains sensitive data and you want to mask the value on the Secure Agent details page, enable the **Sensitive** option.
7. To remove a custom property, click the **Remove** icon next to the custom property.
8. To reset all configuration properties to the default settings, click **Reset All**.
9. Click **Save**.

INDEX

C

Cloud Application Integration community
  URL 6
Cloud Developer community
  URL 6
CMI Streaming Agent
  Secure Agent service 15
Connector Service
  overview 21
custom configuration properties
  Secure Agent 113
Customer Managed Data Integration service
  overview 108

D

Data Integration community
  URL 6
Data Integration Server
  overview 35

E

Elastic Server
  overview 46

F

File Integration Service 50

G

GitRepoConnectApp
  local repository directory 51
  overview 51

I

Informatica Global Customer Support
  contact information 7
Informatica Intelligent Data Management Cloud
  web site 6

M

maintenance outages 7

N

NetworkRetryInterval
  Data Integration Server property 35
NetworkTimeoutPeriod
  Data Integration Server property 35

R

ResilientManagerApp
  overview 110

S

schedules
  Secure Agent service restart 10
SecretManagerApp
  overview 107
Secure Agent services
  CMI Streaming Agent 15
  Database Ingestion agent environment variable 34
  Database Ingestion service properties 30
  restart schedule configuration 10
  rolling upgrade error handling 106
  rolling upgrades 106
Secure Agents
  changing the agent name 113
  Common Integration Components properties 18
  configuring service properties 113
  Connector Service configuration properties 21
  Connector service overview 21
  custom configuration properties 113
  Customer Managed Data Integration service overview 108
  Customer Managed Data Integration Service properties 108
  Data Access Management Agent Service 22
  Data Access Management Agent service properties 22
  Data Access Management Proxy Service 27
  Data Access Management Proxy service properties 28
  Data Integration Server configuration properties 36
  Data Integration Server service overview 35
  Elastic Server configuration properties 46
  Elastic Server service overview 46
  GitRepoConnectApp configuration properties 52
  GitRepoConnectApp service overview 51
  IDMC Data Gateway Service 54
  IDMC Data Gateway Service properties 54
  masking configuration properties 113
  Mass Ingestion agent service properties 60
  Metadata Foundation Application 64
  Metadata Foundation Application properties 64
  Metadata Platform Service 69
  Metadata Platform Service properties 69
  network interruption settings 35
  ResilientManagerApp service overview 110

Secure Agents *(continued)*
SecretManagerApp service overview 107
services overview 8
source control
configuring the local repository directory 51
status
IDMC 7
system status 7

T

trust site
description 7

U

upgrade notifications 7

W

web site 6