Informatica® Intelligent Data Management Cloud

October 2026

IDMC Glossary of Terms

Informatica Intelligent Data Management Cloud IDMC Glossary of Terms
October 2026

© Copyright Informatica LLC 2025, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices and AI assistant acknowledgements are included with the product.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-10-16

Table of Contents

Preface 4

Informatica Resources 4

- Informatica Documentation 4
- IDMC web site 4
- IDMC Communities 4
- IDMC Marketplace 4
- Data Integration connector documentation 5
- Informatica Knowledge Base 5
- IDMC Trust Center 5
- IDMC Pulse Dashboard 5
- Informatica Global Customer Support 5

Chapter 1: IDMC glossary 6

Chapter 2: Glossary of IDMC terms 7

A 7
B 9
C 10
D 13
E 19
F 20
G 21
H 21
I 22
J 24
L 24
M 24
N 27
O 27
P 28
R 30
S 32
T 35
U 37
V 37
W 38

Chapter 3: Analogous Informatica and Salesforce terms 39

Index 41

Preface

Refer to the *Glossary* to learn about common terms in IDMC and to discover terminology about complementary featues across IDMC and Salesforce Data 360.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

IDMC web site

You can access the Informatica® Intelligent Data Management Cloud™ (IDMC) web site at http://www.informatica.com/cloud.

IDMC Communities

Use the IDMC Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the IDMC Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

IDMC Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

IDMC Trust Center

The IDMC Trust Center provides information about Informatica security, compliance, and privacy practices.

You can access the trust center at https://trust.informatica.com/.

IDMC Pulse Dashboard

The IDMC Pulse Dashboard provides system status and upgrade information for all PODs and services across IDMC.

Follow the services you use and subscribe to alerts to receive notifications about upgrades, maintenance, production incidents, and upcoming releases. The IDMC Pulse Dashboard displays the production status of all the IDMC products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single service or all IDMC services. Subscribing to all services is the best way to be certain you never miss an update.

For more information, see the Service Status and Communications guide.

Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the IDMC Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

IDMC glossary

Welcome to the IDMC glossary. The glossary explains common terms that you'll encounter as you use IDMC and explore the product documentation. The glossary terms are organized alphabetically.

The glossary also defines features and functionality that are similar or complementary across IDMC and Salesforce Data 360. The glossary presents the definitions as a parallel list of terms.

You can use IDMC and Salesforce Data 360 together to deliver foundational data management capabilities to your organization. For more information, see A Solid Data Foundation: Data 360 and Informatica IDMC.

CHAPTER 2

Glossary of IDMC terms

Enter a short description of the concept here (required).

This is the start of the concept.

A

access control

The practice of managing the level of user access to the assets in your organization through a set of access policies that control permissions on assets.

Used by Data Governance and Catalog, Data Marketplace.

access policy

A set of rules to control access to assets and define permissions on those assets in an organization.

For example, you can create an access policy to grant data stewards permissions to create, read, update, and delete business terms in your organization.

Used by Data Governance and Catalog, Data Marketplace.

advanced cluster

A Kubernetes cluster that provides a distributed processing environment on the cloud. An advanced cluster can be a fully-managed, self-service, or local cluster.

Can be used by all services.

advanced configuration

An asset that defines an advanced cluster. A Secure Agent uses an advanced configuration to either create a fully-managed or local cluster, or to connect to a self-service cluster.

Used by Data Integration.

advanced mode

A mode in the Mapping Designer that enables transformations, functions, and connectors for advanced use cases that process data such as multilevel hierarchical data, embedded code snippets, and workloads at any scale.

You can create a mapping in advanced mode.

Used by Data Integration.

agent

A program that runs tasks in IDMC. An agent can be a Secure Agent that runs locally within your environment or within a cloud computing services environment, or it can be the Hosted Agent that runs at an Informatica Cloud hosting facility.

Can be used by all services.

appconnection

An asset that you configure to provide access to data in cloud and on-premises applications, APIs, web services, and databases.

Used by Application Integration.

application

An Integration Hub asset that represents a system in the organization that needs to share data with other systems.

Used by Integration Hub.

application ingestion and replication task

A task that propagates data from source objects in a Software-as-a-Service or an on-premises application to targets. The task can transfer a point-in-time snapshot of all source data to a target. The task can also incrementally propagate only the records that contain data changes on a continuous basis.

Used by Data Ingestion and Replication.

array of structs

An array data type where each element is a struct data type.

Used by Data Integration.

asset

An object that contains usable information about your data or about processes that apply to your data. You can create, read, update, and delete assets.

Can be used by all services.

asset discovery

The processes of understanding the shape of the data that you ingest into your organization and deriving actionable insights from the data.

Used by Data Governance and Catalog.

asset enrichment

The process of adding business context, custom attributes, ratings, and tags to cataloged data assets to make them more discoverable, understandable, and usable.

Used by Business 360 Console, Data Governance and Catalog, Data Quality.

asset group

An organizational category that you can assign as an attribute to assets. Use an asset group within an access policy to control access to multiple assets in a single operation. Create an asset group in Metadata Command Center. You can create asset groups in a hierarchical manner so that one asset group is a parent to others.

Used by Data Governance and Catalog, Data Marketplace.

automap

A feature in Data Integration that automatically links source and target fields in transformations and tasks. The Automap menu contains two options: Exact Field Name and Smart Map. Runs at the field level.

Used by Data Integration.

auto-match

The process of automatically running the match process to identify duplicate records. Runs at the entity level.

Used by Master Data Management.

auto-scaling

The ability to dynamically increase the amount of computational resources when needed.

In Operational Insights, administrators define auto-scaling policies based on CPU utilization or memory consumption thresholds for nodes within a grid. Each time the processes running in the grid exceed a threshold, Operational Insights executes a script to provision a node in the cloud and add it to the grid.

In Data Integration, advanced clusters can auto-scale by dynamically increasing or decreasing the number of cluster nodes and cluster storage.

Used by Data Integration, Operational Insights.

B

blurring

A range of output values within a fixed variance or percent variance of numeric or date source data that you can configure in a masking rule. You can configure blurring properties to restrict masked data to within a fixed or percent deviation from source data.

Used by Data Integration.

bundle

A set of data integration templates that you can use in your organization.

Can be used by all services.

business asset

An asset that you create in Data Governance and Catalog to document a business concept. You can use business assets to add business context to technical assets.

Use business assets to perform governance activities such as establishing organizational processes and complying with industry or statutory regulations.

Business assets include glossaries, policies, and domains.

Used by Data Governance and Catalog.

business entity

An entity of importance to your organization, such as people, places, or things. A business entity is an implementation of a master data domain. For example, within the context of a health care organization, the Customer master data domain might be implemented in the form of a Patient business entity.

Used by Master Data Management.

business entity record

An instance of information that is organized into a business entity. For example, John Smith is a business entity record for the Person business entity.

Used by Master Data Management.

C

catalog source

An object that represents the source system from which you can extract metadata and data facts. Amazon S3 and Oracle are examples of source systems.

Used by Data Governance and Catalog, Metadata Command Center.

catalog source accelerator

A catalog source that supports complex environments. You can use catalog source accelerators to extract metadata from systems that are difficult to analyze and require a more sophisticated configuration.

To enable and configure a catalog source accelerator, you need assistance from Informatica Professional Services.

Examples of catalog source accelerators include SAS Base Programs and IBM Mainframe Job Control Language.

Used by Data Governance and Catalog, Metadata Command Center.

catalog source job

A job that you run against a source system based on the configured catalog source. When Metadata Command Center runs a catalog source job, it creates and runs a task for each configured capability.

Used by Metadata Command Center.

category

A grouping of related data collections with a common theme that helps consumers browse for and find relevant data.

Used by Data Marketplace.

CDI-PC domain

The fundamental administrative unit for a collection of nodes and services in Cloud Data Integration for PowerCenter.

Used by Cloud Data Integration for PowerCenter.

CDI-PC Integration Service

An on-premises application service that runs sessions and workflows that you create in the Cloud Data Integration for PowerCenter client.

Used by Cloud Data Integration for PowerCenter.

CDI-PC repository

A database that stores metadata created by the Cloud Data Integration for PowerCenter client and application services.

Used by Cloud Data Integration for PowerCenter.

CDI-PC Repository Service

An on-premises application service that manages the Cloud Data Integration for PowerCenter repository. It retrieves, inserts, and updates metadata in the repository database tables.

Used by Cloud Data Integration for PowerCenter.

change data capture

The process of capturing changes that were made to source databases, tables, and data sets for transmission to a target.

Used by Data Ingestion and Replication.

change stream

The stream of change records that PowerExchange reads from a CDC source or PowerExchange Logger for Linux, UNIX, and Windows log files.

Used by Connectors, Data Ingestion and Replication, Data Integration, PowerExchange.

character labeling

A data operation that searches for character patterns in an input field and writes a descriptive label as output for each pattern found. You configure character labeling in a labeler asset.

Used by Data Quality.

checkout

The steps taken by a data consumer to order a data collection.

Used by Data Marketplace.

checkpoint

Recovery information that PowerExchange generates and that the Data Integration service and CDC client store on the target system so that a mapping task can resume the extraction of change records from where it last left off.

Used by Connectors, Data Integration, Data Ingestion and Replication, PowerExchange.

CLAIRE

A suite of autonomous digital assistants designed to augment enterprise data management. CLAIRE agents harness advanced AI reasoning and planning models to automate complex data operations and achieve end-to-end data management goals.

Can be used by all services.

cleanse asset

An asset that standardizes the form and content of your data to render the data more accurate, usable, and consistent. Configure a cleanse asset to remove unwanted values from data fields, replace the values, or convert the character case of the values.

Used by Data Quality.

cleansing

The process of standardizing data to a correct or desired format while correcting anomalies and errors in the data. Configure cleansing operations in a cleanse asset in Data Quality.

Used by Data Quality.

Cloud Data Integration for PowerCenter (CDI-PC)

An IDMC service that you can use to manage and monitor the status of Cloud Data Integration for PowerCenter domains and assess and convert repository assets.

Used by Cloud Data Integration for PowerCenter.

Cloud Server

A runtime environment that is hosted on the cloud. You deploy Cloud Application Integration assets to the Cloud Server or to a Secure Agent.

Used by Application Integration.

cluster

The records in a data set that a Deduplicate transformation identifies as potential duplicates of one another.

Used by Data Integration, Data Quality.

cluster lifecycle

The sequence of changes that occurs as a Secure Agent creates a Secure Agent cluster, scales the cluster up or down, stops the cluster, and applies changes in the advanced configuration to the cluster when the cluster starts up again. Each point in the cluster lifecycle is a cluster event.

See also *Secure Agent cluster*.

Can be used by all services.

code list

A set of reference data that comes from the same application, industry standard list, or internal list. You organize code lists into reference data sets.

Used by Reference 360.

code value

A unique value, such as a business term, code, or lookup value. A code value is the lowest representation of reference data. You create code values in code lists.

Used by Reference 360.

collector

A service that collects data, such as job and workflow statistics, performance metrics, and configuration metadata, from components in an Informatica domain monitored by Operational Insights. Collectors run within the Secure Agent that enables communication between an Informatica domain and IDMC.

Used by Operational Insights.

complex data type

A data type that allows you to represent multiple data values in a single row or column position.

Used by Data Integration.

complex file

Contains semi-structured data in text, XML, JSON, sequence files, or binary files such as PDF, Microsoft Word, and Microsoft Excel.

Used by Connectors, Data Integration.

complex operator

A type of operator that can access elements in a complex data type.

Used by Data Integration.

connection

An object that you configure to provide access to data in applications, platforms, databases, and flat files.

Can be used by all services.

connection assignment

The linking of catalog sources to establish lineage between the source systems that the catalog sources represent.

Used by Metadata Command Center.

consolidation

The process of building a single record from a set of matching records. The consolidated record is sometimes known as the survivor record.

Used by Data Quality, Master Data Management.

consumer access

A record that indicates a data consumer's access to a data collection, along with other details such as the date of delivery, stakeholders, and the delivery option that was used for the delivery.

Used by Data Marketplace.

contributor

A version of a source record or an edit record that contributes data to a master record.

Used by Master Data Management.

control flow

A conditional dependency between assets in a lineage. A control flow is a relationship between two fields, where one field's value influences how data is produced, filtered, or aggregated, without the source data being copied to the target.

Used by Data Governance and Catalog.

crosswalk

A visual representation of value mappings between code values in a pair of code lists. Crosswalks exist between code lists in the same reference data set.

Used by Master Data Management, Reference 360.

D

data access control

A policy that grants users access to assets based on user-defined conditions in an external system. For example, Data Governance and Catalog pushes this policy into your external system. The external system enforces the policy directly.

Used by Data Governance and Catalog.

data access control rule

A rule that grants a user access to assets based on user-defined conditions in an external system.

Used by Data Governance and Catalog.

Data Access Management Agent

A component within the Secure Agent that implements, configures, or enforces policies regarding access to data.

Used by Data Governance and Catalog.

Data Access Management Proxy

A component within the Secure Agent that grants or restricts data access when a user submits a request for data in a SQL query through the JDBC client driver.

Used by Data Governance and Catalog.

data access policy

A set of rules that you can use to protect data and control access to your data. Data access controls, data filters, and data de-identifications are all data access policies.

Used by Data Governance and Catalog.

data access rule

A process within a data access policy that evaluates user, usage, or metadata context in relation to a data source and generates an action to enforce that policy and protect or control access to that data.

Used by Data Governance and Catalog.

data asset

A representation of data in an organization.

You can represent any form of data, including flat files and database tables, as a data asset in Data Marketplace.

Used by Data Marketplace.

data catalog

An indexed, centralized, searchable inventory of metadata extracted from different external sources across cloud, on-premises, and hybrid environments in your organization.

Used by Data Governance and Catalog and Metadata Command Center.

data classification

The process of identifying the semantics of data elements, entities, and policies in a data container. The Data Classification capability applies classification to the elements or entities based on the facts collected from a source system. For example, the service classifies the column in a specific table as Email or SSN or Credit card.

Used by Metadata Command Center.

data collection

A collection of one or more data assets. A data consumer can order a data collection to request access to the data.

Used by Data Marketplace.

data collection request

A request made by a data consumer for a new data collection.

If a consumer cannot find a data collection that meets their requirements, they can submit a data collection request. Stakeholders of the category or data collection in which the request is placed review the request and respond as necessary.

Used by Data Marketplace.

data de-identification

A policy that protects sensitive data attributes based on user-defined conditions.

Used by Data Governance and Catalog.

data de-identification rule

A rule that applies pre-defined data protections to data based on user-defined conditions.

Used by Data Governance and Catalog.

data discovery

The process of searching for and finding assets in a data catalog.

Used by CLAIRE GPT.

data element

The smallest unit of data that is present in your organization.

In Data Marketplace, a group of one or more related data elements forms a data asset.

Used by Data Marketplace, Data Governance and Catalog.

data exploration

The process of understanding data, such as previewing sample data and asking questions about the data, to assess if the data meets expectations.

Used by CLAIRE GPT.

data fact

A fact about the data contained in data elements and entities.

A data fact represents the outcome of a data profiling task that you configure for a catalog source. The facts include statistics such as frequent values and mean, median, and inferred data types. Data facts can also refer to derived facts, such as the signature of a column (for example, MinHash) and to other facts, such as whether the data is continuous or categorical.

Used by Metadata Command Center.

data filter policy

A policy that identifies records to withhold from a data asset based on user-defined conditions.

Used by Data Governance and Catalog.

data filter rule

A rule that omits records based on user-defined conditions.

Used by Data Governance and Catalog.

Data Integration Server

A Secure Agent service that performs data integration jobs for Data Integration. Data integration jobs include previewing data and running mappings, tasks, and taskflows.

Can be used by all services.

data model

A definition of the structure of data.

In Master Data Management, a data model defines the structure of business entities, reference data, and hierarchies. A single data model can cover multiple master data domains.

Used by Master Data Management.

data profiling

A process of assessing source metadata and viewing the collected column data statistics to discover details of content and structure, such as value distribution, patterns, and data types.

Used by Data Profiling, Metadata Command Center.

data profiling task

A task that determines the characteristics of the columns in a data source, such as value frequency, patterns, and data types. You create and run a data profiling task on a data source to assess source data and metadata and view the collected column data statistics.

Used by Data Profiling.

data protection

An asset that defines one or more privacy-enhancing techniques that can de-identify data.

Used by Data Governance and Catalog.

data quality rule

A rule created in Data Quality that is referred to in Data Governance and Catalog.

Used by Data Governance and Catalog.

data quality rule occurrence

The representation of a data quality rule that originates in Data Quality and that runs on a data element in Data Governance and Catalog.

Used by Data Governance and Catalog.

data quality rule template

The semantic representation in Data Governance and Catalog of a data quality rule that originates in Data Quality.

Used by Data Governance and Catalog.

data quality score

The results, whether individual or aggregate, of a data quality rule that originates in Data Quality and that runs on one or more data elements in Data Governance and Catalog.

Used by Data Governance and Catalog.

data set

A collection of data.

In Data Governance and Catalog, the business representation of one or more data assets from your source systems is a data set. For example, if your organization stores employee records in a database table called 'Employees,' you can create an "Employees" data set within the "HR" system in Data Governance and Catalog. You can create a data set out of several related data assets, so that you can enrich them with business or governance context.

Used by all services.

data subset

A subset of production data that is small, targeted, and referentially intact. You can run a masking task to create a data subset. The masking task maintains primary and foreign key relationships in the subset data and reconciles the object relationships in the subset data.

Used by Data Integration.

database ingestion and replication task

A task that propagates data from source objects in a database management system (DBMS) to targets. The task can transfer a point-in-time snapshot of all source data in a schema to a target. The task can also incrementally propagate only the rows that contain data changes on a continuous basis.

Used by Data Ingestion and Replication.

deduplicate asset

An asset that measures the degrees of similarity between the records in a data set in order to find duplicate records. Optionally, consolidates duplicate records into a single, preferred version of the record.

The asset logic is optimized for identity data. An identity is a group of data values in a record that identify a person or an organization.

Used by Data Quality.

deduplication threshold

The lowest match score that can identify two records as duplicates of each other. You set a threshold score in a deduplicate asset.

Used by Data Quality.

de-identification technique

A function you can use to de-identify data. Examples include retain, generalize date, and redact with NULL.

Used by Data Governance and Catalog.

delivery target

An available location for the delivery of data related to a particular data collection, along with the format and method in which the data will be made available at that location.

For example, a stakeholder for a collection might specify an Amazon S3 bucket as a delivery location in a data collection's delivery target.

Used by Data Marketplace.

delivery template

The description of a type of location where a data collection can be delivered to a consumer in response to an order, including the available formats and methods for data in that location.

An administrator typically creates and manages delivery templates in Data Marketplace. The templates are typically consistent with the physical repositories where the data can be accessed, for example in a data warehouse or a report mart.

Used by Data Marketplace.

dependent code list

A code list that contains code values that depend on code values from a code list in a different reference data set. For example, the California code value in the CRM State Code List depends on the USA code value in the CRM Countries Code List.

Used by Reference 360.

dependent reference data set

A reference data set that depends on code values in another reference data set. Code lists inherit the dependency from the reference data set. For example, the CRM State Code List depends on the CRM Countries Code List.

Used by Reference 360.

dictionary

A reference data set that you can use to evaluate the usefulness or accuracy of the values in a data column.

A dictionary might contain a single column that represents the standard or required versions of a set of data values. When a dictionary contains two or more columns, one column contains the standard or preferred values and the additional columns contain alternative versions of the values.

Used by Data Quality.

dictionary file

A flat file containing data that substitution masking rules use to mask source data. A masking task that contains the substitution masking rule performs a lookup on the specified dictionary. It replaces source data with data from the dictionary to mask the data.

Used by Data Integration.

directed AI match rule

A set of conditions and business entity fields that are required to identify duplicate records in Master Data Management.

Used by Master Data Management.

domain

A data category that is managed at the enterprise level to support semantic consistency across an organization.

In Master Data Management, data is categorized into master data domains that are critical to an organization. Common master data domains include Customer, Supplier, Partner, Location, Product, Asset, Finance, and General Ledger Account.

In Data Governance and Catalog, a domain is a collection of concepts and activities grouped logically by business functions or requirements. A domain is a term in the root category, and it may contain hierarchical terms. For example, "finance" is a domain, under which there can be hierarchical terms such as "retail finance", "corporate finance", and "investment banking".

Used by Master Data Management, Data Governance and Catalog.

domain management app

A Secure Agent application that runs behind the customer firewall and is responsible for communication between the domain and Informatica cloud. Handles back-end tasks required for Cloud Data Integration for PowerCenter domain updates.

Used by Cloud Data Integration for PowerCenter.

Domain Management Service

A microservice that runs in IDMC. It is responsible for jobs related to registering domains, managing domains, and tasks that you perform on the Cloud Data Integration for PowerCenter home page.

Used by Cloud Data Integration for PowerCenter.

drill down

The display of the rows of source data that a value, data type, or pattern in profiling results represents.

Used by Data Profiling.

driver score

The match score between the current record and the driver record in a set of matching records. Use a Deduplicate transformation in a mapping to find the matching records. The transformation returns the score on the Out_DriverScore field.

Used by Data Integration, Data Quality.

duplicate record

A record that is identical or similar in significant ways to a record it's being matched against. The match process identifies duplicate records, also known as matching records.

Used by Master Data Management, Data Quality.

E

edit record

A type of record that Master Data Management creates when you edit a master record in Master Data Management. An edit record is similar to a source record.

Used by Master Data Management.

elastic runtime environment

A type of runtime environment that uses elastic scaling to optimize resource management. Use an elastic runtime environment to handle fluctuating workload demands and manage workload costs.

Used by Data Integration.

Elastic Server

A Secure Agent service that pushes data integration jobs to an advanced cluster for processing and manages the cluster.

Used by Data Integration.

embedded guide

A guide that can be accessed from within another guide.

Used by Application Integration.

event

An action that takes place at a point in time, such as starting a process, saving a change, sending a message. An event may also be an anomaly observed in the data.

Used by Data Governance and Catalog, Data Integration, Integration Hub, Master Data Management.

exact match

A one hundred percent match between two values.

In Data Integration, the Exact field name option automatically maps fields with the same name.

In a deduplicate asset in Data Quality, the Filter Exact Duplicates option determines whether pairs of identical records pass directly to the next stage at run time without additional analysis.

In Master Data Management, exact match is a strategy that matches records based on identical values in a set of fields that an administrator defines. The matching records represent the same entity, even if other fields in the record contain different values.

See also *fuzzy match*.

Used by Data Integration, Data Quality, Master Data Management.

exception

A record identified in a data quality rule that falls below the threshold limit for a score that is considered acceptable.

Used by Data Governance and Catalog, Data Quality.

expression editor

A tool that you use to create expressions using fields and functions.

Used by Application Integration, Data Integration.

extension

A package of pre-configured assets that accelerates the implementation of a business application and extends its capabilities.

Used by Master Data Management, Reference 360.

F

fault handling

The configuration of a process to account for an exception or an unanticipated condition that occurs during a process flow. With fault handling, a predictable result always occurs.

Used by Application Integration.

file ingestion and replication task

A Data Ingestion and Replication task that transfers a large number of files of different types between on-premises and cloud repositories.

Used by Data Ingestion and Replication.

file listener

A mechanism that monitors files in a defined location and notifies an asset when a file event occurs, such as when a new file arrives in the monitored folder or the files in the monitored folder are updated or deleted. Use a file listener as a scheduling option in taskflows, file ingestion and replication tasks, and B2B Gateway partner flows.

Used by Data Ingestion and Replication, Data Integration.

file transfer task

A task that performs actions on inbound files that a service receives from file servers or on outbound files that a service sends to file servers. For example, you can decompress and decrypt inbound files or encrypt and compress outbound files. You can use REST APIs to run file transfer tasks, or you can trigger them from B2B Gateway.

Used by Administrator, B2B Gateway.

flatten

The process of creating a row for each hierarchical data element in an array or struct.

Used by Data Integration.

fulfillment

The process of providing access to data that a data consumer has requested.

Used by Data Marketplace.

full load

A type of load where an entity or task processes data for all rows of the source objects.

In Data Integration, a replication task that runs in full load mode truncates the target database tables and performs a full data refresh from the source.

In Cloud Integration Hub, a publication that runs in full load mode writes a full snapshot of the data to the topic.

Used by Data Integration, Integration Hub.

fuzzy match

A way to determine if two different strings are similar enough to constitute a match. Fuzzy match can match strings that differ due to the presence of spelling variations, spelling or typing errors, common abbreviations, and acronyms.

A fuzzy match algorithm calculates a value that represents the similarity between the two strings. The value is called the match score or alternatively, in Master Data Management, the edit distance. Values match when the match score meets or exceeds a match threshold.

See also *exact match*.

Used by Data Integration, Data Quality, Master Data Management.

G

glossary

A dictionary of business or technical concepts that are categorized by domains, subdomains, or other themes that are relevant for the business.

Used by Data Governance and Catalog.

guide

A set of screens or steps that prompts users to review, enter, or confirm data. For example, a step might display account details and prompt the user to confirm the status of a sales call.

See also *step*.

Used by Application Integration.

H

hierarchical code list

A code list that supports hierarchical data structures. You can arrange its code values into levels to create hierarchies.

Used by Reference 360.

hierarchical data

A set of data that is hierarchically related. The hierarchical relationship is represented in a schema.

Used by Data Integration.

hierarchical mapper

A component that maps a hierarchical schema to another hierarchical schema. For example, you can map the XML output of a parser data service for industry solutions to a target XSD file.

Used by Data Integration.

hierarchical reference data set

A reference data set that supports hierarchical data structures. Code lists inherit the hierarchical structure from the reference data set. You can arrange code values in a hierarchical reference data set into levels to create hierarchies.

Used by Reference 360.

hierarchy

In Master Data Management, the relationships that exist among or between business entities and reference data.

Used by Master Data Management.

historical record

An older version of a master record or contributor. When a master record is updated, the updated version is the new master record, and the existing master record becomes a historical record.

Used by Master Data Management.

hop

In a lineage, the distance between the seed asset and a connected asset, expressed as a number.

Used by Data Governance and Catalog.

Hosted Agent

A runtime environment that runs Data Integration tasks that use certain connectors. The Informatica Cloud Hosted Agent (Hosted Agent) is hosted at an Informatica cloud hosting facility.

Used by Data Integration.

human task

A WS-BPEL 2.0 specification that allows human workflow activities within a BPEL process with Process Developer.

Used by Application Integration, Master Data Management.

I

incremental load

A type of load where an entity or task processes data for new rows and the rows that have changed since the last processing.

Used by Business 360, Data Ingestion and Replication, Data Integration, Integration Hub.

inferred data type

Data type that the data profiling task derives for a data source column based on the column data or column title.

Used by Data Profiling.

Informatica Cloud Hosted Agent

See *Hosted Agent*.

Used by Data Integration.

Informatica Cloud Secure Agent

See *Secure Agent*.

Used by all services.

Informatica Cloud Secure Agent Manager

A program used to manage the Informatica Cloud Secure Agent on Windows.

Used by all services.

ingress process

The process that imports data from source systems into the Business 360 data store.

Used by Business 360.

initial and incremental load

A type of operation where an application ingestion and replication job or database ingestion and replication job first loads a point-in-time snapshot of data from a source to a target and subsequently replicates insert, update, and delete changes to the target until the job is stopped or terminates.

Used by Data Ingestion and Replication.

inplace masking

An operation that masks source data in the same system from which it reads the data.

Used by Data Integration.

instream masking

An operation that masks data from a source system to a target system in a single pass.

Used by Data Integration.

intelligent prompt completion

The ability to provide suggestions in a prompt based on the conversation history.

For example, intelligent prompt completion can suggest asset names, stakeholder names, and user names to quickly reference in a prompt.

Used by CLAIRE GPT.

intelligent structure model

An asset that enables you to determine the underlying patterns in a sample file and auto-generate a model for files with the same data and structure. The model can be used to transform and parse structured and semi-structured data.

Used by Data Integration.

IPU

A unit of measurement for customer transactions. Customers consume IPUs when they run jobs in IDMC.

Used by all services.

J

job

A set of one or more operations that a service performs. In some services, such as Data Ingestion and Replication and Master Data Management, a job is an executable instance of a task or process. In other services, such as Data Integration, a job is the work done at run time based on the instructions in a task or process.

Used by all services.

L

labeler asset

An asset that evaluates the types of information that the values in an input field represent. The asset assigns a descriptive label to each value that it recognizes. Use a labeler asset to identify usable and non-usable data values in a data column.

Used by Data Quality.

lineage

The tracking of the flow of data from one or more systems to another system.

In Data Governance and Catalog, lineage gives a visual representation of the data flow from its origin to its destination. This flow includes the dependencies of the data, the various processes that the data undergoes, and how the data is transformed along the way.

In Master Data Management, lineage refers to the versions of source records from different source systems that contribute to a master record.

Used by Data Governance and Catalog, Master Data Management.

linear taskflow

An asset that allows you to group multiple tasks. You can run a linear taskflow immediately or on a schedule. The tasks in a linear taskflow run serially in the specified order.

Used by Data Integration.

link score

The match score between two records that a Deduplicate transformation links together as good matches. The transformation returns the score on the Out_LinkScore field.

Used by Data Integration, Data Quality.

M

managed access

An option in Data Marketplace that determines whether data access management operations create a unique delivery location for each order. Select the option when you define a delivery template in Data Marketplace. If you enable the option, data access management operations customize the data that the

stakeholder of a data collection delivers according to the data access policies defined for your organization.

Used by Data Marketplace.

managed service

A service for which you can manage and monitor API access with usage policies and analytics.

Used by API Manager.

mapping

An asset that defines data flow logic that you can use in mapping tasks to analyze, extract, transform, and load data.

Used by Data Integration.

mapping task

A task that allows you to process data based on the data flow logic defined in a mapping.

Used by Data Integration.

mapplet

Transformation logic that you can create and use to transform source data before it is loaded into the target.

Used by Data Integration.

mask rule parameter

A placeholder for a value that you can use when you configure a Data Masking transformation object in a mapping. A mask rule parameter can hold masking technique information that you can add when you run the mapping instead of when you create the mapping.

Used by Data Integration.

masking rule

A built-in masking type that you can apply to a selected field in a masking task. You choose the masking rule based on the data type of the field that you want to mask. The masking rule contains the logic to mask the data.

Used by Data Integration.

masking task

A task that creates realistic test data from production source data. The format of the original columns and relationships between the rows are preserved in the masked data. A masking task can include data filters to create a subset or mapplets for the masking logic.

Used by Data Integration.

masking techniques

Types of data masking that you can apply to a column when you use the Data Masking transformation.

Used by Data Integration.

master data

The core entities and data that are critical to the operations of an organization. For example, master data can include customer, product, employee, and location data.

Used by Master Data Management.

master data domain

An area of data critical to the organization that is managed at the enterprise level to support semantic consistency across the organization. Common master data domains include Customer, Supplier, Location, Channel, Partner, Product, Asset, and General Ledger Account.

Used by Master Data Management.

master record

A record that represents a single, trusted view of a customer, product, supplier, or other entity. You create a master record by identifying duplicate records and consolidating them into a single record.

Used by Master Data Management.

match rule

A rule that defines the criteria by which to match records.

Used by Master Data Management.

match score

A score assigned to a pair of matched records. Match scores are based on match rules. A high score indicates a close match.

Used by Data Integration, Data Quality, Master Data Management.

matching

The process of comparing records based on a set of criteria or rules and identifying duplicate records.

In Master Data Management and Data Quality, the matching process identifies duplicates and also identifies related records.

Used by Data Quality, Master Data Management.

matching record

A record that is identical or similar to another record. All matches might not be duplicates.

Used by Data Quality, Master Data Management.

merge

The process to consolidate similar records into a single master record.

See also *consolidation*.

Used by Master Data Management.

merge candidate

A potential contributor to a master record. Merge candidates can be included or excluded from the merge process.

Used by Master Data Management.

metadata exploration

The process of exploring, viewing, and understanding the metadata of assets across IDMC with CLAIRE GPT.

Used by CLAIRE GPT.

monitoring rule

A rule that specifies assets to monitor, the event statuses that trigger actions, and the actions to take when an event is in a defined status.

Used by B2B Gateway, Integration Hub.

most frequent values

Values that appear frequently in a column relative to other values.

Used by Data Profiling.

multidomain

The mastering of critical data across multiple master data domains concurrently. Multidomain MDM encompasses related master data domains that are central to an organization’s business and business processes. The observations that arise out of multidomain master data are of significant interest to business executives.

Used by Master Data Management.

N

native data type

Data types specific to the source and target databases or flat files.

Used by Data Integration.

nested data type

A complex data type that contains other complex data types.

Used by Data Integration.

O

orchestration flow

A control flow for an AI agent's lineage. The flow represents the relationship created when one asset invokes, triggers, or communicates with another asset. Examples of such calls include an agent call to an API or MCP tool, a capability call to another capability, or an agent call to another agent.

Used by Data Governance and Catalog.

order

A record that indicates a data consumer's request for access to a data collection, along with other details such as date, business purpose, delivery format, and delivery details.

Used by Data Marketplace.

organization

A secure area within the IDMC repository that stores your licenses, user accounts, data integration assets such as mappings and tasks, and information about jobs and security. Based on your license, you might have access to one organization or to a parent organization and one or more sub-organizations.

Can be used by all services.

organization administrator

An IDMC user configured with the Admin role who has full access to the organization. The organization administrator is responsible for managing the organization and performing administrative tasks, such as configuring runtime environments, configuring the organization profile, and managing organization

security. If the organization has multiple users with the Admin role, the organization administrator is the lead administrator.

Can be used by all services.

P

parse asset

An asset that categorizes the values in an input field based on the types of information that the values represent and writes each value to an output field dedicated to its information type. Use to organize unfielded data into discrete columns with consistent data values.

Used by Data Quality.

partner

An external or internal entity that sends documents for processing in B2B Gateway or receives documents after processing in B2B Gateway.

Used by B2B Gateway.

pattern outlier

An outlier that a data profiling task identifies based on the data patterns in the column.

Used by Data Profiling.

permission

Access rights to individual assets. You assign permissions to users or user groups.

Can be used by all services.

persistence

The amount of information that is passed from one step to another in a Cloud Application Integration process.

Used by Application Integration.

pipeline

A set of actions that read data from a source and write the data to a target.

In Data Integration, a mapping contains one or more pipelines. The Secure Agent separates a mapping pipeline into pipeline stages and then performs the extract, transformation, and load operations for each pipeline stage in parallel.

Used by CLAIRE GPT, Data Integration.

POD

The modular set of components that together constitute an IDMC instance that users can connect to. A POD contains the networking, compute, storage, and application services that IDMC uses.

Used by all services.

policy pushdown

A feature in which data access management policies push a data access control into an external system. The external system enforces the data access control directly.

Used by Data Governance and Catalog.

PowerCenter task

A task that runs a PowerCenter workflow that you import into Data Integration.

Used by Data Integration.

precedence tier

An ordered grouping of data de-identification policies that determines the priority and sequence in which the policies are applied. You assign de-identification policies to a precedence tier.

Used by Data Governance and Catalog.

primitive data type

A data type that allows you to represent a single data value in a single row or column position.

Used by Data Integration.

privilege

Access rights to product features or types of assets. You assign privileges to roles.

Can be used by all services.

Process Designer

A web interface that you can use to create Cloud Application Integration assets.

Used by Application Integration.

Process Developer

An Eclipse-based tool for developers that incorporates the BPMN, BPEL, and BPEL Extensions for People (BPEL4People) standards.

Used by Application Integration.

process object

An asset that groups and structures data.

Used by Application Integration.

Process Server

A component of the Secure Agent that carries out Cloud Application Integration tasks.

Used by Application Integration.

profiling

A process that determines the composition and characteristics of the columns in a source object. Use Data Governance and Catalog for data profiling to discover value frequencies, patterns, and data types in your data.

Used by Data Governance and Catalog, Data Profiling.

publication

An asset that defines the type, format, and schedule of data flow from a data source to the Cloud Integration Hub publication repository.

Used by Integration Hub.

publication repository

A relational database table set that contains published data sets that subscribers can consume.

Used by Integration Hub.

publish

The process of releasing artifacts or data to a wider audience.

Used by Application Integration, Data Integration, Integration Hub, Master Data Management.

R

recipe

A collection of prebuilt, reusable assets that you can use to connect, automate, and standardize business processes that require integration across multiple applications.

Used by Application Integration.

redeploy

The act of deploying an application ingestion and replication job or a database ingestion and replication job again after making certain types of updates to the associated task definition. For example, in the task definition, you can add sources and edit the fields that are available without first undeploying the job. After you make the changes to the task definition, you redeploy the job to restart the job and have the changes take effect.

Used by Data Ingestion and Replication.

reference catalog source

A catalog source that contains references from other source systems along with the source and target tables mapping. When you perform metadata extraction on an ETL catalog source, Metadata Command Center extracts connections from the ETL catalog source and creates a reference catalog source.

Used by Data Governance and Catalog, Metadata Command Center.

reference data set

A logical grouping of reference data. A reference data set represents a category of reference data and acts as a template and container for code lists.

Used by Reference 360.

reference source system

An external source that is referenced by a source system associated with a catalog source. Also called "referenced source system."

Used by Data Governance and Catalog, Metadata Command Center.

related objects

Multiple source objects joined by a relationship defined in the source system or a custom relationship defined in the Source transformation.

Used by Data Integration.

relationship behavior

Relationships configured between parent and child objects. If you select multiple source objects and you apply a data filter in a masking task, you can configure the relationship behavior in the task. A masking task selects all parent records of an object in order to maintain referential integrity. You can configure the behavior to include child objects that you want to include. The results of the task differ based on how you configure the behavior.

Used by Data Integration.

relationship discovery

The inference of relations between assets. For example, relationship discovery identifies related columns and tables in a catalog source and provides recommendations for joining them.

Used by Metadata Command Center.

relationship inference model

A model consisting of user-defined rules and machine learning components. It is used to predict column similarity relationships within a catalog source.

Used by Metadata Command Center.

repeatable output

Deterministic masked output values created when you configure a masking rule with a seed value. A masking task with the same source data and the same seed value returns the same masked values each time it runs.

Used by Data Integration.

replication task

A task that replicates data from Salesforce or database sources to database or file targets. You might replicate data to archive data, perform offline reporting, or consolidate and manage data.

Used by Data Integration.

restart point

The point from which a mapping task starts extracting source change records in logs that contains source data.

In Application Ingestion and Replication or in Database Ingestion and Replication, the start point is the change stream or database log that contains source data from which an ingestion and replication job starts extracting source change records.

Used by Connectors, Data Ingestion and Replication, Data Integration.

role

A set of privileges that you can assign to a user or group.

Can be used by all services.

rule

A process that evaluates a data or metadata input and generates a result that a person or another process can act on.

In Data Governance and Catalog, a rule can trigger an action on metadata access or an action related to data access management.

In Data Quality, rule specifications can be abbreviated to rules.

Used by Data Governance and Catalog, Data Quality.

rule association

An asset that associates business entity fields with a data enhancement rule to validate, cleanse, or enrich data.

Used by Master Data Management.

rule specification

An asset that represents the data requirements of a business rule in logical form. You can define a rule specification with regular expression syntax, or you can configure a rule specification as a process flow in a low-code environment.

Used by Data Quality, Master Data Management.

rule statement

A unit of logic in a basic rule specification. A rule statement is an IF/THEN/ELSE statement that reads an input value and returns an output or a logical decision as a response to the input. Users configure a rule statement in a rule set within a rule specification.

Used by Data Quality, Master Data Management.

runtime environment

The execution platform that run tasks. A runtime environment is either the Informatica Cloud Hosted Agent or a Secure Agent group. You must have at least one runtime environment in each organization so that users in the organization can run tasks.

Can be used by all services.

S

Salesforce Managed Package

An Application Integration package that you install in your Salesforce organization. The Salesforce Managed Package links your organization and Salesforce organizations. Use the Salesforce Managed Package to create and run Salesforce-related assets.

Used by Application Integration.

sampling option

The process to determine whether to run a data profiling task on all rows or on a limited number of rows.

Used by Data Profiling.

saved query

A Data Integration object that you can create from one or more source database tables. You can use a saved query as the source object in a synchronization task. For example, you might create a saved query to include source filters or to perform a complicated join of multiple tables.

Used by Data Integration.

schema graph

A graphical representation of the relationships between multiple source objects in a masking task.

Used by Data Integration.

Secure Agent

A lightweight program that runs tasks and collects metadata for IDMC. A Secure Agent enables secure communication across the firewall between IDMC and your organization or a cloud computing services environment. A Secure Agent runs within a Secure Agent group.

Can be used by all services.

Secure Agent cluster

A Secure Agent group with a master Secure Agent. All agents within a cluster share the master agent's PostgreSQL database.

Can be used by all services.

Secure Agent group

A type of runtime environment that consists of one or more Secure Agents.

Can be used by all services.

Secure Agent machine

The machine that runs the Secure Agent.

Can be used by all services.

seed asset

An asset for which a data lineage is generated and displayed.

Used by Data Governance and Catalog.

seed value

A starting point for creating repeatable output in masked data. Assign the same seed value to related columns and use key masking to enforce consistent masking.

Used by Data Integration.

segment matching

A process that limits match analysis in Master Data Management to specific subsets or segments of data based on attribute values.

Used by Master Data Management.

serverless runtime environment

A type of runtime environment that a service in IDMC creates and manages. For example, Data Integration creates and manages a serverless runtime environment that you can use to run tasks based on mappings.

A serverless runtime environment doesn't require the download or maintenance of a Secure Agent or Secure Agent group. The IDMC service creates the serverless runtime environment in Informatica's cloud environment and connects it to your cloud environment.

Used by Data Integration.

service

A component at the sub-product level that runs within IDMC. For example, Administrator, Application Integration, Data Integration, Monitor, and Operational Insights are individual services that run within IDMC.

Can be used by all services.

service endpoint

A REST or SOAP service URL that is available when you publish a process or connection, for example in Application Integration. You can invoke a service endpoint in a browser or a client or embed the service endpoint within another application.

Can be used by all services.

singleton master record

A master record that's derived from a single source record but that might have patch records from multiple source systems.

Used by Master Data Management.

Smart Map

An auto-match option that leverages CLAIRE intelligence to map fields with similar names. Also known as "fuzzy match."

Used by Data Integration.

source filter characters

The source characters that you want to mask or the source characters that you want to skip masking, based on the source filter type. Each character is case-sensitive.

Used by Data Integration.

source record

A record that originates from an external system or from changes made within Master Data Management. Source records from multiple source systems can contribute to the master record. A source record can have multiple versions.

Used by Master Data Management.

SQL ELT mode

A mapping mode that writes data to a cloud data warehouse and reads data from a source in the same cloud ecosystem or in a compatible hyperscaler. In SQL ELT mode, data processing occurs within the underlying cloud infrastructure. For example, you need to move data in an Azure Data Lake Storage data lake to your Snowflake cloud data warehouse, and you want all the data processing to occur within the Snowflake ecosystem.

Used by Data Integration.

SQL ELT optimization

A runtime optimization method in a mapping task that applies to relational database and cloud data warehouse endpoints. For relational endpoints, you can use SQL ELT optimization to push transformation logic to source or target endpoints within the same ecosystem. For cloud data warehouse endpoints, the source and target can reside within the same ecosystem, or the source can be a data lake from a different cloud ecosystem.

Used by Data Integration.

stakeholder role

A set of privileges that provide access to an asset or asset type.

In Data Governance and Catalog and Data Marketplace, a user with the stakeholder role can have granular access to assets based on the policies configured in Metadata Command Center.

In Reference 360, stakeholder roles are predefined roles that provide asset-specific privileges. An asset might be a reference data set, code list, or crosswalk.

Used by Data Governance and Catalog, Data Marketplace, and Reference 360.

step

One or more links that you add to an asset, process, or guide.

In Application Integration, examples include a Data Decision step, Parallel step, and Assignment step.

In Data Quality, you configure steps in a cleanse asset.

Used by Application Integration, Data Quality.

streaming ingestion

The ingestion of data at scale from any streaming data source, such as logs, clickstream, social media, and IoT sources. You can perform streaming ingestion in the Data Ingestion and Replication service.

Used by Data Ingestion and Replication.

streaming ingestion and replication task

A Mass Ingestion task that transfers real-time streaming and machine data from selected sources to selected messaging systems and batch targets.

Used by Data Ingestion and Replication.

subdomain

A division within a domain hierarchy that represents concepts and activities. A subdomain separates definitions across relevant themes.

Used by Data Governance and Catalog.

sub-organization

A hierarchical group of resources, environments, or teams under a parent organization. A sub-organization enables enterprises to segment projects, control user permissions, and enforce policies across different business units, regions, or development stages.

Can be used by all services.

subprocess

A process embedded within another process.

Used by Application Integration.

subscription

An asset that defines the type, format, and schedule of data flow from the Informatica Cloud Integration Hub publication repository to a data target.

Used by Integration Hub.

synchronization task

A Data Integration task that synchronizes data between a source and target. A synchronization task loads data and integrates applications, databases, and files. Includes add-on functionality such as custom queries and mapplets.

Used by Data Integration.

system service

A built-in connection in Application Integration. For example, email service and messaging service. You can use a system service within a guide or process.

Used by Application Integration.

T

tag

An asset property that you can use to group or filter assets. Create tags to filter assets that share a common attribute on the Explore page.

In B2B Gateway, you can also use tags to filter events on the Events page.

Can be used by all services.

target filter characters

The characters that you want to use in masked data or the characters that you do not want to use in masked data, based on the values of the target filter type. Configure the target filter character property in key or random string masking.

Used by Data Integration.

task

An asset that you configure to analyze, extract, transform, and load data. You can configure and run different types of tasks. For example, in Cloud Data Integration, you can run a synchronization task that reads sales leads from your sales database and writes them into Salesforce.

Used by CLAIRE GPT, Data Ingestion and Replication, Data Integration, Data Profiling.

taskflow

A Data Integration workflow that consists of multiple tasks linked together. You can use a taskflow to run multiple tasks in sequential order or run multiple parallel sets of tasks, either on demand or according to a schedule.

Used by Data Integration.

technical asset

An asset that contains metadata about an object in a source system. The objects that technical assets represent include catalog sources, databases, tables, columns, and views. Collectively, the technical assets represent the data landscape of the source system.

A metadata extraction job creates technical assets when it extracts metadata from a source system. Users do not create technical assets but can enrich them to add business context about the source data.

Used by Data Governance and Catalog.

token

A string that a labeling or natural language processing operation recognizes as a discrete value. A token is commonly a word, but any delimited string can be a token.

Used by Data Quality.

token labeling

A data operation that searches for values in an input field and writes a descriptive label as output for each value found. You configure token labeling in a labeler asset.

Used by Data Quality.

topic

An asset that represents a data domain that applications publish and consume through the hub.

See also *domain*.

Used by Integration Hub.

transformation

An object in a mapping that analyzes, modifies, or passes data. Transformations also define the data source that the mapping reads and the data target that the mapping writes to.

Used by Data Integration.

transformation data type

A set of data types that appear in transformations. They are internal data types, based on ANSI SQL-92 generic data types, which the Secure Agent uses to move data across platforms. Transformation data types appear in all transformations in a mapping.

Used by Data Integration.

U

undeploy

The act of dissociating an application ingestion and replication job or database ingestion and replication job from a Secure Agent. The undeploy operation removes all job information, including monitoring statistics, and frees up the storage space that the job used. If you undeploy an ingestion and replication job and then want to run the job again, you must deploy the task again.

Used by Data Ingestion and Replication.

unmasking

The intentional reversal of a data de-identification technique's effect on masked data to return it to its raw state.

Used by Data Governance and Catalog.

usage type

The context within which a data consumer can use the data for which they are granted access.

In Data Marketplace, a usage type is a configurable list of possible uses for data. Stakeholders of data collections can specify the intended use of their data collections so that potential data consumers can decide whether the data collection is suitable for them. Data consumers can use usage types to cite their intention when they order a collection.

Used by Data Marketplace.

user

An IDMC user account that allows secure access to an organization. A user can perform tasks in the organization based on the role assigned to the user or to the user group that the user is a member of.

Can be used by all services.

user-defined function

A user-created, reusable function that you can use in expressions. You create a user-defined function to build a complex expression using the IDMC transformation language. User-defined functions use the same syntax and can use the same transformation language components as transformation and field expressions.

Used by Data Integration.

V

valid column

The column in a dictionary that contains the preferred version of a data value. Contrasts with the other columns in the dictionary, which may contain alternative or unwanted versions. You select the valid column when you add the dictionary to an asset in Data Quality. You can select any column as the valid column, depending on your data concerns.

Used by Data Quality.

value frequency

The number of times a value appears in a source column, expressed as a number or percentage.

Used by Data Profiling.

value frequency outlier

An outlying value that a data profiling task identifies based on the values or frequencies in a column.

Used by Data Profiling.

verifier asset

An asset that verifies and improves the structure and content of contact data. In its current implementation, you can use a verifier to verify and improve address record data.

Used by Data Quality.

W

workflow

A process that orchestrates a sequence of steps to manage and approve organizational change. Use workflows to design and visualize the changes and ensure compliance. Workflows allow frequent repetition of steps in a clear and consistent manner and provide evidence that the steps are followed every time the workflow is run.

Used by Data Governance and Catalog, Master Data Management, Metadata Command Center.

CHAPTER 3

Analogous Informatica and Salesforce terms

Several concepts and features in IDMC have a similar function and purpose in Salesforce Data 360. If you use both IDMC and Data 360, or if you are interested in using the tools together, you can use this glossary to as a reference.

The following table lists some of the analogous features across IDMC and Salesforce Data 360:
Note: Some features do not demonstrate a 1:1 functional match.

Salesforce term	Definition	Informatica term	Definition
credit	An increment of usage that's deducted as you interact with consumption-based products like Data 360.	IPU	A unit of measurement for customer transactions. Customers consume IPUs when they run jobs in IDMC.
data governance	A framework for securing and managing data through the combined use of tags, classifications, user attributes, and policy-based governance.	data governance	A framework of rules, standards, and processes that ensures data is consistent, trustworthy, and used appropriately across an organization. Data governance establishes the policies and accountability required to manage data quality and security throughout the data lifecycle.
data share	A data share provides easy access for external systems (called data share targets) to use data from Data 360 via data lake objects (DLOs), data model objects (DMOs), or calculated insight objects (CIOs)	delivery target	An available location for the delivery of data related to a data collection, along with the format and method in which the data will be made available at that location. For example, a stakeholder for a data collection might specify an Amazon S3 bucket as a delivery location in a data collection's delivery target.
data space	A logical partition to organize your data for profile unification, insights, and marketing in Data 360. You can segregate your data, metadata, and processes into categories, such as brand, region, or department, and then enable users to see and work on data only in the context of their category.	asset group	An organizational category that you can assign as an attribute to assets. Create asset groups in Metadata Command Center. You can create asset groups in a hierarchical manner so that one asset group is a parent to others.

Salesforce term	Definition	Informatica term	Definition
data stream	A connection and associated data ingested or connected to Data 360. A data stream can be based on batched data or data ingested in near real-time.	streaming ingestion	The ingestion of data at scale from any streaming data source, such as logs, clickstream, social media, and IoT sources. You can perform streaming ingestion in the Data Ingestion and Replication service.
data transform	A feature that combines, shapes, cleans, and preps your data directly in Data 360.	cleansing	The process of standardizing data to a correct or desired format while correcting anomalies and errors in the data. Configure cleansing operations in a cleanse asset in Data Quality.
external data source	An external data source specifies how to access an external system. Salesforce Connect uses external data sources to access data that's stored outside your organization. Files Connect uses external data sources to access third-party content systems.	connector	A component within IDMC that provides access to data in cloud and on-premises applications, platforms, databases, and flat files for the purposes of ingesting and integrating data and applications.
functional domain	The functional domain refers to Salesforce's public cloud infrastructure where your instance is located.	POD	The modular set of components that together constitute an IDMC instance that users can connect to. A POD contains the networking, compute, storage, and application services that IDMC uses.
identity resolution	The process of identity management by means of matching and reconciling data about people and organizations into a comprehensive view called unified profiles. Identity resolution is powered by rulesets and creates unified and link objects.	master data management	The process of identifying and consolidating duplicate records across an organization by matching and merging data about customers, products, suppliers, and other entities into a single, trusted view called a master record.
object	An object allows you to store information in your Salesforce organization. The object is the overall definition of the type of information you're storing. For each object, your organization has multiple records that store the information about specific instances of that type of data.	business entity	An entity of importance to your organization, such as people, places, or things. A business entity is an implementation of a master data domain. For example, within the context of a health care organization, the Customer master data domain might be implemented in the form of a Patient business entity.
reconciliation rule	A user-defined rule that determines which source the system uses when creating a unified profile.	directed AI match rule	A set of conditions and business entity fields that are required to identify duplicate records in master data management.
unified profile	A profile that contains reconciled and linked data across multiple sources using identity resolution rulesets.	master record	A record that represents a single, trusted view of a customer, product, supplier, or other entity. You create a master record by identifying duplicate records and consolidating them into a singe record.

INDEX

C

Cloud Application Integration community
  URL 4
Cloud Developer community
  URL 4

D

Data Integration community
  URL 4

I

Informatica Global Customer Support
  contact information 5
Informatica Intelligent Data Management Cloud
  web site 4

M

maintenance outages 5

S

status
  IDMC 5
system status 5

T

trust site
  description 5

U

upgrade notifications 5

W

web site 4