Informatica® Cloud Data Integration for PowerCenter

October 2026

Troubleshooting

Informatica Cloud Data Integration for PowerCenter Troubleshooting
October 2026

© Copyright Informatica LLC 2023, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices and AI assistant acknowledgements are included with the product.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-10-15

Table of Contents

Preface 4

Informatica Resources 4

- Informatica Documentation 4
- IDMC web site 4
- IDMC Communities 4
- IDMC Marketplace 4
- Data Integration connector documentation 5
- Informatica Knowledge Base 5
- IDMC Trust Center 5
- IDMC Pulse Dashboard 5
- Informatica Global Customer Support 5

Chapter 1: Troubleshooting CDI-PC errors 6

Operating system patch and library errors 6

Domain registration and validation errors 7

Domain deregistration errors 9

Update domain errors 9

CDI-PC installer errors 13

CDI-PC Client errors 13

General errors 14

Chapter 2: Troubleshooting Kerberos authentication 15

Chapter 3: Troubleshooting asset conversion errors 17

Chapter 4: Troubleshooting privileges and roles 18

Appendix A: CDI-PC domain log files 20

Index 21

Preface

Refer to *Troubleshooting* for information about troubleshooting errors in Cloud Data Integration for PowerCenter (CDI-PC).

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

IDMC web site

You can access the Informatica® Intelligent Data Management Cloud™ (IDMC) web site at http://www.informatica.com/cloud.

IDMC Communities

Use the IDMC Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the IDMC Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

IDMC Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

IDMC Trust Center

The IDMC Trust Center provides information about Informatica security, compliance, and privacy practices.

You can access the trust center at https://trust.informatica.com/.

IDMC Pulse Dashboard

The IDMC Pulse Dashboard provides system status and upgrade information for all PODs and services across IDMC.

Follow the services you use and subscribe to alerts to receive notifications about upgrades, maintenance, production incidents, and upcoming releases. The IDMC Pulse Dashboard displays the production status of all the IDMC products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single service or all IDMC services. Subscribing to all services is the best way to be certain you never miss an update.

For more information, see the Service Status and Communications guide.

Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the IDMC Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

Troubleshooting CDI-PC errors

If you encounter any issue when working with the CDI-PC domain, use the following information to troubleshoot the issue.

Operating system patch and library errors

Consider the following troubleshooting tips for CDI-PC operating system patches and library errors:

On Red Hat Enterprise Linux 9 hosts, enabling the repository service fails with the following error:

```
2024-04-24 20:56:45.178 IST : ERROR : (20468 | Domain Monitor) : (Domain | Service Manager) : node01 : SPC_10008 : Service process [RS_SQL] generated the following output error: [/root/Informatica/platform/home/server/bin/pmrepagent: error while loading shared libraries: libnsl.so.1: cannot open shared object file: No such file or directory]. Check the service logs also for more information.
```

Workaround: This error occurs if the `libnsl.so` package doesn't exist in the Linux operating system. Install the `libnsl.so.1` package and restart the CDI-PC Repository Service.

On Red Hat Enterprise Linux 9 hosts, the `defineDomain` command fails with the following error: `OutPut : [ICMD_10033] Command [defineDomain] failed with error [[INFASETUP_10002] Cannot create the domain because of the following error: /export/home/svcoca/Informatica/platform/home/server/bin/libpmjrepn.so: libidn.so.11: cannot open shared object file: No such file or directory.].`

This error occurs if `libidn.so.*` package doesn't exist in the Linux operating system.

Solution: Install the `libidn.so.11` package and create a softlink as follows:

```
/usr/lib64 : ln -s libidn.so.12.6.3 libidn.so.11
```

Run the `definedomain` command again.

For more information, see the following Informatica Knowledge Base article:

https://knowledge.informatica.com/s/article/000195755

On Windows, the CDI-PC emergency bug fix (EBF) installer fails with `findstr` error.

Solution: Add `C:\Windows\System32` to the system PATH variable, then run the EBF installer as an administrator in a new command session.

When you run `dmlistenerlauncher.bat` **on Windows 11, the Listener Service fails to generate time stamps for log entries.**

The `dmlistenerlauncher.bat` uses the `wmic os get localdatetime` command to get time stamps. Microsoft deprecated the Windows Management Instrumentation command-line utility (WMIC) and removed it from supported versions of Windows 11.

Workaround: In `dmlistenerlauncher.bat`, replace the `wmic os getlocaldatetime` command with the following sample code:

```
powershell -NoProfile -Command "Get-Date -Format yyyyMMddHHmmss"
```

Domain registration and validation errors

Consider the following troubleshooting tips when you register or validate a CDI-PC domain:

Error message: `com.informatica.isp.tools.cloudconnect.exception.DomainAuthenticationException: User is not authorized to perform the operation. Check the cloud connect logs`

This error appears when the registered domain user doesn't have administrator privileges.

Solution: Register the domain user with administrator privileges. For more error details, see the CloudConnect logs.

Error message: `The request failed because of error [Connection refused (Connection refused)]. Please ensure the requested host and port are correct and the process is running on the requested port.`

This error appears when a CDI-PC domain is unavailable.

Solution: Restart the CDI-PC domain or node. For more error details, see the Domain Management App log file.

Error message: `The request failed because of error [Connection refused (Connection refused)]`

This error occurs when you can't connect to a CDI-PC domain.

Solution: Resolve the network connectivity issue and try again. For more error details, see the Domain Management App log files.

Error message: `Requested Domain name did not match with the domain name`

Solution: Verify that the domain name of the on-premises domain matches the domain name provided in Informatica Cloud. For more error details, see the CloudConnect logs.

Error message: `None of the agents is able to handle the request`

This error appears when the Secure Agent is not available.

Solution: Restart the Secure Agent.

Error message: `The request failed because of error [No trusted certificate found in the trust stores to verify the server certificate chain.]. Please ensure the Keystore and Truststore are configured correctly and the process is running on the requested port.`

This error appears when you don't import the domain certificate to the Domain Management App.

Solution: To enable communication between the Domain Management App and the domain, both the truststore certificates must be shared and available. Verify that the Domain Management App contains the domain truststore and the domain certificates folder contains the Domain Management App certificate.

For more error details, see the Domain Management App log and CloudConnect log files.

Error message: `The domain with Display Name my_domain is in invalid state for Modification`

This error appears when the CDI-PC domain status fluctuates between Available and Offline modes when you edit the domain details.

Solution: Wait for the Domain Management App to restart. For more error details, see the Domain Management App log files.

Error message: `The request failed because of error [ilabsdxtqa76-23: Name or service not known]. Please ensure the requested host and port are correct and the process is running on the requested port.`

This error appears when you couldn't connect to the CDI-PC domain because the host name is not correct.

Solution: Verify that the CDI-PC domain host name is correct. For more error details, see the Domain Management App log files.

Error message: `The request failed because of error [Connection timed out (Connection timed out)]. Please ensure the requested host and port are correct and the process is running on the requested port.`

This error appears when you couldn't connect to the CDI-PC domain because the port number is not valid.

Solution: Verify that the CDI-PC domain port number is valid. For more error details, see the Domain Management App log files.

Error message: `Request failed due to client error with status code [404 NOT_FOUND]. Please ensure the requested host and port are correct and the process is running on the requested port.`

This error appears when you couldn't connect to the CDI-PC because the `AC_PORT` number is used instead of the node port number.

Solution: Use the correct CDI-PC domain port number.

You can find the correct port number in the `domain.info` file in the following location:

`<CDI-PC installation directory>/Informatica/platform/home`

For more error details, see the Domain Management App log file.

Error message: `The request failed because of error [No trusted certificate found in the trust stores to verify the server certificate chain.]. Please ensure the Keystore and Truststore are configured correctly and the process is running on the requested port.`

This error appears when the Secure Agent truststore or keystore path is not valid.

Solution: Verify that the path and password of the Secure Agent truststore and keystore are valid.

Verify that you have imported the CDI-PC domain truststore to the Domain Management App. Similarly, import the Domain Management App truststore to the CDI-PC domain truststore.

For more error details, see the Domain Management App log file.

After you update the CDI-PC domain to October 2025, the Domain Management App fails at startup. The Agent core log file contains the following error:

```
tid="28" tn="LifecycleManagerFactoryDefault-akka.actor.default-dispatcher-2" ERROR
[com.informatica.saas.lcm.lcmnative.ApplicationWorker] -
[Domain_Management_App-202510.1.3.1] Deploy script deploy-wrapper.bat failed to
execute: ProcessResult [EXITED_NONZERO, exit code=900, command=D:\Secure_Agent
```

```
\install\apps\Domain_Management_App\202510.1.3.1\.lcm\deploy-wrapper.bat]
2025-07-29 13:44:41,359 BST  tid="28" tn="LifecycleManagerFactoryDefault-
akka.actor.default-dispatcher-2" INFO [agentAuditLogger] - [LCM_10004]
Domain_Management_App-202510.1.3.1 encountered an error during deployment:
[Domain_Management_App-202510.1.3.1] Deploy script deploy-wrapper.bat failed to
execute: ProcessResult [EXITED_NONZERO, exit code=900, command
```

This error appears when the file paths for the keystore and truststore on Windows systems contain a single backslash. The single backslash (\) is treated as an escape character and can lead to incorrect path interpretation.

Solution: Use double backslashes (\\) in the file path. This ensures the system parses the path correctly.

Error: `Domain is not connected to IDMC`

This error appears when the CDI-PC domain is not available or the connection with IDMC is lost.

Check the CDI-PC domain status in IDMC. If the status shows as offline or deregistered, then see the CloudConnect log file for more details.

- If the CDI-PC domain is not available, run the `infacmd.sh` startup to restore the domain.
- If the Secure Agent is not available, enable the Secure Agent by running the `infaagent.sh startup` command.

See Appendix A, " CDI-PC domain log files" on page 20 for the log file paths of each component of a CDI-PC domain

Domain deregistration errors

Consider the following troubleshooting tips when you deregister a CDI-PC domain:

Error: `com.informatica.isp.tools.cloudconnect.exception.DomainAuthenticationException: User is not authorized to perform the operation. Check the cloud connect logs`

This error appears when the registered domain user doesn't have administrator privileges required to deregister the domain.

Solution: Register the domain user with administrator privileges. For more error details, see the CloudConnect logs.

See Appendix A, " CDI-PC domain log files" on page 20 for the log file paths of each component of a CDI-PC domain.

Update domain errors

Consider the following troubleshooting tips when you update a CDI-PC domain:

When you initiate an update of a CDI-PC domain running as a Windows service, the domain starts in the process mode instead of the service mode.

Reason: With the April 2026 update, CDI-PC has upgraded its JDK to version 17 and Tomcat to version 10. As a result, certain registry properties associated with Windows CDI-PC domains are configured to run as a service updates. CDI-PC creates these service-specific registry entries during domain setup.

However, you can't modify the service-specific registry entries during the update process from the CDI-PC Home page due to permission limitations on the Windows host. Consequently, after a successful domain update, your domain might start in process mode instead of service mode.

Solution:

1. After the domain is updated successfully, use the following command to stop the CDI-PC service on the target Windows system where you want to start the domain as a Windows service.

   ```
   INFA_HOME/tomcat/bin/infaservice.bat shutdown
   ```

2. Run the following command to remove the CDI-PC service:

   ```
   INFA_HOME/tomcat/bin/infaservice.bat remove "InformaticaCDI-PC"
   ```

3. Run the following command to reinstall the CDI-PC service:

   ```
   INFA_HOME/tomcat/bin/infaservice.bat install "InformaticaCDI-PC" "Informatica
   CDI-PC"
   ```

When you migrate a non-TLS PowerCenter domain with HTTPS enabled for the Administrator tool to CDI-PC, the UpdateDomainOptions command fails.

Solution:

1. Before you start the migration process, shut down all nodes except the first gateway node. It is mandatory to shut down all nodes except the gateway node during migration.
2. Run the UpdateDomainOptions command to convert the domain from non-SSL to SSL mode:

   ```
   infacmd UpdateDomainOptions -dn <DOMAIN_NAME> -pd <DOMAIN_PASSWORD> -un
   <DOMAIN_USER> -do TLSMode=true -sdn <SECURITY_DOMAIN_NAME>
   ```

   For detailed instructions on how to run the UpdateDomainOptions command, see UpdateDomainOptions.

Error: No such file or directory error is being logged during `wait_for_node_shutdown` command

After you register a multi-node CDI-PC domain and perform an update operation, the update is successful. However, the taskoutput.log file contains the following error:

```
2024-07-30 15:39:53.692    INFO: [cf-task-pool-5][commandframework.TaskExecutor]
[reqid:6E8WC6ayXzuix6r8vls2ac] [DML_20003] Subtask ID [wait_for_node_shutdown]
started.
2024-07-30 15:39:53.692   ERROR: [cf-task-pool-1][commandframework.TaskExecutor]
[reqid:6E8WC6ayXzuix6r8vls2ac] [DML_30001] Command [/data/Informatica/cdipc/
202410_update_hardening/master/Informatica/platform/home/isp/bin/plugins/ms/
clientgateway/msgateway.sh stopservice] failed. Error: [Cannot run program "/data/
Informatica/cdipc/202410_update_hardening/master/Informatica/platform/home/isp/bin/
plugins/ms/clientgateway/msgateway.sh": error=2, No such file or directory]
2024-07-30 15:39:53.693    INFO: [cf-task-pool-5][commandframework.TaskExecutor]
[reqid:6E8WC6ayXzuix6r8vls2ac] [DML_30003] Node service operation [shutdownAndWait]
started.
2024-07-30 15:39:53.695   ERROR: [cf-task-pool-1][commandframework.TaskExecutor]
[reqid:6E8WC6ayXzuix6r8vls2ac] [DML_30001] Command [/data/Informatica/cdipc/
202410_update_hardening/master/Informatica/platform/home/isp/bin/plugins/wfs/cmdgw/
wfsgw.sh stopservice] failed. Error: [Cannot run program "/data/Informatica/cdipc/
202410_update_hardening/master/Informatica/platform/home/isp/bin/plugins/wfs/cmdgw/
wfsgw.sh": error=2, No such file or directory]
2024-07-30 15:39:53.695    INFO: [cf-task-pool-1][commandframework.TaskExecutor]
[reqid:6E8WC6ayXzuix6r8vls2ac] [DML_20005] Subtask ID [stop_gateway_services]
succeeded.
```

You can ignore this error.

Error: `The request failed because of error [Connection refused (Connection refused)]. Please ensure the requested host and port are proper and the process is running on the requested port.`

This error appears when update fails because you couldn't connect to the CDI-PC domain.

Updating the CDI-PC domain fails because of one of the following reasons:

- The CDI-PC domain is unavailable before the Listener service starts. Restart the CDI-PC domain and retry the update process manually.
- There is no communication between IDMC and the CDI-PC domain. Resolve the network issues and retry the update process manually.
- CDI-PC domain node is unavailable. Restart the node and retry the update process manually.

For more error details, see the Domain Management App log file.

Error: `/export/home/ispqa/<user_name>/Node1/Informatica/platform/sys/apps/listener/202308/dmlistenerlauncher.sh (Permission denied)`

This error appears when update fails in the Initialize stage because the `dmlistenerlauncher` script doesn't have correct permissions to run the script.

Solution: Assign `execute (755)` permission to the `dmlistenerlauncher` script and retry the update process manually. For more error details, see the CloudConnect log file.

Error: `INFO: [`

`][commandframework.TaskExecutor] [reqId=85e0157411a142139df8330009883ca1] [DML_30051] Required disk space [10,000MB]. Available disk space [1,788MB]. 2023-05-09 15:36:32.079 ERROR: [cf-task-pool-1][commandframework.TaskExecutor] [reqId=85e0157411a142139df8330009883ca1] [DML_30052] Required disk space is unavailable.`

This error appears when update fails because the required amount of disk space is not available on the node.

Solution: Create the required amount of disk space (a minimum of 10 GB) and retry the update. For more error details, see the taskoutput log file.

Error: `[DML_20010] Task [Downloading patch] failed on node [node01] in host]. Please check the Listener logs of the node [node01] for more details. For more details, view the LISTENER logs in listener. <System log directory>/listener/DMLTaskOutputError in taskoutput log`

This error appears when update fails because the CDI-PC binaries are not available in the Secure Agent.

Solution: Make sure that the Secure Agent contains the appropriate binaries. For more error details, see the taskoutput log file.

Error: `[pool-3-thread-2][commandframework.TaskExecutor] [reqId=deee669b67064b07979e742c4cd17842] [DMU_10009] Can't download the file. ERROR: [Connection reset]`

This error appears when update fails because you can't connect to a CDI-PC domain.

Solution: Resolve the connectivity issue between the CDI-PC domain host and Secure Agent host. For more error details, see the taskoutput log file.

Error: `Regarding 2023-06-14 12:31:10.520 ERROR: [cf-task-pool-4][commandframework.TaskExecutor] [reqId=46ef9dcbdf5740e09c895c4fc7cff614] [DML_30065] Unexpected file found in extracted installer directory. 2023-06-14 12:31:10.520 WARN: [cf-task-pool-4] [commandframework.TaskExecutor] [reqId=46ef9dcbdf5740e09c895c4fc7cff614] [DML_20004] Subtask ID [verify_integrity] failed.`

This error appears when update fails as the installer script is corrupted.

Solution: Retry the update process manually. For more error details, see the taskoutput log file.

Error: `INFO: [cf-task-pool-1][commandframework.TaskExecutor] [reqId=a23da466d220418eb626f01a97eac904] [DML_30051] Required disk space [4,000MB]. Available disk space [27MB]. 2023-05-29 13:25:33.774 ERROR: [cf-task-pool-1]`

`[commandframework.TaskExecutor] [reqId=a23da466d220418eb626f01a97eac904] [DML_30052] Required disk space is unavailable.`

This error appears when update fails in Pre-update stage because the required amount of disk space is not available on the host.

Solution: Minimum of 4GB disk space is required for the update to run successfully. Create the required amount of disk space and retry the update. For more error details, see the taskoutput log file.

Error: `[/export/home/prodxuser/build189/Node1/Informatica/platform/sys/data/downloads (Permission denied)]`

This error appears when update fails in Download stage because the downloads folder doesn't have appropriate privileges.

Assign correct permissions to the downloads folder and retry the update process manually. For more error details, see the taskoutput log file.

Error: `INFO: [cf-task-pool-1][commandframework.TaskExecutor] [reqId=a23da466d220418eb626f01a97eac904] [DML_30051] Required disk space [4,000MB]. Available disk space [27MB]. 2023-05-29 13:25:33.774 ERROR: [cf-task-pool-1] [commandframework.TaskExecutor] [reqId=a23da466d220418eb626f01a97eac904] [DML_30052] Required disk space is unavailable.`

This error appears when update fails in Updating stage because the required amount of disk space is not available on the host.

Solution: Create the required amount of disk space and retry the update. For more error details, see the taskoutput log file.

Error: `Domain port in use`

This error appears when update fails in Updating stage because the CDI-PC domain port is used by another process.

Solution: Shut down any other process running on the CDI-PC domain port and retry the update. For more error details, see the taskoutput log file.

Error: `The request failed because of error [No trusted certificate found in the trust stores to verify the server certificate chain.]. Please ensure the Keystore and Truststore are configured correctly and the process is running on the requested port.`

This error appears when update fails in Updating stage with a certificate error.

Solution: To enable communication between the Domain Management App and the domain, both the truststore certificates must be shared and available. Verify that the Domain Management App contains the domain truststore and the domain certificates folder contains the Domain Management App certificate.

For more error details, see the Domain Management App log file.

Error: `None of the agents in the agent group can handle the request.`

This error appears when update fails in Updating stage because the Domain Management App is not available.

Solution: Make sure that the Secure Agent is available and running. Retry the update manually. For more error details, see the Domain Management App log file.

Update fails with a connection refused error when the listener is terminated during the updating stage of the master gateway node.

During a multi-node domain update, if the master gateway node listener is terminated during its update stage, the update retries but fails at initialization with a connection refused error. All retry attempts receive the same error.

Solution: Start the master gateway node and retry update.

CDI-PC multinode update fails during the listener start stage with the following error:

```
[catalina-exec-1] [JWTTokenAuthenticationFilter]
[reqid:5b47093f435444929c43ed628ec3c7c4] [CloudConnectCommon_10015] Failed to
validate the token because of
error [{*}Token is not sign by the
domain{*}.]
```

This error appears when you use different private keys in each CDI-PC node keystore file.

Solution: Use the same private keys in each CDI-PC node keystore file.

See Appendix A, " CDI-PC domain log files" on page 20 for the log file paths of each component of a CDI-PC domain.

CDI-PC installer errors

Consider the following troubleshooting tip for CDI-PC installer errors:

The CDI-PC silent installer is unresponsive on AIX with UTF-8 locales

When you run `silentinstall.sh` on IBM AIX systems, the script might hang indefinitely if you set the environment variables LANG or LC_ALL to a multibyte UTF-8 locale, such as en_US.UTF-8.

Note: The third-party information included in Informatica documentation is subject to change without prior notice. Check the vendor's documentation for the most up-to-date information.

Workaround: To run the silent installer on AIX, override the locale. Temporarily set the locale to a standard single-byte ASCII environment, immediately before running the installer, such as C or en_US.

Use the following sample code to set the locale immediately before running the installer:

```
export LANG=en_US
export LC_ALL=en_US
./silentinstall.sh
```

CDI-PC Client errors

Consider the following troubleshooting tip for CDI-PC Client errors:

Error: `[PCSF_46024] SSL has failed because [Peer certificate cannot be authenticated with given CA certificates]`

This error appears when you configure a domain from the CDI-PC Client.

Set the following environment variables in the CDI-PC Client virtual machine:

- INFA_TRUSTSTORE
  1. Copy the SSL related files in binary format from the server location to the CDI-PC Client virtual machine.
  2. Set the environment variable to this location.

- INFA_TRUSTSTORE_PASSWORD
  1. Encrypt the truststore password used by the CDI-PC Client using the `pmpasswd` utility.
  2. Set the environment variable to the the output of `pmpasswd`.

General errors

Consider the following troubleshooting tip when you work with CDI-PC:

When you create a CDI-PC domain using non-ASCII characters in the domain and node names, and configure the CDI-PC Integration Service and CDI-PCRepository Service with the Japanese Extended UNIX Code (including JIS X 0212) code page, the CDI-PC Integration Service fails to enable with a code page mismatch error.

Solution: Align the code pages so they are identical.

- **Option 1 (Recommended)**: Modify the Integration Service code page in the Administrator tool to match the system's locale. Change it from Japanese Extended UNIX Code (including JIS X 0212) to Japanese EUC (packed format).
- **Option 2**: The CDI-PC Integration Service requires Japanese Extended UNIX Code (incl. JIS X 0212) to correctly process and display Japanese characters. Update the LANG and LC_ALL environment variables for the CDI-PC user to a locale that corresponds to the exact code page, and then restart the CDI-PC domain.

Define domain command fails for SSL enabled database with latest Java

When you create a CDIPC domain with SSL enabled database, configure the database to use modern cipher suites, such as ECDHE-based suites. The configuration cannot rely exclusively on TLS_RSA_* for SSL/TLS handshake negotiation. TLS_RSA_* cipher suites are disabled within the CDI-PC domain and can no longer be used for outgoing connections to external servers.

CHAPTER 2

Troubleshooting Kerberos authentication

You can use Kerberos utilities to verify that the service principal and keytab file names created by the Kerberos administrator match the service principal and keytab file names that you requested. You can also use the utilities to determine the status of the Kerberos key distribution center (KDC).

You can use Kerberos utilities such as *setspn*, *kinit*, and *klist* to view and verify the SPNs and keytab files. To use the utilities, ensure that the KRB5_CONFIG environment variable contains the path and file name of the Kerberos configuration file.

Note: The following examples show ways to use the Kerberos utilities to verify that SPNs and keytab files are valid. The examples might be different than the way that the Kerberos administrator uses the utilities to create the SPNs and keytab files required for the CDI-PC domain. For more information about running the Kerberos utilities, see the Kerberos documentation.

Use the following utilities to verify the SPNs and keytab files:

klist

You can use *klist* to list the Kerberos principals and keys in a keytab file. To list the keys in the keytab file and the time stamp for the keytab entry, run the following command:

```
klist -k -t <keytab_file>
```

The following output example shows the principals in a keytab file:

```
Keytab name: FILE:int_srvc01.keytab
KVNO Timestamp         Principal
---- ----------------- --------------------------------------------------------
   3 12/31/69 19:00:00 int_srvc01/node01_vMPE/Domn96_vMPE@REALM
   3 12/31/69 19:00:00 int_srvc01/node01_vMPE/Domn96_vMPE@REALM
   3 12/31/69 19:00:00 int_srvc01/node01_vMPE/Domn96_vMPE@REALM
   3 12/31/69 19:00:00 int_srvc01/node01_vMPE/Domn96_vMPE@REALM
   3 12/31/69 19:00:00 int_srvc01/node01_vMPE/Domn96_vMPE@REALM
```

kinit

You can use *kinit* to request a ticket-granting ticket for a user account to verify that the KDC is running and can grant tickets. To request a ticket-granting ticket for a user account, run the following command:

```
kinit <user_account>
```

You can also use *kinit* to request a ticket-granting ticket and verify that the keytab file can be used to establish a Kerberos connection. To request a ticket-granting ticket for an SPN, run the following command:

```
kinit -V -k -t <keytab_file> <SPN>
```

The following output example shows the ticket-granting ticket created in the default cache for a specified keytab file and SPN:

```
Using default cache: /tmp/krb5cc_10000073
Using principal: int_srvc01/node01_vMPE/Domn96_vMPE@REALM
Using keytab: int_srvc01.keytab
Authenticated to Kerberos v5
```

setspn

You can use *setspn* to view, modify, or delete the SPN of an Active Directory service account. On the machine that hosts the Active Directory service, open a command line window and run the command.

To view the SPNs that are associated with a user account, run the following command:

```
setspn -L <user_account>
```

The following output example shows the SPN associated with the user account `is96svc`:

```
Registered ServicePrincipalNames for CN=is96svc,OU=AllSvcAccts,OU=People,
DC=ds,DC=intrac0rp,DC=zec0rp:
       int_srvc01/node02_vMPE/Domn96_vMPE
```

To view the user accounts associated with an SPN, run the following command:

```
setspn -Q <SPN>
```

The following output example shows the user account associated with the SPN `int_srvc01/node02_vMPE/Domn96_vMPE`:

```
Checking domain DC=ds,DC=intrac0rp,DC=zec0rp
CN=is96svc,OU=AllSvcAccts,OU=People,DC=ds,DC=intrac0rp,DC=zec0rp
        int_srvc01/node02_vMPE/Domn96_vMPE

Existing SPN found!
```

To search for duplicate SPNs, run the following command:

```
setspn -X
```

The following output example shows multiple user accounts associated with one SPN:

```
Checking domain DC=ds,DC=intrac0rp,DC=zec0rp
Processing entry 1125
HOST/mtb01.REALM is registered on these accounts:
        CN=Team1svc,OU=AllSvcAccts,OU=People,DC=ds,DC=intrac0rp,DC=zec0rp
        CN=MTB1svc,OU=IIS,OU=WPC960K3,OU=WINServers,DC=ds,DC=intrac0rp,DC=zec0rp
```

Note: Searching for duplicate SPNs can take a long time and a large amount of memory.

kdestroy

You can use *kdestroy* to delete the active Kerberos authorization tickets and the user credentials cache that contains them. If you run *kdestroy* without parameters, you delete the default credentials cache.

CHAPTER 3

Troubleshooting asset conversion errors

Consider the following troubleshooting tip when you convert your PowerCenter assets to the corresponding assets in Cloud Data Integration:

A conversion job fails with the following error if the Default folder contains Data Integration assets.

```
403 Forbidden: A Mapping task with the same name already exists. Enter a different name.
```

Delete the assets with the same name from the Data Integration Default folder and run the conversion task again.

CHAPTER 4

Troubleshooting privileges and roles

I cannot assign privileges or roles to users for an existing CDI-PC Repository Service.

You cannot assign privileges and roles to users and groups for an existing CDI-PC Repository Service in the following situations:

- The application service is disabled.
- The CDI-PC Repository Service is running in exclusive mode.

I removed a privilege from a group. Why do some users in the group still have that privilege?

You can use any of the following methods to assign privileges to a user:

- Assign a privilege directly to a user.
- Assign a role to a user.
- Assign a privilege or role to a group that the user belongs to.

If you remove a privilege from a group, users that belong to that group can be directly assigned the privilege or can inherit the privilege from an assigned role.

I am assigned all domain privileges and permission on all domain objects, but I cannot complete all tasks in the Administrator tool.

Some of the Administrator tool tasks are determined by the Administrator role, not by privileges or permissions. You can be assigned all privileges for the domain and granted full permissions on all domain objects. However, you cannot complete the tasks determined by the Administrator role.

I am assigned the Administrator role for an application service, but I cannot configure the application service in the Administrator tool.

When you have the Administrator role for an application service, you are an application client administrator. An application client administrator has full permissions and privileges in an application client.

However, an application client administrator does not have permissions or privileges on the Informatica domain. An application client administrator cannot log in to the Administrator tool to manage the service for the application client for which it has administrator privileges.

To manage an application service in the Administrator tool, you must have the appropriate domain privileges and permissions.

I cannot use pmrep to connect to a new CDI-PC Repository Service running in exclusive mode.

The Service Manager might not have synchronized the list of users and groups in the CDI-PC repository with the list in the domain configuration database. To synchronize the list of users and groups, restart the CDI-PC Repository Service.

I am assigned all privileges in the Folders privilege group for the CDI-PC Repository Service and have read, write, and execute permission on a folder. However, I cannot configure the permissions for the folder.

Only the folder owner or a user assigned the Administrator role for the CDI-PC Repository Service can complete the following folder management tasks:

- Assign operating system profiles to folders if the CDI-PC Integration Service uses operating system profiles. Requires permission on the operating system profile.
- Change the folder owner.
- Configure folder permissions.
- Delete the folder.
- Designate the folder to be shared.
- Edit the folder name and description.

APPENDIX A

CDI-PC domain log files

CDI-PC domain log files are stored in the following location: `<CDI-PC Installation Directory>/Informatica/platform/logs`

The following table shows the log file paths of each component in a CDI-PC domain:

Component	Log File Path
Node	- `<CDI-PC installation directory>/Informatica/platform/logs/system_logs/<node_name>/node.log` - `<CDI-PC installation directory>/Informatica/platform/logs/system_logs/<node_name>/catalina.ou`
Cloud Connect	`<CDI-PC installation directory>/Informatica/platform/logs/system_logs/<node_name>/cloudconnect`
Listener service	`<CDI-PC installation directory>/Informatica/platform/logs/system_logs/<node_name>/listener/DML` `dmlistener.log`
Listener Launcher	`<CDI-PC installation directory>/Informatica/platform/logs/system_logs/<node_name>/listener/` `DMListenerLauncherLogs/launcher_log_yyyy-mm-dd.log`
Listener Task	`<CDI-PC installation directory>/Informatica/platform/logs/system_logs/<node_name>/listener/DML` `taskoutput.log`

Installer	- Update: `<CDI-PC installation directory>/Informatica/platform/logs/installer/<release_version>/`
	`Informatica_CDIPC_Services_Update_<release_version>_<component>_<operation>_<reuqest_id>_Inst`
	- EBF: `<CDI-PC installation directory>/Informatica/platform/logs/installer/<EBF_ID>/`
	`CDIPC_EBF_<EBF_ID>_<component>_<operation>_<reuqest_id>_Install.log`

INDEX

C

Cloud Application Integration community
  URL 4
Cloud Developer community
  URL 4

D

Data Integration community
  URL 4

I

Informatica Global Customer Support
  contact information 5
Informatica Intelligent Data Management Cloud
  web site 4

M

maintenance outages 5

S

status
  IDMC 5
system status 5

T

trust site
  description 5

U

upgrade notifications 5

W

web site 4