Informatica® Cloud Data Integration

# Chatter Connector

Informatica Cloud Data Integration Chatter Connector
October 2022

© Copyright Informatica LLC 2016, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, Informatica Cloud, and PowerCenter are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-05-12

# Table of Contents


**Preface** . . . . . 4

Informatica Resources . . . . . 4

- Informatica Documentation . . . . . 4
- Informatica Intelligent Cloud Services web site . . . . . 4
- Informatica Intelligent Cloud Services Communities . . . . . 4
- Informatica Intelligent Cloud Services Marketplace . . . . . 4
- Data Integration connector documentation . . . . . 5
- Informatica Knowledge Base . . . . . 5
- Informatica Intelligent Cloud Services Trust Center . . . . . 5
- Informatica Global Customer Support . . . . . 5

**Chapter 1: Introduction to Chatter Connector** . . . . . 6

Chatter Connector Overview . . . . . 6

Introduction to Chatter . . . . . 6

Supported Features, Objects, and Task Operations . . . . . 7

**Chapter 2: Chatter Connections** . . . . . 12

Chatter Connections Overview . . . . . 12

Chatter connection properties . . . . . 12

Configuring the Proxy Settings on Windows . . . . . 13

- Configuring Proxy Settings through Secure Agent Manager . . . . . 13
- Configuring Proxy Settings through ProxySettings.ini File . . . . . 13

**Chapter 3: Synchronization Tasks with Chatter Connector** . . . . . 15

Chatter Sources in Synchronization Tasks . . . . . 15

- Advanced Source Properties . . . . . 16
- Data Filters . . . . . 16
- Synchronization Task Example . . . . . 16

Chatter Targets in Synchronization Task . . . . . 19

- Synchronization Task Example . . . . . 19

**Chapter 4: Troubleshooting** . . . . . 23

Troubleshooting a Chatter Synchronization Task . . . . . 23

**Chapter 5: Increasing Secure Agent Memory** . . . . . 24

Increasing the secure agent memory . . . . . 24

**Index** . . . . . 26

# Preface

Use *Chatter Connector* to learn how to read from or write to Chatter by using Cloud Data Integration. Learn to create a Chatter connection and run synchronization tasks in Cloud Data Integration.

# Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

## Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

## Informatica Intelligent Cloud Services web site

You can access the Informatica Intelligent Cloud Services web site at http://www.informatica.com/cloud. This site contains information about Informatica Cloud integration services.

## Informatica Intelligent Cloud Services Communities

Use the Informatica Intelligent Cloud Services Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the Informatica Intelligent Cloud Services Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

## Informatica Intelligent Cloud Services Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

## Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

## Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

## Informatica Intelligent Cloud Services Trust Center

The Informatica Intelligent Cloud Services Trust Center provides information about Informatica security policies and real-time system availability.

You can access the trust center at https://www.informatica.com/trust-center.html.

Subscribe to the Informatica Intelligent Cloud Services Trust Center to receive upgrade, maintenance, and incident notifications. The Informatica Intelligent Cloud Services Status page displays the production status of all the Informatica cloud products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single component or all Informatica Intelligent Cloud Services components. Subscribing to all components is the best way to be certain you never miss an update.

To subscribe, on the Informatica Intelligent Cloud Services Status page, click **SUBSCRIBE TO UPDATES**. You can choose to receive notifications sent as emails, SMS text messages, webhooks, RSS feeds, or any combination of the four.

## Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the Informatica Intelligent Cloud Services Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

# Introduction to Chatter Connector

This chapter includes the following topics:


- Chatter Connector Overview, 6
- Introduction to Chatter, 6
- Supported Features, Objects, and Task Operations, 7


## Chatter Connector Overview

You can use Data Integration Chatter Connector to share, fetch, post, and search Chatter feeds and comments from the Salesforce application.

You can use Chatter Connector to perform the following tasks:

- Share information within an organization through end users or applications.
- Fetch Chatter feeds and comments from Salesforce.
- Load Chatter feeds and comments into the Salesforce Chatter application.
- Post a feed in a Chatter account. Also, specify Salesforce objects such as accounts, opportunity, and contact by using Data Integration Chatter Connector.
- Post comments to Salesforce feeds.
- Use filters to retrieve feeds from a Chatter account. Chatter connector supports all the filters such as Equals, Not Equals, Starts With, Ends With, Contains, Is Null, Is Not Null, Less Than, Less than or Equals, Greater Than, and Greater Than or Equals.

You can enable or disable proxy for Chatter Connector.

## Introduction to Chatter

Chatter software connects employees within an organization. You can share knowledge, files, and data. You can also choose to follow individuals users and groups, and receive status updates.

You can use Chatter Connector for collaborative features such as real-time feed updates, user profiles, and feeds.

Chatter Connector user profile helps you to share important information about yourself, and helps other users to learn more about you. You can update your user profile, click the Profile tab within the Salesforce Chatter Application to update your user profile.

You can track feeds with real-time notification for changes to a particular object. The system administrator tracks feeds through Chatter system and customizes feed tracking on an object and field basis.

You can create groups and collaborate between a set of users with Chatter Connector.

For example, if you are working on a project and you want to share information exclusively with your team members, you can create a Chatter group for your team. Chatter Groups can be Public or Private. You can create and join a Public Group. However, you have to ask the Group owner for permission to join a Private Group.

You can also identify the people, groups, and records that closely relate to your job and interests with Chatter recommendations. In addition, users can also like a Chatter post, share files with selected users and view trending topics.

# Supported Features, Objects, and Task Operations

When you create a Chatter connection, you must select the feature that you wish to use. Features are different entities of Chatter Connector. Each feature contains a set of objects under them.

The following table provides a list of features and objects that Chatter Connector supports:

| Objects | Read | Insert | Update | Upsert | Delete | Lookup | Data Preview |
|---|---|---|---|---|---|---|---|
| FeedItem | Yes | Yes | NA | NA | Yes | Yes | Yes |
| FeedComment | Yes | Yes | NA | NA | Yes | Yes | Yes |
| CollaborationGroupMember | Yes | Yes | NA | NA | Yes | Yes | Yes |

| Object | Filter Column | Criteria | Supported | Example |
|---|---|---|---|---|
| FeedItem | CreatedDate | Equals | Y | Support $LastRunTime |
| | | Not Equals | Y | 2012-04-30 00:00:00 |
| | | Less Than | Y | 2012-04-30 00:00:00 |
| | | Less Than/Equals | Y | 2012-04-30 00:00:00 |
| | | GreaterThan | Y | 2012-04-30 00:00:00 |
| | | GreaterThan/Equals | Y | 2012-04-30 00:00:00 |
| | | IsNull | Y | NA |
| | | Is Not Null | Y | NA |
| | Type | Equals | Y | TrackedChange / UserStatus / TextPost / LinkPost /ContentPost/ PollPost/ DashboardComponentSnapshot / ApprovalPost / CollaborationGroupCreated |

| Object | Filter Column | Criteria | Supported | Example |
|---|---|---|---|---|
| | | Not Equals | Y | TrackedChange / UserStatus / TextPost / LinkPost /ContentPost/ PollPost/ ashboardComponentSnapshot / ApprovalPost / CollaborationGroupCreated |
| | | Starts With | N | NA |
| | | Ends With | N | NA |
| | | Contains | N | NA |
| | | Is Null | N | NA |
| | | Is Not Null | N | NA |
| | body | Equals | Y | Informatica |
| | | Not Equals | N | Informatica |
| | | Starts With | Y | Informatica |
| | | Ends With | Y | Informatica |
| | | Contains | Y | Informatica |
| | | Is Null | N | NA |
| | | Is Not Null | N | NA |
| | Id | Equals | Y | 0F7G0000001zMtOKAU |
| | | Not Equals | Y | 0F7G0000001zMtOKAU |
| | | Starts With | N | NA |
| | | Ends With | N | NA |
| | | Contains | N | NA |
| | | Is Null | Y | NA |
| | | Is Not Null | Y | NA |
| | ParentId | Equals | Y | 0F7G0000001zMtOKAU |
| | | Not Equals | Y | 0F7G0000001zMtOKAU |
| | | Starts With | N | NA |
| | | Ends With | N | NA |
| | | Contains | N | NA |

| Object | Filter Column | Criteria | Supported | Example |
|---|---|---|---|---|
| | | Is Null | Y | NA |
| | | Is Not Null | Y | NA |
| | CommentCount | Equals | Y | 5 |
| | | Not Equals | Y | 5 |
| | | Less Than | Y | 5 |
| | | Less Than/Equals | Y | 5 |
| | | Greater Than | Y | 5 |
| | | Greater Than/Equals | Y | 5 |
| | | IsNull | Y | NA |
| | | Is Not Null | Y | NA |
| | IsDeleted | Equals | Y | 1 – “True” & 0 – “False” |
| | | Not Equals | Y | 1 – “True” & 0 – “False” |
| | LikeCount | Equals | Y | 5 |
| | | Not Equals | Y | 5 |
| | | Less Than | Y | 5 |
| | | Less Than/Equals | Y | 5 |
| | | Greater Than | Y | 5 |
| | | Greater Than/Equals | Y | 5 |
| | | IsNull | Y | N/A |
| | | Is Not Null | Y | N/A |
| FeedComment | CommentId | Equals | Y | 0F7G0000001zMtOKAU |
| | | Not Equals | Y | 0F7G0000001zMtOKAU |
| | | Starts With | N | NA |
| | | Ends With | N | NA |
| | | Contains | N | NA |
| | | Is Null | Y | NA |
| | | Is Not Null | Y | NA |

| Object | Filter Column | Criteria | Supported | Example |
|---|---|---|---|---|
| | CommentFeedItemId | Equals | Y | 0F7G0000001zMtOKAU |
| | | Not Equals | Y | 0F7G0000001zMtOKAU |
| | | Starts With | N | NA |
| | | Ends With | N | NA |
| | | Contains | N | NA |
| | | Is Null | Y | NA |
| | | Is Not Null | Y | NA |
| | CommentBody | Equals | Y | Informatica |
| | | Not Equals | N | Informatica |
| | | Starts With | Y | Informatica |
| | | Ends With | Y | Informatica |
| | | Contains | Y | Informatica |
| | | Is Null | N | NA |
| | | Is Not Null | N | NA |
| | CommentType | Equals | Y | ContentComment / TextComment |
| | | Not Equals | N | ContentComment / TextComment |
| | | Starts With | Y | NA |
| | | Ends With | Y | NA |
| | | Contains | Y | NA |
| | | Is Null | N | NA |
| | | Is Not Null | N | NA |
| | CommentInsertedById | Equals | Y | 0F7G0000001zMtOKAU |
| | | Not Equals | Y | 0F7G0000001zMtOKAU |
| | | Starts With | N | NA |
| | | Ends With | N | NA |
| | | Contains | N | NA |
| | | Is Null | Y | NA |

| Object | Filter Column | Criteria | Supported | Example |
|---|---|---|---|---|
| | | Is Not Null | Y | NA |
| | CommentParentId | Equals | Y | 0F7G0000001zMtOKAU |
| | | Not Equals | Y | 0F7G0000001zMtOKAU |
| | | Starts With | N | NA |
| | | Ends With | N | NA |
| | | Contains | N | NA |
| | | Is Null | Y | NA |
| | | Is Not Null | Y | NA |
| | CommentCreatedDate | Equals | Y | Support $LastRunTime |
| | | Not Equals | Y | 2012-04-30 00:00:00 |
| | | Less Than | Y | 2012-04-30 00:00:00 |
| | | Less Than/Equals | Y | 2012-04-30 00:00:00 |
| | | GreaterThan | Y | 2012-04-30 00:00:00 |
| | | GreaterThan/Equals | Y | 2012-04-30 00:00:00 |
| | | IsNull | Y | NA |
| | | Is Not Null | Y | NA |

You can enable proxy settings for Chatter Connector.

CHAPTER 2

# Chatter Connections

This chapter includes the following topics:


- Chatter Connections Overview, 12
- Chatter connection properties, 12
- Configuring the Proxy Settings on Windows, 13


## Chatter Connections Overview

Create a Chatter connection in Data Integration before you use Chatter Connector in a synchronization task.

You can create a Chatter connection on the **Connections** page. When you create the Chatter connection, you can enter the connection attributes that are specific to the Chatter Connector application to which you want to connect. You can use Chatter connections when you create a target object in a synchronization task.

You can specify Secure Agent, User Name, Password, Security Token, Service URL, and Attachment Path in the Chatter connection properties to set up Chatter connection.

## Chatter connection properties

To use the Chatter Connector in a synchronization task, you must create a connection in Data Integration and configure the connection properties.

**Important:** Chatter Connector is deprecated and has been moved to maintenance mode. Informatica intends to drop support in a future release.

The following table describes the Chatter connection properties:

| Connection property | Description |
|---|---|
| Connection Name | Name of the connection. |
| Runtime Environment | The name of the runtime environment where you want to run the tasks. |
| User Name | User name of the Chatter account. |
| Password | Password of the Chatter account. |

| Connection property | Description |
|---|---|
| Security Token | The security token generated from Salesforce. |
| Service URL | The service endpoint URL with the API version. The Chatter Connector supports up to API version 34.0.<br>For example: `https://login.salesforce.com/services/Soap/u/34.0` |
| Attachment Path | The path where the attachments of the feeds need to be copied. |

# Configuring the Proxy Settings on Windows

If your organization uses an outgoing proxy server to connect to the internet, the Secure Agent connects to Data Integration through the proxy server. You can configure the proxy server settings for the Secure Agent on a Windows machine through the Secure Agent Manager or the ProxySettings.ini file.

## Configuring Proxy Settings through Secure Agent Manager

Perform the following steps to enable proxy server through the Secure Agent Manager:

1. Click **Start** > **All Programs** > **Informatica Cloud Secure Agent** > **Informatica Cloud Secure Agent** to launch the Secure Agent Manager.

   You can also click the Data Integration icon in the Windows taskbar notification area to open the Secure Agent Manager.

   The Secure Agent Manager displays the Secure Agent status.
2. Click **Proxy** in the Secure Agent Manager page.
3. Click **Use a Proxy Server** to enter proxy server settings.
4. Configure the following proxy server details:

| Field | Description |
|---|---|
| Proxy Host | Required. Host name of the outgoing proxy server that the Secure Agent uses. |
| Proxy Port | Required. Port number of the outgoing proxy server. |
| User Name | User name to connect to the outgoing proxy server. |
| Password | Password to connect to the outgoing proxy server. |

5. Click **OK**.

   The Secure Agent Manager restarts the Secure Agent to apply the settings.

## Configuring Proxy Settings through ProxySettings.ini File

The Secure Agent creates the `ProxySettings.ini` file when you test the connection.

Perform the following steps to enable the proxy server flag in the `ProxySettings.ini` file:

1. Copy the `ProxySettings.ini` file from the following directory:

   `<Secure Agent installation directory>\downloads\<latest connector package>\package \plugins\Chatter\`

2. Paste the `ProxySettings.ini` file to the following directory:


   `<Secure Agent installation directory>\apps\Data_Integration_Server\ext\deploy_to_main\bin \rdtm-extra\Chatter\`

   **Note:** If the `deploy_to_main\bin\rdtm-extra\Chatter\` directory does not already exist, create the directory.

3. Restart the Secure Agent.

4. Set the value of the **setProxy** field to true to enable the proxy. By default, the value is false.

   The following image shows an example of `ProxySettings.ini` file:



CHAPTER 3

# Synchronization Tasks with Chatter Connector

This chapter includes the following topics:


- Chatter Sources in Synchronization Tasks, 15
- Chatter Targets in Synchronization Task, 19


## Chatter Sources in Synchronization Tasks

You can use a Chatter object as a single source in a synchronization task.

You can configure Chatter source properties on the Source page of the Synchronization task wizard.

The following table describes the Chatter source properties:

| Properties | Description |
|---|---|
| Connection | Name of the source connection. |
| Source Type | Default source type is single. |
| Source Object | Name of the source object. You can choose one of the following source objects when you read data from Chatter:<br>- FeedItem<br>- CollaborationGroupMember<br>- FeedComment |

You need to configure specific advanced properties to use specific source objects in a synchronization task.

## Advanced Source Properties

You can configure the advanced source properties on the Schedule page of the Synchronization Task Wizard.

The following table describes the advanced source properties for a Chatter source object:

| Advanced Source Properties | Description |
|---|---|
| Source Filter | Filter the source data. |
| Sorted Ports | Ports used to sort source data. |
| Maximum Page Size | The maximum number of records read from Chatter in a page.<br>Default is 50. |
| Retry Value | Determines the retry value. |
| TimeOut Value | Determines the timeout value. |

## Data Filters

Use data filters to fetch specific data of a particular object. You can assign a filter field to the object.

Perform the following tasks to use the data filters:

1. In the synchronization task, select the Data Filters tab.

   The Data Filter dialog box appears.
2. Click **New**.

   The Data Filter page where you can define filter appears.
3. Specify the data filter fields as described in the following table:

| Field Type | Description |
|---|---|
| Object | Select object for which you want to assign filter fields. |
| Filter By | Select the filter field. |
| Operator | Select the corresponding operator. |
| Filter Value | Enter the filter value. |

4. Click **OK**.

## Synchronization Task Example

Consider a task to read data from Chatter and write data to a flat file.

**Note:** You need to create a connection before you create a synchronization task.

To set up a synchronization task in Data Integration, perform the following tasks:

1. Go to **New** > **Tasks**.
2. Select **Synchronization Task**, and click **Create**.

The New Synchronization Task page appears.

3. Specify the task name, provide a description, and select the task operation **Insert**.
4. Click **Next**.

   The Source tab appears.
5. Select the source connection, source type, and source object for the task, and click **Next**.

   You can read feed from multiple objects in Chatter.
6. Select the target connection, target type, and target object for the task, and click **Next**.
7. To assign filters to a synchronization task, see "Data Filters" on page 16. To select all rows, click **Data Filters**.

   Use the following filter fields to read feeds from feedItem object:

| Column Name | Description |
|---|---|
| Body | The content of the FeedItem. |
| CommentCount | The number of FeedComments associated with the feed item. |
| ConnectionId | When a PartnerNetworkConnection makes a change to a record that is tracked, the CreatedBy field contains the ID of the system administrator while the Connection Id contains the ID of the PartnerNetworkConnection that performed the changes.<br>Available if Salesforce to Salesforce is enabled for your organization. |
| AttachmentPath | Specifies the location where you want to copy the attachment. |
| ContentDescription | The description of the file to be attached to the feed. |
| ContentFileName | The name of the file uploaded to the feed. |
| ContentSize | The size of the file (in bytes) uploaded to the feed. |
| ContentType | The MIME type of the file uploaded to the feed. |
| Id | Unique Id to indicate a feed. |
| InsertedById | ID of the user that added the object to the feed. |
| IsDeleted | Indicates whether the record has been moved to the Recycle Bin (true) or not (false). |
| LikeCount | The number of FeedLikes associated with the feed item. |
| LinkUrl | To post URL on a feed. |
| ParentId | The ID of the object type to which the FeedItem is related. For example, set this field to a UserId to post to someone's profile feed, or an AccountId to post to a specific account. |
| RelatedRecordId | The ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost. |
| Title | The title of the FeedItem. |

| Column Name | Description |
|---|---|
| Type | The type of FeedItem:<br>- TrackedChange: A change or group of changes to a tracked field.<br>- UserStatus: Automatically generated status when a user adds a post.<br>- TextPost: To post a text on a feed.<br>- LinkPost: To post an URL on a feed.<br>- ContentPost: An uploaded file on a feed.<br>- PollPost: Post a poll in the feed to gather opinions.<br>- DashboardComponentSnapshot: To Post a dashboard snapshot on a feed.<br>- ApprovalPost: Automatically generated by a feed query on an approval item.<br>- CollaborationGroupCreated: Automatically generated post on your feed when you creates a public group. |
| Parent name | Name of the object type to which the FeedItem is related. |

Use the following filter fields to get the feed comments from a FeedComment object in Chatter:

| Column Name | Description |
|---|---|
| CommentBody | The text in the comment |
| CommentType | You can use the following type of comment:<br>- ContentComment : the comment that contains an attachment. The Chatter Connector does not support ContentType comment.<br>- TextComment – A comment that contains only text. |
| CommentFeedItemId | The ID of the feed that contains the comment. |
| CommentInsertedById | The ID of the user who added the object to the feed. |
| CommentParentId | The ID of the record associated with the feed. |
| CommentRelatedRecordId | The ID of the ContentVersion object associated with a ContentComment. |
| CommentCreatedDate | The date and time when the comment was posted. |
| CommentId | The unique Id of the comment. |
| CommentAttachmentPath | Location of the file attached to the FeedComment.<br>**Note:** When you download the attachment and you face an out of memory exception, you must increase the memory. |
| CommentContentSize | The size of the file attached to the FeedComment. |
| CommentContentDescription | The description about the attachment. |

8. In the field mapping tab, map the source fields to the appropriate target fields.
9. Click **Next**.

   The Schedule tab appears.
10. In the Schedule tab, you can schedule the task for each requirement and save.
11. If you do not want to schedule the task, click **Save** to save the task.

You can monitor the status of synchronization tasks in the Monitor log.

# Chatter Targets in Synchronization Task

When you run a synchronization task, specify the operation and the source that you want the Secure Agent to write to the target. The Secure Agent inserts, updates, upserts, or deletes source rows that you specify into the target based on the configured operation for the target object.

The task operations depend on the target object that you select. You can configure the target properties when you schedule the synchronization task. You configure Chatter target properties on the **Target** page of the Synchronization task wizard. Enter the name of the target connection and specify the target object to write data to Chatter.

When you configure a synchronization task, you can configure the advanced target properties. The advanced target properties appear on the **Schedule** page of the Synchronization task wizard.

The following table describes the Chatter advanced target properties:

| Advanced Target Properties | Description |
|---|---|
| Success File Directory | Directory for the Chatter success rows file.<br>Specify a directory path that is available on each Secure Agent machine in the runtime environment. |
| Error File Directory | Directory for the Chatter error rows file.<br>Specify a directory path that is available on each Secure Agent machine in the runtime environment. |

**Note:** When you create a task to delete data from Chatter and data in the input file does not match with data in the target table, the task does not fail.

## Synchronization Task Example

Perform the following actions to post comments or feeds to Chatter:

**Note:** You need to create a connection before you create a synchronization task.

1. Click **New** > **Tasks**.
2. Select **Synchronization Task**, and click **Create**.

   The New Synchronization Task page appears.
3. Specify the task name, description, and select the task operation **Insert**.

   To delete a feed or comment from Chatter select delete operation.
4. Click **Next**.


   The Source tab appears.
5. Select the source connection, source type, and source object.

   The source object should contain the following fields when you post feeds or comments to Chatter or delete feeds or comments from Chatter:

### User Feed

Specify the type as TextPost and mention the content of the post in the body.

| Body | Type | LinkUrl | ParentId | Title | RelatedRe | ContentFileName | AttachmentPath | ContentDescription |
|---|---|---|---|---|---|---|---|---|
| Testing for user text post | TextPost | | | | | | | |




### Account Feed

To post an account feed, you must specify the Parent Id.


| Body | Type | LinkUrl | ParentId | Title | RelatedRecordId | ContentFileName | AttachmentPath | ContentDescription |
|---|---|---|---|---|---|---|---|---|
| Posting Feed under an account | TextPost | | 001G000000na9Th | | | | | |




### Content Post

Specify the type as ContentPost to attach a file to the feed.

| Body | Type | LinkUrl | ParentId | Title | RelatedRecordId | ContentFileName | AttachmentPath | ContentDescription |
|---|---|---|---|---|---|---|---|---|
| Testing Content Post | ContentPost | | | Sample | | chatter.txt | C:/Test/ | testing |




### Search Tag Feed

To add a search tag in a feed, you must append # to the keyword. The following image shows details of search tag feed:

| Body | Type | LinkUrl | ParentId | Title | RelatedRecordId | ContentFileName | AttachmentPath | ContentDescription |
|---|---|---|---|---|---|---|---|---|
| Testing Search #ABC 1 | TextPost | | | | | | | |
| Testing Search #ABC 2 | TextPost | | | | | | | |
| Testing Search #ABC 3 | TextPost | | | | | | | |
| Testing Search #ABC 4 | TextPost | | | | | | | |




### Delete Feed

To delete a feed, select FeedItem object as a target in Data Integration. To delete a feed comment select FeedComment object as a target in Data Integration. You must specify the FeedID to delete feeds and commentID to delete feed comments from Chatter.

6. Select the target connection, target type, and target object for the task. To post feeds to Chatter, select FeedItem object. To post feed comments to Chatter, select FeedComment object. Click **Next**.
7. To assign filters to a synchronization task, see "Data Filters" on page 16. To select all rows, click **Data Filters**, and then click **Next**.

   In the data filters tab, you can use the following filter fields:

| Column Name | Description |
|---|---|
| ParentId | ID of the object type to which the FeedItem is related. For example, set this field to a UserId to post to someone's profile feed, or an AccountId to post to a specific account. |
| Body | The message that appears in the feed. If you want to post a feed with the search keyword. In the feed make use of the # character before the search keyword. For example, if your search keyword is ABC, specify '#ABC'. |
| Type | You can select the following type of FeedItem:<br>- TrackedChange: A change or group of changes to a tracked field.<br>- UserStatus: Automatically generated status when a user adds a post.<br>- TextPost: Text entry on a feed.<br>- LinkPost: Post an URL on a feed.<br>- ContentPost: An uploaded file on a feed.<br>- PollPost: Post a poll in the feed to gather opinions.<br>- DashboardComponentSnapshot: Post a dashboard snapshot on a feed.<br>- ApprovalPost: Automatically generated by a feed query on an approval item.<br>- CollaborationGroupCreated: Automatically generated post on your feed when you creates a public group. |
| LinkUrl | To post URL on a feed. |
| RelatedRecordId | The ID of the ContentVersion object associated with a ContentPost. This field is null for all posts except ContentPost. |
| Title | The title of the FeedItem. |
| AttachmentPath | The location of the file to be attached to the feed. For example, C:\Test\ (Mandatory field for Content Post) . |
| ContentFileName | The name of the file that you want to attach. |
| ContentDescription | The description of the file to be attached to the feed. |
| RelatedRecordId | The ID of the ContentVersion object associated with a ContentPost. For example, set this field to an existing ContentVersion and post it to a feed as a FeedItem object of TypeContentPost. |

   To post a feed comment, use the following filter fields:

| Field Name | Description |
|---|---|
| CommentFeedItemId | The Id of the feed to which the comment needs to be posted. |
| CommentBody | The text to be posted as comment. |

| Field Name | Description |
|---|---|
| CommentType | The comment Type should be TextComment or ContentComment. |
| CommentContentPath | The full path of the file to be attached to the FeedComment. |
| CommentContentDescription | The Description about the attachment. |

8. In the field mapping tab, map the source fields to the target fields.
9. Click **Next**.

   The Schedule tab appears.
10. In the Schedule tab, you can schedule the task for each requirement and save.
11. If you do not want to schedule the task, click **Save** to save the task.

You can monitor the status of synchronization tasks in the Monitor log.

CHAPTER 4

# Troubleshooting

This chapter includes the following topic:


- Troubleshooting a Chatter Synchronization Task, 23


## Troubleshooting a Chatter Synchronization Task

The solution to the following situations might help you troubleshoot Chatter synchronization task:

- When you configure the log file, the log file captures the exception and the log messages in a specific location. For example, `<Secure Agent installation directory>\apps\Data_Integration_Server\<latest version of connector>\ICS\main\tomcat\log`.
- When you create a synchronization task, the `null` error message occurs when a connector with invalid configuration is selected. The exception details are available in the following location: `<Secure Agent installation directory>\apps\Data_Integration_Server\<latest version of connector>\ICS\main\tomcat\log`
- When a synchronization task fails, the exception and log details are captured in the Session Log. To run the application in debug mode, you require special permission from the administrator.

CHAPTER 5

# Increasing Secure Agent Memory

This chapter includes the following topic:


- Increasing the secure agent memory, 24


## Increasing the secure agent memory

To increase performance and avoid runtime environment memory issues, perform the following steps:


1. In Administrator, select **Runtime Environments**.
2. Select the Secure Agent for which you want to increase memory from the list of available Secure Agents.
3. In the upper-right corner, click **Edit**.
4. In the **System Configuration Details** section, select the **Type** as **DTM** for the Data Integration Service.
5. Edit **JVMOption1** as **-Xms4056m** and **JVMOption2** as **-Xmx4056m**.

   The following image shows the **Details** page:




6. In the **System Configuration Details** section, select the **Type** as **TomCatJRE**
7. Edit **INFA_memory** as **-Xms256m -Xmx512m**.

The following image shows the **Agent Details** page:




**Note:** The minimum and maximum values for the Java heap size are given as an example. Specify the size according to your requirements.

8. Restart the Secure Agent.

# INDEX


## C

Chatter
  connection properties 12
Cloud Application Integration community
  URL 4
Cloud Developer community
  URL 4
connections
  Chatter 12

## D

Data Integration community
  URL 4

## I

Informatica Global Customer Support
  contact information 5
Informatica Intelligent Cloud Services
  web site 4

## M

maintenance outages 5

## P

proxy settings
  configuring on Windows 13

## S

Secure Agent
  increasing memory 24
status
  Informatica Intelligent Cloud Services 5
system status 5

## T

trust site
  description 5

## U

upgrade notifications 5

## W

web site 4
Windows
  configuring proxy settings 13