Informatica
from Salesforce

Informatica® Cloud Data Integration

Hadoop Files Connector

Informatica Cloud Data Integration Hadoop Files Connector
February 2025

© Copyright Informatica LLC 2016, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, Informatica Cloud, and PowerCenter are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-05-12

Table of Contents

Preface 4

Informatica Resources 4

- Informatica Documentation 4
- Informatica Intelligent Cloud Services web site 4
- Informatica Intelligent Cloud Services Communities 4
- Informatica Intelligent Cloud Services Marketplace 4
- Data Integration connector documentation 5
- Informatica Knowledge Base 5
- Informatica Intelligent Cloud Services Trust Center 5
- Informatica Global Customer Support 5

Chapter 1: Introduction to Hadoop Files Connector 6

Hadoop Files Connector Overview 6

Hadoop Files Connector Example 6

Hadoop Files Connector Task and Object Types 7

Hadoop Files Source and Target Objects 7

Hadoop Files Compression Formats 7

ComplexFileProcessor Connector Administration 8

- ComplexFileProcessor Connector Migration Task 8
- Access Kerberos Enabled Hadoop Cluster 8
- Access the non-Kerberos Enabled Hadoop Cluster 9

Chapter 2: Hadoop Files Connections 10

Hadoop Files Connection Overview 10

Hadoop Files connection properties 10

Chapter 3: Synchronization Tasks with Hadoop Files 12

Hadoop Files Sources in Synchronization Tasks 12

Hadoop Files Targets in Synchronization Tasks 13

Chapter 4: Mappings and Mapping Tasks with Hadoop Files 15

Hadoop Files Objects in Mappings 15

Hadoop Files Sources in Mappings 15

Hadoop Files Targets in Mappings 16

Appendix A: Hadoop Files Data Type Reference 19

Data Type Reference Overview 19

Index 20

Preface

The *Data Integration Hadoop Files Connector Guide* contains information about how to set up and use Hadoop Files Connector. The guide explains how organization administrators and business users can use Hadoop Files Connector to securely read data from or write data to complex files on local system or in HDFS.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Intelligent Cloud Services web site

You can access the Informatica Intelligent Cloud Services web site at http://www.informatica.com/cloud. This site contains information about Informatica Cloud integration services.

Informatica Intelligent Cloud Services Communities

Use the Informatica Intelligent Cloud Services Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the Informatica Intelligent Cloud Services Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

Informatica Intelligent Cloud Services Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Intelligent Cloud Services Trust Center

The Informatica Intelligent Cloud Services Trust Center provides information about Informatica security policies and real-time system availability.

You can access the trust center at https://www.informatica.com/trust-center.html.

Subscribe to the Informatica Intelligent Cloud Services Trust Center to receive upgrade, maintenance, and incident notifications. The Informatica Intelligent Cloud Services Status page displays the production status of all the Informatica cloud products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single component or all Informatica Intelligent Cloud Services components. Subscribing to all components is the best way to be certain you never miss an update.

To subscribe, on the Informatica Intelligent Cloud Services Status page, click **SUBSCRIBE TO UPDATES**. You can choose to receive notifications sent as emails, SMS text messages, webhooks, RSS feeds, or any combination of the four.

Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the Informatica Intelligent Cloud Services Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

Introduction to Hadoop Files Connector

This chapter includes the following topics:

- Hadoop Files Connector Overview, 6
- Hadoop Files Connector Example, 6
- Hadoop Files Connector Task and Object Types, 7
- Hadoop Files Source and Target Objects, 7
- Hadoop Files Compression Formats, 7
- ComplexFileProcessor Connector Administration, 8

Hadoop Files Connector Overview

You can use Hadoop Files Connector to securely read data from and write data to complex files on local system or to HDFS. You can read or write structured, semi-structured, and unstructured data.

Hadoop Files Connector uses Hadoop API infrastructure to read from or write to a local file system or to HDFS. The agent connects to the name node to read data from or write data to HDFS. You can read from and write to one or more complex files in different format such as PDF, JSON, and JPG. Hadoop Files Connector reads or writes data in the binary format. You can use complex file objects as sources and targets in synchronization tasks, mappings, and mapping tasks.

When you use the Hadoop Files Connector to read or write complex files, you can perform operations such as copy, rename, compress, or decompress a file.

Hadoop Files Connector Example

You are a data analyst in a large-scale social media enterprise. The enterprise stores departmental data in multiple formats such as PDF, XML, and JSON. A large amount of data is stored in the local file system of multiple computers. You need to consolidate this large amount of data and analyze it for business-critical decisions in near future.

You can consolidate data in the Hadoop environment and run various analytics tools to analyze the data quickly. You can use Hadoop Files Connector to read data from complex files in multiple formats from the

local file systems and write data to HDFS. After you write data to HDFS, use tools such as Hadoop Analytics to analyze the data.

Hadoop Files Connector Task and Object Types

The following table lists the Hadoop Files object types that you can include in Data Integration tasks:

Task Type	Source	Target	Lookup
Synchronization	Yes	Yes	No
Mapping	Yes	Yes	No
Mapping	Yes	Yes	No

Hadoop Files Source and Target Objects

You can specify a single complex file or multiple complex files as source and target objects.

Specify the complex file name in the source and target object if you want to perform the read or write operation to a single complex file. Specify a directory if you want to perform read or write operations to multiple files in a directory and its sub directories.

To specify a directory as a source object, configure **File Path** in the advanced source properties.

To specify a directory as a target object, configure **File Directory** in the advanced target properties.

Hadoop Files Compression Formats

You can read or write compressed complex files, specify compression formats for the target objects, and decompress the output files.

You can use compression formats such as Gzip, Bzip2, and DEFLATE. The compressed files must be of the binary format. The following table describes the complex file compression formats for binary files:

Compression Options	Description
None or empty	The file is not compressed.
Auto	The Data Integration Service detects the compression format of the file based on the file extension.
DEFLATE	The DEFLATE compression format that uses a combination of the LZ77 algorithm and Huffman coding.

Compression Options	Description
Gzip	The GNU zip compression format that uses the DEFLATE algorithm.
Bzip2	The Bzip2 compression format that uses the Burrows–Wheeler algorithm.

ComplexFileProcessor Connector Administration

Before you use Hadoop Files Connector in tasks, an administrator must verify the following prerequisites:

- You must have a license to use Cloudera CDH, Amazon Elastic MapReduce (EMR), or Hortonworks HDP packages. When you use a Microsoft HDInsight package, you can read data only from or write data only to a HDFS file system. To read data from or write data to HDFS running on Microsoft HDInsight, you need to use Hortonworks HDP package.
- You must use Hadoop Files Connector on Linux 64-bit operating system.

ComplexFileProcessor Connector Migration Task

To migrate ComplexFileProcessor Connector from the Informatica Cloud Spring 2017 release to the Informatica Intelligent Cloud Services Data Integration Spring 2018 April release, you must perform the following tasks:

1. If you used multiple licenses within an organization in the Informatica Cloud Spring 2017 release, you must create separate sub-organizations for each Hadoop distribution that you want to use and assign license for the Hadoop distribution.
2. Copy the required configuration files to the following directory:

   `<Secure Agent installation directory>/downloads/package-<distribution_name>/package/<distribution_name>_<version>/conf`
3. Restart the Secure Agent for the changes to take effect.

Access Kerberos Enabled Hadoop Cluster

Configure the `/etc/hosts` file and copy the Kerberos configuration file for HDFS instances that use Kerberos authentication.

1. Open the `/etc/hosts` file, located in the `/etc` directory on the machine where Secure Agent is installed.
2. To configure the Secure Agent to work with the Kerberos Key Distribution Center (KDC), make an entry of the KDC hosts in the `/etc/hosts` file.
3. Copy the `krb5.conf` configuration file from the `/etc` directory in the Hadoop cluster node to either of the following directories available within your Secure Agent installation:
   - `<Secure Agent installation directory>/jdk/jre/lib/security`
   - `<Secure Agent installation directory>/jdk8/jre/lib/security`
4. If there is a jdk directory within the `<Secure agent installation directory>\apps` folder, navigate to the following directory and copy the `krb5.conf` configuration file from the `/etc` directory in the Hadoop cluster node to the following directory within your Secure Agent installation:

`<Secure agent installation directory>\apps\jdk\zulu8<latest_version>\jre\lib\security`

5. If the cluster is SSL enabled, import the certificate alias file to either of the following directories available within your Secure Agent installation:
   - `<Secure Agent installation directory>/jdk/jre/lib/security/cacerts`
   - `<Secure Agent installation directory>/jdk8/jre/lib/security/cacerts`
6. If there is a jdk directory within the `<Secure agent installation directory>\apps` folder, navigate to the following directory and import the certificate alias file to the following directory within your Secure Agent installation:
   `<Secure agent installation directory>\apps\jdk\zulu8<latest_version>\jre\lib\security\cacerts`
7. Restart the Secure Agent.

Access the non-Kerberos Enabled Hadoop Cluster

If you have a Cloudera, Amazon EMR, Hortonworks, or Microsoft HDInsight instance that does not use Kerberos authentication and runs in a Hadoop cluster environment, perform the following steps:

1. Copy the `hdfs-site.xml` file with valid name node configuration to the appropriate `<package>/conf` folder.
2. Restart the Secure Agent.

CHAPTER 2

Hadoop Files Connections

This chapter includes the following topics:

- Hadoop Files Connection Overview, 10
- Hadoop Files connection properties, 10

Hadoop Files Connection Overview

You can use a Hadoop Files connection in mappings, mapping tasks, or synchronization tasks.

Create a Hadoop Files connection so that the agent can read complex files from and write hadoop files to a local file system or HDFS. You create a Hadoop Files connection on the **Connections** page. Use the connection when you create a synchronization task, mapping, or a mapping task.

Hadoop Files connection properties

When you set up a Hadoop Files connection, you must configure the connection properties.

Important: Hadoop Files Connector is deprecated and has been moved to maintenance mode. Informatica intends to drop support in a future release. Informatica recommends that you use Hadoop Files V2 Connector to access Hadoop Distributed File System (HDFS).

The following table describes the Hadoop Files connection properties:

Connection property	Description
Connection Name	Name of the Hadoop Files connection.
Description	Description of the connection. The description cannot exceed 765 characters.
Runtime Environment	The name of the runtime environment where you want to run the tasks.
User Name	Required to read data from HDFS. Enter a user name that has access to the single-node HDFS location to read data from or write data to.

Connection property	Description

NameNode URI	The URI to access HDFS.
	Use the following format to specify the name node URI in Cloudera, Amazon EMR, and Hortonworks distributions:
	`hdfs://<namenode>:<port>/`
	Where
	- `<namenode>` is the host name or IP address of the name node.
	- `<port>` is the port that the name node listens for remote procedure calls (RPC).
	If the Hadoop cluster is configured for high availability, you must copy the `fs.defaultFS` value in the `core-site.xml` file and append `/` to specify the name node URI.
	For example, the following snippet shows the `fs.defaultFS` value in a sample `core-site.xml` file:
	`<property>`
	`<name>fs.defaultFS</name>`
	`<value>hdfs://nameservice1</value>`
	`<source>core-site.xml</source>`
	`</property>`
	In the above snippet, the `fs.defaultFS` value is
	`hdfs://nameservice1`
	and the corresponding name node URI is
	`hdfs://nameservice1/`
	Note: Specify either the name node URI or the local path. Do not specify the name node URI if you want to read data from or write data to a local file system path.

Local Path	A local file system path to read data from or write data to. Do not specify local path if you want to read data from or write data to HDFS. Read the following conditions to specify the local path: - You must enter **NA** in local path if you specify the name node URI. If the local path does not contain **NA**, the name node URI does not work. - If you specify the name node URI and local path, the local path takes the preference. The connection uses the local path to run all tasks. - If you leave the local path blank, the agent configures the root directory (/) in the connection. The connection uses the local path to run all tasks.
Hadoop Distribution	Hadoop distribution name. Enter **CLOUDERA**, **EMR**, or **HDP** based on the HDFS instance you want to use for the connection. You can use Kerberos authentication for the Cloudera CDH and Hortonworks HDP Hadoop distributions. **Note:** Use all uppercase letters to specify the Hadoop distribution name.
Keytab File	The file that contains encrypted keys and Kerberos principals to authenticate the machine.
Principle Name	Users assigned to the superuser privilege can perform all the tasks that a user with the administrator privilege can perform.
Impersonation Username	You can enable different users to run mappings in a Hadoop cluster that uses Kerberos authentication or connect to sources and targets that use Kerberos authentication. To enable different users to run mappings or connect to big data sources and targets, you must configure user impersonation.

CHAPTER 3

Synchronization Tasks with Hadoop Files

This chapter includes the following topics:

- Hadoop Files Sources in Synchronization Tasks, 12
- Hadoop Files Targets in Synchronization Tasks, 13

Hadoop Files Sources in Synchronization Tasks

When you configure a synchronization task to use a Hadoop Files source, you can configure the source properties.

The source properties appear on the **Source** page of the Synchronization Task wizard when you specify a Hadoop Files connection.

The general properties display the name and description of the Hadoop Files source. Configure the source properties for the source object.

The following table describes the Hadoop Files source properties:

Property	Description
Connection	Name of the connection.
Source Type	Select Single.
Source Object	Select the file from which you want to read data. Though selecting a source object is mandatory, the agent ignores this object. The agent processes the source object specified in File Path in advanced source properties.

You can also configure advanced source properties when you schedule the synchronization task. Advanced source properties appear on the **Schedule** page of the Synchronization Task wizard.

The following table describes the Hadoop Files advanced source properties:

Advanced Property	Description
File Path	Mandatory. Location of the file or directory from which you want to read data. Maximum length is 255 characters. If the path is a directory, all the files in the directory must have the same file format. If the file or directory is in HDFS, enter the path without the node URI. For example, /user/lib/testdir specifies the location of a directory in HDFS. The path must not contain more than 512 characters. If the file or directory is in the local system, enter the fully qualified path. For example, /user/testdir specifies the location of a directory in the local system.
File Format	File format. Default is Binary.
Compression Format	Optional. Compression format of the source files. Select one of the following options: - AUTO - DEFLATE - gzip - bzip2 Select AUTO to detect the compression format based on the source file extension.

Hadoop Files Targets in Synchronization Tasks

When you configure a synchronization task to perform operations on a Hadoop Files target, you can configure the target properties.

The target properties appear on the **Target** page of the Synchronization Task wizard when you specify a Hadoop Files connection. The general properties display the name and description of the Hadoop Files target.

The following table describes the Hadoop Files target properties:

Property	Description
Connection	Name of the target connection.
Target Object	Select the file to which you want to write data. Though selecting a target object is mandatory, the agent ignores this object. The agent processes the target object specified in File Directory and File Name in advanced target properties.
Child Object	Not applicable.

You can also configure advanced target properties when you schedule the synchronization task. Advanced target properties appear on the **Schedule** page of the Synchronization Task wizard.

The following table describes the Hadoop Files advanced target properties:

Advanced Property	Description
File Directory	Optional. The directory location of one or more output files. Maximum length is 255 characters. If you do not specify a directory location, the output files are created at the location specified in the connection. If the directory is in HDFS, enter the path without the name node URI. For example, /user/lib/testdir specifies the location of a directory in HDFS. The path must not contain more than 512 characters. If the file or directory is in the local system, enter the fully qualified path. For example, /user/testdir specifies the location of a directory in the local system.
File Name	Optional. Renames the output file. The file name is not applicable if the source object is a directory.
File Format	File format. Default is Binary.
Compression Format	Optional. Compression format of the source files. The compression format for binary files. Select one of the following options: - AUTO - DEFLATE - gzip - bzip2 Select AUTO to detect the compression format based on the source file extension.
Success File Directory	Directory for the success file. Specify a directory path that is available on each Secure Agent machine in the runtime environment. By default, Data Integration writes the success file to the following directory: `<Secure Agent installation directory>/apps/Data_Integration_Server/data/success`
Error File Directory	Directory for the error file. Specify a directory path that is available on each Secure Agent machine in the runtime environment. By default, Data Integration writes the error file to the following directory: `<Secure Agent installation directory>/apps/Data_Integration_Server/data/error`

CHAPTER 4

Mappings and Mapping Tasks with Hadoop Files

This chapter includes the following topics:

- Hadoop Files Objects in Mappings, 15
- Hadoop Files Sources in Mappings, 15
- Hadoop Files Targets in Mappings, 16

Hadoop Files Objects in Mappings

When you create a mapping, you can configure a Source or Target transformation to represent a Hadoop Files object.

After you configure a mapping, deploy the mapping in a mapping task. If you parameterize the connection or object in a mapping, you must specify the parameterized values when you create the mapping task.

Hadoop Files Sources in Mappings

To read data from a complex file, configure a Hadoop Files object as the Source transformation in a mapping. You can configure a Source transformation to represent a single complex file source.

Specify the name and description of the Hadoop Files source. Configure the source and advanced properties for the source object.

The following table describes the Hadoop Files source properties that you can configure in a Source transformation:

Source Property	Description
Connection	Name of the source connection or create a connection parameter. If you choose to create a parameter for the connection, provide the connection type as Toolkit Application or leave it blank.
Source Type	Type of source object. Select Single or Parameter as the source type.

Source Property	Description
Object	Select the source object from which you want to read data. Though selecting a source object is mandatory, the agent ignores this object. The agent processes the source object specified in File Path in advanced source properties.
Parameter	The parameter for the source object. Create or select the parameter for the source object. **Note:** The parameter property appears if you select parameter as the source type.

The following table describes the Hadoop Files source advanced properties that you can configure in a Source transformation:

Advanced Property	Description
File Path	Mandatory. Location of the file or directory from which you want to read data. Maximum length is 255 characters. If the path is a directory, all the files in the directory must have the same file format. If the file or directory is in HDFS, enter the path without the node URI. For example, /user/lib/testdir specifies the location of a directory in HDFS. The path must not contain more than 512 characters. If the file or directory is in the local system, enter the fully qualified path. For example, /user/testdir specifies the location of a directory in the local system.
File Format	File format. Default is Binary.
Compression Format	Optional. Compression format of the source files. The compression format for binary files. Select one of the following options: - AUTO - DEFLATE - gzip - bzip2 Select AUTO to detect the compression format based on the source file extension.
Tracing Level	Sets the amount of detail that appears in the log file. You can choose terse, normal, verbose initialization, or verbose data. Default is normal.

Hadoop Files Targets in Mappings

To write data to a complex file, configure a Hadoop Files object as the Target transformation in a mapping. You can configure a Target transformation to represent a single Hadoop Files target.

When you use an Hadoop Files target object, select an Hadoop Files object as the target.

The following table describes the Hadoop Files target properties that you can configure in a Target transformation:

Target Property	Description
Connection	Name of the target connection or create a connection parameter. If you choose to create a parameter for the connection, provide the connection type as Toolkit Application.
Target Type	Type of target object. Select Single Object or Parameter.
Object	Select the file to which you want to write data. Though selecting a target object is mandatory, the agent ignores this object. The agent processes the target object specified in File Directory and File Name in advanced target properties.
Parameter	The parameter for the target object. Create or select the parameter for the target object. **Note:** The parameter property appears if you select parameter as the target type.
Operation	Select the target operation. You can select insert, update, upsert, delete, or data driven in an complex file target.

The following table describes the Hadoop Files target advanced properties that you can configure in a Target transformation:

Advanced Property	Description
File Directory	Optional. The directory location of one or more output files. Maximum length is 255 characters. If you do not specify a directory location, the output files are created at the location specified in the connection. If the directory is in HDFS, enter the path without the node URI. For example, /user/lib/testdir specifies the location of a directory in HDFS. The path must not contain more than 512 characters. If the file or directory is in the local system, enter the fully qualified path. For example, /user/testdir specifies the location of a directory in the local system.
File Name	Optional. Renames the output file. The file name is not applicable when you read or write multiple complex files.
File Format	File format. Default is Binary.
Compression Format	Optional. Compression format of the source files. The compression format for binary files. Select one of the following options: - AUTO - DEFLATE - gzip - bzip2 Select AUTO to detect the compression format based on the source file extension.
Success File Directory	Directory for the success file. Specify a directory path that is available on each Secure Agent machine in the runtime environment. By default, Data Integration writes the success file to the following directory: `<Secure Agent installation directory>/apps/Data_Integration_Server/data/success`

Advanced Property	Description
Error File Directory	Directory for the error file. Specify a directory path that is available on each Secure Agent machine in the runtime environment. By default, Data Integration writes the error file to the following directory: `<Secure Agent installation directory>/apps/Data_Integration_Server/data/error`
Forward Rejected Rows	Determines whether the transformation passes rejected rows to the next transformation or drops rejected rows. By default, the mapping task forwards rejected rows to the next transformation.

APPENDIX A

Hadoop Files Data Type Reference

This appendix includes the following topic:

- Data Type Reference Overview, 19

Data Type Reference Overview

Data Integration uses complex files in synchronization tasks and mapping tasks with Hadoop Files Connector.

Data Integration uses the following data types in mappings, synchronization tasks, and mapping tasks with complex file:

Complex file data types

Complex file data types appear in the physical data object column properties.

Transformation data types

Set of data types that appear in the transformations. They are internal data types based on ANSI SQL-92 generic data types, which the Secure Agent uses to move data across platforms. Transformation data types appear in all transformations in a mappings, synchronization tasks, and mapping tasks.

When Data Integration reads source data, it converts the native data types to the comparable transformation data types before transforming the data. When Data Integration writes to a target, it converts the transformation data types to the comparable native data types.

The following table lists the complex file data types that Data Integration supports and the corresponding transformation data types:

Complex File Data Type	Transformation Data Type
Binary	Binary

INDEX

A

administration 8

C

Cloud Application Integration community
  URL 4
Cloud Developer community
  URL 4
connection
  creating a 6
connections
  hadoop files 10
  Hadoop Files 10

D

Data Integration community
  URL 4
data type reference
  overview 19

H

hadoop files
  compression 7
  decompression 7
  mappings 15
  source object 7
  source transformation 15
  sources in mappings 15
  target object 7
  target transformation 16
  targets in mappings 16
Hadoop Files
  connection properties 10
Hadoop Files Connector
  example 6
  overview 10
  task and object types 7
hadoop files sources
  synchronization tasks 12

I

Informatica Global Customer Support
  contact information 5
Informatica Intelligent Cloud Services
  web site 4

M

maintenance outages 5
mappings
  hadoop files 15
  hadoop files source properties 15
  hadoop files target properties 16

S

source object
  hadoop files 7
source transformation
  hadoop files properties 15
sources
  hadoop files in mappings 15
status
  Informatica Intelligent Cloud Services 5
synchronization tasks
  hadoop files targets 13
system status 5

T

target object
  hadoop files 7
target transformation
  hadoop files properties 16
targets
  hadoop files in mappings 16
trust site
  description 5

U

upgrade notifications 5

W

web site 4