Informatica®

Informatica® Cloud Data Integration

OpenAir Connector

Informatica Cloud Data Integration OpenAir Connector
October 2022

© Copyright Informatica LLC 2016, 2024

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, Informatica Cloud, and PowerCenter are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2024-10-21

Table of Contents

Preface 4

Informatica Resources 4

- Informatica Documentation 4
- Informatica Intelligent Cloud Services web site 4
- Informatica Intelligent Cloud Services Communities 4
- Informatica Intelligent Cloud Services Marketplace 4
- Data Integration connector documentation 5
- Informatica Knowledge Base 5
- Informatica Intelligent Cloud Services Trust Center 5
- Informatica Global Customer Support 5

Chapter 1: Introduction to OpenAir Connector 6

OpenAir Connector assets 6

Enabling OpenAir Connector 12

Recommendations 12

Chapter 2: OpenAir Connections 14

OpenAir connection properties 14

Chapter 3: Synchronization Task with OpenAir Connector 15

OpenAir Sources in Synchronization Task 15

OpenAir Targets in Synchronizationn Tasks 16

Defining Precision of Fields 16

Data Filters 17

- Simple Filters 18
- Advanced Filters 20

Chapter 4: Troubleshooting 21

Troubleshooting 21

Troubleshooting Synchronization Task 22

Increasing the secure agent memory 22

Configuring the File Size 23

Chapter 5: Future Enhancements and Current Issues 24

Index 26

Preface

Use *Data Integration OpenAir Connector* to learn how to set up and use OpenAir Connector. Learn to create an OpenAir connection and run synchronization tasks in Cloud Data Integration.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Intelligent Cloud Services web site

You can access the Informatica Intelligent Cloud Services web site at http://www.informatica.com/cloud. This site contains information about Informatica Cloud integration services.

Informatica Intelligent Cloud Services Communities

Use the Informatica Intelligent Cloud Services Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the Informatica Intelligent Cloud Services Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

Informatica Intelligent Cloud Services Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Intelligent Cloud Services Trust Center

The Informatica Intelligent Cloud Services Trust Center provides information about Informatica security policies and real-time system availability.

You can access the trust center at https://www.informatica.com/trust-center.html.

Subscribe to the Informatica Intelligent Cloud Services Trust Center to receive upgrade, maintenance, and incident notifications. The Informatica Intelligent Cloud Services Status page displays the production status of all the Informatica cloud products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single component or all Informatica Intelligent Cloud Services components. Subscribing to all components is the best way to be certain you never miss an update.

To subscribe, on the Informatica Intelligent Cloud Services Status page, click **SUBSCRIBE TO UPDATES**. You can choose to receive notifications sent as emails, SMS text messages, webhooks, RSS feeds, or any combination of the four.

Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the Informatica Intelligent Cloud Services Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

Introduction to OpenAir Connector

OpenAir Connector enables you to securely read data from or write data to OpenAir.

You can use OpenAir objects as sources and targets in the synchronization tasks.

For example, you can use OpenAir Connector to synchronize contacts between Salesforce and OpenAir.

OpenAir Connector supports the following tasks:

- All OpenAir entity objects perform CRUD operations.
- While retrieving feeds from OpenAir account, OpenAir supports filters such as Equals, Not Equals, Is Null, Is Not Null, Less Than, Less than or Equals, Greater Than, and Greater Than or Equals.
- OpenAir supports the AND conjunction between filters.
- OpenAir offers filtering on any column supported by the OpenAir entity objects.

OpenAir Connector assets

Create assets in Data Integration to integrate data using OpenAir Connector.

When you use OpenAir Connector, you can create a synchronization task to read data from or write data to OpenAir.

Features are different entities of OpenAir Connector which contains set of objects. You can select the feature while creating an OpenAir Connector.

The following table lists the feature objects and task operations supported by OpenAir Connector:

Objects	**Task Operations**					
	Read	Lookup	Insert	Modify	Upsert	Delete
Contact	Yes	Yes	Yes	Yes	Yes	Yes
Project	Yes	Yes	Yes	Yes	Yes	Yes
Resourceprofile	Yes	Yes	Yes	Yes	Yes	No

Objects	Task Operations					
Resourceprofile_type	Yes	Yes	Yes	Yes	Yes	Yes
IssueStage	Yes	Yes	Yes	Yes	Yes	No
Revenue_recognition_transaction	Yes	Yes	Yes	Yes	Yes	No
Dealschedule	Yes	Yes	Yes	No	No	No
Budget	Yes	Yes	Yes	Yes	Yes	No
Category_5	Yes	Yes	Yes	Yes	Yes	No
UserWorkschedule	Yes	Yes	No	No	No	No
Projectbillingrule	Yes	Yes	Yes	Yes	Yes	No
Payment	Yes	Yes	Yes	Yes	Yes	Yes
Approvalprocess	Yes	Yes	No	No	No	No
Leave_accrual_rule	Yes	Yes	Yes	Yes	Yes	No
User	Yes	Yes	Yes	Yes	No	Yes
Attributeset	Yes	Yes	No	No	No	No
Ccrate	Yes	Yes	No	No	No	No
TagGroup	Yes	Yes	No	No	No	No
RevenueStage	Yes	Yes	No	No	No	No
Uprate	Yes	Yes	Yes	Yes	Yes	No
Timesheet	Yes	Yes	Yes	Yes	Yes	Yes
Scheduleexception	Yes	Yes	No	No	No	No
Projectgroup	Yes	Yes	Yes	Yes	Yes	No
Dealcontact	Yes	Yes	No	No	No	No
CustField	Yes	Yes	Yes	Yes	Yes	No
IssueStatus	Yes	Yes	Yes	Yes	Yes	No

Objects	Task Operations					
Workspacelink	Yes	Yes	Yes	Yes	Yes	No
Proposal	Yes	Yes	No	No	No	No
Slip	Yes	Yes	Yes	Yes	Yes	Yes
Currency	Yes	Yes	Yes	Yes	Yes	No
Customer	Yes	Yes	Yes	Yes	Yes	Yes
BookingType	Yes	Yes	Yes	Yes	Yes	No
Fulfillment	Yes	Yes	No	No	No	No
Estimateadjustment	Yes	Yes	No	No	No	No
Approval	No	No	No	No	No	No
RevenueContainer	Yes	Yes	No	No	No	No
History	Yes	Yes	No	No	No	No
Task	Yes	Yes	Yes	Yes	Yes	Yes
Repeat	Yes	Yes	Yes	Yes	Yes	No
Issue	Yes	Yes	Yes	Yes	Yes	Yes
Scheduleresquest_item	Yes	Yes	Yes	Yes	Yes	Yes
Agreement	Yes	Yes	Yes	Yes	Yes	Yes
Category_1	Yes	Yes	Yes	Yes	Yes	No
ImportExport	Yes	Yes	Yes	Yes	Yes	No
Workspaceuser	Yes	Yes	Yes	Yes	Yes	No
Company	Yes	Yes	Yes	Yes	Yes	No
Timetype	Yes	Yes	Yes	Yes	Yes	Yes
Revenue_recognition_rule_amount	Yes	Yes	Yes	Yes	Yes	No
Customerpo_to_project	Yes	Yes	Yes	Yes	Yes	No

Objects	Task Operations					
Estimate	Yes	Yes	No	No	No	No
Jobcode	Yes	Yes	Yes	Yes	Yes	No
Ticket	Yes	Yes	Yes	Yes	Yes	Yes
Event	Yes	Yes	Yes	Yes	Yes	No
TaskTimecard	Yes	Yes	No	No	No	No
TaxLocation	Yes	Yes	Yes	Yes	Yes	No
InvoiceLayout	Yes	Yes	No	No	No	No
Revenue_recognition_rule	Yes	Yes	Yes	Yes	Yes	No
Payrolltype	Yes	Yes	Yes	Yes	Yes	Yes
Actualcost	Yes	Yes	Yes	Yes	Yes	No
Customerpo	Yes	Yes	Yes	Yes	Yes	Yes
Projectstage	Yes	Yes	Yes	Yes	Yes	Yes
Department	Yes	Yes	Yes	Yes	Yes	Yes
Estimatemarkup	Yes	Yes	No	No	No	No
IssueSeverity	Yes	Yes	Yes	Yes	Yes	No
LoadedCost	Yes	Yes	Yes	Yes	Yes	No
Filterset	Yes	Yes	No	No	No	No
Category_4	Yes	Yes	Yes	Yes	Yes	No
Viewfilterrule	Yes	Yes	No	No	No	No
TagGroupAttribute	Yes	Yes	No	No	No	No
BudgetAllocation	Yes	Yes	Yes	Yes	Yes	No
Leave_accrual_transaction	Yes	Yes	Yes	Yes	Yes	No
Ratecard	Yes	Yes	Yes	Yes	Yes	No
Slipstage	Yes	Yes	Yes	Yes	Yes	No

Objects	Task Operations					
Projectlocation	Yes	Yes	No	No	No	No
Projecttask_type	Yes	Yes	Yes	Yes	Yes	No
Request_item	Yes	Yes	No	No	No	No
Purchaserequest	Yes	Yes	No	No	No	No
Projectbillingtransaction	Yes	Yes	No	No	No	No
TaxRate	Yes	Yes	Yes	Yes	Yes	No
Viewfilter	Yes	Yes	No	No	No	No
TargetUtilization	Yes	Yes	Yes	Yes	Yes	Yes
Deal	Yes	Yes	No	No	No	No
SlipProjection	Yes	Yes	No	No	No	No
Address	No	No	Yes	No	No	No
Invoice	Yes	Yes	Yes	Yes	Yes	Yes
ForexInput	Yes	Yes	Yes	Yes	Yes	No
Error	Yes	Yes	No	No	No	No
Category_2	Yes	Yes	Yes	Yes	Yes	No
Costtype	Yes	Yes	Yes	Yes	Yes	No
Attachment	Yes	Yes	Yes	Yes	Yes	Yes
Envelope	Yes	Yes	Yes	Yes	Yes	Yes
Todo	Yes	Yes	No	No	No	No
Purchaser	Yes	Yes	No	No	No	No
Booking	Yes	Yes	Yes	Yes	Yes	Yes
Attribute	Yes	Yes	No	No	No	No
Timecard	Yes	Yes	No	No	No	No
Category	Yes	Yes	Yes	Yes	Yes	Yes

Objects	Task Operations					
FormPermissionField	Yes	Yes	No	No	No	No
Purchaseorder	Yes	Yes	Yes	Yes	Yes	Yes
Projecttask	Yes	Yes	Yes	Yes	Yes	Yes
Estimateexpense	Yes	Yes	No	No	No	No
Purchase_item	Yes	Yes	Yes	Yes	Yes	Yes
Preference	Yes	Yes	Yes	Yes	Yes	No
Schedulebyday	Yes	Yes	No	No	No	No
Currencyrate	Yes	Yes	No	No	No	No
Category_3	Yes	Yes	Yes	Yes	Yes	No
Agreement_to_project	Yes	Yes	Yes	Yes	Yes	Yes
Reimbursement	Yes	Yes	Yes	Yes	Yes	Yes
Product	Yes	Yes	Yes	Yes	Yes	No
Projecttaskassign	Yes	Yes	Yes	Yes	Yes	Yes
Paymenttype	Yes	Yes	Yes	Yes	Yes	Yes
Proposalblock	Yes	Yes	No	No	No	No
Schedulerequest	Yes	Yes	Yes	Yes	Yes	Yes
Report	Yes	Yes	No	No	No	No
Hierarchy	Yes	Yes	Yes	Yes	Yes	No
Estimatelabor	Yes	Yes	No	No	No	No
HierarchyNode	Yes	Yes	Yes	Yes	Yes	Yes
Vendor	Yes	Yes	Yes	Yes	Yes	Yes
IssueSource	Yes	Yes	Yes	Yes	Yes	No
Paymentterms	Yes	Yes	Yes	Yes	Yes	No

Objects	Task Operations					
Leave_accrual_rule_to_user	Yes	Yes	Yes	Yes	Yes	No
Item	Yes	Yes	Yes	Yes	Yes	Yes
Costcategory	Yes	Yes	Yes	Yes	Yes	No
IssueCategory	Yes	Yes	Yes	Yes	Yes	No
Costcenter	Yes	Yes	Yes	Yes	Yes	No
Entitytag	Yes	Yes	Yes	Yes	Yes	Yes
Projectassign	Yes	Yes	Yes	Yes	Yes	No
Estimatephase	Yes	Yes	No	No	No	No
RateCardItem	Yes	Yes	Yes	Yes	Yes	No
Module	Yes	Yes	No	No	No	No
Term	Yes	Yes	No	No	No	No

For more information about configuring assets and transformations, see *Transformations* and *Tasks* in the Data Integration documentation.

Enabling OpenAir Connector

Contact Informatica Global Customer Support to enable OpenAir Connector.

It takes 15 minutes for the OpenAir Connector to download to Secure Agent after it is enabled.

Recommendations

OpenAir Connector recommends that you use the OpenAir data dictionary to read the data type access and fetch values from the OpenAir objects.

You need to define the custom object in the Web Service Definition Language and create the metadata stub if your OpenAir account has a custom object.

While handling reserved characters in advanced data filters, you need to be careful using special characters.

You need to include the custom object entry in the properties file `OpenAirCodes.properties` in Secure Agent connector path under the section *TABLENAME*.

When you use special characters follow the following rules:

- Single quote (‘) must precede with /
- Double quote (“) must precede with \
- Use \\ for backslash
- Use // for forward-slash

CHAPTER 2

OpenAir Connections

Create an OpenAir connection to connect to OpenAir and read data from or write data to OpenAir buckets.

You can use OpenAir connections in synchronization tasks, mapping tasks, and mappings.

OpenAir connection properties

When you create an OpenAir connection, you must configure the connection properties.

Important: OpenAir Connector is deprecated and has been moved to maintenance mode. Informatica intends to drop support in a future release.

The following table describes the OpenAir connection properties:

Property	Description
Secure Agent	The Secure Agent used to access OpenAir.
Username	User name of the OpenAir account.
Password	Password of the OpenAir account.
Company	Enter the company name.
API NameSpace	Enter the API NameSpace.
API Key	Enter the API Key.
Client Name	Enter the client name.
WSDL Url	Enter WSDL URL.
Endpoint Url	Enter end-point URL.
Batch Size	Enter the OpenAir write batch size. Default is 100.
Version	Enter the version number.
Enable Logging	Select to enable logging.

CHAPTER 3

Synchronization Task with OpenAir Connector

Use the Synchronization task to synchronize data between a source and target.

You can configure a synchronization task using the Synchronization Task wizard.

When you create a task, you can associate it with a schedule to run it at specified times or on regular intervals. Or, you can run it manually. You can monitor tasks that are currently running in the activity monitor and view logs about completed tasks in the activity log.

OpenAir Sources in Synchronization Task

You can configure the OpenAir source properties on the **Source** page of the Synchronization Task wizard.

The following table describes the OpenAir source properties:

Property	Description
Connection	Name of the OpenAir source connection.
Source Type	Type of the OpenAir source object available.
Source Object	Name of the source object.
Display technical names instead of labels	Displays technical names instead of business names.
Display source fields in alphabetical order	Displays source fields in alphabetical order. By default, fields appear in the order returned by the source system.

OpenAir Targets in Synchronizationn Tasks

You can use a single OpenAir object as a target in a synchronization task.

The following table describes the OpenAir target properties:

Property	Description
Connection	Name of the OpenAir target connection.
Target Object	Name of the OpenAir target object.
Child Object	This attribute is not applicable for OpenAir Connector.
Display target fields in alphabetical order	Displays target fields in alphabetical order. By default, fields appear in the order returned by the target system

Defining Precision of Fields

All fields are defined as string data type according to OpenAir Web Service Definition Language. You need to use a default precision of 255 characters for all string data type for a connector code.

You need to define the fields in `OpenAirCodes.properties` file to override the default value of 255 characters. These fields are downloaded in the Secure Agent path when OpenAir Connector is enabled.

The following image shows how to define field in the property file:

```
Term=Term,Read
#Object Name.Field Name=FieldLength
[FIELDLENGTH]
Contact.notes=512
Filterset.notes=512
Project.notes=512
IssueStage.notes=512
Revenue_recognition_transaction.notes=51
Budget.notes=512
Category_5.notes=512
Projectbillingrule.notes=512
Payment.notes=512
Leave_accrual_rule.notes=512
Attributeset.notes=512
Ccrate.notes=512
Uprate.notes=512
Timesheet.notes=512
Projectgroup.notes=512
Proposal.notes=512
Slip.notes=512
Customer.notes=512
BookingType.notes=512
Fulfillment.notes=512
```

You find the property file in the following path:

- `<Secure Agent installation directory>\downloads\<latest connector zip package>\package \plugins\<Plugin ID>`
- `<Secure Agent installation directory>\downloads\<latest connector zip package>\package \rdtm\javalib\<Plugin ID>`

  Note: Property file in both the paths must be in synchronized manner.

Data Filters


Data filter contains set of fields based on attribute filter fields and data filter fields.

Attribute Filter Fields are set of static fields for all OpenAir objects with name starting with '__'. These fields do not fetch data and represent the OpenAir attribute.

The following shows an example of attribute filter fields:

'__' + <Attribute field from developer guide> = <Attribute filter field>

The following image shows the list of attribute filter fields:



Data Filter Fields belongs to OpenAir objects. The data filter tab lists all the fields in the OpenAir object where few fields are filterable.

If non-filterable fields are used for any fetch operation, then OpenAir voids the filter condition and fetches all data.

Simple Filters

Simple filter uses fields starting with '_ '= to define OpenAir attributes to control read data set from OpenAir. You can use the attribute fields to define simple filters.

To define simple filters, use the following attributes:

Filter Field Name	Attribute Name	Value	Remark/Result
_AttrFld_deleted	deleted	1	Returns deleted records. It can be used together with newer-than filter.
_AttrFld_include_flags	include_flags	1	Returns account or user switches, by default those are not populated.
_AttrFld_include_nondeleted	include_nondeleted	1	Returns all records, deleted, and non deleted. **Note:** This attribute works in conjunction with the "deleted" attribute.
_AttrFld_with_project_only	with_project_only	1	Used with type: Customer will return customers which have associated project records.
_AttrFld_base_currency	base_currency	Eg: USD, CAN, INR,	Letter currency code. Works with type: Currencyrate. Converts values on the fly to currency specified.
_AttrFld_generic	generic		Returns generic resources (users), where by default, the API returns regular users.

Filter Field Name	Attribute Name	Value	Remark/Result
_AttrFld_filter	filter	open-envelopes	Returns records associated with an open envelope.
		approved-envelopes	Returns records associated with an approved envelope.
		rejected-envelopes	Returns records associated with a rejected envelope.
		submitted-envelopes	Returns records associated with a submitted envelope.
		nonreimbursed-envelopes	Returns envelopes that have a non zero balance attribute.
		reimbursable-envelope	Returns records associated with a reimbursable envelope.
		open-slips	Returns records associated with an open slip.
		approved-slips	Returns records associated with an approved slip.
		open-timesheets	Returns records associated with an open timesheet.
		approved-timesheets	Returns records associated with an approved timesheet.
		rejected-timesheets	Returns records associated with a rejected timesheet.
		submitted-timesheets	Returns records associated with a submitted timesheet.
		not-exported	Returns records not marked as exported.
		approved-revenue-recognition-transactions	Returns revenue recognition transactions belonging to approved revenue_container records.
		date filters: * newer-than * older-than * date-equal-to * date-not-equal-to	Returns records that have a value in the 'updated' field that is newer-than, older-than, date-equal-to, or date-not-equal-to the date specified in the oaDate object in the objects collection. To compare date fields other than 'updated', add the following additional attribute information: name="field" value="[some date field]"

Advanced Filters

You can use advanced data filter to run search queries containing complex filter expressions.


Note: You will know the selected filter field is not filterable after you run the synchronization task.

Perform the following steps to use advanced filters:

1. Click **Advanced** in the **Data Filter** dialog box.

   The **Advanced Data Filter** dialog box appears.
2. Enter the **Filter Expression**.
3. Click **OK**.

   The following image shows the **Advanced Data Filter** dialog box:



Advanced data filter contains some filter properties. Advanced data filter supports equals and not equals operators, attributes filters, but basic filters does not support OR operator.

Follow these guidelines to write an advanced data filter expression:

- You need to separate field name and value by an operator such as equals or not equals.
- Use operators which are enclosed within angular brackets.
- You need to separate each filter by a semi colon.

CHAPTER 4

Troubleshooting

Use the following sections to troubleshoot errors when you use OpenAir Connector

Troubleshooting

You might face the following issues during configuration of OpenAir Connectors:

1. If the fetch size of data for source object is large, an error message `Out of Memory` might occur. You can either decrease the batch size in the connection tab or increase the cloud Secure Agent memory size.
2. Failure of synchronization task with error message `The DTM process terminated unexpectedly` might occur due to **Enable Logging** attribute in connection.

   Do not select the box and run the task again to disable the **Enable Logging** field.
3. All string fields in the OpenAir have a precession of 225 characters by default. You need to define that field with record name in the property file if any field needs to have more than 225 length.
4. The OpenAir Connector generates an error message `Invalid XML character` if OpenAir read operation fetches data containing special character.
5. You need to specify each currency in individual filter.

   For example, specify

   ```
   currencies<equal to>'USD'; currencies<equal to >'AUD' when you fetch data based on
   filter currencies and not like currencies <equal to>
   'USD,AUD,CAD,EUR,GBP,JPY,MXN,NZD,CHF,AED,ARS,BHD,BRL,CLP,CNY,COP,CRC,DKK,HKD,HRK,IDR,
   ILS,INR,JMD,KES,KRW,MYR,NOK,PEN,PHP,PLN,SAR,SEK,SGD,THB,TWD,VEB,XCD,ZAR,TRY,RUB'.
   ```

6. If you use an object whose fields are updated by OpenAir and you use an earlier `OpenAir-metadata.jar` file, an error occurs. Use the latest WSDL version and generate the `OpenAir-metadata.jar` file from the latest WSDL version when OpenAir makes any updates, for example, adding new fields.

The Secure Agent generates a log file to capture the messages thrown during task configuration. The messages are saved in the following location:`<Secure Agent installation directory>\apps\Data_Integration_Server\logs`

Troubleshooting Synchronization Task

When you create a synchronization task with a configuration that is not valid, NULL error message appears.

Session Log saves the messages of a failed synchronization task. You require special privileges to run the application in debug mode.

For example, `<Secure Agent installation directory>\apps\Data_Integration_Server\logs`

Increasing the secure agent memory

To increase performance and avoid runtime environment memory issues, perform the following steps:


1. In Administrator, select **Runtime Environments**.
2. Select the Secure Agent for which you want to increase memory from the list of available Secure Agents.
3. In the upper-right corner, click **Edit**.
4. In the **System Configuration Details** section, select the **Type** as **DTM** for the Data Integration Service.
5. Edit **JVMOption1** as **-Xms4056m** and **JVMOption2** as **-Xmx4056m**.

   The following image shows the **Details** page:



6. In the **System Configuration Details** section, select the **Type** as **TomCatJRE**
7. Edit **INFA_memory** as **-Xms256m -Xmx512m**.

The following image shows the **Agent Details** page:



Note: The minimum and maximum values for the Java heap size are given as an example. Specify the size according to your requirements.

8. Restart the Secure Agent.

Configuring the File Size

To configure the file size, perform the following steps:

1. In Administrator, select **Runtime Environments**.
2. On the **Runtime Environments** page, select the Secure Agent for which you want to increase memory from the list of available Secure Agents.
3. In the upper-right corner, click **Edit**.
4. In the **System Configuration Details** section, select the **Type** as **System** for the Data Integration Service.
5. Add the `-DfileIO.maxFileSize` property and set the value to `xyz`. `xyz` is the size of the largest file you want to handle.
6. Restart the Secure Agent.

CHAPTER 5

Future Enhancements and Current Issues


In OpenAir, batch size is defined in the **Connection** tab. OpenAir fetches all data set instead of fetching records in pages for each defined batch size. All the fields in the OpenAir object are listed in the **Data Filter** tab and few fields in OpenAir object are filterable.

OpenAir users have custom objects or fields for incorporating custom OpenAir solution. OpenAir Connector uses the Web Service Definition Language to fetch the object and field metadata.

You need to keep the OpenAir object structure in synchronization manner and add the custom fields to the default Web Service Definition Language.

Perform the following steps to create a stub for the OpenAir Web Service Definition Language:

1. Download jdk 1.7.0_25 from the link http://www.oracle.com/technetwork/java/javase/downloads/java-archive-downloads-javase7-521261.html#jdk-7u25-oth-JPR



2. Download the Axis 1.4 from the link - http://www.apache.org/dyn/closer.cgi/ws/axis/1_4 and unzip the file in a folder. For example, \\temp\AXIS_LIB.

   Note: Create the directory paths before executing any command.

3. The following are the commands for creating the OpenAir stub:

   You can either run the command one by one in the command prompt or copy paste the entire commands to a win batch file.

   ```
   set JAVA_HOME=\\Program Files\Java\jdk1.7.0_25
   set AXIS_PATH=\\temp\axis-1_4
   set AXIS_LIB=%AXIS_PATH%\lib\axis-ant.jar;%AXIS_PATH%\lib\axis.jar;%AXIS_PATH%\lib
   \commons-discovery-0.2.jar;%AXIS_PATH%\lib\commons-logging-1.0.4.jar;%AXIS_PATH%\lib
   \jaxrpc.jar;%AXIS_PATH%\lib\log4j-1.2.8.jar;%AXIS_PATH%\lib\saaj.jar;%AXIS_PATH%\lib
   \wsdl4j-1.5.1.jar
   set classpath=%JAVA_HOME%;%AXIS_LIB%
   set PATH=%JAVA_HOME%;%PATH%
   mkdir \\temp\OpenAir
   java org.apache.axis.wsdl.WSDL2Java -v -p com.openair.api -a -o \\temp\OpenAir\ \
   \temp\OpenAir.wsdl
   mkdir \\temp\classes
   javac -cp .;"%classpath%" OpenAir/com/openair/api/*.java -d classes
   jar -cvf \\temp\OpenAir-metadata.jar -C C:\temp\classes com
   ```

   You will find that a new `OpenAir-metadata.jar` is created.

4. Stop the Secure Agent.
5. Copy the `OpenAir-metadata-1.0.0.jar` to the following directory:

   `<Secure Agent installation directory>\downloads\<latest connector zip package>\package \rdtm\javalib\<Plugin ID>`

6. Start the Secure Agent.

INDEX

A

advanced data filters 20
atch size 24

C

Cloud Application Integration community
  URL 4
Cloud Developer community
  URL 4
connections
  OpenAir 14
Custom object 12

D

Data Integration community
  URL 4

I

Informatica Global Customer Support
  contact information 5
Informatica Intelligent Cloud Services
  web site 4

M

maintenance outages 5

O

ODBC
  Synchronization task 15
OpenAir
  connection properties 14
OpenAir connections
  overview 14
OpenAir Connector
  objects and task operations 6
  overview 6
  troubleshooting 21
OpenAir Connector source
  Synchronization task 15
OpenAir Connector target
  Synchronization task 16

S

Secure Agent
  configuring file size 23
  increasing memory 22
Secure Agent path 16
status
  Informatica Intelligent Cloud Services 5
system status 5

T

troubleshooting
  Synchronization task 22
trust site
  description 5

U

upgrade notifications 5

W

web site 4