Informatica

Informatica® Cloud Data Integration

Salesforce Analytics Connector

Informatica Cloud Data Integration Salesforce Analytics Connector
April 2026

© Copyright Informatica LLC 2015, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, Informatica Cloud, and PowerCenter are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-04-10

Table of Contents

Preface 4

Informatica Resources 4

- Informatica Documentation 4
- Informatica Intelligent Cloud Services web site 4
- Informatica Intelligent Cloud Services Communities 4
- Informatica Intelligent Cloud Services Marketplace 4
- Data Integration connector documentation 5
- Informatica Knowledge Base 5
- Informatica Intelligent Cloud Services Trust Center 5
- Informatica Global Customer Support 5

Chapter 1: Introduction to Salesforce Analytics Connector 6

Introduction to Salesforce Analytics 6

Salesforce Analytics Connector assets 6

Salesforce Analytics objects 7

- Generating a JSON file 7
- Manually creating a JSON file 7
- Sample JSON file 8

Salesforce Analytics Connector example 8

Salesforce Analytics target operations 9

Administration of Salesforce Analytics Connector 9

Chapter 2: Salesforce Analytics connections 10

Salesforce Analytics connection properties 10

Chapter 3: Synchronization tasks with Salesforce Analytics Connector 12

Salesforce Analytics targets in synchronization tasks 12

Synchronization task example 13

Chapter 4: Mappings and mapping tasks with Salesforce Analytics 15

Salesforce Analytics targets in mappings 15

Salesforce Analytics targets in synchronization tasks 16

Chapter 5: Data type reference 17

Salesforce Analytics and transformation data types 17

Index 18

Preface

Use *Salesforce Analytics Connector* to learn how to write to Salesforce Analytics by using Cloud Data Integration. Learn to create a Salesforce Analytics connection, develop and run synchronization tasks, mappings, and mapping tasks in Cloud Data Integration.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Intelligent Cloud Services web site

You can access the Informatica Intelligent Cloud Services web site at http://www.informatica.com/cloud. This site contains information about Informatica Cloud integration services.

Informatica Intelligent Cloud Services Communities

Use the Informatica Intelligent Cloud Services Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the Informatica Intelligent Cloud Services Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

Informatica Intelligent Cloud Services Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Intelligent Cloud Services Trust Center

The Informatica Intelligent Cloud Services Trust Center provides information about Informatica security policies and real-time system availability.

You can access the trust center at https://www.informatica.com/trust-center.html.

Subscribe to the Informatica Intelligent Cloud Services Trust Center to receive upgrade, maintenance, and incident notifications. The Informatica Intelligent Cloud Services Status page displays the production status of all the Informatica cloud products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single component or all Informatica Intelligent Cloud Services components. Subscribing to all components is the best way to be certain you never miss an update.

To subscribe, on the Informatica Intelligent Cloud Services Status page, click **SUBSCRIBE TO UPDATES**. You can choose to receive notifications sent as emails, SMS text messages, webhooks, RSS feeds, or any combination of the four.

Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the Informatica Intelligent Cloud Services Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

Introduction to Salesforce Analytics Connector

Salesforce Analytics Connector provides connectivity between Data Integration and Salesforce Analytics. You can integrate and transform data from sources, such as flat files, databases, and applications, to write to a Salesforce Analytics target. You can then view reports on Salesforce Analytics.

Salesforce Analytics targets represent objects in the Salesforce Analytics object model. Salesforce Analytics objects are tables that correspond to tabs and other user interface elements on the Salesforce Analytics website.

Use a Salesforce Analytics connection in synchronization tasks, mappings, and mapping tasks.

You can switch mappings to advanced mode to include transformations and functions that enable advanced functionality.

Note: You cannot read data from a partitioning-enabled source.

Introduction to Salesforce Analytics

Salesforce Analytics is a cloud-based platform that connects data from multiple sources, creates interactive views of that data, and displays those views in dashboards.

You can use Salesforce Analytics to get instant access to analytics data and explore data of any data source. You can integrate data from multiple business applications and solutions, such as Customer Relationship Management (CRM) and Enterprise resource planning (ERP) into a single view. You can securely transmit data of any data source with the native Salesforce cloud service. Sales, service, and marketing users can use Salesforce Analytics reports to understand and act on real-time information.

Salesforce Analytics Connector assets

When you create a Salesforce Analytics connection to perform a task, you can select objects supported by Salesforce Connector for the task.

When you use Salesforce Analytics Connector, you can include the following Data Integration assets:

- Mapping

- Mapping task
- Synchronization task

For more information about configuring assets and transformations, see *Mappings*, *Transformations*, and *Tasks* in the Data Integration documentation.

Salesforce Analytics objects

Salesforce Analytics does not contain predefined metadata. Salesforce Analytics uses the JSON file format to describe the metadata. You must create a JSON file that contains metadata in the Salesforce Analytics schema format.

To create a JSON file, create a .csv file that contains the data that you want to load into Salesforce Analytics. Use the Salesforce `datasetloader.jar` file to convert the .csv file into a JSON file.

You can also create a JSON file at the time of target creation. On the Target page, click **Create Target**. The Secure Agent generates a JSON file and saves the file to the temporary directory that you specify when creating a connection.

Generating a JSON file

You must create a JSON file before you can import the file into the Salesforce Analytics Connector.

Before you create a JSON file, you must download the `datasetloader.jar`. Contact Salesforce for the `datasetloader.jar` file.

1. Create a .csv file with the supported data types and data.
2. From the command prompt, run the command: `java -jar datasetloader.jar <filename>.csv`.

   A JSON file is created in the Salesforce Analytics schema format.

Manually creating a JSON file

1. Open a text editor and enter data in the following Salesforce Analytics schema format:

```
{
  "fileFormat" : {

  },
  "objects" : [ {
    <object_detail>,
                "fields" : [ {
                                <Field1 details>
                }
                {               <Field2 details>
                }……
    ]
}]
}
```

2. Save and close the file in the .json format.

Sample JSON file

The following example shows a sample JSON file in the Salesforce Analytics schema format:

```
{
  "fileFormat" : {
    "charsetName" : "UTF-8",
    "fieldsDelimitedBy" : ",",
    "fieldsEnclosedBy" : "\"",
    "linesTerminatedBy" : "\n",
    "numberOfLinesToIgnore" : 1
  },
  "objects" : [ {
    "name" : "emp_hf2",
    "fullyQualifiedName" : "emp_hf2",
    "connector" : "SalesforceAnalyticsCloudDatasetLoader",
    "label" : "emp_hf2",
    "description" : "emp_hf2",
    "acl" : null,
    "rowLevelSecurityFilter" : null,
    "fields" : [ {
      "name" : "id",
      "fullyQualifiedName" : "id",
      "label" : "id",
      "description" : "id",
      "type" : "Int",
      "precision" : 10,
      "scale" : 0,
      "defaultValue" : "0",
      "format" : null,
      "isSystemField" : false,
      "isUniqueId" : false,
      "isMultiValue" : false,
      "multiValueSeperator" : null,
      "acl" : null,
      "fiscalMonthOffset" : 0
    }
} ]
```

Salesforce Analytics Connector example

You are a sales analyst in an enterprise. You want to track the overall growth trend in sales, geographic distribution of sales, and top customers, and present a snapshot of the sales distribution to senior executives.

You can integrate data from multiple sources, filter the data, and make the data available on Salesforce Analytics through Salesforce Analytics Connector. You can then use the data for analysis. The visual representation of data helps you understand the profitability, with views presented by geography, product category, and customer segment.

Note: Ensure that the field name does not contain two consecutive underscores. However, you can use `__c` as suffix in the field name when you read data.

Salesforce Analytics target operations

The following table describes Salesforce Analytics Target operations in synchronization and mapping tasks:

Property	Description
Target Load Type	You can choose Normal mode or Bulk mode. Default is Normal mode.
Insert	Inserts a row to the Salesforce Analytics database.
Delete	Deletes a row from the Salesforce Analytics database. When you enable DELETE, the Secure Agent deletes all rows flagged for delete and rejects all rows flagged when you disable DELETE .
Upsert	When you enable UPSERT, the Secure Agent upserts records, links the external ID to the external ID field from the source through the transformations in the target definition. Salesforce uses UPSERT to identify the records that must be upserted.

Administration of Salesforce Analytics Connector

As a user, you can use Salesforce Analytics Connector after the organization administrator ensures that users have access to the Secure Agent directory that contains the success and error files. This directory path must be the same on each Secure Agent machine in the runtime environment.

To avoid a Java heap space error when you create or run a task, set the JVM options for type DTM to increase the -Xmx value in the system configuration details of the Secure Agent. For example, -Xmx1024m. Restart the Secure Agent for the property to take effect.

CHAPTER 2

Salesforce Analytics connections

Create a Salesforce Analytics connection to write data to Salesforce Analytics.

You can use Salesforce Analytics connections to specify targets in synchronization and mapping tasks. When you create a Salesforce Analytics connection, you enter properties specific to Salesforce Analytics.

You can create a Salesforce Analytics connection in the Administrator > Connections page in the Synchronization Task wizard, or in the Mapping Task wizard when you create a task. The connection becomes available to the entire organization to use.

Note: When a connection to Salesforce Analytics fails, the Secure Agent retries a maximum of three attempts at a 300-second interval to establish the connection.

Salesforce Analytics connection properties

When you set up a Salesforce Analytics connection, you must configure the connection properties.

The following table describes the Salesforce Analytics connection properties:

Connection property	Description
Connection Name	Name of the connection. Each connection name must be unique within the organization. Connection names can contain alphanumeric characters, spaces, and the following special characters: _ . + -, Maximum length is 255 characters.
Description	Description of the connection. Maximum length is 4000 characters.
Use Secret Vault	Stores sensitive credentials for this connection in the secrets manager that is configured for your organization. This property appears only if secrets manager is set up for your organization. When you enable the secret vault in the connection, you can select which credentials that the Secure Agent retrieves from the secrets manager. If you don't enable this option, the credentials are stored in the repository or on a local Secure Agent, depending on how your organization is configured. **Note:** If you're using this connection to apply data access policies through pushdown or proxy services, you cannot use the Secret Vault configuration option. For information about how to configure and use a secrets manager, see "Secrets manager configuration" in the Administrator help.

Connection property	Description
Runtime Environment	The name of the runtime environment where you want to run the tasks. Select a Secure Agent or elastic runtime environment. For more information about how to configure and use the runtime environments, see *Runtime Environments* in the Administrator help.
Username	User name of the Salesforce Analytics account.
Password	Password for the Salesforce Analytics account.
Security Token	The token used to login to Salesforce Analytics from an untrusted network.
Service URL	URL of the Salesforce Analytics service that you want to access. For example: `https://login.salesforce.com/services/Soap/u/48.0` In a test or development environment, you might want to access the Salesforce Analytics Sandbox testing environment.
Temp Folder Name	The directory where the Secure Agent stores the JSON files and data archive files. After the successful execution of a task, the temporary .gz files are deleted.
Default Date Format	The date format to read date columns in the JSON file.

CHAPTER 3

Synchronization tasks with Salesforce Analytics Connector

Use the Synchronization task to synchronize data between a source and target.

You can configure a synchronization task using the Synchronization Task wizard.

When you create a task, you can associate it with a schedule to run it at specified times or on regular intervals. Or, you can run it manually. You can monitor tasks that are currently running in the activity monitor and view logs about completed tasks in the activity log.

Salesforce Analytics targets in synchronization tasks

You can use a Salesforce Analytics object as a target in a synchronization task.

When you use Salesforce Analytics target objects, you can select a standard object as the primary source.

You can configure Salesforce Analytics target properties on the **Schedule** page of the Synchronization Task wizard.

The following table describes the Salesforce Analytics advanced target properties:

Advanced Target Property	Description
Target Load Type	Sets the default load type for sessions. You can choose standard or bulk loading.
Target Folder	Sets the location of the target on Salesforce Analytics.
Override Target Dataset	Overwrites the target data before loading data into Salesforce Analytics.
Monitor Job Status	Monitors the status of all the four phases in the Salesforce job. Default is false. For more information on monitor job status, see https://knowledge.informatica.com/s/article/The-status-of-the-Salesforce-Analytics-job-in-Cloud-Data-Integration-does-not-match-the-status-in-Salesforce-Analytics?language=en_US.

Advanced Target Property	Description
Success File Directory	Directory for the success rows file. You must specify a directory path that is available on each Secure Agent machine in the runtime environment to save the success rows file. Ensure that your administrator has granted you access to this directory. If you do not specify a directory, the success rows file is not created.
Error File Directory	Directory for the error rows file. By default, the error rows file is written to the following Secure Agent directory: `<Secure Agent installation directory>\apps\Data_Integration_Server\data\error` Specify a directory path that is available on each Secure Agent machine in the runtime environment. Ensure that your administrator has granted you access to this directory.

Synchronization task example

You work in the retail industry, and business analysts in your enterprise need to analyze product sales trends based on a particular region.

Sales record files can contain information about products that are sold in multiple outlets and regions. You can consolidate the data from the sales record in Salesforce.

Configure a synchronization task to write to Salesforce Analytics.

You perform the following synchronization tasks:

Define the synchronization task.

Configure a synchronization task to use the insert operation.

Use a Salesforce source object.

The source for the synchronization task is a Salesforce connection that contains the product sales data. The Salesforce object is a single source in the synchronization task. Include the Row ID, Order ID, Order Quantity, Order Date, Unit Price, Region, and Product Category source columns in Salesforce. Specify *SALES_RECORDS* as the resource for the source object.


Create a Salesforce Analytics target object.

Select the fields *Row_Id*, *Order_Id*, *Order_Quantity*, *Order_Date*, *Unit_Price*, *Region*, and *Product_Catagory* from the source object that you want to insert into the target object. Provide a name *SALESFORCE_ANALYTICS_SALES* for the target object and specify the connection type as Salesforce Analytics. The synchronization task populates the fields in the location you specify in the connection.

Configure a field mapping.

Map all the fields under *SALES_RECORDS* source data to all the fields in the target *SALESFORCE_ANALYTICS_SALES*. The synchronization task writes the mapped source data to Salesforce Analytics.

The following image shows the mapping of the *SALES_RECORDS* source with the *SALESFORCE_ANALYTICS_SALES* target:




Configure the advanced target properties.

In the advanced target properties, you choose to publish to Salesforce Analytics. Provide the project name *Salesforce_Analytics_Sales* and site name, *Sales*. Specify a directory path that is available on each Secure Agent machine in the runtime environment. Save and run the task.

Open the site in Salesforce Analytics to visualize the exported data.

The following image shows the data categorized by region in Salesforce Analytics.



CHAPTER 4

Mappings and mapping tasks with Salesforce Analytics

Use the Data Integration Mapping Designer to create a mapping. In advanced mode, the Mapping Designer updates the mapping canvas to include transformations and functions that enable advanced functionality.

Salesforce Analytics targets in mappings

When you create a mapping, you can configure a Target transformation to represent a single Salesforce Analytics object.

The following table describes the Salesforce Analytics target properties:

Property	Description
Connection	Name of the target connection.
Target Object	Target object for a single target or primary target object for multiple targets.

Note: You cannot use any of the following as Target Object Name:

- Unicode characters
- Keywords in Java language, such as constants, operators, and built-in variables. These keywords are reserved for specific functions. For example, NULL, NEW, SYSDATE, AND, OR, TRUE, FALSE, SET.

The following table describes the Salesforce Analytics target advanced properties:

Advanced Property	Description
Target Load Type	Sets the default load type for mappings. You can choose standard or bulk loading.
Target Folder	Sets the location of the target on Salesforce Analytics.
Override Target Dataset	Overwrites the target data before loading data into Salesforce Analytics.

Advanced Property	Description
Monitor Job Status	Monitors the status of all the four phases in the Salesforce job. Default is false. For more information on monitor job status, see https://knowledge.informatica.com/s/article/The-status-of-the-Salesforce-Analytics-job-in-Cloud-Data-Integration-does-not-match-the-status-in-Salesforce-Analytics?language=en_US.
Success File Directory	Directory for the success rows file. You must specify a directory path that is available on each Secure Agent machine in the runtime environment to save the success rows file. Ensure that your administrator has granted you access to this directory. If you do not specify a directory, the success rows file is not created.
Error File Directory	Directory for the error rows file. By default, the error rows file is written to the following Secure Agent directory: `<Secure Agent installation directory>/apps/Data_Integration_Server/data/error` Specify a directory path that is available on each Secure Agent machine in the runtime environment. Ensure that your administrator has granted you access to this directory.

Salesforce Analytics targets in synchronization tasks

When you configure a mapping task based on an integration template, you can configure advanced properties for Salesforce Analytics targets.

For Salesforce Analytics target connections used in template-based mapping tasks, you can configure advanced properties in the **Targets** page of the Mapping Task wizard.

The following table describes the Salesforce Analytics target advanced properties:

Advanced Property	Description
Target Load Type	Sets the default load type for mappings. You can choose standard or bulk loading.
Target Folder	Sets the location of the target on Salesforce Analytics.
Override Target Dataset	Overwrites the target data before loading data into Salesforce Analytics.
Success File Directory	Directory for the success rows file. You must specify a directory path that is available on each Secure Agent machine in the runtime environment to save the success rows file. Ensure that your administrator has granted you access to this directory. If you do not specify a directory, the success rows file is not created.
Error File Directory	Directory for the error rows file. By default, the error rows file is written to the following Secure Agent directory: `<Secure Agent installation directory>\apps\Data_Integration_Server\data\error` Specify a directory path that is available on each Secure Agent machine in the runtime environment. Ensure that your administrator has granted you access to this directory.

CHAPTER 5

Data type reference

Data Integration uses the following data types in mappings, synchronization tasks, and mapping tasks with Salesforce Analytics:

Salesforce Analytics Native Data Types

Salesforce Analytics data types appear in the Target transformations when you edit metadata for the fields.

Transformation Data Types

Set of data types that appear in the transformations. They are internal data types based on ANSI SQL-92 generic data types, which the Secure Agent uses to move data across platforms. Transformation data types appear in all transformations in mappings, synchronization tasks, and mappingtasks.

When Data Integration reads source data, it converts the native data types to the comparable transformation data types before transforming the data. When Data Integration writes to a target, it converts the transformation data types to the comparable native data types.

Salesforce Analytics and transformation data types

The following table lists the Salesforce Analytics data types that the Secure Agent supports and the corresponding transformation data types:

Salesforce Analytics Data Type	Transformation Data Type	Description
DateTime	Date/Time	Jan 1, 0001 A.D. to Dec 31, 9999 A.D. (precision to nanosecond)
Int	Integer	-2,147,483,648 to 2,147,483,647 Precision of 10, scale of 0 Integer value.
String	String	1 to 104,857,600 characters

INDEX

A

administration 9

C

Cloud Application Integration community
  URL 4
Cloud Developer community
  URL 4
connections
  Salesforce Analytics 10

D

data filters 13
Data Integration community
  URL 4
data type reference
  overview 17

I

Informatica Global Customer Support
  contact information 5
Informatica Intelligent Cloud Services
  web site 4

M

maintenance outages 5
Mapping tasks
  Salesforce Analytics target properties 16
mappings
  Salesforce Analytics target properties 15
metadata file 9

O

ODBC
  Synchronization task 12

S

Salesforce Analytics
  connection properties 10
  Target transformation 15
  targets in Mapping tasks 16
  targets in mappings 15
  targets in Synchronization tasks 12
Salesforce Analytics Connector
  creating a metadata file 7
  data types 17
  overview 10
  salesforce analytics introduction 6
status
  Informatica Intelligent Cloud Services 5
Synchronization task
  example 13
Synchronization tasks
  Salesforce Analytics target properties 12
system status 5

T

Target transformation
  Salesforce Analytics properties 15
targets
  Salesforce Analytics in Mapping tasks 16
  Salesforce Analytics in mappings 15
  Salesforce Analytics in Synchronization tasks 12
trust site
  description 5

U

upgrade notifications 5

W

web site 4