Informatica®

Informatica® Cloud Data Integration

JIRA Connector

Informatica Cloud Data Integration JIRA Connector
July 2025

© Copyright Informatica LLC 2016, 2025

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, Informatica Cloud, and PowerCenter are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2025-10-03

Table of Contents

Preface 4

Informatica Resources 4

- Informatica Documentation 4
- Informatica Intelligent Cloud Services web site 4
- Informatica Intelligent Cloud Services Communities 4
- Informatica Intelligent Cloud Services Marketplace 4
- Data Integration connector documentation 5
- Informatica Knowledge Base 5
- Informatica Intelligent Cloud Services Trust Center 5
- Informatica Global Customer Support 5

Chapter 1: Introduction to JIRA Connector 6

JIRA Connector supported objects and task operations 6

JIRA Connector assets 7

Chapter 2: Connections for Jira 8

Connect to Jira 8

- Before you begin 8
- Connection details 8

Chapter 3: Synchronization Tasks with JIRA Connector 10

Creating a Synchronization Task 10

- Rules and Guidelines for Synchronization Task 11

Configure the Data Filter 12

- Rules and Guidelines for Data Filters Task 12

Configure an Advanced Data Filter 13

- Rules and Guidelines for Advanced Filters 13

Configuring the Field Length 13

Troubleshooting a Synchronization Task 14

Chapter 4: Mappings and mapping tasks with JIRA Connector 15

JIRA sources in mappings 15

JIRA targets in mappings 16

Index 17

Preface

Use *JIRA Connector* to learn how to read from or write to JIRA by using Cloud Data Integration. Learn to create a connection and run synchronization and mapping tasks in Cloud Data Integration.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Intelligent Cloud Services web site

You can access the Informatica Intelligent Cloud Services web site at http://www.informatica.com/cloud. This site contains information about Informatica Cloud integration services.

Informatica Intelligent Cloud Services Communities

Use the Informatica Intelligent Cloud Services Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the Informatica Intelligent Cloud Services Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

Informatica Intelligent Cloud Services Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Intelligent Cloud Services Trust Center

The Informatica Intelligent Cloud Services Trust Center provides information about Informatica security policies and real-time system availability.

You can access the trust center at https://www.informatica.com/trust-center.html.

Subscribe to the Informatica Intelligent Cloud Services Trust Center to receive upgrade, maintenance, and incident notifications. The Informatica Intelligent Cloud Services Status page displays the production status of all the Informatica cloud products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single component or all Informatica Intelligent Cloud Services components. Subscribing to all components is the best way to be certain you never miss an update.

To subscribe, on the Informatica Intelligent Cloud Services Status page, click **SUBSCRIBE TO UPDATES**. You can choose to receive notifications sent as emails, SMS text messages, webhooks, RSS feeds, or any combination of the four.

Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the Informatica Intelligent Cloud Services Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

Introduction to JIRA Connector

Use JIRA Connector to connect to JIRA, read data, and write data to applications, such as Salesforce, flatfile, and databases. You can also read data from other applications and write to JIRA. You can create custom fields in JIRA. You can use Jira Connector to read the custom attributes that are present in an object.

You can use JIRA Connector to read and write JIRA issues and to filter all the fields that JIRA Rest API supports. JIRA Connector supports the Contains operator.

You can switch mappings to advanced mode to include transformations and functions that enable advanced functionality.

JIRA Connector supported objects and task operations

The following table lists the object types and the task operations that JIRA Connector supports:

Objects	Read	Data Preview	Lookup
Projects/Issues	Yes	Yes	Yes
Projects/Attachment	Yes	Yes	Yes
Projects/Comments	Yes	Yes	Yes
Projects/LinkedIssues	Yes	Yes	Yes
Components	Yes	Yes	Yes
Projects/FixVersions	Yes	Yes	Yes
Projects/Watchers	Yes	Yes	Yes
Projects/AffectsVersion	Yes	Yes	Yes
Projects/Components	Yes	Yes	Yes

In JIRA Connector, you can use special characters in the Project field.

JIRA Connector assets

Create assets in Data Integration to integrate data using JIRA Connector.

When you use JIRA Connector, you can include the following Data Integration assets:

- Mapping
- Mapping task

For more information about configuring assets and transformations, see *Mappings*, *Transformations*, and *Tasks* in the Data Integration documentation.

CHAPTER 2

Connections for Jira

Create a JIRA connection to connect to JIRA so that you can read data from and write data to JIRA. You can use the JIRA connection to specify source or target objects in synchronization tasks, mappings, and mapping tasks.

Connect to Jira

Let's configure the JIRA connection properties to connect to JIRA.

Before you begin

Before you configure a connection, you'll need to get the user name, password, and the base URL from your Jira account.

The following video shows you how to get the information you need:



Connection details

The following table describes the basic connection properties:

Property	Description
Connection Name	Name of the connection. Each connection name must be unique within the organization. Connection names can contain alphanumeric characters, spaces, and the following special characters: _ . + -, Maximum length is 255 characters.
Description	Description of the connection. Maximum length is 4000 characters.

Property	Description
Use Secret Vault	Stores sensitive credentials for this connection in the secrets manager that is configured for your organization. This property appears only if secrets manager is set up for your organization. When you enable the secret vault in the connection, you can select which credentials that the Secure Agent retrieves from the secrets manager. If you don't enable this option, the credentials are stored in the repository or on a local Secure Agent, depending on how your organization is configured. **Note:** If you're using this connection to apply data access policies through pushdown or proxy services, you cannot use the Secret Vault configuration option. For information about how to configure and use a secrets manager, see "Secrets manager configuration" in the Administrator help.
Runtime Environment	The name of the runtime environment where you want to run tasks. Select a Secure Agent, Hosted Agent, serverless, or elastic runtime environment. Hosted Agent doesn't apply to mappings in advanced mode. For more information about how to configure and use the runtime environments, see *Runtime Environments* in the Administrator help.
Username	User name of the JIRA account.
Password	Password of the JIRA account.
URI	The base URL of your Jira instance. For example, if your JIRA instance is hosted at mycompany.atlassian.net, the URI is https://mycompany.atlassian.net/.

Advanced settings

The following table describes the advanced connection properties:

Property	Description
UTC Offset	Appends the Coordinated Universal Time (UTC) to your datetime field to represent the time in your time zone. Select the UTC offset from the list based on your time zone. The adjustment to UTC yields the local time based on your region. UTC is expressed as UTC±, with a plus sign (+) that indicates time ahead of UTC and a minus sign (-) indicates time behind UTC. For instance, if your location is 5 hours ahead of UTC, select UTC+5. If your location is 3 hours behind UTC, select UTC-3. Default is UTC.
Enable Logging	Enables logging for the connector. Select the checkbox to enable logging when you create a connection, and use the connection to import metadata and run tasks. You can access the connection and design time logs in the Tomcat in the following location: `<Secure Agent installation directory>\apps\Data_Integration_Server\logs\tomcat` For the runtime logs, see the session log in the **My Jobs** page.

CHAPTER 3

Synchronization Tasks with JIRA Connector

This chapter includes the following topics:

- Creating a Synchronization Task , 10
- Configure the Data Filter, 12
- Configure an Advanced Data Filter, 13
- Configuring the Field Length, 13
- Troubleshooting a Synchronization Task, 14

Creating a Synchronization Task

Create a JIRA connection before you create a synchronization task.

1. In Data Integration, click **New** > **Tasks**.
2. Select **Synchronization Task**, and click **Create**.

   The New Synchronization Task page appears.
3. Specify the task name, provide a description, and select the Insert task operation.
4. Click **Next**.

   The **Source** tab appears.
5. Select the source **Connection**, **Source Type**, and **Source Objects** for the task.
6. Click **Next**.

   The **Target** tab appears.
7. Select the target connection and target object.
8. Click **Next**.

   The **Data Filters** tab appears.
9. To assign filters to the synchronization task, see "Configure the Data Filter" on page 12.
10. Configure the data filter, and click **Next**.
11. On the **Field Mapping** tab, enter JIRA projectkey in the Project field, while performing insert, update and delete operations into JIRA application for any project object.
12. Click **Next**.

The **Schedule** tab appears.

13. In the advance Source properties, use the read time out attribute to specify the maximum number of milliseconds that the connector waits to connect to JIRA. You can use the Retry Count attribute to specify the number of times to reconnect to JIRA. If the response code is other than 200 or the read time out is achieved, the connector attempts to reconnect to JIRA.
14. Schedule the task according to the requirement and save. If you do not want to schedule the task, click **Save** to save the task.

Rules and Guidelines for Synchronization Task

Consider the following guidelines to configure a synchronization task:

- The fields in the synchronization task must not contain duplicate names.
- The field names can have a maximum length of 65 characters.
- You need to create separate synchronization tasks for child objects, such as comments, attachments, and linked issues.
- You cannot use array data type fields.
- You cannot use custom data types for JIRA plugin custom fields. You can only use standard data types for JIRA plugin custom fields.
  You can use the following standard data types:
  - com.atlassian.jira.plugin.system.customfieldtypes:cascadingselect
  - com.atlassian.jira.plugin.system.customfieldtypes:datepicker
  - com.atlassian.jira.plugin.system.customfieldtypes:datetime
  - com.atlassian.jira.plugin.system.customfieldtypes:textarea
  - com.atlassian.jira.plugin.system.customfieldtypes:grouppicker
  - com.atlassian.jira.plugin.system.customfieldtypes:labels
  - com.atlassian.jira.plugin.system.customfieldtypes:multigrouppicker
  - com.atlassian.jira.plugin.system.customfieldtypes:multiselect
  - com.atlassian.jira.plugin.system.customfieldtypes:multiuserpicker
  - com.atlassian.jira.plugin.system.customfieldtypes:float
  - com.atlassian.jira.plugin.system.customfieldtypes:project
  - com.atlassian.jira.plugin.system.customfieldtypes:radiobuttons
  - com.atlassian.jira.plugin.system.customfieldtypes:select
  - com.atlassian.jira.plugin.system.customfieldtypes:version
  - com.atlassian.jira.plugin.system.customfieldtypes:textfield
  - com.atlassian.jira.plugin.system.customfieldtypes:url
  - com.atlassian.jira.plugin.system.customfieldtypes:userpicker
  - com.atlassian.jira.plugin.system.customfieldtypes:multiversion
  - com.atlassian.jira.plugin.system.customfieldtypes:readonlyfield
  - com.atlassian.jira.plugin.system.customfieldtypes:multicheckboxes
  - com.atlassian.jira.plugin.system.customfieldtypes:importid

Configure the Data Filter

You can use data filters to fetch specific data of a particular object. The synchronization task processes the data based on the filter field assigned to the object.

1. In the synchronization task, select **Data Filters** tab.

   The **Data Filters** tab appears.
2. Click **New**.

   The Data Filter dialog box appears.
3. Specify the following details:

Field Type	Description
Object	Object for which you want to assign filter fields.
Filter By	Lists all filter fields. Select the filter field.
Operator	Functional operator. Select the corresponding operator.
Filter Value	Specific filter value. Enter the filter value.

4. Click **OK**.

Rules and Guidelines for Data Filters

Consider the following rules and guidelines to configure data filters when you use JIRA Connector:

- You can filter only those fields that the JIRA REST APIs support.
- Data Filters does not filter the array data type fields.
- In basic filters, encode the special characters in the search string with relevant JIRA escape sequences.
- You cannot filter the project field. It is automatically embedded in the query based on the selected source object.
- Basic filter has time zone support for all datetime fields. You can select the time zone on the Connections page.

  Note: If an existing task has datetime fields in a filter, JIRA Connector applies the default time zone for the datetime fields. If you change the time zone in the Connections page, refresh the existing tasks to update the time zone.
- You can use all the filter fields that are available in JIRA. You also have the option of creating custom fields in your JIRA application.

Configure an Advanced Data Filter

Use the Advanced Data Filter to execute search queries that contains complex filter expressions. Advanced data filter operation functions similarly to the Advanced Filter operation in JIRA Application.JIRA Application uses the same syntax which the connector uses.

1. In **Data Filter** dialog box, click **Advanced**.

   The **Advanced Data Filter** dialog box appears.
2. Enter the **Filter Expression**.
3. Click **OK**.

Rules and Guidelines for Advanced Filters

Consider the following guidelines to configure advanced filters in JIRA Connector:

- You can filter all the fields that JIRA advanced search supports.
- JIRA advanced filters does not support $LastRunTime command.
- You must select the **Advanced Data Filter** option to select fields that contain space characters to be used in filters. Enclose the field name in double quotes. For example, in JIRA advance search , "Group Picker" = JIRA-Administrators.
- Mention the project field when you select __ALL_PROJECTS object type.
- Do not mention the Project field in the filter Expression for other object types. The connector affixes the project field internally.
- Advanced filter does not support time zone for datetime fields.

Configuring the Field Length

The following fields, **field length** can be configured using `jirafields.ini` file:

- Comments
- Description
- Environment
- File Size
- Standard Custom field text area (Free text)

Configure the custom fields in the `jirafields.ini` file located in the following directories:

- `<Secure Agent installation directory>\downloads\<latest connector zip package>\package \plugins\<Plugin ID>\`
- `<Secure Agent installation directory>\downloads\<latest connector zip package>\package \rdtm\javalib\<Plugin ID>\`

Troubleshooting a Synchronization Task

If you configure a synchronization task that is not valid, a NULL error message appears. The null error message files are saved in specific location.

For example, `<Secure Agent installation directory>\apps\Data_Integration_Server\<latest version of connector>\ICS\main\tomcat\log`

The log and exception details of a failed synchronization task are captured under the Session Log. You require special permission privileges to run the application in debug mode.

CHAPTER 4

Mappings and mapping tasks with JIRA Connector

Use the Data Integration Mapping Designer to create a mapping. When you create a mapping, you can configure a source or a target to represent a JIRA object.

Validate the mapping and describe the flow of data from source and target along with the required transformations before the Secure Agent reads data from or writes data to the JIRA object. Use the Mapping Task wizard to create a mapping task and select the mapping that you configured. The mapping task processes data based on the data flow logic you define in the mapping. Run the mapping task to read data from or write data to a JIRA object.

In advanced mode, the Mapping Designer updates the mapping canvas to include transformations and functions that enable advanced functionality.

JIRA sources in mappings

When you create a mapping, you can configure the source properties to use JIRA objects to read the data from your JIRA account. The source properties appear on the **Source** tab when you specify a JIRA connection.

The following table describes the JIRA source properties.

Source Property	Description
Connection Type	Name of the JIRA source connection.
Source Type	Select **Single** or **Multiple** as the source type. Select **Single** to read data from a standard JIRA object. Select **Multiple** to read data from a standard JIRA object and add a single child object.
Source Object	Select the JIRA source object for the task.

The following table describes the query options that you can configure in a Source transformation:

Property	Description
Filter	Filter value in a read operation. Click **Configure** to add conditions to filter records and reduce the number of rows that the Secure Agent reads from the source. Select **Not Parameterized** filter condition and use a basic filter to specify the object, field, operator, and value to select specific records. You can use advanced filters to execute search queries that contain complex filter expressions. For more information, see "Rules and Guidelines for Data Filters" on page 12 and "Rules and Guidelines for Advanced Filters" on page 13.
Sort	Not applicable.

The following table describes the advanced properties that you configure for a JIRA source object:

Property	Description
Source Filter	The filter to be applied when you query an entity.
Sorted Ports	The ports used to sort the source data.
Maximum Page Size	The maximum number of records read from JIRA in a page.
Read Time Out	The timeout value in milliseconds for a read operation. For example, 1000 milliseconds
Read Retry Count	The retry value for a read operation.

JIRA targets in mappings

When you configure a mapping, you can use JIRA Connector as a target connection to write data to your JIRA account. The target properties appear on the **Target** tab when you specify a JIRA connection.

The following table describes the JIRA target properties:

Target Property	Description
Connection	Name of the JIRA target connection.
Target Type	Select **Single** or **Multiple** as the target type. Select **Single** to write data to a standard JIRA object. Select **Multiple** to write data to a standard JIRA object and add a single child object.
Object	Select the target object for the task.
Operation	Select the target operation. You can perform insert, update, and delete operations with JIRA Connector.

Note: The advanced properties are not applicable for a JIRA target.

INDEX

A

Aadvanced Data Filter
  configuring 13
  filter expression 13

C

Cloud Application Integration community
  URL 4
Cloud Developer community
  URL 4
connections
  JIRA 8

D

Data Filter
  configure 12
Data Integration community
  URL 4

F

Field length
  configuring 13
  jirafields 13

I

Informatica Global Customer Support
  contact information 5
Informatica Intelligent Cloud Services
  web site 4

J

JIRA
  connection properties 8
JIRA connector
  assets 7
JIRA Connector
  functionality 6
  object types 6
  overview 6

M

maintenance outages 5

S

status
  Informatica Intelligent Cloud Services 5
synchronization task
  troubleshooting 14
system status 5

T

trust site
  description 5

U

upgrade notifications 5

W

web site 4