Informatica®

Informatica® Cloud Data Integration

JSON Target Connector

Informatica Cloud Data Integration JSON Target Connector
November 2024

© Copyright Informatica LLC 2015, 2025

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, Informatica Cloud, and PowerCenter are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2025-08-07

Table of Contents

Preface 4

Informatica Resources 4

- Informatica Documentation 4
- Informatica Intelligent Cloud Services web site 4
- Informatica Intelligent Cloud Services Communities 4
- Informatica Intelligent Cloud Services Marketplace 4
- Data Integration connector documentation 5
- Informatica Knowledge Base 5
- Informatica Intelligent Cloud Services Trust Center 5
- Informatica Global Customer Support 5

Chapter 1: Introduction to JSON Target Connector 6

JSON Target Supported Task Types and Objects Types 6

How JSON Target Connector Works 6

Chapter 2: JSON Target Connections 9

JSON Target Connections Overview 9

JSON Target connection properties 9

Rules and Guidelines for JSON Target Connections 10

Chapter 3: Synchronization Tasks with JSON Target Connector 11

JSON Target Targets in Synchronization Tasks 11

Working with the JSON File 11

- Updating or Merging the Existing JSON File 11
- Cleaning the Merged JSON File 12
- Passing Null Values in the Source File 14

Chapter 4: Troubleshooting 16

Increasing Secure Agent Memory 16

Index 18

Preface

Use *JSON Target Connector* to learn how to read from or write to a REST based web service application by using Cloud Data Integration. Learn to create a connection and run synchronization tasks in Cloud Data Integration.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Intelligent Cloud Services web site

You can access the Informatica Intelligent Cloud Services web site at http://www.informatica.com/cloud. This site contains information about Informatica Cloud integration services.

Informatica Intelligent Cloud Services Communities

Use the Informatica Intelligent Cloud Services Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the Informatica Intelligent Cloud Services Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

Informatica Intelligent Cloud Services Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Intelligent Cloud Services Trust Center

The Informatica Intelligent Cloud Services Trust Center provides information about Informatica security policies and real-time system availability.

You can access the trust center at https://www.informatica.com/trust-center.html.

Subscribe to the Informatica Intelligent Cloud Services Trust Center to receive upgrade, maintenance, and incident notifications. The Informatica Intelligent Cloud Services Status page displays the production status of all the Informatica cloud products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single component or all Informatica Intelligent Cloud Services components. Subscribing to all components is the best way to be certain you never miss an update.

To subscribe, on the Informatica Intelligent Cloud Services Status page, click **SUBSCRIBE TO UPDATES**. You can choose to receive notifications sent as emails, SMS text messages, webhooks, RSS feeds, or any combination of the four.

Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the Informatica Intelligent Cloud Services Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

Introduction to JSON Target Connector

You can use JSON Target Connector to connect to JSON Target from Data Integration. Use JSON Target Connector to write data to a REST based Web Services.

The JSON Target Connector converts source data into JSON format by providing JSON template. You can use JSON Target Connector objects as targets in synchronization tasks.

JSON Target Supported Task Types and Objects Types

The following table lists the JSON Target object and operation types that you can include in Data Integration tasks:

Objects	Select	Insert	Update	Upsert	Delete	Data Preview	Lookup
JSON Target	NA	Yes	Yes	NA	NA	NA	NA


How JSON Target Connector Works

Let us consider a sample JSON file, which provides Customer-Address details, to explain how JSON Target Connector works.

JSON Target Connector is based on the following principles:

- The XPaths are the building blocks of JSON Target Connector.
- JSON Target Connector parses the JSON file and generates the XPaths of each JSON object or JSON array.
- JSON Target Connector uses the XPaths to generate XML file with adequate primary and foreign key relationships.
- The XMLStreamReader and XMLStreamWriter cleans the generated XML file.
- The cleaned XML file is transformed into a valid JSON file based on the SAXevent parsing approach.

The following figure shows a sample JSON file of Customer - Address details.




```
{
    "Customers" : {
        "Customer" : {
            "Name" : "Satish",
            "DOB" : 1983,
            "Age" : 29,
            "Address" : [ {
                "Line1" : "Radiant",
                "Line2" : "Bangalore",
                "Pincode" : 560048
            } , {
                "Line1" : "Radiant1",
                "Line2" : "Bangalore1",
                "Pincode" : 5600481
            } ]
        }
    }
}
```

JSON Target Connector follows the following principles to group elements into tables or fields:

- JSON file must have root element. When the JSON file does not contain any root element, then the connector creates a dummy root called JSONRoot. The root element is used for further processing of files.
- All the simple and attribute elements are considered as fields. Complex elements are not considered as fields.
- Unbound elements are segregated and considered as separate tables.
- Any bound element to the former element becomes the child element of the former element.
  Based on the sample file shown in the above figure, the following tables are created:
  - Table-1: JsonRoot with XPath/JsonRoot
  - Table-2: Customers_Customer_Address with XPath/Customers/Customer/Address

The following figure shows the tables written to the target:



CHAPTER 2

JSON Target Connections

This chapter includes the following topics:

- JSON Target Connections Overview, 9
- JSON Target connection properties, 9
- Rules and Guidelines for JSON Target Connections, 10

JSON Target Connections Overview

Create a JSON Target connection to connect to JSON Target and write data to a REST based Web Services. You can use JSON Target connections in a synchronization task.

JSON Target connection properties

When you create a JSON Target connection, you must configure the connection properties.

Important: JSON Target Connector is deprecated and has been moved to maintenance mode. Informatica intends to drop support in a future release. Informatica recommends that you use Hadoop Files V2 Connector to access JSON Target.

The following table describes the JSON Target connection properties:

Connection property	Description
Secure Agent	Select the appropriate Secure Agent from the list.
Sample JSON Schema Name	Enter sample JSON file path. For example, `ABCD.JSON`.
JSON Working Directory	Enter the folder path for JSON working directory.
Final JSON File Name	Enter final JSON file path with the file name.

Connection property	Description
Requires JSON Customization	Allows JSON customization. Default is **NO**.
Final Customized JSON File Name	Enter final customized JSON file path with the file name.

Rules and Guidelines for JSON Target Connections

Consider the following rules and guidelines when you create a JSON Target connection:

- The JSON file must have a valid `.JSON` file extension.
- The JSON file must not have references pertaining to other JSON files.
- The JSON files from the same root element can be merged together.
- Do not run the same synchronization task repeatedly. It creates duplicate JSON records.
- When you perform the insert operation, the Secure Agent creates a new merged file.
- After you have created a clean file, the synchronization task generates `*.JSON` file which contains XPK and XFK elements with suffix removed.
- JSON Target Connector does not support data preview.

CHAPTER 3

Synchronization Tasks with JSON Target Connector

This chapter includes the following topics:

- JSON Target Targets in Synchronization Tasks, 11
- Working with the JSON File, 11

JSON Target Targets in Synchronization Tasks

You can use a JSON Target object as a target in a synchronization task.

The following table describes the JSON Target target properties:

Property	Description
Connection	Name of the JSON Target target connection.
Target Object	Name of the JSON Target target object.
Child Object	This attribute is not applicable for JSON Target Connector.
Display target fields in alphabetical order	Displays target fields in alphabetical order. By default, fields appear in the order returned by the target system.

Working with the JSON File

You can perform the following tasks with a JSON file in a synchronization task.

Updating or Merging the Existing JSON File

When you want to add other modules such as address, phone numbers, location, references to existing JSON file, select **Update** as the task operation.

1. Create a new synchronization task.

2. In **Definition** tab, select **Update** as the task operation.
3. Follow the same procedure of creating a JSON Target file using Insert task operation to update the existing JSON file.

Note: In Source tab, select the source object file with which you want to update-merge the existing JSON file.


Note: In Target tab, select the target object that is the child element of the element present in the existing JSON target file.

Cleaning the Merged JSON File


You must clean the merged JSON file to remove all the unnecessary syntax and quotes.

1. Select the updated synchronization task in the synchronization page.
2. Create a copy of the task.
3. Click **Edit** to rename the task.
4. In the **Field Mapping** tab, click edit next to the **ISFINALJSON** field.

   The Field Expression page appears. The following image shows the **Field Mapping** tab:




5. Enter the value of the **ISFINALJSON** field as 'false' to 'true accordingly.



- Enter ‘false’ for creating and updating the JSON target file
- Enter ‘true’ for cleaning the JSON target file.


6. Click **Save and run** the task.

The following image shows the updated and cleaned JSON Target File:



```
{
    "XPK.0" : 0,
    "Customers.0" : {
        "Customer.0" : {
            "DOB.0" : 1983,
            "Age.0" : 29,
            "Name.0" : "Satish",
            "Address.0" : {
                "XPK.0" : 0,
                "XFK.0" : 0,
                "Line1.0" : "radiant",
                "Line2.0" : "bangalore",
                "Pincode.0" : 48
            },
            "Address.CUSTOMDUPLICATE" : ,
            "Address.1" : {
                "XPK.1" : 1,
                "XFK.1" : 0,
                "Line1.1" : "AvinashNgr",
                "Line2.1" : "bhopal",
                "Pincode.1" : 21
            }
        }
    },
    "XPK.1" : 1,
    "Customers.1" : {
        "Customer.1" : {
            "DOB.1" : 1985,
            "Age.1" : 27,
            "Name.1" : "Sachin"
        }
    }
}
```

UPDATED JSON Target File



```
{
    "Customers" : [ {
        "Customer" : {
            "DOB" : 1983,
            "Age" : 29,
            "Name" : "Satish",
            "Address" : [ {
                "Line1" : "radiant",
                "Line2" : "bangalore",
                "Pincode" : 48
            } , {
                "Line1" : "AvinashNgr",
                "Line2" : "bhopal",
                "Pincode" : 21
            } ]
        }
    }, {
        "Customer" : {
            "DOB" : 1985,
            "Age" : 27,
            "Name" : "Sachin"
        }
    } ]
}
```

Cleaned JSON Target File

The following are the XPK and XFK values for the given sample JSON file.

	A	B	C	D	E	F	G	H
1	Name	DOB	Age	Line1	Line2	Pincode	XPK	XFK
2	Satish	1983	29	radiant	bangalore	48	0	0
3	Sachin	1985	27	AvinashNgr	bhopal	21	1	0

Passing Null Values in the Source File


You can use the `config.ini` file to pass null values to the empty fields in the source file.

The values provided in the `config.ini` file replaces all empty fields of the source file in the target JSON file.

You can customize the `config.ini` file located in the following directories:

- `<Secure Agent installation directory>\downloads\<latest connector zip package>\package \plugins\<Plugin ID>`
- `<Secure Agent installation directory>\downloads\<latest connector zip package>\package \rdtm\javalib\<Plugin ID>`

For example, you can pass null value for the replace_empty_xml_field field as shown in the following figure:



When you provide the value as null, the value is considered as null for all the empty parameters. You can also provide empty string (“ ”) as a value for this field. Any other values, besides null and empty string (“ ”) are considered as null.

CHAPTER 4

Troubleshooting

This chapter includes the following topic:


- Increasing Secure Agent Memory, 16

Increasing Secure Agent Memory

To increase performance and avoid runtime environment memory issues, perform the following steps:

1. In Administrator, select **Runtime Environments**.
2. Select the Secure Agent for which you want to increase memory from the list of available Secure Agents.
3. In the **System Configuration Details** section, select the **Type** as **TOMCAT JRE** .

The following images shows the **System Configuration Details** box:



4. Edit **INFA_Memory** as **–Xms256m-Xmx512m**.

   The default value is **–Xms32m-Xmx256m**.
5. Click **OK**.
6. In the **System Configuration Details** section, select the **Type** as **DTM**.
7. Edit **JVMOption1** as **–Xmx512m**.
8. Click **OK**.
9. Restart the Secure Agent.

INDEX

C

cleaning the merged JSON file 12
Cloud Application Integration community
  URL 4
Cloud Developer community
  URL 4
connections
  JSON Target 9

D

Data Integration community
  URL 4

I

Informatica Global Customer Support
  contact information 5
Informatica Intelligent Cloud Services
  web site 4

J

JSON Target
  object types 6
  task types 6
JSON Target connection
  properties 9
JSON Target connections
  overview 9
  rules and guidelines 10
JSON Target Connector
  overview 6
JSON Target targets
  Synchronization task 11

M

maintenance outages 5

S

Secure Agent
  increasing memory 16
status
  Informatica Intelligent Cloud Services 5
system status 5

T

trust site
  description 5

U

upgrade notifications 5

W

web site 4
working with the JSON file 11