Informatica

Informatica® Cloud Data Integration

OData Connector

Informatica Cloud Data Integration OData Connector
July 2025

© Copyright Informatica LLC 2015, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, Informatica Cloud, and PowerCenter are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-04-10

Table of Contents

Preface 4

Informatica Resources 4

- Informatica Documentation 4
- IDMC web site 4
- IDMC Communities 4
- IDMC Marketplace 4
- Data Integration connector documentation 5
- Informatica Knowledge Base 5
- IDMC Trust Center 5
- Informatica Global Customer Support 5

Chapter 1: Introduction to OData Connector 6

OData Connector assets 6

Chapter 2: OData connections 7

Connect to OData 7

- Before you begin 7
- Connection details 7
- Advanced settings 8

Proxy server settings 8

Chapter 3: Synchronization tasks with OData Connector 9

OData sources in synchronization tasks 9

OData targets in synchronization tasks 9

Chapter 4: Mappings and mapping tasks with OData Connector 11

OData sources in mappings 11

OData targets in mappings 12

Rules and guidelines for OData mappings 13

Troubleshooting 13

Chapter 5: Data type reference 14

OData and transformation data types 14

Index 15

Preface

Use *OData Connector* to learn how to read from or write to an OData service by using Cloud Data Integration. Learn to create an OData connection, develop mappings, and run mapping and synchronization tasks in Cloud Data Integration.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

IDMC web site

You can access the IDMC web site at http://www.informatica.com/cloud. This site contains information about Informatica Cloud integration services.

IDMC Communities

Use the IDMC Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the IDMC Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

IDMC Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

IDMC Trust Center

The IDMC Trust Center provides information about Informatica security policies and real-time system availability.

You can access the trust center at https://www.informatica.com/trust-center.html.

Subscribe to the IDMC Trust Center to receive upgrade, maintenance, and incident notifications. The Informatica Intelligent Cloud Services Status page displays the production status of all the Informatica cloud products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single component or all IDMC components. Subscribing to all components is the best way to be certain you never miss an update.

To subscribe, on the Informatica Intelligent Cloud Services Status page, click **SUBSCRIBE TO UPDATES**. You can choose to receive notifications sent as emails, SMS text messages, webhooks, RSS feeds, or any combination of the four.

Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the IDMC Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

Introduction to OData Connector

Open Data Protocol (OData) is an OASIS standard that defines best practices to build and consume RESTful APIs.

You can focus on business logic and build RESTful APIs with OData instead of defining request headers, response headers, status codes, HTTP methods, URL conventions, media types, payload formats and the query options. OData guides you to track changes and define functions, or actions for reusable procedures and send asynchronous, or batch requests. Use OData for extension and to fulfill any custom needs of your RESTful APIs. OData builds on core protocols, such as HTTP and commonly recognized methodologies like REST.

OData Connector integrates Data Integration with systems, such as SharePoint, databases, SAP OData services, and Team Foundation Services. These systems are OData compliant, on-premise compliant or cloud applications compliant. OData Connector communicates with these systems in the OData protocol. OData Connector uses restful API calls to connect to an OData service. Rest calls can be in XML or JSON format. Choose the format that the OData service supports. Use OData Connector to connect to endpoints that support OData protocol version 2.

Create an OData connection to specify objects that are exposed in an OData service that you want to include in a task. You can use the OData connection in synchronization tasks, mappings, and mapping tasks.

You can configure a synchronization task using the Synchronization Task wizard. Create a synchronization task to synchronize data between a source and target. You can perform insert, update, upsert, or delete operations on OData objects.

Create a mapping task to process data based on the data flow logic defined in a mapping or integration template. You can switch mappings to advanced mode to include transformations and functions that enable advanced functionality.

OData Connector assets

Create assets in Data Integration to integrate data using OData Connector.

When you use OData Connector, you can include the following Data Integration assets:

- Mapping
- Mapping task
- Synchronization task

For more information about configuring assets and transformations, see *Mappings*, *Transformations*, and *Tasks* in the Data Integration documentation.

CHAPTER 2

OData connections

Create an OData connection to read data from or write data to an OData service.

Use the connection to specify sources and targets in mappings and mapping tasks.

Connect to OData

Let's configure the OData connection properties to connect to OData.

Before you begin

Before you configure the connection properties, keep the user name, password, and endpoint URI from the OData service handy.

Connection details

The following table describes the basic connection properties:

Property	Description
Connection Name	Name of the connection. Each connection name must be unique within the organization. Connection names can contain alphanumeric characters, spaces, and the following special characters: _ . + -, Maximum length is 255 characters.
Description	Description of the connection. Maximum length is 4000 characters.
Use Secret Vault	Stores sensitive credentials for this connection in the secrets manager that is configured for your organization. This property appears only if secrets manager is set up for your organization. When you enable the secret vault in the connection, you can select which credentials that the Secure Agent retrieves from the secrets manager. If you don't enable this option, the credentials are stored in the repository or on a local Secure Agent, depending on how your organization is configured. For information about how to configure and use a secrets manager, see "Secrets manager configuration" in the Administrator help.

Property	Description
Runtime Environment	The name of the runtime environment where you want to run tasks. Select a Secure Agent, Hosted Agent, elastic, or serverless runtime environment. For more information about how to configure and use the runtime environments, see *Runtime Environments* in the Administrator help.
User Name	User name to connect to the OData service.
Password	Password associated with the user name.
Service Root URI	Root URI of the OData service. The service root URI must follow the OData URI conventions.

Advanced settings

The following table describes the advanced connection properties:

Property	Description
OData Parameter File Path	Absolute path to a file that you append to the URL. The file contains key value pairs separated by a new line. You can use this file to check additional parameter values required in the URL. **Note:** Ensure that you use percent encoding to encode the key value pairs in the file.
Data Serialization Format	The format of data you want to transfer. Choose from ATOM/XML or JSON. Default is ATOM/XML.

Proxy server settings

If your organization uses an outgoing proxy server to connect to the Internet, the Secure Agent connects to Informatica® Intelligent Data Management Cloud™ (IDMC) through the proxy server.

You can configure the Secure Agent to use the proxy server on Windows and Linux. You can use the unauthenticated or authenticated proxy server. The proxy settings applies to connections used in mappings and in mappings in advanced mode.

To configure the proxy settings for the Secure Agent, use one of the following methods:

- Configure the Secure Agent through the Secure Agent Manager on Windows or shell command on Linux.

  For instructions, see "Configure the proxy settings on Windows" or "Configure the proxy settings on Linux" in *Getting Started* in the Data Integration help.
- Configure the JVM options for the DTM in the Secure Agent properties. For instructions, see the Proxy server settings Knowledge article.

To configure proxy settings for the serverless runtime environment, see "Using a proxy server" in *Runtime Environments* in the Administrator help.

CHAPTER 3

Synchronization tasks with OData Connector

Use the connection in the Synchronization Task wizard when you create a synchronization task. You can perform insert, update, upsert, or delete target operations in a synchronization task. You can also configure data filters based on your requirements.

When you configure a synchronization task to read from an OData service, you can configure the source properties. When you configure a synchronization task to write to an OData service, you can configure the target properties.

OData sources in synchronization tasks

When you configure a synchronization task to read from an OData service, you can configure the source properties.

The source properties appear on the Source page of the Synchronization Task wizard when you specify an OData connection.

The following table describes the OData source properties:

Source Property	Description
Connection Name	Name of the source connection.
Source Type	Source Type. Select Single for a single source object.
Source Object	Source object for the task.

OData targets in synchronization tasks

When you configure a synchronization task to write to an OData service, you can configure the target properties.

The target properties appear on the Target page of the Synchronization Task wizard when you specify an OData connection.

The following table describes the OData target properties:

Target Property	Description
Connection	Name of the target connection.
Target Type	Target object for the task.
Child Object	Select a related child object to use more than one object as the target.

CHAPTER 4

Mappings and mapping tasks with OData Connector

Use the Data Integration Mapping Designer to create a mapping. When you create a mapping, you configure a source or target to represent an OData object.

Use the Mapping Task wizard to create a mapping task. The mapping task processes data based on the data flow logic you define in the mapping.

In advanced mode, the Mapping Designer updates the mapping canvas to include transformations and functions that enable advanced functionality.

OData sources in mappings

To read data from an OData service, configure an OData resource object as the Source transformation in a mapping.

Specify the name and description of the OData source. Configure the source and advanced properties for the source object.

The following table describes the source properties that you can configure in a Source transformation:

Property	Description
Connection Name	Name of the source connection.
Source Type	Source type. Select Single for a single source object.
Object	Source object for the mapping.

The following table describes the advanced source properties that you can configure in a Source transformation:

Advanced Source Property	Description
Maximum Page Size	Set the number of records to be fetched per page when you read data. You can set the page size when you want to read a large amount of data from a source. Default is 50. **Note:** The value must be less than the default page size of the server. Else, the server might return duplicate rows in the target file when you run the mapping.
Tracing Level	Set the amount of detail that appears in the log file. You can choose terse, normal, verbose initialization, or verbose data. Default is normal.

OData targets in mappings

To write data to an OData service, configure an OData resource object as the Target transformation in a mapping.

Specify the name and description of the OData target. Configure the target and advanced properties for the target object.

The following table describes the target properties that you can configure in a Target transformation:

Property	Description
Connection	Name of the target connection.
Target Type	Target type. Select one of the following target types: - Single Object - Parameter. Select Parameter to define the target type when you configure the task.
Object	Name of the target object.
Operation	Target operation. Select one of the following operations: - Insert - Update - Upsert - Delete - Data Driven. Configure an expression to specify an update strategy based on the data. You can use one of the following constants in an expression: - DD_INSERT - DD_UPDATE - DD_REJECT - DD_DELETE **Note:** If you use the Data Driven operation, you cannot upsert.
Truncate Target	Truncates the target before loading data.

The following table describes the advanced target properties that you can configure in a Target transformation:

Advanced Property	Description
Primary Key Override	Column names that you want to use as the primary key. Use commas to separate multiple column names.
Success File Directory	Directory for the success file. Specify a directory path that is available on each Secure Agent machine in the runtime environment. By default, Data Integration writes the success file to the following directory: `<Secure Agent installation directory>/apps/Data_Integration_Server/data/success`
Error File Directory	Directory for the error file. Specify a directory path that is available on each Secure Agent machine in the runtime environment. By default, Data Integration writes the error file to the following directory: `<Secure Agent installation directory>/apps/Data_Integration_Server/data/error`
Forward Rejected Rows	Determines whether the transformation passes rejected rows to the next transformation or drops rejected rows. By default, the mapping task forwards rejected rows to the next transformation.

Rules and guidelines for OData mappings

You cannot configure an OData mapping to roll back transactions.

Troubleshooting

When you configure the **Maximum Page Size** property to read data from a source, you might get an out of memory issue.

The issue occurs because client side pagination is enabled by default. Enable server side pagination to increase the memory.

Perform the following steps to enable server side pagination and increase the memory for the Java heap size:

1. In **Administrator**, select **Runtime Environments**.
2. Select the Secure Agent from the list of available Secure Agents.
3. In the upper-right corner, click **Edit**.
4. In the **System Configuration Details** section, select the**Type** as **DTM** for the Data Integration Server.
5. Set the value of JVMOption to **-DServerSidePagination=true**.
6. Restart the Secure Agent.

CHAPTER 5

Data type reference

OData native data types

OData data types appear in the Fields tab for Source and Target transformations when you choose to edit metadata for the fields.

Transformation data types

Set of data types that appear in the remaining transformations. They are internal data types based on ANSI SQL-92 generic data types, which Data Integration uses to move data across platforms. Transformation data types appear in all remaining transformations in Data Integration tasks.

When the Data Integration application reads source data, it converts the native data types to the comparable transformation data types before transforming the data.

When the Data Integration application writes to a target, it converts the transformation data types to the comparable native data types.

OData and transformation data types

The following table compares the OData native data type to the transformation data type:

OData Data Type	Transformation Data Type
Boolean	Integer
Date	Date and time values. Use the following formats for date and time: - yyyy-MM-ddTHH:mm:ss For example, 2015-04-30T07:08:06 - yyyy-MM-ddTHH:mm:ss:SSSZ For example, 2015-04-30T07:08:06.879 or 2015-04-30T07:08:06.8798888
Decimal	String/Decimal
Int16	Integer
Int32	Integer
String	String

INDEX

C

Cloud Application Integration community
  URL 4
Cloud Developer community
  URL 4

D

Data Integration community
  URL 4
data types 14

I

Informatica Global Customer Support
  contact information 5
Informatica Intelligent Cloud Services
  web site 4

M

maintenance outages 5
mappings
  OData sources 11
  OData targets 12

N

native data type 14

O

OData
  supported assets 6
OData Connector
  overview 6
OData sources
  mappings 11
OData targets
  mappings 12

S

status
  Informatica Intelligent Cloud Services 5
synchronization tasks
  read from OData service 9
  write to OData service 9
system status 5

T

transformation data type 14
trust site
  description 5

U

upgrade notifications 5

W

web site 4