Informatica®

Informatica® Cloud Data Integration

Slack Connector

Informatica Cloud Data Integration Slack Connector
October 2025

© Copyright Informatica LLC 2024, 2025

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, Informatica Cloud, and PowerCenter are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2025-10-03

Table of Contents

Preface 4

Informatica Resources 4

- Informatica Documentation 4
- Informatica Intelligent Cloud Services web site 4
- Informatica Intelligent Cloud Services Communities 4
- Informatica Intelligent Cloud Services Marketplace 4
- Data Integration connector documentation 5
- Informatica Knowledge Base 5
- Informatica Intelligent Cloud Services Trust Center 5
- Informatica Global Customer Support 5

Chapter 1: Introduction to Slack Connector 6

Slack Connector assets 6

Chapter 2: Connections for Slack 7

Prepare for authentication 7

- OAuth 2.0 authentication 7
- Bearer token authentication 8

Connect to Slack 8

- Before you begin 8
- Connection details 8
- Authentication types 9

Scopes in Slack 10

Chapter 3: Mappings for Slack 13

Slack sources in mappings 13

Slack targets in mappings 14

Chapter 4: Data type reference 15

Slack and transformation data types 15

Index 16

Preface

Use *Slack Connector* to learn how to read from or write to Slack by using Cloud Data Integration. Learn to create a Slack connection and develop and run mappings and mapping tasks in Cloud Data Integration.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Intelligent Cloud Services web site

You can access the Informatica Intelligent Cloud Services web site at http://www.informatica.com/cloud. This site contains information about Informatica Cloud integration services.

Informatica Intelligent Cloud Services Communities

Use the Informatica Intelligent Cloud Services Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the Informatica Intelligent Cloud Services Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

Informatica Intelligent Cloud Services Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Intelligent Cloud Services Trust Center

The Informatica Intelligent Cloud Services Trust Center provides information about Informatica security policies and real-time system availability.

You can access the trust center at https://www.informatica.com/trust-center.html.

Subscribe to the Informatica Intelligent Cloud Services Trust Center to receive upgrade, maintenance, and incident notifications. The Informatica Intelligent Cloud Services Status page displays the production status of all the Informatica cloud products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single component or all Informatica Intelligent Cloud Services components. Subscribing to all components is the best way to be certain you never miss an update.

To subscribe, on the Informatica Intelligent Cloud Services Status page, click **SUBSCRIBE TO UPDATES**. You can choose to receive notifications sent as emails, SMS text messages, webhooks, RSS feeds, or any combination of the four.

Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the Informatica Intelligent Cloud Services Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

Introduction to Slack Connector

You can use Slack Connector to securely read data from and write data to Slack.

Slack sources and targets represent operations such as messaging, administration, and file management in Slack.

Note: This connector is developed by Informatica partners, third-party system integrators, or customers. You can look up the Product Availability Matrix or Informatica Marketplace for more information.

Slack Connector assets

Create assets in Data Integration to integrate data using Slack Connector.

When you use Slack Connector, you can include the following Data Integration assets:

- Mapping
- Mapping task

For more information about configuring assets and transformations, see *Mappings*, *Transformations*, and *Tasks* in the Data Integration documentation.

CHAPTER 2

Connections for Slack

Create a Slack connection to securely read data from or write data to Slack.

You can use a Slack connection to specify Slack sources and targets in mappings and mapping tasks.

Prepare for authentication

You can configure bearer token and OAuth 2.0 authentication types to access Slack.

Before you configure the connection properties, you need to keep the authentication details handy based on the authentication type that you want to use.

OAuth 2.0 authentication

The OAuth 2.0 authentication requires the client ID, client secret, and access token of your Slack application to connect to Slack.

Complete the following prerequisites to use OAuth 2.0 authentication:

- Create and install the Slack application in your workspace in Slack or for your enterprise organization. The organization administrator installs the Slack application for the enterprise organization.

  You can create a Slack application for a user or a bot.

  For more information about how to create a Slack application, see Creating an application.
- To use administration operations, create and install the Slack application for the enterprise organization and ensure that the public distribution option is enabled for the application.
- When you enable public distribution for the Slack application, add the redirect URL of the application to authenticate access to Slack from Data Integration.
  For example, you can add the following redirect URL:

  `https://iics-icinq1.informaticacloud.com/ma/proxy/oauthcallback`
- Add the required scopes to your Slack application that determine what operations the application can perform within your Slack workspace.
  For example, add the chat:write scope to allow your application to post messages in your workspace.

  For more information about the scopes required to perform operations in Slack, see "Scopes in Slack" on page 10.

  For more information about how to add scopes for you application, see Adding scopes.
- Get the client ID and client secret for the Slack application. You can find the client ID and client secret in the **Basic Information** tab of your Slack application.

Bearer token authentication

The bearer token authentication requires the token of your Slack application to connect to Slack.

Complete the following prerequisites to use bearer token authentication:

- Create and install the Slack application in your workspace in Slack or across your enterprise organization. The organization administrator installs the Slack application for the enterprise organization.

  You can create a Slack application for a user or a bot.

  For more information about how to create a Slack application, see Creating an application.
- To use administration operations, install the application for the enterprise organization.
- Add the required scopes to your Slack application that determine what operations the application can perform within your Slack workspace.
  For example, add the chat:write scope to allow your application to post messages in your workspace.

  For more information about how to add scopes for you application, see Adding scopes.

  For more information about the scopes required to perform operations in Slack, see "Scopes in Slack" on page 10.
- Get the token for the Slack application. You can find the token under **OAuth Tokens for Your Workspace** on the **OAuth & Permissions** page in your Slack application.

Connect to Slack

Let's configure the Slack connection properties to connect to Slack.

Before you begin

Before you get started, you'll need to get information from your Slack account.

Check out Prepare for authenticationon page 7 to learn more about the authentication prerequisites.

Connection details

The following table describes the basic connection properties:

Property	Description
Connection Name	Name of the connection. Each connection name must be unique within the organization. Connection names can contain alphanumeric characters, spaces, and the following special characters: _ . + -, Maximum length is 255 characters.
Description	Description of the connection. Maximum length is 4000 characters.

Property	Description
Use Secret Vault	Stores sensitive credentials for this connection in the secrets manager that is configured for your organization. This property appears only if secrets manager is set up for your organization. When you enable the secret vault in the connection, you can select which credentials that the Secure Agent retrieves from the secrets manager. If you don't enable this option, the credentials are stored in the repository or on a local Secure Agent, depending on how your organization is configured. **Note:** If you're using this connection to apply data access policies through pushdown or proxy services, you cannot use the Secret Vault configuration option. For information about how to configure and use a secrets manager, see "Secrets manager configuration" in the Administrator help.
Runtime Environment	The name of the runtime environment where you want to run tasks. You can specify a Secure Agent or Hosted Agent. For more information about how to configure and use the runtime environments, see *Runtime Environments* in the Administrator help.
Base URL	The base URL to connect to the Slack APIs. For example, `https://slack.com/api/`

Authentication types

You can configure bearer token and OAuth 2.0 authentication types to access Slack.

Select the required authentication method and then configure the authentication-specific parameters.

OAuth 2.0 authentication

The OAuth 2.0 authentication requires the client ID, client secret, and access token of your Slack application to connect to Slack.
The following table describes the basic connection properties for OAuth 2.0 authentication:

Property	Description
Client ID	Client ID of your Slack application.
Client Secret	Client secret of your Slack application.
Scope	The permissions for the Slack application to perform specific operations in your Slack workspace. Separate multiple values with a comma. Do not add spaces between the values. For operations that require chat:write or files:write scopes, ensure that you use chat:write:user, chat:write:bot, or files:write:user based on whether you created the application for a user or a bot.
Access Token	Access token of your Slack application. Generate the access token for a user or a bot for which you created the application. When you generate the access token, specify the workspace name in the following format: `your-workspace.slack.com` To use administration operations, enter the URL of your enterprise organization. For example, `your-workspace.enterprise.slack.com`

Property	Description
Access Token Parameters	Additional parameters to be included in the access token URL to get the access token. Define the parameters in key-value pairs in JSON format. Separate multiple key-value pairs with a comma. For example, `client_id=1234567890,client_secret=abcd1234`
Authorization Code Parameters	Additional parameters to be included in the authorization code URL to get the authorization code. Define the parameters in key-value pairs in JSON format. Separate multiple key-value pairs with a comma. For example, `client_id=1234567890,scope=channels:read+groups:read+im:read+mpim:read,redirect_uri=https://iics-icinq1.informaticacloud.com/ma/proxy/oauthcallback`

Bearer token authentication

The bearer token authentication requires the token of your Slack application to connect to Slack.
The following table describes the basic connection properties for bearer token authentication:

Property	Description
Token	Token of your Slack application. Specify the token for a user or a bot for which you created the Slack application.

Scopes in Slack

Scopes are permissions for the Slack application to perform operations in your workspace.
The following tables describes the scopes required by the Slack application to perform operations in your workspace:

Operation	Scopes for user	Scopes for bot
Add_Reminder	reminders:write	Not applicable
Add_User	admin.users:write	Not applicable
Approve_Invite_Requests	admin.invites:write	Not applicable
Archive_Channel	channels:write, groups:write, im:write, mpim:write	channels:manage, groups:write, im:write, mpim:write
Channel_Information	channels:read, groups:read, im:read, mpim:read	channels:read, groups:read, im:read, mpim:read
Conversation_History	channels:history, groups:history, im:history, mpim:history	channels:history, groups:history, im:history, mpim:history
Create_Channel	channels:write, groups:write, im:write, mpim:write	channels:manage, groups:write, im:write, mpim:write

Operation	Scopes for user	Scopes for bot
Create_Workspace	admin.teams:write	Not applicable
Delete_Channel	admin.conversations:write	Not applicable
Delete_Files	files:write, files:write:user	files:write
Delete_Message	chat:write, chat:write:user, chat:write:bot	chat:write
Delete_Reminder	reminders:write	Not applicable
Invite_user_to_channel	channels:write.invites, groups:write.invites, mpim:write.invites, channels:write, groups:write, im:write, mpim:write	channels:write.invites, groups:write.invites, mpim:write.invites, channels:manage,groups:write, im:write, mpim:write
List_Channels	channels:read, groups:read, im:read, mpim:read	channels:read, groups:read, im:read, mpim:read
List_Channel_Members	channels:read, groups:read, im:read, mpim:read	channels:read, groups:read, im:read, mpim:read
List_Reminders	reminders:read	Not applicable
List_User_Invites	admin.invites:read	Not applicable
List_Users	users:read	users:read
List_Users_As_an_Admin	admin.users:read	Not applicable
List_Workspaces	admin.teams:read	Not applicable
Remove_User_From_Channel	channels:write, groups:write, im:write, mpim:write	channels:manage, groups:write, im:write, mpim:write
Remove_User_From_Workspace	admin.users:write	Not applicable
Rename_Channel	channels:write, groups:write, im:write, mpim:write	channels:manage, groups:write, im:write, mpim:write
Search	search:read	Not applicable
Send_Ephemeral_Message	chat:write, chat:write:user, chat:write:bot	chat:write
Send_Message	chat:write ,chat:write:user,chat:write:bot	chat:write
Set_User_Profiles	users.profile:write	Not applicable
Test_Authentication	No scope required	No scope required
Unarchive_Channel	channels:write, groups:write, im:write, mpim:write	channels:manage, groups:write, im:write, mpim:write

Operation	Scopes for user	Scopes for bot
Update_Chat	chat:write, chat:write:bot, chat:write:user	chat:write
User_Information	users:read	users:read

CHAPTER 3

Mappings for Slack

When you configure a mapping, you describe the flow of data from the source to the target. A mapping defines reusable data flow logic that you can use in mapping tasks.

When you create a mapping, you define the Source or Target transformations to represent a Slack operation. Use the Mapping Designer in Data Integration to add the Source or Target transformations in the mapping canvas and configure the Slack source or target properties.

Slack sources in mappings

In a mapping, you can configure a Source transformation to represent a Slack source.

The following table describes the Slack source properties that you can configure in a Source transformation:

Property	Description
Connection	Name of the source connection. You can select an existing connection or create a new connection.
Operation	The operation that you want to perform in Slack.

Request Message	Request message for the operation that you want to perform in Slack.
	The request message is in JSON format. You can copy and paste the request message from the request message template.
	Do not leave the request message empty. You must at least specify a blank JSON object {} in the request message.
	Sample request message:
	{
	"requestbody" : { "channel" : "CXX" }
	}
	For more information about the Slack APIs that the connector interacts with when you use a request message, see Slack APIs.

Field Mapping	Map the parameters in the response to the output fields.

The following table describes the advanced source properties that you can configure in a Source transformation:

Property	Description
Tracing Level	Detail level of error and status messages that Data Integration writes in the session log. You can choose terse, normal, verbose initialization, or verbose data. Default is normal.
Cache Size for Web Service Response (KB)	Memory available for the web service response. If the web service response contains many rows or columns, you might want to increase the cache size. Default is 1024 KB.

Slack targets in mappings

In a mapping, you can configure a Target transformation to represent a Slack target.

The following table describes the Slack target properties that you can configure in a Target transformation:

Property	Description
Connection	Name of the target connection. You can select an existing connection or create a new connection.
Operation	The operation that you want to perform in Slack.
Field Mapping	Map your input fields to the target fields. Ensure that you map all the mandatory fields in the target.

The following table describes the advanced target properties that you can configure in a Target transformation:

Property	Description
Cache Size for Web Service Request (KB)	Memory available for the web service request. If the web service request contains many rows or columns, you might want to increase the cache size. Default is 1024 KB.
Transaction Commit Control	Control to commit or roll back transactions based on the set of rows that pass through the transformation. Use the transaction commit control if you have a large amount of data and you want to control how it is processed.
Transformation Scope	Specifies how Data Integration applies the transformation logic to incoming data: - Transaction. Applies the transformation logic to all rows in a transaction. Choose Transaction when a row of data depends on all rows in the same transaction, but does not depend on rows in other transactions. - All Input. Applies the transformation logic on all incoming data. When you choose All Input, Data Integration drops incoming transaction boundaries. Choose All Input when a row of data depends on all rows in the source.

CHAPTER 4

Data type reference

Cloud Data Integration uses the following data types in Slack mappings:

- Slack native data types appear in the source and target transformations when you choose to edit metadata for the fields.
- Transformation data types. Set of data types that appear in the transformations. These are internal data types based on ANSI SQL-92 generic data types, which the agent uses to move data across platforms. They appear in all transformations in a mapping or mapping in advanced mode.

When the agent reads source data, it converts the native data types to the comparable transformation data types before transforming the data. When the agent writes to a target, it converts the transformation data types to the comparable native data types.

Slack and transformation data types

The following table lists the Slack data types that Data Integration supports and the corresponding transformation data types:

Slack data type	Transformation data type	Description
Boolean	Integer	Precision 10, Scale 0
Double	Double	Precision 15, scale 0
Float	Double	Precision 15, scale 0
Integer	Integer	Precision 10, scale 0
String	String	1 to 104,857,600 characters Default precision is 4000
Timestamp	Date/Time	Jan 1, 0001 A.D. to Dec 31, 9999 A.D (precision to the milliseconds)

INDEX

C

Cloud Application Integration community
  URL 4
Cloud Developer community
  URL 4

D

Data Integration community
  URL 4

I

Informatica Global Customer Support
  contact information 5
Informatica Intelligent Cloud Services
  web site 4

M

maintenance outages 5

S

status
  Informatica Intelligent Cloud Services 5
system status 5

T

trust site
  description 5

U

upgrade notifications 5

W

web site 4