Informatica® Cloud Data Integration

Xactly Connector

Informatica Cloud Data Integration Xactly Connector
July 2025

© Copyright Informatica LLC 2015, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, Informatica Cloud, and PowerCenter are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-05-12

Table of Contents

Preface 4

Informatica Resources 4

- Informatica Documentation 4
- Informatica Intelligent Cloud Services web site 4
- Informatica Intelligent Cloud Services Communities 4
- Informatica Intelligent Cloud Services Marketplace 4
- Data Integration connector documentation 5
- Informatica Knowledge Base 5
- Informatica Intelligent Cloud Services Trust Center 5
- Informatica Global Customer Support 5

Chapter 1: Introduction to Xactly Connector 6

Xactly Connector overview 6

Supported Features Objects and Task Operations 6

Chapter 2: Xactly Connections 8

Xactly Connection Overview 8

Creating an Xactly Connection 8

Xactly connection properties 9

Configure proxy settings 10

- Configuring the Proxy Settings on Windows 10
- Configuring the Proxy Settings on Linux 12

Chapter 3: Synchronization Tasks with Xactly Connector 14

Xactly Sources in Synchronization Tasks 14

Xactly Targets in Synchronization Tasks 15

Data Filters 15

Creating an Xactly Synchronization Task 16

Defining Xactly Write Operations 16

Chapter 4: Mappings for Xactly 18

Xactly sources in mappings 18

Chapter 5: Troubleshooting overview 20

Troubleshooting the Xactly Connector 20

Appendix A: Generating the client stub for Xactly WSDL 21

Index 22

Preface

Use *Xactly Connector* to learn how to read from or write to Xactly by using Cloud Data Integration. Learn to create an Xactly connection and run synchronization tasks in Cloud Data Integration.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Intelligent Cloud Services web site

You can access the Informatica Intelligent Cloud Services web site at http://www.informatica.com/cloud. This site contains information about Informatica Cloud integration services.

Informatica Intelligent Cloud Services Communities

Use the Informatica Intelligent Cloud Services Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the Informatica Intelligent Cloud Services Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

Informatica Intelligent Cloud Services Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Intelligent Cloud Services Trust Center

The Informatica Intelligent Cloud Services Trust Center provides information about Informatica security policies and real-time system availability.

You can access the trust center at https://www.informatica.com/trust-center.html.

Subscribe to the Informatica Intelligent Cloud Services Trust Center to receive upgrade, maintenance, and incident notifications. The Informatica Intelligent Cloud Services Status page displays the production status of all the Informatica cloud products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single component or all Informatica Intelligent Cloud Services components. Subscribing to all components is the best way to be certain you never miss an update.

To subscribe, on the Informatica Intelligent Cloud Services Status page, click **SUBSCRIBE TO UPDATES**. You can choose to receive notifications sent as emails, SMS text messages, webhooks, RSS feeds, or any combination of the four.

Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the Informatica Intelligent Cloud Services Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

Introduction to Xactly Connector

You can use Xactly Connector to connect to Xactly from Data Integration. Use Xactly Connector to read data such as commissions, bonus, orders, users, and roles from Xactly and integrate the data with other on-premise or cloud applications. You can also write data from other applications to the Xactly Connector.

Xactly Connector overview

Xactly is a cloud-based software, which helps you to manage sales performance, sales compensation, and sales effectiveness. You can read data from Xactlyand write the data to Xactly. Xactly Connector supports API Version 1.4.

Supported Features Objects and Task Operations

When you create an Xactly connection, you must select the feature that you want to use. Features are different entities of Xactly Connector. Each feature contains a set of objects.

The following table provides a list of features and objects that Xactly Connector supports:

Features	Read	Insert	Update	Upsert	Delete	Lookup
BusinessGroup	Yes	NA	NA	Yes	Yes	Yes
CurrencyRate	Yes	NA	NA	Yes	Yes	Yes
EmployeeStatus	Yes	NA	NA	NA	Yes	Yes
Person	Yes	NA	NA	Yes	Yes	Yes
Position	Yes	NA	NA	Yes	NA	Yes
PositionHierarchy	Yes	NA	NA	Yes	NA	Yes
PositionHierarchyType	Yes	NA	NA	NA	NA	Yes
PositionRelations	Yes	NA	NA	Yes	NA	Yes

Features	Read	Insert	Update	Upsert	Delete	Lookup
PositionRelationType	Yes	NA	NA	Yes	NA	Yes
Role	Yes	NA	NA	NA	NA	Yes
Title	Yes	NA	NA	Yes	Yes	Yes
UnitType	Yes	NA	NA	Yes	Yes	Yes
User	Yes	NA	NA	Yes	Yes	Yes

For more information about configuring assets and transformations, see *Mappings*, *Transformations*, and *Tasks* in the Data Integration documentation.

CHAPTER 2

Xactly Connections

Create an Xactly connection to connect to Xactly so that the agent can read data from and write data to Xactly. You can use Xactly connections to specify sources and targets in synchronization tasks.

Xactly Connection Overview

You can create an Xactly connection on the **Connections** page. You can configure a connection on the Connections page or in a wizard as you configure a task.

Creating an Xactly Connection

To use Xactly Connector in a synchronization task, you must first create a connection.

You can configure a connection on the Connections page or in a wizard as you configure a task.

Perform the following steps to create an Xactly connection:

1. On the **Connections** page, click **New Connection** to create a connection.

   The **New Connection** page appears.
2. Specify the following details:

Connection Property	Description
Connection Name	Enter a unique name for the connection.
Description	Provide a relevant description for the connection.
Type	Type of connection. Select **Xactly** from the list.
Secure Agent	Select the appropriate secure agent from the list.
UserID	Enter the UserID for accessing the Xactly portal.
PassKey	Enter the password for accessing the Xactly portal.

Connection Property	Description
Xactly App Name	Specify the application name to sign in to Xactly.
WSDL URL	Provide a WSDL URL.
Endpoint URL	Enter the endpoint URL where you want to send the request.
Enable Logging	Select to log SOAP request and response in the session log file.

3. Click **Save** to save the connection.

   You should test the connection before saving the connection details. You can click **Test Connection** to verify if the connection is successful.

Xactly connection properties

When you set up an Xactly connection, configure the connection properties.

Important: Xactly Connector is deprecated and has been moved to maintenance mode. Informatica intends to drop support in a future release.

The following table describes the Xactly connection properties:

Property	Description
Connection Name	Name of the connection. Each connection name must be unique within the organization. Connection names can contain alphanumeric characters, spaces, and the following special characters: _ . + -, Maximum length is 255 characters.
Description	Description of the connection. Maximum length is 4000 characters.
Runtime Environment	Name of the runtime environment where you want to run tasks. Select a Secure Agent, Hosted Agent, serverless, or elastic runtime environment. For more information about how to configure and use the runtime environments, see *Runtime Environments* in the Administrator help.
UserID	The UserID for accessing the Xactly portal.
PassKey	The password for accessing the Xactly portal.
Xactly App Name	The application name to sign in to Xactly.
WSDL URL	The WSDL URL.
Endpoint URL	The endpoint URL where you want to send the request.
Enable Logging	Enables logging for the task. Select to log SOAP request and response in the session log file.

Configure proxy settings

If your organization uses an outgoing proxy server to connect to the Internet, you can use the agent to connect to Informatica Intelligent Cloud Services through the proxy server.

You can configure the Secure Agent to use the proxy server on Windows and Linux. You can use the unauthenticated or authenticated proxy server.

To configure the proxy settings for the serverless runtime environment, see *Runtime Environments* in the Administrator help.

Configuring the Proxy Settings on Windows

To configure the proxy server settings for the Secure Agent on a Windows machine, you must configure the proxy server settings through the Secure Agent Manager and the JVM options of the Secure Agent.

Contact your network administrator for the correct proxy settings.

1. Click **Start** > **All Programs** > **Informatica Cloud Secure Agent** > **Informatica Cloud Secure Agent** to launch the Secure Agent Manager.

   The Secure Agent Manager displays the Secure Agent status.
2. Click **Proxy** in the Secure Agent Manager page.
3. Click **Use a Proxy Server** to enter proxy server settings.
4. Configure the following proxy server details:

Field	Description
Proxy Host	Required. Host name of the outgoing proxy server that the Secure Agent uses.
Proxy Port	Required. Port number of the outgoing proxy server.
User Name	User name to connect to the outgoing proxy server.
Password	Password to connect to the outgoing proxy server.

5. Click **OK**.
6. Log in to Informatica Intelligent Cloud Services.
7. Open Administrator and select **Runtime Environments**.
8. Select the Secure Agent for which you want to configure a proxy server.
9. On the upper-right corner of the page, click **Edit**.
10. In the **System Configuration Details** section, select the **Type** as **DTM** for the Data Integration Service.
    - To use an unauthenticated proxy server, add the following parameters in any **JVMOption** field and specify appropriate values for each parameter:

Parameter	Description
-Dhttp.proxyHost=	Host name of the outgoing HTTP proxy server.
-Dhttp.proxyPort=	Port number of the outgoing HTTP proxy server.

Parameter	Description
-Dhttps.proxyHost=	Host name of the outgoing HTTPS proxy server.
-Dhttps.proxyPort=	Port number of the outgoing HTTPS proxy server.

For example,

```
JVMOption1=-Dhttp.proxyHost=<proxy_server_hostname>
JVMOption2=-Dhttp.proxyPort=8081
JVMOption3=-Dhttps.proxyHost=<proxy_server_hostname>
JVMOption4=-Dhttps.proxyPort=8081
```

- To use an authenticated proxy server, add the following parameters in any **JVMOption** field and specify appropriate values for each parameter:

Parameter	Description
-Dhttp.proxyHost=	Host name of the outgoing HTTP proxy server.
-Dhttp.proxyPort=	Port number of the outgoing HTTP proxy server.
-Dhttp.proxyUser=	User name for the HTTP proxy server.
-Dhttp.proxyPassword=	Password for the user.
-Dhttps.proxyHost=	Host name of the outgoing HTTPS proxy server.
-Dhttps.proxyPort=	Port number of the outgoing HTTPS proxy server.
-Dhttps.proxyUser=	User name for the HTTPS proxy server.
-Dhttps.proxyPassword=	Password for the user.

For example,

```
JVMOption1=-Dhttp.proxyHost=<proxy_server_hostname>
JVMOption2=-Dhttp.proxyPort=8008
JVMOption3=-Dhttp.proxyUser=adminuser
JVMOption4=-Dhttp.proxyPassword=password
JVMOption5=-Dhttps.proxyHost=<proxy_server_hostname>
JVMOption6=-Dhttps.proxyPort=8008
JVMOption7=-Dhttps.proxyUser=adminuser
JVMOption8=-Dhttps.proxyPassword=password
```

Note: You can configure only five **JVMOption** fields in the **System Configuration Details** section. To configure the remaining parameters, you must add the **JVMOption** fields in the **Custom Configuration Details** section. In the **Custom Configuration Details** section, select the **Type** as **DTM** for the Data Integration Service, add the **JVMOption** fields, and specify the remaining parameters and appropriate values for each parameter.

11. Click **Save**.

    The Secure Agent restarts to apply the settings.

Configuring the Proxy Settings on Linux

You can update the proxy server settings defined for the Secure Agent from the command line. To configure the proxy server settings for the Secure Agent on a Linux machine, you must use a shell command that updates the `proxy.ini` file and configure the JVM options of the Secure Agent.

Contact your network administrator for the correct proxy settings.

1. Navigate to the following directory:

   ```
   <Secure Agent installation directory>/apps/agentcore
   ```

2. To update the `proxy.ini` file, enter the following command:

   ```
   consoleAgentManager.sh configureProxy <proxy host> <proxy port> <proxy user name> <proxy password>
   ```

3. Log in to Informatica Intelligent Cloud Services.
4. Open Administrator and select **Runtime Environments**.
5. Select the Secure Agent for which you want to configure a proxy server.
6. On the upper-right corner of the page, click **Edit**.
7. In the **System Configuration Details** section, select the **Type** as **DTM** for the Data Integration Service.
   - To use an unauthenticated proxy server, add the following parameters in any **JVMOption** field and specify appropriate values for each parameter:

Parameter	Description
-Dhttp.proxyHost=	Host name of the outgoing HTTP proxy server.
-Dhttp.proxyPort=	Port number of the outgoing HTTP proxy server.
-Dhttps.proxyHost=	Host name of the outgoing HTTPS proxy server.
-Dhttps.proxyPort=	Port number of the outgoing HTTPS proxy server.

     For example,

     ```
     JVMOption1=-Dhttp.proxyHost=<proxy_server_hostname>
     JVMOption2=-Dhttp.proxyPort=8081
     JVMOption3=-Dhttps.proxyHost=<proxy_server_hostname>
     JVMOption4=-Dhttps.proxyPort=8081
     ```

   - To use an authenticated proxy server, add the following parameters in any **JVMOption** field and specify appropriate values for each parameter:

Parameter	Description
-Dhttp.proxyHost=	Host name of the outgoing HTTP proxy server.
-Dhttp.proxyPort=	Port number of the outgoing HTTP proxy server.
-Dhttp.proxyUser=	User name for the HTTP proxy server.
-Dhttp.proxyPassword=	Password for the user.

Parameter	Description
-Dhttps.proxyHost=	Host name of the outgoing HTTPS proxy server.
-Dhttps.proxyPort=	Port number of the outgoing HTTPS proxy server.
-Dhttps.proxyUser=	User name for the HTTPS proxy server.
-Dhttps.proxyPassword=	Password for the user.

For example,

```
JVMOption1=-Dhttp.proxyHost=<proxy_server_hostname>
JVMOption2=-Dhttp.proxyPort=8008
JVMOption3=-Dhttp.proxyUser=adminuser
JVMOption4=-Dhttp.proxyPassword=password
JVMOption5=-Dhttps.proxyHost=<proxy_server_hostname>
JVMOption6=-Dhttps.proxyPort=8008
JVMOption7=-Dhttps.proxyUser=adminuser
JVMOption8=-Dhttps.proxyPassword=password
```

Note: You can configure only five **JVMOption** fields in the **System Configuration Details** section. To configure the remaining parameters, you must add the **JVMOption** fields in the **Custom Configuration Details** section. In the **Custom Configuration Details** section, select the **Type** as **DTM** for the Data Integration Service, add the **JVMOption** fields, and specify the remaining parameters and appropriate values for each parameter.

8. Click **Save**.

   The Secure Agent restarts to apply the settings.

CHAPTER 3

Synchronization Tasks with Xactly Connector

This chapter includes the following topics:

- Xactly Sources in Synchronization Tasks, 14
- Xactly Targets in Synchronization Tasks, 15
- Data Filters, 15
- Creating an Xactly Synchronization Task, 16
- Defining Xactly Write Operations, 16

Xactly Sources in Synchronization Tasks

You can use an Xactly object as a single source in a synchronization task.

You configure the Xactly source properties on the **Source** page of the Synchronization Task wizard.

The following table describes the Xactly source properties:

Property	Description
Connection	Name of the source connection.
Source Type	Type of the source object. Select Single object.
Source Object	Name of the source object. Select the source object for a single source.
Display technical names instead of labels	Displays technical names instead of business names.
Display source fields in alphabetical order	Displays source fields in alphabetical order instead of the order returned by the source system.

Xactly Targets in Synchronization Tasks

You can use a single object as a target in a synchronization task.

You can configure the Xactly target properties on the **Target** page of the Synchronization Task wizard.

The following table describes the Xactly target properties:

Property	Description
Connection	Name of the target connection.
Target Object	Name of the target object.
Child Object	Displays child objects related to the selected target object.
Display technical names instead of labels	Display technical names instead of business names.
Display target fields in alphabetical order	Displays target fields in alphabetical order instead of the order returned by the source system.

Data Filters

Data filters help you to fetch specific data of a particular object. You can assign a filter field to the object, and the synchronization task processes the data.

Perform the following steps to use data filters:

1. In a synchronization task, select the **Data Filters** tab.
2. Click **New**.

   The Data Filter dialog box appears.
3. Enter the data filter fields as described in the following table:

Field Type	Description
Object	Select object for which you want to assign filter fields.
Filter By	Select the filter field.
Operator	Select the corresponding operator.
Filter Value	Enter the filter value.

   Note: When you use Xactly Connector to read from Xactly, you can only use the **Equals** operator when you create a data filter.
4. Click **OK**.

Creating an Xactly Synchronization Task

Create a connection before you create a synchronization task.

Consider the task operation Insert to perform the synchronization task.

Perform the following steps to set up a synchronization task in Data Integration:

1. In Data Integration, click **New** > **Tasks**.
2. Select **Synchronization Task**, and click **Create**.

   The **Definition** tab appears.
3. Specify the task name, provide a description, and select the task operation **Insert**.
4. Click **Next**.

   The Source tab appears.
5. Select the source connection, source type, and source object for the task.
6. Click **Next**.

   The Target tab appears.
7. Select the target connection, target type, and target object for the task.
8. Click **Next**.

   The Data Filters tab appears.
9. To process all rows, select the **Data Filters** tab.

   To assign filters to a synchronization task, see "Data Filters" on page 15.
10. Click **Next**.

    The Field Mapping tab appears.
11. On the **Field Mapping** tab, map source fields to the appropriate target fields.
12. Click **Next**.

    The Schedule tab appears.
13. On the **Schedule** tab, schedule the task as required and save.
14. Click **Save** and then **Finish**.
15. From the **Explore** page, select the task, and click **Actions** > **Run**.

    In Monitor, you can monitor the status of the task.

Defining Xactly Write Operations

You can perform the following write operations with Xactly objects:

- To perform an Xactly save operation, select an upsert operation on the **Definition** tab of a synchronization task.
- To perform an Xactly delete operation, select a delete operation in the **Definition** tab of a synchronization task.


You can also perform the following operations with Xactly Connector:

- saveversion. Save a version of an effective dated object with the saveversion operation.

- addversion. Add a new version of an effective dated object with the addversion operation.
- deleteversion. Delete a version of an effective dated object with the deleteversion operation.

Note: On the **Field Mapping** tab, you must define the appropriate operations in the **Operation Type** field.

The following figure displays an example of how to define the saveversion operation:



CHAPTER 4

Mappings for Xactly

This chapter includes the following topic:

- Xactly sources in mappings, 18

Xactly sources in mappings

To read data from Xactly, configure an Xactly object as the Source transformation in a mapping.

Specify the name and description of the Xactly source.

The following table describes the source properties that you can configure for an Xactly source:

Property	Description
Connection	Name of the Xactly source connection. You can select an existing connection or create a new connection. You can also click **New Parameter** to define a parameter for the source connection.
Source Type	Type of the source object. Select Single Object or Parameter.
Object	Name of the Xactly source object based on the source type selected. Select the source object for a single source.

The following table describes the query options that you can configure for an Xactly source:

Property	Description
Filter	Filter value in a read operation. Click **Configure** to add conditions to filter records and reduce the number of rows that the Secure Agent reads from the source. Specify one of the following filter conditions: - Not parameterized. Use a basic filter to specify the object, field, operator, and value to select specific records. - Completely parameterized. Use a parameter to represent the field mapping. - Advanced. Use an advanced filter to define a more complex filter condition on an object. Default is **Not parameterized**.
Sort	Not applicable for Xactly Connector.

The following table describes the advanced source property that you can configure in a Source transformation:

Property	Description
Tracing Level	Sets the amount of detail that appears in the log file. Select one of the following options: - Terse - Normal - Verbose initialization - Verbose data Default is Normal.

CHAPTER 5

Troubleshooting overview

Use the following sections to troubleshoot errors in Xactly Connector.

Troubleshooting the Xactly Connector

- Select the **Enable Logging** check box to log the SOAP request and response. You can log the SOAP request and response in the session of the task.
- In Xactly, the **equals** operator behaves as **Contains** operator.
- The metadata ID is a required field for the Xactly.
- You must specify the ID for operations such as `saveversion`, `deleteversion`, and `delete`. You get **The object passed to the API operation is invalid** exception if you do not specify an ID in the .csv file.
- The Xactly objects support **delete** and **deleteVersions** operations. However, the delete and deleteversions opertions do not function for a few objects.
- The Xactly endpoint returns a success status for delete operation for some objects. If the Xactly endpoint does not return a success status data, you can consult the Xactly support.
- You can contact Data Integration Customer Support If you get an **Out of Memory** exception.

Note: Use the Xactly enable logging feature of the connector to collect the SOAP request before contacting the Xactly support. You can see the log and exception messages thrown during the configuration in the log files. You can save the log file in a specific location.

For example, `<Secure Agent installation directory>\apps\Data_Integration_Server\<latest version of connector>\ICS\main\tomcat\log`

APPENDIX A

Generating the client stub for Xactly WSDL

You can create an `Xactly_client-1.0.0.jar` stub for the Xactly WSDL. You must configure the JAVA_HOME environment before you generate a stub creation.

1. Download JDK 1.8 from the following website:

   http://www.oracle.com/technetwork/java/javase/downloads/jdk8-downloads-2133151.html
2. Set the JAVA_HOME environment variable to the location that contains the JDK 1.8 file. For example, set `JAVA_HOME="c:\Program Files\Java\jdk1.8.0_181"`.
3. Download the Xactly WSDL to a temporary path, for example, `C:\temp\Xactly\wsdl`.
4. You can either run the commands one by one in the command prompt or copy paste the entire command to a Win batch file and run the command as a batch file.
5. Navigate to the `C:\temp\Xactly` folder.

   Use the following commands to create the Xactly stub:

   ```
   set classpath=%JAVA_HOME%
   mkdir C:\temp\Xactly\out
   mkdir C:\temp\Xactly\src
   wsimport.exe -keep -XadditionalHeaders -Xdebug -s C:\temp\Xactly\src -d C:\temp
   \Xactly\out -verbose C:\temp\Xactly\wsdl\DiscoveryService.wsdl -wsdllocation /wsdl/
   DiscoveryService.wsdl
   jar -cvf C:\temp\Xactly\Xactly_client-1.0.0.jar -C out . wsdl
   ```
6. Stop the Secure Agent.
7. Copy the Xactly_client-1.0.0 jar to the following directory:

   `<Secure Agent installation directory>\downloads\<latest connector zip package>\package \connectors\ctk\<plugin ID>`
8. Start the Secure Agent.

INDEX

C

Cloud Application Integration community
  URL 4
Cloud Developer community
  URL 4
connections
  Xactly 9

D

Data Integration community
  URL 4

I

Informatica Global Customer Support
  contact information 5
Informatica Intelligent Cloud Services
  web site 4

L

Linux
  configuring proxy settings 12

M

maintenance outages 5
mapping
  Xactly sources 18
mapping tasks
  overview 18

P

proxy settings
  configuring on Linux 12
  configuring on Windows 10

S

status
  Informatica Intelligent Cloud Services 5
system status 5

T

trust site
  description 5

U

upgrade notifications 5

W

web site 4
Windows
  configuring proxy settings 10

X

Xactly
  connection properties 9