Informatica®

Informatica® Cloud Data Integration

Zendesk V2 Connector

Informatica Cloud Data Integration Zendesk V2 Connector
October 2025

© Copyright Informatica LLC 2018, 2025

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, the Informatica logo, Informatica Cloud, and PowerCenter are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2025-10-03

Table of Contents

Preface 5

Informatica Resources 5

- Informatica Documentation 5
- Informatica Intelligent Cloud Services web site 5
- Informatica Intelligent Cloud Services Communities 5
- Informatica Intelligent Cloud Services Marketplace 5
- Data Integration connector documentation 6
- Informatica Knowledge Base 6
- Informatica Intelligent Cloud Services Trust Center 6
- Informatica Global Customer Support 6

Chapter 1: Introduction to Zendesk V2 Connector 7

Zendesk V2 Connector Supported Objects 7

Zendesk V2 Connector assets 9

Chapter 2: Prepare for authentication 10

Basic authentication 10

API token 10

Client credentials authentication 11

Chapter 3: Connections for Zendesk V2 12

Connect to Zendesk 12

- Before you begin 12
- Connection details 12
- Authentication types 13

Zendesk custom fields 15

Proxy server settings 17

Chapter 4: Synchronization Tasks with Zendesk V2 18

Zendesk V2 Sources in Synchronization Tasks 18

- Advanced Source Properties for Zendesk V2 18

Data Filters 19

- Rules and Guidelines for Data Filters 19

Zendesk V2 Targets in Synchronization Tasks 20

- Advanced Target Properties for Zendesk V2 20

Chapter 5: Mappings and Mapping Tasks with Zendesk V2 21

Zendesk V2 Sources in Mappings 21

Zendesk V2 Targets in Mappings 22

Chapter 6: Known Limitations 24

Appendix A: Zendesk V2 Data Type Reference 25

Zendesk V2 and Transformation Data Types 25

Index 27

Preface

Use *Zendesk V2 Connector* to learn how to read from or write to Zendesk by using Data Integration. Learn to create a connection, develop mappings, synchronization tasks, and run synchronization and mapping tasks in Data Integration.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Intelligent Cloud Services web site

You can access the Informatica Intelligent Cloud Services web site at http://www.informatica.com/cloud. This site contains information about Informatica Cloud integration services.

Informatica Intelligent Cloud Services Communities

Use the Informatica Intelligent Cloud Services Community to discuss and resolve technical issues. You can also find technical tips, documentation updates, and answers to frequently asked questions.

Access the Informatica Intelligent Cloud Services Community at:

https://network.informatica.com/community/informatica-network/products/cloud-integration

Developers can learn more and share tips at the Cloud Developer community:

https://network.informatica.com/community/informatica-network/products/cloud-integration/cloud-developers

Informatica Intelligent Cloud Services Marketplace

Visit the Informatica Marketplace to try and buy Data Integration Connectors, templates, and mapplets:

https://marketplace.informatica.com/

Data Integration connector documentation

You can access documentation for Data Integration Connectors at the Documentation Portal. To explore the Documentation Portal, visit https://docs.informatica.com.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Intelligent Cloud Services Trust Center

The Informatica Intelligent Cloud Services Trust Center provides information about Informatica security policies and real-time system availability.

You can access the trust center at https://www.informatica.com/trust-center.html.

Subscribe to the Informatica Intelligent Cloud Services Trust Center to receive upgrade, maintenance, and incident notifications. The Informatica Intelligent Cloud Services Status page displays the production status of all the Informatica cloud products. All maintenance updates are posted to this page, and during an outage, it will have the most current information. To ensure you are notified of updates and outages, you can subscribe to receive updates for a single component or all Informatica Intelligent Cloud Services components. Subscribing to all components is the best way to be certain you never miss an update.

To subscribe, on the Informatica Intelligent Cloud Services Status page, click **SUBSCRIBE TO UPDATES**. You can choose to receive notifications sent as emails, SMS text messages, webhooks, RSS feeds, or any combination of the four.

Informatica Global Customer Support

You can contact a Global Support Center through the Informatica Network or by telephone.

To find online support resources on the Informatica Network, click **Contact Support** in the Informatica Intelligent Cloud Services Help menu to go to the **Cloud Support** page. The **Cloud Support** page includes system status information and community discussions. Log in to Informatica Network and click **Need Help** to find additional resources and to contact Informatica Global Customer Support through email.

The telephone numbers for Informatica Global Customer Support are available from the Informatica web site at https://www.informatica.com/services-and-training/support-services/contact-us.html.

CHAPTER 1

Introduction to Zendesk V2 Connector

You can use Zendesk V2 Connector to connect to Zendesk from Data Integration. You can use Zendesk V2 Connector to read data from and write data to Zendesk.

Zendesk V2 Connector is a REST based cloud connector. You can use Zendesk objects as sources and targets in synchronization tasks, mapping and mapping tasks.

You can switch mappings to advanced mode to include transformations and functions that enable advanced functionality.

When you run a synchronization task or a mapping task, the Secure Agents uses the Zendesk API to read data from and write data to Zendesk. You can use Zendesk objects, such as Users, Tickets, or Organizations in a task.

Zendesk V2 Connector Supported Objects

The following table lists the Zendesk objects that you can use in Data Integration tasks:

Objects	Fetch	Insert	Update	Delete	Upsert	Data Preview	Incremental Export API
ActivityStream	Yes	NA	NA	NA	NA	Yes	NA
AppLocations	Yes	No	No	No	NA	Yes	NA
Automations	Yes	NA	Yes	Yes	NA	Yes	NA
Brands	Yes	Yes	Yes	Yes	NA	Yes	NA
DynamicContent	Yes	Yes	Yes	Yes	NA	Yes	NA
GroupMemberships	Yes	Yes	No	Yes	NA	Yes	NA

Objects	Fetch	Insert	Update	Delete	Upsert	Data Preview	Incremental Export API
Groups	Yes	Yes	Yes	Yes	NA	Yes	NA
Locales	Yes	NA	NA	NA	NA	Yes	NA
MonitoredTwitterHandles	Yes	Yes	NA	NA	NA	Yes	NA
OrganizationFields	Yes	Yes	Yes	Yes	NA	Yes	NA
OrganizationMemberships	Yes	No	NA	Yes	NA	Yes	NA
OrganizationSubscriptions	Yes	Yes	Yes	Yes	NA	Yes	NA
Organizations	Yes	Yes	Yes	Yes	NA	Yes	Yes
Requests	Yes	No	No	No	NA	Yes	NA
Sessions	Yes	NA	NA	Yes	NA	Yes	NA
SupportAddresses	Yes	Yes	Yes	Yes	NA	Yes	NA
SuspendedTickets	Yes	NA	NA	Yes	NA	Yes	NA
Tags	Yes	No	No	No	NA	Yes	NA
TicketAudits	Yes	NA	NA	NA	NA	Yes	NA
TicketComments	Yes	NA	NA	NA	NA	NA	NA
TicketFields	Yes	Yes	Yes	Yes	NA	Yes	NA
TicketForms	Yes	Yes	Yes	Yes	NA	NA	NA
TicketMetricEvents	Yes	NA	NA	NA	NA	Yes	Yes
TicketMetrics	Yes	NA	NA	NA	NA	Yes	NA
Tickets	Yes	Yes	Yes	Yes	NA	Yes	Yes

Objects	Fetch	Insert	Update	Delete	Upsert	Data Preview	Incremental Export API
Triggers	Yes	NA	Yes	Yes	NA	Yes	NA
UserFields	Yes	Yes	Yes	Yes	NA	Yes	NA
UserIdentities	Yes	Yes	Yes	Yes	NA	NA	NA
Users	Yes	Yes	Yes	Yes	NA	Yes	Yes
Variants	Yes	Yes	No	No	NA	NA	NA
Views	Yes	No	No	No	NA	Yes	NA

Consider the following guidelines when you use the Zendesk trial account:

- You cannot read data from the TicketForms object.
- You cannot write or update data to the TicketForms or the Brands object.
- You cannot delete data from the TicketForms object.

Zendesk V2 Connector assets

Create assets in Data Integration to integrate data using Zendesk V2 Connector.

When you use Zendesk V2 Connector, you can include the following Data Integration assets:

- Mapping
- Mapping task
- Synchronization task

For more information about configuring assets and transformations, see *Mappings*, *Transformations*, and *Tasks* in the Data Integration documentation.

CHAPTER 2

Prepare for authentication

You can configure the basic, API token, and OAuth 2.0 client credentials authentication types to access Zendesk.

Before you configure the connection properties, you need to keep the authentication details handy based on the authentication type that you want to use.

Basic authentication

To connect to Zendesk using the basic authentication, you need the Zendesk account user name and password.

Get the required details from your Zendesk account to which you want to connect.

API token

To connect to Zendesk using the API token authentication, you need the Zendesk account user name and API token.

To generate an API token in Zendesk, you need to be an administrator with API token access enabled in your account.

1. Log in to your Zendesk account.
2. Go to **Admin Center**. Click **Apps and integrations**, and then select **APIs** > **API tokens**.
3. Click **Add API token**.
4. Enter a description for the API token.
5. Click **Save** to generate the token.
6. Click **Copy**.

For more information about API token authentication in Zendesk, see Managing API tokens in the Zendesk documentation.

Client credentials authentication

To connect to Zendesk using the OAuth 2.0 client credentials authentication, you need the Zendesk client ID and client secret.

Configure the OAuth endpoint with the client credentials grant type, and then create an authorization integration to get the authorization details.

Use the Identifier value in the Zendesk application as **Client ID** and the Secret value as **Client Secret** when you configure a Zendesk connection using OAuth 2.0 client credentials authentication.

For more information about how to create an authorization integration and get the authorization details, see OAuth authentication with your application in the Zendesk documentation.

CHAPTER 3

Connections for Zendesk V2

Create a Zendesk V2 connection to securely read data from and write data to Zendesk.

You can use a Zendesk V2 connection to specify sources and targets in synchronization tasks, mappings, and mapping tasks.

Connect to Zendesk

Let's configure the Zendesk V2 connection properties to connect to Zendesk.

Before you begin

Before you get started, make sure a user account with administrator privileges is created in Zendesk. Get the relevant configuration details from your Zendesk account based on the authentication type that you want to configure.

Check out Chapter 2, “Prepare for authentication” on page 10 to learn more about the authentication prerequisites.

Connection details

The following table describes the basic connection properties:

Property	Description
Connection Name	Name of the connection. Each connection name must be unique within the organization. Connection names can contain alphanumeric characters, spaces, and the following special characters: _ . + -, Maximum length is 255 characters.
Description	Description of the connection. Maximum length is 4000 characters.

Property	Description
Use Secret Vault	Stores sensitive credentials for this connection in the secrets manager that is configured for your organization. This property appears only if secrets manager is set up for your organization. When you enable the secret vault in the connection, you can select which credentials that the Secure Agent retrieves from the secrets manager. If you don't enable this option, the credentials are stored in the repository or on a local Secure Agent, depending on how your organization is configured. **Note:** If you're using this connection to apply data access policies through pushdown or proxy services, you cannot use the Secret Vault configuration option. For information about how to configure and use a secrets manager, see "Secrets manager configuration" in the Administrator help.
Runtime Environment	The name of the runtime environment where you want to run tasks. Specify a Secure Agent, Hosted Agent, serverless, or elastic runtime environment. For more information about how to configure and use the runtime environments, see *Runtime Environments* in the Administrator help.
URL	URL of the Zendesk account. Specify the complete URL. For example, https://informaticabusinesssolution13.zendesk.com/api/v2.

Authentication types

You can configure the basic, API token, and OAuth 2.0 client credentials authentication types to access Zendesk.

Select the required authentication type, and then configure the authentication-specific parameters.

Basic authentication

Basic authentication requires the Zendesk account user name and password to connect to Zendesk. This is the default authentication type.

The following table describes the basic connection properties for basic authentication:

Property	Description
Username	The user name to connect to the Zendesk account.
Password	The password to connect to the Zendesk account.

Advanced settings

The following table describes the advanced connection properties for basic authentication:

Property	Description
Custom Field	Custom fields for Zendesk objects. For more information about configuring custom fields, see "Zendesk custom fields" on page 15.
Use Proxy	Connects to Zendesk through proxy server. Select the checkbox to use proxy server. For more information about connecting to proxy server, see "Proxy server settings" on page 17.
Enable Logging	Enables logging for the connector. Select the checkbox to enable logging when you create a connection, and use the connection to import metadata and run tasks.

API token authentication

API token authentication requires the Zendesk account user name and an API token to connect to Zendesk.

The following table describes the basic connection properties for API token authentication:

Property	Description
Username	The user name to connect to the Zendesk account.
API Token	The API token generated from the Zendesk application to authenticate the API requests made to the Zendesk endpoint.

Advanced settings

The following table describes the advanced connection properties for API token authentication:

Property	Description
Custom Field	Custom fields for Zendesk objects. For more information about configuring custom fields, see "Zendesk custom fields" on page 15.
Use Proxy	Connects to Zendesk through proxy server. Select the checkbox to use proxy server. For more information about connecting to proxy server, see "Proxy server settings" on page 17.
Enable Logging	Enables logging for the connector. Select the checkbox to enable logging when you create a connection, and use the connection to import metadata and run tasks.

Client credentials authentication

Client credentials authentication requires the Zendesk client ID and client secret to connect to Zendesk.

The following table describes the basic connection properties for OAuth 2.0 client credentials authentication:

Property	Description
Client ID	The client identifier of your application generated when you configure the application for OAuth.
Client Secret	The client secret generated for the client ID.

Advanced settings

The following table describes the advanced connection properties for OAuth 2.0 client credentials authentication:

Property	Description
Custom Field	Custom fields for Zendesk objects. For more information about configuring custom fields, see "Zendesk custom fields" on page 15.
Use Proxy	Connects to Zendesk through proxy server. Select the checkbox to use proxy server. For more information about connecting to proxy server, see "Proxy server settings" on page 17.
Enable Logging	Enables logging for the connector. Select the checkbox to enable logging when you create a connection, and use the connection to import metadata and run tasks.
Client Credentials Scope	The scope of the access request when the Zendesk endpoint has defined custom scopes. You can enter multiple scopes separated by a comma. Default is read write. For more information about specifying scopes, see Scopes in Zendesk documentation.
Client Credentials Expiry Time	The time in seconds to wait before the generated access token expires. Default is 3600.

Zendesk custom fields

You can use Zendesk V2 Connector to read data from the custom fields that are present in the following Zendesk objects:

- Organizations
- Tickets
- Users

To read data from custom fields in Zendesk, you must configure the **Custom Field** property when you create a Zendesk V2 connection.

The following table lists the various custom fields and data types that Zendesk V2 Connector supports:

Zendesk Custom Field Type	Data Type
Checkbox	BOOLEAN
Date	STRING
Decimal	DOUBLE
Multi-line Text	STRING
Numeric	INTEGER
Text	STRING

For more information about configuring Zendesk custom fields, see Custom fields and custom field types in the Zendesk documentation.

Rules and guidelines for custom fields

Consider the following rules and guidelines when you configure a custom field:

- Specify the custom fields in Zendesk using the following format, where FieldKey is value of the **Field key** in Zendesk application:

  ```
  Object1=”FieldKey1,DataType,Size,Filterable,PrimaryKey”;”FieldKey2,DataType,Size,Filterable,PrimaryKey”
  Object2=”FieldKey1,DataType,Size,Filterable,PrimaryKey”;”FieldKey2,DataType,Size,Filterable,PrimaryKey”
  ```

  For example, you can specify the following custom fields for Organizations and Users objects:

  ```
  Organizations="support_description,String,255,true,false"
  Users="problems,String,255,true,false";age,Double,0,true,false";"required,Boolean,0,true,false";"select,
  String,255,true,false";"support_description,String,255,true,false";"reg_ex,String,255,true,false"
  ```

- When you specify a custom field for Tickets object, you must specify the custom fields in the following format:

  ```
  Tickets=”CF_FieldID1,DataType,Size,Filterable,PrimaryKey”;”CF_FieldID2,DataType,Size,Filterable,
  PrimaryKey”
  ```

  For example,

  ```
  Tickets="CF_360003199614,String,255,true,false;"CF_360003373654,String,255,true,false"
  ```

- Specify the custom fields for different objects in a new line.
- When you specify multiple custom fields for an object, you must separate each custom field with a semicolon (;).
- If you specify a size for a custom field, the agent considers the size of only the string data type. You must set the size for custom fields of other data types as zero.
- The field key in a custom field must not contain special characters.
- To find the field key for Tickets object in the Zendesk website, go to **Settings** > **Manage Ticket Fields**.

Proxy server settings

If your organization uses an outgoing proxy server to connect to the Internet, the Secure Agent connects to Informatica Intelligent Cloud Services through the proxy server.

You can configure the Secure Agent to use the proxy server on Windows and Linux. You can use the unauthenticated or authenticated proxy server.

The proxy settings applies to connections used in mappings and in mappings in advanced mode.

To configure the proxy settings for the Secure Agent, perform the following tasks:

- Configure the Secure Agent through the Secure Agent Manager on Windows or shell command on Linux.

  For instructions, see "Configure the proxy settings on Windows" or "Configure the proxy settings on Linux" in *Getting Started* in the Data Integration help.
- Configure the proxy server properties in the `proxy.ini` file.

To configure proxy settings for the serverless runtime environment, see "Using a proxy server" in *Runtime Environments* in the Administrator help.

CHAPTER 4

Synchronization Tasks with Zendesk V2

Use a Synchronization task to synchronize data between a source and target.

You can configure a synchronization task using the Synchronization Task wizard. You can use Zendesk V2 objects as sources or targets objects.

When you create a task, you can associate it with a schedule to run it at specified times or on regular intervals. Or, you can run it manually. You can monitor tasks that are currently running in the activity monitor and view logs about completed tasks in the activity log.

Zendesk V2 Sources in Synchronization Tasks

You can use a Zendesk object as a single source in a synchronization task.

You can configure Zendesk source properties on the **Source** page of the Synchronization Task wizard.

The following table describes the Zendesk source properties:

Property	Description
Connection	Name of the Zendesk V2 source connection.
Source Type	Select **Single** or **Multiple** as the source type. Select **Single** to read data from a standard Zendesk object. Select **Multiple** to read data from a standard Zendesk object and add a single child object. **Note:** When you select **Multiple** as the source type, you cannot add a sibling object. The sibling object appears as a column of the child object and contains a value of string data type.
Source Object	Name of the Zendesk source object.

Advanced Source Properties for Zendesk V2

You can configure advanced source properties on the **Schedule** page of the Synchronization task wizard.

You can perform incremental data export for a Zendesk object by selecting the **Is Incremental Export** check box under the advanced source properties. Zendesk V2 Connector supports incremental data export for the following Zendesk objects:

- Organizations

- Tickets
- TicketMetricEvents
- Users

Data Filters

Data filters help you to fetch specific data of a particular object. You can assign a filter field to the object, and the synchronization task processes the data.

Perform the following steps to use data filters:

1. In a synchronization task, select the **Data Filters** tab.
2. Click **New**.

   The Data Filter dialog box appears.
3. Enter the data filter fields as described in the following table:

Field Type	Description
Object	Select object for which you want to assign filter fields.
Filter By	Select the filter field.
Operator	Select the corresponding operator.
Filter Value	Enter the filter value.

4. Click **OK**.

You cannot assign data filters when you use the following Zendesk objects in a synchronization task:

- Tags
- Requests

Rules and Guidelines for Data Filters

Consider the following rules and guidelines when you configure data filters:

- You cannot configure advanced data filters using Zendesk V2 Connector.
- If you use Variants, UserIdentities, TicketComments, TicketAudits, TicketMetricEvents, or DynamicContent as the source object, it is mandatory to assign data filters.
- When you configure a data filter for a field of Date data type, you must not specify the timestamp.
- If you select the **Is Incremental Export** advanced source property, you must provide a data filter only for **Updated_At** field in GMT format.

  Note: You must not provide data filters for any other field.

Zendesk V2 Targets in Synchronization Tasks

You can use the insert, update, and delete operations for a Zendesk target in a synchronization task.

When you perform an insert operation, define the source data in synchronization application to write to the Zendesk target. The Secure Agent inserts the source rows that you specify into the Zendesk target.

When you perform an update operation, define the source data in the synchronization application to update the records in the Zendesk target. The Secure Agent updates the rows that you specify in the Zendesk target. When you perform a delete operation, define the source data in the synchronization application to delete the records in the Zendesk target. The Secure Agent deletes the records that you specify in the Zendesk target.

The following table describes the Zendesk target properties:

Property	Description
Connection	Name of the Zendesk V2 target connection.
Target Type	Select **Single** or **Multiple** as the target type. Select **Single** to write data to a standard Zendesk object. Select **Multiple** to write data to a standard Zendesk object and add a single child object. **Note:** When you select **Multiple** as the target type, you cannot add a sibling object. The sibling object appears as a column of the child object and contains a value of string data type.
Target Object	Name of the Zendesk target object.

Advanced Target Properties for Zendesk V2

You can configure advanced target properties on the **Schedule** page of the Synchronization task wizard.

You can perform bulk insert, update, and delete operations on a Zendesk object by selecting the **Batch Operation** check box under the advanced target properties. Zendesk V2 Connector supports bulk operations for the following Zendesk objects:

- Organizations
- Tickets
- Users

CHAPTER 5

Mappings and Mapping Tasks with Zendesk V2

Use the Data Integration Mapping Designer to create a mapping. When you create a mapping, you configure a source or a target to represent a Zendesk object.In advanced mode, the Mapping Designer updates the mapping canvas to include transformations and functions that enable advanced functionality.

Validate the mapping and describe the flow of data from source and target along with the required transformations before the Secure Agent reads data from or writes data to the Zendesk object. Use the Mapping Task wizard to create a mapping task and select the mapping that you configured. The mapping task processes data based on the data flow logic you define in the mapping. Run the mapping task to read data from or write data to a Zendesk object.

Zendesk V2 Sources in Mappings

When you create a mapping, you can configure the source properties to use Zendesk objects to read the data from your Zendesk account. The source properties appear on the **Source** tab when you specify a Zendesk V2 connection. When you specify custom fields of Users and Organizations objects in the **Custom Field** connection property, the Secure Agent appends `CF_` to the custom field key and displays the custom fields in the **Field Mapping** tab.

The following table describes the Zendesk source properties.

Source Property	Description
Connection Type	Name of the Zendesk V2 source connection.
Source Type	Select **Single** or **Multiple** as the source type. Select **Single** to read data from a standard Zendesk object. Select **Multiple** to read data from a standard Zendesk object and add a single child object. **Note:** When you select **Multiple** as the source type, you cannot add a sibling object. The sibling object appears as a column of the child object and contains a value of string data type.
Source Object	Select the Zendesk source object for the task.

The following table describes the query options that you can configure in a Source transformation:

Property	Description
Filter	Filter value in a read operation. Click **Configure** to add conditions to filter records and reduce the number of rows that the Secure Agent reads from the source. Select **Not Parameterized** filter condition and use a basic filter to specify the object, field, operator, and value to select specific records. Zendesk V2 Connector does not support **Completely Parameterized** and **Advanced** filter conditions in a mapping. You cannot assign data filters when you use the following Zendesk objects in a mapping task: - Tags - Requests
Sort	Not applicable for Zendesk V2 Connector.

The following table describes the advanced properties that you configure for a Zendesk source object:

Property	Description
Is Incremental Export	Zendesk V2 Connector supports incremental data export for Tickets, TicketMetricEvents, Users, and Organizations objects. Select the check box to enable incremental export. **Note:** If you select the **Is Incremental Export** property, you must only provide data a filter for **Updated_At** field in GMT format. You must not provide data filters for any other field. For example, Updated_At Equals 2016-04-28 21:04:00
Tracing Level	Determines the amount of detail that appears in the log for the source. You can choose Terse, Normal, Verbose Initialization, or Verbose Data tracing level. Default is Normal.

Zendesk V2 Targets in Mappings

When you configure a mapping, you can use Zendesk V2 Connector as a target connection to write data to your Zendesk account. The target properties appear on the **Target** tab when you specify a Zendesk connection.

The following table describes the Zendesk target properties:

Source Property	Description
Connection Type	Name of the Zendesk V2 target connection.
Target Type	Select **Single** or **Multiple** as the target type. Select **Single** to write data to a standard Zendesk object. Select **Multiple** to write data to a standard Zendesk object and add a single child object. **Note:** When you select **Multiple** as the target type, you cannot add a sibling object. The sibling object appears as a column of the child object and contains a value of string data type.

Source Property	Description
Target Object	Select the target object for the task.
Task Operation	Select the target operation. You can perform insert, update, and delete operations with Zendesk V2 Connector.

The following table describes the advanced properties that you can configure for a Zendesk target:

Property	Description
Batch Operation	Select this property to perform bulk insert, update, and delete operations on a Zendesk object. Zendesk V2 Connector supports bulk operations for the following Zendesk objects: - Organizations - Tickets - Users
Success File Directory	Not applicable for Zendesk V2 Connector.
Error File Directory	Not applicable for Zendesk V2 Connector.
Forward Rejected Rows	Not applicable for Zendesk V2 Connector.

CHAPTER 6

Known Limitations

Zendesk V2 Connector has the following known limitations:

- When you run a mapping task to delete rows from the Users object using IDs and re-run the mapping task to delete more rows from the Users object, the Secure Agent does not displays the error rows and returns incorrect number of success rows.
- When you run a mapping to insert data into DynamicContent object, you must also add the Variants child object and ensure that the value of the default field is set to true. Otherwise, the mapping fails.

APPENDIX A

Zendesk V2 Data Type Reference

Data Integration uses the following data types in mappings, synchronization tasks, and mapping tasks with Zendesk:

Zendesk native data types

Zendesk data types appear in the **Fields** tab for Source and Target transformations when you choose to edit metadata for the fields.

Transformation data types

Set of data types that appear in the remaining transformations. They are internal data types based on ANSI SQL-92 generic data types, which Data Integration uses to move data across platforms. Transformation data types appear in all remaining transformations in a mapping, synchronization task, or mapping task.

When Data Integration reads source data, it converts the native data types to the comparable transformation data types before transforming the data. When Data Integration writes to a target, it converts the transformation data types to the comparable native data types.

Zendesk V2 and Transformation Data Types

The following table lists the Zendesk data types that Data Integration supports and the corresponding transformation data types:

Zendesk V2 Data Type	Transformation Data Type	Range
INTEGER	Double	-2,147,483,648 to 2,147,487,647 Precision 10, Scale 0
BOOLEAN	Integer	-2,147,483,648 to 2,147,487,647 Precision 10, Scale 0
DATE	Date/Time	Jan 1, 0001 A.D. to Dec 31, 9999 A.D. (Precision to the nanosecond)

Zendesk V2 Data Type	Transformation Data Type	Range
STRING	String	1 to 104,857,600 characters
DOUBLE	Double	Precision 15

INDEX

C

Cloud Application Integration community
  URL 5
Cloud Developer community
  URL 5

D

Data Integration community
  URL 5
data type reference
  overview 25

I

Informatica Global Customer Support
  contact information 6
Informatica Intelligent Cloud Services
  web site 5

M

maintenance outages 6
mapping tasks
  overview 21

S

status
  Informatica Intelligent Cloud Services 6
system status 6

T

transformation
  data types 25
trust site
  description 6

U

upgrade notifications 6

W

web site 5

Z

Zendesk V2
  assets 9
  data types 25
Zendesk V2 connection 12
Zendesk V2 Connector
  overview 7
  supported object types 7
Zendesk V2 Connector source
  Synchronization tasks 18
Zendesk V2 Connector target
  Synchronization tasks 20
Zendesk V2 sources
  mappings 21
  Synchronization task 18
Zendesk V2 target
  mappings 22