How-To Library

Informatica

Connecting to Oracle Database Cloud Service from Cloud Data Integration

© Copyright Informatica LLC 2021. Informatica, the Informatica logo, and Informatica Cloud are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html

Abstract

You can configure an Oracle connection to connect to Oracle Database Cloud Service from Cloud Data Integration®. This article describes how to configure Oracle connectivity to Oracle Database Cloud Service.

Supported Versions

- Informatica® Cloud Data Integration

Table of Contents

Overview. 2
Create the key store and trust store certificates for secure communication 2
Create an Oracle connection. 3

Overview

Oracle Database Cloud Service is an Oracle database that runs on a dynamic, on-demand cloud infrastructure. You can connect to Oracle Database Cloud Service from Cloud Data Integration to read and write data.

You can then use an Oracle connection in a mapping to connect securely to Oracle Database Cloud Service from Cloud Data Integration.

This article describes the following tasks that you must perform to configure a connection to Oracle Database Cloud Service from Cloud Data Integration:

1. Create the key store and trust store certificates for secure communication
2. Create an Oracle connection to read data from or write data to Oracle Database Cloud Service.

Create the key store and trust store certificates for secure communication

Before you create a connection, you must create the key store and trust store certificates to establish secure communication with Oracle Database Cloud Service.

1. Extract the certificate bundle ZIP file that contains the keystore `ewallet.p12` and truststore `truststore.jks` files.

   Note: Ensure that the trust store and key store files are in the PKCS12(.p12) format.

2. Run the following command to convert the existing `truststore.jks` file into a `truststore.p12` file.

   ```
   keytool -importkeystore -srckeystore truststore.jks -destkeystore truststore.p12 -
   srcstoretype JKS -deststoretype
       PKCS12 -deststorepass [PASSWORD_FOR_NEW_PKCS12_TRUSTSTORE]
   ```

3. Enter the source trust store password when prompted.

Create an Oracle connection

Create an Oracle connection and configure the required Oracle Database Cloud Service properties, including the Oracle advanced security options in Cloud Data Integration.

1. On the **Connections** page in Data Integration, click **New Connection**.

   The **New Connection** page appears.

2. Configure the connection properties.

   The following table describes the connection properties that you must configure to access Oracle Database Cloud Service:

Property	Description
Connection Name	Name of the Oracle connection.
Description	Description of the connection.
Type	Type of the connection. Select the type of the connection as **Oracle**.

3. Configure the Oracle connection properties:

   The following table describes the Oracle connection properties that you must configure to access Oracle Database Cloud Service:

Connection property	Description
Runtime Environment	Runtime environment that contains the Secure Agent used to access Oracle Database Cloud Service.
User Name	User name for the database login. The user name cannot contain a semicolon.
Password	Password for the database login. The password cannot contain a semicolon.
Host	Name of the machine that hosts the database server.
Port	Network port number used to connect to the database server. Default is 1521.
Service Name	Service name or System ID (SID) that uniquely identifies the Oracle Database Cloud Service database. Specify the SID in the following format to connect to Oracle Database Cloud Service databases: `SID:<ORACLE_SID>`
Schema	Schema used for the Oracle Database Cloud Service connection.
Code Page	The code page of the database server.
Encryption Method	The method that the Secure Agent uses to encrypt the data exchanged between the Secure Agent and the database server.
Crypto Protocol Version	Cryptographic protocols to use when you enable SSL encryption.

Connection property	Description
Validate Server Certificate	Validates the certificate that is sent by the database server. If you specify the `HostNameInCertificate` parameter, Secure Agent also validates the host name in the certificate.
Trust Store	The location and name of the trust store file. You must specify the absolute path of the truststore `truststore.p12` file.
Trust Store Password	The password to access the contents of the trust store file.
Host Name in Certificate	Optional. Host name of the machine that hosts the secure database. If you specify a host name, the Secure Agent validates the host name included in the connection with the host name in the SSL certificate. Use the *CN* value from the **tnsnames.ora** file as the hostname in certificate.
Key Store	The location and the file name of the key store `ewallet.p12` file.
Key Store Password	The password for the key store file required for secure communication.
Key Password	The password for the individual keys in the key store file required for secure communication.
Connection Retry Period	Number of seconds the Secure Agent attempts to reconnect to the Oracle Database Cloud Service database if the connection fails. If the Secure Agent cannot connect to the database in the retry period, the operation fails. Used for all operations. Default is 0.
Metadata Advanced Connection Properties	The optional properties for the JDBC driver to fetch the metadata. If you specify more than one property, separate each key-value pair with a semicolon. To connect to an Oracle Database Cloud Service database enabled for advanced security, specify the advanced security encryption options.
Runtime Advanced Connection Properties	The optional properties for the ODBC driver for running mappings. If you specify more than one property, separate each key-value pair with a semicolon. To connect to an Oracle Database Cloud Service database enabled for advanced security, specify the advanced security encryption options.

The following image shows the configured properties to access Oracle Database Cloud Service:



Authors

Gurumoorthy N

Dimple Rai