Informatica®

Informatica® Application Integration
April 2025

OData Connector Guide

Informatica Application Integration OData Connector Guide
April 2025

© Copyright Informatica LLC 1993, 2025

Publication Date: 2025-08-30

Table of Contents

Preface 4

Chapter 1: Introduction to OData Connector 5

OData Connector Overview 5

Chapter 2: OData connections 6

OData Connections Overview 6

Basic Connection Properties 6

OData Connection Properties 8

OData Connection Read Attribute 8

OData Connection Write Attributes 9

Chapter 3: OData Connector processes 10

OData Connector processes overview 10

Index 11

Preface

Read the *OData Connector Guide* to learn how organization administrators and business users can use OData Connector to connect to an OData service through restful API calls. Learn how to integrate OData Connector with Application Integration and OData compliant, on-premise compliant, or cloud applications compliant systems.

This guide assumes that you have an understanding of OData objects and services, and how to create connections and processes in Application Integration.

CHAPTER 1

Introduction to OData Connector

This chapter includes the following topic:

- OData Connector Overview, 5

OData Connector Overview

Open Data Protocol (OData) is an OASIS standard that defines best practices to build and consume RESTful APIs.

You can focus on business logic and build RESTful APIs with OData instead of defining request headers, response headers, status codes, HTTP methods, URL conventions, media types, payload formats and the query options. OData guides you to track changes and define functions, or actions for reusable procedures and send asynchronous, or batch requests. Use OData for extension and to fulfill any custom needs of your RESTful APIs. OData builds on core protocols, such as HTTP and commonly recognized methodologies like REST.

OData Connector integrates Application Integration with systems, such as SharePoint, databases, SAP OData services, and Team Foundation Services. These systems are OData compliant, on-premise compliant or cloud applications compliant. You can use Application Integration to interact with objects that are exposed in an OData service. OData Connector communicates with these systems in the OData protocol. Use the OData Connector to connect to an OData service through restful API calls. Rest calls can be in XML or JSON format. Choose the format that the OData service supports.

Create an OData connection to connect to objects in an OData service. Use the connection in a process to perform multiple activities. You can specify an OData connection in step types such as Assignment and Create.

CHAPTER 2

OData connections

This chapter includes the following topics:

- OData Connections Overview, 6
- Basic Connection Properties, 6
- OData Connection Properties, 8
- OData Connection Read Attribute, 8
- OData Connection Write Attributes, 9

OData Connections Overview

OData connections enable you to read data from or write data to an OData service.

After you create an OData connection, you can validate, save, and test the connection.

You can then publish the OData connection and click the **Metadata** tab to view the generated process objects for the connection.

Basic Connection Properties

The following table describes the basic properties that you can configure on the **Properties** tab of the connection creation page:

Property	Description
Name	Required. Unique name for the OData connection that identifies it in the Process Designer. The name must start with an alphabet and can contain only alphabets, numbers, or hyphens (-).
Location	Optional. The location of the project or folder where you want to save the connection. Click **Browse** to select a location. If the **Explore** page is currently active and a project or folder is selected, the default location for the connection is the selected project or folder. Otherwise, the default location is the location of the most recently saved asset.
Description	Optional. Description of the connection.

Property	Description
Type	Required. The type of connection that you want to create. Select **OData**.
Runtime Environment	Required. The name of Secure Agent or Secure Agent machine where the connection must run.
Connection Test	Not supported for OData Connector.

OData-Enabled	Optional. Select **Yes** to enable OData feeds and specify the allowed users and groups. If you select **Yes**, you must specify either the allowed users or the allowed groups.
	If you had enabled OData feeds in the OData connection, after you publish the connection, you can click **Actions** > **Properties Detail** to view the generated OData Service URL. The OData Service URL is available on an Informatica Cloud endpoint and uses the following format:
	`https://<Informatica Intelligent Cloud Services URL>/active-bpel/odata/v4/<OData_connection_name>`
	If you want to invoke the OData Service from a Secure Agent, use the following format to construct the OData Service URL:
	`https://<host>:<port>/process-engine/odata/v4/<OData_connection_name>/<schema_name>`
	Default is **No**.

Allowed Users for OData	Optional. The users that have access to the connection at design time. You can specify more than one user. After you specify the first value, press the Enter key or the Comma key, and then specify the next value.
Allowed Groups for OData	Optional. The user groups that have access to the connection at design time. You can specify more than one user group. After you specify the first value, press the Enter key or the Comma key, and then specify the next value.
Enable CORS for Domains	Optional. The additional allowed domains from which API consumers can invoke the associated APIs. API consumers running a web application running at one origin can access selected resources from origins that you mention in the **Enable CORS for Domains** field. Enter the wildcard character (*) to enable CORS for all domains. Enter a comma-separated list of domains to enable CORS for specific domains. For example, enter the following phrase to enable CORS for the abc.domain.com and xyz.domain.com domains: `abc.domain.com, xyz.domain.com`
Enable CORS for Verbs	Optional. The allowed verbs that API consumers can use to invoke the APIs from the domains that you specified in the **Enable CORS for Domains** field. Enter a comma-separated list of verbs to enable CORS for specific verbs. For example, enter the following phrase to enable CORS for the POST, PUT, and GET verbs: `POST, PUT, GET` Default is all verbs.

After you configure the basic properties, you must also define the following properties:

- The properties applicable to the OData connection type.
- The read and write attributes for the OData connection.

OData Connection Properties

The following table describes the OData connection properties that you must configure on the **Connection Settings** section:

Connection Property	Description
username	User name to connect to the OData service.
password	Password associated with the user name.
ServiceRootURi	Required. Root URI for the data source offered through the OData protocol. The resource identified by the service root URI must be an AtomPub service document as specified in RFC 5023. The resource must follow the OData conventions for AtomPub service documents or an alternate representation of an AtomPub service document if a different format is requested. You can view all the resource collections available for the data service based on the service document that is returned from the root of the ODate service. **Note:** For information about the service root URI conventions, see http://www.odata.org/documentation/odata-version-2-0/uri-conventions
OData Parameter File Path	Absolute path to a file that you append to the URL. The file contains key value pairs separated by a new line. You can use this file to check additional parameter values required in the URL. **Note:** Ensure that you use percent encoding to encode the key value pairs in the file.
Data Serialization Format	The format of data you want to transfer. You can choose one of the following options: - ATOM/XML - JSON Default is **ATOM/XML**.
Object Filter	Specific object that you want to access in an OData service. You can specify a list of comma separated object names.

OData Connection Read Attribute

The following table describes the read attributes you can specify for a OData connection:

Read Attributes	Description
Maximum Page Size	Specifies the maximum number of entries returned by third-party per page. Default is **50**

OData Connection Write Attributes

The following table describes the write attributes you can specify for a OData connection:

Write Attributes	Description
Primary Key Override	Column names that you want to use as the primary key. Use commas to separate multiple column names.

CHAPTER 3

OData Connector processes

This chapter includes the following topic:

- OData Connector processes overview, 10

OData Connector processes overview

You can use Process Designer in Application Integration to read, create, change, or delete data in OData objects.

In a process in Application Integration, you can configure an OData connection to connect to objects in an OData service. Use the connection in a process to perform multiple activities. You can specify an OData connection in step types such as Assignment and Create.

Example

As an HR administrator in an organization, you want to update the employee database when new employees join your organization. You can create an OData connection to the Employees object in the OData service. You can then design and run a process to insert the employee details from a source file object to the Employee object in the OData service.

INDEX

O

OData
  connection properties 8
OData connections
  overview 6
OData Connector
  overview 5
  process overview 10