Informatica® Cloud Application Integration
August 2025

Cohere Connector Guide

Informatica Cloud Application Integration Cohere Connector Guide
August 2025

© Copyright Informatica LLC 2025

This software and documentation contain proprietary information of Informatica LLC and are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright law. Reverse engineering of the software is prohibited. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC. This Software may be protected by U.S. and/or international Patents and other Patents Pending.

Use, duplication, or disclosure of the Software by the U.S. Government is subject to the restrictions set forth in the applicable software license agreement and as provided in DFARS 227.7202-1(a) and 227.7702-3(a) (1995), DFARS 252.227-7013©(1)(ii) (OCT 1988), FAR 12.212(a) (1995), FAR 52.227-19, or FAR 52.227-14 (ALT III), as applicable.

The information in this product or documentation is subject to change without notice. If you find any problems in this product or documentation, please report them to us in writing.

Informatica, Informatica Platform, Informatica Data Services, PowerCenter, PowerCenterRT, PowerCenter Connect, PowerCenter Data Analyzer, PowerExchange, PowerMart, Metadata Manager, Informatica Data Quality, Informatica Data Explorer, Informatica B2B Data Transformation, Informatica B2B Data Exchange Informatica On Demand, Informatica Identity Resolution, Informatica Application Information Lifecycle Management, Informatica Complex Event Processing, Ultra Messaging, Informatica Master Data Management, and Live Data Map are trademarks or registered trademarks of Informatica LLC in the United States and in jurisdictions throughout the world. All other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties, including without limitation: Copyright DataDirect Technologies. All rights reserved. Copyright © Sun Microsystems. All rights reserved. Copyright © RSA Security Inc. All Rights Reserved. Copyright © Ordinal Technology Corp. All rights reserved. Copyright © Aandacht c.v. All rights reserved. Copyright Genivia, Inc. All rights reserved. Copyright Isomorphic Software. All rights reserved. Copyright © Meta Integration Technology, Inc. All rights reserved. Copyright © Intalio. All rights reserved. Copyright © Oracle. All rights reserved. Copyright © Adobe Systems Incorporated. All rights reserved. Copyright © DataArt, Inc. All rights reserved. Copyright © ComponentSource. All rights reserved. Copyright © Microsoft Corporation. All rights reserved. Copyright © Rogue Wave Software, Inc. All rights reserved. Copyright © Teradata Corporation. All rights reserved. Copyright © Yahoo! Inc. All rights reserved. Copyright © Glyph & Cog, LLC. All rights reserved. Copyright © Thinkmap, Inc. All rights reserved. Copyright © Clearpace Software Limited. All rights reserved. Copyright © Information Builders, Inc. All rights reserved. Copyright © OSS Nokalva, Inc. All rights reserved. Copyright Edifecs, Inc. All rights reserved. Copyright Cleo Communications, Inc. All rights reserved. Copyright © International Organization for Standardization 1986. All rights reserved. Copyright © ej-technologies GmbH. All rights reserved. Copyright © Jaspersoft Corporation. All rights reserved. Copyright © International Business Machines Corporation. All rights reserved. Copyright © yWorks GmbH. All rights reserved. Copyright © Lucent Technologies. All rights reserved. Copyright © University of Toronto. All rights reserved. Copyright © Daniel Veillard. All rights reserved. Copyright © Unicode, Inc. Copyright IBM Corp. All rights reserved. Copyright © MicroQuill Software Publishing, Inc. All rights reserved. Copyright © PassMark Software Pty Ltd. All rights reserved. Copyright © LogiXML, Inc. All rights reserved. Copyright © 2003-2010 Lorenzi Davide, All rights reserved. Copyright © Red Hat, Inc. All rights reserved. Copyright © The Board of Trustees of the Leland Stanford Junior University. All rights reserved. Copyright © EMC Corporation. All rights reserved. Copyright © Flexera Software. All rights reserved. Copyright © Jinfonet Software. All rights reserved. Copyright © Apple Inc. All rights reserved. Copyright © Telerik Inc. All rights reserved. Copyright © BEA Systems. All rights reserved. Copyright © PDFlib GmbH. All rights reserved. Copyright © Orientation in Objects GmbH. All rights reserved. Copyright © Tanuki Software, Ltd. All rights reserved. Copyright © Ricebridge. All rights reserved. Copyright © Sencha, Inc. All rights reserved. Copyright © Scalable Systems, Inc. All rights reserved. Copyright © jQWidgets. All rights reserved. Copyright © Tableau Software, Inc. All rights reserved. Copyright© MaxMind, Inc. All Rights Reserved. Copyright © TMate Software s.r.o. All rights reserved. Copyright © MapR Technologies Inc. All rights reserved. Copyright © Amazon Corporate LLC. All rights reserved. Copyright © Highsoft. All rights reserved. Copyright © Python Software Foundation. All rights reserved. Copyright © BeOpen.com. All rights reserved. Copyright © CNRI. All rights reserved.

This product includes software developed by the Apache Software Foundation (http://www.apache.org/), and/or other software which is licensed under various versions of the Apache License (the "License"). You may obtain a copy of these Licenses at http://www.apache.org/licenses/. Unless required by applicable law or agreed to in writing, software distributed under these Licenses is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the Licenses for the specific language governing permissions and limitations under the Licenses.

This product includes software which was developed by Mozilla (http://www.mozilla.org/), software copyright The JBoss Group, LLC, all rights reserved; software copyright © 1999-2006 by Bruno Lowagie and Paulo Soares and other software which is licensed under various versions of the GNU Lesser General Public License Agreement, which may be found at http:// www.gnu.org/licenses/lgpl.html. The materials are provided free of charge by Informatica, "as-is", without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

The product includes ACE(TM) and TAO(TM) software copyrighted by Douglas C. Schmidt and his research group at Washington University, University of California, Irvine, and Vanderbilt University, Copyright (©) 1993-2006, all rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (copyright The OpenSSL Project. All Rights Reserved) and redistribution of this software is subject to terms available at http://www.openssl.org and http://www.openssl.org/source/license.html.

This product includes Curl software which is Copyright 1996-2013, Daniel Stenberg, <daniel@haxx.se>. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://curl.haxx.se/docs/copyright.html. Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

The product includes software copyright 2001-2005 (©) MetaStuff, Ltd. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://www.dom4j.org/ license.html.

The product includes software copyright © 2004-2007, The Dojo Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://dojotoolkit.org/license.

This product includes ICU software which is copyright International Business Machines Corporation and others. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://source.icu-project.org/repos/icu/icu/trunk/license.html.

This product includes software copyright © 1996-2006 Per Bothner. All rights reserved. Your right to use such materials is set forth in the license which may be found at http:// www.gnu.org/software/ kawa/Software-License.html.

This product includes OSSP UUID software which is Copyright © 2002 Ralf S. Engelschall, Copyright © 2002 The OSSP Project Copyright © 2002 Cable & Wireless Deutschland. Permissions and limitations regarding this software are subject to terms available at http://www.opensource.org/licenses/mit-license.php.

This product includes software developed by Boost (http://www.boost.org/) or under the Boost software license. Permissions and limitations regarding this software are subject to terms available at http:/ /www.boost.org/LICENSE_1_0.txt.

This product includes software copyright © 1997-2007 University of Cambridge. Permissions and limitations regarding this software are subject to terms available at http:// www.pcre.org/license.txt.

This product includes software copyright © 2007 The Eclipse Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http:// www.eclipse.org/org/documents/epl-v10.php and at http://www.eclipse.org/org/documents/edl-v10.php.

This product includes software licensed under the terms at http://www.tcl.tk/software/tcltk/license.html, http://www.bosrup.com/web/overlib/?License, http://www.stlport.org/doc/ license.html, http://asm.ow2.org/license.html, http://www.cryptix.org/LICENSE.TXT, http://hsqldb.org/web/hsqlLicense.html, http://httpunit.sourceforge.net/doc/ license.html, http://jung.sourceforge.net/license.txt , http://www.gzip.org/zlib/zlib_license.html, http://www.openldap.org/software/release/license.html, http://www.libssh2.org, http://slf4j.org/license.html, http://www.sente.ch/software/OpenSourceLicense.html, http://fusesource.com/downloads/license-agreements/fuse-message-broker-v-5-3- license-agreement; http://antlr.org/license.html; http://aopalliance.sourceforge.net/; http://www.bouncycastle.org/licence.html; http://www.jgraph.com/jgraphdownload.html; http://www.jcraft.com/jsch/LICENSE.txt; http://jotm.objectweb.org/bsd_license.html; . http://www.w3.org/Consortium/Legal/2002/copyright-software-20021231; http://www.slf4j.org/license.html; http://nanoxml.sourceforge.net/orig/copyright.html; http://www.json.org/license.html; http://forge.ow2.org/projects/javaservice/, http://www.postgresql.org/about/licence.html, http://www.sqlite.org/copyright.html, http://www.tcl.tk/software/tcltk/license.html, http://www.jaxen.org/faq.html, http://www.jdom.org/docs/faq.html, http://www.slf4j.org/license.html; http://www.iodbc.org/dataspace/iodbc/wiki/iODBC/License; http://www.keplerproject.org/md5/license.html; http://www.toedter.com/en/jcalendar/license.html; http://www.edankert.com/bounce/index.html; http://www.net-snmp.org/about/license.html; http://www.openmdx.org/#FAQ; http://www.php.net/license/3_01.txt; http://srp.stanford.edu/license.txt; http://www.schneier.com/blowfish.html; http://www.jmock.org/license.html; http://xsom.java.net; http://benalman.com/about/license/; https://github.com/CreateJS/EaselJS/blob/master/src/easeljs/display/Bitmap.js; http://www.h2database.com/html/license.html#summary; http://jsoncpp.sourceforge.net/LICENSE; http://jdbc.postgresql.org/license.html; http://protobuf.googlecode.com/svn/trunk/src/google/protobuf/descriptor.proto; https://github.com/rantav/hector/blob/master/LICENSE; http://web.mit.edu/Kerberos/krb5-current/doc/mitK5license.html; http://jibx.sourceforge.net/jibx-license.html; https://github.com/lyokato/libgeohash/blob/master/LICENSE; https://github.com/hjiang/jsonxx/blob/master/LICENSE; https://code.google.com/p/lz4/; https://github.com/jedisct1/libsodium/blob/master/LICENSE; http://one-jar.sourceforge.net/index.php?page=documents&file=license; https://github.com/EsotericSoftware/kryo/blob/master/license.txt; http://www.scala-lang.org/license.html; https://github.com/tinkerpop/blueprints/blob/master/LICENSE.txt; http://gee.cs.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html; https://aws.amazon.com/asl/; https://github.com/twbs/bootstrap/blob/master/LICENSE; https://sourceforge.net/p/xmlunit/code/HEAD/tree/trunk/LICENSE.txt; https://github.com/documentcloud/underscore-contrib/blob/master/LICENSE, and https://github.com/apache/hbase/blob/master/LICENSE.txt.

This product includes software licensed under the Academic Free License (http://www.opensource.org/licenses/afl-3.0.php), the Common Development and Distribution License (http://www.opensource.org/licenses/cddl1.php) the Common Public License (http://www.opensource.org/licenses/cpl1.0.php), the Sun Binary Code License Agreement Supplemental License Terms, the BSD License (http:// www.opensource.org/licenses/bsd-license.php), the new BSD License (http://opensource.org/licenses/BSD-3-Clause), the MIT License (http://www.opensource.org/licenses/mit-license.php), the Artistic License (http://www.opensource.org/licenses/artistic-license-1.0) and the Initial Developer's Public License Version 1.0 (http://www.firebirdsql.org/en/initial-developer-s-public-license-version-1-0/).

This product includes software copyright © 2003-2006 Joe Walnes, 2006-2007 XStream Committers. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://xstream.codehaus.org/license.html. This product includes software developed by the Indiana University Extreme! Lab. For further information please visit http://www.extreme.indiana.edu/.

This product includes software Copyright (c) 2013 Frank Balluffi and Markus Moeller. All rights reserved. Permissions and limitations regarding this software are subject to terms of the MIT license.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

Publication Date: 2025-08-30

Table of Contents

Preface 5

Chapter 1: Introduction to Cohere Connector 6

Cohere overview 6

Chapter 2: Cohere connections 7

Basic connection properties 7

Cohere connection properties 8

Create a Cohere API key 8

Cohere connection metadata 10

Cohere connection actions and objects 10

Using a Cohere connection in a process 14

Preface

Read the *Cohere Connector Guide* to learn how to set up and use Cohere connections. Use a Cohere connection to leverage advanced multilingual models, sophisticated retrieval functionalities, and an AI workspace specifically designed to meet the needs of the modern enterprise, all integrated within a single, secure platform. This guide assumes that you have an understanding of the Cohere concepts.

CHAPTER 1

Introduction to Cohere Connector

Use Cohere Connector to facilitate seamless integration between your applications and Cohere’s advanced natural language processing (NLP) services.

You can use Cohere Connector to leverage advanced multilingual models, sophisticated retrieval functionalities, and an AI workspace specifically designed to meet the needs of the modern enterprise, all integrated within a single, secure platform. It allows users to easily connect their workflows, pipelines, or platforms with Cohere's APIs to leverage functionalities, such as text generation, classification, and embedding.

The connector simplifies the process of authenticating, sending requests, and handling responses, making it easier for developers and analysts to incorporate powerful language models into their solutions without extensive coding. This integration supports automation, enhances user experiences, and accelerates development cycles by providing ready-to-use components for Cohere's AI capabilities.

You can use the Cohere Connector for content generation, customer support automation, sentiment analysis, semantic search, text classification, language translation or multilingual support, data enrichment, and custom AI application development.

Cohere overview

Cohere is a leading provider of natural language processing (NLP) technologies that empower developers and businesses with advanced language models.

The platform offers scalable and customizable AI services, including natural language understanding, text generation, and semantic search. By leveraging large-scale transformer models, Cohere allows users to create sophisticated applications in areas such as content creation, customer support, and sentiment analysis. The platform emphasizes ease of use, flexibility, and high performance, providing APIs that integrate seamlessly into various environments. Cohere supports multiple languages and provides tools for fine-tuning models to meet specific business needs, driving innovation and efficiency through advanced language AI.

CHAPTER 2

Cohere connections

Use a Cohere connection to connect to the Cohere APIs from Application Integration.

You can perform actions, such as chat command, classify, embeddings, get connector details, get model, get model list, list connectors, and rerank.

After you create a Cohere connection, you can validate and save the connection.

You can then publish the Cohere connection and click the **Metadata** tab to view the generated process objects for the connection.

Basic connection properties

The following table describes the basic properties that you can configure on the **Properties** tab of the connection creation page:

Property	Description
Name	Required. Unique name for the Cohere connection that identifies it in the Process Designer. The name must start with an alphabet and can contain only alphabets, numbers, and hyphens (-).
Location	The location of the project or folder where you want to save the connection. Click **Browse** to select a location. If the **Explore** page is currently active and a project or folder is selected, the default location for the connection is the selected project or folder. Otherwise, the default location is the location of the most recently saved asset.
Description	Optional. Description of the connection.
Type	Required. The type of connection you want to use for the connector or service connector. Select **Cohere**.
Runtime Environment	Required. The runtime environment for the connection. You can run the connection on the Cloud Server, a Secure Agent group, or a Secure Agent machine.
Connection Test	Not supported for Cohere Connector.
OData-Enabled	Not supported for Cohere Connector.

Cohere connection properties

To use the Cohere API, you need the base URL and API key to access the Cohere instance.

The following table defines the Cohere connection properties that you must configure in the **Connection Properties** section:

Property	Description
Base_URL	The primary endpoint that connects to the Cohere API and serves as the entry point for all API requests.
API_Key	A unique identifier that is used to authenticate and authorize access to the Cohere API.


Create a Cohere API key

Create a Cohere API key to authenticate and authorize access to Cohere's API services.


To create a Cohere API key, perform the following steps:

1. Log in to Cohere and go to the API Keys section using https://dashboard.cohere.com/api-keys.
2. Click **New Trial key**.

   The following image shows the **New Trial key** option on the **API Keys** page:




3. Enter the key name and click **Generate Trial key**.



4. Copy the API key.

   The following image shows the generated API key:




   You can save the API key for future use.

Cohere connection metadata

After you create a Cohere connection, you can validate and save the connection. You can then publish the Cohere connection and click the **Metadata** tab to view the generated process objects for the connection.

When you publish a Cohere connection in Application Integration, the **Actions** and **Objects** appear on the **Metadata** tab.

The following image shows the **Metadata** tab for a published Cohere connection:



Cohere connection actions and objects

When you publish a Cohere connection in Application Integration, the **Actions** and **Objects** appear on the **Metadata** tab.

Consider the following information when you use specific actions and objects:

- The **Chat Command** action generates a text response to a user message and streams it token by token. The following snippet is a sample request body:

```
<chatInput xmlns:m="urn:informatica:ae:xquery:json2xml:meta-data">
   <model>command</model>
<messages>
<role>system</role>
<content>You respond concisely as a professional assistant respond properly</content>
</messages>
<messages>
<role>user</role>
<content>{who am i}</content>
</messages>
</chatInput>
```

- The **Classify** action predicts the most suitable label for the given text input by referencing the provided examples of text and label pairs.
  The following snippet is a sample request body:

```
<root xmlns:m="urn:informatica:ae:xquery:json2xml:meta-data">
<model>embed-english-v3.0</model>
<inputs m:isArray="true">Confirm your email address</inputs>
<inputs m:isArray="true">hey i need u to send some $</inputs>
<examples m:isArray="true">
<text>Dermatologists don't like her!</text>
<label>Spam</label>
</examples>
<examples m:isArray="true">
<text>Hello, open to this?</text>
<label>Spam</label>
</examples>
<examples m:isArray="true">
<text>I need help please wire me $1000 right now</text>
<label>Spam</label>
</examples>
<examples m:isArray="true">
<text>Nice to know you ;)</text>
<label>Spam</label>
</examples>
<examples m:isArray="true">
<text>Please help me?</text>
<label>Spam</label>
</examples>
<examples m:isArray="true">
<text>Your parcel will be delivered today</text>
<label>Not spam</label>
</examples>
<examples m:isArray="true">
<text>Review changes to our Terms and Conditions</text>
<label>Not spam</label>
</examples>
<examples m:isArray="true">
<text>Weekly sync notes</text>
<label>Not spam</label>
</examples>
<examples m:isArray="true">
<text>Re: Follow up from today's meeting</text>
<label>Not spam</label>
</examples>
<examples m:isArray="true">
<text>Pre-read for tomorrow</text>
<label>Not spam</label>
</examples>
</root>
```

- The **Embeddings** action lists the floating-point numbers that capture the semantic information of the represented content.
  The following snippet is a sample request body:

```
<root xmlns:m="urn:informatica:ae:xquery:json2xml:meta-data">
<model>embed-v4.0</model>
<texts>goodbye</texts>
<texts>goodbye now</texts>
<input_type>classification</input_type>
<embedding_types m:isArray="true">float</embedding_types>
</root>
```

- The **Get Connector Details** action retrieves the connector details using its ID.
  The following snippet is a sample response:

```
<root>
   <connector>
      <updated_at>0001-01-01T00:00:00Z</updated_at>
      <name>Web Search</name>
      <created_at>0001-01-01T00:00:00Z</created_at>
```

```
      <continue_on_failure>true</continue_on_failure>
      <id>web-search</id>
   </connector>
</root>
```

- The **Get Model** action returns detailed information about a model based on its name.
  The following snippet is a sample response:

```
<root>
   <features>logprobs</features>
   <features>json_mode</features>
   <features>json_schema</features>
   <features>strict_tools</features>
   <features>tools</features>
   <endpoints>generate</endpoints>
   <endpoints>chat</endpoints>
   <endpoints>summarize</endpoints>
   <finetuned>false</finetuned>
   <name>command-r</name>
   <context_length>132096</context_length>
   <tokenizer_url>https://storage.googleapis.com/cohere-public/tokenizers/command-
r.json</tokenizer_url>
   <supports_vision>false</supports_vision>
   <default_endpoints/>
</root>
```

- The **Get Model List** action returns a list of available models, including Cohere models and user-created models.
  The following snippet is a sample response:

```
<root>
   <models>
      <features/>
      <endpoints>embed</endpoints>
      <endpoints>classify</endpoints>
      <finetuned>false</finetuned>
      <name>embed-english-light-v3.0</name>
      <context_length>512</context_length>
      <tokenizer_url>https://storage.googleapis.com/cohere-public/tokenizers/embed-
english-light-v3.0.json</tokenizer_url>
      <supports_vision>false</supports_vision>
      <default_endpoints/>
   </models>
   <models>
      <features/>
      <endpoints>embed</endpoints>
      <endpoints>classify</endpoints>
      <finetuned>false</finetuned>
      <name>embed-multilingual-v2.0</name>
      <context_length>256</context_length>
      <tokenizer_url>https://storage.googleapis.com/cohere-public/tokenizers/embed-
multilingual-v2.0.json</tokenizer_url>
      <supports_vision>false</supports_vision>
      <default_endpoints/>
   </models>
</root>
```

- The **List Connectors** action returns a list of connectors ordered by their descending creation date.
  The following snippet is a sample response:

```
<root>
   <connectors>
      <updated_at>0001-01-01T00:00:00Z</updated_at>
      <name>Web Search</name>
      <created_at>0001-01-01T00:00:00Z</created_at>
      <active>true</active>
      <continue_on_failure>true</continue_on_failure>
      <id>web-search</id>
   </connectors>
   <connectors>
      <auth_type>oauth</auth_type>
```

```
      <updated_at>2024-09-16T03:23:25.902505Z</updated_at>
      <organization_id>d489c39a-e152-49da-9ddc-9801bd74d823</organization_id>
      <name>Google Drive (beta)</name>
      <created_at>2024-09-04T20:03:20.420686Z</created_at>
      <active>true</active>
      <continue_on_failure>false</continue_on_failure>
      <id>gdrive-with-oauth-18fbc3</id>
      <oauth>
         <authorize_url>https://accounts.google.com/o/oauth2/auth</authorize_url>
         <scope>https://www.googleapis.com/auth/drive.readonly</scope>
         <token_url>https://oauth2.googleapis.com/token</token_url>
      </oauth>
      <url>https://gdrive-o5btz7ucgq-uc.a.run.app/search</url>
   </connectors>
   <total_count>2</total_count>
</root>
```

- The **Rerank** action takes a query and a list of texts, and then returns an ordered array where each text is assigned a relevance score.
  The following snippet is a sample request body:

```
<root xmlns:m="urn:informatica:ae:xquery:json2xml:meta-data">
<model>rerank-v3.5</model>
<query>What is the capital of the india?</query>
<top_n m:type="xs:int">3</top_n>
<documents m:isArray="true">Mumbai City is the capital city of the india.</documents>
<documents m:isArray="true">The Commonwealth of the Northern Mariana Islands is a
group of islands in the Pacific Ocean. Its capital is Saipan.</documents>
<documents m:isArray="true">DELHI is the capital of the india. It is a union
territory.</documents>
<documents m:isArray="true">Capitalization or capitalisation in English grammar is
the use of a capital letter at the start of a word. English usage varies from
capitalization in other languages.</documents>
<documents m:isArray="true">Capital punishment has existed in the United States since
beforethe United States was a country. As of 2017, capital punishment is legal in 30
of the 50 states.</documents>
</root>
```

  The following snippet is a sample response:


```
<root>
   <meta>
      <billed_units>
         <search_units>1</search_units>
      </billed_units>
      <api_version>
         <version>2</version>
      </api_version>
   </meta>
   <id>737d16b8-9665-420e-b30b-d10c77f63ab2</id>
   <results>
      <index>2</index>
      <relevance_score>0.852752</relevance_score>
   </results>
   <results>
      <index>0</index>
      <relevance_score>0.84183896</relevance_score>
   </results>
   <results>
      <index>1</index>
      <relevance_score>0.08085701</relevance_score>
   </results>
</root>
```

For more information about the specific action in the Cohere connection, see the Cohere documentation.

Using a Cohere connection in a process

After you create a Cohere connection, you can use it in a Service step in a process.

1. Add a Service step to the process.
2. Click the **Service** tab.
3. From the **Service Type** list, select **Connection**.
4. From the **Connection** list, browse and select the Cohere connection that you created.
5. From the **Action** list, select the action that you want to perform. For example, select the **Get Model** action to return detailed information about a model based on its name as shown in the following image:



   In this case, Application Integration populates the **modelName** object under the input fields and the **ModelDetails** object under the output fields.
6. Configure further steps as needed.
7. Validate, save, and publish the process.