Informatica® Cloud Application Integration
May 2025

Microsoft Teams Connector Guide

Informatica Cloud Application Integration Microsoft Teams Connector Guide
May 2025

© Copyright Informatica LLC 2025

This software and documentation contain proprietary information of Informatica LLC and are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright law. Reverse engineering of the software is prohibited. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC. This Software may be protected by U.S. and/or international Patents and other Patents Pending.

Use, duplication, or disclosure of the Software by the U.S. Government is subject to the restrictions set forth in the applicable software license agreement and as provided in DFARS 227.7202-1(a) and 227.7702-3(a) (1995), DFARS 252.227-7013©(1)(ii) (OCT 1988), FAR 12.212(a) (1995), FAR 52.227-19, or FAR 52.227-14 (ALT III), as applicable.

The information in this product or documentation is subject to change without notice. If you find any problems in this product or documentation, please report them to us in writing.

Informatica, Informatica Platform, Informatica Data Services, PowerCenter, PowerCenterRT, PowerCenter Connect, PowerCenter Data Analyzer, PowerExchange, PowerMart, Metadata Manager, Informatica Data Quality, Informatica Data Explorer, Informatica B2B Data Transformation, Informatica B2B Data Exchange Informatica On Demand, Informatica Identity Resolution, Informatica Application Information Lifecycle Management, Informatica Complex Event Processing, Ultra Messaging, Informatica Master Data Management, and Live Data Map are trademarks or registered trademarks of Informatica LLC in the United States and in jurisdictions throughout the world. All other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties, including without limitation: Copyright DataDirect Technologies. All rights reserved. Copyright © Sun Microsystems. All rights reserved. Copyright © RSA Security Inc. All Rights Reserved. Copyright © Ordinal Technology Corp. All rights reserved. Copyright © Aandacht c.v. All rights reserved. Copyright Genivia, Inc. All rights reserved. Copyright Isomorphic Software. All rights reserved. Copyright © Meta Integration Technology, Inc. All rights reserved. Copyright © Intalio. All rights reserved. Copyright © Oracle. All rights reserved. Copyright © Adobe Systems Incorporated. All rights reserved. Copyright © DataArt, Inc. All rights reserved. Copyright © ComponentSource. All rights reserved. Copyright © Microsoft Corporation. All rights reserved. Copyright © Rogue Wave Software, Inc. All rights reserved. Copyright © Teradata Corporation. All rights reserved. Copyright © Yahoo! Inc. All rights reserved. Copyright © Glyph & Cog, LLC. All rights reserved. Copyright © Thinkmap, Inc. All rights reserved. Copyright © Clearpace Software Limited. All rights reserved. Copyright © Information Builders, Inc. All rights reserved. Copyright © OSS Nokalva, Inc. All rights reserved. Copyright Edifecs, Inc. All rights reserved. Copyright Cleo Communications, Inc. All rights reserved. Copyright © International Organization for Standardization 1986. All rights reserved. Copyright © ej-technologies GmbH. All rights reserved. Copyright © Jaspersoft Corporation. All rights reserved. Copyright © International Business Machines Corporation. All rights reserved. Copyright © yWorks GmbH. All rights reserved. Copyright © Lucent Technologies. All rights reserved. Copyright © University of Toronto. All rights reserved. Copyright © Daniel Veillard. All rights reserved. Copyright © Unicode, Inc. Copyright IBM Corp. All rights reserved. Copyright © MicroQuill Software Publishing, Inc. All rights reserved. Copyright © PassMark Software Pty Ltd. All rights reserved. Copyright © LogiXML, Inc. All rights reserved. Copyright © 2003-2010 Lorenzi Davide, All rights reserved. Copyright © Red Hat, Inc. All rights reserved. Copyright © The Board of Trustees of the Leland Stanford Junior University. All rights reserved. Copyright © EMC Corporation. All rights reserved. Copyright © Flexera Software. All rights reserved. Copyright © Jinfonet Software. All rights reserved. Copyright © Apple Inc. All rights reserved. Copyright © Telerik Inc. All rights reserved. Copyright © BEA Systems. All rights reserved. Copyright © PDFlib GmbH. All rights reserved. Copyright © Orientation in Objects GmbH. All rights reserved. Copyright © Tanuki Software, Ltd. All rights reserved. Copyright © Ricebridge. All rights reserved. Copyright © Sencha, Inc. All rights reserved. Copyright © Scalable Systems, Inc. All rights reserved. Copyright © jQWidgets. All rights reserved. Copyright © Tableau Software, Inc. All rights reserved. Copyright© MaxMind, Inc. All Rights Reserved. Copyright © TMate Software s.r.o. All rights reserved. Copyright © MapR Technologies Inc. All rights reserved. Copyright © Amazon Corporate LLC. All rights reserved. Copyright © Highsoft. All rights reserved. Copyright © Python Software Foundation. All rights reserved. Copyright © BeOpen.com. All rights reserved. Copyright © CNRI. All rights reserved.

This product includes software developed by the Apache Software Foundation (http://www.apache.org/), and/or other software which is licensed under various versions of the Apache License (the "License"). You may obtain a copy of these Licenses at http://www.apache.org/licenses/. Unless required by applicable law or agreed to in writing, software distributed under these Licenses is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the Licenses for the specific language governing permissions and limitations under the Licenses.

This product includes software which was developed by Mozilla (http://www.mozilla.org/), software copyright The JBoss Group, LLC, all rights reserved; software copyright © 1999-2006 by Bruno Lowagie and Paulo Soares and other software which is licensed under various versions of the GNU Lesser General Public License Agreement, which may be found at http:// www.gnu.org/licenses/lgpl.html. The materials are provided free of charge by Informatica, "as-is", without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

The product includes ACE(TM) and TAO(TM) software copyrighted by Douglas C. Schmidt and his research group at Washington University, University of California, Irvine, and Vanderbilt University, Copyright (©) 1993-2006, all rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (copyright The OpenSSL Project. All Rights Reserved) and redistribution of this software is subject to terms available at http://www.openssl.org and http://www.openssl.org/source/license.html.

This product includes Curl software which is Copyright 1996-2013, Daniel Stenberg, <daniel@haxx.se>. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://curl.haxx.se/docs/copyright.html. Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

The product includes software copyright 2001-2005 (©) MetaStuff, Ltd. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://www.dom4j.org/ license.html.

The product includes software copyright © 2004-2007, The Dojo Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://dojotoolkit.org/license.

This product includes ICU software which is copyright International Business Machines Corporation and others. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://source.icu-project.org/repos/icu/icu/trunk/license.html.

This product includes software copyright © 1996-2006 Per Bothner. All rights reserved. Your right to use such materials is set forth in the license which may be found at http:// www.gnu.org/software/ kawa/Software-License.html.

This product includes OSSP UUID software which is Copyright © 2002 Ralf S. Engelschall, Copyright © 2002 The OSSP Project Copyright © 2002 Cable & Wireless Deutschland. Permissions and limitations regarding this software are subject to terms available at http://www.opensource.org/licenses/mit-license.php.

This product includes software developed by Boost (http://www.boost.org/) or under the Boost software license. Permissions and limitations regarding this software are subject to terms available at http:/ /www.boost.org/LICENSE_1_0.txt.

This product includes software copyright © 1997-2007 University of Cambridge. Permissions and limitations regarding this software are subject to terms available at http:// www.pcre.org/license.txt.

This product includes software copyright © 2007 The Eclipse Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http:// www.eclipse.org/org/documents/epl-v10.php and at http://www.eclipse.org/org/documents/edl-v10.php.

This product includes software licensed under the terms at http://www.tcl.tk/software/tcltk/license.html, http://www.bosrup.com/web/overlib/?License, http://www.stlport.org/doc/ license.html, http://asm.ow2.org/license.html, http://www.cryptix.org/LICENSE.TXT, http://hsqldb.org/web/hsqlLicense.html, http://httpunit.sourceforge.net/doc/ license.html, http://jung.sourceforge.net/license.txt , http://www.gzip.org/zlib/zlib_license.html, http://www.openldap.org/software/release/license.html, http://www.libssh2.org, http://slf4j.org/license.html, http://www.sente.ch/software/OpenSourceLicense.html, http://fusesource.com/downloads/license-agreements/fuse-message-broker-v-5-3- license-agreement; http://antlr.org/license.html; http://aopalliance.sourceforge.net/; http://www.bouncycastle.org/licence.html; http://www.jgraph.com/jgraphdownload.html; http://www.jcraft.com/jsch/LICENSE.txt; http://jotm.objectweb.org/bsd_license.html; . http://www.w3.org/Consortium/Legal/2002/copyright-software-20021231; http://www.slf4j.org/license.html; http://nanoxml.sourceforge.net/orig/copyright.html; http://www.json.org/license.html; http://forge.ow2.org/projects/javaservice/, http://www.postgresql.org/about/licence.html, http://www.sqlite.org/copyright.html, http://www.tcl.tk/software/tcltk/license.html, http://www.jaxen.org/faq.html, http://www.jdom.org/docs/faq.html, http://www.slf4j.org/license.html; http://www.iodbc.org/dataspace/iodbc/wiki/iODBC/License; http://www.keplerproject.org/md5/license.html; http://www.toedter.com/en/jcalendar/license.html; http://www.edankert.com/bounce/index.html; http://www.net-snmp.org/about/license.html; http://www.openmdx.org/#FAQ; http://www.php.net/license/3_01.txt; http://srp.stanford.edu/license.txt; http://www.schneier.com/blowfish.html; http://www.jmock.org/license.html; http://xsom.java.net; http://benalman.com/about/license/; https://github.com/CreateJS/EaselJS/blob/master/src/easeljs/display/Bitmap.js; http://www.h2database.com/html/license.html#summary; http://jsoncpp.sourceforge.net/LICENSE; http://jdbc.postgresql.org/license.html; http://protobuf.googlecode.com/svn/trunk/src/google/protobuf/descriptor.proto; https://github.com/rantav/hector/blob/master/LICENSE; http://web.mit.edu/Kerberos/krb5-current/doc/mitK5license.html; http://jibx.sourceforge.net/jibx-license.html; https://github.com/lyokato/libgeohash/blob/master/LICENSE; https://github.com/hjiang/jsonxx/blob/master/LICENSE; https://code.google.com/p/lz4/; https://github.com/jedisct1/libsodium/blob/master/LICENSE; http://one-jar.sourceforge.net/index.php?page=documents&file=license; https://github.com/EsotericSoftware/kryo/blob/master/license.txt; http://www.scala-lang.org/license.html; https://github.com/tinkerpop/blueprints/blob/master/LICENSE.txt; http://gee.cs.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html; https://aws.amazon.com/asl/; https://github.com/twbs/bootstrap/blob/master/LICENSE; https://sourceforge.net/p/xmlunit/code/HEAD/tree/trunk/LICENSE.txt; https://github.com/documentcloud/underscore-contrib/blob/master/LICENSE, and https://github.com/apache/hbase/blob/master/LICENSE.txt.

This product includes software licensed under the Academic Free License (http://www.opensource.org/licenses/afl-3.0.php), the Common Development and Distribution License (http://www.opensource.org/licenses/cddl1.php) the Common Public License (http://www.opensource.org/licenses/cpl1.0.php), the Sun Binary Code License Agreement Supplemental License Terms, the BSD License (http:// www.opensource.org/licenses/bsd-license.php), the new BSD License (http://opensource.org/licenses/BSD-3-Clause), the MIT License (http://www.opensource.org/licenses/mit-license.php), the Artistic License (http://www.opensource.org/licenses/artistic-license-1.0) and the Initial Developer's Public License Version 1.0 (http://www.firebirdsql.org/en/initial-developer-s-public-license-version-1-0/).

This product includes software copyright © 2003-2006 Joe Walnes, 2006-2007 XStream Committers. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://xstream.codehaus.org/license.html. This product includes software developed by the Indiana University Extreme! Lab. For further information please visit http://www.extreme.indiana.edu/.

This product includes software Copyright (c) 2013 Frank Balluffi and Markus Moeller. All rights reserved. Permissions and limitations regarding this software are subject to terms of the MIT license.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

Publication Date: 2025-09-18

Table of Contents

Preface 5

Chapter 1: Introduction to Microsoft Teams Connector 6

Microsoft Teams overview 6

Chapter 2: Microsoft Teams connections 7

Create an Azure application 7

Basic connection properties 8

Microsoft Teams connection authentication properties 9

Microsoft Teams connection properties 10

Microsoft Teams connection metadata 10

Microsoft Teams connection actions and objects 10

Using a Microsoft Teams connection in a process 14

Preface

Read the *Microsoft Teams Connector Guide* to learn how to set up and use Microsoft Teams connections. This guide assumes that you have an understanding of Microsoft Teams concepts.

CHAPTER 1

Introduction to Microsoft Teams Connector

The Microsoft Teams Connector is a tool designed to integrate Microsoft Teams with other applications and services, facilitating enhanced communication and collaboration within organizational workflows.

Microsoft Teams is a collaborative platform that brings together chat, meetings, file sharing, and app integration all within a single interface. The Microsoft Teams Connector extends the capabilities of Teams by allowing seamless interaction with external applications, enabling users to integrate various workflows and data sources into their Teams environment.

Microsoft Teams overview

Microsoft Teams is a comprehensive communication and collaboration platform developed by Microsoft as part of the Microsoft 365 suite. Microsoft Teams can be accessed through the Microsoft Graph API. It serves as a centralized hub for teamwork, combining chat, video meetings, file storage, and application integration to enhance productivity and streamline communication within organizations.

Microsoft Teams offers a variety of features designed to enhance collaboration and streamline communication for organizations with distributed teams. These include chat and messaging, video and audio meetings, file sharing and collaboration, channels and tabs, application integration, security and compliance, and customizable workspaces. Microsoft Teams supports various use cases, including remote work collaboration, project management, education and training, and customer service.

CHAPTER 2

Microsoft Teams connections

Use Microsoft Teams Connector to integrate and connect with various applications, services, and platforms. This enhances the functionality of Microsoft Teams and provides a seamless workflow experience. It enables users to streamline processes, automate tasks, and improve communication without leaving the Teams interface.

You can perform CRUD operations, such as create, read, update, and delete, on existing Microsoft Teams objects, such as Teams, Channels, Messages, and Files.

You can also perform actions, such as creating, deleting, updating, retrieving, patching objects, and posting messages.


After you create a Microsoft Teams connection, you can validate and save the connection.

You can then publish the Microsoft Teams connection and click the **Metadata** tab to view the generated process objects for the connection.

Create an Azure application

To use Microsoft Teams connector, you must create an Azure application for a Microsoft Teams connector.

1. Open the Azure portal.
2. Navigate to Microsoft Entra ID.
3. Go to **Manage** > **App registration** > **New registration** and enter a name for your application.
4. For supported account types, choose the appropriate option based on your application needs. For redirect URI, select **Web** and enter your redirect URL.
5. Click **Register**.
6. Go to the newly registered application's overview page.
7. Go to **Manage** > **Authentication** and add the redirect URIs if you haven't already.
8. In the **Implicit grant** section, enable **Access tokens** and **ID tokens**.
9. Go to **Manage** > **API permissions** > **Add a permission** and select **Microsoft Graph**.
10. Choose **Delegated permissions** and select necessary permissions, such as User.Read, email, offline _access, openid, and profile and click **Add permissions**.
11. On the application's overview page, copy the **Application (client) ID**.
12. Go to **Manage** > **Certificates & secrets** > **Client secrets** and click **New client secret** as shown in the following image:



13. Enter a description and select an expiration date and click **Add**.
14. Copy the value of the new client secret. It will not be displayed again.
15. Use the client ID and secret to connect your Teams connector application to Azure.

Basic connection properties

The following table describes the basic properties that you can configure on the **Properties** tab of the connection creation page:

Property	Description
Name	Required. Unique name for the Microsoft Teams connection that identifies it in the Process Designer. The name must start with an alphabet and can contain only alphabets, numbers, and hyphens (-).
Location	The location of the project or folder where you want to save the connection. Click **Browse** to select a location. If the **Explore** page is currently active and a project or folder is selected, the default location for the connection is the selected project or folder. Otherwise, the default location is the location of the most recently saved asset.
Description	Optional. Description of the connection.
Type	Required. The type of connection you want to use for the connector or service connector. Select **Microsoft Teams**.
Runtime Environment	Required. The runtime environment for the connection. You can run the connection on the Cloud Server, a Secure Agent group, or a Secure Agent machine.
Connection Test	Not supported for Microsoft Teams Connector.
OData-Enabled	Not supported for Microsoft Teams Connector.

After you configure the basic properties, you can define the OAuth2 authentication properties for the Microsoft Teams connection.

Microsoft Teams connection authentication properties

When you create a Microsoft Teams connection, you can configure the connection using OAuth2 authentication properties.

To authenticate the Microsoft Teams connection using OAuth2 authentication, select **OAuth2** in the **Authentication Type** list and configure the following properties:

Property	Description
Authorization URL	Required. Enter the OAuth authorization URL for the OAuth provider to authorize the user request. For example: `https://login.microsoftonline.com/xxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxx/oauth2/v2.0/authorize`
Token Request URL	Required. Enter the OAuth token request URL that handles token requests. For example: `https://login.microsoftonline.com/xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx/oauth2/v2.0/token` The expiration of the refresh token depends on the OAuth provider. You must re-authenticate and publish the connection before the token expires. **Note:** The refresh token doesn't apply to agents and agent groups.
Client ID	Required. Specify the identifier value from the OAuth provider.
Client Secret	Required. Enter the client secret to connect to the email application.
Scope	Required. Specify the scope. The scope in OAuth authentication limits an application's access to a user's account. You can select multiple scopes for a single client. To enter multiple scopes, separate each value with a space. For example, Channel.Create Channel.Delete.All Channel.ReadBasic.All ChannelMember.Read.All email offline_access Group.Read.All Group.ReadWrite.All.
Authorization Status	Indicates the current status, the name of the user who authorized, and the last time when the authorization was completed.
Authorize Access	Click to initiate the authorization workflow using OAuth.

Important: The following properties are standard OAuth 2.0 and OpenID Connect (OIDC) scopes commonly used in Microsoft Teams for correct authentication:

- **openid**: A required scope for OpenID Connect. It indicates that you want to authenticate the user.
- **profile**: Adds basic profile information to the id_token, such as first name, last name, display name, and preferred_username.
- **email**: Grants access to the user's email address. This can be included in the id_token.
- **offline_access**: Allows the app to receive a refresh token. This enables continued access to resources even after the access token expires, so the user does not need to log in again.

Microsoft Teams connection properties


To use Microsoft Teams, you need the Microsoft graph API version. Enter the Microsoft Graph API version in the **API_Version** property in the **Connection Properties** section. The API version is used to create a Microsoft Teams connection. For example, `v1.0`.

Microsoft Teams connection metadata

After you create a Microsoft Teams connection, you can validate and save the connection. You can then publish the Microsoft Teams connection and click the **Metadata** tab to view the generated process objects for the connection.

When you publish a Microsoft Teams connection in Application Integration, the **Actions** and **Objects** appear on the **Metadata** tab.

The following image shows the **Metadata** tab for a published Microsoft Teams connection:



Microsoft Teams connection actions and objects

When you publish a Microsoft Teams connection in Application Integration, the **Actions** and **Objects** appear on the **Metadata** tab.

Consider the following information when you use specific actions and objects:

- The **Get Object** action retrieves objects depending on the entity type using the GET Web API method.

The following snippet is a sample response for retrieving a list of available Teams in the organization:

```
<root>
   <odata.context>https://graph.microsoft.com/v1.0/$metadata#teams</odata.context>
   <odata.count>2</odata.count>
   <value>
      <summary/>
      <visibility>private</visibility>
      <guestSettings/>
      <displayName>Teams 1</displayName>
      <isArchived/>
      <tagSettings/>
      <createdDateTime/>
      <description>Teams 1</description>
      <discoverySettings/>
      <classification/>
      <internalId/>
      <isMembershipLimitedToOwners/>
      <messagingSettings/>
      <webUrl/>
      <funSettings/>
      <specialization/>
      <id>7e4f33d5-5297-4af8-b8c7-aff187c86b5d</id>
      <memberSettings/>
   </value>
   <value>
      <summary/>
      <visibility>private</visibility>
      <guestSettings/>
      <displayName>Teams 2</displayName>
      <isArchived/>
      <tagSettings/>
      <createdDateTime/>
      <description>Teams 2</description>
      <discoverySettings/>
      <classification/>
      <internalId/>
      <isMembershipLimitedToOwners/>
      <messagingSettings/>
      <webUrl/>
      <funSettings/>
      <specialization/>
      <id>60b7c33d-1302-45e8-9d55-c634743bcd74</id>
      <memberSettings/>
   </value>
</root>
```

- The **Create Object** action creates a single Microsoft Teams object using the POST HTTP method.
  The following snippet is a sample request payload example to create a channel within a specified team.

```
<root>
    <displayName>Sample channel 1</displayName>
    <description>This channel is a sample channel</description>
    <membershipType>standard</membershipType>
</root>
```

  The following snippet is a sample response payload example of the created ticket:

```
<root>
   <membershipType>standard</membershipType>
   <odata.context>https://graph.microsoft.com/
v1.0/$metadata#teams('ad2e7f8c-8bd4-44f1-a15c-d9a782025066')/channels/$entity</
odata.context>
   <displayName>Sample channel 1</displayName>
   <isArchived>false</isArchived>
   <webUrl>https://teams.microsoft.com/l/channel/
19%3abf15b4d4eaf84f8eb00a488f674be763%40thread.tacv2/Sample+channel+1?
groupId=<Group_ID>&amp;tenantId=<Tenant_ID></webUrl>
   <createdDateTime>2025-04-08T22:59:50.6160702Z</createdDateTime>
   <description>This channel is a sample channel</description>
   <id>19:bf15b4d4eaf84f8eb00a488f674be763@thread.tacv2</id>
   <isFavoriteByDefault>false</isFavoriteByDefault>
```

```
   <email/>
</root>
```

- The **Delete Object** action deletes a single Microsoft Teams object using the DELETE HTTP method.
  To delete an entity, you must specify values in the entityType and entityId fields. For example, to delete a team by ID, you must specify the entity type as teams and the entity ID of the team.

  After the team is deleted, if you try to call this action a second time, you will receive the following error:

```
<root>
   <error>
      <code>NotFound</code>
      <innerError>
         <date>2025-04-08T23:20:24</date>
         <code>1</code>
         <client-request-id>71b1165a-66f1-4a49-b1d8-a938b5098740</client-request-id>
         <message>SoftDeleted-Thread was not found as it is soft-deleted.</message>
         <request-id>71b1165a-66f1-4a49-b1d8-a938b5098740</request-id>
      </innerError>
      <message>NotFound</message>
   </error>
</root>
```

- The **Update Object** action updates and deletes using soft delete a single Microsoft Teams object.
  The following snippet is a sample payload example to update a group of properties:

```
<root xmlns:m="urn:informatica:ae:xquery:json2xml:meta-data">
<memberSettings>
<allowCreatePrivateChannels m:type="xs:boolean"> true</allowCreatePrivateChannels>
<allowCreateUpdateChannels m:type="xs:boolean">true</allowCreateUpdateChannels>
</memberSettings>
<messagingSettings>
<allowUserEditMessages m:type="xs:boolean">true</allowUserEditMessages>
<allowUserDeleteMessages m:type="xs:boolean">true</allowUserDeleteMessages>
</messagingSettings>
<funSettings>
<allowGiphy m:type="xs:boolean">true</allowGiphy>
<giphyContentRating>strict</giphyContentRating>
</funSettings>
</root>
```

- The **Patch Object** action patches a single Microsoft Teams object. This action is similar to the Update action, but uses the PATCH HTTP method.
  The following snippet is a sample request payload to patch a group with the entityType property value as `groups(uniqueName='Group1Unique')`:

```
<root xmlns:m="urn:informatica:ae:xquery:json2xml:meta-data">
    <description>Description 1</description>
    <displayName>Display Name 1</displayName>
    <groupTypes m:isArray="true">Unified</groupTypes>
    <mailEnabled m:type="xs:boolean">true</mailEnabled>
    <mailNickname>someNickname</mailNickname>
    <securityEnabled m:type="xs:boolean">false</securityEnabled>
</root>
```

  An empty response is returned with 204 HTTP status code.

- The **Post Message** action posts a single message to the channel.
  You must specify the team ID and channel ID to post a message to the channel. The following snippet is a sample input payload:

```
<root xmlns:m="urn:informatica:ae:xquery:json2xml:meta-data">
    <body>
        <contentType>html</contentType>
        <content>Content 4.</content>
    </body>
    <attachments m:isArray="true">
        <id>74d20c7f34aa4a7fb74e2b30004247c5</id>
        <contentType>application/vnd.microsoft.card.thumbnail</contentType>
        <jsonContent></jsonContent>
```

```
    </attachments>
</root>
```

The `jsonContent` will be replaced by `attachmentContent`, which is a separate input property. The `attachmentContent` property is in JSON format and must be properly formatted.

The following snippet is a usage example:

```
{ \\"title\\": \\"This is an example of posting a card\\", \\"subtitle\\": \
\"<h3>This is the subtitle</h3>\\" }
```

The following snippet is a sample response payload:

```
<root>
   <summary/>
   <lastModifiedDateTime>2025-04-08T23:34:31.631Z</lastModifiedDateTime>
   <lastEditedDateTime/>
   <attachments>
      <teamsAppId/>
      <contentUrl/>
      <name/>
      <id>74d20c7f34aa4a7fb74e2b30004247c5</id>
      <contentType>application/vnd.microsoft.card.thumbnail</contentType>
      <content>{&#xD;
  "title": "This is an example of posting a card",&#xD;
  "subtitle": "&lt;h3&gt;This is the subtitle&lt;/h3&gt;"&#xD;
}</content>
      <thumbnailUrl/>
   </attachments>
   <odata.context>https://graph.microsoft.com/
v1.0/$metadata#teams('9f3781dd-1838-4e5d-9717-21ebf4419d0d')/
channels('19%3AuHcmVFwkdTf_vdtcymNtE8AbM4I1ZEgnbmBUt_Kvrys1%40thread.tacv2')/messages/
$entity</odata.context>
   <chatId/>
   <replyToId/>
   <subject/>
   <importance>normal</importance>
   <createdDateTime>2025-04-08T23:34:31.631Z</createdDateTime>
   <deletedDateTime/>
   <policyViolation/>
   <locale>en-us</locale>
   <body>
      <contentType>html</contentType>
      <content>&lt;attachment id="74d20c7f34aa4a7fb74e2b30004247c5"&gt;&lt;/
attachment&gt;Content 4.</content>
   </body>
   <channelIdentity>
      <teamId>9f3781dd-1838-4e5d-9717-21ebf4419d0d</teamId>
      <channelId>19:uHcmVFwkdTf_vdtcymNtE8AbM4I1ZEgnbmBUt_Kvrys1@thread.tacv2</
channelId>
   </channelIdentity>
   <messageType>message</messageType>
   <webUrl>https://teams.microsoft.com/l/message/
19%3AuHcmVFwkdTf_vdtcymNtE8AbM4I1ZEgnbmBUt_Kvrys1%40thread.tacv2/1744155271631?
groupId=<Group_ID>&amp;tenantId=<Tenant_ID>&amp;createdTime=1744155271631&amp;parentMe
ssageId=<Parent_Message_ID></webUrl>
   <mentions/>
   <etag>1744155271631</etag>
   <from>
      <application/>
      <device/>
      <user>
         <odata.type>#microsoft.graph.teamworkUserIdentity</odata.type>
         <displayName>ABC</displayName>
         <tenantId>29ecc36f-ba8d-4f7c-b037-22269e437749</tenantId>
         <id>c348b735-5c8b-48a4-be80-064e98b5ff9a</id>
         <userIdentityType>aadUser</userIdentityType>
      </user>
   </from>
   <reactions/>
   <id>1744155271631</id>
```

```
        <eventDetail/>
    </root>
```

Additional action parameters

queryParams is the object that holds query key-value pairs.

The following example is used to display the top 10 records of a particular entity type:

```
<root>
    <queryParam>
        <propertyName>$top</propertyName>
        <value>10</value>
    </queryParam>
</root>
```

Additional HTTP headers


ConsistencyLevel - When specified, the `eventual` value enhances the query capabilities of actions using the GET method.

Prefer - To include unknown member types, you must provide the `include-unknown-enum-members` value. Additionally, the Prefer header determines merge behavior. For example, if you attempt to PATCH a nonexistent object and set the Prefer header value to `create-if-missing`, the object will be created.

Using a Microsoft Teams connection in a process

After you create a Microsoft Teams connection, you can use it in a Service step in a process.

1. Add a Service step to the process.
2. Click the **Service** tab.
3. From the **Service Type** list, select **Connection**.
4. From the **Connection** list, browse and select the Microsoft Teams connection that you created.
5. From the **Action** list, select the action that you want to perform. For example, select the **Update Object** action to update a single Microsoft Teams object as shown in the following image:



In this case, Application Integration populates the **entityType**, **entityId**, **segment1**, …., **segment6**, and **requestObject** objects under the input fields and the **response** and **statusCode** objects under the output fields.

6. Configure further steps as needed.
7. Validate, save, and publish the process.