Informatica

Informatica® Cloud Application Integration
August 2025

AI Agent for Jira using NVIDIA NIM

Informatica Cloud Application Integration AI Agent for Jira using NVIDIA NIM
August 2025

© Copyright Informatica LLC 2025

This software and documentation contain proprietary information of Informatica LLC and are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright law. Reverse engineering of the software is prohibited. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC. This Software may be protected by U.S. and/or international Patents and other Patents Pending.

Use, duplication, or disclosure of the Software by the U.S. Government is subject to the restrictions set forth in the applicable software license agreement and as provided in DFARS 227.7202-1(a) and 227.7702-3(a) (1995), DFARS 252.227-7013©(1)(ii) (OCT 1988), FAR 12.212(a) (1995), FAR 52.227-19, or FAR 52.227-14 (ALT III), as applicable.

The information in this product or documentation is subject to change without notice. If you find any problems in this product or documentation, please report them to us in writing.

Informatica, Informatica Platform, Informatica Data Services, PowerCenter, PowerCenterRT, PowerCenter Connect, PowerCenter Data Analyzer, PowerExchange, PowerMart, Metadata Manager, Informatica Data Quality, Informatica Data Explorer, Informatica B2B Data Transformation, Informatica B2B Data Exchange Informatica On Demand, Informatica Identity Resolution, Informatica Application Information Lifecycle Management, Informatica Complex Event Processing, Ultra Messaging, Informatica Master Data Management, and Live Data Map are trademarks or registered trademarks of Informatica LLC in the United States and in jurisdictions throughout the world. All other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties, including without limitation: Copyright DataDirect Technologies. All rights reserved. Copyright © Sun Microsystems. All rights reserved. Copyright © RSA Security Inc. All Rights Reserved. Copyright © Ordinal Technology Corp. All rights reserved. Copyright © Aandacht c.v. All rights reserved. Copyright Genivia, Inc. All rights reserved. Copyright Isomorphic Software. All rights reserved. Copyright © Meta Integration Technology, Inc. All rights reserved. Copyright © Intalio. All rights reserved. Copyright © Oracle. All rights reserved. Copyright © Adobe Systems Incorporated. All rights reserved. Copyright © DataArt, Inc. All rights reserved. Copyright © ComponentSource. All rights reserved. Copyright © Microsoft Corporation. All rights reserved. Copyright © Rogue Wave Software, Inc. All rights reserved. Copyright © Teradata Corporation. All rights reserved. Copyright © Yahoo! Inc. All rights reserved. Copyright © Glyph & Cog, LLC. All rights reserved. Copyright © Thinkmap, Inc. All rights reserved. Copyright © Clearpace Software Limited. All rights reserved. Copyright © Information Builders, Inc. All rights reserved. Copyright © OSS Nokalva, Inc. All rights reserved. Copyright Edifecs, Inc. All rights reserved. Copyright Cleo Communications, Inc. All rights reserved. Copyright © International Organization for Standardization 1986. All rights reserved. Copyright © ej-technologies GmbH. All rights reserved. Copyright © Jaspersoft Corporation. All rights reserved. Copyright © International Business Machines Corporation. All rights reserved. Copyright © yWorks GmbH. All rights reserved. Copyright © Lucent Technologies. All rights reserved. Copyright © University of Toronto. All rights reserved. Copyright © Daniel Veillard. All rights reserved. Copyright © Unicode, Inc. Copyright IBM Corp. All rights reserved. Copyright © MicroQuill Software Publishing, Inc. All rights reserved. Copyright © PassMark Software Pty Ltd. All rights reserved. Copyright © LogiXML, Inc. All rights reserved. Copyright © 2003-2010 Lorenzi Davide, All rights reserved. Copyright © Red Hat, Inc. All rights reserved. Copyright © The Board of Trustees of the Leland Stanford Junior University. All rights reserved. Copyright © EMC Corporation. All rights reserved. Copyright © Flexera Software. All rights reserved. Copyright © Jinfonet Software. All rights reserved. Copyright © Apple Inc. All rights reserved. Copyright © Telerik Inc. All rights reserved. Copyright © BEA Systems. All rights reserved. Copyright © PDFlib GmbH. All rights reserved. Copyright © Orientation in Objects GmbH. All rights reserved. Copyright © Tanuki Software, Ltd. All rights reserved. Copyright © Ricebridge. All rights reserved. Copyright © Sencha, Inc. All rights reserved. Copyright © Scalable Systems, Inc. All rights reserved. Copyright © jQWidgets. All rights reserved. Copyright © Tableau Software, Inc. All rights reserved. Copyright© MaxMind, Inc. All Rights Reserved. Copyright © TMate Software s.r.o. All rights reserved. Copyright © MapR Technologies Inc. All rights reserved. Copyright © Amazon Corporate LLC. All rights reserved. Copyright © Highsoft. All rights reserved. Copyright © Python Software Foundation. All rights reserved. Copyright © BeOpen.com. All rights reserved. Copyright © CNRI. All rights reserved.

This product includes software developed by the Apache Software Foundation (http://www.apache.org/), and/or other software which is licensed under various versions of the Apache License (the "License"). You may obtain a copy of these Licenses at http://www.apache.org/licenses/. Unless required by applicable law or agreed to in writing, software distributed under these Licenses is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the Licenses for the specific language governing permissions and limitations under the Licenses.

This product includes software which was developed by Mozilla (http://www.mozilla.org/), software copyright The JBoss Group, LLC, all rights reserved; software copyright © 1999-2006 by Bruno Lowagie and Paulo Soares and other software which is licensed under various versions of the GNU Lesser General Public License Agreement, which may be found at http:// www.gnu.org/licenses/lgpl.html. The materials are provided free of charge by Informatica, "as-is", without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

The product includes ACE(TM) and TAO(TM) software copyrighted by Douglas C. Schmidt and his research group at Washington University, University of California, Irvine, and Vanderbilt University, Copyright (©) 1993-2006, all rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (copyright The OpenSSL Project. All Rights Reserved) and redistribution of this software is subject to terms available at http://www.openssl.org and http://www.openssl.org/source/license.html.

This product includes Curl software which is Copyright 1996-2013, Daniel Stenberg, <daniel@haxx.se>. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://curl.haxx.se/docs/copyright.html. Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

The product includes software copyright 2001-2005 (©) MetaStuff, Ltd. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://www.dom4j.org/ license.html.

The product includes software copyright © 2004-2007, The Dojo Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://dojotoolkit.org/license.

This product includes ICU software which is copyright International Business Machines Corporation and others. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://source.icu-project.org/repos/icu/icu/trunk/license.html.

This product includes software copyright © 1996-2006 Per Bothner. All rights reserved. Your right to use such materials is set forth in the license which may be found at http:// www.gnu.org/software/ kawa/Software-License.html.

This product includes OSSP UUID software which is Copyright © 2002 Ralf S. Engelschall, Copyright © 2002 The OSSP Project Copyright © 2002 Cable & Wireless Deutschland. Permissions and limitations regarding this software are subject to terms available at http://www.opensource.org/licenses/mit-license.php.

This product includes software developed by Boost (http://www.boost.org/) or under the Boost software license. Permissions and limitations regarding this software are subject to terms available at http:/ /www.boost.org/LICENSE_1_0.txt.

This product includes software copyright © 1997-2007 University of Cambridge. Permissions and limitations regarding this software are subject to terms available at http:// www.pcre.org/license.txt.

This product includes software copyright © 2007 The Eclipse Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http:// www.eclipse.org/org/documents/epl-v10.php and at http://www.eclipse.org/org/documents/edl-v10.php.

This product includes software licensed under the terms at http://www.tcl.tk/software/tcltk/license.html, http://www.bosrup.com/web/overlib/?License, http://www.stlport.org/doc/ license.html, http://asm.ow2.org/license.html, http://www.cryptix.org/LICENSE.TXT, http://hsqldb.org/web/hsqlLicense.html, http://httpunit.sourceforge.net/doc/ license.html, http://jung.sourceforge.net/license.txt , http://www.gzip.org/zlib/zlib_license.html, http://www.openldap.org/software/release/license.html, http://www.libssh2.org, http://slf4j.org/license.html, http://www.sente.ch/software/OpenSourceLicense.html, http://fusesource.com/downloads/license-agreements/fuse-message-broker-v-5-3- license-agreement; http://antlr.org/license.html; http://aopalliance.sourceforge.net/; http://www.bouncycastle.org/licence.html; http://www.jgraph.com/jgraphdownload.html; http://www.jcraft.com/jsch/LICENSE.txt; http://jotm.objectweb.org/bsd_license.html; . http://www.w3.org/Consortium/Legal/2002/copyright-software-20021231; http://www.slf4j.org/license.html; http://nanoxml.sourceforge.net/orig/copyright.html; http://www.json.org/license.html; http://forge.ow2.org/projects/javaservice/, http://www.postgresql.org/about/licence.html, http://www.sqlite.org/copyright.html, http://www.tcl.tk/software/tcltk/license.html, http://www.jaxen.org/faq.html, http://www.jdom.org/docs/faq.html, http://www.slf4j.org/license.html; http://www.iodbc.org/dataspace/iodbc/wiki/iODBC/License; http://www.keplerproject.org/md5/license.html; http://www.toedter.com/en/jcalendar/license.html; http://www.edankert.com/bounce/index.html; http://www.net-snmp.org/about/license.html; http://www.openmdx.org/#FAQ; http://www.php.net/license/3_01.txt; http://srp.stanford.edu/license.txt; http://www.schneier.com/blowfish.html; http://www.jmock.org/license.html; http://xsom.java.net; http://benalman.com/about/license/; https://github.com/CreateJS/EaselJS/blob/master/src/easeljs/display/Bitmap.js; http://www.h2database.com/html/license.html#summary; http://jsoncpp.sourceforge.net/LICENSE; http://jdbc.postgresql.org/license.html; http://protobuf.googlecode.com/svn/trunk/src/google/protobuf/descriptor.proto; https://github.com/rantav/hector/blob/master/LICENSE; http://web.mit.edu/Kerberos/krb5-current/doc/mitK5license.html; http://jibx.sourceforge.net/jibx-license.html; https://github.com/lyokato/libgeohash/blob/master/LICENSE; https://github.com/hjiang/jsonxx/blob/master/LICENSE; https://code.google.com/p/lz4/; https://github.com/jedisct1/libsodium/blob/master/LICENSE; http://one-jar.sourceforge.net/index.php?page=documents&file=license; https://github.com/EsotericSoftware/kryo/blob/master/license.txt; http://www.scala-lang.org/license.html; https://github.com/tinkerpop/blueprints/blob/master/LICENSE.txt; http://gee.cs.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html; https://aws.amazon.com/asl/; https://github.com/twbs/bootstrap/blob/master/LICENSE; https://sourceforge.net/p/xmlunit/code/HEAD/tree/trunk/LICENSE.txt; https://github.com/documentcloud/underscore-contrib/blob/master/LICENSE, and https://github.com/apache/hbase/blob/master/LICENSE.txt.

This product includes software licensed under the Academic Free License (http://www.opensource.org/licenses/afl-3.0.php), the Common Development and Distribution License (http://www.opensource.org/licenses/cddl1.php) the Common Public License (http://www.opensource.org/licenses/cpl1.0.php), the Sun Binary Code License Agreement Supplemental License Terms, the BSD License (http:// www.opensource.org/licenses/bsd-license.php), the new BSD License (http://opensource.org/licenses/BSD-3-Clause), the MIT License (http://www.opensource.org/licenses/mit-license.php), the Artistic License (http://www.opensource.org/licenses/artistic-license-1.0) and the Initial Developer's Public License Version 1.0 (http://www.firebirdsql.org/en/initial-developer-s-public-license-version-1-0/).

This product includes software copyright © 2003-2006 Joe Walnes, 2006-2007 XStream Committers. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://xstream.codehaus.org/license.html. This product includes software developed by the Indiana University Extreme! Lab. For further information please visit http://www.extreme.indiana.edu/.

This product includes software Copyright (c) 2013 Frank Balluffi and Markus Moeller. All rights reserved. Permissions and limitations regarding this software are subject to terms of the MIT license.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

Publication Date: 2025-09-23

Table of Contents

Preface 5

Chapter 1: Introduction to AI Agent for Jira using NVIDIA NIM recipe 6

AI Agent for Jira using NVIDIA NIM recipe contents 6

AI Agent for Jira using NVIDIA NIM recipe assets 7

Chapter 2: Using the AI Agent for Jira using NVIDIA NIM recipe 8

Step 1. Copy and access the recipe 8

Step 2. Publish the Generic Connector service connector 9

Step 3. Configure and publish the GenericConnection connection 9

Step 4. Configure and publish the Slack connection 10

Step 5. Configure and publish the NVIDIA NIM connection 11

Step 6. Configure and publish the Jira connection 11

Step 7. Configure and publish the processes 11

Step 8. Create webhook in Slack 12

Preface

Use *AI Agent for Jira using NVIDIA NIM* to learn how to receive a user query from Slack, send it to an NVIDIA NIM-powered AI agent that analyzes the request and performs the required actions in Jira, and returns the result to the Slack channel. This guide assumes that you have an understanding of the Jira Connector, NVIDIA NIM Connector, and Slack Connector concepts.

CHAPTER 1

Introduction to AI Agent for Jira using NVIDIA NIM recipe

The AI Agent for Jira using NVIDIA NIM recipe is based on REST and SOAP APIs. Use the recipe to receive a user query from Slack, send it to an NVIDIA NIM-powered AI agent that analyzes the request and performs the required actions in Jira, and returns the result to the Slack channel.

The process receives user input from Slack and skips messages if they are bot responses.


The Agent uses a Large Language Model (LLM) to generate the first API request based on the user's query. After executing the Jira API call, the Agent evaluates the response. If the Agent needs additional information, it formulates and executes a new Jira API request, using the previous response as a context. The Agent repeats this process until it collects enough data to answer the original query.

The Agent then compiles all the gathered information and uses the LLM to produce a clear and comprehensive response. The Agent sends this response back to the user in the same Slack channel, where it appears as a bot or app response.

AI Agent for Jira using NVIDIA NIM recipe contents

The AI Agent for Jira using NVIDIA NIM recipe contains a service connector, app connections, and processes.

The following image shows the assets that the AI Agent for Jira using NVIDIA NIM recipe package contains:



AI Agent for Jira using NVIDIA NIM recipe assets

The following table lists the assets that the AI Agent for Jira using NVIDIA NIM recipe package contains:

Asset Name	Asset Type	Description
Generic Connector	Service Connector	Generic connector for executing Application Integration requests.
GenericConnection	App Connection	Generic connection for executing Application Integration requests.
SlackAIAgentConnection	App Connection	Slack connection.
NVIDIANIMAIAgentConnection	App Connection	NVIDIA NIM connection.
JiraAIAgentConnection	App Connection	Jira connection.
Prompt NVIDIA NIM LLM	Process	Subprocess that calls the NVIDIA NIM LLM and returns the answer.
Query Jira	Process	Subprocess that executes queries in Jira.
AI Agent to API	Process	Subprocess that uses an AI Agent to iteratively generate and refine API payloads based on user input and previous responses. It handles queries, updates, lookups, and dependencies step by step, producing structured JSON requests and user-friendly outputs.
Jira AI Agent	Process	The process that receives a query from Slack, calls the Jira AI agent and returns the generated response to the Slack channel.

CHAPTER 2

Using the AI Agent for Jira using NVIDIA NIM recipe

To use the AI Agent for Jira using NVIDIA NIM recipe, you must perform the following steps manually:

1. Copy and access the recipe.
2. Publish the Generic Connector service connector.
3. Configure and publish the GenericConnection connection.
4. Configure and publish the Slack connection.
5. Configure and publish the NVIDIA NIM connection.
6. Configure and publish the Jira connection.
7. Configure and publish the processes.
8. Create webhook in Slack.

Step 1. Copy and access the recipe


Copy the pre-configured assets in the recipe to a separate project or folder.

1. Open the **AI Agent for Jira using NVIDIA NIM** recipe and click **Use**.
2. Select the location where you want to copy the recipe, and then click **Continue**.
3. In the **Copying the recipe** dialog box, click **OK**.

   It might take some time for the recipe to get copied. You will receive a notification when the recipe is ready for use.
4. After the recipe is copied, click **Explore** to access the recipe content.

5. Navigate to the project or folder where you copied the recipe or enter the recipe name in the **Find** box.

   All the assets in the recipe are displayed as shown in the following image:



Step 2. Publish the Generic Connector service connector

To publish the **Generic Connector** service connector, open the **Generic Connector** service connector and click **Publish**.

Step 3. Configure and publish the GenericConnection connection

Configure the user account credentials to authorize requests, and then publish the GenericConnection connection.

1. Open the **GenericConnection** connection.
2. From the **Type** list, select **Generic Connector** from the recipe assets folder.
3. From the **Runtime Environment** list, select **Cloud Server or any Secure Agent**.
4. In the **Connection Properties** section, enter values for the following properties:

Property	Description
Username	User name of the user account to authorize requests.
Password	Password for the user account to authorize requests.

5. Save and publish the connection.

Step 4. Configure and publish the Slack connection

Configure the base URL to access the Slack instance, and then publish the SlackAIAgentConnection connection.

1. Open the **SlackAIAgentConnection** connection.
2. From the **Type** list, select **Slack**.
3. From the **Runtime Environment** list, select **Cloud Server or any Secure Agent**.
4. From the **Authentication Type** list, select **OAuth2** and enter values for the following properties:

Property	Description
Grant Type	Required. Select the required grant type based on your use case.
Authorization URL	Required. Enter the OAuth authorization URL for the OAuth provider to authorize the user request. For example: `https://slack.com/oauth/v2/authorize`
Token Request URL	Required. Enter the OAuth token request URL that handles token requests. For example: `https://slack.com/api/oauth.v2.access` The expiration of the refresh token depends on the OAuth provider. You must re-authenticate and publish the connection before the token expires. **Note:** The refresh token doesn't apply to agents and agent groups.
Client ID	Required. Specify the identifier value from the OAuth provider.
Client Secret	Required. Enter the client secret to connect to the OAuth provider.
Scope	Required. Specify the scope. The scope in OAuth authentication limits an application's access to a user's account. You can select multiple scopes for a single client. To enter multiple scopes, separate each value with a space.
Session Duration	Optional. Enter the number of minutes to wait before refreshing the session. This is used if you cannot obtain the token expiration from the OAuth provider. Default is 60 minutes.
Other Parameters	Optional. Enter parameters to customize the authorization request, separated with semicolons. You can provide extra information or specify requirements of the OAuth provider.
Authorization Status	Optional. Indicates the current status, the name of the user who authorized, and the last time when the authorization was completed.
Authorize Access	Click to initiate the authorization workflow using OAuth.

5. In the **Connection Properties** section, enter the base URL in the **Base_URL** property. The base URL connects to the Slack API and sets the primary endpoint for all Slack requests.
6. Save and publish the connection.

Step 5. Configure and publish the NVIDIA NIM connection

Configure the API key to authenticate NVIDIA NIM API requests, and then publish the NVIDIANIMAIAgentConnection connection.

1. Open the **NVIDIANIMAIAgentConnection** connection.
2. From the **Type** list, select **NVIDIA NIM**.
3. From the **Runtime Environment** list, select **Cloud Server or any Secure Agent**.
4. In the **Connection Properties** section, enter the API key in the **Api_Key** property. The **Api_Key** property authenticates NVIDIA NIM API requests.
5. Save and publish the connection.

Step 6. Configure and publish the Jira connection

Configure the instance domain, user name, and authentication token to connect to the Jira instance, and then publish the JiraAIAgentConnection connection.

1. Open the **JiraAIAgentConnection** connection.
2. From the **Type** list, select **Jira**.
3. From the **Runtime Environment** list, select **Cloud Server or any Secure Agent**.
4. In the **Connection Properties** section, enter values for the following properties:

Property	Description
InstanceDomain	The URL to access the Jira instance. For example, `https://<<name>>.atlassian.net`
UserName	The user name of the Jira account.
AuthToken	The Jira API token that you generated from **Manage Account** > **Security** > **Create and manage API tokens**.

5. Save and publish the connection.

Step 7. Configure and publish the processes

Configure the API URL and LLM URL and publish the processes.

1. To publish the **AI Agent to API** process, click **Actions** in the row that contains the process and select **Publish**.
2. Open the **Query Jira** process.
3. On the **Start** tab of the Start step, in the **Allowed Users** or **Allowed Groups** field, enter the user or group that has access to the process service URL at run time.

4. Save and publish the process.
5. On the **Actions** menu, click **Properties Detail** and copy the service URL.
   You will need this API URL in the Jira AI Agent process.
6. Open the **Prompt NVIDIA NIM LLM** process.
7. On the **Start** tab of the Start step, in the **Allowed Users** or **Allowed Groups** field, enter the user or group that has access to the process service URL at run time.
8. Optionally, on the **Assignments** tab of the **Setting and Preparing Prompt** step, you can update the LLM configuration in the **LLM_Configuration** field.
9. Save and publish the process.
10. On the **Actions** menu, click **Properties Detail** and copy the service URL.
    You will need this LLM URL in the Jira AI Agent process.
11. Open the **Jira AI Agent** process.
12. On the **Start** tab of the Start step, select **Allow anonymous access**.
13. On the **Assignments** tab of the **AI Agent Configurations** step, enter the following values:
    - API URL from the Query Jira process in the **API_URL** field.
    - LLM URL from the Prompt NVIDIA NIM LLM process in the **LLM_URL** field.
    - Optionally, edit the system instructions in the **System_Instruction** field.
14. Save and publish the process.

Step 8. Create webhook in Slack

Configure a Slack app that calls an API when a new message arrives.


To create a webhook in Slack, perform the following steps:

1. "Create a Slack App" on page 12
2. "Enable the events API" on page 13
3. "Subscribe to the event" on page 14
4. "Set the required OAuth scopes" on page 15
5. "Enable token rotation" on page 16
6. "Add bot to a channel" on page 17

Create a Slack App

1. Go to `https://api.slack.com/apps` and log in to your account.
2. Click **Create New App** > **From scratch**.


3. Enter the app name and select your workspace, and then click **Create App** as shown in the following image:



Enable the events API

1. From the left navigation bar, go to **Event Subscriptions**.
2. Turn on the toggle switch to enable events.


3. In the **Request URL** field, enter the service URL that you get after publishing the process. Slack sends a `challenge` request to verify the URL as shown in the following image:



Subscribe to the event


1. In the **Subscribe to bot events** section, click **Add Bot User Event** and add one of the following events as required:
   - `message.channels` — to receive messages from public channels.
   - `message.groups` — for private channels.

   The event allows your app to receive messages from channels it belongs to as shown in the following image:



Set the required OAuth scopes

1. Go to **OAuth & Permissions**.
2. In the **Bot Token Scopes** section, click **Add an OAuth Scope** and add one of the following OAuth scopes:
   - `channels:history` — to read public channel messages.
   - `groups:history` — to read messages from private channels, if needed.
   - `chat:write` — if your bot needs to send messages.
3. In the **Redirect URLs** section, click **Add New Redirect URL** and add the redirect URLs in `<Cloud Application Integration POD URL>/oauthcallback` format and save the URLs. For example, `https://na1.dm-us.informaticacloud.com/oauthcallback` as shown in the following image:




4. Install the app using the **Install App** section.

Enable token rotation

1. Go to **OAuth & Permissions**.

2. In the **Advanced token security via token rotation** section, click **Opt In**.



Add bot to a channel

1. In Slack, go to the required channel.
2. Invite the bot using `/invite @<your-bot-name>`.