Informatica

Informatica® Cloud Application Integration
May 2025

# Simple RAG Consumption with Slack AI Agent

Informatica Cloud Application Integration Simple RAG Consumption with Slack AI Agent
May 2025

© Copyright Informatica LLC 2025

This software and documentation contain proprietary information of Informatica LLC and are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright law. Reverse engineering of the software is prohibited. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC. This Software may be protected by U.S. and/or international Patents and other Patents Pending.

Use, duplication, or disclosure of the Software by the U.S. Government is subject to the restrictions set forth in the applicable software license agreement and as provided in DFARS 227.7202-1(a) and 227.7702-3(a) (1995), DFARS 252.227-7013©(1)(ii) (OCT 1988), FAR 12.212(a) (1995), FAR 52.227-19, or FAR 52.227-14 (ALT III), as applicable.

The information in this product or documentation is subject to change without notice. If you find any problems in this product or documentation, please report them to us in writing.

Informatica, Informatica Platform, Informatica Data Services, PowerCenter, PowerCenterRT, PowerCenter Connect, PowerCenter Data Analyzer, PowerExchange, PowerMart, Metadata Manager, Informatica Data Quality, Informatica Data Explorer, Informatica B2B Data Transformation, Informatica B2B Data Exchange Informatica On Demand, Informatica Identity Resolution, Informatica Application Information Lifecycle Management, Informatica Complex Event Processing, Ultra Messaging, Informatica Master Data Management, and Live Data Map are trademarks or registered trademarks of Informatica LLC in the United States and in jurisdictions throughout the world. All other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties, including without limitation: Copyright DataDirect Technologies. All rights reserved. Copyright © Sun Microsystems. All rights reserved. Copyright © RSA Security Inc. All Rights Reserved. Copyright © Ordinal Technology Corp. All rights reserved. Copyright © Aandacht c.v. All rights reserved. Copyright Genivia, Inc. All rights reserved. Copyright Isomorphic Software. All rights reserved. Copyright © Meta Integration Technology, Inc. All rights reserved. Copyright © Intalio. All rights reserved. Copyright © Oracle. All rights reserved. Copyright © Adobe Systems Incorporated. All rights reserved. Copyright © DataArt, Inc. All rights reserved. Copyright © ComponentSource. All rights reserved. Copyright © Microsoft Corporation. All rights reserved. Copyright © Rogue Wave Software, Inc. All rights reserved. Copyright © Teradata Corporation. All rights reserved. Copyright © Yahoo! Inc. All rights reserved. Copyright © Glyph & Cog, LLC. All rights reserved. Copyright © Thinkmap, Inc. All rights reserved. Copyright © Clearpace Software Limited. All rights reserved. Copyright © Information Builders, Inc. All rights reserved. Copyright © OSS Nokalva, Inc. All rights reserved. Copyright Edifecs, Inc. All rights reserved. Copyright Cleo Communications, Inc. All rights reserved. Copyright © International Organization for Standardization 1986. All rights reserved. Copyright © ej-technologies GmbH. All rights reserved. Copyright © Jaspersoft Corporation. All rights reserved. Copyright © International Business Machines Corporation. All rights reserved. Copyright © yWorks GmbH. All rights reserved. Copyright © Lucent Technologies. All rights reserved. Copyright © University of Toronto. All rights reserved. Copyright © Daniel Veillard. All rights reserved. Copyright © Unicode, Inc. Copyright IBM Corp. All rights reserved. Copyright © MicroQuill Software Publishing, Inc. All rights reserved. Copyright © PassMark Software Pty Ltd. All rights reserved. Copyright © LogiXML, Inc. All rights reserved. Copyright © 2003-2010 Lorenzi Davide, All rights reserved. Copyright © Red Hat, Inc. All rights reserved. Copyright © The Board of Trustees of the Leland Stanford Junior University. All rights reserved. Copyright © EMC Corporation. All rights reserved. Copyright © Flexera Software. All rights reserved. Copyright © Jinfonet Software. All rights reserved. Copyright © Apple Inc. All rights reserved. Copyright © Telerik Inc. All rights reserved. Copyright © BEA Systems. All rights reserved. Copyright © PDFlib GmbH. All rights reserved. Copyright © Orientation in Objects GmbH. All rights reserved. Copyright © Tanuki Software, Ltd. All rights reserved. Copyright © Ricebridge. All rights reserved. Copyright © Sencha, Inc. All rights reserved. Copyright © Scalable Systems, Inc. All rights reserved. Copyright © jQWidgets. All rights reserved. Copyright © Tableau Software, Inc. All rights reserved. Copyright© MaxMind, Inc. All Rights Reserved. Copyright © TMate Software s.r.o. All rights reserved. Copyright © MapR Technologies Inc. All rights reserved. Copyright © Amazon Corporate LLC. All rights reserved. Copyright © Highsoft. All rights reserved. Copyright © Python Software Foundation. All rights reserved. Copyright © BeOpen.com. All rights reserved. Copyright © CNRI. All rights reserved.

This product includes software developed by the Apache Software Foundation (http://www.apache.org/), and/or other software which is licensed under various versions of the Apache License (the "License"). You may obtain a copy of these Licenses at http://www.apache.org/licenses/. Unless required by applicable law or agreed to in writing, software distributed under these Licenses is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the Licenses for the specific language governing permissions and limitations under the Licenses.

This product includes software which was developed by Mozilla (http://www.mozilla.org/), software copyright The JBoss Group, LLC, all rights reserved; software copyright © 1999-2006 by Bruno Lowagie and Paulo Soares and other software which is licensed under various versions of the GNU Lesser General Public License Agreement, which may be found at http:// www.gnu.org/licenses/lgpl.html. The materials are provided free of charge by Informatica, "as-is", without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

The product includes ACE(TM) and TAO(TM) software copyrighted by Douglas C. Schmidt and his research group at Washington University, University of California, Irvine, and Vanderbilt University, Copyright (©) 1993-2006, all rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (copyright The OpenSSL Project. All Rights Reserved) and redistribution of this software is subject to terms available at http://www.openssl.org and http://www.openssl.org/source/license.html.

This product includes Curl software which is Copyright 1996-2013, Daniel Stenberg, <daniel@haxx.se>. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://curl.haxx.se/docs/copyright.html. Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

The product includes software copyright 2001-2005 (©) MetaStuff, Ltd. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://www.dom4j.org/ license.html.

The product includes software copyright © 2004-2007, The Dojo Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://dojotoolkit.org/license.

This product includes ICU software which is copyright International Business Machines Corporation and others. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://source.icu-project.org/repos/icu/icu/trunk/license.html.

This product includes software copyright © 1996-2006 Per Bothner. All rights reserved. Your right to use such materials is set forth in the license which may be found at http:// www.gnu.org/software/ kawa/Software-License.html.

This product includes OSSP UUID software which is Copyright © 2002 Ralf S. Engelschall, Copyright © 2002 The OSSP Project Copyright © 2002 Cable & Wireless Deutschland. Permissions and limitations regarding this software are subject to terms available at http://www.opensource.org/licenses/mit-license.php.

This product includes software developed by Boost (http://www.boost.org/) or under the Boost software license. Permissions and limitations regarding this software are subject to terms available at http:/ /www.boost.org/LICENSE_1_0.txt.

This product includes software copyright © 1997-2007 University of Cambridge. Permissions and limitations regarding this software are subject to terms available at http:// www.pcre.org/license.txt.

This product includes software copyright © 2007 The Eclipse Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http:// www.eclipse.org/org/documents/epl-v10.php and at http://www.eclipse.org/org/documents/edl-v10.php.

This product includes software licensed under the terms at http://www.tcl.tk/software/tcltk/license.html, http://www.bosrup.com/web/overlib/?License, http://www.stlport.org/doc/ license.html, http://asm.ow2.org/license.html, http://www.cryptix.org/LICENSE.TXT, http://hsqldb.org/web/hsqlLicense.html, http://httpunit.sourceforge.net/doc/ license.html, http://jung.sourceforge.net/license.txt , http://www.gzip.org/zlib/zlib_license.html, http://www.openldap.org/software/release/license.html, http://www.libssh2.org, http://slf4j.org/license.html, http://www.sente.ch/software/OpenSourceLicense.html, http://fusesource.com/downloads/license-agreements/fuse-message-broker-v-5-3- license-agreement; http://antlr.org/license.html; http://aopalliance.sourceforge.net/; http://www.bouncycastle.org/licence.html; http://www.jgraph.com/jgraphdownload.html; http://www.jcraft.com/jsch/LICENSE.txt; http://jotm.objectweb.org/bsd_license.html; . http://www.w3.org/Consortium/Legal/2002/copyright-software-20021231; http://www.slf4j.org/license.html; http://nanoxml.sourceforge.net/orig/copyright.html; http://www.json.org/license.html; http://forge.ow2.org/projects/javaservice/, http://www.postgresql.org/about/licence.html, http://www.sqlite.org/copyright.html, http://www.tcl.tk/software/tcltk/license.html, http://www.jaxen.org/faq.html, http://www.jdom.org/docs/faq.html, http://www.slf4j.org/license.html; http://www.iodbc.org/dataspace/iodbc/wiki/iODBC/License; http://www.keplerproject.org/md5/license.html; http://www.toedter.com/en/jcalendar/license.html; http://www.edankert.com/bounce/index.html; http://www.net-snmp.org/about/license.html; http://www.openmdx.org/#FAQ; http://www.php.net/license/3_01.txt; http://srp.stanford.edu/license.txt; http://www.schneier.com/blowfish.html; http://www.jmock.org/license.html; http://xsom.java.net; http://benalman.com/about/license/; https://github.com/CreateJS/EaselJS/blob/master/src/easeljs/display/Bitmap.js; http://www.h2database.com/html/license.html#summary; http://jsoncpp.sourceforge.net/LICENSE; http://jdbc.postgresql.org/license.html; http://protobuf.googlecode.com/svn/trunk/src/google/protobuf/descriptor.proto; https://github.com/rantav/hector/blob/master/LICENSE; http://web.mit.edu/Kerberos/krb5-current/doc/mitK5license.html; http://jibx.sourceforge.net/jibx-license.html; https://github.com/lyokato/libgeohash/blob/master/LICENSE; https://github.com/hjiang/jsonxx/blob/master/LICENSE; https://code.google.com/p/lz4/; https://github.com/jedisct1/libsodium/blob/master/LICENSE; http://one-jar.sourceforge.net/index.php?page=documents&file=license; https://github.com/EsotericSoftware/kryo/blob/master/license.txt; http://www.scala-lang.org/license.html; https://github.com/tinkerpop/blueprints/blob/master/LICENSE.txt; http://gee.cs.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html; https://aws.amazon.com/asl/; https://github.com/twbs/bootstrap/blob/master/LICENSE; https://sourceforge.net/p/xmlunit/code/HEAD/tree/trunk/LICENSE.txt; https://github.com/documentcloud/underscore-contrib/blob/master/LICENSE, and https://github.com/apache/hbase/blob/master/LICENSE.txt.

This product includes software licensed under the Academic Free License (http://www.opensource.org/licenses/afl-3.0.php), the Common Development and Distribution License (http://www.opensource.org/licenses/cddl1.php) the Common Public License (http://www.opensource.org/licenses/cpl1.0.php), the Sun Binary Code License Agreement Supplemental License Terms, the BSD License (http:// www.opensource.org/licenses/bsd-license.php), the new BSD License (http://opensource.org/licenses/BSD-3-Clause), the MIT License (http://www.opensource.org/licenses/mit-license.php), the Artistic License (http://www.opensource.org/licenses/artistic-license-1.0) and the Initial Developer's Public License Version 1.0 (http://www.firebirdsql.org/en/initial-developer-s-public-license-version-1-0/).

This product includes software copyright © 2003-2006 Joe Walnes, 2006-2007 XStream Committers. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://xstream.codehaus.org/license.html. This product includes software developed by the Indiana University Extreme! Lab. For further information please visit http://www.extreme.indiana.edu/.

This product includes software Copyright (c) 2013 Frank Balluffi and Markus Moeller. All rights reserved. Permissions and limitations regarding this software are subject to terms of the MIT license.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

Publication Date: 2025-08-31

# Table of Contents

**Preface** . . . . . 5

**Chapter 1: Introduction to Simple RAG Consumption with Slack AI Agent recipe** . . . . . 6

Prerequisites for creating an index in Pinecone . . . . . 6

**Chapter 2: Simple RAG Consumption with Slack AI Agent recipe contents** . . . . . 9

Simple RAG Consumption with Slack AI Agent recipe assets . . . . . 10

**Chapter 3: Using the Simple RAG Consumption with Slack AI Agent recipe** . . . 11

Step 1. Copy and access the recipe . . . . . 11

Step 2. Configure and publish the Gemini connection . . . . . 12

Step 3. Configure and publish the Pinecone connection . . . . . 12

Step 4. Configure and publish the Slack connection . . . . . 13

Step 5. Configure and publish the processes . . . . . 14

Step 6. Create webhook in Slack . . . . . 14

# Preface

Use *Simple RAG Consumption with Slack AI Agent* to learn how to receive a user query from Slack, search for relevant context in a vector database, send the query and context to a Large Language Model (LLM), and return the generated response back to the Slack channel. This guide assumes that you have an understanding of the Gemini Connector, Pinecone Connector, and Slack Connector concepts.

CHAPTER 1

# Introduction to Simple RAG Consumption with Slack AI Agent recipe

The Simple Retrieval Augmented Generation (RAG) Consumption with Slack AI Agent recipe is based on REST and SOAP APIs.

The process begins by receiving user input from Slack and skipping messages if they are bot responses. It then converts the query into a vector representation using a pre-trained embedding model, translating the text into a numerical format that captures the semantic meaning.

The process then uses a vectorized query to search for similar vectors within a vector database that contains representations of various contexts. The process retrieves the top K closest matches from the vector database based on similarity scores, representing contexts similar to the user's query.

The process then filters the retrieved contexts to include only those with a similarity score exceeding a specified cutoff parameter, ensuring that only relevant contexts are considered. The process combines these filtered contexts to formulate the final context, which provides additional information to the model.


Subsequently, the process invokes a Large Language Model (LLM) using the original user query and the processed context. The LLM leverages this information to generate a comprehensive response. This response is returned to the user in the same channel, appearing as a bot (app) response.

This approach ensures the LLM's response is relevant and enriched by the most contextually appropriate information from the vector database.

## Prerequisites for creating an index in Pinecone


To ensure that the process works correctly, you must create an index in Pinecone and add text for the context. The context is then converted into vectors using the Get Embeddings process.

1. Open the **Create a new index** page in Pinecone.
2. In the **Default** field, enter an index name and in the **Dimensions** field, enter the value **768** as shown in the following image:




3. Click **Create index**.

After creating the index, you can use the **HOST** value without `https://` in the **Index_Host** input parameter as shown in the following image:



Back to indexes
somenameindex
METRIC
cosine
DIMENSIONS
768
HOST
https://somenameindex-38s14f2.svc.aped-4627-b74a.pinecone.io
CLOUD
AWS
REGION
us-east-1
TYPE
Serverless
BROWSER
METRICS
NAMESPACES (0)
Index records
No Records Yet
A record is an object you add to an index containing a vector and, optionally, its metadata
Add a Record

CHAPTER 2

# Simple RAG Consumption with Slack AI Agent recipe contents

The Simple RAG Consumption with Slack AI Agent recipe contains a process object, app connections, and processes.

The following image shows the assets that the Simple RAG Consumption with Slack AI Agent recipe package contains:



# Simple RAG Consumption with Slack AI Agent recipe assets

The following table lists the assets that the Simple RAG Consumption with Slack AI Agent recipe package contains:

| Asset Name | Asset Type | Description |
|---|---|---|
| VectorMatchEntry | Process Object | Provides all the information from the Pinecone vector matching. |
| GeminiAIAgentConsumptionConnection | App Connection | Gemini connection. |
| PineconeAIAgentConnection | App Connection | Pinecone connection. |
| SlackAIAgentConnection | App Connection | Slack connection. |
| Generate Embeddings Model | Process | Subprocess that parses the user input into a vector view and matches it with the embedded model. It returns the matching context score and metadata. |
| Get Embeddings | Process | Subprocess that generates embedding vectors from the user input using Gemini. |
| Query LLM with Context using Embeddings Model | Process | Subprocess that submits a query that is received from the user, converts it into a vector, and uses it to search for similar vectors in a database. The top K matches are retrieved, filtered by a cutoff score, and used to form a context. This context including the original query is passed to a Large Language Model (LLM) to generate and return a comprehensive response. |
| Query LLM with Context using Gemini | Process | Subprocess that prepares and sends a request to the Gemini LLM with the context. |
| Query Pinecone | Process | Subprocess that searches for coincidences from input vectors to vectors in the base Pinecone index specified as input parameter Index_Host_Pinecone and returns a result with metadata. |
| Slack AI Agent | Process | Process that receives a query from Slack, searches for relevant context in a vector database, sends both the query and the context to an LLM, and returns the generated response to the Slack channel. |

CHAPTER 3

# Using the Simple RAG Consumption with Slack AI Agent recipe

To use the Simple RAG Consumption with Slack AI Agent recipe, you must perform the following steps manually:

1. Copy and access the recipe.
2. Configure and publish the Gemini connection.
3. Configure and publish the Pinecone connection.
4. Configure and publish Slack connection.
5. Configure and publish the processes.
6. Create webhook in Slack.

## Step 1. Copy and access the recipe


Copy the pre-configured assets in the recipe to a separate project or folder.

1. Open the **Simple RAG Consumption with Slack AI Agent** recipe and click **Use**.
2. Select the location where you want to copy the recipe, and then click **Continue**.
3. In the **Copying the recipe** dialog box, click **OK**.

   It might take some time for the recipe to get copied. You will receive a notification when the recipe is ready for use.
4. After the recipe is copied, click **Explore** to access the recipe content.

5. Navigate to the project or folder where you copied the recipe or enter the recipe name in the **Find** box.

   All the assets in the recipe are displayed as shown in the following image:




# Step 2. Configure and publish the Gemini connection

Configure the API key to authenticate the Gemini connection, and then publish the GeminiAIAgentConsumptionConnection connection.

1. Open the **GeminiAIAgentConsumptionConnection** connection.
2. From the **Type** list, select **Gemini**.
3. From the **Runtime Environment** list, select **Cloud Server or any Secure Agent**.
4. In the **Connection Properties** section, enter the API key in the **API_Key** property. The **API_Key** property authenticates Gemini connection requests.
5. Save and publish the connection.

# Step 3. Configure and publish the Pinecone connection

Configure the API key to authenticate the Pinecone connection, and then publish the PineconeAIAgentConnection connection.

1. Open the **PineconeAIAgentConnection** connection.
2. From the **Type** list, select **Pinecone**.
3. From the **Runtime Environment** list, select **Cloud Server or any Secure Agent**.
4. In the **Connection Properties** section, enter the API key in the **API_Key** property. The **API_Key** property authenticates Pinecone connection requests.
5. Save and publish the connection.

# Step 4. Configure and publish the Slack connection

Configure the base URL to access the Slack instance, and then publish the SlackAIAgentConnection connection.

1. Open the **SlackAIAgentConnection** connection.
2. From the **Type** list, select **Slack**.
3. From the **Runtime Environment** list, select **Cloud Server or any Secure Agent**.
4. From the **Authentication Type** list, select **OAuth2** and enter values for the following properties:

| Property | Description |
|---|---|
| Grant Type | Required. Select the required grant type based on your use case. |
| Authorization URL | Required. Enter the OAuth authorization URL for the OAuth provider to authorize the user request.<br>For example: `https://slack.com/oauth/v2/authorize` |
| Token Request URL | Required. Enter the OAuth token request URL that handles token requests.<br>For example: `https://slack.com/api/oauth.v2.access`<br>The expiration of the refresh token depends on the OAuth provider. You must re-authenticate and publish the connection before the token expires.<br>**Note:** The refresh token doesn't apply to agents and agent groups. |
| Client ID | Required. Specify the identifier value from the OAuth provider. |
| Client Secret | Required. Enter the client secret to connect to the OAuth provider. |
| Scope | Required. Specify the scope. The scope in OAuth authentication limits an application's access to a user's account. You can select multiple scopes for a single client. To enter multiple scopes, separate each value with a space. |
| Session Duration | Optional. Enter the number of minutes to wait before refreshing the session. This is used if you cannot obtain the token expiration from the OAuth provider. Default is 60 minutes. |
| Other Parameters | Optional. Enter parameters to customize the authorization request, separated with semicolons. You can provide extra information or specify requirements of the OAuth provider. |
| Authorization Status | Optional. Indicates the current status, the name of the user who authorized, and the last time when the authorization was completed. |
| Authorize Access | Click to initiate the authorization workflow using OAuth. |

5. In the **Connection Properties** section, enter the base URL in the **Base_URL** property. The base URL connects to the Slack API and sets the primary endpoint for all Slack requests.
6. Save and publish the connection.

# Step 5. Configure and publish the processes

Configure the LLM model and authorization for access, and then publish the processes.

1. To publish the following processes, click **Actions** in the row that contains the process and select **Publish**.
   - Generate Embeddings Model
   - Get Embeddings
   - Query LLM with Context using Gemini
   - Query Pinecone
2. Open the **Query LLM with Context using Embeddings Model** process.
3. On the **Assignments** tab of the **Set LLM Models** step, you can optionally update the LLM model values in the **Set_Content_Model** and **Set_Embedding_Model** fields.
4. Save and publish the process.
5. Open the **Slack AI Agent** process.
6. On the **Start** tab of the Start step, select **Allow anonymous access**.
7. Save and publish the process.
8. On the **Actions** menu, click **Properties Detail** and copy the service URL.
   You will need the service URL to configure the webhook in Slack. For more information, see "Step 6. Create webhook in Slack" on page 14.

# Step 6. Create webhook in Slack

Configure a Slack app that calls an API when a new message arrives.


To create a webhook in Slack, perform the following steps:

1. "Create a Slack App" on page 14
2. "Enable the events API" on page 15
3. "Subscribe to the event" on page 16
4. "Set the required OAuth scopes" on page 17
5. "Enable token rotation" on page 18
6. "Add bot to a channel" on page 19

## Create a Slack App

1. Go to `https://api.slack.com/apps` and log in to your account.
2. Click **Create New App** > **From scratch**.


3. Enter the app name and select your workspace, and then click **Create App** as shown in the following image:




## Enable the events API

1. From the navigation bar, go to **Event Subscriptions**.
2. Turn on the toggle switch to enable events.


3. In the **Request URL** field, enter the service URL that you get after publishing the process. Slack sends a `challenge` request to verify the URL as shown in the following image:




## Subscribe to the event


1. In the **Subscribe to bot events** section, click **Add Bot User Event** and add one of the following events as required:
   - `message.channels` — to receive messages from public channels.
   - `message.groups` — for private channels.

   The event allows your app to receive messages from channels it belongs to as shown in the following image:




## Set the required OAuth scopes

1. Go to **OAuth & Permissions**.
2. In the **Bot Token Scopes** section, click **Add an OAuth Scope** and add one of the following OAuth scopes:
   - `channels:history` — to read public channel messages.
   - `groups:history` — to read messages from private channels, if needed.
   - `chat:write` — if your bot needs to send messages.
3. In the **Redirect URLs** section, click **Add New Redirect URL** and add the redirect URLs in `<Cloud Application Integration POD URL>/oauthcallback` format and save the URLs. For example, `https://na1.dm-us.informaticacloud.com/oauthcallback` as shown in the following image:





4. Install the app using the **Install App** section.

## Enable token rotation

1. Go to **OAuth & Permissions**.

2. In the **Advanced token security via token rotation** section, click **Opt In**.




## Add bot to a channel

1. In Slack, go to the required channel.
2. Invite the bot using `/invite @<your-bot-name>`.