Informatica

Informatica® PowerExchange for Salesforce Analytics

10.5.10

User Guide for PowerCenter

Informatica PowerExchange for Salesforce Analytics User Guide for PowerCenter
10.5.10
February 2026

© Copyright Informatica LLC 2006, 2025

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

Informatica, the Informatica logo, PowerCenter, and PowerExchange are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties, including without limitation: Copyright DataDirect Technologies. All rights reserved. Copyright © Sun Microsystems. All rights reserved. Copyright © RSA Security Inc. All Rights Reserved. Copyright © Ordinal Technology Corp. All rights reserved. Copyright © Aandacht c.v. All rights reserved. Copyright Genivia, Inc. All rights reserved. Copyright Isomorphic Software. All rights reserved. Copyright © Meta Integration Technology, Inc. All rights reserved. Copyright © Intalio. All rights reserved. Copyright © Oracle. All rights reserved. Copyright © Adobe Systems Incorporated. All rights reserved. Copyright © DataArt, Inc. All rights reserved. Copyright © ComponentSource. All rights reserved. Copyright © Microsoft Corporation. All rights reserved. Copyright © Rogue Wave Software, Inc. All rights reserved. Copyright © Teradata Corporation. All rights reserved. Copyright © Yahoo! Inc. All rights reserved. Copyright © Glyph & Cog, LLC. All rights reserved. Copyright © Thinkmap, Inc. All rights reserved. Copyright © Clearpace Software Limited. All rights reserved. Copyright © Information Builders, Inc. All rights reserved. Copyright © OSS Nokalva, Inc. All rights reserved. Copyright Edifecs, Inc. All rights reserved. Copyright Cleo Communications, Inc. All rights reserved. Copyright © International Organization for Standardization 1986. All rights reserved. Copyright © ej-technologies GmbH. All rights reserved. Copyright © Jaspersoft Corporation. All rights reserved. Copyright © International Business Machines Corporation. All rights reserved. Copyright © yWorks GmbH. All rights reserved. Copyright © Lucent Technologies. All rights reserved. Copyright © University of Toronto. All rights reserved. Copyright © Daniel Veillard. All rights reserved. Copyright © Unicode, Inc. Copyright IBM Corp. All rights reserved. Copyright © MicroQuill Software Publishing, Inc. All rights reserved. Copyright © PassMark Software Pty Ltd. All rights reserved. Copyright © LogiXML, Inc. All rights reserved. Copyright © 2003-2010 Lorenzi Davide, All rights reserved. Copyright © Red Hat, Inc. All rights reserved. Copyright © The Board of Trustees of the Leland Stanford Junior University. All rights reserved. Copyright © EMC Corporation. All rights reserved. Copyright © Flexera Software. All rights reserved. Copyright © Jinfonet Software. All rights reserved. Copyright © Apple Inc. All rights reserved. Copyright © Telerik Inc. All rights reserved. Copyright © BEA Systems. All rights reserved. Copyright © PDFlib GmbH. All rights reserved. Copyright © Orientation in Objects GmbH. All rights reserved. Copyright © Tanuki Software, Ltd. All rights reserved. Copyright © Ricebridge. All rights reserved. Copyright © Sencha, Inc. All rights reserved. Copyright © Scalable Systems, Inc. All rights reserved. Copyright © jQWidgets. All rights reserved. Copyright © Tableau Software, Inc. All rights reserved. Copyright© MaxMind, Inc. All Rights Reserved. Copyright © TMate Software s.r.o. All rights reserved. Copyright © MapR Technologies Inc. All rights reserved. Copyright © Amazon Corporate LLC. All rights reserved. Copyright © Highsoft. All rights reserved. Copyright © Python Software Foundation. All rights reserved. Copyright © BeOpen.com. All rights reserved. Copyright © CNRI. All rights reserved.

This product includes software developed by the Apache Software Foundation (http://www.apache.org/), and/or other software which is licensed under various versions of the Apache License (the "License"). You may obtain a copy of these Licenses at http://www.apache.org/licenses/. Unless required by applicable law or agreed to in writing, software distributed under these Licenses is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the Licenses for the specific language governing permissions and limitations under the Licenses.

This product includes software which was developed by Mozilla (http://www.mozilla.org/), software copyright The JBoss Group, LLC, all rights reserved; software copyright © 1999-2006 by Bruno Lowagie and Paulo Soares and other software which is licensed under various versions of the GNU Lesser General Public License Agreement, which may be found at http:// www.gnu.org/licenses/lgpl.html. The materials are provided free of charge by Informatica, "as-is", without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

The product includes ACE(TM) and TAO(TM) software copyrighted by Douglas C. Schmidt and his research group at Washington University, University of California, Irvine, and Vanderbilt University, Copyright (©) 1993-2006, all rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (copyright The OpenSSL Project. All Rights Reserved) and redistribution of this software is subject to terms available at http://www.openssl.org and http://www.openssl.org/source/license.html.

This product includes Curl software which is Copyright 1996-2013, Daniel Stenberg, <daniel@haxx.se>. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://curl.haxx.se/docs/copyright.html. Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

The product includes software copyright 2001-2005 (©) MetaStuff, Ltd. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://www.dom4j.org/ license.html.

The product includes software copyright © 2004-2007, The Dojo Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://dojotoolkit.org/license.

This product includes ICU software which is copyright International Business Machines Corporation and others. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://source.icu-project.org/repos/icu/icu/trunk/license.html.

This product includes software copyright © 1996-2006 Per Bothner. All rights reserved. Your right to use such materials is set forth in the license which may be found at http:// www.gnu.org/software/ kawa/Software-License.html.

This product includes OSSP UUID software which is Copyright © 2002 Ralf S. Engelschall, Copyright © 2002 The OSSP Project Copyright © 2002 Cable & Wireless Deutschland. Permissions and limitations regarding this software are subject to terms available at http://www.opensource.org/licenses/mit-license.php.

This product includes software developed by Boost (http://www.boost.org/) or under the Boost software license. Permissions and limitations regarding this software are subject to terms available at http:/ /www.boost.org/LICENSE_1_0.txt.

This product includes software copyright © 1997-2007 University of Cambridge. Permissions and limitations regarding this software are subject to terms available at http:// www.pcre.org/license.txt.

This product includes software copyright © 2007 The Eclipse Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http:// www.eclipse.org/org/documents/epl-v10.php and at http://www.eclipse.org/org/documents/edl-v10.php.

This product includes software licensed under the terms at http://www.tcl.tk/software/tcltk/license.html, http://www.bosrup.com/web/overlib/?License, http:// www.stlport.org/doc/ license.html, http://asm.ow2.org/license.html, http://www.cryptix.org/LICENSE.TXT, http://hsqldb.org/web/hsqlLicense.html, http:// httpunit.sourceforge.net/doc/ license.html, http://jung.sourceforge.net/license.txt , http://www.gzip.org/zlib/zlib_license.html, http://www.openldap.org/software/ release/license.html, http://www.libssh2.org, http://slf4j.org/license.html, http://www.sente.ch/software/OpenSourceLicense.html, http://fusesource.com/downloads/ license-agreements/fuse-message-broker-v-5-3- license-agreement; http://antlr.org/license.html; http://aopalliance.sourceforge.net/; http://www.bouncycastle.org/ licence.html; http://www.jgraph.com/jgraphdownload.html; http://www.jcraft.com/jsch/LICENSE.txt; http://jotm.objectweb.org/bsd_license.html; . http://www.w3.org/ Consortium/Legal/2002/copyright-software-20021231; http://www.slf4j.org/license.html; http://nanoxml.sourceforge.net/orig/copyright.html; http://www.json.org/ license.html; http://forge.ow2.org/projects/javaservice/, http://www.postgresql.org/about/licence.html, http://www.sqlite.org/copyright.html, http://www.tcl.tk/ software/tcltk/license.html, http://www.jaxen.org/faq.html, http://www.jdom.org/docs/faq.html, http://www.slf4j.org/license.html; http://www.iodbc.org/dataspace/ iodbc/wiki/iODBC/License; http://www.keplerproject.org/md5/license.html; http://www.toedter.com/en/jcalendar/license.html; http://www.edankert.com/bounce/ index.html; http://www.net-snmp.org/about/license.html; http://www.openmdx.org/#FAQ; http://www.php.net/license/3_01.txt; http://srp.stanford.edu/license.txt;

http://www.schneier.com/blowfish.html; http://www.jmock.org/license.html; http://xsom.java.net; http://benalman.com/about/license/; https://github.com/CreateJS/EaselJS/blob/master/src/easeljs/display/Bitmap.js; http://www.h2database.com/html/license.html#summary; http://jsoncpp.sourceforge.net/LICENSE; http://jdbc.postgresql.org/license.html; http://protobuf.googlecode.com/svn/trunk/src/google/protobuf/descriptor.proto; https://github.com/rantav/hector/blob/master/LICENSE; http://web.mit.edu/Kerberos/krb5-current/doc/mitK5license.html; http://jibx.sourceforge.net/jibx-license.html; https://github.com/lyokato/libgeohash/blob/master/LICENSE; https://github.com/hjiang/jsonxx/blob/master/LICENSE; https://code.google.com/p/lz4/; https://github.com/jedisct1/libsodium/blob/master/LICENSE; http://one-jar.sourceforge.net/index.php?page=documents&file=license; https://github.com/EsotericSoftware/kryo/blob/master/license.txt; http://www.scala-lang.org/license.html; https://github.com/tinkerpop/blueprints/blob/master/LICENSE.txt; http://gee.cs.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html; https://aws.amazon.com/asl/; https://github.com/twbs/bootstrap/blob/master/LICENSE; https://sourceforge.net/p/xmlunit/code/HEAD/tree/trunk/LICENSE.txt; https://github.com/documentcloud/underscore-contrib/blob/master/LICENSE, and https://github.com/apache/hbase/blob/master/LICENSE.txt.

This product includes software licensed under the Academic Free License (http://www.opensource.org/licenses/afl-3.0.php), the Common Development and Distribution License (http://www.opensource.org/licenses/cddl1.php) the Common Public License (http://www.opensource.org/licenses/cpl1.0.php), the Sun Binary Code License Agreement Supplemental License Terms, the BSD License (http:// www.opensource.org/licenses/bsd-license.php), the new BSD License (http://opensource.org/licenses/BSD-3-Clause), the MIT License (http://www.opensource.org/licenses/mit-license.php), the Artistic License (http://www.opensource.org/licenses/artistic-license-1.0) and the Initial Developer's Public License Version 1.0 (http://www.firebirdsql.org/en/initial-developer-s-public-license-version-1-0/).

This product includes software copyright © 2003-2006 Joe Walnes, 2006-2007 XStream Committers. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://xstream.codehaus.org/license.html. This product includes software developed by the Indiana University Extreme! Lab. For further information please visit http://www.extreme.indiana.edu/.

This product includes software Copyright (c) 2013 Frank Balluffi and Markus Moeller. All rights reserved. Permissions and limitations regarding this software are subject to terms of the MIT license.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-02-19

Table of Contents

Preface 6

Informatica Resources 6

- Informatica Network 6
- Informatica Knowledge Base 6
- Informatica Documentation 6
- Informatica Product Availability Matrices 7
- Informatica Velocity 7
- Informatica Marketplace 7
- Informatica Global Customer Support 7

Chapter 1: Introduction to PowerExchange for Salesforce Analytics 8

PowerExchange for Salesforce Analytics Overview 8

Introduction to Salesforce Analytics 8

Chapter 2: Configuration 9

Prerequisites 9

Plug-in Registration 9

Java Heap Size Configuration 10

Chapter 3: Salesforce Analytics Targets 11

Salesforce Analytics Targets Overview 11

Generating a JSON File 11

Manually Creating a JSON File 12

Importing a Salesforce Analytics Target Definition 12

Chapter 4: Salesforce Analytics Mappings 14

Salesforce Analytics Mappings Overview 15

Salesforce Analytics Mapping Example 15

Chapter 5: Salesforce Analytics Sessions 17

Salesforce Analytics Sessions Overview 17

Salesforce Analytics Connections 17

- Configuring a Salesforce Analytics Connection 17

Session Configuration for Salesforce Analytics Targets 18

- Success and Error Logs 19

Appendix A: Data Type Reference 20

Data Type Reference Overview 20

Salesforce Analytics and Transformation Data Types 20

Index **22**

Preface

Use the *Informatica® PowerExchange ® for Salesforce Analytics User Guide* to learn how to read from or write to Salesforce Analytics by using PowerCenter Client. Learn to create a Salesforce Analytics connection, develop mappings, and run sessions in an Informatica domain.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Network

The Informatica Network is the gateway to many resources, including the Informatica Knowledge Base and Informatica Global Customer Support. To enter the Informatica Network, visit https://network.informatica.com.

As an Informatica Network member, you have the following options:

- Search the Knowledge Base for product resources.
- View product availability information.
- Create and review your support cases.
- Find your local Informatica User Group Network and collaborate with your peers.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Product Availability Matrices

Product Availability Matrices (PAMs) indicate the versions of the operating systems, databases, and types of data sources and targets that a product release supports. You can browse the Informatica PAMs at https://network.informatica.com/community/informatica-network/product-availability-matrices.

Informatica Velocity

Informatica Velocity is a collection of tips and best practices developed by Informatica Professional Services and based on real-world experiences from hundreds of data management projects. Informatica Velocity represents the collective knowledge of Informatica consultants who work with organizations around the world to plan, develop, deploy, and maintain successful data management solutions.

You can find Informatica Velocity resources at http://velocity.informatica.com. If you have questions, comments, or ideas about Informatica Velocity, contact Informatica Professional Services at ips@informatica.com.

Informatica Marketplace

The Informatica Marketplace is a forum where you can find solutions that extend and enhance your Informatica implementations. Leverage any of the hundreds of solutions from Informatica developers and partners on the Marketplace to improve your productivity and speed up time to implementation on your projects. You can find the Informatica Marketplace at https://marketplace.informatica.com.

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:
https://www.informatica.com/services-and-training/customer-success-services/contact-us.html.

To find online support resources on the Informatica Network, visit https://network.informatica.com and select the eSupport option.

CHAPTER 1

Introduction to PowerExchange for Salesforce Analytics

This chapter includes the following topics:

- PowerExchange for Salesforce Analytics Overview, 8
- Introduction to Salesforce Analytics, 8

PowerExchange for Salesforce Analytics Overview

PowerExchange for Salesforce Analytics provides connectivity between PowerCenter and Salesforce Analytics. You can use PowerExchange for Salesforce Analytics to write data to Salesforce Analytics. You can then run queries on the Salesforce Analytics database to analyze the data.

Salesforce Analytics target represent objects in the Salesforce Analytics object model. Salesforce Analytics objects are tables that correspond to tabs and other user interface elements on the Salesforce Analytics web site.

Example

You work for a social media organization that tracks users website activity. You use Salesforce Analytics to store the users online activity. You can then analyze the activity through Salesforce Analytics to identify trends such as the top users for a period.

Introduction to Salesforce Analytics

Salesforce Analytics is a cloud-based platform that connects data from multiple sources, creates interactive views of that data, and displays those views in dashboards. Business users can use Salesforce Analytics reports to understand and act on real-time information.

You can use Salesforce Analytics to get instant access to analytics data and explore data of any data source.

CHAPTER 2

Configuration

This chapter includes the following topics:

- Prerequisites, 9
- Plug-in Registration, 9
- Java Heap Size Configuration, 10

Prerequisites

Before you can use PowerExchange for Salesforce Analytics, perform the following tasks:

- Install or upgrade PowerCenter.
- Verify that you have read and write permissions on the following directories on each machine that runs the PowerCenter Integration Service and PowerCenter Repository Service:

  ```
  <Informatica Installation Directory>\server\bin\plugin
  <Informatica Installation Directory>\server\bin\native
  <Informatica Installation Directory>\server\bin\javalib
  ```

  The installer must be able to add and overwrite files in these directories.
- Verify that you have read and write permissions on the following directories of each PowerCenter Client machine:

  ```
  <Informatica Installation Directory>\clients\PowerCenterClient\client\bin
  <Informatica Installation Directory>\clients\PowerCenterClient\client\bin\Help
  <Informatica Installation Directory>\clients\PowerCenterClient\client\bin\Help
  \<language>
  <Informatica Installation Directory>\clients\PowerCenterClient\client\bin\javalib
  ```

  The installer must be able to add and overwrite files in these directories.

Plug-in Registration

After you install PowerExchange for Salesforce Analytics, upgrade it from a previous version, or apply a hotfix, it is mandatory to register the PowerExchange for Salesforce Analytics plug-in with the PowerCenter repository.

A plug-in is an XML file that defines the functionality of PowerExchange for Salesforce Analytics. To register the plug-in, the repository must be running in exclusive mode. Use the Informatica Administrator or the *pmrep* RegisterPlugin command to register the plug-in.

The plug-in file for PowerExchange for Salesforce Analytics is `AnalyticsPlugin.xml`. When you install the Repository component, the installer copies `AnalyticsPlugin.xml` to the following directory:

```
<Informatica installation directory>/server/bin/plugin
```

Note: If you do not have the correct privileges to register the plug-in, contact the user who manages the PowerCenter Repository Service.

Java Heap Size Configuration

For the Salesforce Analytics session to successfully perform the read operation, configure the memory for the Java heap size in the node that runs the PowerCenter Integration Service.

1. In the Administrator Console, navigate to the PowerCenter Integration Service for which you want to change the Java heap size.
2. Click the **Processes** tab.
3. Click **Custom Properties**.

   The Edit Custom Properties dialog box appears.
4. Click **New** to add a new custom property.
5. Specify the property name and value.

   The following table lists the property names and sample values:

Property Name	Property Value	Sample Value
JVMOption1	`-Xmx<memory_size>` to set the maximum heap size	`-Xmx1024m`
JVMOption2	`-Xms<memory_size>` to set the minimum heap size	`-Xms512m`

   Note: Specify the maximum and minimum heap size based on the data you want to process.
6. Restart the PowerCenter Integration Service.

CHAPTER 3

Salesforce Analytics Targets

This chapter includes the following topics:

- Salesforce Analytics Targets Overview, 11
- Generating a JSON File, 11
- Manually Creating a JSON File, 12
- Importing a Salesforce Analytics Target Definition, 12

Salesforce Analytics Targets Overview

Use the Designer to import Salesforce Analytics target definitions into the PowerCenter repository.

Salesforce Analytics does not contain predefined metadata. Salesforce Analytics uses the JSON file format to describe the metadata. You must create a JSON file that contains metadata in the Salesforce Analytics schema format.

To create a JSON file, create a .csv file that contains the data that you want to load into Salesforce Analytics. Use the Salesforce `datasetloader.jar` file to convert the .csv file into a JSON file.

You can also manually create the JSON file based on the Salesforce Analytics schema format.

After you create the JSON files, store the JSON files in a directory on the Windows machine where you have installed the PowerExchange for Salesforce Analytics client component.

Generating a JSON File

You must create a JSON file before you can import the file into the Designer.

Before you create a JSON file, you must download the `datasetloader.jar` from the following location:

`https://marketplace.informatica.com/listings/cloud/solutions/salesforce-analytics-schema-creator.html`

1. Create a .csv file with the supported data types and data.
2. From the command prompt, run the command: `java -jar datasetloader.jar <filename>.csv`.

   A JSON file is created in the Salesforce Analytics schema format.

Manually Creating a JSON File

1. Open a text editor and enter the data in the following Salesforce Analytics schema format:

```
{
 "name" : "AmountWithoutOwnerAdjustment",
 "type" : "Numeric",
 "precision" : 18,
 "scale" : 0
 },
 {
 "name" : "CurrencyIsoCode",
 "type" : "Text"
 }
```

   If the type is not text, specify the data type and precision details in the field name.

2. Save the JSON file with a file name that ends with _schema and close the file. For example, MyDataset_schema.json.

   Note: You cannot use any of the following as target object name:

   - Unicode characters
   - Keywords in Java language, such as constants, operators, and built-in variables. These keywords are reserved for specific functions. For example, NULL, NEW, SYSDATE, AND, OR, TRUE, FALSE, SET.

Importing a Salesforce Analytics Target Definition

1. In the Target Designer, click **Targets** > **Import from SFDC Analytics**.
2. In the Import Tables from Salesforce Analytics dialog box, enter the following information:

Import Attribute	Description
User Name	Salesforce Analytics user name.
Password	Password for the Salesforce Analytics user name. The password is case sensitive.
Service URL	URL of the Salesforce Analytics service that you want to access. In a test or development environment, you might want to access the Salesforce Analytics Sandbox testing environment. For more information about the Salesforce Analytics Sandbox, see the Salesforce documentation.
Security Token	The token used to log in to Salesforce Analytics from an untrusted network.
Temp Folder Name	The directory where the JSON files are stored.
Default Date Format	The date format to read date columns in the JSON file. Use the hyphen (-) delimiter for the Windows platform, and the forward slash (/) delimiter for the Linux platform.

3. Click **Connect**.
4. Click **Next**.

The Designer displays a list of JSON metadata files to import.

Note: If the connection wizard does not refresh the file listings in the directory, click the Back button, connect again, and click Next to refresh the list of JSON files.

5. Select the files that you want to import, and click **Finish**.

CHAPTER 4

Salesforce Analytics Mappings

This chapter includes the following topics:

- Salesforce Analytics Mappings Overview, 15
- Salesforce Analytics Mapping Example, 15


Salesforce Analytics Mappings Overview

After you import a Salesforce Analytics target definition into the PowerCenter repository, create a mapping to write data to the Salesforce Analytics target.

Salesforce Analytics Mapping Example

You work for an organization that sells electronic products through multiple websites and warehouses. You want to determine the sales details for a particular warehouse and write the sales information to Salesforce Analytics.

The following image shows the Salesforce Analytics mapping example:



The Salesforce Analytics mapping contains the following objects:

Sources

The mapping contains the following flat file sources:

- Contains details of the sales placed through websites and warehouses.
- Contains details of the warehouses from where the products are shipped.
- Contains details of the websites through which customers can place orders for products.

Transformations

The websales_join Joiner transformation joins the sales details with the website details. The sales record contains the website key. The transformation uses the website key to retrieve web site details from the web_site source.

The websales_warehouse_join_website Joiner transformation joins the output of the websales_join Joiner transformation with the warehouse details.

Target

The target named `SFDCA` is a Salesforce Analytics target.

When you run the session, the PowerCenter Integration Service writes the sales information of the specified warehouse to Salesforce Analytics. You can then run queries on Salesforce Analytics to analyze the data.

CHAPTER 5

Salesforce Analytics Sessions

This chapter includes the following topics:

- Salesforce Analytics Sessions Overview, 17
- Salesforce Analytics Connections, 17
- Session Configuration for Salesforce Analytics Targets, 18

Salesforce Analytics Sessions Overview

After you create mappings, you can create a session and use the session in a workflow to load data. Create sessions and workflows in the Workflow Manager.

When you configure a Salesforce Analytics session, you create connections to write data to Salesforce Analytics. You can also define properties in a session to determine how the PowerCenter Integration Service writes data to a Salesforce Analytics target.

Salesforce Analytics Connections

Before the PowerCenter Integration Service can connect to Salesforce Analytics, you must configure a Salesforce Analytics application connection in the Workflow Manager.

When you configure a Salesforce Analytics application connection, you specify connection attributes the PowerCenter Integration Service uses to connect to Salesforce Analytics. A connection object stores the Salesforce Analytics user ID, password, and the service URL information for the run-time connection.

Configuring a Salesforce Analytics Connection

1. In the Workflow Manager, connect to a PowerCenter repository.
2. Click **Connections** > **Application**.

   The Application Connection Browser dialog box appears.
3. From Select Type, select **Analytics**.
4. Click **New**.

5. In the **Connection Object Definition** dialog box, enter the following information:

Attribute Name	Description
Username	Salesforce Analytics user name for the application connection.
Password	Password for the Salesforce Analytics user name. The password is case sensitive.
Security Token	The token used to login to Salesforce Analytics from an untrusted network.
Service URL	URL of the Salesforce Analytics service that you want to access. In a test or development environment, you might want to access the Salesforce Analytics Sandbox testing environment. For more information about the Salesforce Analytics Sandbox, see the Salesforce documentation.
Temp Folder Name	The directory where the JSON files are stored.
Default Date Format	The date format to read date columns in the JSON file. Use the hyphen (-) delimiter for the Windows platform, and the forward slash (/) delimiter for the Linux platform.

6. Click **OK**.

   The application connection appears in the Application Object Browser.

Session Configuration for Salesforce Analytics Targets

You can configure the session properties for a Salesforce Analytics target on the Mapping tab. Define the properties for each target instance in the session.

The following table describes the session properties that you can configure for a Salesforce Analytics target:

Target Load Type

You can choose Normal mode or Bulk mode.

Default is Normal mode.

INSERT

Inserts a row to the Salesforce Analytics database.

DELETE

Deletes a row from the Salesforce Analytics database.

When you enable **DELETE,** the PowerCenter Integration Service deletes all rows flagged for delete and rejects all rows flagged when you disable **DELETE**.

UPSERT

When you enable **UPSERT,** the PowerCenter Integration Service upserts records, links the external ID to the external ID field from the source through the transformations in the target definition. Salesforce uses **UPSERT** to identify the records that must be upserted.

Success File Directory

Path to the success log files that the PowerCenter Integration Service generates.

Error File Directory

Path to the error log files that the PowerCenter Integration Service generates.

For a Salesforce Analytics target, you cannot configure the UPDATE operation.

Success and Error Logs

The PowerCenter Integration Service can generate record-level logs for each session that writes data to a Salesforce Analytics target.

The PowerExchange for Salesforce Analytics success and error logs are different from the PowerCenter session logs. The PowerExchange for Salesforce Analytics success and error logs contain record-level details that are specific to sessions with Salesforce Analytics targets.

The PowerCenter Integration Service can generate the following types of Salesforce Analytics logs:

Success log

The success log contains an entry for each record that successfully loads data into the Salesforce Analytics. Each entry contains the values loaded for all fields of the record. Use this file to understand what data is loaded into the Salesforce Analytics target. The naming convention for the success log is: <session name><timestamp>_success.csv.

Error log

The error log contains an entry for each data error. Each log entry contains the values for all fields of the record and the error message. The error log displays error messages from Salesforce Analytics and PowerCenter. Use this file to understand why records did not load data into Salesforce Analytics. The naming convention for the error log is: <session name><timestamp>_error.csv.

To configure the PowerCenter Integration Service to generate success and error logs for a session that writes data into Salesforce Analytics, configure the Success File and Error File Directory session properties.

APPENDIX A

Data Type Reference

This appendix includes the following topics:

- Data Type Reference Overview, 20
- Salesforce Analytics and Transformation Data Types, 20

Data Type Reference Overview

When the PowerCenter Integration Service loads data into a Salesforce Analytics object, it converts each PowerCenter transformation data type to a compatible Salesforce Analytics data type.

PowerExchange for Salesforce Analytics uses the following data types:

Salesforce Analytics data types

Salesforce Analytics data types appear in Salesforce Analytics definitions in a mapping.

Transformation data types

Set of data types that appear in the transformations. They are internal data types based on ANSI SQL-92 generic data types, which the PowerCenter Integration Service uses to move data across platforms. They appear in all transformations in a mapping.

Salesforce Analytics and Transformation Data Types

When the PowerCenter Integration Service writes data to a Salesforce Analytics target, it converts the data based on the native data types in the target.

The following table shows the conversion between Salesforce Analytics data types and transformation data types:

Salesforce Analytics Data Type	Transformation Data Type	Range and Description
DateTime	Date/Time	Jan 1, 0001 A.D. to Dec 31, 9999 A.D. (precision to nanosecond)
Int	Integer	Precision 10, scale 0
String	String	1 to 104,857,600 characters

INDEX

D

data type reference
  overview 17, 20
data types
  salesforce analytics and transformation data types 20

O

overview
  PowerExchange for Salesforce Analytics 8

P

PowerExchange for Salesforce Analytics
  salesforce analytics introduction 8
  targets overview 11

S

Salesforce Analytics Installation
  plug-in registration 9
  prerequisites 9
Salesforce Analytics Mapping
  mapping example 15
Salesforce Analytics Mappings
  mappings overview 15
salesforce analytics sessions
  overview 17, 20
Salesforce Analytics Sessions
  logging session details 19
  session configuration for targets 18
Salesforce Analytics Targets
  creating a metadata file 11
  importing a target definition 12
Salesforce Sessions
  configuring a connection 17