Informatica® PowerExchange® 10.5.10 Release Notes
March 2026

© Copyright Informatica LLC 2019, 2026

Contents

Enhancements. 1
Fixed issues. 2
Known issues. 3
PowerExchange 10.5.10 Installation and Upgrades. 5
Upgrade Considerations. 5
New SAMPLIB Member for CICS/VSAM ECCR Programs That Support CICS TS 6.3. 5
Informatica Global Customer Support. 5

Read the *Informatica® PowerExchange® Release Notes* to get important information about enhancements, fixed issues, and known issues in PowerExchange 10.5.10. The release notes also include upgrade considerations, if applicable.

To access the PowerExchange 10.5.10 documentation set, browse the Informatica Documentation Portal at https://docs.informatica.com.

Enhancements

The following table describes closed enhancement requests:

Enhancement	Description
PWX-11792	To prevent the repeated insertion of empty transactions into the replication slot table during PowerExchange for PostgreSQL CDC, capture processing now passes the skip-empty-xacts parameter to the replication slot plugin by default. If no activity occurs on any registered tables, no rows are inserted into the replication store table.
PWX-11667	PowerExchange includes updated physical driver locations in `odbc.ini` and `odbcinst.ini` for supported sources. The installer automatically recognizes the Driver, Setup, and HelpRootDirectory keys within the `odbc.ini` and `odbcinst.ini` files and updates any existing hard-coded paths for these keys to reference the `PWX_installed_dir/ODBC7.1` directory.
PWX-11441	PowerExchange now supports CICS Transaction Server (CICS TS) version 6.3 as a CDC data source. PowerExchange can capture changes that CICS TS 6.3 transactions make to VSAM data sets.

Fixed issues

The following table describes fixed issues:

Issue	Description
PWX-11816	PowerExchange IMS synchronous CDC jobs that have a HIDAM, PHIDAM, HISAM, or SHISAM database source might encounter data loss related to the primary index dataset during an online reorg. The problem occurs if BMC fix BQQ7462 is installed in the CRG library and the CRG library is placed before the BMC tools library in the online reorg JCL.
PWX-11803	After an upgrade to PowerExchange 10.5.6, sessions that have a Db2 for i target might fail during delete processing if NULL parameters are passed to it. The sessions fail with error code `SQLCODE 204`.
PWX-11802	PowerExchange CDC sessions that have an IMS target might report some deletes as rejected in session log although the deletes were actually written to the target successfully.
PWX-11793	If you use the PWXCATMY utility with a MySQL v9 source that includes columns with the vector data type, the utility generates catalog table entries incorrectly for the vector columns. As a result, tables with vector columns are invalidated for capture processing.
PWX-11777	After a Test Data Management (TDM) upgrade, the PowerExchange session fails with the following message: `PWX-00967 Unexpected keyword parameter "PaceSize=" Position 100.`
PWX-11772	The PowerExchange Listener ends abnormally with the S0C4 abend code in the DTLDMUT module when the CDC connection is processing an event table.
PWX-11760	After PowerExchange 10.5.5 EBF 13 is applied, when PowerExchange IMS log-based CDC runs, the IMS ECCR fails to shut down with messages on multipart (MPART) processing.
PWX-11748	During PowerExchange CDC processing of a PostgreSQL source, PowerExchange forwards entire transactions to the PowerExchange Logger for LUW instead of forwarding rows individually. This behavior can lead to Logger failures.
PWX-11732	PowerExchange sessions with a Db2 for z/OS source might end with a failed call to a Db2 stored procedure using the SQL `CALL STORPROC().`

Known issues

The following table describes known issues:

Issue	Description
PWX-11197	The PowerExchange DTLURDMO utility fails to generate extraction maps. Workaround: Either run the utility with CREATEXMAPS LOCATION=SOURCE specified or do not rename the SCHEMA and run the utility using the CREATEXMAPS LOCATION=TARGET specification.
PWX-10034	If you selected the **Full Audit** option in a capture registration for a SAP HANA CDC source, the shadow _CDC table and SAP HANA triggers are generated when the PowerExchange Logger for LUW starts. However, if a shadow_CDC table was dropped and one or more of the corresponding triggers still exist, the table is not created. If the PowerExchange Logger then tries to restart from an earlier restart point without a shadow _CDC table, it ends abnormally. Workaround: Before starting the PowerExchange Logger, either manually re-create the shadow _CDC table or drop the triggers.
PWX-9939	If you enter a passphrase that includes an apostrophe in the **Password** field in a PWX application connection in PowerCenter, the session fails. Workaround: Use a passphrase that does not include an apostrophe.
PWX-9647	During PowerExchange CDC for Db2 for i processing, the PowerExchange Listener on IBM i intermittently stops responding if alternate logging is enabled. A connection error is issued. Workaround: Disable alternate logging and try running the job again.
PWX-9014	If you select **View Paths** for an IDMS capture registration in the PowerExchange Navigator, the parent hierarchy for the IDMS base record is not displayed.
PWX-8930	The IMS log-based ECCR REFRESH command causes the ECCR to end abnormally.
PWX-8563	In the PowerExchange Navigator, if you open a Microsoft SQL Server capture registration and click **Save**, the PowerExchange Navigator creates a new SQL Server article and deletes the previous one even if no changes were made to the registration. The data associated with the previous SQL Server article is deleted. Workaround: Do not click **Save** unless you are making changes to the capture registration.
PWX-8527	After a PowerExchange IMS ECCR REFRESH operation, CDC processing might fail with an SVC99 error because of an IMS log deletion. Workaround: Stop and restart the IMS ECCR and the PowerExchange Listener on the system where change capture occurs.
PWX-8333	During PowerExchange Express CDC for Oracle, a transaction assembler error might occur for indexed-organized tables (IOTs) that contain OVERFLOW tables with chained rows. The following error message is issued: `PWX-36465 ORAD Info: DML sequence error: Subordinate DML sequence and active DML sequence is not only kdolkr/kdolmn/kdollb.`
PWX-8097	The PWXUCDCT utility fails with a segmentation fault when running a derive_cdct_backup command and trying to process corrupted PowerExchange Logger log records. The messages that the utility issues do not contain useful diagnostic information. Workaround: Ensure that the EXT_CAPT_MASK parameter value in the PowerExchange Logger configuration file is correct and that the Logger log files exist.

Issue	Description
PWX-7917	If you select the **Pre SQL run once per Connection** check box in a PWXPC connection definition for a nonrelational target, any SQL statements that you specify in the **Pre SQL** connection attribute will not be executed. Workaround: Clear the **Pre SQL run once per Connection** check box to allow the SQL to run one or more times for the connection.
PWX-7202	If you define a PowerCenter session that uses a PWX NRDB Lookup relational connection and set the TCPIP_OP_TIMEOUT and TCPIP_CON_TIMEOUT overrides in the **PWX Override** connection attribute, the session fails. Workaround: Use the connection string to specify the overrides.
PWX-7104	If you issue a pwxcmd command such as displaystats to an ECCR on a z/OS system, the pwxcmd command handler might hang. This problem occurs when the amount of command output is greater than 4 KB.
PWX-7033	If the PowerExchange Agent encounters an error in the DBMOVER configuration file, it does not end processing as expected. As a result, the Agent cannot successfully connect to the PowerExchange Listener for change data capture. Workaround: Shut down the PowerExchange Agent by using the SHUTDOWN COMPLETELY command. Edit the DBMOVER configuration file to correct the error and then restart the PowerExchange Agent.
PWX-6917	For PowerExchange on z/OS, if you use the IPV6 protocol for a TCP/IP connection, the IP address is truncated in SMF reports. The connection is not affected, but the IP address is not complete in SMF.
PWX-1971	If the file permissions on the directory path that is defined in the LOGPATH statement in the DBMOVER configuration file on the Linux Data Integration Service machine are not set correctly, a core dump occurs and a Java Runtime Environment fatal error is reported. Workaround: Ensure that the file permissions are not too restrictive. Permissions of 755 are sufficient.
PWX-1672	A CAPXRT database row test in the PowerExchange Navigator for an IMS complex table source returns no changes even though the PowerExchange Logger for z/OS contains data for the source. This problem occurs when a capture registration is re-created for the source with the same tag name as the previous registration and the new registration includes an additional IMS segment. As a result, PowerExchange cannot map the new registration to the data in the PowerExchange Logger log files. Workaround: None available. Contact Informatica Global Customer Support.
PWX-1521	If you capture change data from a Db2 for Linux, UNIX, and Windows source table that uses range partitioning and a DDL operation that adds, attaches, or detaches a partition is performed on the table, data loss might occur and cause data corruption on the target. Workaround: Do not issue DDL statements that add, attach, or detach a partition for a source table. Alternatively, if you must perform these DDL operations on a source, before you start CDC processing, synchronize the source and target tables by using PowerExchange bulk data movement or another tool.
PWX-1387	If you use PowerCenter to write Updates to a PowerExchange target and an Update fails, the PowerCenter session log displays an incorrect counts of Update rows in the Load Summary. An Update might fail, for example, because the target record does not exist.

Issue	Description
PWX-1271	When you import a copybook that contains certain German-language characters, such as ' ß' or vowels with umlauts, into a PowerExchange data map, the lines that contain these characters are not imported. Workaround: If these German-language characters appear within comments, edit the comments to remove or replace the characters.
PWX-1184	When you create a data map in the PowerExchange Navigator, if you import a PL/I copybook and enter **Start** and **End** values that define a column range that includes line sequence numbers, the PowerExchange Navigator might add an extraneous "NEW_RECORD__" record and then either fail or produce unpredictable results. Workaround: When importing a PL/I copybook, do not define a column range or accept a default column range that includes line sequence numbers.
PWX-1143	When you import a PL/1 copybook for a z/OS source into a data map from the PowerExchange Navigator, the import succeeds, but the import record is not created.

PowerExchange 10.5.10 Installation and Upgrades

Follow the procedures in the *PowerExchange Installation and Upgrade Guide* for a full or upgrade installation.

Upgrade Considerations

New SAMPLIB Member for CICS/VSAM ECCR Programs That Support CICS TS 6.3

PowerExchange 10.5.10 adds the #CICS63 member in the SAMPLIB library for defining the CICS/VSAM ECCR programs and transaction for the newly supported CICS Transaction Server (TS) version 6.3.

Because the definition of the CICS/VSAM ECCR programs and transaction changed, you must restart the CICS region after upgrading to PowerExchange 10.5.10.

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:
https://www.informatica.com/services-and-training/customer-success-services/contact-us.html.

To find online support resources on the Informatica Network, visit https://network.informatica.com and select the Support option.