Informatica® PowerExchange® 10.5.11 Release Notes

August 2026

© Copyright Informatica LLC 2019, 2026

Contents

Enhancements. 1
Fixed issues. 2
Known issues. 2
PowerExchange 10.5.11 Installation and Upgrades. 5
Upgrade Considerations. 5
Updated SAP HANA Adapter Latest Supported Versions. 5
Informatica Global Customer Support. 5

Read the *Informatica® PowerExchange® Release Notes* to get important information about enhancements, fixed issues, and known issues in PowerExchange 10.5.11. The release notes also include upgrade considerations, if applicable.

You can access the PowerExchange 10.5.11 documentation set by browsing the Informatica Documentation Portal at https://docs.informatica.com.

Enhancements

The following table describes enhancements:

Enhancement	Description
PWX-11936	PowerExchange adds two EField functions, `GetGeneratedKey()` and `GetGeneratedColumnId()`, for mappings that normalize multi-occurring fields into vertical array rows. Use `GetGeneratedKey()` to return a unique sequence number for each source record. Use `GetGeneratedColumnId()` to return the occurrence index of a multi-occurring field within that record.
PWX-11905	PowerExchange Navigator now permits you to edit the length of PostgreSQL and Microsoft SQL Server "long" columns during capture registration creation. You can configure a column length that matches your source definition instead of using a fixed default.
PWX-11835	PowerExchange adds the `ConvertDataToUtf8()` EField function to convert column data from a specified code page to UTF-8 at run time. Use this function when a source table stores data in more than one code page within the same column.

Fixed issues

The following table describes fixed issues:

Issue	Description
PWX-11949	When you run the PWXUMSGS utility without specifying the OUTDIR parameter, PowerExchange returns a Program Logic Error from DTLOS. The error does not identify the missing parameter. When you specify a date and time range with STARTDATE and ENDDATE, the utility returns only messages at the end of the range. The utility does not return the other messages within the range. The utility accepts invalid date and time values, such as an out-of-range month or day, without returning an error.
PWX-11899	PowerExchange logger operations fail when column data for a supported long-column data source, such as PostgreSQL, exceeds the fixed 96 KB size limit for long columns. The operation returns error PWX-38715: `Data would be truncated for DATA LENGTH bytes on TABLE COLUMN. Limited to DATA LIMIT bytes.`
PWX-11878	PowerExchange issues message PWXEDM176425W stating that a registered VSAM file allows only read-only access. The actual cause is a missing CICS FILEID attribute (READ, DELETE, UPDATE, or ADD) required for change data capture. The message does not identify which attribute is missing.
PWX-11874	PowerExchange does not always apply the ABEND_SW=Y setting, so PowerExchange does not consistently end the task abnormally when the setting is activated.
PWX-11832	On IBM i, PowerExchange overrides QPRINT to set the maximum record count to *NOMAX. If PowerExchange writes a message to QPRINT before applying the override, the override has no effect. QPRINT keeps its default maximum of 100,000 records.
PWX-11697	On IBM i, PowerExchange returns error 1545 (fields mismatch) for files that PowerExchange created, even though the file definition matches the data being processed.
PWX-10855	When the batch logger EDMUPARM creation job encounters an error, the job fails without writing a message that identifies the failure. This behavior makes the failure difficult to detect.

Known issues

The following table describes known issues:

Issue	Description
PWX-11197	The PowerExchange DTLURDMO utility fails to generate extraction maps. Workaround: Either run the utility with CREATEXMAPS LOCATION=SOURCE specified or do not rename the SCHEMA and run the utility using the CREATEXMAPS LOCATION=TARGET specification.
PWX-10034	If you selected the **Full Audit** option in a capture registration for a SAP HANA CDC source, the shadow _CDC table and SAP HANA triggers are generated when the PowerExchange Logger for LUW starts. However, if a shadow_CDC table was dropped and one or more of the corresponding triggers still exist, the table is not created. If the PowerExchange Logger then tries to restart from an earlier restart point without a shadow _CDC table, it ends abnormally. Workaround: Before starting the PowerExchange Logger, either manually re-create the shadow _CDC table or drop the triggers.

Issue	Description
PWX-9939	If you enter a passphrase that includes an apostrophe in the **Password** field in a PWX application connection in PowerCenter, the session fails. Workaround: Use a passphrase that does not include an apostrophe.
PWX-9647	During PowerExchange CDC for Db2 for i processing, the PowerExchange Listener on IBM i intermittently stops responding if alternate logging is enabled. A connection error is issued. Workaround: Disable alternate logging and try running the job again.
PWX-9014	If you select **View Paths** for an IDMS capture registration in the PowerExchange Navigator, the parent hierarchy for the IDMS base record is not displayed.
PWX-8930	The IMS log-based ECCR REFRESH command causes the ECCR to end abnormally.
PWX-8563	In the PowerExchange Navigator, if you open a Microsoft SQL Server capture registration and click **Save**, the PowerExchange Navigator creates a new SQL Server article and deletes the previous one even if no changes were made to the registration. The data associated with the previous SQL Server article is deleted. Workaround: Do not click **Save** unless you are making changes to the capture registration.
PWX-8527	After a PowerExchange IMS ECCR REFRESH operation, CDC processing might fail with an SVC99 error because of an IMS log deletion. Workaround: Stop and restart the IMS ECCR and the PowerExchange Listener on the system where change capture occurs.
PWX-8333	During PowerExchange Express CDC for Oracle, a transaction assembler error might occur for indexed-organized tables (IOTs) that contain OVERFLOW tables with chained rows. The following error message is issued: `PWX-36465 ORAD Info: DML sequence error: Subordinate DML sequence and active DML sequence is not only kdolkr/kdolmn/kdollb.`
PWX-8097	The PWXUCDCT utility fails with a segmentation fault when running a derive_cdct_backup command and trying to process corrupted PowerExchange Logger log records. The messages that the utility issues do not contain useful diagnostic information. Workaround: Ensure that the EXT_CAPT_MASK parameter value in the PowerExchange Logger configuration file is correct and that the Logger log files exist.
PWX-7917	If you select the **Pre SQL run once per Connection** check box in a PWXPC connection definition for a nonrelational target, any SQL statements that you specify in the **Pre SQL** connection attribute will not be executed. Workaround: Clear the **Pre SQL run once per Connection** check box to allow the SQL to run one or more times for the connection.
PWX-7202	If you define a PowerCenter session that uses a PWX NRDB Lookup relational connection and set the TCPIP_OP_TIMEOUT and TCPIP_CON_TIMEOUT overrides in the **PWX Override** connection attribute, the session fails. Workaround: Use the connection string to specify the overrides.
PWX-7104	If you issue a pwxcmd command such as displaystats to an ECCR on a z/OS system, the pwxcmd command handler might hang. This problem occurs when the amount of command output is greater than 4 KB.

Issue	Description
PWX-7033	If the PowerExchange Agent encounters an error in the DBMOVER configuration file, it does not end processing as expected. As a result, the Agent cannot successfully connect to the PowerExchange Listener for change data capture. Workaround: Shut down the PowerExchange Agent by using the SHUTDOWN COMPLETELY command. Edit the DBMOVER configuration file to correct the error and then restart the PowerExchange Agent.
PWX-6917	For PowerExchange on z/OS, if you use the IPV6 protocol for a TCP/IP connection, the IP address is truncated in SMF reports. The connection is not affected, but the IP address is not complete in SMF.
PWX-1971	If the file permissions on the directory path that is defined in the LOGPATH statement in the DBMOVER configuration file on the Linux Data Integration Service machine are not set correctly, a core dump occurs and a Java Runtime Environment fatal error is reported. Workaround: Ensure that the file permissions are not too restrictive. Permissions of 755 are sufficient.
PWX-1672	A CAPXRT database row test in the PowerExchange Navigator for an IMS complex table source returns no changes even though the PowerExchange Logger for z/OS contains data for the source. This problem occurs when a capture registration is re-created for the source with the same tag name as the previous registration and the new registration includes an additional IMS segment. As a result, PowerExchange cannot map the new registration to the data in the PowerExchange Logger log files. Workaround: None available. Contact Informatica Global Customer Support.
PWX-1521	If you capture change data from a Db2 for Linux, UNIX, and Windows source table that uses range partitioning and a DDL operation that adds, attaches, or detaches a partition is performed on the table, data loss might occur and cause data corruption on the target. Workaround: Do not issue DDL statements that add, attach, or detach a partition for a source table. Alternatively, if you must perform these DDL operations on a source, before you start CDC processing, synchronize the source and target tables by using PowerExchange bulk data movement or another tool.
PWX-1387	If you use PowerCenter to write Updates to a PowerExchange target and an Update fails, the PowerCenter session log displays an incorrect counts of Update rows in the Load Summary. An Update might fail, for example, because the target record does not exist.
PWX-1271	When you import a copybook that contains certain German-language characters, such as ' ß' or vowels with umlauts, into a PowerExchange data map, the lines that contain these characters are not imported. Workaround: If these German-language characters appear within comments, edit the comments to remove or replace the characters.
PWX-1184	When you create a data map in the PowerExchange Navigator, if you import a PL/I copybook and enter **Start** and **End** values that define a column range that includes line sequence numbers, the PowerExchange Navigator might add an extraneous "NEW_RECORD__" record and then either fail or produce unpredictable results. Workaround: When importing a PL/I copybook, do not define a column range or accept a default column range that includes line sequence numbers.
PWX-1143	When you import a PL/1 copybook for a z/OS source into a data map from the PowerExchange Navigator, the import succeeds, but the import record is not created.

PowerExchange 10.5.11 Installation and Upgrades

Follow the procedures in the *PowerExchange Installation and Upgrade Guide* for a full or upgrade installation.

Upgrade Considerations

Updated SAP HANA Adapter Latest Supported Versions

PowerExchange updates the SAP HANA Adapter to use the latest supported versions of its third-party libraries.

PowerExchange SAP HANA CDC requires JDBC access in addition to ODBC access.

PowerExchange installs the following .jar files for the SAP HANA CDC:

- commons-codec-1.22.0.jar
- dworacle-6.0.0.001877.jar
- HanaAdapter.jar v2.12.1
- HanaLogReader.jar v2.12.1
- log4j-api-2.26.0.jar
- log4j-core-2.26.0.jar

See *PowerExchange CDC Guide for Linux UNIX and Windows* for more information.

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:
https://www.informatica.com/services-and-training/customer-success-services/contact-us.html.

To find online support resources on the Informatica Network, visit https://network.informatica.com and select the Support option.