Informatica
from Salesforce

Informatica® Cloud Data Quality
July 2026

API Reference

Informatica Cloud Data Quality API Reference
July 2026

© Copyright Informatica LLC 2025, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica®, Informatica Cloud, Intelligent Data Management Cloud™, Cloud Data Integration for PowerCenter (CDI-PC), PowerExchange, and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-07-10

Table of Contents

Preface . . . 4

Chapter 1: Introduction . . . 5

Authentication . . . 5

Send requests . . . 5

Response codes . . . 6

Chapter 2: Manage dictionaries . . . 7

Create a dictionary . . . 7

- Request body . . . 7
- Example request . . . 8
- Example response . . . 8

Delete a dictionary . . . 9

- Request body . . . 9
- Example request . . . 10
- Response . . . 10

Chapter 3: Manage dictionary data . . . 11

Add dictionary data . . . 11

- Request body . . . 11
- Example request . . . 12
- Response . . . 12

Replace dictionary data . . . 12

- Request body . . . 13
- Example request . . . 13
- Response . . . 13

Delete dictionary data . . . 13

Finalize dictionary updates . . . 14

Preface

Read *API Reference* to learn how to create and manage dictionary content in your application using the API that Informatica provides.

This guide is written for developers and administrators who want to create and manage dictionaries that data quality assets and transformations can use in Intelligent Data Management Cloud. The guide assumes that you have a basic knowledge of how to use Data Quality. It also assumes that you understand JSON and API programming techniques.

CHAPTER 1

Introduction

Use the Data Quality Dictionary API to create, update, and delete dictionary content in a third-party application.

Use a REST client, URL, or another programming interface to call the Data Quality Dictionary API.

Authentication

Before you can make REST API calls, you must authenticate yourself with the Intelligent Data Management Cloud POD that your organization wants to connect to.

The REST APIs use a common set of steps to log in and authenticate with Intelligent Data Management Cloud.

For more information about how to authenticate with Intelligent Data Management Cloud, see *REST API Reference* help in the Administrator.

Send requests

When you make an API call in the REST client, the request is sent in JSON format. The REST client receives a response in JSON format that contains the response to the request that you've sent.

Include the URL that identifies the API, header requests, methods, and request parameters in your call.

URL structure

Use the following URL structure for requests:

```
<baseApiUrl><endpoint>
```

Defining the base API URL

The login response includes the base API URL that you must include in subsequent calls. The base API URL differs for each POD.

The base API URL has the following format:

https://idmc-api.dm-[two-letter-regional-identifier].informaticacloud.com/

For example, you use the following base API URL for the USW1 POD:

https://idmc-api.dm-us.informaticacloud.com/

Header request parameters

The following table describes the header request that you use in API requests:

Header	Description
`Content-Type:application/json`	Required to indicate that the client is sending a JSON request.
`Authorization:Bearer <jwt_token>`	Required to secure your API requests if you don't enter a value for `IDS-SESSION-ID`.
`IDS-SESSION-ID`	Required to secure the API requests via JSON Web Token-based authentication if you don't enter a value for `Authorization:Bearer <jwt_token>`.

Response codes

When you call a Data Quality API, the response returns one of the standard HTTP response codes with information about the success or failure of the API call.

The following table defines the standard response codes:

Response Code	Description
200 OK	The request completed successfully.
201 Created	The request to create the resource completed successfully.
204 No Content	The request to delete the resource completed successfully.
400 Bad Request	The request cannot be processed because information is missing or not valid.
401 Unauthorized	The request is not authorized. The authentication may be missing or not valid.
403 Forbidden	The user cannot be authorized to perform this request.
404 Not Found	The request includes a resource URL that does not exist.
409 Conflict	The request cannot be completed because it conflicts with the current state of the resource on the server.
413 Payload Too Large	The request cannot be processed because the request payload exceeds the server configuration limit.
424 Failed Dependancy	The request cannot be processed because a dependent request did not succeed.
500 Internal Server Error	The server encountered an error because of which the request is not fulfilled.

CHAPTER 2

Manage dictionaries

Use APIs to create and delete dictionaries in your application.

Create a dictionary

Send a POST request to create dictionaries.

The following table describes the method and endpoint to use in the request:

Method	Endpoint
POST	<baseApiUrl>/quality/public/v2/dictionaries/

The base API URL differs for each pod. For more information, see "Send requests" on page 5.

Request body

Use the request body to specify the parameters of the dictionary that you want to create.

In the body of the request, specify the parameters in the following format:

```
{
  "name": "<dictionary name>"
  "description": "<dictionary description>",
  "columns": ["<column1>", "<column2>", "<column3>"],
  "path": "<location of project folder>"
}
```

The following table describes the parameters that you can specify in the body of the request:

Parameter	Type	Description
name	String	Contains the name of the dictionary. **Note:** The dictionary name must not exceed 125 characters.
description	String	Contains the basic description of the dictionary.

Parameter	Type	Description
columns	Array of Strings	Contains the names of the columns to add to the new dictionary. **Note:** The column names you specify must be unique within the dictionary. Each column name must not exceed 64 characters, and the number of columns must not exceed 42.
path	String	Specifies the location of the dictionary in the cloud project and folder structure. **Note:** If you don't specify the name of the project folder, the dictionary is created in the default project.

Example request

The following example shows a POST request to create a dictionary:

```
POST https://use4-dqcloud-api.dm-us.informaticacloud.com/quality/public/v2/dictionaries/
Authorization: Bearer <jwt_token>
Accept: application/json
Content-Type: application/json
Body
{
  "name": "address_street_line_infa",
  "description": "List to interpret street line of address”,
  "columns": ["StreetDesc1", "StreetDesc2", "StreetDesc3"],
  "path": "CDQ Bundle 2"
}
```

Example response

The POST request response returns the newly created dictionary.

The following example shows the response to the POST request to create a dictionary:

```
{
  "id": "2MqSZ5b4EUkhtKxyJv6j2H",
  "name": "address_street_line_infa",
  "description": "List to interpret street line of address",
  "path": "CDQ Bundle 2",
  "type": "DICTIONARY",
  "columns": ["StreetDesc1", "StreetDesc2", "StreetDesc3"],
  "customAttributes": {
    "stringAttrs": [
      {
        "name": "OWNER",
        "value": "PUBLIC_REST_API"
      },
      {
        "name": "MODE",
        "value": "API"
      },
      {
        "name": "ReferencedPublishingAllowed",
        "value": true
      }
    ]
  },
  "updateTime": "2025-10-17T10:30:00Z"
}
```

The following table describes the parameters in the response body:

Parameter	Description
id	Contains the internal ID of the dictionary. You can derive this ID from the URL of the dictionary in Data Quality.
name	Contains the name of the dictionary.
description	Contains the description of the dictionary.
path	Specifies the location of the dictionary in the cloud project and folder structure.
type	The type of asset.
columns	Contains the names of the columns added to the new dictionary.
customAttributes	Contains the attributes of the dictionary. Includes the stringAttrs attribute, which contains a range of information about the dictionary. For example, the MODE attribute identifies the environment in which a user can update or delete the dictionary.
updateTime	Contains the date and time at which the dictionary was last updated.

Delete a dictionary

Send a DELETE request to delete a dictionary.

The following table describes the method and endpoint to use in the request:

Method	Endpoint
DELETE	<baseApiUrl>/quality/public/v2/dictionaries/<dictionaryId>

The base API URL differs for each pod. For more information, see "Send requests" on page 5.

Request body

To delete a dictionary, include the dictionary ID in the URL.

The following example shows the request format:

```
DELETE https://use4-dqcloud-api.dm-us.informaticacloud.com/quality/public/v2/
dictionaries/<dictionaryId>
Authorization: Bearer <jwt_token>
```

Example request

The following example shows a request to delete a dictionary:

```
DELETE https://use4-dqcloud-api.dm-us.informaticacloud.com/quality/public/v2/
dictionaries/2MqSZ5b4EUkhtKxyJv6j2H
Authorization: Bearer <jwt_token>
```

Response

The call returns a status code that confirms the result of the action. If the action fails, the call returns an applicable error code.

For more information about the response codes, see “Response codes” on page 6.

CHAPTER 3

Manage dictionary data

Use APIs to add, replace, and delete dictionary data.

Add dictionary data

Send a POST request to add one or more rows of data to a dictionary. You can add up to 10,000 rows in a single request.

The following table describes the method and endpoint to use in the request:

Method	Endpoint
POST	<baseApiUrl>/quality/public/v2/dictionaries/<dictionaryId>/rows

After you add dictionary data, you must finalize the operation in the database. Until you run the `finishUpload` API, the updated data is stored in an internal database and are not accessible to your customers. When you run the `finishUpload` API, the updated data is encrypted and stored in Intelligent Data Management Cloud.

You can add rows in multiple calls to the POST method and finalize the uploads when all of your additions are complete. For more information about the method and endpoint to use in finalizing the uploads, see "Finalize dictionary updates" on page 14.

Request body

Use the request body to specify the data values you want to add to the dictionary.

In the body of the request, specify the parameters in the following format:

```
{
  "cols": ["<column1>", "<column2>", "<column3>"],
  "rows": [
    ["<value1>", "<value2>", "<value3>"],
    ["<value4>", "<value5>", "<value6>"],
    ["<value7>", "<value8>", "<value9>"]
  ]
}
```

The following table describes the parameters that you can specify in the request URL:

Parameter	Type	Description
dictionaryId	String	Contains the ID of the dictionary to which you want to add rows.
cols	Array of Strings	Contains the names of the columns to add to the dictionary. **Note:** The column names you specify must be unique within the dictionary. Each column name must not exceed 64 characters, and the number of columns must not exceed 42.
rows	Array of Strings	Contains the values to add to each column. The row data you add must match the number of columns you add to the dictionary. You can add up to 10,000 rows to a dictionary in a single API request.

Example request

The following example shows a POST request that adds three rows to the dictionary:

```
POST https://use4-dqcloud-api.dm-us.informaticacloud.com/quality/public/v2/dictionaries/
2MqSZ5b4EUkhtKxyJv6j2H
/rows
Authorization: Bearer <jwt_token>
Accept: application/json
Content-Type: application/json
Body
{
  "cols": ["Streetdesc1", "Streetdesc2", "Streetdesc3"],
  "rows": [
    ["ALLEY", "ALLEE", "ALLY"],
    ["ANNEX", "ANEX", "ANX"],
    ["AVENUE", "AVE", "AVN"]
  ]
}
```

Response

The call returns a status code that confirms the result of the action. If the action fails, the call returns an applicable error code.

For more information about the response codes, see "Response codes" on page 6.

Replace dictionary data

Send a PUT request to replace all current dictionary data with new data. You can replace up to 10,000 rows in a single request.

The following table describes the method and endpoint to use in the request:

Method	Endpoint
PUT	<baseApiUrl>/quality/public/v2/dictionaries/<dictionaryId>/rows

Request body

Use the request body to list the new values that will populate the dictionary. The operation deletes all current values and replaces them with the values that you provide.

In the body of the request, specify the parameters in the following format:

```
{
  "cols": ["<column1>", "<column2>", "<column3>"],
  "rows": [
    ["<newValue1>", "<newValue2>", "<newValue3>"],
    ["<newValue4>", "<newValue5>", "<newValue6>"]
  ]
}
```

Example request

The following example shows a POST request to replace the current dictionary contents with two rows of data values:

```
PUT https://use4-dqcloud-api.dm-us.informaticacloud.com/quality/public/v2/dictionaries/
2MqSZ5b4EUkhtKxyJv6j2H/rows
Authorization: Bearer <jwt_token>
Accept: application/json
Content-Type: application/json
Body
{
  "cols": ["Streetdescr1", "Streetdescr2", "Streetdescr3"],
  "rows": [
    ["BOULEVARD", "BLVD", "BVD"],
    ["STREET", "STR", "ST"]
  ]
}
```

Response

The call returns a status code that confirms the result of the action. If the action fails, the call returns an applicable error code.

For more information about the response codes, see "Response codes" on page 6.

Delete dictionary data

Send a DELETE request to remove all rows in the dictionary.

The following table describes the method and endpoint to use in the request:

Method	Endpoint
DELETE	<baseApiUrl>/quality/public/v2/dictionaries/<dictionaryId>/rows

The base API URL differs for each pod. For more information, see "Send requests" on page 5.

After you delete dictionary data, you must finalize the operation in the database. Until you run the `finishUpload` API, the updates are not committed to Intelligent Data Management Cloud and the deleted dictionary data remains available to your customers. When you run the `finishUpload` API, the updated data

is encrypted and stored in Intelligent Data Management Cloud. For more information about the method and endpoint to use in finalizing the deletion request, see "Finalize dictionary updates" on page 14.

Finalize dictionary updates

After you use a POST or DELETE method to add or delete dictionary data, finalize the operation in Intelligent Data Management Cloud storage.

You can make a single `finishUpload` API call to finalize multiple POST or DELETE operations. For example, if you add multiple rows to the dictionary data in successive operations, call the `finishUpload` API to commit all updates to the cloud storage. The data you finalize and upload is encrypted and securely stored in Intelligent Data Management Cloud.

Until you run the `finishUpload` API, the updated data is stored in an internal database and is not accessible to your customers.

The following table describes the method and endpoint to use in the request:

Method	Endpoint
POST	`<baseApiUrl>/quality/public/v2/dictionaries/<dictionaryId>/finishUpload`

The base API URL differs for each pod. For more information, see "Send requests" on page 5.