Informatica® Metadata Command Center
July 2026

Salesforce Sources

Informatica Metadata Command Center Salesforce Sources
July 2026

© Copyright Informatica LLC 2025, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Informatica, Informatica Cloud, Informatica Intelligent Cloud Services, PowerCenter, PowerExchange, and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-07-24

Table of Contents

Preface 5

Chapter 1: Introduction to Salesforce catalog sources 6

Extraction and view process 7

About the Salesforce catalog source 8

Extracted metadata 8

Data profiling for Salesforce objects 9

Compatible connectors 10

Chapter 2: Before you begin 11

Verify permissions 11

Permissions to extract metadata 11

Permissions to run data profiles 12

Permissions to perform data classification 12

Permissions to perform relationship discovery 12

Permissions to perform glossary association 12

Create a connection 12

Create a connection to run profile and data quality jobs 14

Troubleshooting 15

Create endpoint catalog sources for connection assignment 16

Import a relationship inference model 17

Chapter 3: Create catalog sources in Metadata Command Center 18

Step 1. Register a catalog source 18

Step 2. Configure capabilities 20

Configure metadata extraction 21

Configure data profiling and quality 23

Configure data observability 26

Configure data classification 27

Configure relationship discovery 28

Configure glossary associations 29

Step 3. Associate stakeholders and asset groups 30

Step 4. Run or schedule the job 31

Step 5. Assign reference catalog source connections to endpoint catalog source objects 32

Chapter 4: View results in Data Governance and Catalog 35

View metadata extraction results 35

View data lineage 37

View lineage at the catalog source level 37

View lineage at the data set level 37

View lineage at the data element level. 38
View data profiling results 38
View data observability results 39
View classified data. 40
View glossary associations. 40

Appendix A: Managing catalog sources. 42

Cloning a catalog source configuration. 42
Deleting or purging a catalog source. 43
Purging obsolete objects from a catalog source. 43
Curating CLAIRE recommendations. 44
Managing configuration permissions for catalog sources. 44

Preface

Read *Salesforce Sources* to learn how to register and configure Salesforce sources in Metadata Command Center as catalog sources. After you configure a catalog source, you extract metadata and then view the results in Data Governance and Catalog.

CHAPTER 1

Introduction to Salesforce catalog sources

You can use Metadata Command Center to extract metadata from a source system.

A source system is any system that contains data or metadata. For example, Salesforce is a source system from which you can extract metadata through a Salesforce catalog source with Metadata Command Center. A catalog source is an object that represents and contains metadata from the source system.

Before you extract metadata from a source system, you first create and register a catalog source that represents the source system. Then you configure capabilities for the catalog source. A capability is a task that Metadata Command Center can perform, such as metadata extraction, lineage discovery, data profiling, data classification, or glossary association.

When Metadata Command Center extracts metadata, Data Governance and Catalog displays the extracted metadata and its attributes as technical assets. You can then perform tasks such as analyzing the assets, viewing lineage, and creating links between those assets and their business context.

The following table describes the capabilities of the catalog source:


Capability	Description
Serverless Runtime Environment	A serverless runtime environment is an advanced serverless deployment solution that doesn't require downloading, installing, configuring, or maintaining a Secure Agent or Secure Agent group. You can use a serverless runtime environment in the same way that you use a Secure Agent when you configure a catalog source.
Data Profiling and Quality	- **Data Profiling**. Assesses source metadata and analyzes the collected statistics to discover content and structure, such as value distribution, patterns, and data types. - **Data Quality**. Measures the reliability of the data and enables data usage.
Data Observability	Identifies anomalies in the characteristics of the data that you profile.
Data Classification	Data classification is the process of identifying and organizing data into relevant categories based on the functional meaning of the data. Classifying data can help your organization manage risks, compliance, and data security.

Capability	Description
Relationship Discovery	You can associate terms that are in the glossary with technical assets to provide user-friendly business names to technical assets. Glossary Association automatically associates glossary terms with technical assets or recommends glossary terms that you can manually associate with technical assets in Data Governance and Catalog.
Glossary Association	You can associate terms that are in the glossary with technical assets to provide user-friendly business names to technical assets. Glossary Association automatically associates glossary terms with technical assets or recommends glossary terms that you can manually associate with technical assets in Data Governance and Catalog.

Extraction and view process

To extract metadata from a source system, configure the catalog source and run the extraction job in Metadata Command Center. Then view the results in Data Governance and Catalog.

The following image shows the process to extract metadata from a source system:



After you verify prerequisites, perform the following tasks to extract metadata from Salesforce:

1. Register a catalog source. Create a catalog source object, select Salesforce, and then select and test the connection.
2. Configure the catalog source. Specify the runtime environment and configure parameters for metadata extraction. Optionally, add filters to include or exclude source system assets from metadata extraction. You can also configure other capabilities such as data profiling and quality, data classification, or glossary association.
3. Optionally, associate stakeholders. Associate users with technical assets, giving the users permission to perform actions determined by their roles.
4. Run or schedule the catalog source job.
5. Optionally, if the catalog source job generates referenced asset objects, you can assign a connection to referenced source system assets.
   You can view the lineage with object references without performing connection assignment. After connection assignment, you can view the objects.

After you run the catalog source job, you view the results in Data Governance and Catalog.

About the Salesforce catalog source

You can use the Salesforce catalog source to extract metadata from a Salesforce source system.

Salesforce is a cloud-based platform that integrates Salesforce CRM, Salesforce Data 360, and Salesforce Flows applications for customer service, analytics, and automation.

Extracted metadata

You can extract specific metadata from a Salesforce source system with a Salesforce catalog source.

Metadata Command Center extracts metadata of the following objects from a Salesforce CRM application:

- Organization
  - List View
    - List View Column
  - Trigger
  - Salesforce Object
    - Field

Note: If there is a duplicate global list view that is not associated with a specific object in the source system, then only one global list view is extracted.

Metadata Command Center extracts metadata of the following objects from a Salesforce Data 360 application:

- Organization
  - Data Lake Object
    - Data Lake Object Field
  - Data Space
    - Calculated Insight created with Visual Builder or by SQL authoring
      - Dimension
      - Measure
    - Data Mapping linked to Data Model Object
    - Data Model Object mapped and used within a Salesforce Data 360 application
      - Data Model Object Field
    - Identity Resolution
      - Match and Reconciliation
  - Data Stream
    - Data Stream Calculation including Formula Field and Filter
  - Data Transform
    - Batch Data Transform and Streaming Data Transform including Data Transform Definition

Metadata Command Center extracts metadata of the following objects from a Salesforce Flows application:

- Organization
  - Flow
    - Autolaunched Flow (No Trigger)
    - Data 360-Triggered Flow
    - Record-Triggered Flow
    - Schedule-Triggered Flow

Note: You can only extract metadata of the unmanaged flows.

Data profiling for Salesforce objects

Configure data profiling to run profiles on the metadata extracted from a Salesforce source system. You can view the profiling statistics in Data Governance and Catalog.

You can run data profiles on metadata extracted from the following Salesforce CRM objects:

- Organization
  - Salesforce Object

You can run data profiles on metadata extracted from the following Salesforce Data 360 objects:

- Organization
  - Data Lake Object from the default data space
  - Data Space
    - Calculated Insight created with Visual Builder or by SQL authoring
    - Data Model Object mapped and used within a Salesforce Data 360 application

      Note: When you run data profiles on unmapped Data Model Object fields, the results display empty values.

The data profiling task runs profiles on the following data types from Salesforce CRM applications:

- ANY TYPE
- BOOLEAN
- COMPLEX VALUE
- CURRENCY
- DATE
- DATETIME
- DOUBLE
- EMAIL
- ID
- INT
- JSON
- LONG
- MULTI PICK LIST
- PERCENT
- PHONE

- PICKLIST
- REFERENCE
- STRING
- TEXT AREA
- URL

The data profiling task runs profiles on the following data types from Salesforce Data 360 applications:

- BOOLEAN
- DATE
- DATETIME
- EMAIL
- NUMBER
- CURRENCY
- PERCENT
- PHONE
- TEXT
- URL

Compatible connectors

Before you configure a Salesforce catalog source, you must connect to the Salesforce source system.

Use the Salesforce connector to connect to the Salesforce source system.

To run data profiling and data quality jobs on objects extracted from a Salesforce Data 360 application, use the Salesforce Data 360 connector.

Note: The Salesforce Data 360 application integrates data through connectors. You can use the application with the ingestion API connector.

For information about configuring a connection, see *Connections* in the Administrator help.

CHAPTER 2

Before you begin

Before you create a catalog source, ensure that you have the information required to connect to the source system.

Perform the following tasks:

- Assign the required permissions.
- Configure a connection to the Salesforce source system in Administrator.
- Configure a Salesforce Data 360 connection in Administrator to run data profiling and data quality jobs on objects extracted from a Salesforce Data 360 application.
- To extract metadata from a Salesforce source system, verify that you have access to Salesforce REST API or SOAP API.
- To set up authorization to restrict access to your organization's protected resources, use the OAuth 2.0 Refresh Token Flow for Renewed Sessions. For more information about this authorization method, see the Salesforce documentation on OAuth 2.0 Refresh Token Flow for Renewed Sessions.
- Create endpoint catalog sources for connection assignment.
- Optionally, if you want to identify pairs of similar columns and relationships between tables within a catalog source, import a relationship inference model.

Verify permissions

To extract metadata and to configure other capabilities that a catalog source might include, you need account access and permissions on the source system. The permissions required might vary depending on the capability.

Permissions to extract metadata

Ensure that you have the required permissions to enable metadata extraction.

Perform the following tasks:

- Assign the `Data Cloud Admin` or the `Data Cloud User` permission sets to the user.
- Grant access to the data spaces for the `Data Cloud User` permission set in the Data Space Management settings.

- Assign the following permissions to the Salesforce profile or permission sets:
  - `Modify All Data`. Allows you to extract all objects. If you don't want Salesforce to modify all data, select `View All Data`.

    Note: If you select `View All Data`, you might not extract some objects. For more information, see the Knowledge Base article 000196069.
  - `API Enabled`. Allows you to access the data of your organization through API requests to your Salesforce instance.
  - `Manage Flows` permissions to use flows.
- Assign the following OAuth scopes to external client apps:
  - Perform requests at any time (`refresh_token, offline_access`)
  - Access the Salesforce API Platform (`sfap_api`)
  - Access all Data Cloud API resources (`cdp_api`)

  For more information about Oauth tokens and scopes, see the Salesforce documentation.

Permissions to run data profiles

You can run profiles with the permissions required on the source system to perform metadata extraction.

Permissions to perform data classification

You can perform data classification with the permissions required on the source system to perform metadata extraction.

Permissions to perform relationship discovery

You can perform relationship discovery with the permissions required on the source system to perform metadata extraction.

Permissions to perform glossary association

You can perform glossary association with the permissions required on the source system to perform metadata extraction.

Create a connection

Before you configure the Salesforce catalog source, create a connection object in Administrator.

To use an external secrets manager to connect to the source system, use one of the following authentication tools:

- AWS Secrets Manager
- Azure Key Vault

1. In Administrator, select **Connections**.
2. Click **Add Connection**.
3. Select Salesforce and click **Next**.

4. Enter the connection properties.

   The following table describes the connection properties:

Connection Name	Name of the connection. Each connection name must be unique within the organization. Connection names can contain alphanumeric characters, spaces, and the following special characters: _ . + -, Maximum length is 255 characters.
Description	Description of the connection. Maximum length is 4000 characters.
Use Secret Vault	Stores sensitive credentials for this connection in the secrets manager that is configured for your organization. This property appears only if secrets manager is set up for your organization. When you enable the secret vault in the connection, you can select which credentials that the Secure Agent retrieves from the secrets manager. If you don't enable this option, the credentials are stored in the repository or on a local Secure Agent, depending on how your organization is configured. **Note:** If you're using this connection to apply data access policies through pushdown or proxy services, you cannot use the Secret Vault configuration option. For information about how to configure and use a secrets manager, see "Secrets manager configuration" in the Administrator help.
Runtime Environment	The name of the runtime environment where you want to run tasks. For more information about how to configure and use the runtime environments, see *Runtime Environments* in the Administrator help.
Salesforce Connection Type	The authentication type to use for the connection. Select one of the following methods: - Standard. - OAuth authentication.

5. Enter the following connection details for the Standard authentication type:

Property	**Description**
User Name	The user name to connect to the Salesforce account.
Password	The password to connect to the Salesforce account.
Service URL	URL of the Salesforce service. For example: `https://login.salesforce.com/services/Soap/u/64.0` By default, Salesforce connections for new organizations use version 64.0 of the Salesforce API. You can use any Salesforce API version up to 64.0, except the versions 58.0 and 61.0. Maximum length is 100 characters. If you edit the service URL for an existing standard connection, you need to re-enter the password and security token.

The following table describes the advanced connection properties for standard connection:

Property	Description
Security Token	Security token generated from the Salesforce application. **Note:** If you don't enter the Salesforce security token in this field, you need to add the Data Integration IP addresses to the trusted IP ranges in your Salesforce account. Otherwise, the connection might fail.
Bypass proxy server settings defined for the Secure Agent	Bypasses the proxy server settings defined for the Secure Agent in the Secure Agent Manager and directly connects to Salesforce. If you do not select this option, the Salesforce connection uses the proxy server setting defined for the Secure Agent to connect to Salesforce.

6. Enter the following connection details for the OAuth authentication type:

Property	Description
OAuth Consumer Key	The consumer key to generate a refresh token.
OAuth Consumer Secret	The consumer secret to generate a refresh token.
OAuth Refresh Token	The refresh token that you generated using the SFDC OAuth 2.0 tool. For more information about how to generate the OAuth refresh token, see the *Before you begin* section.
Service URL	URL of the Salesforce service endpoint. For example: `https://login.salesforce.com/services/Soap/u/64.0` You can use any Salesforce API version up to 64.0, except the versions 58.0 and 61.0. Maximum length is 100 characters. When you edit the service URL for an existing OAuth connection, you need to re-enter the consumer key, consumer secret, and refresh token.

7. Click **Test** to test your connection to the source system.
8. Click **Save**.

Note: To run data profiling or data quality jobs on metadata extracted from Salesforce Data 360 objects, "Create a connection to run profile and data quality jobs" on page 14 in Administrator.

Create a connection to run profile and data quality jobs

Before you run data profiling or data quality jobs on metadata extracted from a Salesforce Data 360 application, create a Salesforce Data 360 connection object in Administrator.

You need to configure the OAuth 2.0 client credentials authentication type.

1. In Administrator, select **Connections**.
2. Click **Add Connection**.
3. Select Salesforce Data 360 and click **Next**.
4. Enter the connection properties.

The following table describes the connection properties:

Property	Description
Connection Name	Name of the connection. Each connection name must be unique within the organization. Connection names can contain alphanumeric characters, spaces, and the following special characters: _ . + -, Maximum length is 255 characters.
Description	Description of the connection. Maximum length is 4000 characters.
Runtime Environment	The name of the runtime environment where you want to run tasks. For more information about how to configure and use the runtime environments, see *Runtime Environments* in the Administrator help.
Authentication Type	The authentication type to use for the connection. Choose to connect using OAuth 2.0 client credentials.

5. Enter the following connection details for the OAuth 2.0 client credentials authentication type:

Property	Description
Access Token URL	The endpoint where OAuth 2.0 requests are sent to obtain an access token to connect to the Salesforce Data 360 instance. Specify the URL in the following format: `https://<Salesforce Data 360 organization ID>.salesforce.com/services/oauth2/token`
Client ID	Client ID of your application to connect to Salesforce Data 360.
Client Secret	The client secret associated with the client ID.
Access Token	The access token value. Click **Generate Access Token** to populate the access token value.

6. Click **Test** to test your connection to the source system.
7. Click **Save**.

Troubleshooting


If you run into connection errors, refer to the following section.

Metadata extraction jobs fail with "Cannot retrieve the organization"

If you select the OAuth authentication type and run a metadata extraction job, the job fails during the 'Test Connection' stage with the following error:

```
Unexpected error occurred: Cannot retrieve the organization for
\"https://login.salesforce.com/services/data/v53.0/query/?
q=SELECT+Name+FROM+Organization\", no graphs created"
```

You can see the error on the **Logs** tab of the **Monitor** page. The following image shows the error:



This issue occurs when you provide login.salesforce.com as the service URL in the Salesforce catalog source connection configuration. You cannot use a generic service URL, such as login.salesforce.com.


To resolve this issue, use the specific service URL in the Salesforce catalog source connection configuration.

To identify the specific service URL, perform the following steps:

1. Log in to your account with the https://login.salesforce.com/ URL.
   The service URL appears. For example, https://company-abc.my.salesforce.com.
2. Copy the service URL from the URL bar.
   The service URL is specific to the credentials that you use to connect to the Salesforce REST API. The standard login or OAuth keys are generated based on the service URL.

Note: The service URL configured in Administrator has the following structure: https://company-abc.my.salesforce.com/services/Soap/u/55.0.

The following image shows a reference service URL:



Create endpoint catalog sources for connection assignment


An endpoint catalog source represents a source system that the catalog source references. Before you perform connection assignment, create endpoint catalog sources and run the catalog source jobs.

You can then perform connection assignment to reference source systems to view complete lineage with source system objects.

Import a relationship inference model

Import a relationship inference model if you want to configure the relationship discovery capability. You can either import a predefined relationship inference model, or import a model file from your local machine.

1. In Metadata Command Center, click **Explore** on the navigation panel.
2. Expand the menu and select **Relationship Inference Model**. The **Explore** page opens with the **Relationship Inference Model** menu.



3. Select one of the following options:
   - **Import Predefined Content**. Imports a predefined relationship inference model called Column Similarity Model v1.0.
   - **Import**. Imports the predefined relationship inference model from your local machine. Select this if you previously imported predefined content into your local machine and the inference model is stored on the machine.
     To import a file, click **Choose File** in the **Import Relationship Inference Model** window and navigate to the model file on your local machine. You can also drag and drop the file.

   The imported models appear in the list of relationship inference models on the **Relationship Discovery** tab.

CHAPTER 3

Create catalog sources in Metadata Command Center

Use Metadata Command Center to configure a catalog source for Salesforce and run the catalog source job.

When you configure a catalog source, you define the source system that you want to extract metadata from. Configure filters to include or exclude source system metadata before you run the job. Optionally, configure other capabilities, such as lineage discovery, data profiling and quality, data classification, relationship discovery, and glossary association.

To provide stakeholders access to technical assets, you can assign access through stakeholder roles. You can also associate technical assets extracted from the catalog source to asset groups. If your catalog source references other source systems, you can create a connection assignment to the endpoint catalog source to view complete lineage.

Step 1. Register a catalog source


When you register a catalog source, provide general information and connection values.

1. Log in to Intelligent Data Management Cloud.

   The **My Services** page appears.


2. Click **Metadata Command Center**.

   The **Metadata Command Center** box appears on the **My Services** page.



The Metadata Command Center home page appears.


3. Click **New**.
4. Select **Catalog Source** from the list of asset types.
5. Select Salesforce from the list of catalog source types.



6. Click **Create**.

   The **New Catalog Source** page opens.

The following image shows the **Registration** tab on the **New Catalog Source** page:



7. In the **General Information** section, enter a name and an optional description for the catalog source.

   Note: You can rename a catalog source after you create it, but to apply the change to all associated objects you must rerun the metadata extraction job.

   After you save the catalog source, you can update the description in Metadata Command Center and Data Governance and Catalog. The update appears only in the service in which you update it.
8. In the **Connection Information** area, select the connection that you created in Administrator.

   Note: To create or edit a catalog source, you need permissions on the connection to the source system. Select a connection that you have access to, or ask the administrator to grant the necessary permissions to the connection that you want to use.
9. Click **Connection Properties** to expand and view the connection properties for the selected connection.
10. Click **Test Connection** to test your connection to the source system.
11. Click **Next**.

The **Configuration** page appears.

Step 2. Configure capabilities

When you configure the Salesforce catalog source, you define the settings for the metadata extraction capability and other optional capabilities.

The metadata extraction capability extracts source metadata from external source systems. You can also configure other capabilities that the catalog source includes.

You can save the catalog source configuration at any point after you enter the connection information. After you save the catalog source, you can choose to run the catalog source job. To run the job once, click **Run**. To run metadata extraction and other capabilities on a recurring schedule, configure schedules on the **Schedule** tab.

Configure metadata extraction

When you configure the Salesforce catalog source, you choose a runtime environment, define filters, and enter configuration parameters for metadata extraction.

If you plan to extract large volumes of metadata, check the **API Requests, Last 24 Hours** value in the Salesforce application to see the total API usage consumed for the last 24 hours and your organization's daily limit.

1. In the **Connection and Runtime** area, choose a serverless runtime environment or the Secure Agent group where you want to run catalog source jobs.

   Note: Serverless runtime environment options are available if the catalog source works with a serverless runtime environment.

2. Choose to retain, delete, or deprecate objects that are deleted from the source system in the catalog with the **Metadata Change Option**.

   - **Retain**. Retains objects that are deleted from the source system in the catalog. If you update or add a filter, the catalog retains objects extracted from the previous job and extracts additional objects that match the current filter. Objects deleted from the source system are not deleted from the catalog. Enrichments added on deleted objects and relationships are retained.
   - **Delete**. Deletes metadata from the catalog based on objects deleted from the source system and changes you make to the filter. Enrichments added on deleted objects and relationships are also permanently lost. Objects renamed in the source system are removed and recreated in the catalog.
   - **Deprecate**. When objects are deleted from the source system, the catalog changes the lifecycle of the imported objects to Obsolete. The lifecycle of objects also changes to Obsolete when you add exclusion filters or reduce the scope so that objects extracted in earlier jobs are no longer included. For example, the first job includes the sales schema. The second job also includes the sales schema, but excludes the sales.transactions table. In this case, the second job marks the sales.transactions object as Obsolete, even though the first job includes it. This does not impact enrichments applied to deprecated objects and relationships. Objects renamed in the source system are removed and recreated in the catalog. When you run the catalog source job again for other capabilities such as data classification, relationship discovery, or glossary association, the job doesn't consider obsolete objects. Obsolete objects remain in the catalog until they are purged when you run a **Purge Obsolete Objects** job on the **Explore** page.

   Note: You can also change the configured metadata change option when you run a catalog source.

3. In the **Filters** area, define one or more filter conditions to apply for metadata extraction:

   a. Select **Yes** to view filter options.

   b. From the Include/Exclude list, choose to include or exclude metadata based on the filter parameters.

   c. From the Object type list, select **CRM**, **Data 360**, or **Flows**.

   d. From the Filter criteria, select the object that you want to extract metadata from.


      - For CRM object type, select **Object, using API name** or **ListView, using API name** as the filter criteria.
      - For Data 360 object type, select **All types**, **Calculated Insight**, **Data Lake Object**, **Data Model Object**, **Data Stream**, **Data Transform**, or **Identity Resolution** as the filter criteria.
      - For Flows object type, select **All Types** as the filter criteria.

   e. Enter a value to specify the object location.

Filters can contain the following wildcards:

- Question mark. Represents a single character.
- Asterisk. Represents multiple characters or empty text.

When you enter values for filters, enclose them in double quotes if the value includes an asterisk or spaces before or after a string value.



Examples:

- To include or exclude metadata from all Salesforce CRM list views with the API name 'Finance', select **CRM** as the object type and **ListView, using API name** as the filter criteria, and then enter `Finance` in the value field.
- To include or exclude metadata from all Salesforce CRM objects with the API name that begins with 'Finance', select **CRM** as the object type and **Object, using API name** as the filter criteria, and then enter `Finance*` in the value field.
- To include or exclude metadata from all Salesforce Data 360 delta lake objects that begin with the name 'Account', select **Data 360** as the object type and **Data Lake Object** as the filter criteria, and then enter `Account*` in the value field.
- To include or exclude metadata from all Salesforce Data 360 calculated insights with names that start with 'SalesOrders' followed by a single character, select **Data 360** as the object type and **Calculated Insight** as the filter criteria, and then enter `SalesOrders?` in the value field.
- To include or exclude metadata from all Salesforce Flows metadata, select **Flows** as the object type and **All Types** as the filter criteria, and then enter `*` in the value field.
- To include or exclude metadata from all Salesforce Data 360 data model objects with names that start with 'Individual', along with the metadata from the associated data model mappings, select **Data 360** as the object type, and **Data Model Object** as the filter criteria, and then enter `Individual*` in the value field.

f. Optionally, to define an additional filter with an OR condition, click the **Add** icon.

4. Optional. In the **Configuration Parameters** area, enter additional settings.

   The following table describes the property that you enter for additional settings:

   Note: The **Additional Settings** section appears when you click **Show Advanced**.

Property	Description
Expert Parameters	Enter additional configuration options to be passed at runtime. Required if you need to troubleshoot the catalog source job. **Caution:** Use expert parameters when it is recommended by Informatica Global Customer Support.

5. Configure additional capabilities for the catalog source by clicking on the tabs.

Configure data profiling and quality

Enable the data profiling capability to evaluate the quality of metadata extracted from the Salesforce source system.

1. Click the **Data Profiling and Quality** tab.
2. Expand **Data Profiling** and select **Enable Data Profiling**.
3. In the **Connection and Runtime** area, choose the Secure Agent group where you want to run catalog source jobs.
4. Optionally, specify data profiling filters to run the profile on a subset of the metadata that you extract.
   a. Select **Yes** to view filter options.
   b. From the Include/Exclude list, choose to include or exclude metadata based on the filter parameters.
   c. From the Object type list, select **Salesforce Object**.
   d. Enter a value to specify the object location.

      Examples:

      - You extracted metadata from all Salesforce CRM objects and now you want to run a profile on objects that begin with the name, Finance. Select **CRM** from the Object type option, **Salesforce Object** from the Filter criteria option, and then enter `Finance*` in the input field.
      - You extracted metadata from all Salesforce Data 360 Data Lake objects and now you want to run a profile on all objects that begin with the name, Account. Select **Data 360** from the Object type option, **Data Lake Object** from the Filter criteria option, and then enter `Account*` in the input field.

      To include or exclude multiple objects, click the **Add** icon to add filters with the OR condition.
5. In the **Parameters** area, configure the parameters.

Parameter	Description
Modes of Run	Determines the type of data that you want the data profiling task to collect. Choose one of the following options: • **Keep Signatures Only**. Collects only aggregate information such as data types, average, standard deviation, and patterns. • **Keep Signatures and Values**. Collects both signatures and data values.
Profiling Scope	Determines whether you want to run data profiling only on the changes made to the source system or on the entire source system. Choose one of the following options: • **Incremental**. Includes only source metadata that is changed or updated since the last profile run. • **Full**. Includes the entire metadata that is extracted based on the filters applied for extraction.

Parameter	Description
Sampling Type	Determines the sample rows on which you want to run the data profiling task. Choose any of the following options: • **All Rows**. Runs data profiling on all rows in the metadata. • **Limit N Rows**. Runs data profiling on a limited number of rows. • **Custom Query**. Provides an SQL clause to select sample rows to run the data profiling task.
No of rows to limit	Required if you select Limit N Rows in Sampling Type. Specify the number of rows that you want to run the profile on. Default is 1000.
Sampling Query	Required if you select Custom Query in Sampling Type. Specify an SQL clause to select sample rows to run the data profiling task. For example, `WHERE Name__c = 'ABC Corporation'` The `Name__c` field name is the name of the Salesforce API.
Salesforce Data 360 Connection	Required if you want to run the data profiling task on Salesforce Data 360 objects. Select the Salesforce Data 360 connection that you created in Administrator.
Maximum Precision of String Fields	The maximum precision value to be used for profiling fields that include the string data type. Default is 50.
Text Qualifier	The character that defines string boundaries. If you select a quote character, profiling ignores delimiters within the quotes. Select a qualifier from the list. Default is Double Quote.

6. Expand **Data Quality** and select **Enable Data Quality**.

   Note: You can click **Use Data Profiling Parameters** to use the same parameters as in the **Data Profiling** section.

7. In the **Connection and Runtime** area, choose the Secure Agent group where you want to run catalog source jobs.
8. In the **Parameters** area, configure the parameters.

Parameter	Description
Data Quality Rule Automation	Enable the option to automatically create or update rule occurrences for data elements in the catalog source. Choose one of the following options: • **Apply on Data Elements linked with Business Dataset**. Creates rule occurrences for all data elements that are linked with business data sets in the catalog source. • **Apply on all Data Elements**. Creates rule occurrences for all data elements in the catalog source.
Data Quality Remediation	Enable the option to specify a flat file connection to store the list of failed rows so that users can remediate poor data quality scores. Choose one of the following options: • **No**. Doesn't enable the data quality failure ticket option. • **Yes**. Shows a list of flat file connections where you write failed rows to customer-managed locations.

Parameter	Description
Data Quality Failure Ticket	Specify whether you want to create data quality failure tickets for poor data quality scores based on the threshold defined for the rule occurrence in Data Governance and Catalog. Choose one of the following options: • **No**. Doesn't automatically create data quality failure tickets when the data quality scores are poor. • **Yes**. Automatically creates data quality failure tickets based on the data quality threshold values you define in Data Governance and Catalog, and notifies you when a data quality score is below the threshold. **Note:** You must configure a workflow event for the data quality failure and enable the event in Metadata Command Center.
Cache Result	Enable the option to generate a cache file in the runtime environment and preview the cached results faster in subsequent data preview runs. Choose one of the following options: • **Agent Cache**. Stores the results in the runtime environment cache for seven days by default after the first run. • **No Cache**. Doesn't store the preview results in the cache. You can only view live results.
Run Rule Occurrence Frequency	Specify whether you want to run data quality rules based on the frequency defined for the rule occurrence in Data Governance and Catalog.
Sampling Type	Determines the sample rows on which you want to run the data quality task. Choose one of the following options: • **All Rows**. Runs data quality on all rows in the metadata. • **Limit N Rows**. Runs data quality on a limited number of rows. • **Custom Query**. Provides an SQL clause to select sample rows to run the data quality task.
No of rows to limit	Required if you select **Limit N Rows** in Sampling Type. Specify the number of rows that you want to run the data quality task on. Default is 1000.
Sampling Query	Required if you select **Custom Query** in Sampling Type. Specify an SQL clause to select sample rows to run the data quality task. For example, `WHERE Name__c = 'ABC Corporation'` The `Name__c` field name is the name of the Salesforce API.
Salesforce Data 360 Connection	Required if you want to run the data quality task on Salesforce Data 360 objects. Select the Salesforce Data 360 connection that you created in Administrator.
Maximum Precision of String Fields	The maximum precision value to be used for fields that include the string data type. Default is 50.
Text Qualifier	The character that defines string boundaries. If you select a quote character, the data quality task ignores delimiters within the quotes. Select a qualifier from the list. Default is Double Quote.

Configure data observability

Enable the data observability capability to receive anomaly notifications for metadata extracted from the source system.

To include profiling anomalies, enable data profiling for the catalog source. For accurate results, set the **Profiling Scope** option to **Full** in the **Data Profiling and Quality** configuration.

1. Click the **Data Observability** tab.
2. Select **Enable Data Observability**.
3. In the **Parameters** area, enter a value to specify the minimum number of catalog source job runs required to start detecting anomalies. For example, if you enter a value of 5, then the job starts to detect anomalies from the sixth run.

   Note: This option does not apply to anomalies that require a minimum of two runs to generate.
4. Specify the maximum number of anomaly events to generate for each catalog source run. Default is 1000.
5. Optionally, in the **Asset Filters** area, enable filters to run data observability on specific assets.
   - Specify volume filters if you want to extract volume anomaly data for specific metadata extracted.
   - Specify data profiling filters if you want to override the data profiling filter and extract profiling anomalies for assets based on a different filter.
6. To add a volume filter, perform the following steps:
   a. Select **Yes** to view filter options.
   b. From the **Include/Exclude** list, choose to include or exclude metadata.
   c. Enter a value to specify the object location.

      For example, you want to observe volume metrics of a specific table from the schema extracted. Enter the schema name followed by the table name in the input field.
      Example: `Schema_Name.Table_Name`
   d. To include or exclude multiple objects, click the **Add** icon to add filters with the OR condition.
7. To add a data profiling filter, perform the following steps:
   a. Select **Yes** to view filter options.
   b. From the **Include/Exclude** list, choose to include or exclude metadata.
   c. From the **Specify data profiling filters** list, select an object type.
   d. Enter a value to specify the object location.

      For example, you ran a profile on multiple schemas, and now you want to generate profiling anomalies on a specific schema. Enter the schema name in the input field.
   e. To include or exclude multiple objects, click the **Add** icon to add filters with the OR condition.
8. Optionally, in the **Metric Filter** area, specify filters to generate events based on specific metrics. If you don't include a filter, the job detects both profiling and other anomalies applicable to the catalog source.
   a. Select **Filter conditions**.
   b. From the **Include Metric** list, choose to include or exclude a metric.
   c. From the **All Metrics** list, select a metric for which you want to generate events.
   d. From the **Sensitivity** list, select the sensitivity of the anomaly.
   e. From the **Select detection rules** list, select rules that you apply to detect anomalies.

The following table describes the detection rules that you can select:

Table 1.


Option	Description
Static Data	Detects the following anomalies: - Percentage variation. If percentage values other than 0% or 100% remain constant for three or more profile runs, any subsequent change generates a Percentage Variation anomaly. - Count variation. A change in a value that is usually constant indicates that there is an anomaly.
100% or 0% Change Detection	Detects the following anomalies: - Drop from maximum. A drop from 100% to a lower value generates a Drop from Maximum anomaly. - Surge from minimum. A spike from 0% to any higher value generates a Surge from Minimum anomaly.
Standard Deviation	Detects the following anomalies: - Drop in transition. A drop from a value that has been decreasing at a constant rate to a significantly lower value generates a Drop in Transition anomaly. - Surge in transition. A spike from a value that has been increasing at a constant rate to a significantly higher value generates a Surge in Transition anomaly. - Deviation. If the percentage values of a record change with each profile run, the algorithm calculates an expected range based on the changes observed in each profile run. A new value that falls outside of this expected range generates a Deviation anomaly.
Breaking Trends	Detect the following types of count-based anomalies: - Drop. A drop in a value that has been increasing to a lower value generates a Drop anomaly. - Surge. A spike in a value that has been decreasing to a higher value generates a Surge anomaly.

Configure data classification

Enable the data classification capability to identify and organize data into relevant categories based on the functional meaning of the data.

1. Click the **Data Classification** tab.
2. Select **Enable Data Classification**.
3. Choose one or both of the following options:
   - **Generated Data Classifications**. CLAIRE automatically generates data classifications for the data elements.

- **Data Classification Rules**. Choose from predefined or custom data classifications.
  1. Click **Add Data Classification**. The **Select Data Classifications** dialog box appears.



  2. Select the data classifications that you want to use.
  3. Click **OK**.

Configure relationship discovery

Enable the relationship discovery capability to identify pairs of similar columns and relationships between tables within a catalog source.

Before you configure relationship discovery, perform the following tasks:

- Import a relationship inference model. For more information about importing a relationship inference model, see " Import a relationship inference model" on page 17.
- Enable data profiling on the **Data Profiling and Quality** tab, and select **Keep Signatures and Values** as the run mode in the **Parameters** section. These configurations enable you to retain values of the columns in the profiling results and discover relationships.

1. Click the **Relationship Discovery** tab.
2. Select **Enable Relationship Discovery**.
3. In the **Column Similarity** area, select the **Relationship Inference Model**.

   Note: The relationship inference models that you imported appear in the **Relationship Inference Model** field.
4. In the **Joinable Tables Relationship** area, specify the **Containment Score Threshold** to identify joinable table relationships within the catalog source. This score is an indicator of the data overlap between any two given columns which determines whether the tables are joinable.

   Note: A higher score means that the objects have more overlapping data and a lower score means lesser overlapping data between the two objects. A containment score threshold lower than 0.4 might result in a large number of false positives.

After you run the catalog source job, you can view the inferred relationships on the **Relationships** tab of the extracted assets in Data Governance and Catalog.

Configure glossary associations

Enable the glossary association capability to associate glossary terms with technical assets, or to get recommendations for glossary terms that you can manually associate with technical assets in Data Governance and Catalog.

Metadata Command Center considers all published business terms in the glossary while making recommendations to associate your technical assets.

1. **Note:** Salesforce source systems can contain ambiguous data with technical field names. To generate accurate glossary associations, CLAIRE uses the extracted Label attribute for such technical field names.
1. Click the **Glossary Association** tab.
2. Select **Enable Glossary Association**.
3. Select **Enable auto-acceptance** to automatically accept glossary association recommendations.
4. Specify the **Confidence Score Threshold for Auto-Acceptance** to set a threshold limit based on which the glossary association capability automatically accepts the recommended glossary terms.

   Note: Specify a percentage from 80 to 100. If the score is higher than the specified limit, the glossary association capability automatically assigns a matching glossary term to the data element.
5. Select **Enable Below-threshold Recommendations** to receive glossary association recommendations below the auto-acceptance threshold. If you enable auto-acceptance, you can enable below-threshold recommendations to receive glossary recommendations below the auto-acceptance threshold.
6. Specify the **Confidence Score Threshold for Recommendations** to set a threshold based on which the glossary association capability makes recommendations

   If you enable auto-acceptance, specify a percentage from 80 to the selected auto-acceptance threshold. You can accept or reject the recommended glossary terms that fall within this range in Data Governance and Catalog.

   If you disable auto-acceptance, specify a percentage from 80 to 100 inclusive.
7. Choose to automatically assign business names and descriptions to technical assets. You can then choose to retain existing assignments and only assign business names and descriptions to assets that don't have assignments, or allow overwrite of existing assignments.

   By default, existing assignments are retained.
8. Optional. Choose to ignore specific parts of data elements when making recommendations. Select **Yes** and enter prefix and suffix keyword values as needed.

   Click **Select** to enter a keyword. You can enter multiple unique prefix and suffix keywords. Keyword values are case insensitive.
9. Optional. Choose specific top-level business glossary assets to associate with technical assets. Selecting a top-level asset selects its child assets as well. Select **Top-level Glossary Assets** and specify the assets on the **Select Assets** page.
10. Optional. Choose to use abbreviations and synonym definitions from lookup tables for accurate glossary association. Select **Yes** to enable, and then click **Select** to upload a lookup table.
11. Click **Next**.

    The **Associations** page appears.


Step 3. Associate stakeholders and asset groups

Associate users or user groups within a stakeholder role as stakeholders for technical assets in Data Governance and Catalog. Also, you can choose to assign technical assets extracted from the catalog source to asset groups. You can then use access policies to control permissions on assets that are assigned to asset groups.

Verify that the administrator assigned users and user groups to the stakeholder role that you want to associate with technical assets.

1. To associate users or user groups as stakeholders with technical assets extracted from the catalog source, perform the following steps:
   a. On the **Associations** page, click **Stakeholders**.
   b. Select **Assign Stakeholders**.
   c. Select a stakeholder role.
   d. Click **Select** to add users and user groups from the stakeholder role as stakeholders for the technical assets.

      The **Add Users & User Groups** dialog box displays a list of users and user groups assigned to the selected stakeholder role.




   e. Select one or more users or user groups to assign as stakeholders for the technical assets, and click **OK**.

      Only the selected users and user groups belonging to the specified stakeholder role are granted the permissions to technical assets.
   f. To assign users or user groups from another stakeholder role, click **Add** and then repeat the steps.
2. To assign asset groups to technical assets extracted from the catalog source, perform the following steps:
   a. On the **Associations** page, click **Asset Groups**.
   b. Select **Assign Asset Groups**.
   c. Click **Select**.

      The **Select Asset Groups** dialog box displays the list of asset groups.

   If you enabled an access policy that includes an asset group, you can only view assets that belong to that asset group.

3. Select the asset groups to which you want to assign technical assets extracted from the catalog source, and click **OK**.



4. Choose to save and run the job or to schedule a recurring job.
   - To save and run the job, click **Save** and then **Run**.
   - To schedule a recurring job, click **Next** to open the **Schedule** page.

Step 4. Run or schedule the job

Choose to run a catalog source job manually, or configure it to run on schedule.

Note: You can't run multiple jobs simultaneously.

You can choose to perform a full or an incremental metadata extraction. A full metadata extraction extracts all objects from the source to the catalog. An incremental metadata extraction extracts only the changed and new objects since the last successful catalog source job run. Incremental metadata extraction doesn't remove deleted objects from the catalog and doesn't extract metadata of code-based objects if applicable.

When you run an incremental metadata extraction job with a filter to include metadata from objects, the job extracts only the objects that have the latest timestamp since the last successful job.

Note: If incremental metadata extraction is available for the catalog source, the option is always visible, but incremental metadata extraction jobs can run only after a scheduled full metadata extraction job. Manual jobs do not enable the incremental metadata extraction option.

Run the job manually

Click **Save** to save the catalog source and click **Run**. On the **Run Catalog Source Job** window, click **Run** to run the job.

You can override the capabilities that you selected while configuring your catalog source on the **Configuration** page. The first time you run the catalog source job, the metadata extraction capability is mandatory. From the second run onwards, you can choose to override the configured metadata change option. You can retain, delete, or deprecate objects that are deleted from the source in the catalog. For subsequent runs of the catalog source job, the metadata extraction capability is optional.

Note: You can choose incremental metadata extraction for subsequent runs only after one full metadata extraction job completes successfully. Incremental metadata extraction jobs run with the **Retain** metadata change option even if you set the option to **Delete** or **Deprecate** in the catalog source.

Note: To run a catalog source job, you need permissions on the connection to the source system. To run a catalog source job for catalog sources that reference other source systems, you need permissions on the connections for all the reference source systems.

Run the job on a schedule

You can choose to run metadata extraction and other capabilities on a recurring schedule. You can't choose incremental metadata extraction and full metadata extraction in the same schedule. To create a schedule for incremental metadata extraction, you must have completed at least one full metadata extraction job successfully. If not, first create a schedule for a full metadata extraction.

If an incremental metadata extraction is scheduled to run when the last run details aren't available, the job first performs a full metadata extraction, followed by incremental metadata extraction on subsequent runs.

For example, this can happen in the following scenarios:

- You create schedules for both incremental metadata extraction and full metadata extraction, but schedule the incremental extraction to run before the first full metadata extraction job.
- You create schedules for both incremental metadata extraction and full metadata extraction, but delete the full metadata extraction schedule before its first run.

1. On the **Schedule** tab, select **Run on Schedule**.
   The **Schedule** configuration page opens.
2. Click the checkbox corresponding to each capability that you want to include in the schedule.
3. Enter the start date, time zone, and the interval at which you want to run the job.
4. You can manage additional schedules using the following options:
   - To create a new schedule, click the **Add** button.
   - To delete a schedule, click the **Delete** button.
   - To enable or disable a schedule, click the **Enable Schedule** toggle button.

   Note: You can create a maximum of one schedule per capability that you enable. If you purged a catalog source or did not run the metadata extraction job, the catalog source job runs metadata extraction before running other scheduled capabilities.

   Note: To create a schedule, you need permissions on the connection to the source system. If you lose permissions on the connection after you create a schedule, the scheduled jobs continue to run.
5. Click **Save** to save the schedule.

Monitor job status

After the job runs, you can monitor the status of the job on the **Overview** page of the job.

For more information about job monitoring, see *Administration*.

Step 5. Assign reference catalog source connections to endpoint catalog source objects

When you run the catalog source job, if the catalog source references another source system, a reference catalog source and connection get created that point to the reference source system. To view the complete

lineage for your catalog source, you can perform connection assignment from the reference catalog source connection to the objects in the reference source system. A reference source system might be a cloud service, such as Salesforce. You must first create and run an endpoint catalog source that connects to the reference source system.

Before you assign a connection, ensure that you have created and run an endpoint catalog source for each reference source system.
Note: If the source schema contains case-sensitive tables or if the reference objects contain multiple objects with the same name in different cases, perform case-sensitive connection assignment to get correct lineage.

If you enabled the lineage discovery capability for your catalog source, you can either curate the CLAIRE recommended endpoint objects on the **Related Catalog Sources** tab or assign connections manually.

For more information about related catalog sources and lineage discovery, see *Lineage discovery* in the *Administration* help.

1. On the **Configure** page, select the **Lineage** tab, and then select the **Lineage Discovery** tab. On the **Catalog Sources** panel, select the required catalog source and click the **Assign Connections** tab.

   The **Assign Connections** tab displays a list of assigned and unassigned connections along with details for each connection. Use filters to view the connections based on the connection names. Click the **Add Filter** menu to add filters.
2. Select the connection to the reference source system and click **Assign**.

   The connection name appears prefixed to the reference catalog source name on the **Hierarchy** tab of your catalog source in Data Governance and Catalog.

   The **Assign Connection** dialog box appears with a list of recommended objects from the endpoint catalog sources. Click **All** to view all endpoint catalog source objects.
3. In the **Assign Connection** dialog box, select one or more objects from the endpoint catalog sources and click **Assign**.

   You can filter the list in the **Assign Connection** dialog box by name, type, or endpoint.

   The following table lists the types of reference source systems that you can connect to and the class type that the endpoint objects must belong to:

   Table 2.

Reference source system	Endpoint object class type
Amazon Redshift	Database
Amazon S3	Database
Databricks	Database
File System	Database
Google BigQuery	Database
Google Cloud Storage	Database
Microsoft Azure Blob Storage	Database
Microsoft SQL Server	Database

Reference source system	Endpoint object class type
MySQL	Database
PostgreSQL	Database
Salesforce	Organization
Snowflake	Database
Workday	Database

When you click **Assign**, Metadata Command Center creates links between matching objects in the connected catalog sources, and it calculates the percentage of matched and unmatched objects. The higher the percentage of matched objects, the more accurate the lineage that you view in Data Governance and Catalog.

CHAPTER 4

View results in Data Governance and Catalog

After Metadata Command Center runs a job, you can view the results in Data Governance and Catalog where the catalog source and its elements are called technical assets. You can view a catalog source as a hierarchy. Expand each technical asset to see its components.

When referenced source systems are connected to a catalog source, you can expand the hierarchy to see details about the technical asset's component elements.

You can view the data lineage of an asset contained within a catalog source to see individual elements such as data sources, calculations, and filters. When you view data lineage, you can see the individual upstream elements that contribute data or expressions to each component of a data flow or catalog source.

View metadata extraction results


After a job runs in Metadata Command Center, view the results in Data Governance and Catalog. You can view details about source system contents in a hierarchical structure and trace data lineage.

1. Log in to Intelligent Data Management Cloud.

   The **My Services** page appears.

2. Click Data Governance and Catalog.

   The Data Governance and Catalog box appears on the **My Services** page.



3. On the Data Governance and Catalog home page, click the number in the **Technical Assets** panel.


   The **Technical Assets** page opens.

4. Select **Catalog Source** in the **Filter** list.

   The list of catalog sources opens.

5. Search for the catalog source from which you extracted metadata, and click the name.

   The **Overview** tab of the asset opens.



6. View the asset from different perspectives by clicking on the tabs.

For more information about working with assets, see Working with Assets in *Data Governance and Catalog* help.

View data lineage

Data lineage is a visual representation of the flow of data across the systems in your organization. Lineage depicts how the data flows from the system of its origin to the system of its destination.

Data lineage views are available for technical assets in the catalog source. You can view lineage at the catalog source, data set, or data element level.

The lineage at the catalog source level shows how data flows from one catalog source to another. The lineage at the data set and the data element levels show how other technical assets such as files or tables contribute to the selected asset.

If linking catalog sources is available for your catalog source, you can use Metadata Command Center to generate data lineage based on rules or by generating automated lineage with CLAIRE. You can choose source and target catalog sources and objects to link and generate lineage.

To determine whether linking catalog sources is available for your catalog source, navigate to the **Configuration** tab of the **Link Catalog Sources** page. The catalog source must appear in the list of source and target catalog sources.

For information about linking catalog sources, see *Link catalog sources* in the Administration help.

View lineage at the catalog source level

The catalog source level shows how data flows from one catalog source to another with the lineage aggregating data from the data set and data element levels.


To view data lineage at the catalog source level, open a technical asset, click the **Lineage** tab, and then verify that the level is set to **Catalog Source Level**.

View lineage at the data set level


The data set level displays individual sets of data in the data flow.

To view lineage at the data set level, open a technical asset, click the **Lineage** tab, and then verify that the level is set to **Data Set Level**.

The following image shows data set level lineage where the CustomerInfo_AmazonS3 target reference data set gets data from the customers-100.csv source reference data set before connection assignment:



The following image shows data set level lineage where the CustomerInfo_AmazonS3 target data set gets data from the customers-100.csv source data set after connection assignment:




After connection assignment, the referenced object icons change to specific object icons.

View lineage at the data element level

The data element level displays details of the data set level. At the data element level, you can see the input sources for expressions or commands and calculations or transformations on the data.

To view data lineage at the data element level, open a technical asset, click the **Lineage** tab, and then verify that the level is set to **Data Element Level**.

The following image shows data element level lineage where the City reference data element of the CustomerInfo_AmazonS3 reference data set gets data from the City reference data element of the customers-100.csv reference data set before connection assignment:



The following image shows data element level lineage where the City data element of the CustomerInfo_AmazonS3 reference data set gets data from the City data element of the customers-100.csv data set after connection assignment:




After connection assignment, the referenced object icons change to specific object icons.

View data profiling results

When you enable the data profiling task for a catalog source in Metadata Command Center, the system runs a profile to evaluate the quality of the metadata extracted from the source system. The profiling statistics appear in Data Governance and Catalog when you open the technical assets.

The scope of profiling statistics that Data Governance and Catalog displays depends on the data profiling configuration parameters that you set when you configured the catalog source in Metadata Command Center.

The following image shows the data profiling statistics that appear on a column asset page in Data Governance and Catalog:




For more information about data profiling results, see *Asset Details* in the Data Governance and Catalog help.

View data observability results

When you enable data observability for a catalog source in Metadata Command Center, you can view and evaluate the events that it generates in Data Governance and Catalog. These events indicate anomalies identified in the characteristics of the profiled data in your source system.

You can view the events that data observability generates for anomalies identified for catalog sources, technical data sets, and data elements. You can then take appropriate actions for the generated events.
Note: The administrator of the catalog source might have applied filters to the data to narrow down the data elements that are applicable for business users in Data Governance and Catalog. The data for which users receive anomaly notifications depend on the filters that are configured for the catalog source.

The following image shows the open events for a column asset in Data Governance and Catalog:




For more information about data observability results, see *Working With Assets* in the Data Governance and Catalog help.

View classified data

When you add data classification rules to a catalog source in Metadata Command Center, the system identifies the columns and tables that match the rules and displays one or more matched data classifications on the column or table asset pages in Data Governance and Catalog.

The following image shows a column asset page with the inferred data element classifications that match the column data and metadata:



For more information about data classification assets, see *Asset Details* in the Data Governance and Catalog help.


View glossary associations

When you enable the glossary association capability for a catalog source in Metadata Command Center, you can view the accepted glossary assets in Data Governance and Catalog.

The **Overview** tab for a technical asset in the catalog source displays glossary assets in the Accepted and CLAIRE Recommendations sections.

The **Glossaries** panel shows the automatically accepted and CLAIRE® recommended terms.

The following image shows a sample asset page:



APPENDIX A

Managing catalog sources

You can update, copy, delete, purge, and run a catalog source. You can also grant configuration permissions for catalog sources to different roles in your organization.

On the **Catalog Sources** page of the **Explore** page, you can select a catalog source to see its overview and related catalog sources. The **Overview** tab displays the capabilities, filters, stakeholders, asset groups, and schedules enabled for a catalog source. The **Related Catalog Sources** tab displays a list of related catalog sources that are either assigned manually using connection assignment or are curated based on CLAIRE recommendations using the lineage discovery capability. You can view related catalog sources and accept or reject CLAIRE recommendations for catalog sources that are run with the lineage discovery capability.

Cloning a catalog source configuration

You can clone the configuration of a catalog source to create another catalog source with the same configuration.

Note: Cloning doesn't copy the content of the catalog source.

1. In Metadata Command Center, go to the **Explore** page.
2. Select **Catalog Sources** from the menu.
3. You can clone a catalog source in one of the following ways:
   - Hover your mouse over the catalog source that you want to clone and click **Clone** from the **Action** menu.
   - Open the catalog source that you want to clone and click **Clone**.

   Note: By default, the cloned catalog source has the same name suffixed with _Clone. You can change the name if needed.
4. If needed, modify the configuration of the catalog source by updating the parameters on each tab.

   Cloning doesn't copy the content of sensitive fields. If the catalog source contains sensitive fields such as Client Secret, enter the values.
5. Click **Save**.

Deleting or purging a catalog source

Delete or purge a catalog source based on your business requirements.

When you delete a catalog source, you delete all the configuration specific to that catalog source, along with all the metadata that was extracted and any enrichment made to the associated metadata. Purging a catalog source deletes all the metadata that was extracted, along with any enrichment made to the associated metadata.

Note: Before you delete or purge a catalog source, manually unassign the connections that are assigned to that catalog source.

1. Go to the **Explore** page in Metadata Command Center.
2. Select **Catalog Sources** from the menu.
3. From the list of catalog sources, search for the catalog source that you want to delete or purge.
4. Click the **Action** menu, and select **Delete** or **Purge**.

   Note: You can't delete or purge a catalog source if the catalog source job is in the running state.
5. To confirm delete or purge, click **OK**.

   The catalog source is triggered to delete or purge. You can monitor the status of the job on the **Monitor** page.

   Note: If the deletion job succeeds, the catalog source disappears from Metadata Command Center. If it fails, some associated objects might still be present in Data Governance and Catalog. Such catalog sources continue to appear in the list of catalog sources in Metadata Command Center, but are marked as **Deleted**. Delete the catalog sources to remove them along with any remaining objects present in Data Governance and Catalog.

Purging obsolete objects from a catalog source

You can purge obsolete objects from a catalog source.

When you configure or run a catalog source, you can choose to deprecate objects that are deleted from a source system. If you delete objects from the source system or make changes to the filter, the objects imported into the catalog before the change move to the Obsolete lifecycle in the catalog. You can purge obsolete objects from a catalog source. This permanently deletes all objects with the Obsolete lifecycle status, along with associated enrichments, from the catalog.

1. Go to the **Explore** page in Metadata Command Center.
2. Select **Catalog Sources** from the menu.
3. From the list of catalog sources, search for the catalog source from which you want to purge obsolete objects.
4. Click the **Action** menu, and select **Purge Obsolete Objects**.

   A warning message appears on the page.
5. Click **Yes** to confirm.

   A confirmation message appears on the page and the purge job starts. You can monitor the status of the job on the **Monitor** page. If the job succeeds, all obsolete objects present in the catalog source disappear from the catalog.

   Note: If the job fails, some obsolete objects might remain in the catalog. To remove the remaining obsolete objects, run the purge job again.

Curating CLAIRE recommendations

You can view related catalog sources and accept or reject CLAIRE recommendations for a catalog source.

Applicable to catalog sources that generate lineage.

1. Go to the **Explore** page in Metadata Command Center.
2. Select **Catalog Sources** from the menu.
3. From the list of catalog sources, search for the catalog source for which you want to curate CLAIRE recommendations.
4. Hover your mouse over the catalog source and click **View Lineage Discovery** from the **Action** menu.

   Note: The **View Lineage Discovery** option is available for catalog sources that are run with the lineage discovery capability.

   The **Configure** page appears with the catalog source filtered on the **Lineage Discovery** tab of the **Lineage** tab.
   The **Related Catalog Sources** tab displays a list of related catalog sources.
5. Hover your mouse over a related catalog source and click **Accept** or **Reject** from the **Action** menu.

   For more information about lineage discovery and curating CLAIRE recommendations, see *Lineage discovery* in the *Administration* help.

Managing configuration permissions for catalog sources

As a service administrator, you can grant configuration permissions for catalog sources to different roles in your organization, and add specific users and user groups to those roles so that they can perform operational activities on a catalog source.

To manage permissions for catalog source configuration, verify that at least one role has the catalog source configuration **Set Permissions** functionality enabled for Metadata Command Center in Administrator. In Administrator, create the required roles, assign users and user groups to the roles, and specify appropriate permissions to the roles.

You can select roles and add specific users or user groups to those roles to grant the following levels of permission for catalog source configuration:


- Create
- Read
- Update
- Run
- Set Permissions

Based on the permissions granted to the roles, the selected users and user groups belonging to that role can perform appropriate operations for configuring catalog sources.

1. Go to the **Explore** page in Metadata Command Center.
2. From the list of catalog sources, search for the catalog source for which you want to manage permissions.


3. Click the **Action** menu, and select **Permissions**.

   The **Catalog Source Permissions** dialog box appears.




4. In the **Roles** panel, click **Add Roles**.

   The **Add Roles** dialog box appears.



5. Select one or more roles, and click **OK** to add the roles.
6. In the **Add Users & User Groups** panel, by default, all users and user groups that belong to the selected role are granted the role-defined permissions for the catalog source configuration.

To assign permissions only to the selected users and user groups that belong to this role, choose **Specific Users and User Groups**.



7. Select **Add Specific Users and User Groups**.

   The **Add Users & User Groups** dialog box displays the list of users and user groups that the administrator has assigned to the selected role.

8. Select one or more users or user groups to assign to the selected role, and click **OK**.

   Only the selected users and user groups belonging to the specified role will be granted the role-defined permissions for catalog source configuration.

9. View the assigned permissions for each user and or group, and click **Save**.