Informatica®

10.5.10

Enterprise Data Catalog REST API Reference

Informatica Enterprise Data Catalog REST API Reference
10.5.10
February 2026

© Copyright Informatica LLC 2017, 2025

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

Subject to your opt-out rights, the software will automatically transmit to Informatica in the USA information about the computing and network environment in which the Software is deployed and the data usage and system statistics of the deployment. This transmission is deemed part of the Services under the Informatica privacy policy and Informatica will use and otherwise process this information in accordance with the Informatica privacy policy available at https://www.informatica.com/in/privacy-policy.html. You may disable usage collection in Administrator tool.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices are included with the product.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

See patents at https://www.informatica.com/legal/patents.html.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-02-19

Table of Contents

Preface 9

Informatica Resources 9

- Informatica Network 9
- Informatica Knowledge Base 9
- Informatica Documentation 9
- Informatica Product Availability Matrices 10
- Informatica Velocity 10
- Informatica Marketplace 10
- Informatica Global Customer Support 10

Chapter 1: Overview 11

Enterprise Data Catalog REST API Overview 11

Prerequisites 12

Accessing the APIs 12

Chapter 2: Business Terms REST APIs 13

Business Terms REST APIs Overview 13

Business Terms APIs 13

- List Accepted Business Term 13
- Update Accepted Business Term 14
- Delete Accepted Business Term 15
- List Inferred Business Terms 16
- List Rejected Business Terms 17
- Update Rejected Business Terms 17
- Delete Rejected Business Terms 18

Chapter 3: Catalog Events REST APIs 20

Catalog Events REST APIs Overview 20

Catalog Events APIs 20

- List the Application Configuration 21
- Create or Update the Application Configuration 21
- List the Email Configuration 22
- Update Email Configuration 23
- List Application Events 24
- List Class Types for Application Events 26
- List Application Event Counts 27
- List Subscriptions 28
- Create or Update Subscriptions 29
- Delete Subscriptions 30
- List Subscription Details 30

Update Subscription Details. . . . 31
Delete Subscription Details. . . . 32
List Subscribers for an Object. . . . 33

Chapter 4: Data Provision APIs 35

Data Provision REST APIs Overview. . . . 35
Data Provision REST APIs. . . . 35
List Configured Connections. . . . 36
List the Configured Connection for a Connection ID. . . . 37
Validate a Test Connection. . . . 38
List Configured Connections for all Supported Resource Types. . . . 40
List Configured Connections for a Resource Type. . . . 41
List Data Provisioning Details. . . . 42
Preview Data for a Data Object. . . . 42
List Supported Resources for Data Provisioning. . . . 43
List Resources with Connection Details. . . . 44
List a Resource with Connection Details. . . . 45
Create or Update Resource Connection Configuration Options 45
Delete the Connection to the Resource. . . . 47
List All the Provisioning Tasks. . . . 48
Submit a Provisioning Task. . . . 48
List Provisioning Tasks for a Task ID. . . . 51
Delete a Provisioning Task. . . . 52
List Configured Informatica Intelligent Cloud Services Users. . . . 52
Create or Update Credentials for Enterprise Data Catalog Users. . . . 53
Create or Update Credentials for an Enterprise Data Catalog User. . . . 54
Delete an Enterprise Data Catalog User. . . . 56
Validate and Return the Informatica Intelligent Cloud Services User Details. . . . 56

Chapter 5: Lineage Filter APIs. . . . 58

Lineage Filter REST APIs Overview. . . . 58
Lineage Filter REST APIs. . . . 58
List the Default Lineage Filter. . . . 58
Create a Default Lineage Filter. . . . 59
Create a Lineage Filter. . . . 60
List a Lineage Filter Definition. . . . 61
Update a Lineage Filter. . . . 62
Delete a Lineage Filter Definition. . . . 64

Chapter 6: Model REST APIs. . . . 65

Model REST APIs Overview. . . . 65
Model Information APIs. . . . 65
List Association Kinds. . . . 66

Association Kind Details. . . . 67
List Associations. . . . 68
Association Kinds. . . . 69
List Attributes. . . . 70
Attribute Details. . . . 71
List Classes. . . . 71
Class Details. . . . 72
List Data Types. . . . 73
Data Type Details. . . . 74
List the Facet Definitions. . . . 74
List Field Facet Definitions. . . . 75
List a Field Facet Definition. . . . 76
List the Query Facet Definitions. . . . 77
List a Query Facet Definition. . . . 78
List Predefined Slider Facets. . . . 79
List a Slider Facet Definition. . . . 79
List Lineage Filters. . . . 80
List Reference Attributes. . . . 81
Reference Attribute Details. . . . 82
List Reference Data Types. . . . 83
Reference Data Type Details. . . . 83
List the Search Tabs. . . . 84
List the Definition for a Search Tab. . . . 85
Changing the Search Tab Order. . . . 86
Model Modification APIs. . . . 87
Create Custom Attributes. . . . 87
Update Custom Attribute. . . . 90
Delete Custom Attribute. . . . 93
Update a Class. . . . 94
Create a Field Facet Definition. . . . 95
Update a Field Facet Definition. . . . 96
Delete a Field Facet Definition. . . . 98
Create a Query Facet. . . . 99
Update a Query Facet. . . . 100
Delete a Query Facet Definition. . . . 102
Create a Slider Facet 103
Update a Slider Facet. . . . 104
Delete a Slider Facet. . . . 106
Create Custom Reference Attribute. . . . 107
Update a Custom Reference Attribute. . . . 109
Delete Custom Reference Attribute. . . . 112
Create a New Search Tab. . . . 113

Update a Search Tab. . . . 114
Delete a Search Tab Definition. . . . 116
Update the Search Tab Order. . . . 117

Chapter 7: Monitoring Info REST APIs. . . . 119

Monitoring Information REST APIs Overview. . . . 119
Monitoring Information REST APIs. . . . 119
List the Job Details. . . . 120
List the Details for a Job. . . . 122
List the Logs for a Job. . . . 122
Download the Logs Generated for a Job to a ZIP file. . . . 123
View a Job Status. . . . 124
Update the Job Status. . . . 125
List the Job Details about the Backup Job. . . . 125
Submit the Backup Job. . . . 127
List the Job Details for a Backup Job. . . . 129
Download the ZIP file of the Backup Job. . . . 129
List the Job Details for Object Export Jobs. . . . 130
Submit the Job Configuration to Export Objects. . . . 131
List the Job Configuration for an Object Export Job. . . . 133
Download the File with Object Export Jobs. . . . 133
List the Job Details for Object Import Jobs. . . . 134
Submit the Job Configuration to Import Objects. . . . 135
List the Job Configuration for an Import Job. . . . 136
List the Job Details for Resource Export Jobs. . . . 137
Submit the Job Configuration to Export Resources. . . . 138
List the Job Details for a Resource Export Job. . . . 140
Download the File with Resource Export Jobs. . . . 140
List the Job Details for a Resource Scan Log Job 141
Submit a Resource Scan Log Job. . . . 142
Download the Resource Scan Logs for a Job. . . . 144
List the Job Details for Search Export Jobs. . . . 144
Submit the Job Configuration to Export Search Results. . . . 146
List the Job Details for a Search Export Job. . . . 147
Download the Results File for a Search Export Job. . . . 148
List the Job Details for Service Log Jobs. . . . 149
Submit a Service Log Job. . . . 150
Download the Service Logs for a Job. . . . 152
Submit the Job Configuration to Export Data Domains. . . . 152
Download the Data Domain Export Logs for a Job. . . . 153
Submit the Job Configuration to Export Axon Assets. . . . 154
Download the Axon Asset Export Logs for a Job. . . . 155
Download the Results File for Relationship Export Job. . . . 156

Submit the Job Configuration to Export Relationships. . . . 157

Chapter 8: Object APIs. . . . 159

Object REST APIs Overview. . . . 159
Object Certification APIs. . . . 160
List the Certification Properties for an Object. . . . 160
Create or Update Certification Properties for an Object. . . . 161
Delete Certification Properties for an Object. . . . 162
Object Comments APIs. . . . 162
List the Comments for an Object. . . . 163
Create Comment. . . . 164
List a Specific Comment for an Object. . . . 165
Update Existing Comments for an Object. . . . 166
Delete Replies. . . . 167
List All the Replies for an Object. . . . 168
Create a Reply for a Comment. . . . 169
List a Specific Reply. . . . 169
Update a Specific Reply. . . . 170
Delete a Reply for a Comment. . . . 171
List the Aggregated Votes for a Reply. . . . 172
Create a Vote for a Reply to a Comment. . . . 173
Delete the Vote for a Reply. . . . 174
List the Aggregated Votes for a Comment. . . . 175
Create a Vote for a Comment. . . . 175
Delete the Votes for a Comment. . . . 176
Object Information APIs. . . . 177
Data Objects. . . . 178
Data Object IDs. . . . 180
Relationships. . . . 183
List the Catalog Search Results. . . . 186
List the Suggestions. . . . 189
Object Modification APIs. . . . 190
Data Objects Modification. . . . 190
Data Object Modification IDs. . . . 191
Object Reviews APIs. . . . 193
List All the Reviews and Ratings for an Object. . . . 193
Create a Review for an Object. . . . 194
List the Details for a Review. . . . 195
Update An Existing Review. . . . 196
Delete Reviews and Ratings for a Data Object. . . . 197
List the Aggregated Votes for a Review. . . . 198
Create a Vote for a Review. . . . 199
Delete Votes for a Review. . . . 200

Object Child Count REST API. 200
List the Child Count. 201

Chapter 9: Product Info REST API. 202

Product Information REST APIs Overview. 202
List Enterprise Data Catalog Details. 202

Chapter 10: Resource REST APIs. 203

Resource REST APIs Overview. 203
Resource Execution API. 203
Load Resource Job. 203
Resource Info API. 204
Monitor a Resource Job. 204

Chapter 11: Security REST API. 206

Security REST API Overview. 206
List Access Filters. 206

Chapter 12: Analytics APIs. 208

Analytics REST APIs Overview. 208
Accessing the APIs. 208
Analytics REST APIs. 208
List Chart Data. 209
List Hero Stats Data. 211

Chapter 13: Use Cases. 213

Sample Use Cases. 213
Retrieve Attribute Details. 214
Retrieve Attribute Details for a Class. 215
Retrieve Objects Using Object Name. 215
Retrieve Object Details Using Object ID. 216
Retrieve Relationships Between Objects. 216
Update Custom Attribute. 217
Update a Custom Attribute and Custom Reference Attribute for an Object. 218
Create Custom Attribute. 219
Create Reference Attribute. 220
Load Resource Job. 221
Monitor a Resource Job. 221

Preface

Refer to the *Informatica® Enterprise Data Catalog REST API Reference* for the REST API commands that you can use to perform tasks in Enterprise Data Catalog. The REST API reference also provides use cases and sample REST APIs.

This guide assumes that you have a good understanding of REST concepts and experience using REST APIs.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Network

The Informatica Network is the gateway to many resources, including the Informatica Knowledge Base and Informatica Global Customer Support. To enter the Informatica Network, visit https://network.informatica.com.

As an Informatica Network member, you have the following options:

- Search the Knowledge Base for product resources.
- View product availability information.
- Create and review your support cases.
- Find your local Informatica User Group Network and collaborate with your peers.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Product Availability Matrices

Product Availability Matrices (PAMs) indicate the versions of the operating systems, databases, and types of data sources and targets that a product release supports. You can browse the Informatica PAMs at https://network.informatica.com/community/informatica-network/product-availability-matrices.

Informatica Velocity

Informatica Velocity is a collection of tips and best practices developed by Informatica Professional Services and based on real-world experiences from hundreds of data management projects. Informatica Velocity represents the collective knowledge of Informatica consultants who work with organizations around the world to plan, develop, deploy, and maintain successful data management solutions.

You can find Informatica Velocity resources at http://velocity.informatica.com. If you have questions, comments, or ideas about Informatica Velocity, contact Informatica Professional Services at ips@informatica.com.

Informatica Marketplace

The Informatica Marketplace is a forum where you can find solutions that extend and enhance your Informatica implementations. Leverage any of the hundreds of solutions from Informatica developers and partners on the Marketplace to improve your productivity and speed up time to implementation on your projects. You can find the Informatica Marketplace at https://marketplace.informatica.com.

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:
https://www.informatica.com/services-and-training/customer-success-services/contact-us.html.

To find online support resources on the Informatica Network, visit https://network.informatica.com and select the eSupport option.

CHAPTER 1

Overview

This chapter includes the following topics:

- Enterprise Data Catalog REST API Overview, 11
- Prerequisites, 12
- Accessing the APIs, 12

Enterprise Data Catalog REST API Overview

Representational State Transfer (REST) Web Services provide interoperability between computers that communicate through internet. You can use a REST Web Service to interact with Web resources and perform updates on Web resources. A REST Web Service conforms to the principles of REST by being client-server oriented and stateless and uses the HTTP protocol and methods for communication. APIs that conform to the REST principles are known as REST APIs. You can use REST APIs to extract, create, modify or delete information in the system through REST Web Services. The REST APIs are created using Swagger specification.

You can use the Enterprise Data Catalog REST APIs to extract information from models and objects and update models and objects. The APIs expose the following concepts:

Model

A model defines the structure for the metadata that the scanner ingests in the catalog.

Data

Data represents the metadata ingested in the catalog.

Concepts Exposed by the Model

Attributes

A model property that you can set on an object as a fact.

Association

A model link that you can create between two objects.

Association Kinds

Types of associations.

Data Types

Types of attributes.

Classes

Types of objects.

Reference Attributes

Type of attribute that projects a value from a source object to a target object.

Concepts Exposed by Data

Object

An object is an asset in the catalog. The object includes facts and you can link an object to other objects. Scanners or users create facts and links.

Fact

An instantiated attribute of an object. For example, Created by and Modified by are facts.

Links

An instantiated association between two objects.

Prerequisites

Verify that you perform the following prerequisites before you use the REST APIs:

- Install Enterprise Data Catalog.
- Identify and install the HTTP client that you want to use to call the REST APIs.

Accessing the APIs

You can use the following URL to view the list of REST APIs exposed: `<CatalogAdmin>:<port>/access/swagger-ui.html#/`
`<CatalogAdmin>` represents the URL of the machine where you installed Catalog Administrator. `<port>` represents the port number configured for the Catalog Service.

You can use the following URL format to call the REST APIs: **<Type of HTTP method> http://<CatalogAdmin>:<port>/access/2/catalog/models/<REST API>.** The **models** directory includes all the REST APIs exposed for retrieving and updating information related to models. You can replace the models directory with **data** directory to call the REST APIs exposed to retrieve information about objects.

For example, to call the REST API **GET 2/catalog/models/associationKinds**, use the following URL: **GET http://<CatalogAdmin>:<port>/access/2/catalog/models/associationKinds**

You can use any standard HTTP client or use the Java client provided with Enterprise Data Catalog to call the REST APIs.

You can download the Java client and the source files with the Javadocs from the following locations:

- Java client. `<CatalogAdmin>:<port>/access/2/files/client.jar`
- Source files and Javadocs. `<CatalogAdmin>:<port>/access/2/files/client-sources.jar`

CHAPTER 2

Business Terms REST APIs

This chapter includes the following topics:

- Business Terms REST APIs Overview, 13
- Business Terms APIs, 13

Business Terms REST APIs Overview

To return, update, or delete an accepted, inferred, or rejected business term, you can use the Business Terms REST APIs.

Business Terms APIs

You can use the following Business Term REST APIs for accepted, inferred, or rejected business term:

Catalog Events REST API	Description
GET /data/objects/{id}/acceptedBusinessTerm	Lists the accepted business term for the specified object
PUT /data/objects/{id}/acceptedBusinessTerm	Updates the accepted business term
DELETE /data/objects/{id}/acceptedBusinessTerm	Deletes the accepted business term
GET /data/objects/{id}/inferredBusinessTerms	Lists the inferred business terms
GET /data/objects/{id}/rejectedBusinessTerms	Lists the rejected business term
PUT /data/objects/{id}/rejectedBusinessTerms	Updates the rejected business term
DELETE data/objects/{id}/rejectedBusinessTerms	Deletes the business term

List Accepted Business Term

Use the List Accepted Business Term API to list the accepted business terms for the specified object.

The API supports the GET method.

GET request

To list the accepted business terms for the specified object, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/acceptedBusinessTerm
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String

Response Codes

Code	Reason
200	Listed the accepted business term for the specified object.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/323/
acceptedBusinessTerm" -H  "accept: application/json"
```

Update Accepted Business Term

Use the Update Accepted Business Term API to update the accepted business term for the specified object.

The API supports the PUT method.

PUT request

To update the accepted business term for the specified object, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/data/objects/{id}/acceptedBusinessTerm
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
object	Required. Reference to an object resource.	Body	-
If-Match	Optional. Enter a value to display the results that match the value. Do not update if the entity tag or Etag for the resource has changed.	Header	String

Response Codes

Code	Reason
200	Business term accepted.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/332/
acceptedBusinessTerm" -H  "accept: application/json" -H  "Content-Type: application/
json" -d "{  \"id\": \"2\",  \"readOnly\": false}"
```

Delete Accepted Business Term

Use the Delete Accepted Business Term API to delete the accepted business term for the specified object.

The API supports the DELETE method.

DELETE request

To delete the accepted business term for the specified object, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/data/objects/{id}/acceptedBusinessTerm
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the object.	Path	String

Response Codes

Code	Reason
200	Deleted business term.
204	No content.
400	Missing or invalid parameter.
401	Missing credentials.

Code	Reason
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/222/
acceptedBusinessTerm" -H  "accept: application/json"
```

List Inferred Business Terms

Use the List Inferred Business Terms API to retrieve the details of the inferred business terms for the specified data object.

The API supports the GET method.

GET request

To retrieve the details of the inferred business terms for the specified data object, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/inferredBusinessTerms
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object	Path	String

Response Codes

Code	Reason
200	Listed the details of the inferred business terms.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/332/
inferredBusinessTerms" -H  "accept: application/json"
```

List Rejected Business Terms

Use the List Rejected Business Terms API to list the rejected business terms for the specified data object.

The API supports the GET method.

GET request

To list the rejected business terms for the specified data object, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/rejectedBusinessTerms
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
offset	Optional. The offset position from which the association types must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Listed the rejected business terms for the specified object.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/432/
rejectedBusinessTerms?offset=0&pageSize=20" -H  "accept: application/json"
```

Update Rejected Business Terms

Use the Update Rejected Business Terms API to update the rejected business term for the specified object.

The API supports the PUT method.

PUT request

To update the rejected business term for the specified object, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/data/objects/{id}/rejectedBusinessTerms
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
object	Required. Object references.	Body	-
If-Match	Optional. Enter a value to display the results that match the value. Do not update if the entity tag or Etag for the resource has changed.	Header	String

Response Codes

Code	Reason
200	Business term rejected.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
409	Conflict.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/12331/
rejectedBusinessTerms" -H  "accept: application/json" -H  "Content-Type: application/
json" -d "{  \"items\": [    {      \"id\": \"3\",      \"readOnly\": false    }  ]}"
```

Delete Rejected Business Terms

Use the Delete Rejected Business Terms API to delete the rejected business term for the specified object.

The API supports the DELETE method.

DELETE request

To delete the rejected business term for the specified object, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/data/objects/{id}/rejectedBusinessTerms
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
termId	Optional. IDs of rejected business terms to be deleted.	Query	Array [String]

Response Codes

Code	Reason
200	Deleted business term.
204	No content to display.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/33/
rejectedBusinessTerms?termId=" -H  "accept: application/json"
```

CHAPTER 3

Catalog Events REST APIs

This chapter includes the following topics:

- Catalog Events REST APIs Overview, 20
- Catalog Events APIs, 20

Catalog Events REST APIs Overview

To access, update, or delete the user configuration, email configuration, and user subscriptions, you can use the Catalog Events REST APIs.

Catalog Events APIs

You can use the following Catalog Events REST APIs for user configuration, email configuration, and user subscription:

Catalog Events REST API	Description
GET /configuration/app_events	Lists the user configuration for application events
PUT /configuration/app_events	Creates or updates the user configuration for application events
GET /configuration/email_events	Lists the user configuration for email notifications
PUT /configuration/email_events	Creates or updates the user configuration for email notifications
GET /data/app_events	Lists the events for the objects that the user subscribed
GET /data/app_events_class_types	Lists the class types of the events for the objects that the user subscribed
GET /data/app_events/count	Lists the unread event counts since the last read time
GET /data/subscriptions	Lists the user subscriptions for notifications
PUT /data/subscriptions	Creates or updates user subscriptions for multiple objects

Catalog Events REST API	Description
DELETE /data/subscriptions	Deletes the subscription of objects for a user
GET /data/subscriptions/{id}	Lists the user subscription details for the specified object
PUT /data/subscriptions/{id}	Creates or updates the user subscription details for the specified object
DELETE /data/subscriptions/{id}	Deletes the subscription details for the given subscription ID
GET /data/subscriptions/{id}/subscribers	Lists the subscribers for the specified object or subscription ID

List the Application Configuration

Use the List the Application Configuration API to list the user configuration for application events.

The API supports the GET method.

GET request

To list the user configuration for application events, submit a GET request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/configuration/app_events
```

Response Codes

Code	Reason
200	Listed the user configuration for application events.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/configuration/app_events" -H
"accept: application/json"
```

Create or Update the Application Configuration

Use the Create or Update the Application Configuration API to create or update the user configuration for application events.

The API supports the PUT method.

PUT request

To create or update the user configuration for application events, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/configuration/app_events
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
_configuration	Required. Configuration for application. Read events till the specified time. Best practice is to pass the value of the *until* field that you get from the output of the "List Application Events" on page 24 REST API.	Body	-
If-Match	Optional. Enter a value to display the results that match the value. Do not update if the entity tag or Etag for the resource has changed.	Header	String

Response Codes

Code	Reason
200	Updated the user configuration for application events.
201	Created the application configuration.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting update detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/configuration/app_events" -H
"accept: application/json" -H  "Content-Type: application/json" -d "{  \"until\": 0}"
```

List the Email Configuration

Use the List the Email Configuration API to list the user configuration for email notifications.

The API supports the GET method.

GET request

To list the user configuration for email notifications, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/configuration/email_events
```

Response Codes

Code	Reason
200	Listed the user configuration for email notifications.
400	Missing or invalid parameter.

Code	Reason
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/configuration/email_events" -
H  "accept: application/json"
```

Update Email Configuration

Use the Update Email Configuration API to create or update the user configuration for email notifications.

The API supports the PUT method.

PUT request

To create or update the user configuration for email notifications, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/configuration/email_events
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
_configuration	Required. Configuration for emails. Send emails at specified intervals. Enter one of the following frequency values: - EVERY_CHANGE - DAILY - WEEKLY - MONTHLY - NONE	Body	-
If-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Response Codes

Code	Reason
200	Updated the user configuration for email notifications.
400	Missing or invalid parameter.
401	Missing credentials.

Code	Reason
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting update detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/configuration/email_events" -H  "accept: application/json" -H  "Content-Type: application/json" -d "{  \"frequency\": \"EVERY_CHANGE\"}"
```

List Application Events

Use the List Application Events API to list the changes in change summary and events for the objects that you subscribed.

The API supports the GET method.

GET request

To list the changes in change summary and events for the objects that you subscribed, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/app_events
```

To list the changes in change summary, perform the following steps:

1. In the **Catalog Administrator**, open an existing resource or create a resource for which you want to list the change summary and events for objects.
2. On the **Metadata Load Settings** tab, enable the **Track Data Source** option.
3. Save and run the resource.
4. Repeat Step 1 through Step 3 for the rest of the required resources.
5. Use the `/access/2/catalog/data/app_events` API to list the changes in change summary and events for the objects in the resource.

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
since	Optional. Time from which the event count needs to be returned. If you do not provide a value, the API returns the event count from the point of last read.	Query	Integer
until	Optional. Time until which the event count needs to be returned. If you do not provide a value, the API returns the event count until the current time.	Query	Integer
objectId	Optional. The ID of the object to filter the events.		

Parameter	Description	Parameter Type	Data Type
objectName	Optional. The name of the object to filter the events.	Query	String
changeType	Required. Enter one or more change type of the events from the following list to filter the events: - INFERENCES_ANNOTATIONS - RESOURCE - COLLABORATION You must enter SOURCE as a changeType parameter.	Query	Array [String]
classType	Optional. The class type to filter the events. You must enter SOURCE as a classType parameter.	Query	Array [String]
resourceName	Optional. The resource name to filter the events.	Query	Integer
jobId	Optional. The job ID to filter the events.	Query	Integer
sortBy	Optional. Enter one of the following parameters: - createdOn. Lists the results based on resource create date from the latest to oldest by default . - objectName. Lists the results based on the object names from the latest to oldest by default. To list the results from oldest to latest, choose true for the ascending parameter.	Query	String
ascending	Optional. Sort the filter results in ascending or descending order. Default is false.	Query	Boolean
responseType	Optional. Select one of the following response types: - SIMPLE - DETAILED - EXPORT **Note:** Select DETAILED to view the changes in change summary. The eventCount property displays the number of changes in the change summary and events for the objects. Select EXPORT to export the change summary to a file.	Query	String
pageSize	Optional. Number of results to display in a page. Default is 20 results per page.	Query	Integer
offset	Optional. The offset position from which the API lists the results. Default is 0.	Query	Integer

Response Codes

Code	Reason
200	Listed the events for the objects that the user subscribed.
400	Missing or invalid parameter.
401	Missing credentials.

Code	Reason
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/app_events?
since=12122018&changeType=SOURCE&pageSize=20&offset=0" -H  "accept: application/json"
```

List Class Types for Application Events

Use the List Class Types for Application Events API to list the class types of events for the objects that the user subscribed.

The API supports the GET method.

GET request

To list the class types of events for the objects that the user subscribed, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/app_events_class_types
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
resourceName	Optional. The resource name to filter the events.	Query	Integer

Response Codes

Code	Reason
200	Listed the class types of the events for the objects that the user subscribed.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/app_events_class_types" -
H  "accept: application/json"
```

List Application Event Counts

Use the List Application Event Counts API to list the unread event counts since the last read time.

The API supports the GET method.

GET request

to list the unread event counts since the last read time, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/app_events/count
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
since	Optional. Time from which the event count needs to be returned. If you do not provide a value, the API returns the event count from the point of last read.	Query	Integer
until	Optional. Time until which the event count needs to be returned. If you do not provide a value, the API returns the event count until the current time.	Query	Integer
objectName	Optional. The name of the object to filter the events.	Query	String
changeType	Required. Enter one or more change type of the events from the following list to filter the events: - INFERENCES_ANNOTATIONS - RESOURCE - COLLABORATION	Query	Array [String]
resourceName	Optional. Resource name of the events to filter the events.	Query	Integer
jobId	Optional. Job ID of the events to filter the events.	Query	Integer

Response Codes

Code	Reason
200	Listed unread event counts since the last read time.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/app_events/count" -H
"accept: application/json"
```

List Subscriptions

Use the List Subscriptions API to list the user subscriptions for notifications.

The API supports the GET method.

GET request

To list the user subscriptions for notifications, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/subscriptions
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
objectId	Optional. The ID of the data object.	Query	Array [String]
resourceName	Optional. Resource name of the user subscription. **Note:** This parameter is ignored if you specify the object ID.	Query	Array [String]
classType	Optional. Class type of the user subscription. **Note:** This parameter does not apply if you specify the object ID.	Query	Array [String]
changeType	Optional. Change type of the user subscription. **Note:** This parameter does not apply if you specify the object ID.	Query	Array [String]
pageSize	Optional. Number of results to display in a page. By default, you can view 20 results per page.	Query	Integer
offset	Optional. The offset position from which the API lists the results. Default is 0.	Query	Integer

Response Codes

Code	Reason
200	Listed the user subscriptions for notifications.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting update detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/subscriptions?
objectId=3543&pageSize=20&offset=0" -H  "accept: application/json"
```

Create or Update Subscriptions

Use the Create or Update Subscriptions API to create or update user subscriptions for multiple objects.

The API supports the PUT method.

PUT request

To create or update user subscriptions for multiple objects, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/data/subscriptions
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
subscriptions	Required. Enter the subscription attributes for notifications on an object.	Body	-
If-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type
changeTypes	Required. Change type of the user subscription. Enter one of the following changeTypes: - SOURCE - INFERENCES_ANNOTATIONS - COLLABORATION - RESOURCE	String
objectId	Required. The ID of the data object.	String

Response Codes

Code	Reason
200	Updated the user subscriptions for multiple objects.
201	Created the subscriptions for multiple objects.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
409	Object has an existing subscription.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/data/subscriptions" -H
"accept: application/json" -H  "Content-Type: application/json" -d "{  \"items\":
[    {      \"changeTypes\": [        \"SOURCE\"      ],      \"objectId\":
\"111\"    }  ]}"
```

Delete Subscriptions

Use the Delete Subscriptions API to delete the subscription of objects for a user.

The API supports the DELETE method.

DELETE request

To delete the subscription of objects for a user, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/data/subscriptions
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
objectId	Required. The ID of the data object.	Query	Array [String]

Response Codes

Code	Reason
200	Deleted the subscription of objects for a user.
204	No content for the specified object ID.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/data/subscriptions?
objectId=342" -H  "accept: application/json"
```

List Subscription Details

Use the List Subscription Details API to list the user subscription details for the specified subscription ID.

The API supports the GET method.

GET request

To list the user subscription details for the specified subscription ID, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/subscriptions/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String

Response Codes

Code	Reason
200	Listed the subscription details for the specified subscription ID.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/subscriptions/423" -H
"accept: application/json"
```

Update Subscription Details

Use the Update Subscription Details API to update the user subscription details for the specified subscription.

The API supports the PUT method.

PUT request

To update the user subscription details for the specified subscription, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/data/subscriptions/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
subscription	Required. Enter the subscription details for an object.	Body	-
If-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type
changeTypes	Required. Change type of the user subscription. Enter one of the following changeTypes: - SOURCE - INFERENCES_ANNOTATIONS - COLLABORATION - RESOURCE	String
classType	Optional. Class type of the user subscription.	String
href	Optional. Link to the resource.	String
id	Optional. The unique ID of the resource.	String
objectId	Optional. The ID of the data object.	String
resourceName	Optional. The name of the resource.	String

Response Codes

Code	Reason
200	Updated the user subscription for the object.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting update detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/data/subscriptions/333" -H
"accept: application/json" -H  "Content-Type: application/json" -d "{  \"changeTypes\":
[    \"SOURCE\"  ],  \"classType\": \"1\", }"
```

Delete Subscription Details

Use the Delete Subscription Details API to delete the subscription details for the specified subscription ID. The subscription ID is same as the object ID.

The API supports the DELETE method.

DELETE request

To delete the subscription details for the specified subscription ID, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/data/subscriptions/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String

Response Codes

Code	Reason
200	Deleted the subscription details for the specified object.
204	No content to delete.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/data/subscriptions/423" -
H  "accept: application/json"
```

List Subscribers for an Object

Use the List Subscribers for an Object API to list the subscribers for the specified object ID or subscription ID.

The API supports the GET method.

GET request

To list the subscribers for the specified object ID or subscription ID, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/subscriptions/{id}/subscribers
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String

Response Codes

Code	Reason
200	Listed the subscribers for the specified object ID or subscription ID.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/subscriptions/231/
subscribers" -H  "accept: application/json"
```

CHAPTER 4

Data Provision APIs

This chapter includes the following topics:

- Data Provision REST APIs Overview, 35
- Data Provision REST APIs, 35

Data Provision REST APIs Overview

To create, update, list, or delete a data provisioning task, you can use Data Provision REST APIs.

Data Provision REST APIs

You can use the following Data Provision REST APIs to list, create, and delete data provisioning actions:

Data Provision REST API	Description
GET provision/connections	Lists the connections configured in an Informatica Intelligent Cloud Services organization
GET provision/connections/{id}	Lists the connections configured in an Informatica Intelligent Cloud Services organization for a connection ID
POST provision/connections/{id}/test	Creates a test connection
GET provision/connections/config	Lists the connection configuration option for all the supported types
GET provision/connections/config/{type}	Lists the connection configuration options for a supported type
GET provision/info	Lists whether data provisioning is available to user
GET provision/preview	Lists the preview data of a data object
GET provision/provisionableResources	Lists the resources that support data provisioning
GET provision/resources	Lists all the resources with connection details
GET provision/resources/{resourceName}	Lists the connections configured for a resource

Data Provision REST API	Description
PUT provision/resources/{resourceName}	Creates or updates the connection configuration for a resource
DELETE provision/resources/{resourceName}	Deletes the connection for a resource
GET provision/task	Lists all provisioning tasks
POST provision/task	Submits a provisioning task
GET provision/task/{id}	Lists the provisioning tasks for a task ID
DELETE provision/task/{id}	Deletes a provisioning task
GET provision/users	Lists the list of configured Informatica Intelligent Cloud Services users in the enterprise
PUT provision/users	Configures or updates the credentials of all the Informatica Intelligent Cloud Services users
PUT provision/users/{id}	Configures or updates the credentials of an Informatica Intelligent Cloud Services user
DELETE provision/users/{id}	Deletes an Informatica Intelligent Cloud Services user
POST provision/users/validate	Validates and returns the Informatica Intelligent Cloud Services user details

List Configured Connections

Use the List Configured Connections API to list all the configured connections in Informatica Intelligent Cloud Services.

The API supports the GET method.

GET request

To list all the configured connections in Informatica Intelligent Cloud Services, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/provision/connections
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
icsUsername	Required. The user name to log in to Informatica Intelligent Cloud Services.	Query	String
runTimeEnvId	Optional. The runtime environment ID to filter the connections.	Query	String
connType	Optional. Choose one of the following supported Informatica Intelligent Cloud Services connection types to filter the connections: - Oracle - SqlServer - Amazon S3 - Tableau Online	Query	String

Response Codes

Code	Reason
200	Listed Informatica Intelligent Cloud Service connections.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/connections?
icsUsername=testuser1" -H  "accept: application/json"
```

List the Configured Connection for a Connection ID

Use the List Configured Connection for a Connection ID API to list the configured connection in Informatica Intelligent Cloud Services for a connection ID.

The API supports the GET method.

GET request

To list the configured connection in Informatica Intelligent Cloud Services for a connection ID, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog//provision/connections/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
icsUsername	Required. The user name to log in to Informatica Intelligent Cloud Services.	Query	String
id	Required. The ID of the connection.	Path	String

Response Codes

Code	Reason
200	Listed Informatica Intelligent Cloud Services connections.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/connections/01100C?
icsUsername=testuser1" -H "accept: application/json"
```

Validate a Test Connection

Use the Validate a Test Connection API to validate a test connection for a connection ID in Enterprise Data Catalog.

The API supports the POST method.

POST request

To validate a test connection for a connection ID in Enterprise Data Catalog, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/provision/connections/{id}/test
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the connection.	Path	String
testRequest	Required. Enter the connection attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type	Values
configOptions	Optional. Configuration options for a connection.	-	Enter the following configuration options: - defaultValue - description - id - isEditable - isRequired - isRuntimeAttr - isSensitive - label - supportedValues - value
href	Optional. The link to the resource.	String	-
id	Required. The connection ID.	-	-
isAppendable	Optional. Allowed to create append target. Default is false.	Boolean	-
isCreatable	Optional. Allowed to create a target. Default is false.	Boolean	-
name	Optional. The name of the connection.	String	-
orgId	Optional. The ID of the organization.	String	-
runtimeEnvironmentId	Optional. The runtime environment used by the connection.	String	-
type	Optional. Enter one of the following connection types: - Oracle - SqlServer - Amazon S3 - Tableau Online	String	-
icsUsername	Required. The user name to log in to Informatica Intelligent Cloud Services.	String	-

Response Codes

Code	Reason
200	Created the test connection.
201	Created the test connection.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/connections/
334444440000000000PK/test" -H "accept: application/json" -H "Content-Type: application/
json" -d "{ \"connDetails\": { \"configOptions\": [{ \"id\": \"Access Key\", \"value\":
\"AKIAJCA\" }, { \"id\": \"Master Symmetric Key\", \"value\": \"COJ9oRl+G8Qv6em6e8kEY=
\" }, { \"id\": \"Secret Key\", \"value\": \"jocQFy08kJXP4VJPdQkk3\" } ], \"id\": \"0000K
\" }, \"icsUsername\": \"ams\"}"
```

List Configured Connections for all Supported Resource Types

Use the List Configured Connections for all Supported Resource Types API to list the connection configuration options for all the supported resource types.

The API supports the GET method.

GET request

To list the connection configuration options for all the supported resource types, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/provision/connections/config
```

Response Codes

Code	Reason
200	Listed the connection configuration options for the supported resource types.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/connections/config"
-H  "accept: application/json"
```

List Configured Connections for a Resource Type

Use the List Configured Connections for a Resource Type API to list the connection configuration options for a resource type.

The API supports the GET method.

GET request

To list the connection configuration options for a resource type, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/provision/connections/config/{type}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
type	Required. Enter one of the following connection types: - Azure DW - JDBC_IC - Amazon S3 - Hive Connector - Amazon Redshift v2 - Google Cloud Storage V2 - Microsoft Azure Blob Storage V3 - Teradata - Google Big Query V2 - SqlServer2016 - Tableau V3 - Qlik - Azure Data Lake Store Gen2 - SqlServer2012 - Oracle - Hadoop Files V2 - Salesforce - SqlServer2000 - SqlServer2005 - SqlServer2017 - SqlServer2019 - SqlServer2008 - SqlServer2014	Path	String

Response Codes

Code	Reason
200	Listed the configured connections for the supported type.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.

Code	Reason
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/connections/config/
Oracle" -H "accept: application/json"
```

List Data Provisioning Details

Use the List Data Provisioning Details API to list whether data provisioning is available.

The API supports the GET method.

GET request

To list whether data provisioning is available, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/provision/info
```

Response Codes

Code	Reason
200	Provided the data provisioning information.
400	Missing or invalid parameter
401	Missing credentials
403	User does not have the required access permissions
404	Requested object not found
429	Rate limit for requests encountered

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/info" -H  "accept:
application/json"
```

Preview Data for a Data Object

Use the Preview Data for a Data Object API to preview the data for a data object.

The API supports the GET method.

GET request

To preview the data for a data object, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/provision/preview
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
icsUsername	Required. The user name to log in to Informatica Intelligent Cloud Services.	Query	String
objectId	Required. The ID of the data object in Enterprise Data Catalog.	Query	String
connectionId	Required. The ID of the connection for the data object in Informatica Intelligent Cloud Services.	Query	String
configOpt	Required. Enter one or more user names and its associated passwords as key-value pairs in the following format: <key>:<value> For example, username:test1 password:test1	Query	Array [String]

Response Codes

Code	Reason
200	Listed the preview of data for the data object.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/preview?
icsUsername=testuser1&objectId=edittable&connectionId=3423&configOpt=username%3Auser1" -
H  "accept: application/json"
```

List Supported Resources for Data Provisioning

Use the List Supported Resources for Data Provisioning API to list the resources that support data provisioning.

The API supports the GET method.

GET request

To list the resources that support data provisioning, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/provision/provisionableResources
```

Response Codes

Code	Reason
200	Listed the resources that support data provisioning.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/
provisionableResources" -H "accept: application/json"
```

List Resources with Connection Details

Use the List Resources with Connection Details API to list the resources with the connection details.

The API supports the GET method.

GET request

To list the resources with the connection details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/provision/resources
```

Response Codes

Code	Reason
200	Listed the resources with the connection details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/resources" -H
"accept: application/json"
```

List a Resource with Connection Details

Use the List Resource with Connection Details API to list a resource and its connection details.

The API supports the GET method.

GET request

To list a resource and its connection details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/provision/resources/{resourceName}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
resourceName	Required. The name of the resource	Path	String

Response Codes

Code	Reason
200	Listed the resource with connection details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/resources/ora" -H
"accept: application/json"
```

Create or Update Resource Connection Configuration Options

Use the Create or Update Resource Connection Configuration Options API to create or update the connection configuration for a resource.

The API supports the PUT method.

PUT request

To create or update the connection configuration for a resource, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/provision/resources/{resourceName}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
resourceName	Required. The name of the resource.	Path	String
connConf	Required. Enter the attribute parameters.	Body	-
If-Match	Optional. Enter a value to display the results that match the value. Do not update if the entity tag or Etag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type	Values
connectionId	Required. The ID of the Informatica Intelligent Cloud Services connection.	String	-
href	Optional. Link to resource configuration.	String	-
icsUsername	Required. The user name to log in to Informatica Intelligent Cloud Services.	String	-
orgId	Required. The ID of the organization that the icsUsername belongs to.	String	
orgName	Required. The name of the organization.	String	-
resourceName	Required. The name of the resource	String	-

Response Codes

Code	Reason
200	Updated the connection configuration for a resource.
201	Created the connection configuration for a resource.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.

Code	Reason
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/provision/resources/ora" -H
"accept: application/json" -H  "Content-Type: application/json" -d "{  \"connectionId\":
\"345\",  \"icsUserName\": \"testuser1\",  \"orgId\": \"VB453B\",  \"orgName\":
\"Orc1\",  \"resourceName\": \"ora\"}"
```

Delete the Connection to the Resource

Use the Delete Resource Connection API to delete the connection to a resource.

The API supports the DELETE method.

DELETE request

To delete the connection to a resource, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/provision/resources/{resourceName}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
resourceName	Required. The name of the resource.	Path	String

Response Codes

Code	Reason
200	Deleted the connection to the resource.
204	No content.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/provision/resources/ora" -
H  "accept: application/json"
```

List All the Provisioning Tasks

Use the List All Provisioning Tasks API to list all the provisioning tasks in Enterprise Data Catalog.

The API supports the GET method.

GET request

To list all the provisioning tasks in Enterprise Data Catalog, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/provision/task
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
objectId	Optional. Enter one or more data object IDs.	Query	Array [String]
resourceName	Optional. Enter one or more resource names. Enterprise Data Catalog ignores this parameter if you enter an objectId.	Query	Array [String]

Response Codes

Code	Reason
200	Listed the provisioning tasks.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/task" -H  "accept: application/json"
```

Submit a Provisioning Task

Use the Submit a Provisioning Task API to submit a provisioning task in Enterprise Data Catalog.

The API supports the POST method.

POST request

To submit a provisioning task in Enterprise Data Catalog, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/provision/task
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
provisionTask	Required. Enter the provisioning task attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type	Values
createTarget	Required. Enter **true** to create a target. Enter **false** to append rows to an existing table.	Boolean	Enter one of the following values: - true - false
icsUsername	Required. The user name to log in to Informatica Intelligent Cloud Services.	String	-
objectId	Required. The ID of the source object.	String	-
orgId	Required. The ID of the organization that the icsUsername belongs to.	String	
srcDetails	Required. Enter the source configuration options.	-	Enter the following values: - configOptions - defaultValue - description - id - isEditable - isRequired - isRuntimeAttr - isSensitive - label - supportedValues - value - href - id - isAppendable - isCreatable - name - orgId - runtimeEnvironmentId - type Choose Oracle or SQLServer for the **type** parameter.

Parameter	Description	Data Type	Values
targetName	Required. Name of the target object. You do not need a target name if you want to append rows to an existing table, To create a table, enter a target name.	String	-
tgtDetails	Required. Enter the target configuration options.	-	Enter the following values: - configOptions - defaultValue - description - id - isEditable - isRequired - isRuntimeAttr - isSensitive - label - supportedValues - value - href - id - isAppendable - isCreatable - name - orgId - runtimeEnvironmentId - type Choose Oracle, Amazon S3, SQLServer, or Tableau Online for the **type** parameter.
truncateTarget	Required. Enter **false** to create a new asset or overwrite existing data. Enter **true** to append the data to an existing asset or create a new asset.	Boolean	Enter one of the following values: - true - false

Response Codes

Code	Reason
201	Submitted the provisioning task in Enterprise Data Catalog.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.

Code	Reason
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/task" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"createTarget\": true,
\"icsUsername\": \"testuser1\", \"objectId\": \"CSource://ORA/testuser1/CUSTOMER_MAIN\",
\"orgId\": \"testorg\", \"srcDetails\": { \"configOptions\": [ { \"id\": \"username\",
\"value\": \"testuser1\" }, { \"id\": \"password\", \"value\": \"testuser1\" } ], \"id
\": \"999000002\" }, \"tgtDetails\": { \"configOptions\": [ { \"id\": \"username\",
\"value\": \"testuser1@test123.com\" }, { \"id\": \"password\", \"value\":
\"testorg1\" } ], \"id\": \"999900007\" }, \"truncateTarget\": false}"
```

List Provisioning Tasks for a Task ID

Use the List Provisioning Tasks for a Task ID API to list the provisioning tasks for a task ID.

The API supports the GET method.

GET request

To list the provisioning tasks for a task ID, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/provision/task/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the task	Path	String

Response Codes

Code	Reason
200	Listed the provisioning task for the specified task.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/task/232" -H
"accept: application/json"
```

Delete a Provisioning Task

Use the Delete a Provisioning Task API to delete the provisioning task entry for a task ID.

The API supports the DELETE method.

DELETE request

To delete the provisioning task entry for a task ID, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/provision/task/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the provisioning task	Path	String

Response Codes

Code	Reason
200	Deleted the provisioning task entry.
204	No content.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/provision/task/124" -H
"accept: application/json"
```

List Configured Informatica Intelligent Cloud Services Users

Use the List Configured Informatica Intelligent Cloud Services Users API to list all the Informatica Intelligent Cloud Services users in your enterprise.

The API supports the GET method.

GET request

To list all the Informatica Intelligent Cloud Services users in your enterprise, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/provision/users
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
orgId	Optional. Enter one or more organization ID to filter the users.	Query	Array [String]
username	Optional. Enter one or more Informatica Intelligent Cloud Services user names to filter the users. Enterprise Data Catalog ignores this option if you enter an orgId.	Query	Array [String]

Response Codes

Code	Reason
200	Listed the Informatica Intelligent Cloud Services users in your enterprise.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/provision/users" -H  "accept: application/json"
```

Create or Update Credentials for Enterprise Data Catalog Users

Use the Create or Update User Credentials API to create or update the credentials for Enterprise Data Catalog users.

The API supports the PUT method.

PUT request

To create or update the credentials for Enterprise Data Catalog users, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/provision/users
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
users	Required. Enter the attribute parameters.	Body	-

Attribute Parameters

Parameter	Description	Data Type
href	Optional. The URL to access the secure agent.	String
icsUsername	Required. The username to log in to Informatica Intelligent Cloud Services.	String
orgId	Optional. The name of the orgID of the Informatica Intelligent Cloud Services user.	String
orgName	Optional. The name of the organization that the Informatica Intelligent Cloud Services user belongs to.	String
password	Required. The password of the Informatica Intelligent Cloud Services user.	String

Response Codes

Code	Reason
200	Created or updated the user details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/provision/users" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"items\": [ { \"icsUsername
\": \"amsh\", \"password\": \"abcd@1234\" } ]}"
```

Create or Update Credentials for an Enterprise Data Catalog User

Use the Create or Update User Credentials API to create or update the credentials for an Enterprise Data Catalog user.

The API supports the PUT method.

PUT request

To create or update the credentials for an Enterprise Data Catalog user, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/provision/users/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The user name of the Informatica Intelligent Cloud Services user.	Path	String
user	Required. Enter the attribute parameters.	Body	-
If-Match	Optional. Enter a value to display the results that match the value. Do not update if the entity tag or Etag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type
href	Optional. The URL to access the secure agent.	String
icsUsername	Required. The username to log in to Informatica Intelligent Cloud Services.	String
orgId	Optional. The name of the orgID of the Informatica Intelligent Cloud Services user.	String
orgName	Optional. The name of the organization that the Informatica Intelligent Cloud Services user belongs to.	String
password	Required. The password of the Informatica Intelligent Cloud Services user.	String

Response Codes

Code	Reason
200	Created or updated the user details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/provision/users/asfma" -H
"accept: application/json" -H "Content-Type: application/json" -d "{ \"icsUsername\":
\"asfma\", \"password\": \"abc@1234\"}"
```

Delete an Enterprise Data Catalog User

Use the Delete an Enterprise Data Catalog User API to delete an Enterprise Data Catalog user.

The API supports the DELETE method.

DELETE request

To delete an Enterprise Data Catalog user, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/provision/users/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the Enterprise Data Catalog user.	Path	String

Response Codes

Code	Reason
200	Deleted the specified Enterprise Data Catalog user.
204	No content.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/provision/users/33" -H
"accept: application/json"
```

Validate and Return the Informatica Intelligent Cloud Services User Details

Use the Validate Informatica Intelligent Cloud Services User Details API to validate and return the Informatica Intelligent Cloud Services user details.

The API supports the POST method.

POST request

To validate and return the Informatica Intelligent Cloud Services user details, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/provision/users/validate
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
users	Required. Enter the required user attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type
href	Optional. The URL to access the secure agent.	String
icsUsername	Required. The user name to log in to Informatica Intelligent Cloud Services.	String
orgId	Optional. The name of the orgID of the Informatica Intelligent Cloud Services user.	String
orgName	Optional. The name of the organization that the Informatica Intelligent Cloud Services user belongs to.	String
password	Required. The password of the Informatica Intelligent Cloud Services user.	String
nextCursorMark	Optional. When the request supports cursor pagination this parameter is populated. Deep pagination using cursors can be more efficient.	String
partialResults	Optional. Choose **true** if the response must not contain results from all the appropriate shards.	Boolean
totalCount	Optional. Total number of results.	Integer

Response Codes

Code	Reason
200	Validated and returned the Informatica Intelligent Cloud Services user details.
201	Created.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/provision/users/validate" -H
"accept: application/json" -H "Content-Type: application/json" -d "{ \"items\":
[ { \"icsUsername\": \"afsfa\", \"password\": \"abdc@1234\" } ] }"
```

CHAPTER 5

Lineage Filter APIs

This chapter includes the following topics:

- Lineage Filter REST APIs Overview, 58
- Lineage Filter REST APIs, 58

Lineage Filter REST APIs Overview

You can use Lineage Filter REST APIs to create, update, list, and delete a lineage filter.

Lineage Filter REST APIs

You can use the following Lineage Filter REST APIs to list, create, and delete lineage filters:

Data Provision REST API	Description
GET models/defaultLineageFilter	Lists the default lineage filter
POST models/defaultLineageFilter	Creates a default lineage filter
POST models/lineageFilter	Creates a lineage filter
GET models/lineageFilter/{id}	Lists a lineage filter definition
PUT models/lineageFilter/{id}	Updates a lineage filter definition
DELETE models/lineageFilter/{id}	Deletes a lineage filter definition

List the Default Lineage Filter

Use the List the Default Lineage Filter API to list the default lineage filter.

The API supports the GET method.

GET request

To list the default lineage filter, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/defaultLineageFilter
```

Response Codes

Code	Reason
200	Listed the default lineage filter
400	Missing or invalid parameter
401	Missing credentials
403	User does not have the required access permissions
404	Requested object not found
429	Rate limit for requests encountered

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/defaultLineageFilter" -
H "accept: application/json"
```

Create a Default Lineage Filter

Use the Create a Default Lineage Filter API to create a default lineage filter. When you run the API, it overwrites the existing default lineage filter.

The API supports the POST method.

POST request

To create a default lineage filter, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/models/defaultLineageFilter
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
lineageFilter	Required. The name of the default lineage filter.	Body	-

Response Codes

Code	Reason
200	Created the default lineage filter.
201	Created the default lineage filter
400	Missing or invalid parameter.

Code	Reason
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/models/defaultLineageFilter"
-H  "accept: application/json" -H  "Content-Type: text/plain" -d "\"string\""
```

Create a Lineage Filter

Use the Create a Lineage Filter API to create a lineage filter facet.

The API supports the POST method.

POST request

To create a lineage filter facet, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/models/lineageFilter
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
lineageFilter	Required. Enter the lineage filter facet attribute parameters.	Body	-

Attribute Parameters

Parameter	Description	Data Type	Values
excludeTypeFilter	Optional. The classes to exclude from the lineage filter facet.	String	Provide the following values: - classes - value
filterByDefault	Optional. Specifies whether the lineage filter facet is applied to all lineage queries. Default is true.	Boolean	Provide one of the following values: - true - false
global	Optional. Ignore users and groups so that the facet is visible to all users. Default is true.	String	-

Parameter	Description	Data Type	Values
leafFilter	Optional. The classes to include in the lineage filter facet.	String	Provide the following values: - classes - value
name	Required. The name of the facet.	String	-
owner	Optional. The user who owns the facet.	String	-
passThroughFilter	Optional. The classes to ignore in the lineage filter facet.	String	Provide the following values: - classes - value

Response Codes

Code	Reason
200	Updated the lineage filter facet
201	Created a lineage filter facet
400	Missing or invalid parameter
401	Missing credentials
403	User does not have the required access permissions
404	Requested object not found
412	Conflicting edit detected
429	Rate limit for requests encountered

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/models/lineageFilter" -H
"accept: application/json" -H  "Content-Type: application/json" -d
"{  \"excludeTypeFilter\": {    \"classes\": [      \"string\"    ]  },
\"filterByDefault\": true,  \"global\": true,  \"leafFilter\": {    \"classes\":
[      \"string\"    ]  },  \"name\": \"string\",  \"owner\": \"string\",
\"passThroughFilter\": {    \"classes\": [      \"string\"    ]  }}"
```

List a Lineage Filter Definition

Use the List a Lineage Filter Definition API to list a lineage filter facet definition.

The API supports the GET method.

GET request

To list a lineage filter facet definition, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/lineageFilter/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the lineage filter facet.	Path	String

Response Codes

Code	Reason
200	Listed the lineage filter facet definition.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/lineageFilter/
45345435" -H  "accept: application/json"
```

Update a Lineage Filter

Use the Update a Lineage Filter API to update a lineage filter.

The API supports the PUT method.

PUT request

To update a lineage filter, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/models/lineageFilter/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of lineage filter facet.	Path	String
facet	Required. Enter the facet attributes.	Body	-
if-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type	Values
excludeTypeFilter	Optional. The classes to exclude from the lineage filter facet.	String	Provide the following values: - classes - value
filterByDefault	Optional. Specifies whether the lineage filter facet is applied to all lineage queries. Default is true.	Boolean	Provide one of the following values: - true - false
global	Optional. Ignore users and groups so that the facet is visible to all users. Default is true.	String	-
leafFilter	Optional. The classes to include in the lineage filter facet.	String	Provide the following values: - classes - value
name	Required. The name of the facet.	String	-
owner	Optional. The user who owns the facet.	String	-
passThroughFilter	Optional. The classes to ignore in the lineage filter facet.	String	Provide the following values: - classes - value

Response Codes

Code	Reason
200	Updated the lineage filter facet
201	Created the lineage filter facet
400	Missing or invalid parameter
401	Missing credentials
403	User does not have the required access permissions
404	Requested object not found
412	Conflicting update detected
429	Rate limit for requests encountered

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/models/lineageFilter/45345" -
H  "accept: application/json" -H  "Content-Type: application/json" -d
"{  \"excludeTypeFilter\": {    \"classes\": [      \"string\"    ]  },
```

```
\"filterByDefault\": true,  \"global\": true,  \"leafFilter\": {    \"classes\":
[      \"string\"    ]  },  \"name\": \"string\",  \"owner\": \"string\",
\"passThroughFilter\": {    \"classes\": [      \"string\"    ]  }}"
```

Delete a Lineage Filter Definition

Use the Delete a Lineage Filter Definition API to delete a lineage filter definition.

The API supports the DELETE method.

DELETE request

To delete a lineage filter definition, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/models/lineageFilter/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the lineage filter.	Path	String

Response Codes

Code	Reason
200	Deleted the lineage filter.
204	No content to display.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/models/lineageFilter/
4534535" -H  "accept: application/json"
```

CHAPTER 6

Model REST APIs

This chapter includes the following topics:

- Model REST APIs Overview, 65
- Model Information APIs, 65
- Model Modification APIs, 87

Model REST APIs Overview

To access and update the Enterprise Data Catalog REST Web Services, you can use the Model REST APIs that are classified into the following categories:

- Model Information APIs
- Model Modification APIs

An administrator can create facets and search tabs, and can edit models.

Model Information APIs

You can use the following Model Information REST APIs to extract information from the model:

Model Information REST API	Description
GET models/associationKinds	Lists association types
GET models/associationKinds/{id}	Lists association type details
GET models/associations	Lists associations
GET models/associations/{id}	Lists association details
GET models/attributes	Lists attributes
GET models/attributes/{id}	Lists attribute details
GET models/classes	Lists classes

Model Information REST API	Description
GET models/classes/{id}	Lists class details
GET models/dataTypes	Lists data types
GET models/dataTypes/{id}	Lists data type details
GET models/facets	Lists the facet definitions
GET models/facets/fieldFacets	Lists the field facet definitions
GET models/facets/fieldFacets/{id}	Lists a field facet definition
GET models/facets/queryFacets	Lists the query facet definitions
GET models/facets/queryFacets/{id}	Lists a query facet definition
GET models/facets/sliderFacets/{id}	Lists the definition for a slider facet
GET models/facets/sliderFacets/{id}	Lists the predefined slider facets
GET models/lineageFilters	Lists the definitions for lineage filters
GET models/referenceAttributes	Lists reference attributes
GET models/referenceAttributes/{id}	Lists reference attribute details
GET models/referenceDataTypes	Lists reference data types
GET models/referenceDataTypes{id}	Lists reference data type details
GET models/searchTabs	Lists search tabs
GET models/searchTabs/{id}	Lists search tab definitions
GET models/searchTabs/order	Lists search tab order

List Association Kinds

Use the List Association Kinds API to list the types of association.

The API supports the GET method.

GET request

To list the types of association, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/associationKinds
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. The ID of the association. If you want to provide multiple IDs, verify that you provide each ID on another line.	Query	Array [String]
offset	Optional. The offset position from which the association types must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Listed association types.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/associationKinds?
id=34&offset=0&pageSize=20" -H  "accept: application/json"
```

Association Kind Details

Use the Association Kind Details API to list the association type details.

The API supports the GET method.

GET request

To list the association type details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/associationKinds/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. The ID of the association.	Path	String

Response Codes

Code	Reason
200	Listed association type details.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/associationKinds/334" -
H  "accept: application/json"
```

List Associations

Use the List Associations API to list the associations in Enterprise Data Catalog.

The API supports the GET method.

GET request

To list the associations in Enterprise Data Catalog, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/associations
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. The ID of the association. If you want to provide multiple IDs, verify that you provide each ID on another line.	Query	Array [String]
offset	Optional. The offset position from which the association types must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer
isA	Optional. Displays associations that inherit the specified association types.	Query	Array [String]

Response Codes

Code	Reason
200	Listed association types.
400	Missing or invalid parameter.

Code	Reason
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/associations?
id=32&offset=0&pageSize=20" -H  "accept: application/json"
```

Association Kinds

Use the Association Kinds API to list the details of an association.

The API supports the GET method.

GET request

To list the details of an association, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/associations/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the association.	Path	String

Response Codes

Code	Reason
200	Listed association types.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/associations/324" -H
"accept: application/json"
```

List Attributes

Use the List Attributes API to list the attributes in Enterprise Data Catalog.

The API supports the GET method.

GET request

To list the attributes in Enterprise Data Catalog, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/attributes
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. Enter one or more attribute IDs.	Query	Array [String]
classId	Optional. Enter one or more class IDs to filter the attributes.	Query	Array [String]
packageId	Optional. Enter the package ID to filter the attributes.	Query	Array [String]
name	Optional. Enter the name of the attribute to filter the attributes. You can also enter the package ID along with the name.	Query	Array [String]
resources	Optional. Enter the resource names to filter the attributes.	Query	Array [String]
offset	Optional. The offset position from which the attributes must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Listed the attributes.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/attributes?
id=342&offset=0&pageSize=20" -H  "accept: application/json"
```

Attribute Details

Use the Attribute Details API to list the details of an attribute.

The API supports the GET method.

GET request

To list the details of an attribute, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/attributes/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the attribute.	Path	String

Note: Use *com.infa.ldm.profiling.lastProfileTime* as the attribute ID to view the last time you ran a profile.

Response Codes

Code	Reason
200	Listed attribute details.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/attributes/321" -H
"accept: application/json"
```

List Classes

Use the List Classes API to list the classes in a model.

The API supports the GET method.

GET request

To list the classes in a model, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/classes
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. The ID of the class. If you want to provide multiple IDs, verify that you provide each ID on another line.	Query	Array [String]
offset	Optional. The offset position from which the association types must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer
isA	Optional. Displays classes that inherit the specified class types.	Query	Array [String]

Response Codes

Code	Reason
200	Listed association types.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/classes?
id=345&offset=0&pageSize=20" -H  "accept: application/json"
```

Class Details

Use the Class Details API to list the class details.

The API supports the GET method.

GET request

To list the class details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/classes/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the class.	Path	String

Response Codes

Code	Reason
200	Listed class details.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/classes/213" -H
"accept: application/json"
```

List Data Types

Use the List Data Types API to list the types of data.

The API supports the GET method.

GET request

To list the types of data, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/dataTypes
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. The ID of the data type. If you want to provide multiple IDs, verify that you provide each ID on another line.	Query	Array [String]
offset	Optional. The offset position from which the data types must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Listed association types.
400	Missing or invalid parameter.
401	Missing credentials.

Code	Reason
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/dataTypes?
id=256&offset=0&pageSize=20" -H  "accept: application/json"
```

Data Type Details

Use the Data Type Details API to list the types of association.

The API supports the GET method.

GET request

To list the types of association, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/dataTypes{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data type.	Path	String

Response Codes

Code	Reason
200	Listed association types.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/dataTypes/6786" -H
"accept: application/json"
```

List the Facet Definitions

Use the List the Facet Definitions API to list the facets that you can use in asset search in the catalog.

The API supports the GET method.

GET request

To list the facets that you can use in asset search in the catalog, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/facets
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. Enter one or more facet IDs.	Query	Array [String]
offset	Optional. The offset position from which the association types must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer
attributeId	Optional. Enter the attribute ID to use as a filter. The API returns the facets that reference the attribute ID.	Query	String

Response Codes

Code	Reason
200	Listed all the facets.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets?
offset=0&pageSize=20" -H "accept: application/json"
```

List Field Facet Definitions

Use the List Field Facet Definitions API to list the field facets that you can use to search for assets.

The API supports the GET method.

GET request

To list the field facets that you can use to search for assets, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/facets/fieldFacets
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. Enter one or more field facet IDs.	Query	Array [String]
offset	Optional. The offset position from which the association types must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Listed the field facet definitions.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/fieldFacets/
core.classType" -H "accept: application/json"
```

List a Field Facet Definition

Use the List a Field Facet Definition API to list the definition for a field facet.

The API supports the GET method.

GET request

To list the definition for a field facet, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/facets/fieldFacets/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the field facet.	Query	Array [String]

Response Codes

Code	Reason
200	Listed the field facet definition.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/fieldFacets/
asset1" -H "accept: application/json"
```

List the Query Facet Definitions

Use the List the Query Facet Definitions API to list the query facets that you can use to search for assets.

The API supports the GET method.

GET request

To list the query facets that you can use to search for assets, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/facets/queryFacets
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. Enter one or more predefined query facet IDs.	Query	Array [String]
offset	Optional. The offset position from which the association types must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Listed all the query facets.
400	Missing or invalid parameter.
401	Missing credentials.

Code	Reason
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/queryFacets?
offset=0&pageSize=20" -H "accept: applicat
```

List a Query Facet Definition

Use the List a Query Facet Definition API to list the definitions for a query facet.

The API supports the GET method.

GET request

To list the definitions for a query facet, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/facets/queryFacets/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the query facet.	Query	Array [String]

Response Codes

Code	Reason
200	Listed the query facet definition.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/queryFacets/
facet.query.collab.rating.any" -H "accept: application/json"
```

List Predefined Slider Facets

Use the List Predefined Slider Facets API to list all the predefined slider facets to search for assets.

The API supports the GET method.

GET request

To list all the predefined slider facets to search for assets, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/facets/sliderFacets
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. Enter one or more predefined slider facet IDs.	Query	Array [String]
offset	Optional. The offset position from which the slider facets must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Listed all the slider facets
401	Missing credentials
403	User does not have the required access permissions
404	Requested object not found
429	Rate limit for requests encountered

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/sliderFacets?
offset=0&pageSize=20" -H  "accept: application/json"
```

List a Slider Facet Definition

Use the List a Slider Facet Definition API to list the definition for a slider facet.

The API supports the GET method.

GET request

To list the definition for a slider facet, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/facets/sliderFacets/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the slider facet.	Path	String

Response Codes

Code	Reason
200	Listed the slider facet definition.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/sliderFacets/
534543" -H  "accept: application/json"
```

List Lineage Filters

Use the List Lineage Filters API to list the lineage filter definitions to use in lineage REST APIs.

The API supports the GET method.

GET request

To list the lineage filter definitions to use in lineage REST APIs, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/lineageFilters
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. Enter one or more lineage filter IDs.	Query	Array [String]
offset	Optional. The offset position from which the lineage filters must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Listed all the lineage filters.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/lineageFilters?
offset=0&pageSize=20" -H  "accept: application/json"
```

List Reference Attributes

Use the List Reference Attributes API to list the reference attributes.

The API supports the GET method.

GET request

To list the reference attributes, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/referenceAttributes
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. The ID of the reference attribute. If you want to provide multiple IDs, verify that you provide each ID on another line.	Query	Array [String]
classId	Optional. The ID of the class based on which you want to filter the reference attributes.	Query	Array [String]
packageId	Optional. Enter the package ID to filter the reference attributes.	Query	Array [String]
name	Optional. Enter the name of the reference attribute to filter the reference attributes. You can also enter the package ID along with the name.	Query	Array [String]
resources	Optional. Enter the resource names to filter the reference attributes.	Query	Array [String]
offset	Optional. The offset position from which the reference attributes must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Listed reference attributes.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/referenceAttributes?
id=234&classId=3&offset=0&pageSize=20" -H  "accept: application/json"
```

Reference Attribute Details

Use the Reference Attribute Details API to list the details of a reference attribute.

The API supports the GET method.

GET request

To list the details of a reference attribute, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/referenceAttributes{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the reference attribute.	Path	String

Response Codes

Code	Reason
200	Listed reference attribute types.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/referenceAttributes/
543" -H  "accept: application/json"
```

List Reference Data Types

Use the List Reference Data Types API to list reference data types.

The API supports the GET method.

GET request

To list reference data types, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/referenceDataTypes
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. The ID of the reference data type. If you want to provide multiple IDs, verify that you provide each ID on another line.	Query	Array [String]
offset	Optional. The offset position from which the reference data types must start for listing. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Listed reference data types.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/referenceDataTypes?
id=323&offset=0&pageSize=20" -H  "accept: application/json"
```

Reference Data Type Details

Use the Reference Data Type Details API to list the details of a reference data type.

The API supports the GET method.

GET referenceDataTypes{id}

To list the details of a reference data type, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/referenceDataTypes{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the reference data type.	Path	String

Response Codes

Code	Reason
200	Listed reference data type details.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/referenceDataTypes/34"
-H  "accept: application/json"
```

List the Search Tabs

Use the List the Search Tabs API to list the search tabs that you can access in Enterprise Data Catalog.

The API supports the GET method.

GET request

To list the search tabs that you can access in Enterprise Data Catalog, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/searchTabs
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Optional. Enter one or more search tab IDs.	Query	Array [String]
offset	Optional. The offset position from which the search tabs must start for listing. Default is 0.	Query	Integer

Parameter	Description	Parameter Type	Data Type
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	Integer
includeHidden	Optional. Select one of the options: - true. The API includes the hidden predefined search tabs in the search tab list. - false. The API does not include the hidden predefined search tabs.	Query	Boolean

Response Codes

Code	Reason
200	Listed all the accessible search tabs.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/searchTabs?
offset=0&pageSize=20" -H "accept: application/json"
```

List the Definition for a Search Tab

Use the List the Definition for a Search Tab API to list the definition for a search tab.

The API supports the GET method.

GET request

To list the definition for a search tab, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/searchTabs/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the search tab.	Query	Array [String]

Response Codes

Code	Reason
200	Listed the search tab definition
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/searchTabs/4t56" -H
"accept: application/json"
```

Changing the Search Tab Order

Use the Changing the Search Tab Order API to change the order of the search tabs.

The API supports the GET method.

GET request

To change the order of the search tabs, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/models/searchTabs/order
```

Response Codes

Code	Reason
200	Changed the order of the search tabs.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/models/searchTabs/order" -H
"accept: application/json"
```

Model Modification APIs

You can use the following Model Modification REST APIs to create, delete, or update information in the model:

Model Modification REST API	Description
POST models/attributes	Creates custom attributes
PUT models/attributes/{id}	Updates custom attributes
DELETE models/attributes/{id}	Deletes custom attributes
PUT models/classes/{id}	Update Class
POST models/facets/fieldFacets	Creates a field facet
PUT models/facets/fieldFacets/{id}	Updates field facet
DELETE models/facets/fieldFacets/{id}	Deletes a field facet definition
POST models/facets/queryFacets	Creates a query facet
PUT models/facets/queryFacets/{id}	Updates a query facet
DELETE models/facets/queryFacets/{id}	Deletes a query facet definition
POST models/facets/sliderFacets	Creates a slider facet
PUT models/facets/sliderFacets/{id}	Updates a slider facet
DELETE models/facets/sliderFacets/{id}	Deletes a slider facet definition
POST models/referenceAttributes	Creates custom reference attributes
DELETE models/referenceAttributes/{id}	Deletes custom reference attributes
PUT models/referenceAttributes/{id}	Updates custom reference attributes
POST models/searchTabs	Creates a search tab
PUT models/searchTabs/{id}	Updates a search tab
DELETE models/searchTabs/{id}	Deletes a search tab
PUT models/searchTabs/orderUpdate	Updates a search tab order

Create Custom Attributes

Use the Create Custom Attributes API to create or update a custom attribute.

The API supports the POST method.

POST request

To create or update a custom attribute, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/models/attributes
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
attribute	Required. Enter the attribute parameters for the custom attribute.	Body	Model

Attribute Parameters

Parameter	Description	Data Type	Values
analyzer	Optional. Classification for the custom attribute type.	String	Provide one of the following values: - INT - LONG - FLOAT - DOUBLE - BOOLEAN - DATE - STRING - TEXT_GENERAL - PATH_HIERARCHY
boost	Optional. The search ranking priority for the custom attribute.	String	Provide one of the following values: - LOWEST - LOWER - LOW - MEDIUM - HIGH
classes	Required. The list of classes with the custom attribute.	Array	Provide the list of classes in the following format: `classes": [ { "id": "string", } ]`
dataTypeId	Required. The ID of the model resource.	String	User to provide the ID.
description	Optional. Description for the custom attribute.	String	User to provide the description.
facetable	Optional. Choose **true** to use the attribute in facets and filter queries. Default is true.	Boolean	Provide one of the following values: - true - false
faceted	Optional. Choose **true** so that the catalog indexes the attribute to use it in facets and filter queries. By default, it is set to the *facetable* value.	Boolean	Provide one of the following values: - true - false

Parameter	Description	Data Type	Values
indexed	Optional. Choose **true** to use the attribute for advanced search queries. The catalog references and searches with the attribute in the format *attributeId:<query text>*. For example, when you set the **q** parameter as *q=core.name:customer* and choose **true** for the **indexed** parameter, the catalog searches for the word customer in the assets with the *core.name* attribute. By default, it is set to the *searched* value. **Note:** Re-index the attribute for advanced search If you change an existing attribute.	Boolean	Provide one of the following values: - true - false
multivalued	Optional. Specifies whether the custom attribute appears in the list of filters in Enterprise Data Catalog. Default is true.	Boolean	Provide one of the following values: - true - false
name	Required. The name of the custom attribute.	String	User to provide the name.
resources	Optional. List the resources to update the custom attribute.	-	Provide the following values: - assignmentType. Enter ALL, NONE, or LIST. - values. Enter the list of resources that are applicable only to LIST assignment type.
searchable	Optional. Choose **true** to include the attribute in basic search. Default is true.	Boolean	Provide one of the following values: - true - false
searched	Optional. Choose **true** so that Enterprise Data Catalog uses this attribute for basic queries. By default, it is set to the *searchable* value.	Boolean	Provide one of the following values: - true - false
sortable	Optional. Choose **true** to use the attribute for sorting. Default is true.	Boolean	Provide one of the following values: - true - false
sorted	Optional. Choose **true** so that the catalog indexes the attribute to sort assets. By default, it is set to the *sortable* value.	Boolean	Provide one of the following values: - true - false

Parameter	Description	Data Type	Values
suggestable	Optional. Choose **true** to include the attribute in suggestions. Default is true.	Boolean	Provide one of the following values: - true - false
suggested	Optional. Choose **true** so that the catalog includes matches to this attribute in suggestions. By default, it is set to the *suggestable* value.	Boolean	Provide one of the following values: - true - false

Response Codes

Code	Reason
201	Custom attribute created.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/models/attributes" -H
"accept: application/json" -H  "Content-Type: application/json" -d "{  \"items\":
[    {      \"analyzer\": \"INT\",      \"boost\": \"LOWEST\",      \"classes\":
[        {          \"3\": \"second\"        }      ],      \"dataTypeId\": \"a1\",
\"description\": \"Desc\",      \"facetable\": false,      \"multivalued\": false,
\"name\": \"string\",      \"searchable\": false,      \"sortable\": false,
\"suggestable\": false    }  ]}"
```

Update Custom Attribute

Use the Update Custom Attribute API to update a custom attribute. You must index the catalog after you use the API.

The API supports the PUT method.

PUT request

To update a custom attribute, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/models/attributes/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of custom attribute.	Path	String
attribute	Required. Enter the attribute parameters for the custom attribute.	Body	Model
if-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type	Values
analyzer	Optional. Classification for the custom attribute type.	String	Provide one of the following values: - INT - LONG - FLOAT - DOUBLE - BOOLEAN - DATE - STRING - TEXT_GENERAL - PATH_HIERARCHY
boost	Optional. The search ranking priority for the custom attribute.	String	Provide one of the following values: - LOWEST - LOWER - LOW - MEDIUM - HIGH
classes	Required. The list of classes with the custom attribute.	Array	Provide the list of classes in the following format: `classes": [ { "id": "string", } ]`
description	Optional. Description for the custom attribute.	String	User to provide the description.
faceted	Optional. Choose **true** so that the catalog indexes the attribute to use it in facets and filter queries. By default, it is set to the *facetable* value.	Boolean	Provide one of the following values: - true - false

Parameter	Description	Data Type	Values
indexed	Optional. Choose **true** to use the attribute for advanced search queries. The catalog references and searches with the attribute in the format *attributeId:<query text>*. For example, when you set the **q** parameter as *q=core.name:customer* and choose **true** for the **indexed** parameter, the catalog searches for the word customer in the assets with the *core.name* attribute. By default, it is set to the *searched* value. **Note:** Re-index the attribute for advanced search If you change an existing attribute.	Boolean	Provide one of the following values: - true - false
name	Required. The name of the custom attribute.	String	User to provide the name.
resources	Optional. List the resources to update the custom attribute.	-	Provide the following values: - assignmentType. Enter ALL, NONE, or LIST. - values. Enter the list of resources that are applicable only to LIST assignment type.
searched	Optional. Choose **true** so that Enterprise Data Catalog uses this attribute for basic queries. Default is true	Boolean	Provide one of the following values: - true - false
sorted	Optional. Choose **true** so that the catalog indexes the attribute to sort assets. Default is true	Boolean	Provide one of the following values: - true - false
suggested	Optional. Choose **true** so that the catalog includes matches to this attribute in suggestions. Default is true	Boolean	Provide one of the following values: - true - false

Response Codes

Code	Reason
201	Custom attribute updated.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.

Code	Reason
412	Conflicting update detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/models/attributes/34" -H
"accept: application/json" -H  "Content-Type: application/json" -d "{  \"analyzer\":
\"INT\",  \"boost\": \"LOWEST\",  \"classes\": [    {      \"1\": \"first\"    }  ],
\"description\": \"Updating first attribute\",  \"facetable\": false,  \"name\": \"attr
\"}"
```

Delete Custom Attribute

Use the Delete Custom Attribute API to delete a custom attribute.

The API supports the DELETE method.

DELETE request

To delete a custom attribute, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/models/attributes/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. ID of custom attribute.	Path	String

Response Codes

Code	Reason
200	Custom attribute deleted.
204	No content.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/models/attributes/234" -H
"accept: application/json"
```

Update a Class

Use the Update a Class API to update a class. You must index the catalog after you use the API.

The API supports the PUT method.

PUT request

To update a class, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/models/classes/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of custom attribute.	Path	String
classPutRequest	Required. Enter the attribute parameters.	Body	Model
if-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type	Values
indexed	Optional. Indexes the attribute. Default is true.	Boolean	Provide one of the following values: - true - false
searched	Optional. Specifies whether the class can be searched in the catalog. Default is true.	Boolean	Provide one of the following values: - true - false

Response Codes

Code	Reason
201	Custom attribute updated.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting update detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/models/classes/33" -H
"accept: application/json" -H "Content-Type: application/json" -d "{ \"indexed\": false,
\"searched\": false}"
```

Create a Field Facet Definition

Use the Create a Field Facet Definition API to create a field facet definition. When you create a field facet, you can specify one or more keywords to create the facet or filter.

The API supports the POST method.

POST request

To create a field facet definition, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/models/facets/fieldFacets
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
facet	Required. Enter the field facet attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type	Values
facetByDefault	Optional. Specifies whether the facet or filter has to be applied to all the basic queries. Default is true.	Boolean	Provide one of the following values: - true - false
field	Required. The attribute ID to create the facet or filter.	String	-
global	Optional. Ignore users and groups so that the facet is visible to all users. Default is true.	Boolean	Provide one of the following values: - true - false
group	Optional. The group that the facet belongs to. You can select one or more facets or filters in a group.	String	-
groupLabel	Required. The display name of the group	String	-
groups	Optional. The groups that can use the facet.	String	-
limit	Optional. The number of buckets*. The term **buckets** refers to the count of results for a particular field. For example, if 3 assets have a rating of 5, the bucket value of *rating 5* is 3.	String	-
mincount	Required. Returns the buckets if it has the minimum count. You cannot set a value lesser than 1 for **mincount** parameter.	Integer	-

Parameter	Description	Data Type	Values
name	Required. The name of the field facet.	String	-
owner	Optional. The user name who created the facet.	String	-
prefix	Optional. Creates buckets for terms which start with the configured prefix.	String	-
users	Optional. The users of the facet.	String	-

Response Codes

Code	Reason
201	Created field facet definition.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/fieldFacets" -
H "accept: application/json" -H "Content-Type: application/json" -d "{ \"facetByDefault
\": false, \"field\": \"com.infa.ldm.entity.collaboration.certified\", \"global\":
false, \"group\": \"UserFieldFacet\", \"groupLabel\": \"User Fields\", \"groups\": [],
\"limit\": 10, \"mincount\": 1, \"name\": \"Userfield02\", \"owner\": \"system\", \"users
\": [\"user2\"] }"
```

Update a Field Facet Definition

Use the Update a Field Facet Definition API to update a field facet definition.

The API supports the PUT method.

PUT request

To update a field facet definition, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/models/facets/fieldFacets/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. Enter the field facet ID.	Path	String
facet	Required. Enter the field facet attributes.	Body	-
if-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type	Values
facetByDefault	Optional. Specifies whether the field facet or filter has to be applied to all the basic queries. Default is true.	Boolean	Provide one of the following values: - true - false
field	Required. The attribute ID to create the facet or filter.	String	-
global	Optional. Ignore users and groups so that the facet is visible to all users. Default is true.	Boolean	Provide one of the following values: - true - false
group	Optional. The group that the facet belongs to. You can select one or more facets or filters in a group.	String	-
groupLabel	Optional. The display name of the group	String	-
groups	Optional. The groups that can use the facet.	String	-
limit	Optional. The number of buckets*. The term **buckets** refers to the count of results for a particular field. For example, if 3 assets have a rating of 5, the bucket value of *rating 5* is 3.	String	-
mincount	Optional. Returns the buckets if it has the minimum count. You cannot set a value lesser than 1 for **mincount** parameter.	Integer	-
name	Required. The name of the field facet.	String	-
owner	Optional. The user name who created the facet.	String	-
prefix	Optional. Creates buckets for terms which start with the configured prefix.	String	-
users	Optional. The users of the facet.	String	-

Response Codes

Code	Reason
201	Updated the field facet definition.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting update detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/fieldFacets/
f-7dfc1da2-30e9-425b-9010-c6023b53fe09" -H "accept: application/json" -H "If-Match:
"89462eaa04f877ac925149038ec14ea3"" -H "Content-Type: application/json" -d
"{ \"facetByDefault\": false, \"field\": \"com.infa.ldm.entity.collaboration.certified
\", \"global\": false, \"group\": \"UserFieldFacet\", \"groupLabel\": \"User Fields\",
\"groups\": [], \"limit\": 7, \"mincount\": 2, \"name\": \"Userfield02\", \"owner\":
\"system\", \"users\": [\"user2,user3\"] }"
```

Delete a Field Facet Definition

Use the Delete a Field Facet Definition API to delete a field facet definition.

The API supports the DELETE method.

DELETE request

To delete a field facet definition, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/models/facets/fieldFacets/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the field facet.	Path	String

Response Codes

Code	Reason
200	Field facet definition deleted.
204	No content.
401	Missing credentials.

Code	Reason
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/
fieldFacets/f-7dfc1da2-30e9-425b-9010-c6023b53fe09" -H "accept: application/json"
```

Create a Query Facet

Use the Create a Query Facet API to create a query facet. You can use the Apache Lucene query syntax to create or update a query facet. For more information, see the Apache Lucene documentation.

The API supports the POST method.

POST request

To create a query facet, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/models/facets/queryFacets
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
facet	Required. Enter the query facet definition attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type	Values
facetByDefault	Optional. Specifies whether the query facet or filter has to be applied to all the basic queries. Default is true.	Boolean	Provide one of the following values: - true - false
global	Optional. Ignore users and groups so that the facet is visible to all users. Default is true.	Boolean	Provide one of the following values: - true - false
group	Optional. The group that the facet belongs to. You can select one or more facets or filters in a group.	String	-
groupLabel	Optional. The display name of the group.	String	-

Parameter	Description	Data Type	Values
groupOrder	Optional. The query facets in a groupLabel in ascending or descending order.	Integer	Provide one of the following values: - 0. Displays in ascending order. - 1. Displays in descending order.
groups	Optional. The groups that can use the facet.	String	-
name	Required. The name of the field facet.	String	-
owner	Optional. The user name who created the facet.	String	-
q	Required. Use to create a query that searches matching objects. Uses Apache Lucene to interpret the query.	Query	String
users	Optional. The users who can use the facet.	String	-

Response Codes

Code	Reason
201	Query facet created.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/queryFacets" -
H "accept: application/json" -H "Content-Type: application/json" -d "{ \"name\":
\"UserQueryFacet\", \"groupLabel\": \"User Rating\", \"facetByDefault\": false, \"global
\": true, \"users\": [], \"groups\": [], \"owner\": \"system\", \"id\":
\"facet.query.collab.rating.any\", \"href\": \"/2/catalog/models/facets/queryFacets/
facet~2e~query~2e~collab~2e~rating~2e~any\", \"facetType\": \"QueryFacet\", \"q\":
\"com.infa.ldm.entity.collaboration.rating:[1.5 TO 3.5]\", \"groupOrder\": 3}"
```

Update a Query Facet

Use the Update a Query Facet API to update a query facet.

The API supports the PUT method.

PUT request

To update a query facet, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/models/facets/queryFacets/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. ID of the query facet definition.	Path	String
facet	Required. Enter the query facet attributes.	Body	-
if-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type	Values
facetByDefault	Optional. Specifies whether the query facet or filter can be applied to all the basic queries. Default is true.	Boolean	Provide one of the following values: - true - false
global	Optional. Ignore users and groups so that the query facet is visible to all users. Default is true.	Boolean	Provide one of the following values: - true - false
group	Optional. The group that the query facet belongs to. You can select one or more facets or filters in a group.	String	-
groupLabel	Required. The display name of the group.	String	-
groupOrder	Optional. The query facets in a groupLabel in ascending or descending order.	Integer	Provide one of the following values: - 0. Displays in ascending order. - 1. Displays in descending order.
groups	Optional. The groups that can use the facet.	String	-
name	Required. The name of the field facet.	String	-
owner	Optional. The user name who created the facet.	String	-
q	Required. Use to create a query that searches matching objects. Uses Apache Lucene to interpret the query.	Query	String
users	Optional. The users who can use the facet.	String	-

Response Codes

Code	Reason
201	Query facet definition updated.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting update detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/queryFacets/
q-93dec604-13e4-400c-b796-91848778a811" -H "accept: application/json" -H "If-Match:
"c4b10a5f05e3f7459dc4ceeed93df26f"" -H "Content-Type: application/json" -d "{ \"name\":
\"UserQueryFacet\", \"groupLabel\": \"User Rating\", \"facetByDefault\": false, \"global
\": true, \"users\": [], \"groups\": [], \"owner\": \"system\", \"id\":
\"facet.query.collab.rating.any\", \"href\": \"/2/catalog/models/facets/queryFacets/
facet~2e~query~2e~collab~2e~rating~2e~any\", \"facetType\": \"QueryFacet\", \"q\":
\"com.infa.ldm.entity.collaboration.rating:[2.0 TO 4.0]\", \"groupOrder\": 3}"
```

Delete a Query Facet Definition

Use the Delete a Query Facet Definition API to delete a query facet definition.

The API supports the DELETE method.

DELETE request

To delete a query facet definition, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/models/facets/queryFacets/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of a query facet definition.	Path	String

Response Codes

Code	Reason
200	Query facet definition deleted.
204	No content.
400	Missing or invalid parameter.

Code	Reason
401	Missing credentials.
403	User does not have the required access permissions,
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/
queryFacets/q-c604-13e4-400c-b796-91848778a811" -H "accept: application/json"
```

Create a Slider Facet

Use the Create a Slider Facet API to create a slider facet definition.

The API supports the POST method.

POST request

To create a slider facet definition, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/models/facets/sliderFacets
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
facet	Required. Enter the slider facet parameters.	Body	Model

Attribute Parameters

Parameter	Description	Data Type	Values
facetByDefault	Optional. Specifies whether the slider facet or filter has to be applied to all the basic queries. Default is true.	Boolean	Provide one of the following values: - true - false
field	Required. The attribute ID to create the facet.	String	-
global	Optional. Ignore users and groups so that the facet is visible to all users. Default is true.	Boolean	Provide one of the following values: - true - false
group	Optional. The group that the facet belongs to. You can select one or more facets or filters in a group.	String	-
groupLabel	Required. The display name of the group	String	-
groups	Optional. The groups that can use the facet.	String	-

Parameter	Description	Data Type	Values
name	Required. The name of the field facet.	String	-
owner	Optional. The user who created the facet.	String	-
users	Optional. The users of the facet.	String	-

Response Codes

Code	Reason
200	Slider facet
201	Created
400	Missing or invalid parameter
401	Missing credentials
403	User does not have the required access permissions
404	Requested object not found
429	Rate limit for requests encountered

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/sliderFacets" -
H  "accept: application/json" -H  "Content-Type: application/json" -d
"{  \"facetByDefault\": true,  \"field\": \"string\",  \"global\": true,  \"group\":
\"string\",  \"groupLabel\": \"string\",  \"groups\": [    \"string\"  ],  \"name\":
\"string\",  \"owner\": \"string\",  \"users\": [    \"string\"  ]}"
```

Update a Slider Facet

Use the Update a Slider Facet API to update a slider facet.

The API supports the PUT method.

PUT request

To update a slider facet, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/models/facets/sliderFacets/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. Enter the slider facet ID.	Path	String
facet	Required. Enter the slider facet attributes.	Body	-
if-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type	Values
facetByDefault	Optional. Specifies whether the slider facet or filter has to be applied to all the basic queries. Default is true.	Boolean	Provide one of the following values: - true - false
field	Required. The attribute ID to create the facet or filter.	String	-
global	Optional. Ignore users and groups so that the facet is visible to all users. Default is true.	Boolean	Provide one of the following values: - true - false
group	Optional. The group that the facet belongs to. You can select one or more facets or filters in a group.	String	-
groupLabel	Optional. The display name of the group	String	-
groups	Optional. The groups that can use the facet.	String	-
name	Required. The name of the slider facet.	String	-
owner	Optional. The user who created the facet.	String	-
users	Optional. The users of the facet.	String	-

Response Codes

Code	Reason
201	Updated the slider facet definition
400	Missing or invalid parameter
401	Missing credentials
403	User does not have the required access permissions
404	Requested object not found

Code	Reason
412	Conflicting update detected
429	Rate limit for requests encountered

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/sliderFacets/
453234" -H  "accept: application/json" -H  "Content-Type: application/json" -d
"{  \"facetByDefault\": true,  \"field\": \"string\",  \"global\": true,  \"group\":
\"string\",  \"groupLabel\": \"string\",  \"groups\": [    \"string\"  ],  \"name\":
\"string\",  \"owner\": \"string\",  \"users\": [    \"string\"  ]}"
```

Delete a Slider Facet

Use the Delete a Slider Facet API to delete a slider facet.

The API supports the DELETE method.

DELETE request

To delete a slider facet, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/models/facets/sliderFacets/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of slider facet.	Path	String

Response Codes

Code	Reason
200	Deleted the slider facet
204	No content
400	Missing or invalid parameter
401	Missing credentials
403	User does not have the required access permissions
404	Requested object not found
429	Rate limit for requests encountered

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/models/facets/
sliderFacets/5645643" -H  "accept: application/json"
```

Create Custom Reference Attribute

Use the Create Custom Reference Attribute API to create a custom reference attribute.

The API supports the POST method.

POST request

To create a custom reference attribute, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/models/referenceAttributes
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
attributes	Required. Enter the attribute parameters.	Body	Model

Attribute Parameters

Parameter	Description	Data Type	Values
analyzer	Optional. The classification for the custom reference attribute type.	String	Provide one of the following values: - INT - LONG - FLOAT - DOUBLE - BOOLEAN - DATE - STRING - TEXT_GENERAL - PATH_HIERARCHY
boost	Optional. The search ranking priority for the custom reference attribute.	String	Provide one of the following values: - LOWEST - LOWER - LOW - MEDIUM - HIGH
classes	Optional. The list of classes with the custom reference attribute.	Array	Provide the list of classes in the following format: `classes": [ { "id": "string", } ]`
id	Required. The ID of the model resource.	String	User to provide the ID.
description	Optional. Description for the custom reference attribute.	String	User to provide the description.

Parameter	Description	Data Type	Values
facetable	Optional. Choose **true** to use the attribute in facets and filter queries. Default is true.	Boolean	Provide one of the following values: - true - false
faceted	Optional. Choose **true** so that the catalog indexes the attribute to use it in facets and filter queries. By default, it is set to the *facetable* value.	Boolean	Provide one of the following values: - true - false
indexed	Optional. Choose **true** to use the attribute for advanced search queries. The catalog references and searches with the attribute in the format *attributeId:<query text>*. For example, when you set the **q** parameter as *q=core.name:customer* and choose **true** for the **indexed** parameter, the catalog searches for the word customer in the assets with the *core.name* attribute. By default, it is set to the *searched* value. **Note:** Re-index the attribute for advanced search If you change an existing attribute.	Boolean	Provide one of the following values: - true - false
multivalued	Optional. Specifies whether the custom reference attribute appears in the list of filters in Enterprise Data Catalog. Default is true.	Boolean	Provide one of the following values: - true - false
name	Required. The name of the custom reference attribute.	String	User to provide the name.
refDataTypeId	Required. The ID of the reference data type.	String	-
resources	Optional. List the resources to update the custom attribute.	-	Provide the following values: - assignmentType. Enter ALL, NONE, or LIST. - values. Enter the list of resources that are applicable only to LIST assignment type.
searchable	Optional. Choose **true** to include the attribute in basic search. Default is true.	Boolean	Provide one of the following values: - true - false
searched	Optional. Choose **true** so that Enterprise Data Catalog uses this attribute for basic queries. By default, it is set to the *searchable* value.	Boolean	Provide one of the following values: - true - false
sortable	Optional. Choose **true** to use the attribute for sorting. Default is true.	Boolean	Provide one of the following values: - true - false

Parameter	Description	Data Type	Values
sorted	Optional. Choose **true** so that the catalog indexes the attribute to sort assets. By default, it is set to the *sortable* value.	Boolean	Provide one of the following values: - true - false
suggestable	Optional. Choose **true** to include the attribute in suggestions. Default is true.	Boolean	Provide one of the following values: - true - false
suggested	Optional. Choose **true** so that the catalog includes matches to this attribute in suggestions. By default, it is set to the *suggestable* value.	Boolean	Provide one of the following values: - true - false

Response Codes

Code	Reason
201	Custom reference attribute created.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/models/referenceAttributes" -
H  "accept: application/json" -H  "Content-Type: application/json" -d "{  \"items\":
[    {      \"analyzer\": \"7\",      \"boost\": \"LOWEST\",      \"classes\":
[        {          \"98\": \"one\"        }      ],      \"description\": \"none
\",      \"facetable\": false,      \"multivalued\": false,      \"name\": \"one\",
\"refDataTypeId\": \"one\",      \"searchable\": false,      \"sortable\": false,
\"suggestable\": false    }  ]}"
```

Update a Custom Reference Attribute

Use the Update a Custom Reference Attribute API to update a custom reference attribute. You must index the catalog after you use the API.

The API supports the PUT method.

PUT request

To update a custom reference attribute, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/models/referenceAttributes/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of custom reference attribute.	Path	String
attribute	Required. Enter the attribute parameters.	Body	Model
if-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type	Values
analyzer	Optional. Classification for the custom reference attribute type.	String	Provide one of the following values: - INT - LONG - FLOAT - DOUBLE - BOOLEAN - DATE - STRING - TEXT_GENERAL - PATH_HIERARCHY
boost	Optional. The search ranking priority for the custom reference attribute.	String	Provide one of the following values: - LOWEST - LOWER - LOW - MEDIUM - HIGH
classes	Optional. The list of classes with the custom reference attribute.	Array	Provide the list of classes in the following format: `classes": [ { "id": "string", } ]`
id	Required. The ID of the model resource.	String	User to provide the ID.
description	Optional. Description for the custom reference attribute.	String	User to provide the description.
faceted	Optional. Choose **true** so that the catalog indexes the attribute to use it in facets and filter queries. By default, it is set to the *facetable* value.	Boolean	Provide one of the following values: - true - false

Parameter	Description	Data Type	Values
indexed	Optional. Choose **true** to use the attribute for advanced search queries. The catalog references and searches with the attribute in the format *attributeId:<query text>*. For example, when you set the **q** parameter as *q=core.name:customer* and choose **true** for the **indexed** parameter, the catalog searches for the word customer in the assets with the *core.name* attribute. By default, it is set to the *searched* value. **Note:** Re-index the attribute for advanced search If you change an existing attribute.	Boolean	Provide one of the following values: - true - false
name	Required. The name of the custom reference attribute.	String	User to provide the name.
resources	Optional. List the resources to update the custom attribute.	-	Provide the following values: - assignmentType. Enter ALL, NONE, or LIST. - values. Enter the list of resources that are applicable only to LIST assignment type.
refDataTypeId	Required. The ID of the reference data type.	String	-
searched	Optional. Choose **true** so that Enterprise Data Catalog uses this attribute for basic queries. Default is true	Boolean	Provide one of the following values: - true - false
sorted	Optional. Choose **true** so that the catalog indexes the attribute to sort assets. Default is true	Boolean	Provide one of the following values: - true - false
suggested	Optional. Choose **true** so that the catalog includes matches to this attribute in suggestions. Default is true	Boolean	Provide one of the following values: - true - false

Response Codes

Code	Reason
201	Custom reference attribute updated.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.

Code	Reason
412	Conflicting update detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/models/referenceAttributes/2"
-H  "accept: application/json" -H  "Content-Type: application/json" -d "{  \"analyzer\":
\"3\",  \"boost\": \"LOWEST\",  \"classes\": [    {      \"2\": \"none\"    }  ],
\"description\": \"none\",  \"facetable\": false,  \"name\": \"string\"}"
```

Delete Custom Reference Attribute

Use the Delete Custom Reference Attribute API to delete a custom reference attribute.

The API supports the DELETE method.

DELETE request

To delete a custom reference attribute, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/models/referenceAttributes/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. ID of custom reference attribute.	Path	String

Response Codes

Code	Reason
200	Custom attribute deleted.
204	No content.
401	Missing credentials.
403	User does not have the required access permissions,
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/models/
referenceAttributes/167" -H  "accept: application/json"
```

Create a New Search Tab

Use the Create a New Search Tab API to create a search tab.

The API supports the POST method.

POST request

To create a search tab, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/models/searchTabs
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
tab	Required. Enter the search tab attributes.	Body	Model

Attribute Parameters

Parameter	Description	Data Type	Values
fieldFilters	Optional. The field facets to apply to the tab.	String	Provide the following values: - facetId - value
global	Optional. Ignore users and groups so that the facet is visible to all users. Default is true.	String	-
groups	Optional. The groups that can use the facet.	String	-
isDefault	Optional. Specifies whether the tab is the default tab. Default is true.	Boolean	Provide one of the following values: - true - false
name	Required. The name of the tab.	String	-
order	Optional. Specifies the order to display the tab.	Integer	Provide one of the following values: - 0. Displays in ascending order. - 1. Displays in descending order.
owner	Optional. The user who owns the facet	String	-
queryFilters	Optional. The query facets to apply to the tab.	String	Enter the facetId value.
rootTo	Optional. Specifies whether the results are to be rooted to the parent level.	String	Provide one of the following values: - NONE - RESOURCE - DATA_SET

Parameter	Description	Data Type	Values
sliderFilters	Required. Specifies the slider facets to apply to the tab.	-	Provide the following values: - facetId - max - min
users	Optional. Specifies the users who can use the search tab.	String	-

Response Codes

Code	Reason
200	Created search tab.
201	Created search tab.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/models//searchTabs" -H
"accept: application/json" -H "Content-Type: application/json" -d "{ \"fieldFilters\":
[ { \"facetId\": \"string\", \"value\": \"string\" } ], \"global\": false, \"groups\":
[ \"string\" ], \"isDefault\": false, \"name\": \"string\", \"order\": 0, \"owner\":
\"string\", \"queryFilters\": [ { \"facetId\": \"string\" } ], \"rootTo\": \"NONE\",
\"users\": [ \"string\" ]}"
```

Update a Search Tab

Use the Update a Search Tab API to update a search tab.

The API supports the PUT method.

PUT request

To update a search tab, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/models/searchTabs/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of search tab.	Path	String
tab	Required. Enter the search tab attributes.	Body	-
if-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type	Values
fieldFilters	Optional. The field facets to apply to the tab.	String	Provide the following values: - facetId. - value
global	Optional. Ignore users and groups so that the facet is visible to all users. Default is true.	String	-
groups	Optional. The groups that can use the facet.	String	-
isDefault	Optional. Specifies whether the tab is the default tab. Default is true.	Boolean	Provide one of the following values: - true - false
name	Required. The name of the tab.	String	-
order	Optional. Specifies the order to display the tab.	Integer	Provide one of the following values: - 0. Displays in ascending order. - 1. Displays in descending order.
owner	Optional. The user who owns the facet.	String	-
queryFilters	Optional. The query facets to apply to the tab.	String	Enter the facetId value.
rootTo	Optional. Specifies whether the results are to be rooted to a parent level.	String	Provide one of the following values: - NONE - RESOURCE - DATA_SET

Parameter	Description	Data Type	Values
sliderFilters	Optional. The slider facets to apply to the tab.	String	Provide the following values: - facetId - max - min
users	Optional. Specifies the users who can use the search tab.	String	-

Response Codes

Code	Reason
200	Updated the search tab.
201	Updated the search tab.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/models/searchTabs/tab123" -H
"accept: application/json" -H "Content-Type: application/json" -d "{ \"fieldFilters\":
[ { \"facetId\": \"string\", \"value\": \"string\" } ], \"global\": false, \"groups\":
[ \"string\" ], \"isDefault\": false, \"name\": \"string\", \"order\": 0, \"owner\":
\"string\", \"queryFilters\": [ { \"facetId\": \"string\" } ], \"rootTo\": \"NONE\",
\"users\": [ \"string\" ]}"
```

Delete a Search Tab Definition

Use the Delete a Search Tab Definition API to delete a search tab definition.

The API supports the DELETE method.

DELETE request

To delete a search tab definition, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/models/searchTabs/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of search tab.	Path	String

Response Codes

Code	Reason
200	Deleted a search tab definition.
204	No content.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/models/searchTabs/tab123" -
H "accept: application/json"
```

Update the Search Tab Order

Use the Update the Search Tab Order API to change the order of the search tabs.

The API supports the PUT method.

PUT request

To change the order of the search tabs, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/models/searchTabs/order
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
tabOrder	Required. Enter the search tab order attributes.	Path	String
if-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type
order	Required. Specifies the order to display the tab.	Integer
tabId	Required. The ID of the search tab.	String

Response Codes

Code	Reason
200	Updated the search tab order.
201	Custom reference attribute updated.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting update detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/models/searchTabs/order" -H
"accept: application/json" -H "Content-Type: application/json" -d "{ \"items\":
[ { \"order\": 0, \"tabId\": \"string\" } ]}"
```

CHAPTER 7

Monitoring Info REST APIs

This chapter includes the following topics:

- Monitoring Information REST APIs Overview, 119
- Monitoring Information REST APIs, 119

Monitoring Information REST APIs Overview

You can use the Monitoring Information REST APIs to list and submit jobs. The jobs include backup jobs, object export jobs, object import jobs, resource export jobs, resource scan log jobs, search export jobs, and service log jobs. You can also use the Monitoring Information REST APIs to download the logs and view job status.

Monitoring Information REST APIs

You can use the following Monitoring Information REST APIs to download logs, view job status, list jobs, and submit jobs:

Monitoring Info REST API	Description
GET jobs	Lists the jobs and their job details
GET jobs/{id}	Lists the job details for a job
GET jobs/{id}/logs	Lists the logs for a job
GET jobs/{id}/logs/zip	Downloads the logs generated for a job to a ZIP file
GET jobs/{id}/status	View the job status
PUT jobs/{id}/status	Updates the job status of a job
GET jobs/backup	Lists the job details for the job that backs up the catalog
POST jobs/backup	Submits the job to back up the catalog

Monitoring Info REST API	Description
GET jobs/backup/{id}	Lists the backup job configuration
GET backup/{id}/result	Downloads the ZIP file for the backup job
GET jobs/objectExports	Lists the jobs of object export type and their job details
POST jobs/objectExports	Submits the job configuration to export objects
GET jobs/objectExports/{id}	Lists the job configuration for an object export job
GET jobs/objectExports/{id}/result	Downloads the CSV file that contains the object export jobs and their job details
GET jobs/objectImports	Lists the jobs of object import type and their job details
POST jobs/objectImports	Submits the job configuration to import objects
GET jobs/objectImports/{id}	Lists the job configuration for an object import job
GET jobs/resourceExports	Lists the jobs of resource export type and their job details
POST jobs/resourceExports	Submits the job configuration to export resources
GET jobs/resourceExports/{id}	Lists the resource export jobs and their job details
GET jobs/resourceExports/{id}/result	Downloads the CSV file that contains the resource export jobs and their job details
GET /jobs/resourceScanLogs	Lists the resource scan log jobs and their job details
POST /jobs/resourceScanLogs	Submits a resource scan log job to list the resource scan logs
GET jobs/resourceScanLogs/{id}/result	Downloads the resource scan logs for a job
GET jobs/searchExports	Lists the jobs of search export type and their job details
POST jobs/searchExports	Submits the search export job configuration to export search results
GET jobs/searchExports/{id}	Lists the job details of a search export job
GET jobs/searchExports/{id}/result	Downloads the CSV file that contains the search export jobs and their job details
GET jobs/serviceLogs	Lists the jobs of service log type and their job details
POST jobs/serviceLogs	Submits a service log job to list the service logs
GET jobs/serviceLogs/{id}/result	Downloads the resource scan logs for a job

List the Job Details

Use the List the Job Details API to list the jobs and their job details.

The API supports the GET method.

GET request

To list the jobs and their job details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
jobId	Optional. Enter one or more job IDs to view the job details. If you do not enter a job ID, the API uses the other configured parameters to filter and list the job IDs.	Query	Arrary [String]
jobType	Optional. Enter one or more job types to view the job details.	Query	Arrary [String]
offset	Optional. The offset position from which the API lists the jobs. Default is 0.	Query	Integer
pageSize	Optional. The number of results to display in a page. Default is 20.	Query	Integer
sortBy	Optional. Choose one of the following parameters to sort the jobs: - CREATED_TIME - STARTED_TIME - END_TIME Default is CREATED_TIME.	Query	String
sortOrder	Optional. Choose one of the following parameters to sort the jobs: - DESC - ASC Default is DESC. After the API sorts the job IDs based on sortBy parameter, it sorts the job IDs based on sortOrder parameter.	Query	String
jobStatus	Optional. Choose one of the following parameters to filter the jobs based on job status: - RUNNING - COMPLETED - SUBMITTED - FAILED If you do not choose a job status, the API lists all the jobs.	Query	String

Response Codes

Code	Reason
200	Listed the jobs and job details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.

Code	Reason
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs?
jobId=345245&offset=0&pageSize=20&sortBy=CREATED_TIME&sortOrder=DESC" -H  "accept:
application/json"
```

List the Details for a Job

Use the List the Details for a Job API to list the details of a job.

The API supports the GET method.

GET request

to list the details of a job, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job	Path	String

Response Codes

Code	Reason
200	Listed the job details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/54345" -H  "accept:
application/json"
```

List the Logs for a Job

Use the List the Logs for a Job API to list the logs for a job.

The API supports the GET method.

GET request

To list the logs for a job, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/{id}/logs
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String

Response Codes

Code	Reason
200	Listed the logs for the job.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/4523/logs" -H  "accept: application/json"
```

Download the Logs Generated for a Job to a ZIP file

Use the Download the Logs to a ZIP file API to download the logs generated for a job to a ZIP file. You can view and download the zip file from the Downloads folder on your machine.

The API supports the GET method.

GET request

To download the logs generated for a job to a ZIP file, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/{id}/logs/zip
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String

Response Codes

Code	Reason
200	Download complete.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/765456/logs/zip" -H
"accept: application/zip"
```

View a Job Status

Use the View a Job Status API to display the job status.

The API supports the GET method.

GET request

To display the job status, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/{id}/status
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String

Response Codes

Code	Reason
200	Returns the job status as running, completed, failed, or submitted.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/69584/status" -H
"accept: application/json"
```

Update the Job Status

Use the Update the Job Status API to update the status of a job.

The API supports the PUT method.

PUT request

To update the status of a job, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/jobs/{id}/status
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String
status	Required. Enter the status to assign to the job. For example, enter RUNNING as the job status.	Body	-

Response Codes

Code	Reason
200	Updated the job status.
201	Created.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/654/status" -H  "accept:
application/json" -H  "Content-Type: application/json" -d "\"Completed\""
```

List the Job Details about the Backup Job

Use the List the Job Details about the Backup Job API to list the backup job details.

The API supports the GET method.

GET request

To list the backup job details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/backup
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
jobId	Optional. Enter one or more job IDs to view the job details. If you do not enter a job ID, the API uses the other configured parameters to filter and list the job IDs.	Query	Arrary [String]
offset	Optional. The offset position from which the API lists the jobs. Default is 0.	Query	Integer
pageSize	Optional. The number of results to display in a page. Default is 20.	Query	Integer
sortBy	Optional. Choose one of the following parameters to sort the jobs: - CREATED_TIME - STARTED_TIME - END_TIME Default is CREATED_TIME.	Query	String
sortOrder	Optional. Choose one of the following parameters to sort the jobs: - DESC - ASC Default is DESC. After the API sorts the job IDs based on sortBy parameter, it sorts the job IDs based on sortOrder parameter.	Query	String
jobStatus	Optional. Choose one of the following parameters to filter the jobs based on job status: - RUNNING - COMPLETED - SUBMITTED - FAILED If you do not choose a job status, the API lists all the jobs.	Query	String

Response Codes

Code	Reason
200	Listed the logs for the job.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.

Code	Reason
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/backup?
offset=0&pageSize=20&sortBy=CREATED_TIME&sortOrder=DESC" -H  "accept: application/json"
```

Submit the Backup Job

Use the Submit the Backup Job API to submit the backup job to back up the catalog.

The API supports the POST method.

POST request

To submit the backup job to back up the catalog, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/jobs/backup
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
config	Required. Enter the required attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type
fileLocation	Optional. Delete the term 'string' and then enter the path of backup ZIP file located on your machine or leave it blank. Do not enter the file name. If the file location is blank, the Catalog service uses the backup file in the following location: `$<INFA_HOME>/logs/<NodeName>/services/CatalogService/<CatalogServiceName>/JobsStore/` **Note:** When you submit the job, an error appears if you do not have read and write access to the file.	String
maxCores	Optional. The maximum number of resources that can be used in an export job. Default is 15.	Integer

Parameter	Description	Data Type
maxParallelism	Optional. The maximum number of table backups to run in parallel. Default is 0.	Integer
maxRetries	Optional. The maximum number of retries to check for the availability of resources. Default is 5.	Integer
stores	Optional. Provide the required data store that you want to back up or a comma-separated list of data stores that you want to back up. Based on the issues you want to troubleshoot, you can back up the required data stores instead of taking a complete backup of the catalog. You can use the following options to back up the required data stores in the catalog: - ALL - STAGING - GRAPH - SEARCH **Note:** - The data store values are case sensitive. - You must back up the STAGING and GRAPH data stores if you want to view data after you restore data from the backup.	String

Response Codes

Code	Reason
200	Submitted the job configuration.
201	Created.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/backup" -H  "accept:
application/json" -H  "Content-Type: application/json" -d "{  \"fileLocation\": \"string
\",  \"maxCores\": 0,  \"maxParallelism\": 0,  \"maxRetries\": 0" \"stores\": \"STAGING
\",\"GRAPH\"}
```

List the Job Details for a Backup Job

Use the List the Job Details for a Backup Job API to list the backup job configuration.

The API supports the GET method.

GET request

To list the backup job configuration, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/backup/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the backup job.	Path	String

Response Codes

Code	Reason
200	Listed the job details for the backup job.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/backup/3425" -H
"accept: application/json"
```

Download the ZIP file of the Backup Job

Use the Download the ZIP file of the Backup Job API to download the ZIP file for the backup job.

The API supports the GET method.

GET request

To download the ZIP file for the backup job, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/backup/{id}/result
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String

Response Codes

Code	Reason
200	Download complete.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/backup/3434/result" -H
"accept: application/zip"
```

List the Job Details for Object Export Jobs

Use the List the Job Details for Object Export Jobs API to list the jobs of object export type and their job details.

The API supports the GET method.

GET request

To list the jobs of object export type and their job details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/objectExports
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
jobId	Optional. Enter one or more job IDs to view the job details. If you do not enter a job ID, the API uses the other configured parameters to filter and list the job IDs.	Query	Arrary [String]
offset	Optional. The offset position from which the API lists the jobs. Default is 0.	Query	Integer
pageSize	Optional. The number of results to display in a page. Default is 20.	Query	Integer

Parameter	Description	Parameter Type	Data Type
sortBy	Optional. Choose one of the following parameters to sort the jobs: - CREATED_TIME - STARTED_TIME - END_TIME Default is CREATED_TIME.	Query	String
sortOrder	Optional. Choose one of the following parameters to sort the jobs: - DESC - ASC Default is DESC. After the API sorts the job IDs based on sortBy parameter, it sorts the job IDs based on sortOrder parameter.	Query	String
jobStatus	Optional. Choose one of the following parameters to filter the jobs based on job status: - RUNNING - COMPLETED - SUBMITTED - FAILED If you do not choose a job status, the API lists all the jobs.	Query	String

Response Codes

Code	Reason
200	Listed the object export jobs and job details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/objectExports?
jobId=694874&offset=0&pageSize=20&sortBy=CREATED_TIME&sortOrder=DESC" -H  "accept:
application/json"
```

Submit the Job Configuration to Export Objects

Use the Submit the Job Configuration to Export Objects API to submit the job configuration to the catalog for object export task.

The API supports the POST method.

POST request

To submit the job configuration to the catalog for object export task, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/jobs/objectExports
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
config	Required. Enter the required attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type	Values
attributeIds	Required. List comma-separated attributes to export.	String	Enter the IDs, separated by commas.
excludeChildren	Optional. Excludes the children of the objects from object export. Default is true.	Boolean	Provide one of the following values: - true - false
includeReferenceObjects	Optional. Includes the reference objects in object export. Default is true.	Boolean	Provide one of the following values: - true - false
objectId	Required. The ID of the object.	String	-

Response Codes

Code	Reason
200	Bulk object export response.
201	Created
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/objectExports" -H
"accept: application/json" -H  "Content-Type: application/json" -d "{  \"attributeIds\":
```

```
[    \"com.infa.at1\"  ],  \"excludeChildren\": true,  \"includeReferenceObjects\":
true,  \"objectId\": \"3421\"}"
```

List the Job Configuration for an Object Export Job

Use the List the Job Configuration for an Object Export Job API to list the job configuration for an object export job.

The API supports the GET method.

GET request

To list the job configuration for an object export job, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/objectExports/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String

Response Codes

Code	Reason
200	Listed the job configuration.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/objectExports/567356456"
-H  "accept: application/json"
```

Download the File with Object Export Jobs

Use the Download the File with Object Export Jobs API to download the CSV file that has the job details about object export jobs.

The API supports the GET method.

GET request

To download the CSV file that has the job details about object export jobs, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/objectExports/{id}/result
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the object export job.	Path	String

Response Codes

Code	Reason
200	Download complete.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/objectExports/985634/
result" -H  "accept: application/excel"
```

List the Job Details for Object Import Jobs

Use the List the Job Details for Object Import Jobs API to list the jobs of object import type and their job details.

The API supports the GET method.

GET request

To list the jobs of object import type and their job details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/objectImports
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
jobId	Optional. Enter one or more job IDs to view the job details. If you do not enter a job ID, the API uses the other configured parameters to filter and list the job IDs.	Query	Arrary [String]
offset	Optional. The offset position from which the API lists the jobs. Default is 0.	Query	Integer
pageSize	Optional. The number of results to display in a page. Default is 20.	Query	Integer

Parameter	Description	Parameter Type	Data Type
sortBy	Optional. Choose one of the following parameters to sort the jobs: - CREATED_TIME - STARTED_TIME - END_TIME Default is CREATED_TIME.	Query	String
sortOrder	Optional. Choose one of the following parameters to sort the jobs: - DESC - ASC Default is DESC. After the API sorts the job IDs based on sortBy parameter, it sorts the job IDs based on sortOrder parameter.	Query	String
jobStatus	Optional. Choose one of the following parameters to filter the jobs based on job status: - RUNNING - COMPLETED - SUBMITTED - FAILED If you do not choose a job status, the API lists all the jobs.	Query	String

Response Codes

Code	Reason
200	Listed the object import jobs and job details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/objectImports?
jobId=&offset=0&pageSize=20&sortBy=CREATED_TIME&sortOrder=DESC" -H  "accept: application/
json"
```

Submit the Job Configuration to Import Objects

Use the Submit the Job Configuration to Import Objects API to submit the job configuration to the catalog for object import task.

The API supports the POST method.

POST request

To submit the job configuration to the catalog for object import task, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/jobs/objectImports
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
file	Optional. Choose the file to import objects.	formData	file
packages	Optional. Comma-separated list of packages to import.	formData	-
emailId	Optional. Email address of the user.	formData	-

Response Codes

Code	Reason
200	Bulk object import response.
201	Created
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/objectImports" -H
"accept: application/json" -H  "Content-Type: multipart/form-data" -F "packages=pa32"
```

List the Job Configuration for an Import Job

Use the List the Job Configuration for an Import Job API to list the job configuration for an object import job.

The API supports the GET method.

GET request

To list the job configuration for an object import job, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/objectImports/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job	Path	String

Response Codes

Code	Reason
200	Bulk object import configuration
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/objectImports/95867" -H
"accept: application/json"
```

List the Job Details for Resource Export Jobs

Use the List the Job Details for Resource Export Jobs API to list the jobs of resource export type and their job details.

The API supports the GET method.

GET request

To list the jobs of resource export type and their job details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/resourceExports
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
jobId	Optional. Enter one or more job IDs to view the job details. If you do not enter a job ID, the API uses the other configured parameters to list the job IDs.	Query	Arrary [String]
offset	Optional. The offset position from which the API lists the jobs. Default is 0.	Query	Integer
pageSize	Optional. The number of results to display in a page. Default is 20.	Query	Integer

Parameter	Description	Parameter Type	Data Type
sortBy	Optional. Choose one of the following parameters to sort the jobs: - CREATED_TIME - STARTED_TIME - END_TIME Default is CREATED_TIME.	Query	String
sortOrder	Optional. Choose one of the following parameters to sort the jobs: - DESC - ASC Default is DESC. After the API sorts the job IDs based on sortBy parameter, it sorts the job IDs based on sortOrder parameter.	Query	String
jobStatus	Optional. Choose one of the following parameters to filter the jobs based on job status: - RUNNING - COMPLETED - SUBMITTED - FAILED If you do not choose a job status, the API lists all the jobs.	Query	String

Response Codes

Code	Reason
200	Listed the object resource jobs and their job details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/resourceExports?
offset=0&pageSize=20&sortBy=CREATED_TIME&sortOrder=DESC" -H  "accept: application/json"
```

Submit the Job Configuration to Export Resources

Use the Submit the Job Configuration to Export Resources API to submit the job configuration to the catalog for resource export task.

The API supports the POST method.

POST request

To submit the job configuration to the catalog for resource export task, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/jobs/resourceExports
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
config	Required. Enter the required attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type	Values
attributeIds	Required. List comma-separated attributes to be exported.	String	Enter the IDs, separated by commas.
classType	Required. List comma-separated class types to be exported.	String	Enter the IDs, separated by commas.
includeReferenceObjects	Optional. Includes the reference objects in object export. Default is true.	Boolean	Provide one of the following values: - true - false
resourceName	Required. The ID of the resource.	String	-

Response Codes

Code	Reason
200	Bulk resource export response.
201	Created
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/objectExports" -H
"accept: application/json" -H  "Content-Type: application/json" -d "{  \"attributeIds\":
[    \"com.infa.at1\"  ],  \"excludeChildren\": true,  \"includeReferenceObjects\":
true,  \"objectId\": \"3421\"}"
```

List the Job Details for a Resource Export Job

Use the List the Job Details for a Resource Export Job API to list the jobs of resource export type and their details.

The API supports the GET method.

GET request

To list the jobs of resource export type and their details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/resourceExports/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String

Response Codes

Code	Reason
200	Listed the resource export job and job details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/resourceExports/45367" -
H  "accept: application/json"
```

Download the File with Resource Export Jobs

Use the Download the File with Resource Export Jobs API to download the CSV file that has the job details about resource export jobs.

The API supports the GET method.

GET request

To download the CSV file that has the job details about resource export jobs, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/resourceExports/{id}/result
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the resource export job.	Path	String

Response Codes

Code	Reason
200	Download complete.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/resourceExports/45342/
result" -H  "accept: application/excel"
```

List the Job Details for a Resource Scan Log Job

Use the List the Job Details for a Resource Scan Log Job API to list the resource scan log jobs and their job details.

The API supports the GET method.

GET request

To list the resource scan log jobs and their job details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/resourceScanLogs
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
jobId	Optional. Enter one or more job IDs to view the job details. If you do not enter a job ID, the API uses the other configured parameters to filter and list the job IDs.	Query	Arrary [String]
offset	Optional. The offset position from which the API lists the jobs. Default is 0.	Query	Integer
pageSize	Optional. The number of results to display in a page. Default is 20.	Query	Integer

Parameter	Description	Parameter Type	Data Type
sortBy	Optional. Choose one of the following parameters to sort the jobs: - CREATED_TIME - STARTED_TIME - END_TIME Default is CREATED_TIME.	Query	String
sortOrder	Optional. Choose one of the following parameters to sort the jobs: - DESC - ASC Default is DESC. After the API sorts the job IDs based on sortBy parameter, it sorts the job IDs based on sortOrder parameter.	Query	String
jobStatus	Optional. Choose one of the following parameters to filter the jobs based on job status: - RUNNING - COMPLETED - SUBMITTED - FAILED If you do not choose a job status, the API lists all the jobs.	Query	String

Response Codes

Code	Reason
200	Listed the jobs and job details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs?
jobId=345245&offset=0&pageSize=20&sortBy=CREATED_TIME&sortOrder=DESC" -H  "accept:
application/json"
```

Submit a Resource Scan Log Job

Use the Submit a Resource Scan Log Job API to submit a resource scan log job to list the resource scan logs.

The API supports the POST method.

POST request

To submit a resource scan log job to list the resource scan logs, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/jobs/resourceScanLogs
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
config	Required. Enter the required attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type
appDate	Optional. Enter the date in YYYY-MM-DD hh:mm:ss, YYYY-MM-DD hh:mm, or YYYY-MM-DD format. Returns the resource scan logs from appDate to the current date.	String
includeProfilingLogs*	Optional. Enter **true** to collect Data Integration logs for profiling for the resources.	Boolean
includeScannerLogs*	Optional. Enter **true** to collect resource YARN logs.	Boolean
resourceName	Required. List of resource names. Returns the scan logs for the listed resources.	Array [String]

*If you configure the `LdmCustomOptions.ldm.exclusive.mode` custom property to true for the Catalog Service, the service collects only the resource YARN logs. If you configure the property to false, the service collects resource YARN logs and Data Integration logs for profiling. Recycle the Catalog Service after you change the custom property.

To configure this property, navigate to the **Informatica Administrator** > **Manage** > **Services and Nodes** > **Catalog Service** > **Custom Properties** section.

Response Codes

Code	Reason
200	Updated the job configuration.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Cannot find the object.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/resourceScanLogs" -H
"accept: application/json" -H  "Content-Type: application/json" -d "{  \"appDate\":
\"2020-05-05\",  \"resourceName\": [    \"Oracle\"  ]}"
```

Download the Resource Scan Logs for a Job

Use the Download the Resource Scan Logs API to download the resource scan logs for a job.

The API supports the GET method.

GET request

To download the resource scan logs for a job, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/resourceScanLogs/{id}/result
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String

Response Codes

Code	Reason
200	Download complete.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/resourceScanLogs/4534/
result" -H  "accept: application/zip"
```

List the Job Details for Search Export Jobs

Use the List the Job Details for Search Export Jobs API to list the jobs of search export type and their details.

The API supports the GET method.

GET request

To list the jobs of search export type and their details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/searchExports
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
jobId	Optional. Enter one or more job IDs to view the job details. If you do not enter a job ID, the API uses the other configured parameters to filter and list the job IDs.	Query	Arrary [String]
offset	Optional. The offset position from which the API lists the jobs. Default is 0.	Query	Integer
pageSize	Optional. The number of results to display in a page. Default is 20.	Query	Integer
sortBy	Optional. Choose one of the following parameters to sort the jobs: - CREATED_TIME - STARTED_TIME - END_TIME Default is CREATED_TIME.	Query	String
sortOrder	Optional. Choose one of the following parameters to sort the jobs: - DESC - ASC Default is DESC. After the API sorts the job IDs based on sortBy parameter, it sorts the job IDs based on sortOrder parameter.	Query	String
jobStatus	Optional. Choose one of the following parameters to filter the jobs based on job status: - RUNNING - COMPLETED - SUBMITTED - FAILED If you do not choose a job status, the API lists all the jobs.	Query	String

Response Codes

Code	Reason
200	Listed the search export jobs and job details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/searchExports?
offset=0&pageSize=20&sortBy=CREATED_TIME&sortOrder=DESC" -H  "accept: application/json"
```

Submit the Job Configuration to Export Search Results

Use the Submit the Job Configuration to Export Search Results API to submit the job configuration to the catalog for search results export task.

The API supports the POST method.

POST request

To submit the job configuration to the catalog for search results export task, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/jobs/searchExports
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
config	Required. Enter the required attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type	Values
attributeIds	Required. List comma-separated attributes to be exported.	String	Enter the IDs, separated by commas.
basicQuery	Optional. A query string. Uses blockjoin faceting to interpret the query. See Apache Lucene for more information.	String	-
fq	Optional. Filter queries to apply on the **q** parameter. Useful to apply facets.	Array [String]	-
q	Optional. Use to create a query that searches matching objects. Uses Apache Lucene to interpret the query.	String	-
qf	Optional. Specifies the fields in the index to use in query. Enter index attributes that have **index="true"** in the view model.	String	-
relatedId	Optional. Specifies the object ID for which the related assets appear.	String	-

Parameter	Description	Data Type	Values
rootTo	Optional. Join results to resource or data set. Choose one of the following parameters: - RESOURCE - DATA_SET	String	-
tabId	Optional. The tab ID to apply the filters.	String	-

Response Codes

Code	Reason
200	Bulk search export response.
201	Created
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/searchExports" -H
"accept: application/json" -H  "Content-Type: application/json" -d "{  \"attributeIds\":
[    \"string\"  ],  \"basicQuery\": \"string\",  \"fq\": [    \"string\"  ],  \"q\":
\"string\",  \"qf\": [    \"string\"  ],  \"relatedId\": [    \"string\"  ],  \"rootTo
\": \"RESOURCE\",  \"tabId\":
```

List the Job Details for a Search Export Job

Use the List the Job Details for a Search Export Job API to list the job details about a search export job.

The API supports the GET method.

GET request

To list the job details about a search export job, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/searchExports/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the search export job.	Path	String

Response Codes

Code	Reason
200	Listed the job configuration.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/searchExports/87403" -H
"accept: application/json"
```

Download the Results File for a Search Export Job

Use the Download the Results File for a Search Export Job API to download the CSV file that has the job details for a search export job.

The API supports the GET method.

GET request

To download the CSV file that has the job details for a search export job, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/searchExports/{id}/result
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String

Response Codes

Code	Reason
200	Download complete
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.

Code	Reason
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/searchExports/45643/
result" -H  "accept: application/excel"
```

List the Job Details for Service Log Jobs

Use the List the Job Details for Service Log Jobs API to list the jobs of service log type and their job details.

The API supports the GET method.

GET request

To list the jobs of service log type and their job details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/serviceLogs
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
jobId	Optional. Enter one or more job IDs to view the job details. If you do not enter a job ID, the API uses the other configured parameters to filter and list the job IDs.	Query	Arrary [String]
offset	Optional. The offset position from which the API lists the jobs. Default is 0.	Query	Integer
pageSize	Optional. The number of results to display in a page. Default is 20.	Query	Integer
sortBy	Optional. Choose one of the following parameters to sort the jobs: - CREATED_TIME - STARTED_TIME - END_TIME Default is CREATED_TIME.	Query	String

Parameter	Description	Parameter Type	Data Type
sortOrder	Optional. Choose one of the following parameters to sort the jobs: - DESC - ASC Default is DESC. After the API sorts the job IDs based on sortBy parameter, it sorts the job IDs based on sortOrder parameter.	Query	String
jobStatus	Optional. Choose one of the following parameters to filter the jobs based on job status: - RUNNING - COMPLETED - SUBMITTED - FAILED If you do not choose a job status, the API lists all the jobs.	Query	String

Response Codes

Code	Reason
200	Listed the jobs and job details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/objectExports?
jobId=694874&offset=0&pageSize=20&sortBy=CREATED_TIME&sortOrder=DESC" -H  "accept:
application/json"
```

Submit a Service Log Job

Use the Submit a Service Log Job API to submit a service log job to get the service logs.

The API supports the POST method.

POST request

To submit a service log job to get the service logs, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/jobs/serviceLogs
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
config	Optional. Enter the required attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type	Values
endDate	Optional. Enter the end date till which to list the service logs in the YYYY-MM-DD hh:mm:ss, YYYY-MM-DD hh:mm, or YYYY-MM-DD format.	String	-
serviceTypes	Optional. Enter comma-separated list of deployed services.	Arrary [String]	Enter one or more of the following services: - HBASE - SOLR - INGESTION - SERVICE
startDate	Optional. Enter the start date from which to list the service logs in the YYYY-MM-DD hh:mm:ss, YYYY-MM-DD hh:mm, or YYYY-MM-DD format.	String	-

Response Codes

Code	Reason
200	Submitted the job.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/serviceLogs" -H
"accept: application/json" -H  "Content-Type: application/json" -d "{  \"endDate\":
\"YYYY-MM-DD hh:mm:ss\",  \"serviceTypes\": [    \"HBASE\"  ],  \"startDate\": \"YYYY-MM-
DD hh:mm:ss\"}"
```

Download the Service Logs for a Job

Use the Download the Service Logs for a Job API to download the service logs for a job.

The API supports the GET method.

GET request

To download the service logs for a job, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/serviceLogs/{id}/result
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String

Response Codes

Code	Reason
200	Download complete.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/serviceLogs/23432/
result" -H  "accept: application/zip"
```

Submit the Job Configuration to Export Data Domains

Use the Submit the Job Configuration to Export Data Domains API to submit the job configuration to the Catalog for data domain export task. The task exports the assets for which a data domain is accepted, inferred, or rejected to a CSV file.

The API supports the POST method.

POST request

To submit the job configuration to the catalog for data domain export task, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/jobs/DataDomainExports
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
config	Required. Enter the required attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type	Values
association	Required. The asset association type for the data domains to be included in the exported CSV file.	Array [String]	Provide one of the following values: - ACCEPTED - INFERRED - REJECTED
objectId	Required. The ID of the object.	String	-

Response Codes

Code	Reason
200	Data domain export response.
201	Created
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/DataDomainExports" -H
"accept: application/json" -H "Content-Type: application/json" -d "{ \"association\":
[ \"ACCEPTED\" ], \"objectId\": \"3421\"}"
```

Download the Data Domain Export Logs for a Job

Use the Download the Data Domain Export Logs API to download the data domain export logs for a job.

The API supports the GET method.

GET request

To download the data domain export logs for a job, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/DataDomainExports/{id}/result
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String

Response Codes

Code	Reason
200	Download complete.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/DataDomainExports/4534/
result" -H "accept: application/excel"
```

Submit the Job Configuration to Export Axon Assets

Use the Submit the Job Configuration to Export Axon Assets API to submit the job configuration to the catalog for Axon assets export task.

The API supports the POST method.

POST request

To submit the job configuration to the catalog for data domain export task, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/jobs/AxonExports
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
config	Required. Enter the required attributes.	Body	-

Attribute Parameters

Parameter	Description	Data Type	Values
association	Required. The asset association type for the Axon glossary, system, dataset, or attributes to be included in the exported CSV file. Choose to export related glossaries, classified assets, related technical assets, or related business logic assets.	Array [String]	Provide one of the following values: - RELATED_GLOSSARY - CLASSIFIED - RELATED_TECHNICAL - RELATED_LOGICAL
objectId	Required. The ID of the object.	String	-

Response Codes

Code	Reason
200	Axon assets export response.
201	Created
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/AxonExports" -H
"accept: application/json" -H "Content-Type: application/json" -d "{ \"association\":
[ \"RELATED_GLOSSARY\" ], \"objectId\": \"3421\"}"
```

Download the Axon Asset Export Logs for a Job

Use the Download the Axon Asset Export Logs API to download the resource scan logs for a job.

The API supports the GET method.

GET request

To download the Axon asset export logs for a job, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/AxonExports/{id}/result
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String

Response Codes

Code	Reason
200	Download complete.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/AxonExports/4534/result"
-H "accept: application/excel"
```

Download the Results File for Relationship Export Job

Use the Download the Results File for Relationship Export Job API to download the CSV file that has the job details for a relationship export job.

The API supports the GET method.

GET request

To download the CSV file that has the job details for a relationship export job, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/jobs/RelationshipExports/{id}/result
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the job.	Path	String

Response Codes

Code	Reason
200	Download complete.
400	Missing or invalid parameter.

Code	Reason
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/RelationshipExports/ID/
result" -H "accept: application/excel"
```

Submit the Job Configuration to Export Relationships

Use the Submit the Job Configuration to Export Relationships API to submit the job configuration to the catalog to export relationships from the Relationships view.

The API supports the POST method.

POST request

To submit the job configuration to the catalog for a relationship export task, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/jobs/RelationshipExports
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type
config	Required. Enter the required attributes.	Body

Attribute Parameters

Parameter	Description	Data Type
association	Required. The asset association type for the resources to be included in the exported CSV file. Choose to export related assets, such as business terms, users, tables, synonyms, views, and data domains.	Array [String]
objectId	Required. The ID of the object.	String

Response Codes

Code	Reason
200	Relationship export response.
201	Created.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/jobs/RelationshipExports" -H
"accept: application/json" -H "Content-Type: application/json" -d "{ \"association\":
[ \"PRIMARY_KEYS\" ], \"isCompositeDataDomain\": true, \"objectId\": \"string\",
\"resourcesNames\": [ \"string\" ]}"
```

CHAPTER 8

Object APIs

This chapter includes the following topics:

- Object REST APIs Overview, 159
- Object Certification APIs, 160
- Object Comments APIs, 162
- Object Information APIs, 177
- Object Modification APIs, 190
- Object Reviews APIs, 193
- Object Child Count REST API, 200

Object REST APIs Overview

To access, view, and update the data objects in Enterprise Data Catalog, you can use the following REST APIs:

- Object Information APIs. List the objects, view the details of the objects, and view the relationships between the objects in the catalog.
- Object Modification APIs. Update the custom properties for one or multiple objects in the catalog.
- Object Certification APIs. List, update, and delete the certification properties for an object.
- Object Comments APIs. List, create, update, and delete comments, replies, and votes for a data object.
- Object Reviews APIs. List, create, update, and delete reviews, ratings, and votes for a review.

Object Certification APIs

You can use the following Object Certification REST APIs for the objects in the catalog:

Model Information REST API	Description
GET data/objects/{id}/certificate	Lists the certification properties for an object ID.
PUT data/objects/{id}/certificate	Updates the certification properties for an object ID
DELETE data/objects/{id}/certificate	Deletes the certification properties for an object ID

List the Certification Properties for an Object

Use the List the Certification Properties for an Object API to list the certification properties for the specified object.

The API supports the GET method.

GET request

To list the certification properties for the specified object, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/certificate
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String

Response Codes

Code	Reason
200	Listed the certification properties for the specified object.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/1001/
certificate" -H  "accept: application/json"
```

Create or Update Certification Properties for an Object

Use the Create or Update Certification Properties for an Object API to create or update the certification properties for the specified object.

The API supports the PUT method.

PUT request

To create or update the certification properties for the specified object, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/data/objects/{id}/certificate
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
object	Required. Enter certification text and list of tags for the certified object.	Body	-
If-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Response Codes

Code	Reason
200	Updated the certification properties for the specified object.
201	Created the certification properties for the specified object.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/1001/
certificate" -H  "accept: application/json" -H  "Content-Type: application/json" -d
"{  \"certifyText\": \"Add certificate\",  \"tags\": [    \"Update text\"  ]}"
```

Delete Certification Properties for an Object

Use the Delete Certification Properties for an Object API to delete the certification properties for the specified object.

The API supports the DELETE method.

DELETE request

To delete the certification properties for the specified object, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/data/objects/{id}/certificate
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String

Response Codes

Code	Reason
200	Deleted the certification properties for the specified object.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/1001/
certificate" -H  "accept: application/json"
```

Object Comments APIs

You can use the following Object Comments REST APIs for the objects in the catalog:

Model Information REST API	Description
GET data/objects/{id}/comments	Lists all the comments
POST data/objects/{id}/comments	Creates a top-level comment for an object
GET data/objects/{id}/comments/{commentId}	Lists a specific comment for an object

Model Information REST API	Description
PUT data/objects/{id}/comments/{commentId}	Updates a specific comment for an object
DELETE data/objects/{id}/comments/{commentId}	Deletes a specific comment for an object
GET data/objects/{id}/comments/{commentId}/replies	Lists all the replies to a comment
POST data/objects/{id}/comments/{commentId}/replies	Creates a reply for a comment
GET data/objects/{id}/comments/{commentId}/replies/{replyId}	Lists the reply for a specific comment
PUT data/objects/{id}/comments/{commentId}/replies/{replyId}	Updates a reply for a specific comment
DELETE data/objects/{id}/comments/{commentId}/replies/{replyId}	Deletes a reply for a specific comment
GET data/objects/{id}/comments/{commentId}/reply/{replyId}/vote	Lists the aggregated votes for a reply
POST data/objects/{id}/comments/{commentId}/reply/{replyId}/vote	Updates the vote for a specific reply
DELETE data/objects/{id}/comments/{commentId}/reply/{replyId}/vote	Deletes the vote for a specific reply
GET data/objects/{id}/comments/{commentId}/vote	Lists the aggregated votes for a comment
POST data/objects/{id}/comments/{commentId}/vote	Updates the vote for a specific comment
DELETE data/objects/{id}/comments/{commentId}/vote	Deletes the vote for a specific comment

List the Comments for an Object

Use the List the Comments for an Object API to list the comments for an object.

The API supports the GET method.

GET request

To list the comments for an object, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/comments
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
filter	Optional. Choose one of the following filters: - MY_QUESTIONS - UNANSWERED_QUESTIONS - ANSWERED_QUESTIONS - EXCLUDING_MY_QUESTIONS	Query	String
sortOn	Optional. Choose TIMESTAMP to sort based on timestamp.	Query	String
replyLimit	Optional. Limits the number of replies to a comment.	Query	Integer

Parameter	Description	Parameter Type	Data Type
offset	Optional. The offset position from which the API lists the comments. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be display in a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Requested comment sent through API response.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/1001/comments?
filter=MY_QUESTIONS&sortOn=TIMESTAMP&replyLimit=4&offset=0&pageSize=20" -H  "accept:
application/json"
```

Create Comment

Use the Create Comment API to create a new top-level comment for the specified object.

The API supports the POST method.

POST request

To create a new top-level comment for the specified object, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/data/objects/{id}/comments
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
object	Required. Enter the following parameters as necessary: - text. Enter the comments for the object. - type. Enter QUESTION, ANSWER, or OTHERS as the comment type.	Body	-

Response Codes

Code	Reason
201	Created a comment for the specified object.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/1002/comments" -
H  "accept: application/json" -H  "Content-Type: application/json" -d "{  \"text\":
\"Comment5\",  \"type\": \"Query regarding object.\"}"
```

List a Specific Comment for an Object

Use the List a Specific Comment for an Object API to list a specific comment for a data object.

The API supports the GET method.

GET request

To list a specific comment for a data object, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of the comment.	Path	String

Response Codes

Code	Reason
200	Requested comment sent through API response.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.

Code	Reason
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/1003/
comments/54" -H  "accept: application/json"
```

Update Existing Comments for an Object

Use the Update Existing Comments for an Object API to update an existing comment.

The API supports the PUT method.

PUT request

To update an existing comment, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of a data object.	Path	String
commentId	Required. The ID of a comment.	Path	String
object	Required. Enter the following parameters as necessary: - text. Enter the comments for the object. - type. Enter QUESTION, ANSWER, or OTHERS as the comment type.	Body	-
If-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Response Codes

Code	Reason
200	Updated the comment.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.

Code	Reason
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/1002/comments/
192" -H  "accept: application/json" -H  "Content-Type: application/json" -d "{  \"text
\": \"new object\",  \"type\": \"Have a query regarding this.\"}"
```

Delete Replies

Use the Delete Replies API to delete the replies for the specified comment.

The API supports the DELETE method.

DELETE request

To delete the replies for the specified comment, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of the comment.	Path	String

Response Codes

Code	Reason
200	Deleted the replies for the specified comment.
204	No content to display.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/1090/
comments/222" -H  "accept: application/json"
```

List All the Replies for an Object

Use the List All the Replies for an Object API to list the replies for a comment.

The API supports the GET method.

GET request

To list the replies for a comment, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}/replies
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of the comment.	Path	String
sortOn	Optional. Choose one of the following parameters to sort the comments: - TIMESTAMP - VOTE_COUNT - CREATED_BY	Query	String
offset	Optional. The offset position from which the API lists the comments. Default is 0.	Query	Integer
pageSize	Optional. The number of results to display in a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Listed all the replies for the specified comment.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/19992/
comments/321/replies?sortOn=TIMESTAMP&offset=0&pageSize=20" -H  "accept: application/
json"
```

Create a Reply for a Comment

Use the Create a Reply for a Comment API to create a reply for the specified comment.

The API supports the POST method.

POST request

To create a reply for the specified comment, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}/replies
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of the comment.	Path	String
object	Required. Enter the reply text.	Body	-

Response Codes

Code	Reason
201	Created a reply for the comment.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/1020/
comments/112/replies" -H  "accept: application/json" -H  "Content-Type: application/
json" -d "{  \"text\": \"Replying to a comment\"}"
```

List a Specific Reply

Use the List a Specific Reply API to return a specific reply.

The API supports the GET method.

GET request

To return a specific reply, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}/replies/
{replyId}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of the comment.	Path	String
replyId	Required. The ID of the reply.	Path	String

Response Codes

Code	Reason
200	Listed the specified reply.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/232/comments/333/
replies/123" -H  "accept: application/json"
```

Update a Specific Reply

Use the Update a Specific Reply API to update a specific reply.

The API supports the PUT method.

PUT request

To update a specific reply, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}/replies/
{replyId}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of a comment.	Path	String
replyId	Required. The ID of a reply.	Path	String

Parameter	Description	Parameter Type	Data Type
object	Required. Enter the reply text.	Body	-
If-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Response Codes

Code	Reason
201	Updated the reply.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/1111/comments/23/
replies/11" -H  "accept: application/json" -H  "Content-Type: application/json" -d
"{  \"text\": \"Response to comment 23\"}"
```

Delete a Reply for a Comment

Use the Delete a Reply for a Comment API to delete a specific reply.

The API supports the DELETE method.

DELETE request

To delete a specific reply, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}/replies/
{replyId}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of the comment.	Path	String
replyId	Required. The ID of the reply.	Path	String

Response Codes

Code	Reason
200	Deleted the specified reply.
204	No content to display.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/333/
comments/21/replies/222" -H  "accept: application/json"
```

List the Aggregated Votes for a Reply

Use the List the Aggregated Votes for a Reply API to list the total number of votes for a specific reply.

The API supports the GET method.

GET request

To list the total number of votes for a specific reply, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}/reply/{replyId}/
vote
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of the comment.	Path	String
replyId	Required. The ID of the reply.	Path	String

Response Codes

Code	Reason
200	Requested reply sent through API response.
400	Missing or invalid parameter.
401	Missing credentials.

Code	Reason
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/333/comments/
2223/reply/432/vote" -H  "accept: application/json"
```

Create a Vote for a Reply to a Comment

Use the Create a Vote for a Reply to a Comment API to create a vote for a specific reply.

The API supports the POST method.

POST request

To create a vote for a specific reply, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}/reply/
{replyId}/vote
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of the comment.	Path	String
replyId	Required. The ID of the reply.	Path	String
object	Required. Enter a brief description for the parameter *voteKind*.	Body	-

Response Codes

Code	Reason
201	Created a vote for the specified reply to a comment.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.

Code	Reason
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/121/
comments/231/reply/221/vote" -H  "accept: application/json" -H  "Content-Type:
application/json" -d "{  \"voteKind\": \"HELPFUL\"}"
```

Delete the Vote for a Reply

Use the Delete the Vote for a Reply API to delete the votes for a specific reply.

The API supports the DELETE method.

DELETE request

To delete the votes for a specific reply, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}/reply/
{replyId}/vote
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of the comment.	Path	String
replyId	Required. The ID of the reply.	Path	String

Response Codes

Code	Reason
200	Deleted the vote for the specified reply.
204	No content to display.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/121/
comments/222/reply/32/vote" -H  "accept: application/json"
```

List the Aggregated Votes for a Comment

Use the List the Aggregated Votes for a Comment API to list the total number of votes for a comment.

The API supports the GET method.

GET request

To list the total number of votes for a comment, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}/vote
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of the comment.	Path	String

Response Codes

Code	Reason
200	Requested comment sent through API response.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/1444/
comments/342/vote" -H  "accept: application/json"
```

Create a Vote for a Comment

Use the Create a Vote for a Comment API to create a vote for the specified comment.

The API supports the POST method.

POST request

To create a vote for the specified comment, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}/vote
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of the comment.	Path	String
object	Required. Enter HELPFUL or NOT_HELPFUL as voteKind.	Body	-

Response Codes

Code	Reason
201	Created a vote for the specified comment.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/2/comments/3/
vote" -H  "accept: application/json" -H  "Content-Type: application/json" -d
"{  \"voteKind\": \"HELPFUL\"}"
```

Delete the Votes for a Comment

Use the Delete the Votes for a Comment API to delete the votes for a specific comment.

The API supports the DELETE method.

DELETE request

To delete the votes for a specific comment, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/catalog/data/objects/{id}/comments/{commentId}/vote
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
commentId	Required. The ID of the comment.	Path	String

Response Codes

Code	Reason
200	Deleted the vote for the comment.
204	No content to display.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/233/
comments/22/vote" -H  "accept: application/json"
```

Object Information APIs

You can use the following Object Information REST APIs for the objects in the catalog:

Model Information REST API	Description
GET data/objects	Lists the objects
GET data/objects/{id}	Lists the object details
GET data/relationships	Lists the relationships between the objects
GET catalog/data/search	Lists the search results
GET catalog/data/suggest	Lists the suggestions

Data Objects

objects

The endpoint object returns the objects in the catalog. An endpoint is an object that has a connection to another object in a different resource.

REST API Element	Input Format
Request URL	<CatalogAdmin>:<port>/access/2/catalog/data/objects
HTTP Method Type	GET

Request Parameters

Parameter	Required or Optional	Description	Parameter Type	Data Type
q	Optional	Use to create a query that searches matching objects. Uses Apache Lucene to interpret the query.	Query	String
fq	Optional	Enter one or more filter queries that you can apply to search query.	Query	Arrary [String]
id	Optional	Enter one or more data object IDs.	Query	Arrary [String]
offset	Optional	The starting point in the results. The results after the offset value is displayed. By default, the offset value is 0.	Query	Integer
pageSize	Optional	The number of results to display in a page. Default is 20 results per page.	Query	Integer

Parameter	Required or Optional	Description	Parameter Type	Data Type
sort	Optional	Enter **core.name_sort asc** to sort the results in ascending order. Enter **core.name_sort desc** to sort the results in descending order.	Query	String
relatedId	Optional	Enter one or more object IDs to display the results of related IDs.	Query	Arrary [String]
cursor	Optional	Enter query for faster paginated results for deep paging. This parameter is an alternative to **offset** parameter.	Query	String
associations	Optional	The list of association types to include in the response. By default, the links of all types are included in the parameter.	Query	Arrary [String]
includeSrcLinks	Optional	Select **true** if you want to include source links.	Query	Boolean
includeDstLinks	Optional	Select **true** if you want to include destination links.	Query	Boolean
shards	Optional	The list of search shards to query. By default all shards are queried.	Query	Arrary [String]
includeRefObjects	Optional	Include reference objects in the object details. Default is false.	Query	Boolean

Response Codes

Code	Reason
200	Returns objects and object details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET --header "Accept: application/json" "http://<CatalogAdmin>:<port>/access/2/
catalog/data/objects?q=*"
```

Data Object IDs

Use the Data Object IDs API to return the details about an object.

The API supports the GET method.

GET request

To return the details about an object, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
includeRefObjects	Optional. Include reference objects in the object details. Default is false.	Query	Boolean

Response Codes

Code	Reason
200	Returns the object and object details.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.

Code	Reason
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET --header "Accept: application/json" "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/3371000366"
```

Note: In Enterprise Data Catalog 10.5.1.0.1 and later versions, the API response does not contain the items parameter.

Understanding the Output

When you pass the API query parameters to a REST client, the client retrieves and displays object details for the data object that you specify.

The following table lists the important parameters in the output:

Parameter	Description
id	The ID of the object resource.
href	The URL of the object.
nativeId	A unique ID for the object.
seeAlsoHref	The URL of the alternative endpoint for the object.
facts	The list of facts that apply to the object.
facts : attributeId	The attribute ID.
facts : value	The fact value.
facts : label	The display name of the fact.
facts : description	The fact description.
facts : providerId	The asserter or provider ID of the fact.
facts : xid	The ID of the exchange document containing the fact.
facts : modifiedBy	The username of the user that modified a fact.
facts : readOnly	Indicates if the fact can be modified.
srcLinks	The upstream object.
srcLinks : id	The ID of the resource object.
srcLinks : association	The association ID.
srcLinks : linkProperties	The property of the link.

Parameter	Description
srcLinks : linkProperties : attributeId	The link property attribute ID.
srcLinks : linkProperties : value	The link property value.
srcLinks : linkProperties : label	The link property label.
srcLinks : providerId	The asserter or provider ID of the link.
srcLinks : xid	The ID of the exchange document containing the link.
srcLinks : modifiedBy	The username of the user that modified the upstream object.
srcLinks : readOnly	Indicates if the upstream object can be modified.
srcLinks : name	The name of the object connected by the link.
srcLinks : classType	The class type of the upstream object.
srcLinks : href	The URL of the object.
dstLinks	The downstream object.
dstLinks : id	The ID of the resource object.
dstLinks : association	The association ID.
dstLinks : linkProperties	The property for the link.
dstLinks : linkProperties : attributeId	The link property attribute ID.
dstLinks : linkProperties : value	The link property value.
dstLinks : linkProperties : label	The link property label.
dstLinks : providerId	The asserter or provider ID of the link.
dstLinks : xid	The ID of the exchange document containing the link.
dstLinks : modifiedBy	The username of the user that modified the downstream object.
dstLinks : readOnly	Indicates if the downstream object can be modified.
dstLinks : name	The name of the object connected by the link.
dstLinks : classType	The class type of the downstream object.
dstLinks : href	The URL of the object.
businessTerms	The associated business terms.
commentHref	The URL to access the comments for the object.

Relationships

The endpoint object returns the relationship between an object and other objects in Enterprise Data Catalog. An endpoint is an object that has a connection to another object in a different resource.

The API supports the GET method.

GET request

To return the relationship between an object and other objects in Enterprise Data Catalog, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/relationships
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
seed	Required. Enter one or more data asset IDs.	Query	Arrary [String]
association	Required. Enter one or more association IDs or association kind IDs. Lineage or association displays where the data for an asset comes from and the assets that impact it. You can enter the association ID or association kind ID.	Query	Arrary [String]
depth	Required. The depth of traversal which is the number of return links in the lineage. Enter one of the following Enter 0 or N as the depth of traversal, where N is an integer. Enter 0 to display complete lineage. Enter a number N to display the lineage for N hops from the seed node.	Query	Integer
direction	Optional. Direction to traverse for lineage. Enter one of the following parameters: - BOTH - IN - OUT Default is BOTH.	Query	String
removeDuplicateAggregateLinks	Optional. Select **true** if you do not want the duplicate aggregate links to appear in the response. Default is true. Sometimes, the scanners create duplicate aggregate links.	Query	Boolean
includeTerms	Optional. Select **true** if the connected business terms are to be embedded in the response. Default is false.	Query	Boolean
includeAttribute	Optional. Enter one or more attribute IDs that you want to embed in the response.	Query	Array [String]

Parameter	Description	Parameter Type	Data Type
includeRefObjects	Optional. Include reference objects in the object relationships details. Default is false.	Query	Boolean
edgeQuery	Optional. Enter edges to filter the relationships.	Query	Array [String]

Response Codes

Code	Reason
200	Listed relationships.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET --header "Accept: application/json" "http://<CatalogAdmin>:<port>/access/2/
catalog/data/relationships?
seed=<seedValue>&association=<AssociationValue>&depth=<depthValue>&direction=<Direction>&
removeDuplicateAggregateLinks=<true/false>&includeTerms=<true/false>"
```

Understanding the Output

When you pass the API query parameters to a REST client, the client retrieves and displays relationships that match your search query.

The following table lists the important parameters in the output:

Parameter	Description
items	The list of lineage links or associations.
items : associationId	The association type of the link.
items : inEmbedded	The downstream object of the link.
items : inEmbedded : businessTerms	The business terms associated with the downstream object.
items : inEmbedded : businessTerms : classType	The class type of business terms associated with the downstream object.
items : inEmbedded : businessTerms : href	The URL of business terms associated with the downstream object.
items : inEmbedded : businessTerms : id	The ID of business terms associated with the downstream object.

Parameter	Description
items : inEmbedded : businessTerms : name	The name of the business terms associated with the downstream object.
items : inEmbedded : businessTerms : readOnly	Indicates if the business term is read only.
items : inEmbedded : facts	The facts of the downstream object.
items : inEmbedded : facts : attributeId	The attribute ID of facts of the downstream object.
items : inEmbedded : facts : label	The label of the fact.
items : inEmbedded : facts : projectedFrom	Indicates that if the attribute is a reference attribute, it is projected from the actual attribute.
items : inEmbedded : facts : readOnly	Indicates if the fact is read only.
items : inEmbedded : facts : value	The value of the fact.
items : inId	The object ID of the downstream object.
items : inResource	The resource name of the downstream object.
items : outEmbedded	The upstream object of the link.
items : outEmbedded : businessTerms	The business terms associated with the upstream object.
items : outEmbedded : businessTerms : classType	The class type of business terms associated with the upstream object.
items : outEmbedded : businessTerms : href	The URL of business terms associated with the upstream object.
items : outEmbedded : businessTerms : id	The ID of business terms associated with the upstream object.
items : outEmbedded : businessTerms : name	The name of the business terms associated with the upstream object.
items : outEmbedded : businessTerms : readOnly	Indicates if the business term is read only.
items : outEmbedded : facts	The facts of the upstream object.
items : outEmbedded : facts : attributeId	The attribute ID of the fact.
items : outEmbedded : facts : label	The label of the fact.
items : outEmbedded : facts : projectedFrom	Indicates that if the attribute is a reference attribute, it is projected from the actual attribute.
items : outEmbedded : facts : readOnly	Indicates if the fact is read only.
items : outEmbedded : facts : value	The value of the fact.
items : outId	The object ID of the upstream object.
items : outResource	The resource name of the upstream object.

Parameter	Description
items : properties	The properties of the link.
items : properties : attributeId	The attribute ID of the link.
items : properties : label	The label of the link.
items : properties : value	The value of the link.

List the Catalog Search Results

Use the List Catalog Search Results API to return the catalog search results.

The API supports the GET method.

GET request

To return the catalog search results, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/search
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
q	Optional. Use to create a query that searches matching objects. Uses Apache Lucene to interpret the query.	Query	String
basicQuery	Optional. A query string. Uses blockjoin faceting to interpret the query. See Apache Lucene for more information.	Query	String
fq	Optional. Filter queries to apply on the **q** parameter. Useful to apply facets.	Query	Array [String]
facet	Optional. Select **true** to return facets for the query.	Query	Boolean
defaultFacets	Optional. Select **true** to return facets for the query.	Query	Boolean
facetId	Optional. Enter one or more facets to include in the query if the **facet** parameter is true.	Query	Array [String]
queryFacetJson	Optional. Enter one or more query facets in JSON format to create an on-the-fly facet when the **facet** parameter is true.	Query	Array [String]
fieldFacetJson	Optional. Enter one or more field facets in JSON format to create an on-the-fly facet when the **facet** parameter is true.	Query	Array [String]
sliderFacetJson	Optional. Enter one or more slider facets in JSON format to create an on-the-fly facet when the **facet** parameter is true.	Query	Array [String]

Parameter	Description	Parameter Type	Data Type
rootTo	Optional. Join results to resource or data set. Choose one of the following parameters: - RESOURCE - DATA_SET	Query	String
relatedId	Optional. Specifies the object ID for which the related assets appear.	Query	Array [String]
highlight	Optional. Select **true** to highlight the tokens in different properties of an asset.	Query	Boolean
offset	Optional. The starting point in the results. The results after the offset value is displayed. Default is 0.	Query	Integer
pageSize	Optional. The number of results to display in a page. Default is 20 results per page.	Query	Integer
sort	Optional. The filter to sort results. Choose one of the following parameters: - relevance(score) - core.name_sort asc - core.name_sort desc Default is **relevance(score)**.	Query	String
cursor	Optional. As an alternative to offset, this parameter can provide faster paginated results when Enterprise Data Catalog performs deep paging.	Query	String
shards	Optional. The list of search shards to query. Default is queries all the shards.	Query	Array [String]
tabId	Optional. The tab ID to apply the filters.	Query	String
fl	Optional. Specifies the fields to include in the query response.	Query	Array [String]
qf	Optional. Specifies the fields in the index to use in query. Enter index attributes that have **index="true"** in the view model.	Query	Array [String]
enableLegacySearch	Optional. Search in legacy fields. Default is false.	Query	Boolean
disableSemanticSearch	Optional. Semantic search or auto filter objects in search. Default is false.	Query	Boolean
includeRefObjects	Optional. Include reference objects in search. Default is false.	Query	Boolean

Response Codes

Code	Reason
200	Returns the search results.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET --header "Accept: application/json" "http://<CatalogAdmin>:<port>/access/2/
catalog/data/search?
basicQuery=CUSTOMERTIER&facet=false&defaultFacets=true&highlight=true&offset=0&pageSize=2
0" -H "accept: application/json"
```

Understanding the Output

When you pass the API query parameters to a REST client, the client retrieves and displays search results that match your search query.

The following table lists the important parameters in the output:

Parameter	Description
metadata	The metadata of the search.
metadata : totalCount	The total number of results.
metadata : partialResults	If true, the response does not contain results from all the appropriate shards.
metadata : nextCursorMark	Indicates that the request supports cursor pagination.
tabRedirect	Indicates that the search prefilter is changed to All on the search results page.
appliedFilters	If true, it indicates that semantic search is performed and objects are auto filtered.
facetResults	The facets returned for the search query in the first page.
hits	The total number of hits.
hits : id	The external object ID of the searched object.
hits : href	The URL of the searched object.
hits : nativeId	The internal object ID of the searched object.
hits : values	The indexed facts of the searched object.
hits : values : attributeId	The attribute ID of the indexed fact.

Parameter	Description
hits : values : label	The label of the indexed fact.
hits : values : value	The value of the indexed fact.
hits : values : highlights	Highlights the keyword that matches the search term.
hits : subHits	The child object of objects that are returned on the search results page.

List the Suggestions

Use the List Suggestions API to lists suggestions.

The API supports the GET method.

GET request

To list suggestions, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/suggest
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
basicQuery	Required. The query string. All characters are treated as literals except the * character, which represents a wildcard	Query	String
pageSize	Optional. The number of results to display in a page. Default is 20 results per page.	Query	Integer

Response Codes

Code	Reason
200	Returns suggestions.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET --header "Accept: application/json" "http://<CatalogAdmin>:<port>/access/2/
catalog/data/suggest?basicQuery=Customer&pageSize=20" -H "accept: application/json"
```

Understanding the Output

When you pass the API query parameters to a REST client, the client retrieves and displays suggestions that match your query.

The following table lists the important parameters in the output:

Parameter	Description
suggestions	The list of suggestions.

Object Modification APIs

You can use the following Object Modification REST APIs to update the custom properties of an object:

Model Modification REST API	Description
PUT data/objects	Updates the custom properties for multiple objects
PUT data/objects/{id}	Updates the custom properties for an object

Data Objects Modification

Use the Data Objects Modification API to update the custom properties of multiple objects.

The API supports the PUT method.

PUT request

To update the custom properties of multiple objects, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/data/objects
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
objects	Required. The data objects for which you want to update the custom properties.	Body	Model
If-Match	Optional. Enter a value to display the results that match the value. Do not update if the entity tag or Etag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type	Values
businessTerms	Optional. Associated business terms	Array [String]	Enter the following parameters: - id. The ID of the associated business term. - readOnly. Enter true if the object reference cannot be modified and cannot be included in requests to the server.
facts	Required. List of facts that apply to this object.	Array [String]	Enter the following parameters: - attributeId. Enter the attribute ID. - projectedFrom. Enter the ID of the object from which the fact is projected. - readOnly. Enter true if the fact cannot be modified and cannot be included in requests to the server. - value. Enter the fact value. This parameter is ignored if you provide the projectedFrom parameter.
id	Required. The ID of the object resource.	String	Enter the resource ID.
srcLinks	Optional. An upstream of objects.	Array [String]	Enter the following parameters: - association. Enter the association ID. - id. Enter the ID of the resource object. - linkProperties. Enter the attribute ID and link property value. - readOnly. Enter true if the link cannot be modified and cannot be included in requests to the server

Response Codes

Code	Reason
201	Created.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT --header "Accept: application/json" -d "28037" "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects"
```

Data Object Modification IDs

Use the Data Object Modification IDs API to update custom object properties of an object.

The API supports the PUT method.

PUT request

To update custom object properties of an object, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/data/objects/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the object.	Path	String
objects	Required. The data object for which you want to update the custom properties.	Body	Model
If-Match	Optional. Enter a value to display the results that match the value. Do not update if the entity tag or Etag for the resource has changed.	Header	String

Attribute Parameters

Parameter	Description	Data Type	Values
businessTerms	Optional. Associated business terms.	Array [String]	Enter the following parameters: - id. The ID of the associated business term. - readOnly. Enter true if the object reference cannot be modified and cannot be included in requests to the server.
facts	Required. List of facts that apply to this object.	Array [String]	Enter the following parameters: - attributeId. Enter the attribute ID. - projectedFrom. Enter the ID of the object from which the fact is projected. - readOnly. Enter true if the fact cannot be modified and cannot be included in requests to the server. - value. Enter the fact value. This parameter is ignored if you provide the projectedFrom parameter.
id	Required. The ID of the object resource.	String	Enter the resource ID.
srcLinks	Optional. An upstream of objects.	Array [String]	Enter the following parameters: - association. Enter the association ID. - id. Enter the ID of the resource object. - linkProperties. Enter the attribute ID and link property value. - readOnly. Enter true if the link cannot be modified and cannot be included in requests to the server

Response Codes

Code	Reason
201	Created.
400	Missing or invalid parameter.

Code	Reason
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT --header "Accept: application/json" -d "cust" "http://<CatalogAdmin>:<port>/
access/2/catalog/data/objects/100"
```

Object Reviews APIs

You can use the following Object Reviews REST APIs for the objects in the catalog:

Model Information REST API	Description
GET data/objects/{id}/reviews	Lists the reviews and ratings for an object
POST data/objects/{id}/reviews	Creates a review for an object
GET data/objects/{id}/reviews/{reviewId}	Lists the reviews and ratings for a specific review
PUT data/objects/{id}/reviews/{reviewId}	Updates a specific review
DELETE data/objects/{id}/reviews/{reviewId}	Deletes a specific review
GET data/objects/{id}/reviews/{reviewId}/vote	Lists aggregated votes for a review
POST data/objects/{id}/reviews/{reviewId}/vote	Creates a vote for a review
DELETE data/objects/{id}/reviews/{reviewId}/vote	Deletes a vote for a review

List All the Reviews and Ratings for an Object

Use the List the Reviews and Ratings for an Object API to list all the reviews and ratings for a data object.

The API supports the GET method.

GET request

To list all the reviews and ratings for a data object, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/reviews
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
userFilter	Optional. Choose one of the following user-based filter parameters: - MY_REVIEW_ONLY - EXCLUDING_MY_REVIEW	Query	String
ratingFilter	Optional. Choose one of the following rating filters: - ONE_AND_ABOVE - TWO_AND_ABOVE - THREE_AND_ABOVE - FOUR_AND_ABOVE	Query	String
sortOn	Optional. Choose one of the following parameters to sort comments: - TIMESTAMP - VOTE_COUNT - RATING	Query	String
offset	Optional. The offset position from which the API lists the results. Default is 0.	Query	Integer
pageSize	Optional. The number of results to be display in a page. Default is 20.	Query	Integer

Response Codes

Code	Reason
200	Returned all reviews and ratings on single object.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/34523/reviews?
userFilter=MY_REVIEW_ONLY&ratingFilter=FOUR_AND_ABOVE&sortOn=VOTE_COUNT&offset=0&pageSize
=20" -H  "accept: application/json"
```

Create a Review for an Object

Use the Create a Review for an Object API to create a review for a data object.

The API supports the POST method.

POST request

To create a review for a data object, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/data/objects/{id}/reviews
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
object	Required. Enter the following review options: - ratings. Enter the rating type and rating value. You can rate a review on a scale of 1 through 5. - reviewText. Enter a review for the object.	Body	-

Response Codes

Code	Reason
201	Created a review for the specified data object.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/22234/reviews" -
H  "accept: application/json" -H  "Content-Type: application/json" -d "{  \"ratings\":
[    {      \"ratingType\": \"Good\",      \"ratingValue\": 3    }  ],  \"reviewText\":
\"Good.\"}"
```

List the Details for a Review

Use the List the Details for a Review API to list the review details.

The API supports the GET method.

GET request

To list the review details, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/reviews/{reviewId}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
reviewId	Required. The ID of the review.	Path	String

Response Codes

Code	Reason
200	Review object.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/34678/reviews/
875" -H  "accept: application/json"
```

Update An Existing Review

Use the Update An Existing Review API to update an existing review for a data object.

The API supports the PUT method.

PUT request

To update an existing review for a data object, submit a PUT request with the following URI:

```
PUT <baseApiURL>/access/2/catalog/data/objects/{id}/reviews/{reviewId}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of a data object.	Path	String
reviewId	Required. The ID of a review.	Path	String

Parameter	Description	Parameter Type	Data Type
object	Required. Enter the following review options: - ratings. Enter the rating type and rating value. You can rate a review on a scale of 1 through 5. - reviewText. Enter a review for the object.	Body	-
If-Match	Optional. Identify the ETag for the resource. Enterprise Data Catalog does not update the resource if the ETag for the resource has changed.	Header	String

Response Codes

Code	Reason
201	Updated the review.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X PUT "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/87656/reviews/
5456" -H  "accept: application/json" -H  "Content-Type: application/json" -d
"{  \"ratings\": [    {      \"ratingType\": \"Good\",      \"ratingValue\": 3    }  ],
\"reviewText\": \"Helpful\"}"
```

Delete Reviews and Ratings for a Data Object

Use the Delete Reviews and Ratings for a Data Object API to delete the reviews and ratings for a data object.

The API supports the DELETE method.

DELETE request

To delete the reviews and ratings for a data object, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/data/objects/{id}/reviews/{reviewId}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
reviewId	Required. The ID of the review.	Path	String

Response Codes

Code	Reason
200	Deleted reviews and ratings for the data object.
204	No content to display.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/23453/
reviews/22224" -H  "accept: application/json"
```

List the Aggregated Votes for a Review

Use the List the Aggregated Votes for a Review API to list the total number of votes for the specified review.

The API supports the GET method.

GET request

To list the total number of votes for the specified review, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objects/{id}/reviews/{reviewId}/vote
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
reviewId	Required. The ID of the review.	Path	String

Response Codes

Code	Reason
200	Listed the votes for the specified review.
400	Missing or invalid parameter.
401	Missing credentials.

Code	Reason
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/3424/reviews/332/
vote" -H  "accept: application/json"
```

Create a Vote for a Review

Use the Create a Vote for Review API to create a vote for a review.

The API supports the POST method.

POST request

To create a vote for a review, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/data/objects/{id}/reviews/{reviewId}/vote
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
reviewId	Required. The ID of a review.	Path	String
object	Required. Enter HELPFUL or NOT_HELPFUL as voteKind.	Body	-

Response Codes

Code	Reason
200	Upvote on comment.
201	Created a vote for the specified review successfully.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/3456/
reviews/333/vote" -H  "accept: application/json" -H  "Content-Type: application/json" -d
"{  \"voteKind\": \"HELPFUL\"}"
```

Delete Votes for a Review

Use the Delete Votes for a Review API to delete the vote for a specific review.

The API supports the DELETE method.

DELETE request

To delete the vote for a specific review, submit a DELETE request with the following URI:

```
DELETE <baseApiURL>/access/2/data/objects/{id}/reviews/{reviewId}/vote
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String
reviewId	Required. The ID of the review.	Path	String

Response Codes

Code	Reason
200	Deleted the votes for the specified review.
204	No content to display.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
412	Conflicting edit detected.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X DELETE "http://<CatalogAdmin>:<port>/access/2/catalog/data/objects/3333/
reviews/223/vote" -H  "accept: application/json"
```

Object Child Count REST API

You can use the Object Child Count REST API to list the total number of child assets for an object.

List the Child Count

Use the List the Child Count API to list the total number of child assets for an object.

The API supports the GET method.

GET request

To list the total number of child assets for an object, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/objectsChildSummary/{id}
```

You can use the following parameter in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. The ID of the data object.	Path	String

Response Codes

Code	Reason
200	Listed the total number of child assets for an object.
400	Missing or invalid parameter
401	Missing credentials
403	User does not have the required access permissions
404	Requested object not found
429	Rate limit for requests encountered

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/objectsChildSummary/
543534" -H  "accept: application/json"
```

CHAPTER 9

Product Info REST API

This chapter includes the following topic:

- Product Information REST APIs Overview, 202

Product Information REST APIs Overview

You can use the Product Info API to list the details about Enterprise Data Catalog, which includes release version, build version, and build date.

List Enterprise Data Catalog Details

Use the List Enterprise Data Catalog Details API to list the details about Enterprise Data Catalog which include release version, build version, and build date.

The API supports the GET method.

GET request

To list the details about Enterprise Data Catalog, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/data/productInformation
```

Response Codes

Code	Reason
200	Listed the details about Enterprise Data Catalog.
400	Missing or invalid parameter
401	Missing credentials
403	User does not have the required access permissions
404	Requested object not found
429	Rate limit for requests encountered

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/data/productInformation" -H
"accept: application/json"
```

CHAPTER 10

Resource REST APIs

This chapter includes the following topics:

- Resource REST APIs Overview, 203
- Resource Execution API, 203
- Resource Info API, 204

Resource REST APIs Overview

You can run Resource Execution API to manually load a resource and Resource Info API to monitor a resource job in Enterprise Data Catalog.

Resource Execution API

Administrators can run the *POST <CatalogAdmin>:<port>/access/2/catalog/resources/jobs/loads* REST API to manually load the specified resource.

Load Resource Job

Use the Load Resource Job API to trigger a resource run for the specified resource.

The API supports the POST method.

POST request

To trigger a resource run for the specified resource, submit a POST request with the following URI:

```
POST <baseApiURL>/access/2/catalog/resources/jobs/loads
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
resourceExecutionRequest	Required. Name of the resource.	Body	String

Response Codes

Code	Reason
200	Submitted the resource job to run.
201	Created a resource.
400	Missing or invalid resource name.
401	Missing login credentials.
403	User does not have the access permission to view or edit the resource.
404	Requested resource not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X POST "http://<CatalogAdmin>:<port>/access/2/catalog/resources/jobs/loads" -H
"accept: application/json" -H  "Content-Type: application/json" -d "{  \"resourceName\":
\"OracleResource\"}"
```

Resource Info API

You can run the *GET <CatalogAdmin>:<port>/access/2/catalog/resources/jobs/loads/{id}* REST API to get the job status for the specified resource.

Monitor a Resource Job

Use the Monitor a Resource Job API to list the job status of the specified resource.

The API supports the GET method.

GET request

To list the job status of the specified resource, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/resources/jobs/loads/{id}
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
id	Required. ID of the resource job.	Path	String

Response Codes

Code	Reason
200	Listed the details about the specified resource job.
400	Missing or invalid resource name
401	Missing login credentials
403	User does not have the access permission to view or edit the resource
404	Requested resource not found
429	Rate limit for requests encountered

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/resources/jobs/loads/232" -H
"accept: application/json"
```

CHAPTER 11

Security REST API

This chapter includes the following topic:

- Security REST API Overview, 206

Security REST API Overview

You can use the Security API to list the access permissions on resources for specific users and groups.

List Access Filters

Use the List Access Filters API to access permissions for resources and assets in Enterprise Data Catalog.

The API supports the GET method.

GET request

To access permissions for resources and assets in Enterprise Data Catalog, submit a GET request with the following URI:

```
GET <baseApiURL>/access/2/catalog/security/accessFilters
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
memberName	Optional. The name of the user or group to filter the list.	Query	string
includeInherited	Optional. Choose **true** if you want to retrieve the access filters assigned to groups that the user belongs to.	Query	boolean
memberType	Optional. Specify whether the value that you entered for the **memberName** parameter is the name of a user or a group. Provide one of the following values: - USER - GROUP	Query	string
offset	Optional. The offset position from which the list of permissions must start. Default is 0.	Query	integer

Parameter	Description	Parameter Type	Data Type
pageSize	Optional. The number of results to be displayed on a page. Default is 20.	Query	integer
resourceName	Optional. The name of the resource to filter the list.	Query	string

Response Codes

Code	Reason
200	Listed the access filters.
400	Missing or invalid parameter.
401	Missing credentials.
403	User does not have the required access permissions.
404	Requested object not found.
429	Rate limit for requests encountered.

Sample Call Using Curl

```
curl -X GET "http://<CatalogAdmin>:<port>/access/2/catalog/security/accessFilters?
includeInherited=false&memberType=USER&offset=0&pageSize=20&resourceName=Ora" -H
"accept: application/json"
```

CHAPTER 12

Analytics APIs

This chapter includes the following topics:

- Analytics REST APIs Overview, 208
- Accessing the APIs, 208
- Analytics REST APIs, 208

Analytics REST APIs Overview

You can use Analytics REST APIs to list the data from charts and hero stats in Data Asset Analytics.

Accessing the APIs

You can use the following URL to view the list of REST APIs for Data Asset Analytics:
`<CatalogAdmin>:<port>/analytics/swagger-ui.html#/`
`<CatalogAdmin>` represents the URL of the machine where you installed Catalog Administrator. `<port>` represents the port number configured for the Catalog Service.

You can use any standard HTTP client to call the REST APIs.

Analytics REST APIs

You can use the following Analytics REST APIs to list the data from charts and hero stats in Data Asset Analytics:

Analytics REST API	Description
POST getChartData	Returns the Dashboard Data from charts.
POST getHeroStatsData	Returns the Dashboard Data from hero stats.

List Chart Data

Use the List Chart Data API to list the chart data from Data Asset Analytics.

The API supports the POST method.

POST request

To list the chart data from Data Asset Analytics, submit a POST request with the following URI:

```
POST <baseApiURL>/analytics/v1/getChartData
```

You can use the following parameters in the request:

<table>
<tr><th>Parameter</th><th>Description</th><th>Parameter Type</th><th>Data Type</th></tr>
<tr><td>chartFilter</td><td>Optional. Provide the list of filters that you want to apply to the chart in the following format:
<pre>{
"filter1": "value",
"filter2": "value"
}</pre>You can apply the following filters to the charts:
<table><tr><th>Chart</th><th>Filter</th></tr><tr><td>Active User Growth</td><td>USER_GROUP_NAME</td></tr><tr><td>User Searches</td><td>USER_GROUP_NAME</td></tr><tr><td>Data Assets with Lineage and Impact</td><td>ASSET_GROUP</td></tr><tr><td>Assets with Enrichment</td><td>- ASSET_GROUP
- ENRICH_TYPE</td></tr><tr><td>Asset Growth</td><td>RESOURCE_NAME</td></tr><tr><td>Asset Changes</td><td>RESOURCE_NAME</td></tr></table></td><td>Body</td><td>Model</td></tr>
<tr><td>chartName</td><td>Required. The name of the chart from which the data must be listed. Provide one of the following values:
- UserLogins
- ActiveUserGrowth
- UserSearches
- TopAssetsViewed
- ResourceGrowth
- AssetGrowth
- Top15ResourceTypes
- AssetChanges
- AssociatedBusinessTerms
- AssetsWithLineageAndImpact
- AssetsWithEnrichment
- DegreeOfCollaborationAcrossResources
- TopCollaborators
- CollaborationActivity
- TopAssetsWithCollaboration
- AssetEnrichmentValue
- FeatureUsageValue
- CollaborationValue
- ResourceValue</td><td>Query</td><td>String</td></tr>
</table>

Parameter	Description	Parameter Type	Data Type
fromDate	Required. Specify the start date for the time range for which you want to view the chart data. Enter the date in MM/DD/YYYY format.	Query	String
toDate	Required. Specify the end date for the time range for which you want to view the chart data. Enter the date in MM/DD/YYYY format.	Query	String

Response Codes

Code	Reason
200	List the chart data
400	Missing or invalid parameter
401	Missing credentials
404	Chart not found
500	Internal server error

Sample Call Using Curl

```
curl -X POST "http://<DataAssetAnalytics>:<port>/analytics/v1/getChartData?
chartName=TopAssetsViewed&fromDate=04%2F10%2F2020&toDate=01%2F01%2F2021" -H "accept:
application/json" -H "Content-Type: application/json" -d "{ \"additionalProp1\": \"string
\", \"additionalProp2\": \"string\", \"additionalProp3\": \"string\"}"
```

List Hero Stats Data

Use the List Hero Stats Data API to list the hero stats data from Data Asset Analytics.

The API supports the POST method.

POST request

To list the hero stats data from Data Asset Analytics, submit a POST request with the following URI:

```
POST <baseApiURL>/analytics/v1/getHeroStatsData
```

You can use the following parameters in the request:

Parameter	Description	Parameter Type	Data Type
fromDate	Required. Specify the start date for the time range for which you want to view the hero stats. Enter the date in MM/DD/YYYY format.	Query	String
toDate	Required. Specify the end date for the time range for which you want to view the hero stats. Enter the date in MM/DD/YYYY format.	Query	String

Response Codes

Code	Reason
200	List the hero stats data
400	Missing or invalid parameter
401	Missing credentials
500	Internal server error

Sample Call Using Curl

```
curl -X POST "http://<DataAssetAnalytics>:<port>/analytics/v1/getHeroStatsData?
fromDate=04%2F10%2F2020&toDate=01%2F01%2F2021" -H "accept: application/json"
```

CHAPTER 13

Use Cases

This chapter includes the following topics:

- Sample Use Cases, 213
- Retrieve Attribute Details, 214
- Retrieve Attribute Details for a Class, 215
- Retrieve Objects Using Object Name, 215
- Retrieve Object Details Using Object ID, 216
- Retrieve Relationships Between Objects, 216
- Update Custom Attribute, 217
- Update a Custom Attribute and Custom Reference Attribute for an Object, 218
- Create Custom Attribute, 219
- Create Reference Attribute, 220
- Load Resource Job, 221
- Monitor a Resource Job, 221

Sample Use Cases

The sample use cases provide scenarios to show you how you can use the REST APIs to retrieve or update information. The samples include Java code samples that you can use with the bundled Java client and the Curl call samples for the REST APIs.
The following are the list of sample use cases for the REST APIs:

- Retrieve the last modified details of an attribute.
- Retrieve the attribute details of a class.
- Retrieve objects using object name.
- Retrieve object details using object ID.
- Retrieve relationships for columns.
- Create a custom attribute with specific properties to search for locations based on a ZIP code.
- Update a custom attribute and custom reference attribute for an object.
- Update a custom attribute.
- Create a custom reference attribute that updates a change to the attribute across all the fields where the attribute is associated.

The commands common for all the sample use cases to import the package, included models, HTTP client, and the code to initialize the Java client are provided for reference:

```
// Copyright (c) 2017 Informatica Corporation. All rights reserved.

package com.infa.products.ldm.ingestion.rest.api.samples;

import com.infa.products.ldm.core.rest.v2.client.api.CatalogApi;
import com.infa.products.ldm.core.rest.v2.client.invoker.ApiException;
import com.infa.products.ldm.core.rest.v2.client.invoker.ApiResponse;
import com.infa.products.ldm.core.rest.v2.client.models.AttributePostRequest;
import com.infa.products.ldm.core.rest.v2.client.models.AttributePutRequest;
import com.infa.products.ldm.core.rest.v2.client.models.AttributeResponse;
import com.infa.products.ldm.core.rest.v2.client.models.AttributesRequest;
import com.infa.products.ldm.core.rest.v2.client.models.AttributesResponse;
import com.infa.products.ldm.core.rest.v2.client.models.FactRequest;
import com.infa.products.ldm.core.rest.v2.client.models.Link;
import com.infa.products.ldm.core.rest.v2.client.models.Links;
import com.infa.products.ldm.core.rest.v2.client.models.ModelRefRequest;
import com.infa.products.ldm.core.rest.v2.client.models.ObjectIdRequest;
import com.infa.products.ldm.core.rest.v2.client.models.ObjectResponse;
import com.infa.products.ldm.core.rest.v2.client.models.ObjectsResponse;
import com.infa.products.ldm.core.rest.v2.client.models.RefAttributePost;
import com.infa.products.ldm.core.rest.v2.client.models.RefAttributesPost;
import com.infa.products.ldm.core.rest.v2.client.models.RefAttributesResponse;
import com.infa.products.ldm.core.rest.v2.client.utils.ObjectAdapter;

import java.math.BigDecimal;
import java.util.ArrayList;
import java.util.Arrays;
import java.util.List;

import com.squareup.okhttp.CurlLogger;
public class RestSamples {

  private final CatalogApi api;

  /**
   * Initialize the api client. Must be done once before it can be used.
   *
   * @param username
   * @param password
   * @param basePath Base URL of rest api ex. http://localhost:8080/access/2
   */
  public RestSamples(String username, String password, String basePath) {
    this.api = new CatalogApi();
    this.api.getApiClient().setUsername(username);
    this.api.getApiClient().setPassword(password);
    this.api.getApiClient().setBasePath(basePath);
  }
```

Retrieve Attribute Details

The sample use case is to retrieve the last modified details of an attribute.
You can use the REST API to retrieve the information in one of the following ways:

Using Java code and the Bundled Java Client

```
  public void getAttributeLastModifiedDetails() throws ApiException {
      final String attributeId = "core.lastModified";
  // Method 1, filter catalog/models/attributes using id parameter
  AttributesResponse attrsResponse = this.api.catalogModelsAttributesGet(
          new ArrayList<>(Arrays.asList(attributeId)), null, null, null);
      AttributeResponse attrResponse = attrsResponse.getItems().get(0);
      attrResponse.getSearchable();
  //Method 2, use the attributeId to directly fetch the details
```

```
attrResponse = this.api.catalogModelsAttributesIdGet(attributeId);
    attrResponse.getDataTypeId();
  }

}
```

Using Curl

```
// Method 1, filter catalog/models/attributes using id parameter
    curl -X GET --header "Accept: application/json" "http://localhost:13000/2/
catalog/models/attributes?id=core.lastModified"//
//Method 2, use the catalog/models/attributes/{id} to directly fetch the details
    curl -X GET --header "Accept: application/json" "http://localhost:13000/2/
catalog/models/attributes/core.lastModified"
```

Retrieve Attribute Details for a Class

The sample use case is to retrieve the attribute details of a class and all the included sub classes.
You can use the REST API and create the custom reference attribute in one of the following ways:

Using Java code and the Bundled Java Client

```
public void getAttributesForClassDataElement() throws ApiException {
    final String classId = "core.DataElement";

    AttributesResponse response = null;
    List<String> attributeNames = new ArrayList<>();
    int offset = 0;
    do {
response = this.api.catalogModelsAttributesGet(null,
          new ArrayList<>(Arrays.asList(classId)),
          new BigDecimal(offset),
          new BigDecimal(20));

      // Increment offset to fetch next page
      offset += 20;

      for (AttributeResponse attr : response.getItems()) {
        attributeNames.add(attr.getName());
      }

      // If there are more than 20 results, you can do a loop operation to fetch all
the results
    } while (offset < response.getMetadata().getTotalCount().intValue());
  }
  }

}
```

Using Curl

```
curl -X GET --header "Accept: application/json" "http://localhost:13000/2/catalog/
models/attributes?classId=core.DataElement&offset=0&pageSize=20"
```

Retrieve Objects Using Object Name

The sample use case is to find all the tables that has the word **Customer** in the table name.
You can use the REST API to retrieve the information in one of the following ways:

Using Java code and the Bundled Java Client

```
  public void searchForObjects() throws ApiException {
    BigDecimal offset = BigDecimal.ZERO;
    final BigDecimal pageSize = BigDecimal.valueOf(20);
    ObjectsResponse response = null;

    do {
      response = this.api.catalogDataObjectsGet(
          "core.name:*customer* AND core.classType:com.infa.ldm.relational.Table",
null, offset, pageSize, false);

      for (ObjectResponse obj : response.getItems()) {
        // Do something with the returned objects
        obj.getFacts();
      }

      offset = offset.add(pageSize);
    } while (response.getMetadata().getTotalCount().longValue() >
pageSize.longValue());
  }
```

Using Curl

```
curl -X GET --header "Accept: application/json" --header "Content-Type: application/
json" "http://localhost:13000/2/catalog/data/objects?q=core.name%3A*customer*%20AND
%20core.classType%3Acom.infa.ldm.relational.Table&offset=0&pageSize=20&related=false"
```

Retrieve Object Details Using Object ID

The sample use case is to use the object ID **resource://1262125** to retrieve the details of the object. You can use the REST API to retrieve the information in one of the following ways:

Using Java code and the Bundled Java Client

```
public void getObjectDetails() {
    try {
      ObjectResponse response = this.api.catalogDataObjectsIdGet("resource://
1262125");
      // Do something with the returned object
      response.getFacts();
    } catch (ApiException e) {}
  }} catch (ApiException e) {}
  }
```

Using Curl

```
              curl -X GET --header "Accept: application/json" --header "Content-
Type: application/json" "http://localhost:13000/2/catalog/data/objects/
resource~3a~~2f~~2f~1262125"
      ObjectResponse response = this.api.catalogDataObjectsIdGet("resource://
1262125");
```

Retrieve Relationships Between Objects

The sample use case is to retrieve the columns that are downstream in the data flow from the **Employee_Name** column.

You can use the REST API to retrieve the information in one of the following ways:

Using Java code and the Bundled Java Client

```
 public void getDownstreamColumns() {
    try {
      Links links = this.api.catalogDataRelationshipsGet(new
ArrayList<>(Arrays.asList("resource://Employees/Name")),
          new ArrayList<>(Arrays.asList("core.DataFlow")), BigDecimal.ZERO, "OUT",
true, false,
          new ArrayList<>(Arrays.asList("core.name")));

      for (Link link : links.getItems()) {
        // Do something with the returned link
        link.getOutEmbedded().getFacts();
      }
    } catch (ApiException e) {}
  }
```

Using Curl

```
curl -X GET --header "Accept: application/json" --header "Content-Type: application/
json" "http://localhost:13000/2/catalog/data/relationships?seed=resource%3A%2F
%2FEmployees
%2FName&association=core.DataFlow&direction=OUT&removeDuplicateAggregateLinks=true&de
pth=0&includeTerms=false&includeAttribute=core.name"
```

Update Custom Attribute

The sample use case is to search for a custom attribute by the name `Region` that needs to be updated with the following properties:

- Boost value for the custom attribute to be made **High**.
- The custom attribute must be displayed in the list of facets.
- The description of the custom attribute must be updated to `Custom attribute to search for locations based on ZIP code.`

You can use the REST API and update the custom attribute in one of the following ways:

Using Java code and the Bundled Java Client

```
public void updateRegionCustomAttribute(String regionAttributeId) throws
ApiException {
// Fetch attribute to be updated
ApiResponse<AttributeResponse> httpResponse =
this.api.catalogModelsAttributesIdGetWithHttpInfo(
        regionAttributeId);
// ETag ensures there are no conflicting edits
   String etag = httpResponse.getHeaders().get("ETag").get(0);
   AttributeResponse attrResponse = httpResponse.getData();
// Copy the response into a request so that you can modify the request.
    AttributePutRequest attrRequest =
ObjectAdapter.INSTANCE.copyIntoAttributePutRequest(attrResponse);
    attrRequest.boost(AttributePutRequest.BoostEnum.HIGH);
    attrRequest.addClassesItem(new ModelRefRequest().id("core.DataElement"));
    attrRequest.facetable(true);
    attrRequest.description("Custom attribute to search for locations based on ZIP
code.");
this.api.catalogModelsAttributesIdPut(regionAttributeId, attrRequest, etag);
  }

}
```

Using Curl

```
// Fetch attribute to be updated
    curl -X GET --header "Accept: application/json" "http://localhost:13000/2/
```

```
catalog/models/attributes/
com.infa.appmodels.ldm.LDM_a496a2d3_0c07_47e6_a941_fe081ff90f01"
// Send request to update
    curl -X PUT --header "If-Match: 49590122486d7e1d2a726f4ff1bf3276" --header
"Accept: application/json" --header "Content-Type: application/json" -d "{
  \"boost\": \"HIGH\",
  \"name\": \"Region\",
  \"facetable\": true,
  \"description\": \"Custom attribute to search for locations based on ZIP code.\",
  \"classes\": [
    {
      \"id\": \"core.DataElement\"
    }
  ]
}" "http://localhost:13000/2/catalog/models/attributes/
com.infa.appmodels.ldm.LDM_a496a2d3_0c07_47e6_a941_fe081ff90f01"
```

Update a Custom Attribute and Custom Reference Attribute for an Object

The sample use case is to update a custom attribute and a custom reference attribute for an object. To update the object, you fetch the object and create a request object from the response. Next, configure the facts and send the request.

You can use the REST API to retrieve the information in one of the following ways:

Using Java code and the Bundled Java Client

```
public void setContactAndRegion(String contactAttrId, String regionAttrId) {
    try {
      // Fetch the object you want to update
      ApiResponse<ObjectResponse> objApiResponse =
this.api.catalogDataObjectsIdGetWithHttpInfo("resource://obj1");

      String etag = objApiResponse.getHeaders().get("ETag").get(0);
      ObjectResponse obj = objApiResponse.getData();

      // Always create a request object from response.
      ObjectIdRequest request = ObjectAdapter.INSTANCE.copyIntoObjectIdRequest(obj);

      // Set the fact values.
      // Since the contact is a reference attribute, set the projectedFrom field to
the id of the object that you are referencing instead of the value
      request.getFacts().add(new
FactRequest().attributeId(contactAttrId).projectedFrom("resource://User1"));

      // Region is a string, so set the value directly
      request.getFacts().add(new
FactRequest().attributeId(regionAttrId).value("North East"));

      // Send the request, etag is required to ensure no concurrent modifications
are made to the object.
      this.api.catalogDataObjectsIdPut("resource://obj1", request, etag);
    } catch (ApiException e) {}

  }

}
```

Using Curl

Fetch the object JSON to has to be updated. Also, read the ETag header returned in the response.

```
curl -X GET --header "Accept: application/json" --header "Content-Type: application/
json" "http://localhost:13000/2/catalog/data/objects/resource~3a~~2f~~2f~obj1"
```

From the returned JSON, remove all the read only facts and links. Do not remove any custom facts and links or they get deleted. Add the updated facts to JSON. Send the JSON along with ETag using curl command.

```
curl -X PUT --header "If-Match: 0f7ddbbfc724c49364bf632aa73a906b" --header "Accept:
application/json" --header "Content-Type: application/json" -d "{
  \"facts\": [
    {
      \"attributeId\":
\"com.infa.appmodels.ldm.LDM_c952777e_e2bd_4dfe_871c_80fa1a51087f\",
      \"projectedFrom\": \"resource://User1\"
    },
    {
      \"attributeId\":
\"com.infa.appmodels.ldm.LDM_de552671_6939_4f13_b68c_7b4f8d5e4c80\",
      \"value\": \"North East\"
    }
  ],
  \"srcLinks\": [],
  \"businessTerms\": []
}" "http://localhost:13000/2/catalog/data/objects/resource~3a~~2f~~2f~obj1"
```

Create Custom Attribute

The sample use case is to create a custom attribute with the with the following properties:

- The custom attribute must be named `Region`.
- The custom attribute must be of data type string.
- The boost value for the custom attribute must be Medium.
- The custom attribute can have multiple values.
- You must be able to search in the catalog using the custom attribute.
- You must be able to sort the catalog search results based on the custom attribute.
- The custom attribute must appear in suggestions.

You can use the REST API and create the custom reference attribute in one of the following ways:

Using Java code and the Bundled Java Client

```
public String createRegionCustomAttribute() throws ApiException {
    AttributesRequest attributes = new AttributesRequest()
        .addItemsItem(new AttributePostRequest()
            .name("Region")
            .dataTypeId("core.String")
            .boost(AttributePostRequest.BoostEnum.MEDIUM)
            .multivalued(true)
            .searchable(true)
            .sortable(true)
            .suggestable(true));
AttributesResponse response = this.api.catalogModelsAttributesPost(attributes);
    AttributeResponse createdAttribute = response.getItems().get(0);
    // Unique id is created by the system
    return createdAttribute.getId();
  }
  }
```

```
}
```

Using Curl

```
curl -X POST --header "Accept: application/json" --header "Content-Type: application/
json" -d "{
  \"items\": [
    {
      \"boost\": \"MEDIUM\",
      \"name\": \"Region\",
      \"dataTypeId\": \"core.String\",
      \"multivalued\": true,
      \"suggestable\": true,
      \"sortable\": true,
      \"searchable\": true,
      \"facetable\": false,
      \"classes\": []
    }
  ]
}" "http://localhost:13000/2/catalog/models/attributes
```

Create Reference Attribute

The sample use case is to create a reference attribute with the with the following properties:

- The custom reference attribute must be named `Contact`.
- The custom reference attribute projects the name of an ISP user into the Contact attribute field of an object.
- If the name of the ISP user changes, all the Contact custom reference attribute fields must be updated.
- The Contact custom reference attribute can be associated with any class.
- Provide the description for the custom reference attribute as `Person to contact for more information`.
- You must be able to search in the catalog using the custom reference attribute.

You can use the REST API and create the custom reference attribute in one of the following ways:

Using Java code and the Bundled Java Client

```
public void createContactReferenceAttribute() throws ApiException {
this.api.catalogModelsReferenceAttributesPost(new RefAttributesPost()
        .addItemsItem(new RefAttributePost()
            .name("Contact")
            .refDataTypeId("com.infa.ldm.isp.UserDatatype")
            .description("Person to contact for more information.")
            .searchable(false)
            .addClassesItem(new ModelRefRequest().id("core.IClass"))));
  }

}
```

Using Curl

```
curl -X POST --header "Accept: application/json" --header "Content-Type: application/
json" -d "{
  \"items\": [
    {
      \"refDataTypeId\": \"com.infa.ldm.isp.UserDatatype\",
      \"name\": \"Contact\",
      \"description\": \"Person to contact for more information.\",
      \"searchable\": false,
      \"classes\": [
```

```
        {
          \"id\": \"core.IClass\"
        }
      ]
    }
  ]
}" "http://localhost:13000/2/catalog/models/referenceAttributes"
```

Load Resource Job

The sample use case is to load a resource using the resource name.
You can use the REST API to retrieve the information in one of the following ways:

Using Java code and the Bundled Java Client

```
public void loadResource() throws ApiException {
JobPostRequest request = new JobPostRequest().resourceName("<resourceName>");
JobMonitor response = this.api.catalogResourcesJobsLoadsPost(request);
//Do something with the returned job details;
}
```

Using Curl

```
curl -X POST --header "Accept: application/json" --header "Content-Type: application/
json" -d "{
  "resourceName": "string"}"
"http://localhost:13000/2/catalog/resources/jobs/loads"
```

Monitor a Resource Job

The sample use case is to use the job ID to retrieve the details of the job.
You can use the REST API to retrieve the job details in one of the following ways:

Using Java code and the Bundled Java Client

```
public void getJobDetails(){
                try {
                    JobMonitor response=
this.api.catalogResourcesJobsLoadsIdGet("<jobID>");
                    //Do something with the returned job details;
                } catch (ApiException e){
                  }
}
```

Using Curl

```
curl -X GET --header "Accept: application/json" --header "Content-Type: application/
json"
"http://localhost:13000/2/catalog/resources/jobs/loads/<jobID>"
JobMonitor response = this.api.catalogResourcesJobsLoadsIdGet("<jobID>");
```