How-To Library

Informatica

High-Priority Scans in Enterprise Data Catalog

© Copyright Informatica LLC 2020, 2021. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

You can use the high-priority resource scan to extract metadata from a specific file or a folder and not the entire data source.

This article includes the guidelines and steps to trigger a high-priority resource scan.

Supported Versions

- Enterprise Data Catalog 10.4.0 or later

Table of Contents

Overview. 2
Guidelines to invoke High-Priority Resource Scans. 2
Invoking a High Priority Resource Scan. 2

Overview

A high-priority resource scan refers to configuring a resource to prioritize and scan a particular file or a folder and not the entire data source.

The following resources support high-priority scans in Enterprise Data Catalog:

- HDFS
- Microsoft Azure Blob Storage
- Azure Data Lake Store Gen1
- Azure Data Lake Store Gen2
- Amazon S3

Guidelines to invoke High-Priority Resource Scans

Consider the following guidelines before you invoke a high-priority resource scan:

- You must use the domain node to extract metadata from a specific file or folder.
- You can invoke high priority resource scans only by using the REST API.
- Execute a high priority resource scan in the Java Virtual Machine (JVM) where the Catalog Service is running, and not on a separate Yarn container in the Informatica cluster.
- You can append an ongoing resource scan to an existing scan using the **Cumulative** flag. By default, the **Cumulative** flag is set to true, and the resource scan results under the file path provided for the high priority resource scan execution are appended to the scan. If the flag is set to false, the previous scan results are deleted, and the metadata extracted by the current scan is available in the Catalog.

Invoking a High Priority Resource Scan

To invoke a high-priority resource scan, perform the following steps:

1. Create a resource in the Model Repository Service (MRS) using REST API or Catalog Administrator.
2. Execute the resource using the following URL:

http://<catalog_service_uri>/access/1/catalog/resources/<resource_name>/execute

3. Include a payload in the following format:

```
{
        "inputParams": [
            {
                "scannerId": "<core-scanner-id>",
                "params": [
                    {
                        "id": "FilePath",
                        "values": [
                            "<complete_path>"
                        ]
                    },
                    {
                        "id": "PRIORITY",
                        "values": [
                            "HIGH"
                        ]
                    },
                    {
                        "id": "Cumulative",
                        "values": [
                            "<Cumulative flag>"
                        ]
                    }
                ]
            }
        "scannersToExecute": [
            "<core-scanner-id>"
        ]
    }
```

- FilePath is the complete path of the file or folder in the data source.
- scannerID is the ID of the resource that you created using REST API or the Catalog Administrator.

You can view the metadata scan results of the specific file or folder in the Catalog UI.

Author

Shruthi Venkatesh