How-To Library

Informatica

Install Enterprise Data Catalog on Docker with Informatica Deployment Manager 10.5.3

© Copyright Informatica LLC 2022. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

Informatica Deployment Manager provides a quick and easy way to install the Informatica domain. This article describes how to install Enterprise Data Catalog on Docker from the Docker image using Informatica Deployment Manager.

Supported Versions

- Enterprise Data Catalog 10.5, 10.5.1, 10.5.2, and 10.5.3

Table of Contents

Overview. . . . 3
Informatica Deployment Manager Process Checklist. . . . 3
Before You Begin 4
Verify System Requirements. . . . 4
Set Up the Keystore and Truststore Files. . . . 4
Contact Informatica Global Customer Support. . . . 5
Set Up Databases. . . . 5
Generate Content for Silent Input Properties File. . . . 6
Build the Informatica Docker Image. . . . 6
Step 1. Choose the Deployment Type. . . . 6
Step 2. Configure the Docker Image. . . . 7
Step . Verify the Informatica Docker Image. . . . 8
Run the Informatica Docker Image to Create a Domain. . . . 8
Step 1. Choose the Deployment Type. . . . 9
Step 2. Provide Docker Information. . . . 9
Step 3. Provide the Domain Connection Information 10
Step 4. Configure the Domain Configuration Repository. . . . 10
Step 5. Configure the Model Repository Service. . . . 11
Step 6. Configure the Data Integration Service. . . . 12
Step 7. Configure the Content Management Service. . . . 13
Step 8. Configure the Profiling Warehouse Connection Database. . . . 14
Step 9. Configure the Informatica Cluster Service. . . . 14
Step 10. Configure the Catalog Service. . . . 17
Step 11. Configure the MetaDex Repository Connection. . . . 17
Run the Informatica Docker Image to Join a Domain. . . . 18
Step 1. Choose the Deployment Type. . . . 18
Step 2. Provide Docker Information. . . . 19
Step 3. Provide the Domain Connection Information 19
Step 4. Configure the Domain. . . . 20
Quick Deployment. . . . 20

Step 1. Choose the Deployment Type. 20
Step 2. Provide Configuration Options. 21
Build or Run the Docker Image in Silent Mode. 22
Running the Silent Installer. 22
Complete the Post-Install Tasks. 22
Complete the Domain Configuration. 22
Complete the Domain Integration. 23
Start and Stop the Informatica Services. 23
Troubleshooting 23
Appendix A: Sample Silent Properties for Build Image. 25
Appendix B: Sample Silent Properties for Run Image. 25

Overview

Use the web-based interface in Informatica Deployment Manager to quickly create standard Docker images and a container using Docker.

Docker is an open source platform that provides an isolated environment called containers to run the applications. Docker allows independent containers to run within a single Linux instance. A Docker image is an executable package that can run an application, a code, run-time files, environment variables, or configuration files. A container is a run-time instance of an image.

You can use Informatica Deployment Manager to build or run the Docker image. You can build the Docker image with the default base or custom operating system and Informatica product binaries. With Informatica Deployment Manager, you can create containers using this Docker image to configure the Informatica domain.

When you run the Docker image, you can install Informatica products and you can create or join a domain.

With Informatica Deployment Manager, you can build or run the Docker image with the silent installer. If you want to run the silent installer, you can choose to generate the silent input properties when you go through the wizard steps, and then copy the properties directly to the silent install properties file.

Installing and running Enterprise Data Catalog on Docker is not supported in production environments or any environment that you plan to push to production. Also, Data Asset Analytics is not supported by Informatica Deployment Manager.

Informatica Deployment Manager Process Checklist

Perform the following tasks associated with the installation:

- ❑ Plan for all installation components within the domain, such as nodes and services. For more information, see the *Installation for Enterprise Data Catalog* guide for the Enterprise Data Catalog version to install.
- ❑ Complete prerequisites:
  - Verify system requirements.
  - Configure Docker engine.
  - Set up keystore and truststore files.
  - Extract Informatica Deployment Manager and access the Informatica installer .tar file.
  - Verify the license key.

- Set up the databases.
- Prepare for the cluster configuration.
- Automate the generation of the silent input property file.

❑ Build the Informatica Docker image with base operating system and Informatica binaries.

❑ Run the Docker image to configure the Informatica domain.

❑ Deploy the Docker image quickly or download and run the default image.

❑ Build or run the Docker image in silent mode.

❑ Complete the post-requisites:

- Complete the domain configuration.
- Create the application services.
- Install the Developer tool.

Before You Begin

Before you install Enterprise Data Catalog, verify that the machine meets the pre-installation requirements for the Informatica product installation.

Verify System Requirements

Verify that your environment meets the following minimum system requirements for the installation process:

- Disk space of 75 GB in the Docker root directory.
- Disk space of 40 GB in the Docker image working directory.
- If you want to use a single directory as both root directory and working directory for Docker, ensure that you allocate a disk space of 100 GB in the directory.
- Register and subscribe the machine where you build the docker images.
- Temporary disk space and permissions.
- Patch requirements.
- Sizing requirements.

Note: For more information about the temporary disk space, permission, patch, and sizing requirements, see the *Installation for Enterprise Data Catalog* guide for the Enterprise Data Catalog version to install.

Set Up the Keystore and Truststore Files

When you install the Informatica services, you can configure secure communication for the domain and set up a secure connection to Informatica Administrator (the Administrator tool). If you configure the security options, you must set up the keystore and truststore files. For more information, see the *Installation for Enterprise Data Catalog* guide for the Enterprise Data Catalog version to install.

If you plan to enable Kerberos or SSL authentication for the cluster, the keystore and truststore files must be located in the machine that hosts the Informatica domain.

If you plan to enable SSL authentication for the existing cluster, merge all the cluster certificates in a JKS file.

Contact Informatica Global Customer Support

When you initially contact Informatica Global Customer Support for Informatica installation access, the Informatica Global Customer Support team initiates a shipping request. The shipping team sends the Informatica installation link and license information to you.

You can contact Informatica Global Customer Support online for access to the following files:

- Informatica installer .tar file
- License key
- Informatica client installation

Access to the .tar File

You require access to both the Informatica Deployment Manager and the Informatica installer.tar file to install the product.

Download and extract the Informatica Deployment Manager installer files from Informatica Marketplace.

After you extract the informatica_1052_deployment_manager.zip file, contact the support team to access the Informatica installer .tar file. You can then place the Informatica installer tar file on the machine where you build the image.

Note: The name of the folder that contains the Informatica Deployment Manager installer files must not contain any space.

To gather inputs for the silent input properties files, launch Informatica Deployment Manager and click **Generate silent properties**. You can then change the format of the properties file to UNIX before you run the silent installation.

Verify the License Key

Before you install an Informatica product using Informatica Deployment Manager, ensure that you have the license key for the product.

The Informatica product is provided as a Bring Your Own License (BYOL). Copy the license key file to a directory accessible to the user account that installs the product. You can use an existing Informatica license or contact Informatica Global Customer Support if you do not have a license key or if you have an incremental license key.

Note: You do not need a license for Informatica Deployment Manager.

Access the Informatica Client Installation

Ensure that the Informatica Global Customer Support team has provided you with access to the Informatica client installation.

Before you install the Informatica clients, verify that the machine meets the minimum system and third-party software requirements. If the machine where you install the Informatica clients is not configured correctly, the installation can fail.

Set Up Databases

Before you install Enterprise Data Catalog, you must set up some databases for the repositories and application services associated with Enterprise Data Catalog. The databases store data, metadata, and run-time results of the repositories and application services.

When you set up a database, you must ensure that the required disk space is available on the database and create the database with parameters required by Enterprise Data Catalog. You must also create user accounts for the databases and install the database clients.

Note: For more information about the disk space, parameters, user accounts, and clients for the databases, see the guide for the Enterprise Data Catalog version that you want to install.

To install Enterprise Data Catalog with all its supported application services, you must set up the following databases:

Domain configuration repository database

The domain stores configuration and user information in the domain configuration repository. You can create the domain configuration repository on an Oracle, PostgreSQL, or Microsoft SQL Server database.

You can either create an on-premises database or use a managed database for each repository and application service. When you run the Docker image, you must provide information about the databases.

Generate Content for Silent Input Properties File

When you create or build the Docker image using Informatica Deployment Manager, you can generate the property values to run the silent installer. Before you can run the silent installer, click **Generate silent properties** in Informatica Deployment Manager. Use the generated values to replace the contents of the silent input properties file. You must convert the properties file to the UNIX format before you run the silent installer.

In Informatica Deployment Manager, you can use the option to generate the silent properties to copy all the user input values entered to build or run the Docker image from a single panel. The generated contents are in the supported format of the silent install property files. Manually save the generated contents into the silent input properties file located in the silent installation directory. Convert the properties file to the UNIX format before you run the silent installation.

Build the Informatica Docker Image

Build a Docker image for Informatica products. After you build the Docker image, Informatica Deployment Manager uses the Docker image to run the containers. Ensure that the Informatica Docker image is stored in the local host or Docker registry before you install Informatica products in Docker with Informatica Deployment Manager.

Step 1. Choose the Deployment Type

On the **Deployment type** page, select the Enterprise Data Catalog version to deploy. You can deploy Enterprise Data Catalog on a single data node or on a multi-node cluster. Additionally, you can choose to configure secure authentication to build the Docker image on a remote host.

1. Launch Informatica Deployment Manager. You can use the Secure Sockets Layer (SSL) protocol to launch Informatica Deployment Manager in a secure way. If you choose to use SSL, you can use a custom SSL certificate or the default Informatica SSL certificate.
   - To launch without SSL, run `sh startup.sh nonssl .`
   - To launch with the default SSL certificate, run `sh startup.sh .`
   - To launch with a custom SSL certificate, run `sh startup.sh SSL <certificate location> <certificate password>` . The password must be in single quotes.

   Note: By default, Informatica Deployment Manager uses four ports that are available within the port range of 12100 to 12200. To specify a different port range, add the first port number of the required port range at the end of the startup command as shown in the following example: `sh startup.sh SSL <certificate location> <certificate password> <port number>`
2. To build the Informatica Docker image, select **Build image**.

   The **Deployment type** page appears.
3. On the **Deployment type** page, select **Enterprise Data Catalog** for the product.

The build image uses Docker as the default deployment type.

4. Choose **Single node** if you want to deploy Enterprise Data Catalog on a single data node. Choose **Multi node** if you want to deploy Enterprise Data Catalog on a multi-node cluster.
5. Select the Enterprise Data Catalog version to deploy.
6. Optionally, choose to configure Secure Shell (SSH) protocol for secure authentication to build the image on a remote host. If you do not want to set the secure authentication, go to step 9.
7. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
8. If you want to update an existing image by applying or rolling back Emergency Bug Fixes (EBF), select the **Update existing Informatica image** check box.

   Note: This step is applicable only for Informatica Deployment Manager v10.5.3.
9. Click **Next**.

   The **Configure Docker image** page appears.

Step 2. Configure the Docker Image

On the **Configure Docker image** page, specify details of the Docker image. The fields on the **Configure Docker image** page vary depending on whether or not you selected the **Update existing Informatica image** check box on the **Deployment type** page.

1. If you did not select the **Update existing Informatica image** check box on the **Deployment type** page, perform the following steps:
   a. Specify the base operating system to build the Docker image. If you want to build the Docker image on a custom operating system, select `Custom`, and then enter the name of the operating system.
   b. Enter the path to the Informatica installer .tar file.

      The .tar file must be present on the machine where you want to build the image. The Informatica Deployment Manager uses the tar utility to extract the installer server files to a directory on the machine.
   c. Enter the name of the Docker image.

      Default Docker image name is `informatica<product_version>:1.0`, where `1.0` is the tag name.
   d. Enter the machine working directory to build the Docker image.

      Default is `/root`.
   e. Specify the location where the scanner binaries and resource drivers for Enterprise Data Catalog are stored.
   f. Specify whether you want to install packages to integrate the Informatica domain with Hadoop or Databricks.

      Note: This step is applicable only for Informatica Deployment Manager v10.5.3.
   g. If you choose to install packages to integrate the Informatica domain with Hadoop or Databricks, select one or more integration packages.

      Note: The integration packages must be available in the directory that contains the Informatica installer file.

2. If you chose to update an existing Docker image, perform the following steps:
    a. Specify the base operating system to build the Docker image. If you want to build the Docker image on a custom operating system, select `Custom`, and then enter the name of the operating system.
    b. Enter the name of the Docker image that you want to update.
    c. Enter the name that you want to assign to the updated Docker image.

       The image name must be in the following format: `<image_name>:<tag_name>`
    d. Enter the machine working directory to build the Docker image.

       Default is `/root`.
    e. Specify whether you want to apply or roll back an EBF from the existing Docker image.

       Note: You can apply or roll back multiple EBFs together.
    f. If you choose to apply an EBF, perform the following steps:
        1. Enter the path to the folder that contains the .tar files of all the EBFs that you want to apply.
        2. If you want to apply multiple EBFs in a particular order, enter the EBF IDs in the order in which they must be applied. Ensure that you enter the EBF IDs as comma-separated values.
        3. Optionally, choose to delete the backup content for the EBFs. If you delete the backup content for an EBF, users cannot roll back the EBF after you apply it.
        4. If you choose to delete the backup content, enter the ID of the EBF for which you want to disable rollback support. To specify multiple EBF IDs, enter the IDs as comma-separated values.
    g. If you choose to roll back an EBF, perform the following steps:
        1. Enter the path to the folder that contains the .tar files of all the EBFs that you want to roll back.
        2. If you want to roll back multiple EBFs in a particular order, enter the EBF IDs in the order in which they must be rolled back. Ensure that you enter the EBF IDs as comma-separated values.

Step . Verify the Informatica Docker Image

You can verify that the Informatica image is present in the host that you specified when you built the Docker image.

To verify that the Informatica Docker image exists, enter the docker images command from the command prompt. Ensure that the values for the tag, image ID, created date, and size information appears for the Informatica Docker image.

The following sample displays the result of the docker image command:

```
{root@master abc]#docker images
REPOSITORY                    TAG         IMAGE ID       CREATED       SIZE
informatica1052               1.0         f9923fb2cfa0   20 hours ago  17.7 GB
```

Run the Informatica Docker Image to Create a Domain

You can install Informatica products by running the Docker image.

Run the Docker image to create nodes in the Informatica domain. The first time that you run the Docker image, choose to create a domain. When you create a domain, the node that you create becomes a gateway node in the domain. The gateway node contains a Service Manager that manages all the domain operations.

Step 1. Choose the Deployment Type

On the **Deployment type** page, select the Enterprise Data Catalog version to deploy. Additionally, you can choose to configure secure authentication to run the Docker image and deploy the product on a remote host.

1. Launch Informatica Deployment Manager. You can use the Secure Sockets Layer (SSL) protocol to launch Informatica Deployment Manager in a secure way. If you choose to use SSL, you can use a custom SSL certificate or the default Informatica SSL certificate.
   - To launch without SSL, run `sh startup.sh nonssl .`
   - To launch with the default SSL certificate, run `sh startup.sh .`
   - To launch with a custom SSL certificate, run `sh startup.sh SSL <certificate location> <certificate password>` . The password must be in single quotes.

   Note: By default, Informatica Deployment Manager uses four ports that are available within the port range of 12100 to 12200. To specify a different port range, add the first port number of the required port range at the end of the startup command as shown in the following example: `sh startup.sh SSL <certificate location> <certificate password> <port number>`

   Note: You must clean the volume and working directories before you launch Informatica Deployment Manager.
2. To run the Informatica Docker image, select **Run image**.

   The **Deployment type** page appears.
3. On the **Deployment type** page, select **Enterprise Data Catalog** for the product.
4. Choose **Single node** if you want to deploy Enterprise Data Catalog on a single data node. Choose **Multi node** if you want to deploy Enterprise Data Catalog on a multi-node cluster.
5. Select the Enterprise Data Catalog version to deploy.
6. Optionally, choose to configure Secure Shell (SSH) protocol for secure authentication to deploy the containers on a remote host. If you do not want to set the secure authentication, go to step 8.
7. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
8. Click **Next**.

   The **Docker information** page appears.

Step 2. Provide Docker Information

In the **Docker configuration** section of the **Docker information** page, provide the required information to connect to the Docker image and container.

1. Enter the names of the Docker image and container.

   Default Docker image name is `informatica<product_version>:1.0`, where `1.0` is the tag name.
2. Select the Informatica license key file.
3. Enter the tmps volume directory and working directory.

   The tmpfs volume is the common directory between the container and the host. Ensure that you have read, write, and execute permissions on the tmps volume directory.
4. Enter the network name. Default network name is infa.

Step 3. Provide the Domain Connection Information

In the **Domain selection** section of the **Docker information** page, provide information to create a domain, connection details for Informatica Administrator, and whether to secure communication to the domain or not.

1. In the **Domain selection** section, choose to create a domain.
2. Optionally, choose to enable secure communication for services in the Informatica domain.

   By default, if you enable secure communication for the domain, the installer sets up an HTTPS connection. You can also create a domain configuration repository on a secure database.
3. Specify the connection details for Informatica Administrator.
   a. If you disabled secure communication for the domain, you can specify whether to set up a secure HTTPS connection for Informatica Administrator.
   b. If you enabled secure connection for the domain or if you enabled HTTPS connection, enter the HTTPS port number and the keystore file information. Choose to use a default keystore or a custom keystore file.
      - If you use the default keystore, the installer creates a self-signed keystore file named Default.keystore in the following location:
        `<Informatica installation directory>/tomcat/conf/`
      - If you use a custom keystore, select the keystore file and specify its password.
4. If you enabled secure connection for the domain, specify whether to use the default Informatica SSL certificates or to use your SSL certificates to secure domain communication.
5. If you choose to provide the SSL certificates, select the keystore and truststore files and specify their passwords. The keystore file is named infa_keystore.jks and the truststore file is named infa_truststore.jks.
6. Click **Next**.

   The **Domain database** page appears.

Step 4. Configure the Domain Configuration Repository

On the **Domain database** page, provide the domain configuration repository database information, JDBC connection information, and specify information for the domain and gateway node.

1. Select the database to use for the domain configuration repository.
2. Optionally, specify if you created a database in the container. If you created a database in the container, enter the name of the database.
3. Enter the database user account ID and password.
4. Specify the database parameters.
   a. If you selected **Microsoft SQL Server** or **PostgreSQL**, specify if you want to provide the schema name for the database. If you choose to specify the schema name, enter the schema name for the database. If you selected **Oracle**, the installer creates the tables in the default schema.
   b. To enter the JDBC connection information, you can use either the JDBC URL or the JDBC connection string.

      To use the JDBC URL information, select **JDBC URL**, and specify the following JDBC URL properties:

      - **Database address.** Host name and port number for the database.
      - **Database service name.** Oracle service name, the database name for Microsoft SQL Server, or the database name for PostgreSQL.

      Optionally, choose to include additional JDBC parameters.

c. To use a custom JDBC connection string, select **JDBC connection string**.

You can use the following syntax in the JDBC connection string to connect to a secure database:
Oracle

```
jdbc:Informatica:oracle://<host name>:<port number>;ServiceName=<service
name>;EncryptionMethod=SSL;HostNameInCertificate=<database host
name>;ValidateServerCertificate=<true or false>
```

Microsoft SQL Server

```
jdbc:Informatica:sqlserver://<host name>:<port
number>;SelectMethod=cursor;DatabaseName=<database
name>;EncryptionMethod=SSL;HostNameInCertificate=<database host
name>;ValidateServerCertificate=<true or false>
```

PostgreSQL

```
jdbc:Informatica:postgresql://<host name>:<port number>;DatabaseName=<database
name>;EncryptionMethod=SSL;HostNameInCertificate=<database host
name>;ValidateServerCertificate=<true or false>
```

5. In the **Domain and node configuration** section, enter the directory that contains the encryption key for the Informatica domain. By default, the encryption key is created in the following directory: `<Informatica installation directory>/isp/config/keys`.
6. Specify the name of the domain and node along with the port number, user name, and password for the domain. When you enter the information for the domain and the gateway node that you want to create, consider the following guidelines:
   - The default domain name is Domain. The domain name must not exceed 128 characters and must be 7-bit ASCII only. The name cannot contain a space or any of the following characters:
     ` % * + ; " ? , < > \ /
   - The default port number for the node is 6005.
   - Informatica Deployment Manager exposes the ports from the range <domain port> - <domain port > + 110 ports from the container to the Docker host, where the initial port number is the domain port number. Enter the service ports within the supported service port range.
   - The password for the domain administrator must be more than 2 characters and must not exceed 128 characters.

Step 5. Configure the Model Repository Service

The Model Repository Service manages the Model repository. The service receives requests from Informatica clients and application services to store or access metadata in the Model repository. On the **Model Repository Service** page, you can configure the database for the Model repository.

1. In the **Model Repository Service information** section, enter a name for the Model Repository Service.

   Default value is mrs. If you want to specify a different name for the service, consider the following guidelines:
   - The name of the service must be unique within the domain. It must not exceed 128 characters or begin with the special character `@`. It must also not contain spaces or the following special characters:
     ` ~ % ^ * + = { } \ ; : ' " / ? . , < > | ! ( )] [
   - You cannot change the name of the service after it is created.
2. Select the database to use for the Model repository and specify the user ID and password for the database.

3. Specify the database parameters.
   a. If you selected **Microsoft SQL Server** or **PostgreSQL**, enter the schema name for the database. If you selected **Oracle**, the installer creates the tables in the default schema.
   b. To enter the JDBC connection information, you can use either the JDBC URL or the JDBC connection string.

      To use the JDBC URL information, select **JDBC URL**. To enter the connection information using the JDBC URL information, specify the following JDBC URL properties:

      - **Database address.** Host name and port number for the database.
      - **Database service name.** Oracle service name, the database name for Microsoft SQL Server, or the database name for PostgreSQL.

      Optionally, choose to include additional JDBC parameters.

      Note: When specify the JDBC URL properties, a custom string specific to the database is automatically created and added to the silent properties file.
   c. To use a custom JDBC connection string, select **JDBC connection string**.

      You can use the following syntax in the JDBC connection string to connect to a secure database:
      Oracle

      ```
      jdbc:informatica:oracle://<host name>:<port number>;ServiceName=<service name>
      ```

      Microsoft SQL Server

      ```
      jdbc:informatica:sqlserver://<host name>:<port
      number>;SelectMethod=cursor;DatabaseName=<database name>
      ```

      PostgreSQL

      ```
      jdbc:informatica:postgresql://<host name>:<port number>;DatabaseName=<database name>
      ```
4. If the database that you want to use for the Model repository is a secure database, select the **Is the database secure** check box.

   If you select the **Is the database secure** check box, you must select the database truststore file and enter the password for the truststore file. Additionally, enter the secure JDBC parameters for the database. Default value for the secure JDBC parameters is:

   ```
   EncryptionMethod=SSL;HostNameInCertificate=;ValidateServerCertificate=false;
   ```
5. Click **Next** to configure additional services, or run the Docker image.

Step 6. Configure the Data Integration Service

The Data Integration Service receives requests from Informatica client tools to run integration, profile, and data preparation jobs. The service writes results to different databases and writes run-time metadata to the Model repository. On the **Data Integration Service** page, you can configure the parameters for the Data Integration Service.

1. In the **Data Integration Service information** section, enter a name for the Data Integration Service.

   Default value is dis. If you want to specify a different name for the service, consider the following guidelines:

   - The name of the service must be unique within the domain. It must not exceed 128 characters or begin with the special character `@`. It must also not contain spaces or the following special characters:
     ```
     ` ~ % ^ * + = { } \ ; : ' " / ? . , < > | ! ( ) ] [
     ```
   - You cannot change the name of the service after it is created.
2. Specify the communication protocol for the Data Integration Service. Default value is http.
3. Based on the protocol that you select, enter the port number to use for the service.

4. Specify whether to use the default Informatica SSL certificates or to use your SSL certificates to secure the communication for the service.

   Note: The option to choose the SSL certificates is available only if you selected **https** or **http & https** as the communication protocol.

5. If you choose to provide the SSL certificates, select the keystore and truststore files that contain the SSL certificates and specify the passwords for the files.
6. Click **Next** to configure additional services, or run the Docker image.

Step 7. Configure the Content Management Service

The Content Management Service manages reference data for data domains that use reference tables. The service uses the Data Integration Service to run mappings to transfer data between reference tables and external data sources. On the **Content Management Service** page, you can configure the parameters for the Data Integration Service. Additionally, you can configure the database for the reference data warehouse.

1. In the **Content Management Service parameters and database** section, enter a name for the Content Management Service.

   Default value is cms. If you want to specify a different name for the service, consider the following guidelines:

   - The name of the service must be unique within the domain. It must not exceed 128 characters or begin with the special character `@`. It must also not contain spaces or the following special characters:
     `` ` ~ % ^ * + = { } \ ; : ' " / ? . , < > | ! ( ) ] [ ``
   - You cannot change the name of the service after it is created.
2. Specify the communication protocol for the service. Default value is http.
3. Based on the protocol that you select, enter the port number to use for the service.
4. Specify whether to use the default Informatica SSL certificates or to use your SSL certificates to secure the communication for the service.

   Note: The option to choose the SSL certificates is available only if you selected **https** as the communication protocol.

5. If you choose to provide the SSL certificates, select the keystore file that contains the SSL certificates and specify the password for the keystore file.
6. Select the database to use for the reference data warehouse and specify the user ID and password for the database.
7. Specify the database parameters.
   a. If you selected **Microsoft SQL Server** or **PostgreSQL**, enter the schema name for the database. If you selected **Oracle**, the installer creates the tables in the default schema.
   b. To enter the JDBC connection information, you can use either the JDBC URL or the JDBC connection string.

      To use the JDBC URL information, select **JDBC URL**. To enter the connection information using the JDBC URL information, specify the following JDBC URL properties:

      - **Database address.** Host name and port number for the database.
      - **Database service name.** Oracle service name or the database name for Microsoft SQL Server.

      Optionally, enter additional JDBC parameters.

   c. To use a custom JDBC connection string, select **JDBC connection string**.

You can use the following syntax in the JDBC connection string to connect to a secure database:
Oracle

```
jdbc:informatica:oracle://<host name>:<port number>;ServiceName=<service name>
```

Microsoft SQL Server

```
jdbc:informatica:sqlserver://<host name>:<port
number>;SelectMethod=cursor;DatabaseName=<database name>
```

PostgreSQL

```
jdbc:informatica:postgresql://<host name>:<port number>;DatabaseName=<database
name>;EncryptionMethod=SSL;HostNameInCertificate=<database host
name>;ValidateServerCertificate=<true or false>
```

d. Enter the data access connection string.

8. Click **Next** to configure additional services, or run the Docker image.

Step 8. Configure the Profiling Warehouse Connection Database

The profiling warehouse stores profiling and scorecard results for the Data Integration Service. On the **Profiling Warehouse Connection** page, you can configure the database for the profiling warehouse.

1. In the **Profiling warehouse connection database information** section, select the database to use for the profiling warehouse and specify the user ID and password for the database.
2. Specify the database parameters.
   a. If you selected **Microsoft SQL Server**, enter the schema name for the database. If you selected **Oracle**, the installer creates the tables in the default schema.
   b. To enter the JDBC connection information, you can use either the JDBC URL or the JDBC connection string.

      To use the JDBC URL information, select **JDBC URL**. To enter the connection information using the JDBC URL information, specify the following JDBC URL properties:

      - **Database address.** Host name and port number for the database.
      - **Database service name.** Oracle service name or the database name for Microsoft SQL Server.

      Optionally, enter additional JDBC parameters.
   c. To use a custom JDBC connection string, select **JDBC connection string**.

      You can use the following syntax in the JDBC connection string to connect to a secure database:
      Oracle

      ```
      jdbc:informatica:oracle://<host name>:<port number>;ServiceName=<service name>
      ```

      Microsoft SQL Server

      ```
      jdbc:informatica:sqlserver://<host name>:<port
      number>;SelectMethod=cursor;DatabaseName=<database name>
      ```

   d. Enter the data access connection string.
3. Click **Next** to configure additional services, or run the Docker image.

Step 9. Configure the Informatica Cluster Service

The Informatica Cluster Service is an application service that runs and manages the nodes and services associated with Enterprise Data Catalog. On the **Informatica Cluster Service** page, you can configure the parameters for the

Informatica Cluster Service. You can also configure the ports and directories for all the associated services such as Nomad, ZooKeeper, Apache Solr, MongoDB, and PostgreSQL.

1. In the **Informatica Cluster Service Properties** section, enter the user name for the gateway host. Default is nroot.
2. Enter a name for the Informatica Cluster Service.

   Default value is Informatica_Cluster_Service. If you want to specify a different name for the service, consider the following guidelines:

   - The name of the service must be unique within the domain. It must not exceed 128 characters or begin with the special character `@`. It must also not contain spaces or the following special characters:
     ` ~ % ^ * + = { } \ ; : ' " / ? . , < > | ! ( )] [
   - You cannot change the name of the service after it is created.
3. Enter the fully qualified domain name of the node that you want to configure as the gateway host.

   Note: The node that you configure as the gateway host must be a data node or a processing node. The container name is the host name for the gateway node. For a multi-node cluster setup, only three nodes are supported. The host names for the data node and processing node are assigned as edc01.informatica.com and edc02.informatica.com. You cannot create multiple multi-node deployments in a single container.
4. Enter a unique HTTP port number to use for the service. If you enabled secure communication for the domain, enter a unique HTTPS port number.

   Note: The port number must not be the same as the domain port number.
5. Optional. If you want to configure custom SSL certificates to secure the Informatica Cluster Service, see the Configure Custom SSL Certificates section of the *Enterprise Data Catalog Installation Guide*.
6. If you enabled secure communication for the domain, you can choose to use the default keystore generated by the installer to enable secure communication for the service or specify the location, alias, and password of a custom keystore file.
7. Specify the directory for the service.
8. In the **Nomad Service Properties** section, configure the following properties:

Property	Description
Nomad Serf Port	The Serf port configured as the gossip protocol for the Nomad servers.
Nomad RPC Port	The Remote Procedure Call (RPC) port configured for communication.
Nomad HTTP Port	The HTTP port number configured for the Nomad server.
Nomad Server Working Directory	The directory that includes sub directories with tasks running on the Nomad server. Default is `/opt/informatica/ics/nomad/server`.
Nomad Client Working Directory	The directory configured for tasks in the Nomad client. Default is `/opt/informatica/ics/nomad/client`.

Note: The port number must not be the same as the domain port number.

9. In the **ZooKeeper Service Properties** section, configure the following properties:

Property	Description
Zookeeper Port	Port number configured for the Apache ZooKeeper Server.
Zookeeper Peer Port	Port number configured for Apache ZooKeeper peer communication.
Zookeeper Leader Port	Port number configured for the ZooKeeper Sever identified as the Leader.
Zookeeper Installation Directory	Specify the path to the directory where you want to install Apache ZooKeeper. Default is `/opt/informatica/ics/zk/install`.
Zookeeper Data Directory	Specify the path to the directory where you want to store data from Apache ZooKeeper. Default is `/opt/informatica/ics/zk/data`.

Note: The port number must not be the same as the domain port number.

10. In the **Apache Solr Service Properties** section, configure the following properties:

Property	Description
Solr Port	Port number configured for Apache Solr Server. **Note:** The port number must not be the same as the domain port number.
Solr Installation Directory	Specify the path to the directory where you want to install Apache Solr Server. Default is `/opt/informatica/ics/solr/install`.
Solr Data Directory	Specify the path to the directory where you want to store data from Apache Solr. Default is `/opt/informatica/ics/solr/data`.

11. In the **MongoDB Service Properties** section, configure the following properties:

Property	Description
MongoDB Port	Port number configured for MongoDB. **Note:** The port number must not be the same as the domain port number.
MongoDB Log Directory	Specify the path to the directory where you want to store the log files. Default is `/opt/informatica/ics/mongo/log`.
MongoDB Data Directory	Specify the path to the directory where you want to store data from the MongoDB database. Default is `/opt/informatica/ics/mongo/data .`

12. In the **PostgreSQL Service Properties** section, configure the following properties:

Property	Description
PostgreSQL Port	Port number configured for PostgreSQL. **Note:** The port number must not be the same as the domain port number.
PostgreSQL Installation Directory	Specify the path to the directory where you want to install the PostgreSQL database. Default is `/opt/informatica/ics/postgres/install`.
PostgreSQL Log Directory	Specify the path to the directory where you want to store the log files from the PostgreSQL database. Default is `/opt/informatica/ics/postgres/log`.
PostgreSQL Data Directory	Specify the path to the directory where you want to store PostgreSQL data. Default is `/opt/informatica/ics/postgres/data`.

Note: If you built the Docker image on CentOS 8, you must run the yum install libncurses* command to install the additional packages required for PostgreSQL.

13. Click **Next** to configure the Catalog Service.

Step 10. Configure the Catalog Service

The Catalog Service runs the Enterprise Data Catalog application and manage the connections between the Enterprise Data Catalog components. On the **Catalog Service** page, you can configure the parameters for the Catalog Service.

1. In the **Catalog Service** section, enter a name for the Catalog Service.
2. Enter a unique HTTP port number to use for the service. If you enabled secure communication for the domain, enter a unique HTTPS port number.

   Note: The port number must not be the same as the domain port number.
3. If you enabled secure communication for the domain, you can choose to use the default keystore generated by the installer to enable secure communication for the service or specify the location, alias, and password of a custom keystore file. You must also specify the domain keystore alias.
4. Click **Next** to configure additional services, or run the Docker image.

Step 11. Configure the MetaDex Repository Connection

On the **Advanced Scanners Repository Connection** page, you can configure the database for MetaDex.

1. In the **Advanced Scanner Repository Configuration** section, select the database that you want to configure as the repository for MetaDex.

   You can select from the following options:

   1. Oracle
   2. Microsoft SQL Server
2. Enter the user name configured to access the database.
3. Enter the password configured for the user name.
4. If you selected Oracle as the database, specify the schema that you want to use.
5. Specify the JDBC connection string to connect to the database.

The JDBC connection string field is pre-populated with the following value for the Oracle database: `jdbc:informatica:oracle://host_name:port_no;ServiceName=`.
The JDBC connection string field is pre-populated with the following value for the Microsoft SQL Server database: `jdbc:informatica:sqlserver://host_name:port_no;SelectMethod=cursor;DatabaseName=`.

6. Enter a unique port number to use for the MetaDex repository server.
7. Specify if TLS is enabled for communication with the repository.

   Specify the following properties if the repository is TLS enabled:

   - Select the database truststore file.
   - Enter the truststore password
   - Specify the secure database parameters as shown in the following sample: `EncryptionMethod=SSL;HostNameInCertificate=ORATLS .informatica.com;ValidateServerCertificate=true;CryptoProtocolVersion=TLSv1.2;`

     The Secure JDBC parameters field is pre-populated with the following value: `EncryptionMethod=SSL;HostNameInCertificate=;ValidateServerCertificate=`

     Note: If you want to use secure parameters that are not listed by default, add them using the separator (;). If you include the secure JDBC parameters directly in the connection string, do not enter any parameter in the Secure JDBC Parameters field.
8. Specify if you want to use the default SSL certificates or custom SSL certificates to secure the repository.

   Specify the following properties if you want to use custom SSL certificates:

   - Keystore file. Specify the keystore file that contains the required keys and certificates.
   - Keystore password. Password to access the keystore file.
   - Keystore type. Specify the type of keystore.
   - Keystore alias. Unique alias to access the keystore entry.

Run the Informatica Docker Image to Join a Domain

After you create the domain, you can use Informatica Deployment Manager on any machine to join the domain. When you join the domain, you need to create a node on the machine and then add the node to the domain.

Step 1. Choose the Deployment Type

On the **Deployment type** page, you must select the Informatica product and version to deploy. Additionally, you can choose to configure secure authentication to run the Docker image and deploy the product on a remote host.

1. Launch Informatica Deployment Manager. You can use the Secure Sockets Layer (SSL) protocol to launch Informatica Deployment Manager in a secure way. If you choose to use SSL, you can use a custom SSL certificate or the default Informatica SSL certificate.

   - To launch without SSL, run `sh startup.sh nonssl .`
   - To launch with the default SSL certificate, run `sh startup.sh .`
   - To launch with a custom SSL certificate, run `sh startup.sh SSL <certificate location> <certificate password> .` The password must be in single quotes.

   Note: By default, Informatica Deployment Manager uses four ports that are available within the port range of 12100 to 12200. To specify a different port range, add the first port number of the required port range at the end of the startup command as shown in the following example: `sh startup.sh SSL <certificate location> <certificate password> <port number>`
2. To run the Informatica Docker image, select **Run image**.

The **Deployment type** page appears.

3. On the **Deployment type** page, select **Enterprise Data Catalog** for the product.
4. Choose the version of the product to deploy.
5. Optionally, you can choose to configure Secure Shell (SSH) protocol for secure authentication to deploy the containers on a remote host. If you do not want to set the secure authentication, go to step 7.
6. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
7. Click **Next**.

   The **Docker information** page appears.

Step 2. Provide Docker Information

In the **Docker configuration** section of the **Docker information** page, provide the required information to connect to the Docker image and container.

1. Enter the names of the Docker image and container.

   Default Docker image name is `informatica<product_version>:1.0`, where `1.0` is the tag name.
2. Select the Informatica license key file.
3. Enter the paths of the tmps volume directory and working directory.

   The tmpfs volume is the common directory between the container and the host. Ensure that you have read, write, and execute permissions on the tmps volume directory.
4. Enter the network name. Default network name is infa.

Step 3. Provide the Domain Connection Information

In the **Domain selection** section of the **Docker information** page, provide information to join a domain, connection details for Informatica Administrator, and whether to secure communication to the domain or not.

1. In the **Domain selection** section, choose to join a domain.

   The installer creates a node on the container where you install. You can specify the type of node to create and the domain to join.
2. Optionally, choose to join a domain with secure connection. You can also choose if you want the node you create to be a gateway node for the domain. Default is worker node.
3. Specify the connection details for Informatica Administrator.
   a. If you did not choose join a secure domain, you can specify whether to set up a secure HTTPS connection for Informatica Administrator.
   b. If you chose to join a secure domain or if you enabled HTTPS connection, enter the HTTPS port number and the keystore file information. Choose to use a default keystore or a custom keystore file.
      - If you use the default keystore, the installer creates a self-signed keystore file named Default.keystore in the following location: `<Informatica installation directory>/tomcat/conf/`

- If you use a custom keystore, specify the location and password of the keystore file.

4. Specify whether to use the default Informatica SSL certificates or to use your SSL certificates to secure domain communication.
5. If you choose to provide the SSL certificates, select the keystore and truststore files and specify their passwords. The keystore file is named infa_keystore.jks and the truststore file is named infa_truststore.jks.
6. Click **Next**.

   The **Domain configuration** page appears.

Step 4. Configure the Domain

On the **Domain configuration** page, provide the domain, node, gateway node, and gateway container information.

1. In the **Existing domain configuration** section, specify the domain name, gateway container name, gateway node port, domain user name and password, security domain name.
2. Optionally, choose to join an Informatica domain created through the container database and enter the name of the database.
3. Specify the key and directory for the encryption key for the Informatica domain.
   - **Select the encryption key.** Specify the custom site key to secure sensitive data in the domain. Before you can enter the site key path, copy the file from the encryption key directory of the master container to the host with the following command:
     `docker cp <container name>: <encryption key directory>/siteKey <dst path in host>`
   - **Encryption key directory.** Directory in which to store the encryption key for the Informatica domain. The encryption key is created in the following directory: `<Informatica installation directory>/isp/config/keys`.
4. In the **New node configuration** section, enter the node name and node port number for the current node.
5. If you used a secure database to create the domain, enter the path and password of the database truststore file.

Quick Deployment

With the quick deployment, you can download and run the Informatica Docker image with a pre-built image. With the one-click deployment of Informatica Deployment Manager, you can configure the Informatica domain for Enterprise Data Catalog.

When you download and run the Docker image, Informatica Deployment Manager uses the PostgreSQL database that is bundled with the Docker image. The Docker Hub is the registry where the Docker images are stored.

Step 1. Choose the Deployment Type

On the **Deployment type** page, you must select the Informatica product and version to deploy. Additionally, you can choose to configure secure authentication to run the Docker image and deploy the product on a remote host.

1. Launch Informatica Deployment Manager. You can use the Secure Sockets Layer (SSL) protocol to launch Informatica Deployment Manager in a secure way. If you choose to use SSL, you can use a custom SSL certificate or the default Informatica SSL certificate.
   - To launch without SSL, run `sh startup.sh nonssl .`
   - To launch with the default SSL certificate, run `sh startup.sh .`
   - To launch with a custom SSL certificate, run `sh startup.sh SSL <certificate location> <certificate password> .` The password must be in single quotes.

Note: By default, Informatica Deployment Manager uses four ports that are available within the port range of 12100 to 12200. To specify a different port range, add the first port number of the required port range at the end of the startup command as shown in the following example: `sh startup.sh SSL <certificate location> <certificate password> <port number>`

2. On the Informatica Deployment Manager home page, select **Quick deployment**.

   The **Deployment type** page appears.

3. On the **Deployment type** page, select **Enterprise Data Catalog** for the product.

   Note: Informatica Deployment Manager does not support Enterprise Data Catalog on multi-node deployments and deployment on SSL-enabled domain in quick deployment mode.

4. Choose the version of the product to deploy.
5. Optionally, choose to configure Secure Shell (SSH) protocol for secure authentication to deploy the containers on a remote host. If you do not want to set the secure authentication, go to step .
6. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
7. Click **Next**.

   The **Configuration options** page appears.

Step 2. Provide Configuration Options

On the **Configuration options** page, provide the required information to connect to the Docker image and container.

1. In the **Quick deployment** section, select the Informatica license key file.
2. Enter the paths of the tmps volume directory and working directory.

   The tmpfs volume is the common directory between the container and the host. Ensure that you have read, write, and execute permissions on the tmps volume directory.

3. Specify the Docker registry from where you can download the Docker image. You can download the Docker image from the local host machine, public registry, private registry, or Informatica hosted registry.

   Note: The Docker image that is available in the Informatica hosted registry is supported only in Docker v17.07 and higher versions.

4. If you choose to download the Docker image from the local host machine or public registry, enter the name of the Docker image.

   The image name must be in the following format: `<image_name>:<tag_name>`

5. If you choose to download the Docker image from a private registry, enter the login credentials for the registry, and then enter the name of the Docker image.

   The image name must be in the following format: `<image_name>:<tag_name>`

6. If you choose to download the Docker image from the Informatica hosted registry, perform the following steps:

   a. In the **User Acceptance** dialog box, review the terms and conditions and click **Accept** to proceed with the Docker image download.

   b. Click **Browse Docker Images** and select the default Docker image available in the Informatica hosted registry.

Build or Run the Docker Image in Silent Mode

You can build or run the Docker image in silent mode after updating the required properties files with the generated silent properties from Informatica Deployment Manager.

To run the installer in silent mode, complete the following tasks:

1. Run Informatica Deployment Manager and choose to generate the silent properties.
2. Configure the silent input properties file and specify the installation options.

   When you generate silent properties from Informatica Deployment Manager, you can copy all the installation options and the values specified in Informatica Deployment Manager. You can then paste the copied contents into the property file for the silent installer.
3. Save the properties file in the UNIX format to the file path that contains the silent installer.
4. Run the silent installer with the silent installation properties file.

If you want to run Informatica Deployment Manager for additional images, you must save each property file before every run of the silent installer.

Running the Silent Installer

Manually copy the generated silent properties when you build or run the Docker image from Informatica Deployment Manager into the supported silent properties file. The customized `SilentInput_BuildImage.properties` or `SilentInput.properties` file has different content based on whether you run the silent installer to build or run the Docker image. After you configure the properties file, open a command prompt to start the silent installation.

1. Run Informatica Deployment Manager and choose to generate the silent properties.
2. Copy the generated silent properties from Informatica Deployment Manager into the supported silent properties file when you build or run the Docker image.
3. From the terminal, go to the root of the directory that contains the installation files. For build image, navigate to the following directory: `<working directory>/appconTemp/<image_name>`. For run image, navigate to the following directory: `<working_directory>/appconTemp/<image_name>`.
4. Verify that the directory contains the customized `SilentInput_BuildImage.properties` or `SilentInput.properties` file based on whether you build or run the docker image.
5. From the terminal, run the `dos2unix` command to convert the silent input properties file to the Unix format.
6. Create a log directory: `mkdir logs`
7. Run sh silentInstall.sh >> logs/<debug configure>.log.

When the silent installation is complete, you can view the log file in the working directory.

Complete the Post-Install Tasks

After you deploy Enterprise Data Catalog, perform the post-installation tasks.

Complete the Domain Configuration

To complete the domain configuration after you install the Informatica services, perform the following tasks:

- Verify locale settings and code page
- Configure Informatica environment variables
- Configure the library path environment variables
- Configure locale environment variables

Note: For more information about how to perform the tasks, see the guide for the Enterprise Data Catalog version to install.

Complete the Domain Integration

Complete the following tasks:

Update the hosts file to access the Administrator tool through the browser.

Enter the following information in the hosts file to access the Administrator tool through the browser:

```
<IP address of the machine> <host name of Informatica domain>.
```

You can find the hosts file in the following location: `/etc/hosts`.

Log in to Informatica Administrator.

You must have a user account to log in to the Informatica Administrator web application with the administrator name that you used in the wizard. You can access the Administrator tool using the following link format: `https://<host name of the machine>:<port number>/administrator`

Create the application services if you did not create them during deployment.

If you did not create the Model Repository Service, Data Integration Service, Catalog Service, and the Informatica Cluster Service when you created the domain, you can use the service creation wizard in Administrator tool to create the application services. You need to create the Informatica Cluster Service if you are deploying Enterprise Data Catalog in an embedded cluster.

Create the following services:

Note: For more information about creating the services, see the guide for the Enterprise Data Catalog version to install.

Start and Stop the Informatica Services

Run infaservice.sh to start and stop the Informatica daemon.

You can start the daemon with the infaservice.sh startup command. To stop the daemon, enter the infaservice.sh shutdown command. By default, infaservice.sh is installed in the following directory:

```
<Informatica installation directory>/tomcat/bin
```

Note: If you use a softlink to specify the location of infaservice.sh, set the INFA_HOME environment variable to the location of the Informatica installation directory.

Troubleshooting

I tried to build the Docker image, but the build image fails.

If build image fails during installer tar file extraction or before the Docker build image starts, verify that adequate disk space of 40 GB is available in the Docker image working directory.

If the build image fails at the step `Copy/Binaries/home/Informatica` in the log file, then there is not enough disk space in the Docker root directory. To find the Docker root directory, run the `docker info` command. Enterprise Data Catalog requires 75 GB disk space in the Docker root directory.

You can also free up some space from the Docker root directory when you delete a dangling image. When you create the new build of the image but do not specify a new name, you create a dangling image and the old image becomes the dangling image. Those old images remain untagged and display "<none>" as the name when you run the `docker images` command.

To delete the dangling images, complete the following steps:

1. To list all dangling images and to get the image ID, run the command: `docker images -f dangling=true`
2. To delete each dangling image, run the command: `docker image rm -f <image id>`

If the build image fails with the following error, you need to manually pull the Docker image:

```
Sending build context to Docker daemon 74.75GB
Step 1/30: FROM registry.access.redhat.com/rhel7:7.7
Trying to pull repository registry.access.redhat.com/rhel7 ...
Installation Status:ERROR
```

To fix the issue, you can manually run the following command:

```
docker pull registry.access.redhat.com/rhel7:7.7
```

If the build image fails with the following error, the Docker build script has failed to access the repository to download dependencies:

```
This system is not registered with an entitlement server.
```

To register and subscribe the machine where you build the Docker image:

1. Run the `yum repolist all` command to see all the repositories.
2. Use the `subscription-manager` to register with the following command: `subscription-manager repos --enable`.
3. To enable custom repositories, run the command: `yum-config-manager --enable`

If the build image displays the `authenticationrequired` error when you run the docker pull command to pull the image from RHEL, the authentication with the Docker authentication might have expired. Run the `docker logout` command and then pull the Docker image. If the issue persists, try to pull the Docker image from registry.redhat.io instead of registry.access.redhat.com. If any issue remains with RHEL, you could try to use Centos7 for proof of concept cases.

I tried to build the Docker image, but the process of building the Docker image runs indefinitely without any result.

Perform the following steps:

- Verify that your environment meets the minimum system requirements for the temporary disk space. For more information, see the guide for the Enterprise Data Catalog version that you want to install.
- Verify that you have read, write, and execute permissions on the `/tmp` directory.
- Verify that the system that hosts Informatica Deployment Manager has uninterrupted access to the internet.

I cannot access Administrator tool from the browser.

Check the IP address from where you access the Administrator tool:

Ensure that you use the host IP of the node on which container is running to access the Administrator tool.

PostgreSQL fails on the CentOS 8 Docker image.

If you built the Docker image on CentOS 8, PostgreSQL fails with the following error: `error while loading shared libraries: libtinfo.so.5: cannot open shared object file: No such file or directory`. To fix this issue, run the yum install libncurses* command to install the additional packages required for PostgreSQL, and then recycle the Informatica Cluster Service.

Appendix A: Sample Silent Properties for Build Image

The following example shows the contents of the file:

```
INSTALL_OPTION=1
IMAGE_NAME=edc1040:1.0
TAR_FILE_LOC=
OS_NAME=centos:centos7
MULTI_NODE=0
IMAGE_NAME_MULTI_NODE=
AMBARI_FILE_LOC=
SCANNER_FILE_LOC=
DPM_TAR_FILE_LOC=
INSTALL_DPM=0
CLUSTER_TYPE=1
INSTALL_EDP=0
DOWNLOAD_AND_RUN=0
productType=
PCRSIS_ONLYIMAGE=0
HubUserName=
HubPassword=
PRIVATE_HUB=1
INFA_REPO=0
FULL_IMAGE=1
```

Appendix B: Sample Silent Properties for Run Image

The following example shows the contents of the file:

```
IMAGE_NAME=edc1040:1.0
INFA_CONTAINER_NAME=edc1040
PORT_RANGE=8000-8300
VOLUME_DIRECTORY=/data/Volume
LICENSE_KEY_LOC=/data/EDC_Resources/abdeic_1020_All_8850.key
SILENT_FILE_LOC=/data/EDC_Resources/SilentInput.properties
DOCKER_NETWORK_NAME=
DPM_LICENSE_KEY_LOC=/data2/EDC_Resources/DataPrivacyManagement.key
INSTALL_DPM=0
productType=PC
MULTI_NODE=0
IMAGE_NAME_MULTI_NODE=
USE_DB_CONTAINER=false
DB_CONTAINER_NAME=
PCRS_DB_TYPE=
PCRS_DBTYPE_AZURE=
PCRS_DB_HOST=
PCRS_DB_PORT=
EXTERNAL_CLUSTER_TRUSTSTORE_FILE_LOC=
EXTERNAL_CLUSTER_TRUSTSTORE_FILE_PASSWD=
INSTALL_EDP=0
DPS_CLUSTER_TRUSTSTORE_FILE_LOC=
DPS_CLUSTER_TRUSTSTORE_FILE_PASSWD=
EDC_KDC_HOST_IP=
DPS_KDC_HOST_IP=
```

Author

Ashwin G