Informatica®
10.5.11

Enterprise Data Preparation Upgrade Guide

Informatica Enterprise Data Preparation Upgrade Guide
10.5.11
August 2026

© Copyright Informatica LLC 2016, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html. Other company and product names may be trade names or trademarks of their respective owners.

This Software may be protected by patents. See https://www.informatica.com/legal/patents.html.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Portions of this software and/or documentation are subject to copyright held by third parties. Required third party notices and AI assistant acknowledgements are included with the product.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Publication Date: 2026-08-18

Table of Contents

Preface 5

Informatica Resources 5

- Informatica Network 5
- Informatica Knowledge Base 5
- Informatica Documentation 5
- Informatica Product Availability Matrices 6
- Informatica Marketplace 6
- Informatica Global Customer Support 6

Chapter 1: Upgrading Enterprise Data Preparation 7

Upgrade Paths 7

Upgrade Process 9

Chapter 2: Before You Upgrade 10

Back Up the Installation 10

Download and Extract the Installer Files 10

- Verify Installer Package Checksum on Linux 11

Verify Distribution Package Requirements (Linux and UNIX) 11

Upgrade the Domain Services 12

Chapter 3: Upgrade Enterprise Data Preparation 13

Upgrade the Enterprise Data Preparation Binaries 13

Upgrade the Application Services 14

Upgrade the Data Preparation Repository 14

Upgrade the Enterprise Data Preparation Service 15

Chapter 4: After You Upgrade Enterprise Data Preparation 16

Copy JDBC JAR Files 16

Chapter 5: Hotfix installation and rollback 17

Hotfix installation and rollback overview 17

Applying the services hotfix 18

- Before you apply the hotfix 18
- Apply the services hotfix in console mode 20
- Apply the services hotfix in silent mode 21
- After you apply the hotfix 24

Rolling back the services hotfix 25

- Before You Roll Back the Hotfix 25
- Roll back the services hotfix in console mode 25
- Roll back the services hotfix in silent mode 26

After You Roll Back the Hotfix. . . . 27
Applying the client hotfix. . . . 28
Apply the client hotfix in graphical mode. . . . 28
Apply the client hotfix in silent mode. . . . 28
Remove the distribution packages from the backup location. . . . 30
Rolling back the client hotfix. . . . 30
Rolling back the client hotfix in graphical mode. . . . 30
Rolling back the client hotfix in silent mode. . . . 31

Appendix A: Managing Distribution Packages. . . . 32

Managing Distribution Packages Overview. . . . 32
Before You Begin. . . . 32
Install or Remove Distribution Packages in Console Mode. . . . 33
Install or Remove Distribution Packages in Silent Mode. . . . 34
After You Install. . . . 34

Preface

Follow the instructions in the *Enterprise Data Preparation Upgrade Guide* to upgrade Enterprise Data Preparation. The guide also includes information on prerequisite tasks and post upgrade tasks that you need to perform to complete the upgrade. Unless otherwise noted, the upgrade path includes hotfixes and service packs.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Network

The Informatica Network is the gateway to many resources, including the Informatica Knowledge Base and Informatica Global Customer Support. To enter the Informatica Network, visit https://network.informatica.com.

As an Informatica Network member, you have the following options:

- Search the Knowledge Base for product resources.
- View product availability information.
- Create and review your support cases.
- Find your local Informatica User Group Network and collaborate with your peers.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Product Availability Matrices

Product Availability Matrices (PAMs) indicate the versions of the operating systems, databases, and types of data sources and targets that a product release supports. You can browse the Informatica PAMs at https://network.informatica.com/community/informatica-network/product-availability-matrices.

Informatica Marketplace

The Informatica Marketplace is a forum where you can find solutions that extend and enhance your Informatica implementations. Leverage any of the hundreds of solutions from Informatica developers and partners on the Marketplace to improve your productivity and speed up time to implementation on your projects. You can find the Informatica Marketplace at https://marketplace.informatica.com.

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:
https://www.informatica.com/services-and-training/customer-success-services/contact-us.html.

To find online support resources on the Informatica Network, visit https://network.informatica.com and select the Support option.

CHAPTER 1

Upgrading Enterprise Data Preparation

You can upgrade Enterprise Data Preparation to Enterprise Data Preparation version 10.5.11.

You can upgrade Enterprise Data Preparation to the current version from Enterprise Data Preparation 10.5 including service packs and hotfixes.

If you are on a version prior to 10.5, you need to upgrade to version 10.5 and then upgrade to 10.5.11.

If you are on version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4 or 10.5.5, you can apply the 10.5.11 hotfix.

You use the Informatica installer to upgrade to the latest version. The installer detects whether the Informatica services, Enterprise Data Catalog, or Enterprise Data Preparation are installed on the node. The installer then upgrades the binaries on the node to the latest binaries.

Upgrade Paths

The upgrade path that you take depends on the products and versions that you're currently using.

Consider the following rules and guidelines to applying the hotfix or upgrade:

- You can apply the hotfix if you are on any version associated with the major release. For example 10.5 is a major release, so you can apply the hotfix from any version of 10.5.x.
- If you're not currently using a version associated with the major release, you can upgrade to the current release from any supported previous release.
- If you are on a version that doesn't support a direct upgrade, you must first upgrade to a supported version.
- Any supported update also includes hotfixes, service packs, and cumulative patches.

Important: If Data Engineering is in the same domain as any other product supported by the Informatica installer, verify that all products are upgraded to the same supported upgrade version before you upgrade to 10.5.11.

The following table provides details for the rules and guidelines:

Product	Versions
PowerCenter	You can apply the10.5.11 hotfix to version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5.11 from the following previous versions: - 10.2 including any hotfix, service pack, or cumulative patch - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch
Informatica Data Quality	You can apply the 10.5.11 hotfix to version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5.11 from the following previous versions: - 10.2 including any hotfix, service pack, or cumulative patch - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch
Data Engineering Integration Data Engineering Quality	You can apply the 10.5.11 hotfix to version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5 from the following previous versions, and then you can apply the 10.5.11 hotfix: - 10.2 including any hotfix, service pack, or cumulative patch - 10.2.1 including any hotfix, service pack, or cumulative patch - 10.2.2 including any hotfix, service pack, or cumulative patch - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch **Important:** If Data Engineering is in the same domain as any other product supported by the Informatica installer, verify that all products are upgraded to the same supported upgrade version before you upgrade to 10.5.11.
Data Engineering Streaming	You can apply the 10.5.11 hotfix to version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5 from the following previous versions, and then you can apply the 10.5.11 hotfix: - 10.2.2 including any hotfix, service pack, or cumulative patch - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch
Data Privacy Management	You can apply the 10.5.11 hotfix to versions 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5 from the following previous versions, and then you can apply the 10.5.11 hotfix: - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch
Enterprise Data Catalog	You can apply the 10.5.11 to version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5, 10.5.1, 10.5.2, 10.5.3, or 10.5.4 from the following previous versions, and then you can apply the 10.5.11 hotfix: - 10.4 (including any service packs or cumulative patches) - 10.4.1 (including any service packs or cumulative patches) **Important:** If Enterprise Data Catalog and Data Engineering are in the same domain of a version 10.4.1, 10.4 or earlier, upgrade them both to version 10.5, 10.5.1, 10.5.2, 10.5.3, or 10.5.4 before you upgrade to 10.5.11.

Product	Versions
Enterprise Data Preparation	You can apply the 10.5.11 hotfix to version 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. **Note:** You cannot upgrade to version 10.5.11 from Enterprise Data Preparation version 10.5.7. You can upgrade to version 10.5, 10.5.1, 10.5.2, 10.5.3, or 10.5.4 from the following previous versions, and then you can apply the 10.5.11 hotfix: - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch
Test Data Management	You can apply the 10.5.11 hotfix to versions 10.5, 10.5.1, 10.5.2, 10.5.3, 10.5.4, 10.5.5, 10.5.6, 10.5.7, 10.5.8, 10.5.9, or 10.5.10 including any service pack or cumulative patch. You can upgrade to version 10.5 from the following previous versions, and then you can apply the 10.5.11 hotfix: - 10.4 including any service pack or cumulative patch - 10.4.1 including any service pack or cumulative patch

Upgrade Process

You use the Informatica installer, Informatica Administrator (the Administrator tool), and infacmd to upgrade to Enterprise Data Preparation 10.5.11.

Perform the following steps to upgrade to the latest version:

1. Run the installer to upgrade the Enterprise Data Preparation binaries to Enterprise Data Preparation version 10.5.11.
2. Use the Administrator tool to upgrade the Informatica application services.
3. Use the Administrator tool to upgrade the Data Preparation repository.
4. Use the Administrator tool to enable and upgrade the Enterprise Data Preparation Service.

The installer migrates Enterprise Data Catalog resources configured for the installed version, including Hive scanners and HDFS scanners, to Enterprise Data Preparation version 10.5.11. You can view the migrated catalog resources in the Lake Management page in the Enterprise Data Preparation application.

For more information on managing catalog resources in Enterprise Data Preparation, see the *Enterprise Data Preparation Administrator Guide*.

CHAPTER 2

Before You Upgrade

This chapter includes the following topics:

- Back Up the Installation, 10
- Download and Extract the Installer Files, 10
- Verify Distribution Package Requirements (Linux and UNIX), 11
- Upgrade the Domain Services, 12

Back Up the Installation

Informatica recommends that you back up the service metatdata, repositories, and storage locations associated with your current installation before you upgrade.

Back up the following application services, repositories, and storage locations associated with Enterprise Data Preparation:

- Back up the Model repository associated with the Enterprise Data Preparation Service.
- Document the configuration details for the Hive scanners and HDFS scanners configured in the catalog.
- Back up the MySQL database or Oracle database used as the Data Preparation repository.
- Back up the Interactive Data Preparation Service durable storage location on HDFS.
- Back up the Enterprise Data Catalog data using the export utility to restore it after a successful upgrade.
- If rules are configured for the Enterprise Data Preparation Service, back up the rules metadata.

For more information, see "Backing Up and Restoring Enterprise Data Preparation" in the *Informatica® Enterprise Data Preparation Administrator Guide*.

Download and Extract the Installer Files

The installer files are distributed as compressed files. You can get the Informatica installation file and distribution packages from the FTP link contained in your fulfillment email.

Download the Informatica installation tar file and the required distribution package ZIP files from the Informatica Electronic Software Download site. You can download them to a local directory or a shared network drive that is mapped on your machine.

To download other compressed files and utilities, raise a shipping request with Informatica Global Customer Support.

Extract the Informatica installer files to a directory on your machine. The user that runs the installer must have read and write permissions on the installer files directory and execute permissions on the executable file.

Note: Ensure that you extract the installer files to a local directory as you can't run the installer from a mapped file.

Copy the ZIP files of the distribution packages to the following location: `<Informatica installer files>/source`

Note: The installer fails if the ZIP files for distribution packages aren't available in the source directory.

Verify Installer Package Checksum on Linux

Before you run the upgrade installer for the Informatica services, verify the install package integrity through the cksum command. The cksum command calculates the checksum value for the installer.

Verify the checksum for the specific installer files against the checksum of the installation files downloaded from the Informatica Electronic Software Download site.

The following table lists the checksum and file size for the Informatica services installer for Linux:

File	Checksum Value	File Size
informatica_10510_server_linux-x64.tar	1346986189	17774100480 bytes

A checksum mismatch can occur when there are data errors during download due to network issues or when data corruption occurs in the file on disk. For more information about the checksum errors, see HOW TO: Identify file errors after downloading Informatica installation files.

Verify Distribution Package Requirements (Linux and UNIX)

You can use third-party distribution packages to integrate the Informatica domain with the Hadoop or Databricks environment.

The Informatica domain and client require the distribution packages to process complex files within the Informatica domain, or to connect to Hadoop or Databricks environment when you process within the Informatica domain, or to push processing to Hadoop or Databricks environment.

If you need a distribution package, you can install it through the installer or through Integration Package Manager (the package manager) at any time.

Process within the Informatica domain

You can use the same distribution package that you used in the previous Informatica version to process complex files within the Informatica domain or to connect to the Hadoop or Databricks environment when you process within the Informatica domain.

The following adapters require distribution packages for processing within the Informatica domain:

- PowerExchange for Amazon S3
- PowerExchange for Google Cloud Storage
- PowerExchange for Google Cloud Storage for PowerCenter
- PowerExchange for Hadoop for PowerCenter
- PowerExchange for HBase
- PowerExchange for HDFS
- PowerExchange for Hive
- PowerExchange for JDBC V2
- PowerExchange for Kafka for PowerCenter
- PowerExchange for MapR-DB
- PowerExchange for Microsoft Azure Blob Storage
- PowerExchange for Microsoft Azure Data Lake Storage Gen1
- PowerExchange for Microsoft Azure Data Lake Storage Gen2

Process with Hadoop or Databricks environment

When you push processing to the Hadoop or Databricks environment, the Informatica domain and client require distribution packages. For more information about the supported distribution packages, see the Product Availability Matrix.

Upgrade the Domain Services

Before you upgrade Enterprise Data Preparation, upgrade the domain services.

Note: Before you upgrade the domain services, make sure that you have at least one custom property set for the Data Preparation service. If you do not have any custom property, set a dummy custom property and remove the property after the upgrade is complete. For example, you can set CustomOptions.disableUserTablePermissionCheck = true as the dummy custom property.

For more information, see the *Upgrading from Version 10.4 (10.5.11)* Data Engineering upgrade guide.

CHAPTER 3

Upgrade Enterprise Data Preparation

This chapter includes the following topics:

- Upgrade the Enterprise Data Preparation Binaries, 13
- Upgrade the Application Services, 14
- Upgrade the Data Preparation Repository, 14
- Upgrade the Enterprise Data Preparation Service, 15

Upgrade the Enterprise Data Preparation Binaries

Use the installer to upgrade the binaries on a node to Enterprise Data Preparation 10.5.11

The installer shuts down the domain before starting the upgrade process. After the upgrade completes, the installer starts the services within the domain.

1. Log in to the node host machine with a system user account.
2. On a shell command line, run the `install.sh` file from the root directory.

   The installer displays the message for documentation and copyright information.
3. Press **2** to upgrade the Informatica Data Engineering products installed on the node.
4. Press **2** to upgrade the Informatica services.
5. Press **2** to accept the terms and conditions.
6. Enter the current application installation directory.
7. Enter the directory path where you want to install the Enterprise Data Preparation 10.5.11 binaries.

   The path must not contain spaces or the following special characters: @|* $ # ! % ( ) { } [ ] , ; '.
8. Choose whether to change the node host name, port numbers, or domain configuration repository database during the upgrade.
   - Select **1** to change the node host name, port numbers, or domain configuration repository database during the upgrade.

     If you select this option, you can change the configuration. If you are upgrading to a different machine, you can change the node configuration to match the new machine.
   - Select **2** to retain the current node host name, port numbers, and domain configuration repository database.

9. Choose whether you want to install distribution packages through the Informatica installer.
   - Press **1** if you don't need distribution packages or if you want to install them later.
   - Press **2** if you want to install distribution packages through the installer.

   Default is 1.
10. If you choose to install distribution packages, select one or more packages from the list that you want to install. Separate multiple packages with a comma.

    Default is 1.
11. Enter the path to the directory containing the site key for the domain.

    You must also enter the domain administrator user name and password.
12. Review the pre-installation summary, then press **Enter** to continue.

    The installer copies the Enterprise Data Preparation binaries to the upgrade directory. The installer reads information from the previous version and configures Enterprise Data Preparation based on the configuration for the previous version. It does not modify the files of the previous version.

The Post-upgrade Summary indicates whether the upgrade completed successfully. The summary also shows the status of the upgraded components and their configuration.

The installer generates an Informatica_10.5.11_Services_Upgrade_<datetime>.log file in the Informatica installation directory. If any issues occur during the upgrade, check the upgrade log file for details.

Upgrade the Application Services

Use the upgrade wizard in the Administrator tool to upgrade the Model Repository Service, the Data Integration Service, and the Content Management Service associated with Enterprise Data Preparation.

After the upgrade completes, the installer starts the services within the domain. You must wait for each service to start before you can upgrade the service.

1. In the Administrator tool header, select **Manage** > **Upgrade**.
2. Select the Model Repository Service, the Data Integration Service, and the Content Management Service in the wizard panel.
3. Click **Next**.

   The Administrator tool upgrades the selected services, and displays the status of the upgrade.
4. Click **Close** after the upgrade completes.

Upgrade the Data Preparation Repository

Upgrade the Data Preparation repository and enable the Interactive Data Preparation Service.

1. In the Administrator tool header, click the **Services and Nodes** view.
2. Select the Data Preparation Service.
3. In the **Properties** tab, select **Actions** > **Upgrade Repository**.
4. After the upgrade process completes, click **Actions** > **Enable Service** to start the service.

Upgrade the Enterprise Data Preparation Service

Upgrade the Enterprise Data Preparation Service to complete the upgrade process.

Note: If you attempt to upgrade the service by selecting **Actions > Upgrade** in the **Properties** tab, the upgrade fails.

1. In the Administrator tool, click **Manage** > **Services and Nodes**.
2. In the Domain Navigator, select the Enterprise Data Preparation Service.
3. Click the **Processes** tab.
4. Click **Actions** > **Enable Service** to start the service.
5. In the upper right of the Administrator tool header, click **Manage** > **Upgrade**.
6. Select the Enterprise Data Preparation Service.
7. Click **Next**. The service upgrade wizard upgrades this service and associated database and displays the status and processing details.
8. When the upgrade completes, the Summary section displays the list of application services and their upgrade status. Click each service to view the upgrade details in the Service Details section.
9. Click **Close** after the upgrade completes.

CHAPTER 4

After You Upgrade Enterprise Data Preparation

This chapter includes the following topic:

- Copy JDBC JAR Files, 16

Copy JDBC JAR Files

Copy the JDBC JAR files from a previous version of Informatica to the current version. The JDBC JAR files are required to perform the import and export operations in Enterprise Data Preparation.

1. Disable the Enterprise Data Preparation service.
2. Find the JAR files in the following location:

   ```
   <backup directory>/externaljdbcjars
   ```
3. Copy them to the following location:

   ```
   /<Informatica installation directory>/externaljdbcjars
   ```
4. Recycle the Enterprise Data Preparation service.
5. Recycle Data Integration Service associated with Enterprise Data Preparation.

CHAPTER 5

Hotfix installation and rollback

This chapter includes the following topics:

- Hotfix installation and rollback overview, 17
- Applying the services hotfix, 18
- Rolling back the services hotfix, 25
- Applying the client hotfix, 28
- Rolling back the client hotfix, 30

Hotfix installation and rollback overview

When you apply the hotfix, the installer backs up existing directories, applies the new version of the product, and restores or updates required configuration and run-time files. When you roll back a hotfix, the installer restores Informatica to the previously installed version.

Informatica provides installers to apply hotfixes to the Informatica services and clients.

To apply or roll back the Informatica hotfix, perform the following steps:

1. Complete the preliminary tasks. Before you apply or rollback the hotfix, ensure that you shut down the domain. For a multi-node configuration, you also need to shut down all the nodes.
2. Apply or roll back the hotfix to the Informatica services in console or silent mode.
3. Complete the final tasks for the Informatica services. After you install the server components, start the domain on the gateway node.
4. Apply the hotfix to the Informatica clients in graphical or silent mode. If you are applying the hotfix to Informatica Developer, verify that the Informatica client hotfix version matches the Informatica services hotfix version.

   Note: If the Informatica client hotfix version doesn't match the Informatica services hotfix version, Informatica Developer cannot connect to the domain.

When you roll back a hotfix, the installer restores Informatica to the previously installed version.

Applying the services hotfix

When you apply the hotfix, the installer backs up existing directories, applies the new version of the product, and restores or updates required configuration and run-time files.

You can run the installers to apply hotfixes to Informatica services and clients.

Before you apply the hotfix

Before you run the installer to apply the hotfix, perform the following prerequisite tasks:

Verify distribution package requirements

The Informatica domain and client require the distribution packages to process complex files within the Informatica domain, or to connect to Hadoop or Databricks environment when you process within the Informatica domain, or to push processing to Hadoop or Databricks environment.

If you need a distribution package, you can install it through the installer or through Integration Package Manager (the package manager) at any time.

You can use the same distribution package that you used in the previous Informatica version to process complex files within the Informatica domain or to connect to the Hadoop or Databricks environment when you process within the Informatica domain.

For the supported distribution packages when you push processing to Hadoop or Databricks environment, see the Product Availability Matrix.

Download and extract the installer files

The installer files are distributed as compressed files. You can get the Informatica installation file and distribution packages from the FTP link contained in your fulfillment email. Download the Informatica installation tar file from the Informatica Electronic Software Download site to a directory on your machine.

To download other compressed files and utilities, raise a shipping request with Informatica Global Customer Support.

Note: Make sure that you download the file to a local directory or a shared network drive that is mapped on your machine. You can then extract the installer files. However, you cannot run the installer from a mapped file. Copy the extracted files to a local drive and then run the installer.

1. Download the hotfix package for your product.
2. Untar the contents of the hotfix package.

   Note: Use the native tar or GNU tar command to extract the installer files. The user that runs the installer must have read and write permissions on the directory that contains the installer files and execute permissions on install.sh.
3. If you want to install distribution packages, download the ZIP files of the distribution packages.
4. Copy the ZIP files of the distribution packages to the location: `<Informatica installer files>/source`

   Note: The installer fails if the ZIP files for distribution packages aren't available in the source directory.

Prepare for hotfix installation

1. Stop all processes that access the installation directory and subdirectories, including command prompts and command line programs.
2. Close the Informatica clients on all machines where you want to apply the hotfix.
3. Close the Informatica directory and the subdirectories.

4. Complete the following steps to back up the configuration metadata for the Informatica domain:
   a. Run the infasetup backupDomain command to back up the domain configuration database tables to a file.
   b. Back up the metadata configuration files to any directory accessible by the machines where you install Informatica.

   infasetup is located in the following directory: `<Informatica installation directory>/isp/bin`
5. Back up the binaries from the Informatica installation directory. Also, back up the following files from the Informatica domain:
   - `<Informatica installation directory>/isp/config/keys/siteKey`
   - `<Informatica installation directory>/domains.infa`
   - `<Informatica installation directory>/tomcat/conf/server.xml`
   - `<Informatica installation directory>/isp/config/nodemeta.xml`

   The nodemeta.xml file contains the metadata for a node. It is stored in the following directory on each node in the domain: `isp/config`. If you use the same backup directory name on all the nodes, rename the file before copying it to the backup location. For example, you back up nodemeta.xml to the /nodebak directory on nodeA and nodeB. Rename the configuration files so that on nodeA the file is backed up to /nodebak/nodemeta_A.xml, and on nodeB the file is backed up to /nodebak/nodemeta_B.xml.

   The domains.infa file contains connectivity information for the gateway nodes. It is stored in the Informatica installation directory or the location configured through the INFA_DOMAINS_FILE environment variable.
6. Back up the catalog data using the infacmd ldm backupContents command.

   Note: Verify that you take a full backup of the catalog data. If you deployed the Informatica Cluster Service on multiple nodes, verify that you configured the cluster shared file system path for the Informatica Cluster Service. If you do not configure the shared file system, the SEARCH store is not backed up, and a warning message appears in the console log. If the SEARCH store is not backed up, the backup validation fails when you apply or roll back the hotfix.
7. Back up the following SSL configuration files:
   - The domain truststore and keystore files.
   - The default keystore files.
   - The keystore and truststore files that the application services use.

   By default, the SSL configuration files are stored in the following directory: `<Informatica installation directory>/services/shared/security`
8. Back up the repository and warehouse files. Ensure that you back up the required repositories from the Administrator tool. These backup files are required if you roll back the hotfix. Back up the following databases and files in your environment:
   - Domain
   - Model repository
   - Catalog data
   - Durable Storage of Data Preparation service
9. Stop the Informatica services on all nodes in the domain.
10. Shut down the Informatica Cluster Service using the infacmd ics shutdowncluster command or from the Informatica Administrator.

11. Shut down the Informatica domain using the infaservice shutdown command. By default, the infaservice executable file is located in the following directory: `<Informatica installation directory>/tomcat/bin`.
12. If the machine uses HTTPS to connect to Informatica Administrator, verify that the keystore file is in the default location and that it uses the default file name. The default location for the keystore file is `<Informatica installation directory>/tomcat/conf`. The default file name for the keystore file is Default.keystore.
13. Set the SKIP_VENDOR_CHECK environment variable to true to remove the sudo prompt from the hotfix installation on UNIX.

    Note: If you don't have sudo privileges, set the environment variable to true before you apply or roll back a hotfix. If you have sudo privileges, you don't need to set the environment variable.

Apply the services hotfix in console mode

Run the 10.5.11 installer to apply the hotfix to version 10.5 or 10.5.x.

When you apply the hotfix in console mode, the words Help, Quit, and Back are reserved words. Do not use them as input text.

1. Run the installer using the ./install.sh command.
2. Press **Y** to confirm that you want to proceed with the installation.
3. Press **5** to select the option to apply the hotfix.
4. Press **1** to apply the hotfix.
5. Press **2** to agree to the terms and conditions and apply the license.
6. Verify that all installation requirements are met before you continue to apply the hotfix.
7. Press **Enter**.
8. Enter the directory where you installed Informatica 10.5 or 10.5.x.
   The directory names in the path must not contain spaces or the following special characters: @|* $ # ! % ( ){ } [ ] , ; '
9. Press **2** to confirm that you configured the Catalog Service on the node.
10. Press **2** to confirm that you backed up the catalog data using the infacmd ldm backupContents command.
    Press **1** to skip the backup validation and proceed.

    You must skip the validation in the following scenarios:

    - You configured multiple nodes for the Catalog Service and you do not want to validate the backup on each node.
    - You did not configure the cluster shared file system path for the Informatica Cluster Service on a multi-node setup.
    - You enabled the Model Repository Service and the Data Integration Service, but you did not create the Catalog Service and the Informatica Cluster Service.
11. Enter the location of the backup file. For example, `/data/Informatica/LDM_BACKUP1050SAML12.zip`.
12. Select one of the following options based on the type of installation:

    - Press **1** to set Sandbox environment for a basic environment used for proof of concept with minimal users.
    - Press **2** to set Development environment for the design environment.

- Press **3** to set Test environment for high volume processing that is closest to a production environment.
- Press **4** to set Production environment for high volume processing with high levels of concurrency meant for end users. Advanced production environments are typically multi-node setups.

Default is **1** for Sandbox.

13. Choose whether you want to install distribution packages through the Informatica installer.
    - Press **1** if you don't need distribution packages or if you want to install them later.
    - Press **2** if you want to install distribution packages through the installer.

    Default is 1.
14. If you choose to install distribution packages, select one or more packages from the list that you want to install. Separate multiple packages with a comma.
    Default is 1.
15. Press **Enter**.
16. At the Pre-Installation Summary, review the installation information and press **Enter** to apply the hotfix. The installer copies the Informatica files to the installation directory.
17. At the Post-Installation Summary, verify that the hotfix application completed successfully and press **Enter** to exit the installer.

Apply the services hotfix in silent mode

To apply the hotfix in silent mode, create the SilentInput.properties file and then run the installer.

Informatica provides a sample properties file, called SilentInput_hotFix.properties, that includes the parameters that the installer requires.

1. Go to the root of the directory that contains the installation files.
2. Locate the SilentInput_hotFix.properties file.
3. Back up the file before you modify it.
4. Use a text editor to open the file and modify the values. The following table describes the installation properties that you can modify:

Property Name	Description
INSTALL_TYPE	Indicates whether to apply the hotfix or roll back the hotfix. If the value is 0, the installer applies the hotfix to the current Informatica installation. If the value is 1, the installer rolls back the current hotfix. Set the value to 0 to apply the hotfix.
USER_INSTALL_DIR	Directory for the Informatica installation where you want to apply or roll back the hotfix. To apply the hotfix to Informatica services, enter the absolute path for the directory in which the current version of Informatica services is installed.

Property Name	Description
ENABLE_USAGE_COLLECTION	Enables the software to automatically transmit to Informatica in the USA information about the computing and network environment in which the Software is deployed and the data usage and system statistics of the deployment. This transmission is deemed part of the Services under the Informatica privacy policy and Informatica will use and otherwise process this information in accordance with the Informatica privacy policy available at https://www.informatica.com/in/privacy-policy.html. You may disable usage collection in Administrator tool. For more information about how to disable sending usage statistics, see the *Informatica Administrator Guide*. You must set the value to 1 to apply the hotfix.
INSTALLATION_ENVIRONMENT	If you apply the hotfix, specify the environment type associated with the Informatica services installation. • Press **1** to set Sandbox environment for a basic environment used for proof of concept with minimal users. • Press **2** to set Development environment for the design environment. • Press **3** to set Test environment for high volume processing that is closest to a production environment. • Press **4** to set Production environment for high volume processing with high levels of concurrency meant for end users. Advanced production environments are typically multi-node setups. Default is 1 for Sandbox.
EDC_CATALOG_INST	Required for Enterprise Data Catalog, Data Privacy Management, and Enterprise Data Preparation installations. Set the property to true if the Catalog Service runs on the node on which you want to apply the hotfix.
EDC_HF_BACKUP	Required for Enterprise Data Catalog, Data Privacy Management, and Enterprise Data Preparation installations, if you have set EDC_CATALOG_INST=true. Set the property to true if you have taken a backup of the catalog.
EDC_BACK_UP_DIR	Required for Enterprise Data Catalog, Data Privacy Management, and Enterprise Data Preparation installations, if you set the EDC_CATALOG_INST and EDC_HF_BACKUP properties to true. Enter the location of the catalog data backup file.
INSTALL_HADOOP_LIBRARIES	Determines whether to install distribution packages through the installer. Set the value to true if you want to install distribution packages through the installer. Set the value to false if you don't need distribution packages or if you want to install them later.
SELECTED_HADOOP_LIBRARIES	Determines the distribution packages that you want to install from the supported packages list. Enter the distribution packages that you want to install, separating multiple packages with a comma.

5. Save the properties file with the name SilentInput.properties in the same folder.
6. Go to the root of the services installer directory.
7. Verify that the directory contains the SilentInput.properties file that you edited and saved.
8. To apply the hotfix, on a shell command line, enter the following command to run the silent installer: ./silentInstallHotFix.sh.

   The installer copies the Informatica files to the installation directory.
9. Complete the post-installation tasks. Verify that the hotfix completed successfully by reviewing the log file or the **Post-Installation Summary** page.

Sample silent input properties

The following example shows the contents of the SilentInput.properties file when you apply or roll back the hotfix in silent mode.

```
############################################################
# (C) Copyright Informatica LLC 1993, 2023.
# This software and documentation are provided only under a separate license agreement
containing restrictions on use and disclosure.
# This software is protected by patents as detailed at https://www.informatica.com/legal/
patents.html
# A current list of Informatica trademarks is available on the web at https://
www.informatica.com/trademarks.html
# See the Informatica privacy policy at https://www.informatica.com/privacy-policy.html
############################################################

# Use the following guidelines when editing this file
# * Use this file to install without user interaction.
# * After you create the properties file, save the file with the name
SilentInput.properties
# * Any error condition that leads to failure, such as an invalid
# installation directory, generates a log file in the user home
# directory. For example: /home/<user name>/silentErrorLog<time_stamp>.log

############################################################

# Set ENABLE_USAGE_COLLECTION  to 1 to accept the product usage toolkit end user license
agreement.
# You must set the value as 1 to install the Informatica platform.
# The product usage toolkit end user license agreement is available at: http://
www.informatica.com/us/eula/en-support-eula.aspx.
# As further described in the EULA, your use of the Informatica platform will enable the
product usage toolkit
# to collect certain product usage and failure information. You may disable this feature
at any time.
# For more information on how to disable this feature refer the Informatica
Administrator Guide.

ENABLE_USAGE_COLLECTION=0



## *INSTALL_TYPE - Set this value to '0' to apply the hotfix. Set this value to '1' to
roll back the hotfix.

INSTALL_TYPE=0


# * The USER_INSTALL_DIR variable must point to a valid directory with write
#     permissions enabled.



USER_INSTALL_DIR=/home/Informatica/10.5


#The INSTALLATION_ENVIRONMENT property represents the installation environment
# Set the property to one of the following installation environment types: Sandbox,
Development, Test, or Production. Values are case-sensitive.
# Set to Sandbox for a basic environment used for proof of concept with minimal
users.
# Set to Development for the design environment.
# Set to Test for high volume processing that is closest to a production environment.
# Set to Production for high volume processing with high levels of concurrency meant for
end users. Advanced production environments are typically multi-node setups.

INSTALLATION_ENVIRONMENT=

# Required only for EDC installation
# Set EDC_CATALOG_INST=true if the Catalog Service is running on the node on which you
```

```
want to apply or roll back the hotfix.
EDC_CATALOG_INST=false

# Required only for EDC installation.
# Set EDC_HF_BACKUP=true if you have set EDC_CATALOG_INST=true and you have taken a
backup of the catalog.
# Run the infacmd ldm backupContents command before you apply the hotfix (INSTALL_TYPE=0)
# Run the infacmd ldm restoreContents command after you rollback the hotfix
(INSTALL_TYPE=1)
EDC_HF_BACKUP=false

# Enter the location of the backup file.
# Required for Enterprise Data Catalog installation when the EDC_CATALOG_INST and
EDC_HF_BACKUP parameters are set to true
EDC_BACK_UP_DIR=

# The INSTALL_HADOOP_LIBRARIES property determines whether to install packages to
integrate the domain with Hadoop or Databricks.
# Set INSTALL_HADOOP_LIBRARIES=true if you want to install the integration packages to
push processing to Hadoop or Databricks, process complex files within the domain, or
connect to Hadoop but process within the domain.
# Set INSTALL_HADOOP_LIBRARIES property only if INSTALL_TYPE=0
# If you don't install the integration packages now, you can install them later through
Integration Package Manager.
INSTALL_HADOOP_LIBRARIES=false

# The SELECTED_HADOOP_LIBRARIES property determines the integration packages that you
want to install.
# Lists the supported integration packages and their versions.
# Set SELECTED_HADOOP_LIBRARIES property only if INSTALL_TYPE=0
# Enter the integration package that you want to install. Separate multiple packages
with a comma.
# You can choose from the following options:
# 1->Azure HDInsight 5.1
# 2->Cloudera 7.1
# 3->Cloudera 7.218
# 4->Databricks 11.3
# 5->Dataproc 2.0
# 6->Elastic MapReduce 7.1
# 7->Elastic MapReduce 7.9
# 8->MapR 7.9
# 9->Select all
SELECTED_HADOOP_LIBRARIES=
```

After you apply the hotfix

After you run the installer to apply the hotfix, start the domain and perform the post requisite tasks to complete the hotfix application.

Remove the distribution packages from the backup location

After you apply the hotfix, remove the distribution packages from the backup folder to mitigate the security vulnerabilities.

When you apply the hotfix, all the existing files in the Informatica installation directory are backed up. You need to remove the distribution packages backup from the following location: `<Informatica installation directory>\BACK_FROM_<hotfix version number>\services\shared\hadoop\<distribution package_version>`

The following example shows the backup location for a distribution package when you apply the hotfix: `C:\Informatica\BACK_FROM_3\services\shared\hadoop\EMR_6.4`

Note: The deletion process doesn't remove all files of the distribution packages from the backup folder. Some files might still exist in the following location: `<Informatica installation directory>\BACK_FROM_<hotfix version number>\services\shared\` You can delete these files manually.

Important: When you roll back the hotfix, distribution packages are not restored. You can't enable functionality associated with the Hadoop or Databricks distribution packages in the rolled-back version. To install the distribution packages, contact Informatica Global Customer Support.

Rolling back the services hotfix

You can roll back the hotfix if required. To roll back the hotfix, run the installer.

Before You Roll Back the Hotfix

Before you run the installer to roll back the hotfix, you must perform the prerequisite tasks.

1. Stop all processes that access the installation directory and subdirectories, including command prompts and command line programs.
2. Close the Informatica clients on all machines where you want to roll back the hotfix.
3. Close the Informatica directory and the subdirectories.
4. Stop the Informatica services on all nodes in the domain.
5. If the machine uses HTTPS to connect to Informatica Administrator, verify that the keystore file is in the default location and that it uses the default file name. The default location for the keystore file is `<Informatica installation directory>/tomcat/conf`. The default file name for the keystore file is Default.keystore.

Roll back the services hotfix in console mode

You can roll back the hotfix that you applied. To roll back the hotfix in console mode, run the installer.

1. Run the installer using the ./install.sh command.
2. Press **Y** to confirm that you want to proceed with the installation.
3. Press **5** to roll back the hotfix.
4. Press **2** to roll back the hotfix.
5. Press **2** to accept the license.
6. Verify the prerequisites and press **Enter**.
7. Enter the directory where you installed Informatica and press **Enter**.
8. Press **2** to confirm that you configured the Catalog Service on the node.

   Note: If you confirm that you configured the Catalog Service on the node where you plan to roll back the hotfix, you must validate the backup on the node. Press **1** to skip the backup validation and proceed to step 11.

   You must skip the validation in the following scenarios:

   - You did not configure the cluster shared file system path for the Informatica Cluster Service on a multi-node setup.

- You configured multiple nodes for the Catalog Service and you do not want to validate the backup on each node.
- You enabled the Model Repository Service and the Data Integration Service, but you did not create the Catalog Service and the Informatica Cluster Service.

9. Press **2** to confirm that you backed up the catalog data using the infacmd ldm backupContents command.
10. Enter the location of the backup file. For example, `/data/Informatica/LDM_BACKUP1050SAML12.zip`.

    Note: If the SEARCH store is not included in the backup, the validation fails with an error. You can skip the backup validation if the backup does not include the SEARCH store.
11. Press **Enter** to start the rollback.
12. At the Pre-Installation Summary, press **Enter** to continue.
13. Press **Enter** to exit the installer when the rollback completes successfully.

    Important: When you roll back the hotfix, distribution packages are not restored. You can't enable functionality associated with the Hadoop or Databricks distribution packages in the rolled-back version. To install the distribution packages, contact Informatica Global Customer Support.

Roll back the services hotfix in silent mode

To roll back the hotfix in silent mode, update the SilentInput.properties file and then run the silent installer.

Informatica provides a sample properties file, called SilentInput_hotFix.properties, that includes the parameters that are required by the installer.

1. Go to the root of the directory that contains the installation files.
2. Locate the SilentInput_hotFix.properties file.
3. Back up the file before you modify it.
4. Use a text editor to open the file and modify the values. The following table describes the installation properties that you can modify:

Property Name	Description
INSTALL_TYPE	Indicates whether to apply the hotfix or roll back the hotfix. Set the value to 1 to roll back the current hotfix.
USER_INSTALL_DIR	Directory for the Informatica installation where you want to roll back the hotfix.
ENABLE_USAGE_COLLECTION	Enables the software to automatically transmit to Informatica in the USA information about the computing and network environment in which the Software is deployed and the data usage and system statistics of the deployment. This transmission is deemed part of the Services under the Informatica privacy policy and Informatica will use and otherwise process this information in accordance with the Informatica privacy policy available at https://www.informatica.com/in/privacy-policy.html. You may disable usage collection in Administrator tool. For more information about how to disable sending usage statistics, see the *Informatica Administrator Guide*. You must set the value to 1 to roll back the hotfix.
INSTALLATION_ENVIRONMENT	You can ignore the property during rollback.

Property Name	Description
EDC_CATALOG_INST	Required for Enterprise Data Catalog, Data Privacy Management, and Enterprise Data Preparation installations. Set the property to true if the Catalog Service runs on the node on which you want to apply the hotfix.
EDC_HF_BACKUP	Required for Enterprise Data Catalog, Data Privacy Management, and Enterprise Data Preparation installations, if you have set EDC_CATALOG_INST=true. Set the property to true if you have taken a backup of the catalog.
EDC_BACK_UP_DIR	Required for Enterprise Data Catalog, Data Privacy Management, and Enterprise Data Preparation installations, if you set the EDC_CATALOG_INST and EDC_HF_BACKUP properties to true. Enter the location of the catalog data backup file.

5. Save the properties file with the name SilentInput.properties.
6. Go to root of the Informatica services installer directory.
7. Verify that the directory contains the SilentInput.properties file that you edited and saved.
8. On a shell command line, enter the following command to run the silent installer:

   ./silentInstallHotFix.sh.

   The installer removes the last hotfix and restores the previous version of Informatica.
9. Complete the post rollback tasks. Verify that the rollback completed successfully by reviewing the log file or the **Post-Installation Summary** page.

   Important: When you roll back the hotfix, distribution packages are not restored. You can't enable functionality associated with the Hadoop or Databricks distribution packages in the rolled-back version. To install the distribution packages, contact Informatica Global Customer Support.

After You Roll Back the Hotfix

After you roll back the hotfix, perform these steps to complete the rollback.

1. After the rollback is complete, start the Informatica domain.
2. Run the infacmd mrs deleteContents command to remove the Model repository contents.
3. Enable the Model Repository Service.
4. Run the infacmd mrs RestoreContents to restore the 10.5 and 10.5.2 Model repository content.
5. Enable the Data Integration Service.
6. Enable the Content Management Service.
7. Enable the Analyst Service.
8. Run the infacmd ihs cleanCluster command to clean the Informatica Cluster Service.
9. Enable the Informatica Cluster Service.
10. Run the infacmd ldm restoreContents command to restore the 10.5 catalog.
11. From the Informatica Administrator, remove any custom properties that you had configured for Catalog Service after you upgraded to version 10.5.11.
12. Enable the Catalog Service.

Note: After you roll back the hotfix, the installer retains the Data Asset Analytics configuration properties on the Catalog Service page when you view the Catalog Service in Informatica Administrator.

Applying the client hotfix

When you apply the hotfix, the installer backs up existing directories, applies the new version of the client, and restores or updates required configuration and run-time files.

You can run the client installer to apply a hotfix to Informatica clients that you use. After you apply the hotfix, you can remove the backup files of the distribution packages from the backup folder.

Apply the client hotfix in graphical mode

When you run the installer in graphical mode, a console window opens and runs in the background. If you close this window, the installation stops.

1. Log in to the machine with a system user account. The user account must be the same account used to install the previous version of Informatica services.
2. Close all other applications.
3. To begin the installation, run install.bat from the root directory where you unzipped or untarred the client hotfix installation package.
4. On the Informatica 10.5.11 page, select **Apply hotfix to a version from 10.5 through 10.5.10, or roll back the hotfix**, and then click **Start**.

   The **Installation Type** page appears.
5. Select **Apply the hotfix** to choose to apply the hotfix.
6. Verify that all requirements are met before you continue the hotfix, and then click **Next**.

   The **Installation Directory** page appears.
7. Enter the absolute path for the directory in which the current version of the Informatica client is installed and specify the installation environment.
8. If you want to install distribution packages through the Informatica installer, select the check box.
9. If you choose to install distribution packages, select one or more packages from the list that you want to install.
10. Click **Next**.

    The **Pre-Installation Summary** page appears.
11. Review the installation information, and then click **Install** to apply the hotfix.

    The installer copies the Informatica files to the installation directory.
12. Complete the post-installation tasks. Verify that the hotfix completed successfully by reviewing the log file or the **Post-Installation Summary** page.

Apply the client hotfix in silent mode

To apply the hotfix in silent mode, create the SilentInput.properties file and then run the installer.

Informatica provides a sample properties file, called SilentInput_hotFix.properties, that includes the parameters that the installer requires.

1. Go to the root of the directory that contains the client installation files.
2. Locate the SilentInput_hotFix.properties file.
3. Back up the file before you modify it.

4. Use a text editor to open the file and modify the values. The following table describes the installation properties that you can modify:

Property Name	Description
INSTALL_TYPE	Indicates whether to apply the hotfix or roll back the hotfix. If the value is 0, the installer applies the hotfix to the current Informatica client installation. If the value is 1, the installer rolls back the current hotfix. Set the value to 0 to apply the hotfix.
USER_INSTALL_DIR	Directory for the Informatica client installation where you want to apply or roll back the hotfix. To apply the hotfix, enter the absolute path for the directory in which the current version of the Informatica clients is installed.
INSTALL_HADOOP_LIBRARIES	Determines whether to install distribution packages through the installer. Set the value to true if you want to install distribution packages through the installer. Set the value to false if you don't need distribution packages or if you want to install them later.
SELECTED_HADOOP_LIBRARIES	Determines the distribution packages that you want to install from the supported packages list. Enter the distribution packages that you want to install, separating multiple packages with a comma.

5. Save the properties file with the name SilentInput.properties in the same folder.
6. Double-click the silentInstallHotFix.bat to apply the hotfix.

   The installer copies the Informatica client files to the installation directory.
7. Complete the post-installation tasks. Verify that the hotfix completed successfully by reviewing the log file or the **Post-Installation Summary** page.

Sample silent input properties

The following example shows the contents of the `SilentInput.properties` file when you apply or roll back the hotfix client in silent mode.

```
############################################################
# Informatica Installer Build Details
# Copyright (c) 1993-2026 Informatica LLC
# This software contains confidential and proprietary
# information of Informatica LLC.
# All Rights Reserved.
############################################################

# Use the following guidelines when editing this file
# * Use this file to install without user interaction.
# * After you create the properties file, save the file with the name
SilentInput.properties
# * Any error condition that leads to failure, such as an invalid
# installation directory, generates a log file in the user home directory.
# For example:  c:\silentErrorLog<time_stamp>.log

############################################################


#######
## *INSTALL_TYPE - Set this value to '0' to apply the hotfix. Set this value to '1' to
roll back the hotfix.

INSTALL_TYPE=0
```

```
# * The USER_INSTALL_DIR variable must point to a valid directory with write
#     permissions enabled.

USER_INSTALL_DIR=c:\Informatica\10.5

#######
# After you create the properties file, save the file with the name
SilentInput.properties and
#     run the silent installer to perform the Informatica client installation.
#######
```

Remove the distribution packages from the backup location

After you apply the hotfix, remove the distribution packages from the backup folder to mitigate the security vulnerabilities.

When you apply the hotfix, all the existing files in the Informatica installation directory are backed up. You need to remove the distribution packages backup from the following location: `<Informatica installation directory>\BACK_FROM_<hotfix version number>\clients\DeveloperClient\hadoop\<distribution package_version>`

The following example shows the backup location for a distribution package when you apply the hotfix: `C:\Informatica\BACK_FROM_3\clients\DeveloperClient\hadoop\EMR_6.4`

Note: The deletion process doesn't remove all files of the distribution packages from the backup folder. Some files might still exist in the following location: `<Informatica installation directory>\BACK_FROM_<hotfix version number>\clients\DeveloperClient\` You can delete these files manually.

Important: When you roll back the hotfix, distribution packages are not restored. You can't enable functionality associated with the Hadoop or Databricks distribution packages in the rolled-back version. To install the distribution packages, contact Informatica Global Customer Support.

Rolling back the client hotfix

You can roll back the hotfix if required. To roll back the hotfix, perform the required prerequisite tasks and then run the installer.

Rolling back the client hotfix in graphical mode

When you run the installer in graphical mode, a console window opens and runs in the background. If you close this window, the rollback stops.

1. Log in to the machine with a system user account. The user account must be the same account used to install the previous version of Informatica services.
2. Close all other applications.
3. To begin the installation, run install.bat from the root directory where you unzipped or untarred the client hotfix installation package.
4. On the Informatica 10.5.11 page, select **Apply hotfix to a version from 10.5 through 10.5.10, or roll back the hotfix**, and then click **Start**.

   The **Installation Type** page appears.
5. Select **Roll back the hotfix** to choose to roll back the hotfix.

6. Verify that all requirements are met before you continue the rollback, and then click **Next**.

   The **Installation Directory** page appears.

7. Enter the absolute path for the directory in which the current version of Informatica clients is installed, and then click **Next**.

   The **Pre-Installation Summary** page appears.

8. Review the installation information, and then click **Install** to roll back the hotfix.

   The installer removes the last hotfix and restores Informatica clients to the previous version.

9. Complete the post-installation tasks. Verify that the rollback completed successfully by reviewing the log file or the **Post-Installation Summary** page.

   Important: When you roll back the hotfix, distribution packages are not restored. You can't enable functionality associated with the Hadoop or Databricks distribution packages in the rolled-back version. To install the distribution packages, contact Informatica Global Customer Support.

Rolling back the client hotfix in silent mode

To roll back the hotfix in silent mode, create the SilentInput.properties file and then run the installer with the file.
Informatica provides a sample properties file, called SilentInput_hotFix.properties, that includes the parameters that the installer requires.

1. Go to the root of the directory that contains the client installation files.
2. Locate the SilentInput_hotFix.properties file.
3. Back up the file before you modify it.
4. Use a text editor to open the file and modify the values. The following table describes the installation properties that you can modify:

Property Name	Description
INSTALL_TYPE	Indicates whether to apply the hotfix or roll back the hotfix. If the value is 0, the installer applies the hotfix to the current Informatica client installation. If the value is 1, the installer rolls back the current hotfix. Set the value to 1 to roll back the hotfix.
USER_INSTALL_DIR	Directory for the Informatica client installation where you want to roll back the hotfix. Enter the absolute path for the directory in which the current version of the Informatica clients is installed.

5. Save the properties file with the name SilentInput.properties in the same folder.
6. To roll back the hotfix on Windows, double-click the silentInstallHotFix.bat file.

   The installer removes the last hotfix and restores the previous version of Informatica clients.

7. Complete the post-installation tasks. Verify that the rollback completed successfully by reviewing the log file or the **Post-Installation Summary** page.

   Important: When you roll back the hotfix, distribution packages are not restored. You can't enable functionality associated with the Hadoop or Databricks distribution packages in the rolled-back version. To install the distribution packages, contact Informatica Global Customer Support.

APPENDIX A

Managing Distribution Packages

This appendix includes the following topics:

- Managing Distribution Packages Overview, 32
- Before You Begin, 32
- Install or Remove Distribution Packages in Console Mode, 33
- Install or Remove Distribution Packages in Silent Mode, 34
- After You Install, 34

Managing Distribution Packages Overview

You can use Integration Package Manager (the package manager) to install and remove distribution packages from the Informatica service and client machines.

A distribution package is a set of distribution binaries that you install within the domain for the following processing requirements:

- To push processing to the Hadoop or Databricks environment.
- To process complex files within the Informatica domain.
- To connect to the Hadoop or Databricks environment when you process within the Informatica domain.

You can install distribution packages if you didn't do so during the upgrade or install process or if you want to add a distribution package. You can remove a distribution package if you want to use a different package or if you installed a package that you don't use.

When you install or remove distribution packages, verify that you perform the operation on all service and client machines.

Before You Begin

Before you run the package manager, perform tasks such as setting environment variables and downloading files.

1. Shut down the Informatica services.

2. Set one of the following environment variables:

Variable	Description
INFA_JDK_HOME	Location of the folder containing the supported Java Development Kit (JDK). Set the INFA_JDK_HOME environment variable in the following scenarios: - Informatica domain is on Windows or Linux - Informatica client
INFA_JRE_HOME	Location of the folder containing the supported Java Runtime Environment (JRE). If the Informatica domain is on AIX, set the INFA_JRE_HOME environment variable.

3. Verify that the user that runs the package manager has read and write permissions on the Informatica installation directory and execute permissions on the executable file.
4. Download the following files from the Informatica Electronic Software Download site:
   - Integration Package Manager
   - Distribution packages
5. Extract the Integration Package Manager ZIP files to a local drive.
6. Copy the ZIP files of distribution packages that you need to the following location: `<Integration Package Manager directory>/source`

   Note: The package manager fails if the ZIP files for distribution packages aren't available in the source directory.

Install or Remove Distribution Packages in Console Mode

You can run the package manager in console mode to install or remove distribution packages.

1. From the package manager directory, run one of the following commands:
   - `./Server.sh console` for Linux or UNIX
   - `Server.bat console` for Windows
   - `Client.bat console` for client

   Note: To run the command on Windows, use the administrator command prompt.
2. Enter the installation directory of the services or client and press **Enter**.
3. Choose the operation type and press **Enter**.
   - Select 1 to remove existing distribution packages.
   - Select 2 to install one or more distribution packages.

   The console lists the distribution packages that you can install or remove.
4. Enter the distribution packages that you want to install or remove, separating multiple packages with a comma, and press **Enter**.
5. Verify the installation or removal status in the package manager log file.

   You can find the log file in the following location: `<Integration Package Manager directory>/IntegrationPackageManager_<date and timestamp>.log`

Install or Remove Distribution Packages in Silent Mode

You can run the package manager in silent mode to install or remove distribution packages. The silent input properties file contains the properties for the package manager to run in silent mode for service and clients. Set the appropriate value for each property in the file.

1. Find the IntegrationPackageManager.properties file in the following location: `<Integration Package Manager directory>/`
2. Edit the properties file in a text editor.

   The following table describes the properties that you can modify:

Property Name	Description
USER_INSTALL_DIR	The installation directory of the service or client.
OPERATION_TYPE	The operation that you want to perform: - Set to DELETE to remove existing distribution packages. - Set to EXTRACT to install one or more distribution packages.
SELECTED_HADOOP_LIBRARIES	Lists the distribution packages and versions. Enter the distribution packages that you want to install or remove. Separate multiple packages with a comma.

3. Save the properties file.
4. From the package manager directory, run one of the following commands:
   - `./Server.sh silent` for Linux or UNIX
   - `Server.bat silent` for Windows
   - `Client.bat silent` for client

   Note: To run the command on Windows, use the administrator command prompt.
5. Verify the installation or removal status in the package manager log file.

   You can find the log file in the following location: `<Integration Package Manager directory>/IntegrationPackageManager_<date and timestamp>.log`

After You Install

To use the distribution packages that are installed using the package manager, configure the property or environment variable in service and client machines.

Configure the Developer Tool

After you install the distribution packages in the Developer tool, update the developerCore.ini file with the installed distribution package.

1. Find the developerCore.ini file in the following location: `<Informatica installation directory>\clients\DeveloperClient`

2. Edit the file to update the following property:

   ```
   -DINFA_HADOOP_DIST_DIR=hadoop\<Hadoop distribution name>_<version>
   ```

   For example,

   ```
   -DINFA_HADOOP_DIST_DIR=hadoop\CDH_7.1
   ```

3. Restart the Developer tool.

Configure Environment Variables

Some adapters require environment variables for the Data Integration Service and Metadata Access Service to access the distribution packages. For more information, see Configure environment variables to process complex files.