Informatica® Axon Data Governance
7.3.8

Upgrade Guide

Informatica Axon Data Governance Upgrade Guide
7.3.8
September 2026

© Copyright Informatica LLC 2013, 2026

This software and documentation are provided only under a separate license agreement containing restrictions on use and disclosure. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC.

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation is subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License.

Portions of this software and/or documentation are subject to copyright held by third parties, including without limitation: Copyright DataDirect Technologies. All rights reserved. Copyright © Sun Microsystems. All rights reserved. Copyright © RSA Security Inc. All Rights Reserved. Copyright © Ordinal Technology Corp. All rights reserved. Copyright © Aandacht c.v. All rights reserved. Copyright Genivia, Inc. All rights reserved. Copyright Isomorphic Software. All rights reserved. Copyright © Meta Integration Technology, Inc. All rights reserved. Copyright © Intalio. All rights reserved. Copyright © Oracle. All rights reserved. Copyright © Adobe Systems Incorporated. All rights reserved. Copyright © DataArt, Inc. All rights reserved. Copyright © ComponentSource. All rights reserved. Copyright © Microsoft Corporation. All rights reserved. Copyright © Rogue Wave Software, Inc. All rights reserved. Copyright © Teradata Corporation. All rights reserved. Copyright © Yahoo! Inc. All rights reserved. Copyright © Glyph & Cog, LLC. All rights reserved. Copyright © Thinkmap, Inc. All rights reserved. Copyright © Clearpace Software Limited. All rights reserved. Copyright © Information Builders, Inc. All rights reserved. Copyright © OSS Nokalva, Inc. All rights reserved. Copyright Edifecs, Inc. All rights reserved. Copyright Cleo Communications, Inc. All rights reserved. Copyright © International Organization for Standardization 1986. All rights reserved. Copyright © ej-technologies GmbH. All rights reserved. Copyright © Jaspersoft Corporation. All rights reserved. Copyright © International Business Machines Corporation. All rights reserved. Copyright © yWorks GmbH. All rights reserved. Copyright © Lucent Technologies. All rights reserved. Copyright © University of Toronto. All rights reserved. Copyright © Daniel Veillard. All rights reserved. Copyright © Unicode, Inc. Copyright IBM Corp. All rights reserved. Copyright © MicroQuill Software Publishing, Inc. All rights reserved. Copyright © PassMark Software Pty Ltd. All rights reserved. Copyright © LogiXML, Inc. All rights reserved. Copyright © 2003-2010 Lorenzi Davide, All rights reserved. Copyright © Red Hat, Inc. All rights reserved. Copyright © The Board of Trustees of the Leland Stanford Junior University. All rights reserved. Copyright © EMC Corporation. All rights reserved. Copyright © Flexera Software. All rights reserved. Copyright © Jinfonet Software. All rights reserved. Copyright © Apple Inc. All rights reserved. Copyright © Telerik Inc. All rights reserved. Copyright © BEA Systems. All rights reserved. Copyright © PDFlib GmbH. All rights reserved. Copyright © Orientation in Objects GmbH. All rights reserved. Copyright © Tanuki Software, Ltd. All rights reserved. Copyright © Ricebridge. All rights reserved. Copyright © Sencha, Inc. All rights reserved. Copyright © Scalable Systems, Inc. All rights reserved. Copyright © jQWidgets. All rights reserved. Copyright © Tableau Software, Inc. All rights reserved. Copyright© MaxMind, Inc. All Rights Reserved. Copyright © TMate Software s.r.o. All rights reserved. Copyright © MapR Technologies Inc. All rights reserved. Copyright © Amazon Corporate LLC. All rights reserved. Copyright © Highsoft. All rights reserved. Copyright © Python Software Foundation. All rights reserved. Copyright © BeOpen.com. All rights reserved. Copyright © CNRI. All rights reserved.

This product includes software developed by the Apache Software Foundation (http://www.apache.org/), and/or other software which is licensed under various versions of the Apache License (the "License"). You may obtain a copy of these Licenses at http://www.apache.org/licenses/. Unless required by applicable law or agreed to in writing, software distributed under these Licenses is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the Licenses for the specific language governing permissions and limitations under the Licenses.

This product includes software which was developed by Mozilla (http://www.mozilla.org/), software copyright The JBoss Group, LLC, all rights reserved; software copyright © 1999-2006 by Bruno Lowagie and Paulo Soares and other software which is licensed under various versions of the GNU Lesser General Public License Agreement, which may be found at http:// www.gnu.org/licenses/lgpl.html. The materials are provided free of charge by Informatica, "as-is", without warranty of any kind, either express or implied, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

The product includes ACE(TM) and TAO(TM) software copyrighted by Douglas C. Schmidt and his research group at Washington University, University of California, Irvine, and Vanderbilt University, Copyright (©) 1993-2006, all rights reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (copyright The OpenSSL Project. All Rights Reserved) and redistribution of this software is subject to terms available at http://www.openssl.org and http://www.openssl.org/source/license.html.

This product includes Curl software which is Copyright 1996-2013, Daniel Stenberg, <daniel@haxx.se>. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://curl.haxx.se/docs/copyright.html. Permission to use, copy, modify, and distribute this software for any purpose with or without fee is hereby granted, provided that the above copyright notice and this permission notice appear in all copies.

The product includes software copyright 2001-2005 (©) MetaStuff, Ltd. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://www.dom4j.org/ license.html.

The product includes software copyright © 2004-2007, The Dojo Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http://dojotoolkit.org/license.

This product includes ICU software which is copyright International Business Machines Corporation and others. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://source.icu-project.org/repos/icu/icu/trunk/license.html.

This product includes software copyright © 1996-2006 Per Bothner. All rights reserved. Your right to use such materials is set forth in the license which may be found at http:// www.gnu.org/software/ kawa/Software-License.html.

This product includes OSSP UUID software which is Copyright © 2002 Ralf S. Engelschall, Copyright © 2002 The OSSP Project Copyright © 2002 Cable & Wireless Deutschland. Permissions and limitations regarding this software are subject to terms available at http://www.opensource.org/licenses/mit-license.php.

This product includes software developed by Boost (http://www.boost.org/) or under the Boost software license. Permissions and limitations regarding this software are subject to terms available at http:/ /www.boost.org/LICENSE_1_0.txt.

This product includes software copyright © 1997-2007 University of Cambridge. Permissions and limitations regarding this software are subject to terms available at http:// www.pcre.org/license.txt.

This product includes software copyright © 2007 The Eclipse Foundation. All Rights Reserved. Permissions and limitations regarding this software are subject to terms available at http:// www.eclipse.org/org/documents/epl-v10.php and at http://www.eclipse.org/org/documents/edl-v10.php.

This product includes software licensed under the terms at http://www.tcl.tk/software/tcltk/license.html, http://www.bosrup.com/web/overlib/?License, http:// www.stlport.org/doc/ license.html, http://asm.ow2.org/license.html, http://www.cryptix.org/LICENSE.TXT, http://hsqldb.org/web/hsqlLicense.html, http:// httpunit.sourceforge.net/doc/ license.html, http://jung.sourceforge.net/license.txt , http://www.gzip.org/zlib/zlib_license.html, http://www.openldap.org/software/ release/license.html, http://www.libssh2.org, http://slf4j.org/license.html, http://www.sente.ch/software/OpenSourceLicense.html, http://fusesource.com/downloads/ license-agreements/fuse-message-broker-v-5-3- license-agreement; http://antlr.org/license.html; http://aopalliance.sourceforge.net/; http://www.bouncycastle.org/ licence.html; http://www.jgraph.com/jgraphdownload.html; http://www.jcraft.com/jsch/LICENSE.txt; http://jotm.objectweb.org/bsd_license.html; . http://www.w3.org/ Consortium/Legal/2002/copyright-software-20021231; http://www.slf4j.org/license.html; http://nanoxml.sourceforge.net/orig/copyright.html; http://www.json.org/ license.html; http://forge.ow2.org/projects/javaservice/, http://www.postgresql.org/about/licence.html, http://www.sqlite.org/copyright.html, http://www.tcl.tk/ software/tcltk/license.html, http://www.jaxen.org/faq.html, http://www.jdom.org/docs/faq.html, http://www.slf4j.org/license.html; http://www.iodbc.org/dataspace/ iodbc/wiki/iODBC/License; http://www.keplerproject.org/md5/license.html; http://www.toedter.com/en/jcalendar/license.html; http://www.edankert.com/bounce/

index.html; http://www.net-snmp.org/about/license.html; http://www.openmdx.org/#FAQ; http://www.php.net/license/3_01.txt; http://srp.stanford.edu/license.txt; http://www.schneier.com/blowfish.html; http://www.jmock.org/license.html; http://xsom.java.net; http://benalman.com/about/license/; https://github.com/CreateJS/EaselJS/blob/master/src/easeljs/display/Bitmap.js; http://www.h2database.com/html/license.html#summary; http://jsoncpp.sourceforge.net/LICENSE; http://jdbc.postgresql.org/license.html; http://protobuf.googlecode.com/svn/trunk/src/google/protobuf/descriptor.proto; https://github.com/rantav/hector/blob/master/LICENSE; http://web.mit.edu/Kerberos/krb5-current/doc/mitK5license.html; http://jibx.sourceforge.net/jibx-license.html; https://github.com/lyokato/libgeohash/blob/master/LICENSE; https://github.com/hjiang/jsonxx/blob/master/LICENSE; https://code.google.com/p/lz4/; https://github.com/jedisct1/libsodium/blob/master/LICENSE; http://one-jar.sourceforge.net/index.php?page=documents&file=license; https://github.com/EsotericSoftware/kryo/blob/master/license.txt; http://www.scala-lang.org/license.html; https://github.com/tinkerpop/blueprints/blob/master/LICENSE.txt; http://gee.cs.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html; https://aws.amazon.com/asl/; https://github.com/twbs/bootstrap/blob/master/LICENSE; https://sourceforge.net/p/xmlunit/code/HEAD/tree/trunk/LICENSE.txt; https://github.com/documentcloud/underscore-contrib/blob/master/LICENSE, and https://github.com/apache/hbase/blob/master/LICENSE.txt.

This product includes software licensed under the Academic Free License (http://www.opensource.org/licenses/afl-3.0.php), the Common Development and Distribution License (http://www.opensource.org/licenses/cddl1.php) the Common Public License (http://www.opensource.org/licenses/cpl1.0.php), the Sun Binary Code License Agreement Supplemental License Terms, the BSD License (http:// www.opensource.org/licenses/bsd-license.php), the new BSD License (http://opensource.org/licenses/BSD-3-Clause), the MIT License (http://www.opensource.org/licenses/mit-license.php), the Artistic License (http://www.opensource.org/licenses/artistic-license-1.0) and the Initial Developer's Public License Version 1.0 (http://www.firebirdsql.org/en/initial-developer-s-public-license-version-1-0/).

This product includes software copyright © 2003-2006 Joe Walnes, 2006-2007 XStream Committers. All rights reserved. Permissions and limitations regarding this software are subject to terms available at http://xstream.codehaus.org/license.html. This product includes software developed by the Indiana University Extreme! Lab. For further information please visit http://www.extreme.indiana.edu/.

This product includes software Copyright (c) 2013 Frank Balluffi and Markus Moeller. All rights reserved. Permissions and limitations regarding this software are subject to terms of the MIT license.

See patents at https://www.informatica.com/legal/patents.html.

DISCLAIMER: Informatica LLC provides this documentation "as is" without warranty of any kind, either express or implied, including, but not limited to, the implied warranties of noninfringement, merchantability, or use for a particular purpose. Informatica LLC does not warrant that this software or documentation is error free. The information provided in this software or documentation may include technical inaccuracies or typographical errors. The information in this software and documentation is subject to change at any time without notice.

NOTICES

This Informatica product (the "Software") includes certain drivers (the "DataDirect Drivers") from DataDirect Technologies, an operating company of Progress Software Corporation ("DataDirect") which are subject to the following terms and conditions:

1. THE DATADIRECT DRIVERS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.
2. IN NO EVENT WILL DATADIRECT OR ITS THIRD PARTY SUPPLIERS BE LIABLE TO THE END-USER CUSTOMER FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHER DAMAGES ARISING OUT OF THE USE OF THE ODBC DRIVERS, WHETHER OR NOT INFORMED OF THE POSSIBILITIES OF DAMAGES IN ADVANCE. THESE LIMITATIONS APPLY TO ALL CAUSES OF ACTION, INCLUDING, WITHOUT LIMITATION, BREACH OF CONTRACT, BREACH OF WARRANTY, NEGLIGENCE, STRICT LIABILITY, MISREPRESENTATION AND OTHER TORTS.

The information in this documentation is subject to change without notice. If you find any problems in this documentation, report them to us at infa_documentation@informatica.com.

Informatica products are warranted according to the terms and conditions of the agreements under which they are provided. INFORMATICA PROVIDES THE INFORMATION IN THIS DOCUMENT "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING WITHOUT ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND ANY WARRANTY OR CONDITION OF NON-INFRINGEMENT.

Publication Date: 2026-09-22

Table of Contents

Preface 6

Informatica Resources 6

- Informatica Network 6
- Informatica Knowledge Base 6
- Informatica Documentation 6
- Informatica Product Availability Matrices 7
- Informatica Marketplace 7
- Informatica Global Customer Support 7

Chapter 1: Axon Upgrade Overview 8

Axon Upgrade Overview 8

Axon Upgrade Paths 8

Axon Agent Upgrade Path 9

Chapter 2: Before You Upgrade 11

Before You Upgrade Overview 11

Verify System Requirements 11

Update Cryptogaphic Policy 12

Create an Axon Administrator User 12

Back Up Database 12

Validate YML Files 13

Configure Port Access 13

Verify the Axon License Key 13

Download Compatible Versions of Elasticsearch and Logstash Files 14

Create Directories 14

Extract the Installer Files 14

Run the Validation Utility 15

Identify and Fix Inconsistent Data 15

- Run the Data Health Check Utility 16

Chapter 3: Upgrade Axon and Axon Agent 17

Upgrade Axon and the Axon Agent Overview 17

Running the Installer File 18

Upgrading Axon in Console Mode 18

Upgrading the Axon Agent in Console Mode 20

Upgrading Axon or the Axon Agent in Silent Mode 21

Chapter 4: After You Upgrade 22

Apache Log4j RCE Vulnerabilities for Axon 22

After You Upgrade Overview 23

Configure SSL Certificates for the Message Broker Service. . . . 23
Check the Status of the Services. . . . 23
Verify SSL Details. . . . 25
Update SSO Settings in the IDP. . . . 25
Configure Axon URL for Enterprise Data Catalog. . . . 26
Configure Axon with Operating System Profiles Enabled User for Data Integration Service. . . . 26
Update Enterprise Data Catalog Field Types. . . . 27
Configure the Axon Agent. . . . 27
Disable or Re-enable Segmentation. . . . 27
Migrate Scheduled Jobs. . . . 28
Configure Email Notifications. . . . 28
Create a Daily Email Notification Schedule. . . . 29
Create a Weekly Email Notification Schedule. . . . 29
Create a Monthly Email Notification Schedule. . . . 30
Display Reference Number for Data Sets and Attributes. . . . 30
Clear Cached Browser Images. . . . 31
Log In To Axon. . . . 31
Manage Saved Searches. . . . 32

Chapter 5: Monitor and Troubleshoot. . . . 33

Monitor Scheduled Jobs. . . . 33
Troubleshooting. . . . 33
Axon Does Not Load in the Browser. . . . 33
Incorrect Host Name. . . . 35
Validation Utility Errors. . . . 35
Cannot Log In to Axon. . . . 35
Warnings in Configure.log Files. . . . 36
Revert to an Earlier Version of Axon. . . . 36

Index. . . . 37

Preface

Follow the instructions in the *Axon Data Governance Upgrade Guide* to upgrade Axon from a previous version.

This guide assumes that you have knowledge of the Axon installation process, and that you are familiar with the interface requirements for your supporting applications.

Informatica Resources

Informatica provides you with a range of product resources through the Informatica Network and other online portals. Use the resources to get the most from your Informatica products and solutions and to learn from other Informatica users and subject matter experts.

Informatica Network

The Informatica Network is the gateway to many resources, including the Informatica Knowledge Base and Informatica Global Customer Support. To enter the Informatica Network, visit https://network.informatica.com.

As an Informatica Network member, you have the following options:

- Search the Knowledge Base for product resources.
- View product availability information.
- Create and review your support cases.
- Find your local Informatica User Group Network and collaborate with your peers.

Informatica Knowledge Base

Use the Informatica Knowledge Base to find product resources such as how-to articles, best practices, video tutorials, and answers to frequently asked questions.

To search the Knowledge Base, visit https://search.informatica.com. If you have questions, comments, or ideas about the Knowledge Base, contact the Informatica Knowledge Base team at KB_Feedback@informatica.com.

Informatica Documentation

Use the Informatica Documentation Portal to explore an extensive library of documentation for current and recent product releases. To explore the Documentation Portal, visit https://docs.informatica.com.

If you have questions, comments, or ideas about the product documentation, contact the Informatica Documentation team at infa_documentation@informatica.com.

Informatica Product Availability Matrices

Product Availability Matrices (PAMs) indicate the versions of the operating systems, databases, and types of data sources and targets that a product release supports. You can browse the Informatica PAMs at https://network.informatica.com/community/informatica-network/product-availability-matrices.

Informatica Marketplace

The Informatica Marketplace is a forum where you can find solutions that extend and enhance your Informatica implementations. Leverage any of the hundreds of solutions from Informatica developers and partners on the Marketplace to improve your productivity and speed up time to implementation on your projects. You can find the Informatica Marketplace at https://marketplace.informatica.com.

Informatica Global Customer Support

You can contact a Global Support Center by telephone or through the Informatica Network.

To find your local Informatica Global Customer Support telephone number, visit the Informatica website at the following link:
https://www.informatica.com/services-and-training/customer-success-services/contact-us.html.

To find online support resources on the Informatica Network, visit https://network.informatica.com and select the Support option.

CHAPTER 1

Axon Upgrade Overview

This chapter includes the following topics:

- Axon Upgrade Overview, 8
- Axon Upgrade Paths, 8
- Axon Agent Upgrade Path, 9

Axon Upgrade Overview

When you upgrade Axon Data Governance, you install a new version of Axon on a machine that contains an older version. After you upgrade, the new Axon version replaces the old version on the same machine. This section describes the versions and components of Axon that you can upgrade from a previous version, and the Linux distributions that support Axon upgrade.

When you upgrade Axon to the latest version, you must also upgrade the Axon Agent to the latest version for compatibility.

To see the new features and enhancements in the upgraded version, refer to the *Axon Data Governance What's New and Changed* in the *Informatica Documentation Portal*. If you upgrade Axon to 7.3.8 from a release earlier than version 7.3.1.2, refer to the earlier versions in the *Axon Data Governance What's New and Changed* to see the new features and changes in the interim releases.

Axon Upgrade Paths

Supported Axon Versions for Upgrade

You can upgrade to Axon version 7.3.8 if you have one of the following Axon versions installed on your system:

- Axon 7.3.7
- Axon 7.3.6
- Axon 7.3.5 and its service packs

The following table lists the upgrade paths to upgrade to Axon 7.3.8

Current Version	Upgrade Path
7.3.4	You can first upgrade to Axon 7.3.7. You can then upgrade to Axon 7.3.8.
7.3.3	You can first upgrade to Axon 7.3.6. You can then upgrade to Axon 7.3.8.
7.3.2	You can first upgrade to Axon 7.3.5. You can then upgrade to Axon 7.3.8.
7.3.1	You can first upgrade to Axon 7.3.3. Then upgrade to 7.3.6. You can then upgrade to Axon 7.3.8.
7.3 including any service pack, or cumulative patch	You can first upgrade to Axon 7.3.2. Then upgrade to 7.3.5. You can then upgrade to Axon 7.3.8.
7.2 including any hotfix, service pack, or cumulative patch	You can first upgrade to Axon 7.3.2. Then upgrade to 7.3.5. You can then upgrade to Axon 7.3.8.
7.1 including any hotfix, service pack, or cumulative patch	You can first upgrade to Axon 7.3.1. Then upgrade to 7.3.3. Then upgrade to 7.3.6. You can then upgrade to Axon 7.3.8.
7.0 including any hotfix, service pack, or cumulative patch	You can first upgrade to Axon 7.3.1. Then upgrade to 7.3.3. Then upgrade to 7.3.6. You can then upgrade to Axon 7.3.8.

Axon Components

The installer file upgrades only the core Axon component. If you want to connect Axon to other Informatica products, you must upgrade the other products to ensure that they work with Axon version 7.3.8. To see the versions of other Informatica products that are supported by Axon version 7.3.8, see the Product Availability Matrix on the Informatica Network.

Axon Agent Upgrade Path

Supported Axon Agent Versions for Upgrade

You can upgrade the Axon Agent to version 7.3.8 if your existing installation meets the following requirements:

- You have one of the following Axon Agent versions installed on your system:
  - Axon 7.3.7
  - Axon 7.3.6
  - Axon 7.3.5 and its service packs
- You have configured Axon to connect to one of the following versions of Informatica Data Quality:
  - Informatica Data Quality 10.5.11
  - Informatica Data Quality 10.5.10
  - Informatica Data Quality 10.5.9
  - Informatica Data Quality 10.5.8

- Informatica Data Quality 10.5.7
- Informatica Data Quality 10.5.6

- You have enabled data quality rule automation.

For more information on data quality rule automation, see the *Automate Data Quality Rules* chapter in the *Axon Data Governance User Guide*.

Note: The 7.3.8 Axon installer supports 10.5.11 Axon Agent.

Unsupported Axon Agent Versions for Upgrade

You cannot upgrade the Axon Agent if you have Axon Agent version 6.3 or earlier.

Uninstall or shut down your existing version of the Axon Agent, and perform a fresh installation of Axon Agent 7.3.8.

For more information on uninstalling and installing the Axon Agent, see the *Axon Data GovernanceInstallation Guide*.

CHAPTER 2

Before You Upgrade

This chapter includes the following topics:

- Before You Upgrade Overview, 11
- Verify System Requirements, 11
- Update Cryptogaphic Policy, 12
- Create an Axon Administrator User, 12
- Back Up Database, 12
- Validate YML Files, 13
- Configure Port Access, 13
- Verify the Axon License Key, 13
- Download Compatible Versions of Elasticsearch and Logstash Files, 14
- Create Directories, 14
- Extract the Installer Files, 14
- Run the Validation Utility, 15
- Identify and Fix Inconsistent Data, 15

Before You Upgrade Overview

Before you upgrade your Axon installation, you must prepare your system for the upgrade. You must back up your customization, and upgrade some RPM components.

Verify System Requirements

Verify that the system where you plan to upgrade Axon meets the minimum requirements for the installation process. If you want Axon to use the default ports for the services, make sure that the ports are available before you start the upgrade process.

For more information, see the *System Requirements* topic in the *Axon Data Governance Installation Guide*.

Update Cryptogaphic Policy

Before you install Axon version 7.3.8 on a Red Hat Enterprise Linux (RHEL) version 9.x instance with Federal Information Processing Standards (FIPS) mode enabled and OpenSSL 3.x, complete the following prerequisites:

1. To change the system-wide cryptographic policy, run the following command in a Linux terminal as a root user with Administrator privileges:
   `update-crypto-policies --set FIPS:NO-ENFORCE-EMS`
2. Restart Axon to apply the changes.

Create an Axon Administrator User

Effective in Axon version 5.3, a non-root user in Linux installs and manages Axon. If you are upgrading Axon from version 5.2 or an earlier version, the root user in Linux must create a non-root user and provide the user with the necessary permissions. The non-root user is called the **Axon Administrator** in this guide. Perform the following steps to create the Axon Administrator user.

1. Create a non-root user in the Linux environment.

   Note: This user is a non-root user that must have read and write permissions for the directory where the upgraded Axon files are located. Do not enter the following names for the non-root user: `axon`, `axon_bulkupload`, `axon_changerequest`, `axon_data`, `axon_docupload`, `axon_notification`, `camunda`, `postgres`, `unison`.
2. Create a home directory to upgrade Axon. Provide the non-root user with read and write permission on the home directory.

If you upgrade Axon from version 5.2 or an earlier version, the root user or sudo user must initiate the Axon upgrade, and specify the non-root user during the upgrade process. The Axon installer places the Axon upgrade files in the home directory of the non-root user.

If you upgrade from Axon version 5.3, the Axon Administrator must initiate the upgrade process.

After upgrade, all subsequent tasks in Linux must be done by the Axon Administrator inside the home directory.

Back Up Database

Before you upgrade Axon, back up the PostgreSQL database.

You must back up the database as the Axon Administrator. The Axon Administrator is a non-root user in Linux that manages Axon.

Backup Local PostgreSQL Databases

To back up the local PostgreSQL database, perform the following steps:

1. Go to the `<INSTALLATION_DIR>/scripts` directory and run the following command to back up the database:

   ```
   sh axon_db_backup.sh <BACKUP_DESTINATION_DIR>
   ```

2. Go to the backup destination directory to verify that the database backup file is created. The database backup is an SQL file with the timestamp: `<BACKUP_DESTINATION_DIR>/<backup_sql_file>`
   For example, the backup file name can be in the following format: `<BACKUP_DESTINATION_DIR>/postgres_2018_06_24_025744.sql`

Backup External PostgreSQL Databases

If you have deployed the PostgreSQL database on an external node, Axon automatically backs up the PostgreSQL database according to the predefined schedule. The backup scheduler keeps the backups at the following location:

```
<external_directory_PostgreSQL_path>/db_backup/postgres_backup
```

To back up the external PostgreSQL database, perform the following steps:

1. Log in to the external node, and go to the directory where the PostgreSQL database is deployed.
2. Run the following command to back up the database:

   ```
   sh axon_db_backup_external.sh
   ```
3. Go to the `<external_directory_PostgreSQL_path>/db_backup` directory to verify that the database backup file is created.

Note: The PostgreSQL database backups on external nodes are not deleted if they are more than 10 days old. You need to manually clean up the database backups if you have space constraints.

Validate YML Files

Ensure that the `parameters.ymlc` file is valid. You can use any online YML validator to validate this file. If this file is not valid, the Axon upgrade might fail.

The `parameters.ymlc` file is available in the following location: `<INSTALLATION_DIRECTORY>/axonhome/axon/app/config`

Configure Port Access

Configure your firewall to allow the Axon installer and the application that it installs to access the external ports. Optionally, disable the firewall.

Verify the Axon License Key

Before you upgrade Axon, verify that you have a valid license key. Contact Informatica Global Customer Support to obtain a license key. You must provide the location of the license key file during the upgrade process.

Download Compatible Versions of Elasticsearch and Logstash Files

Effective from Axon version 7.3.4, Informatica does not include Elasticsearch and Logstash files into its upgrade package.

Before you upgrade Axon, download the Elasticsearch and Logstash supported file versions 9.3.2 or later from the Elasticsearch and Logstash official websites. For more information, see the *Axon Data Governance 7.3.8 Installation Guide*.

Create Directories

Before you run the installer file, create the following directories within the home directory of the Axon Administrator. Make sure that the Axon Administrator has read and write permissions on the home directory.

1. Create an upgrade directory. When you run the Axon installer file, the installer creates a home directory inside this upgrade directory. The installer file then upgrades Axon in the home directory.

   The upgrade directory is referred to as `<UPGRADE_DIRECTORY>` in this document.
2. Create a temporary directory for the installer binaries and extract the installer files to this directory. Make sure that you download the installer zip file to a local directory or a shared network drive that is mapped on your machine. You can then securely copy the installer file to this temporary directory and extract the installer files. The installer binaries contain the core Axon components and services that are installed by the installer file.

   This temporary directory is referred to as `<SOURCE_BINARIES_DIRECTORY>` in this document
3. If you plan to integrate Axon with Informatica Data Quality, create a directory for the Axon installer file to install the Axon Agent.

Extract the Installer Files

Before you upgrade Axon, you must first extract the contents of the installer file to the `<SOURCE_BINARIES_DIRECTORY>` directory. This is a temporary location that holds the files that are used to upgrade Axon.

The installer files are compressed and distributed as a .tar file. Use an extraction utility to extract the installer files to the `<SOURCE_BINARIES_DIRECTORY>` directory on your machine. When you extract the file, verify that the extraction utility also extracts empty folders.

Run the Validation Utility

Informatica provides a validation utility that you can run to verify if your system meets the requirements to run the Axon upgrade installer file.

Perform the following steps to run the validation utility:

1. Download the validation utility from the following URL:
   https://download.informatica.com/infa/downloads/Axon/installer-prerequisite-tester_7.3.8.zip

   Note: Use the customer login credentials provided by Informatica. Contact Informatica Global Customer Support for assistance.
2. Copy the `installer-prerequisite-tester_7.3.8.zip` file to your Linux machine.
3. Provide the Linux user with execute permission on the `installer-prerequisite-tester_7.3.8.zip` file.
4. Run the following command to extract the contents of the `installer-prerequisite-tester_7.3.8.zip` file:

   ```
   unzip installer-prerequisite-tester_7.3.8.zip
   ```
5. Run the following command to execute the validation script file:

   ```
   sh validate.sh
   ```

The validation utility checks if your system meets the following requirements:

- System RPM requirements
- Operating System requirements
- Internal RPM requirements

The validation utility displays status messages when it runs. Follow the instructions given in the messages before you proceed with running the Axon upgrade installer file. After you run the validation utility, you can also verify the log directory for log messages. This log directory is present in the location where you extracted the `installer-prerequisite-tester_7.3.8.zip` file.

Identify and Fix Inconsistent Data

Axon provides a Data Health Check Utility that you can use to check the consistency of your data before you upgrade to a new version.

Perform a data health check to identify inconsistent data. Inconsistent data refers to data that may not be synchronized between the objects database and the graph database. If you upgrade Axon while keeping inconsistent data, the upgrade will fail because the data transformation won't happen properly. To ensure a smooth upgrade, fix the inconsistent data before you begin the upgrade.

Note: To avoid the Data Health Check script failures, do not attempt any create, update, or delete operations while the Data Health Check Utility runs.

Run the Data Health Check Utility

Perform the following steps to run the Data Health Check Utility:

1. Download the Data Health Check Utility from the following URL:
   `https://download.informatica.com/infa/downloads/Axon/Axon_Data_Health_Check_7.3.8.tar`

   Note: Use the customer login credentials provided by Informatica. Contact Informatica Global Customer Support for assistance.
2. Copy the *Axon_Data_Health_Check_7.3.8.tar* file to the Linux machine.
3. Navigate to the directory where you have copied the file, and run the following command to extract the contents of the file:
   `tar -xvf Axon_Data_Health_Check_7.3.8.tar`
4. Run the following script to run the Data Health Check Utility:
   `sh dataHealthCheck.sh`

   Wait until the data health check is complete.
5. After the data health check completes, open the following log file to check for the inconsistent data:
   `<INSTALLATION_DIR>/axonhome/dataHealthCheck-<timestamp>.log`
6. Fix the errors in the source system of the data.

After you fix the data, you can proceed to upgrade Axon.

CHAPTER 3

Upgrade Axon and Axon Agent

This chapter includes the following topics:

- Upgrade Axon and the Axon Agent Overview, 17
- Running the Installer File, 18
- Upgrading Axon in Console Mode, 18
- Upgrading the Axon Agent in Console Mode, 20
- Upgrading Axon or the Axon Agent in Silent Mode, 21

Upgrade Axon and the Axon Agent Overview

To upgrade Axon and the Axon Agent, run the Axon installer file and select the upgrade option. Before the upgrade begins, the installer stops the Axon application and all running services. After the upgrade is completed, the installer restarts the Axon application and the services.

To shutdown the services of the previous Axon versions, run the following command in the Linux Environment:

```
sh <Previous_version_Axon_Install_dir>/bin/shutdown.sh
```

Run the following command to check for orphan processes:

```
ps -ef | grep axon
```

Run the following command to stop the orphan processes:

```
kill -9 <pid>
```

If Axon is deployed on an external RDS database instance, the upgrade will be performed on the same external RDS instance. Before you upgrade, ensure that you back up the external databases, such as Microsoft Azure Database for PostgreSQL and Amazon RDS.

Note: Effective in version 7.3.3 or later, the Microsoft Azure PostgreSQL Single Server is deprecated in the upgrade installer. When you upgrade to version 7.3.3 or later, Informatica recommends that you use Microsoft Azure PostgreSQL Flexible Server. If required, you can use the previous Microsoft Azure PostgreSQL Single Server.

Note: Begin the upgrade process during a maintenance period when very few users are using Axon and disruption is minimal. Once you start the Axon upgrade, make sure that you complete the upgrade process without interruptions.

Running the Installer File

Informatica provides an installer file to upgrade Axon Data Governance or the Axon Agent. You can run only one instance of Axon on a machine.

You can upgrade Axon or the Axon Agent in one of the following ways:

- Console mode. Interact with the installer wizard to configure the upgrade parameters. After you run the installer file, the interactive wizard prompts you to enter the parameters at each step of the upgrade.
- Silent mode. Upgrade without user intervention. Enter the upgrade parameters in the installer properties file before you start the upgrade. After you have prepared the installer properties file, run the installer file. The installer reads the parameters from the properties file, runs in the background, and upgrades Axon or the Axon Agent.

Upgrading Axon in Console Mode

Upgrade Axon using a console. When you run the installer file, the words `Quit`, `Back`, and `Help` are reserved words. Do not use them as input text. Enter `help` for getting additional context-sensitive information during the installation process. Enter `Quit` to exit the upgrade process at any point in time.

The Axon Administrator must initiate the upgrade process. The Axon Administrator is the non-root user in Linux that installs and manages Axon. To upgrade Axon, run the `install.sh` file, and then select option 1 **Install only Axon**. The `install.sh` file is located in the temporary directory for installer binaries, `<SOURCE_BINARIES_DIRECTORY>`, where you untarred the installer file.

Upgrade Steps

The following section describes the steps to upgrade Axon.

Note: When you upgrade Axon, the installer prompts you to enter the port numbers of the Axon services. At each prompt, press the **Enter** key to proceed with the default port. If you want to enter custom port numbers, make sure that the port numbers are in the range of 1025 to 65535.

Step 1 of 8

Review the information on the screen, and type in **2** to upgrade your Axon installation.

Step 2 of 8

Enter the following information:

- Existing Axon installation directory
- Directory where you want to place the upgraded Axon files. Press the **Enter** key to proceed with the default directory.

  Note: The new Axon upgrade directory that you specify must be a location that was not used for any previous Axon installation or upgrade.
- Path to the latest Axon license key file. The Axon Administrator must have read and write permissions on the directory of the Axon license file.
- Path to the Elasticsearch file. Download the supported Elasticsearch version 9.3.2 from the Elasticsearch official website.
- Path to the Logstash file. Download the supported Logstash version 9.3.2 from the Logstash official website.

- Path to your cryptographic private key. Press the **Enter** key to proceed with the default key that the Axon installer provides. The installer uses this key to encrypt the passwords that you type during installation.

  Note: The private key file must have a minimum of 16 characters.

- The Axon Administrator that installs and manages Axon. Enter the Axon Administrator if you started the upgrade as a root user or sudo user.

  Note: This user is a non-root user that must have read and write permissions for the directory where the upgraded Axon files are located. Do not enter the following names for the non-root user: `axon`, `axon_bulkupload`, `axon_changerequest`, `axon_data`, `axon_docupload`, `axon_notification`, `camunda`, `postgres`, `unison`.

- Option to allow the Axon SuperAdmin to view log files in the Axon Admin Panel. If you enable this option now, you can disable it any time after upgrade is complete.

  Note: If you enable this option, make sure that the Linux system has 32 GB of memory and 10 CPU cores. For more information on the requirements to run Axon, see the *Axon Data Governance Installation Guide*.

- Option to upgrade Axon using a proxy host name.

- If you have deployed the PostgreSQL database on an external node in the previous version, then during upgrade the specific version directory is created and the PostgreSQL database is deployed on the external node using the same authentication details without displaying the parameters.

  Note: Effective in version 7.3.3 or later, the Microsoft Azure PostgreSQL Single Server is deprecated in the upgrade installer. When you upgrade to version 7.3.3 or later, Informatica recommends that you use Microsoft Azure PostgreSQL Flexible Server. If required, you can use the previous Microsoft Azure PostgreSQL Single Server.

- Option to enter the port numbers for the additional microservices if any. Press the **Enter** key to proceed with the default port numbers.

- Enter the HTTP or HTTPS port. You can either continue with the existing default port, or change the port.

The installer performs a check to validate the system requirements and verifies whether the license key file exists in the directory location that you provided.

Type **1** to continue with the upgrade.

Note: There are no step 3, step 4 of 8 when you upgrade Axon.

Step 5 of 8

Review the pre-installation summary information.

Type **1** to stop the upgrade process and back up your customization settings. You can restart the upgrade process after the backup is complete.

Type **2** to continue with the upgrade.

Step 6 of 8

Review the upgrade progress.

Note: The Axon upgrade process might take some time to complete. To track the progress, view the `<UPGRADE_DIRECTORY>/Configure.log` file.

Note: In step 7 of 8, you can configure advanced settings when you install Axon. This step is not required to upgrade Axon. For more information, see the *Axon Data Governance Installation Guide*.

Step 8 of 8

Review the upgrade summary.

Press the **Enter** key to complete the upgrade.

Upgrading the Axon Agent in Console Mode

Upgrade the Axon Agent using a console. When you run the installer file, the words `Quit`, `Back`, and `Help` are reserved words. Do not use them as input text. Enter `help` for getting additional context-sensitive information during the installation process. Enter `Quit` to exit the upgrade process at any point in time.

The Axon Administrator must run the installer file to initiate the upgrade process. The Axon Administrator is the non-root user in Linux that installs and manages Axon. The installer file is located in the temporary directory for installer binaries, `<SOURCE_BINARIES_DIRECTORY>`, where you untarred the installer file.

Upgrade Steps

To upgrade Axon, go to the `<SOURCE_BINARIES_DIRECTORY>` directory, and run the `install.sh` file. Select option 2 **Install only the Axon Agent**.

Step 1 of 9

Review the information on the screen, and type in **2** to upgrade your Axon installation. Press the **Enter** key to continue.

Step 2 of 9

Enter the following information:

- Existing Axon Agent installation directory.
- Directory where you want to place the upgraded Axon Agent files. Press the **Enter** key to proceed with the default directory.

  Note: The new Axon Agent upgrade directory that you specify must be a location that was not used for any previous Axon or Axon Agent installations or upgrades.
- Version of the Informatica domain to which you want to connect the Axon Agent.

The installer performs a check to validate the system requirements.

Step 4 of 9

Review the pre-installation summary information. Press the **Enter** key to proceed with the upgrade.

Step 5 of 9

Review the upgrade progress.

Step 9 of 9

Review the installation summary to verify that all components are successfully installed.

Press the **Enter** key to complete the installation.

Note: When you upgrade Axon, the upgrade procedure does not have steps 3, 6, 7 and 8.

Upgrading Axon or the Axon Agent in Silent Mode

If you want to upgrade Axon or the Axon Agent without user intervention, choose to upgrade in silent mode

Start the upgrade process as the Axon Administrator. The Axon Administrator is the non-root user in Linux that installs and manages Axon. Before you start the upgrade, make sure that you enter the Axon Administrator user name in the `USER` parameter of the `<SOURCE_BINARIES_DIRECTORY>/SilentInput.properties` and `<SOURCE_BINARIES_DIRECTORY>/SilentInput_AxonAgent.properties` files.

1. Go to the `<SOURCE_BINARIES_DIRECTORY>` directory, and enter the Axon upgrade parameters in the `SilentInput.properties` file.
2. If you want to upgrade the Axon Agent, go to the `<SOURCE_BINARIES_DIRECTORY>` directory, and enter the Axon Agent upgrade parameters in the `SilentInput_AxonAgent.properties` file.
3. Log in to the machine as the Axon Administrator.
4. Go to the `<SOURCE_BINARIES_DIRECTORY>` directory, and run the `silentinstall.sh` file.

   The installer upgrades Axon and displays a message when the upgrade is complete. If you choose to upgrade the Axon Agent, the installer displays a message when the Axon Agent upgrade is complete.
5. Optionally, to view the status of the Axon upgrade, open the `<INSTALLATION_DIRECTORY>/Configure.log` file. If the upgrade fails, open the log file `<user_home_directory>/silentErrorLog.log` to view the details of the error.
6. Optionally, to verify that the Axon Agent is running, open the `<Axon_Agent_Home>/logs/dq-axon/dqagent.log` file.

CHAPTER 4

After You Upgrade

This chapter includes the following topics:

- Apache Log4j RCE Vulnerabilities for Axon, 22
- After You Upgrade Overview, 23
- Configure SSL Certificates for the Message Broker Service, 23
- Check the Status of the Services, 23
- Verify SSL Details, 25
- Update SSO Settings in the IDP, 25
- Configure Axon URL for Enterprise Data Catalog, 26
- Configure Axon with Operating System Profiles Enabled User for Data Integration Service, 26
- Update Enterprise Data Catalog Field Types, 27
- Configure the Axon Agent, 27
- Disable or Re-enable Segmentation, 27
- Migrate Scheduled Jobs, 28
- Configure Email Notifications, 28
- Display Reference Number for Data Sets and Attributes, 30
- Clear Cached Browser Images, 31
- Log In To Axon, 31
- Manage Saved Searches, 32

Apache Log4j RCE Vulnerabilities for Axon

The Log4j vulnerability has been addressed for Axon. You might find earlier versions of Log4j in the Axon and Axon Agent. The Axon backup folders contain earlier versions of Log4j vulnerabilities. These backup folders are not used by Axon. You can safely ignore or remove these backup folders.

If you have the Axon Agent connected to a version of Informatica Data Quality earlier than 10.5.2, you will find the Log4j vulnerability in the earlier version of Axon library files. We recommend you install the Axon Agent for Data Quality version 10.5.2 in order to remove the vulnerability.

Note: Backup folders are required only to revert to an earlier version of Axon. If you do not need to roll back to a previous version of Axon, you can delete the backup folders.The latest Axon version has Log4j fixes included.

After You Upgrade Overview

After you upgrade Axon, you must restore your earlier customizations and verify that Axon and the Axon Agent is running properly.

Configure SSL Certificates for the Message Broker Service

For the message broker service utilized by Axon to be fully functional, ensure that the SSL certificates are still valid.

You can find the SSL certificates in the following locations:

- `<Axon_install_dir>/certs/cacert`
- `<Axon_install_dir>/certs/server`

To verify the validity of the certificates, run the following command in the directory locations provided above:

```
openssl x509 -noout -text -in <cert_name> |grep -i -A2 validity
```

You can also confirm the certificate validity by reviewing the `Configure.log` file present in `<INSTALLATION_DIRECTORY>`. If the certificates have expired, the `Configure.log` file displays the following error: If the file displays the following error when you open it, then it means the certificates have expired:

```
MQPChannelHelper is not initialized. Updates to Lineage consumer will not be sent.
```

If the certificates for the message broker service have expired, replace the expired certificates with the latest certificates, by installing the fix **EBF-22417**.

To install **EBF-22417**, perform the following steps:

1. Navigate to the Technical Support File Transfer Protocol (TSFTP) server location at the following directory:
   `/updates/Axon/7.2.0/`
2. Download and extract the **EBF-22417** installer file to the Axon installation directory.
3. To launch the installer, run the following command:
   `./installEBF.sh`

Check the Status of the Services

You can verify if all the services installed by Axon are running properly.

Log in to Axon as an administrator, go to the **Admin Panel**, and view the **Admin Dashboard**. The **Status of Axon Services** section shows the services that are operational.

Axon uses the following services, which are located in the `<INSTALLATION_DIR>/axonhome/third-party-app/scripts` directory in the Linux environment:

Service	Service Name	Service Script
Authorization	`authorization`	`axon_authorization_microservice_init`
Bulk Upload	`axon_bulk_upload_microservice`	`axon_bulk_upload_microservice_init`
Change Request	`axon_changerequest_microservice`	`axon_changerequest_microservice`
Daemon Tools	`axon_daemontools`	`daemontools`
Data Marketplace	`axon_marketplace_microservice`	`axon_marketplace_microservice_init`
Document Upload	`axon_document_upload_microservice`	`axon_document_upload_microservice`
Email Notification	`jobber`	`jobber`
Event Monitor	`enable_eventmonitor`	`enable_eventmonitor.sh`
Graph Database and Search	`orientdb`	`orientdb`
HTTPD	`httpd`	`httpd`
Log Search	`elasticsearch`	`elasticsearch`
Manage Logs	`Logstash`	`logstash`
Memcached	`memcached`	`memcached`
Messaging	`rabbitmq-server`	`rabbitmq`
Notification	`axon_notification_microservice`	`axon_notification_microservice`
OdbConsumer	`OdbConsumer`	`OdbConsumer`
PostgreSQL	`postgresql`	`postgresql`
Unison Search	`axon_unison_microservice`	`axon_unison_microservice_init`
Value List	`axon_value_list_microservice`	`axon_valuelist_microservice_init`
Workflow	`camunda`	`camunda`

To check the status of a specific service, go to the `<INSTALLATION_DIR>/axonhome/third-party-app/scripts` directory, and run the following command:

```
sh <service_script> status
```

For example, to check the status of the Email Notification service, run the following command:

```
sh jobber status
```

To check the status of all Axon services, go to the `<INSTALLATION_DIR>/axonhome/third-party-app/scripts` directory, and run the following command:

```
sh axonStatus
```

Verify SSL Details

Axon uses HTTP or HTTPS for communication. To use HTTPS communication, the Axon application must have access to a valid Secure Sockets Layer (SSL) certificate file. The SSL certificate file must be in the CRT or PEM format.

If the SSL certificate file is in the CRT or PEM format before the upgrade, the upgrade process applies the SSL settings to the new Axon version. If the SSL certificate file is in the DER format before the upgrade, you must perform the following tasks to use HTTPS communication in the new Axon version:

1. Copy the DER certificate file to a location in the Axon upgrade directory. This step ensures that the Axon Administrator has read and write permission on this file.
2. Go to the DER certificate location and run the following command to convert the certificate file to the PEM format:

   ```
   openssl x509 -in <DER_file_name> -inform der -outform pem -out <PEM_file_output_name>
   ```

   For example, if the SSL certificate file is `cert.der`, and you want to convert the file to `cert.pem`, run the following command:

   ```
   openssl x509 -in cert.der -inform der -outform pem -out cert.pem
   ```
3. Open the `informatica_web.conf` file in the `<UPGRADE_DIR>/axonhome/third-party-app/httpd/conf.d/` directory, and change the `SSLCertificateFile` value to `<PEM_file_output_name>`.
4. Open the `config.properties` file in the `<UPGRADE_DIR>/config/` directory, and change the `SSL_CERTIFICATE_LOC` value to `<PEM_file_output_name>`.
5. Go to the `<UPGRADE_DIR>/axonhome/third-party-app/scripts` directory, and run the following commands to restart the HTTPD and Bulk Upload services:

   ```
   sh httpd restart
   sh axon_bulk_upload_microservice_init restart
   ```

Update SSO Settings in the IDP

If your organization uses Single Sign-On (SSO) for the Axon users, you must update the Identity Provider (IDP) with the Axon port number.

The Axon installer assigns the following default port numbers for the Apache server:

- If you use HTTP authentication, the installer assigns 9999 as the default port number for the Apache server.
- If you use HTTPS authentication, the installer assigns 9443 as the default port number for the Apache server.

You can also enter a custom port number for the Apache server. Depending on whether your Axon installation runs on the default port number or a custom port number for the Apache server, you must enter the correct port number in the SSO domain URL and the audience URL in the IDP.

1. Log in to the IDP configuration page, and open the Axon application.

2. Set the SSO domain URL to `http(s)://<Axon_host>:<9999_or_9443_or_custom_port_number>/saml/acs`. This URL is the endpoint for SSO login to Axon.
3. Set the audience URL to `http(s)://<Axon_host>:<9999_or_9443_or_custom_port_number>/saml/metadata`. This URL is the service provider metadata that is obtained from Axon.
4. Save your settings.

For more information on configuring Axon to use SSO, see the *Configuring Axon* chapter of the *Axon Data Governance Administrator Guide*.

Configure Axon URL for Enterprise Data Catalog

After you upgrade Axon, you must configure Enterprise Data Catalog to point to the new URL of the Axon application.

1. Log in to Enterprise Data Catalog and locate the Axon resource.
2. Enter the Axon host name in the following format: `http(s)://<host_name>`
3. Set the Axon port number to `<9999_or_9443_or_custom_port_number>`.
4. Save the settings.

To know more about how to modify the Axon resource in Enterprise Data Catalog, see the *Axon Resource Type Properties* topic in the *Informatica Catalog Administrator Guide*.

Configure Axon with Operating System Profiles Enabled User for Data Integration Service

After you install or upgrade Axon, you can configure the OS profile enabled user with Data Integration Service. After you configure the profile, you can use the operating system profile in the Axon Agent to run Data Quality rules.

To update the operating system profile user name, choose any of the following options:

Start DQAgent with your operating system profile user credentials

1. In the command prompt, navigate to the following Axon Agent home location: `DQAGENT_HOME` directory
2. To start the Axon Agent with the operating system profile user name, run the following command: `sh startup.sh --dis.ospUsername=<OSP Username>`

Configure DQAgent with the updated `application-mrs-dis properties` file

1. Navigate to the following Axon Agent home location: `DQAGENT_HOME/conf/directory`
2. Edit the `application-mrs-dis.properties` file.
3. Update the `dis.ospUsername` parameter with the user name enabled with the Data Integration Service.
4. To start the Axon Agent, run the following command from the command prompt: `sh startup.sh`

Update Enterprise Data Catalog Field Types

Axon displays physical fields from Enterprise Data Catalog in the **Physical Fields** facet in Unison search. You can search the fields using the filter options in Unison search. After the upgrade is complete, perform the steps in this procedure to display the Enterprise Data Catalog physical field types in Unison search.

The steps in this procedure are applicable in the following situation:

- You want to use the *Attribute X Physical Field* bulk upload template to link Enterprise Data Catalog fields to Axon attributes.

1. Run the following command to define the Axon environment variable so that the Linux system can access the Axon resources at the correct location:

   ```
   source <UPGRADE_DIR>/scripts/exportEnv.sh
   ```

2. Go to the `<UPGRADE_DIR>/axonhome/axon` directory and run the following command:

   ```
   <UPGRADE_DIR>/axonhome/third-party-app/php/bin/php bin/console
   informatica:links:update
   ```

3. Go to the `<UPGRADE_DIR>/scripts` location and run the following script to reindex the database:

   ```
   sh reIndex.sh
   ```

After the upgrade is complete, all Axon users must clear their Internet browser cache to display the Enterprise Data Catalog physical field types in Unison search.

Configure the Axon Agent

After you upgrade Axon, you must configure the Axon Agent to point to the new URL and login details of the Axon application.

1. Run the following command to stop the Axon Agent:

   ```
   <Axon_Agent_Home>/sh shutdown.sh
   ```

2. Go to the `<Axon_Agent_Home>/conf` directory and open the `application-axon.properties` file.
3. Set the Axon URL to `http(s)://<Axon_host>:<9999_or_9443_or_custom_port_number>/saml/acs`.
4. Enter the Axon login credentials.
5. Save the file.
6. Run the following command to restart the Axon Agent

   ```
   <Axon_Agent_Home>/sh startup.sh
   ```

Disable or Re-enable Segmentation

After you install or upgrade Axon, segmentation is automatically enabled, and you can restrict Axon objects by various segments. To make all Axon objects available to all Axon users, disable segmentation.

You must have the Super Admin profile to perform this task.

If you want to disable segmentation after the segments are created, delete all segments, and then disable segmentation.

1. To disable segmentation, go to the `<INSTALLATION_DIR>/bin` directory in the Linux environment, and run the following command:

   ```
   disable_authorization.sh
   ```

2. To enable segmentation again, go to the `<INSTALLATION_DIR>/bin` directory in the Linux environment, and run the following command:

   ```
   enable_authorization.sh
   ```

Migrate Scheduled Jobs

Axon uses the Jobber utility to schedule and run jobs. All Jobber files are located within the Axon home directory. If you upgrade from Axon version 5.2 or an earlier version, you must migrate the Jobber files from the directory of the previous version to the Axon 7.3 home directory.

Migrate Job File

When you upgrade Axon, the installer creates the `axon.jobs` file in the `<UPGRADE_DIR>/axonhome/axon_scheduler` directory. Axon uses the `axon.jobs` file to run scheduled jobs.

If you upgrade from Axon version 5.2 or an earlier version, you must copy the scheduled jobs from the `<user_home_directory>/.jobber` file to the `<UPGRADE_DIR>/axonhome/axon_scheduler/axon.jobs` file.

Note: To access the `<user_home_directory>/.jobber` file, you must be a root user or sudo user.

Migrate Job Scripts

When you upgrade Axon, the installer creates the `daily`, `weekly`, and `monthly` sub-directories in the `<INSTALLATION_DIR>/axonhome/axon_scheduler` directory. If you upgrade from Axon version 5.2 or an earlier version, you must move the Jobber script files from the directory of the previous version to the `daily`, `weekly`, and `monthly` sub-directories.

Configure Email Notifications

Axon uses the Jobber utility instead of the cron utility to configure jobs. If you have configured email notifications using the cron utility, you must reconfigure the notifications using the Jobber utility.

The Jobber utility creates a `axon.jobs` file in the `<INSTALLATION_DIR>/axonhome/axon_scheduler` location. You must configure the properties in this file to create email notifications.

You can schedule email notifications in the following time intervals:

- Daily
- Weekly
- Monthly

Create a Daily Email Notification Schedule

You can create a daily email notification schedule to send notifications to users.

1. Open the `axon.jobs` file available in the `<UPGRADE_DIR>/axonhome/axon_scheduler` location.

   If you have logged in as a sudo user, you must first copy the `axon.jobs` file from the `/root` location to the `<UPGRADE_DIR>/axonhome/axon_scheduler` location.

2. Configure the following properties in the `axon.jobs` file:

Property	Description
name	Enter a name for the notification job.
cmd	Enter `<UPGRADE_DIR>/axonhome/axon_scheduler/daily/dailyscript.sh`
time	Specify the daily email schedule. The six asterisks `* * * * * *` represent `<second> <minute> <hour> <date> <month> <day_of_the_week>`. For example, to receive email notifications at 5.00 p.m. everyday, enter the following value: `0 0 17 * * *`
onError	Enter `Stop`

3. Save your changes.
4. If you make changes to the `axon.jobs` file, you must reload the Jobber schedule settings. Run the following command to reload the settings:

   ```
   <UPGRADE_DIR>/axonhome/third-party-app/scripts/jobber reload
   ```

To send periodic email notifications to the Axon user, the Jobber utility runs the `dailyscript.sh` file that you created. You must have write permission in the `<UPGRADE_DIR>/axonhome/axon_scheduler/daily` directory for the Jobber utility to run the `dailyscript.sh` file.

Create a Weekly Email Notification Schedule

You can create a weekly email notification schedule to send notifications to users.

1. Open the `axon.jobs` file available in the `<UPGRADE_DIR>/axonhome/axon_scheduler` location.

   If you have logged in as a sudo user, you must first copy the `axon.jobs` file from the `/root` location to the `<UPGRADE_DIR>/axonhome/axon_scheduler` location.

2. Configure the following properties in the `axon.jobs` file:

Property	Description
name	Enter a name for the notification job.
cmd	Enter `<UPGRADE_DIR>/axonhome/axon_scheduler/weeklyscript.sh`
time	Specify the weekly email schedule. The six asterisks `* * * * * *` represent `<second> <minute> <hour> <date> <month> <day_of_the_week>`. For example, to receive email notifications at 9.00 a.m. on the third day of each week, enter the following value: `0 0 9 * * 3`
onError	Enter `Stop`

3. Save your changes.
4. If you make changes to the `axon.jobs` file, you must reload the Jobber schedule settings. Run the following command to reload the settings:

   ```
   <UPGRADE_DIR>/axonhome/third-party-app/scripts/jobber reload
   ```

To send periodic email notifications to the Axon user, the Jobber utility runs the `weeklyscript.sh` file that you created. You must have write permission in the `<UPGRADE_DIR>/axonhome/axon_scheduler/weekly` directory for the Jobber utility to run the `weeklyscript.sh` file.

Create a Monthly Email Notification Schedule

You can create a monthly notification schedule to send notifications to users.

1. Open the `axon.jobs` file available in the `<UPGRADE_DIR>/axonhome/axon_scheduler` location.

   If you have logged in as a sudo user, you must first copy the `axon.jobs` file from the `/root` location to the `<UPGRADE_DIR>/axonhome/axon_scheduler` location.
2. Configure the following properties in the `axon.jobs` file:

Property	Description
name	Enter a name for the notification job.
cmd	Enter `<UPGRADE_DIR>/axonhome/axon_scheduler/monthly/monthlyscript.sh`
time	Specify the monthly email schedule. The six asterisks `* * * * * *` represent `<second> <minute> <hour> <date> <month> <day_of_the_week>`. For example, to receive email notifications at 2.30 p.m. on the seventeenth day of each month, enter the following value: `0 30 14 17 * *`
onError	Enter `Stop`

3. Save your changes.
4. If you make changes to the `axon.jobs` file, you must reload the Jobber schedule settings. Run the following command to reload the settings:

   ```
   <UPGRADE_DIR>/axonhome/third-party-app/scripts/jobber reload
   ```

To send periodic email notifications to the Axon user, the Jobber utility runs the `monthlyscript.sh` file that you created. You must have write permission in the `<UPGRADE_DIR>/axonhome/axon_scheduler/monthly` directory for the Jobber utility to run the `monthlyscript.sh` file.

Display Reference Number for Data Sets and Attributes

If you upgrade from Axon version 5.0 HotFix 2 or an earlier version, you must configure the reference number prefix for data sets and attributes.

You must have the Super Admin profile to perform this task.

1. From the Axon toolbar, click the **Admin Panel** menu item under your user name.

2. In the menu on the left, under the **Customize & Configure** category, click **System Settings**.
3. In the **Group** list, select **Reference Number Settings**.
4. Click the **Edit** button, and then click the **Edit** icon.
5. In the **Facets Reference Number** window, enter the following lines of code:

```
"CatalogueItem": {
    "RefNumber": "<Data_Set_prefix>"
},
"CatItemComponent": {
    "RefNumber": "<attribute_prefix>"
}
```

   For example, to define Data Set prefix as `DS` and attribute prefix as `AT`, enter the following lines of code:

```
"CatalogueItem": {
    "RefNumber": "DS-"
},
"CatItemComponent": {
    "RefNumber": "AT-"
}
```

6. Click **Save** to save your changes in the **Facets Reference Number** window.
7. Click **Save** in the main **System Settings** page to save your settings.
8. In the Linux environment, run the following command to clear the Axon cache and restart the necessary services:

```
sh <INSTALLATION_DIR>/axonhome/third-party-app/scripts/paramsync
```

   When you run the `paramsync` script, Axon restarts the HTTPD, Memcached, and email notification services.

Note: When you clear the cache and restart the Axon services, the Axon web interface might be disrupted for some users that are logged into Axon. Informatica recommends that you update the cache after you save your changes in all the **System Settings** pages. Additionally, perform this action during a maintenance period when very few users are using Axon.

Clear Cached Browser Images

After you upgrade Axon, the system administrator must notify all Axon users to clear the cached browser images that apply to Axon. To know more about how to clear the browser cache, see the documentation for your browser.

Log In To Axon

If you have not configured Single Sign-On, use the URL displayed by the Axon installer after the installation completes to log in to Axon from a browser. To configure Single Sign-On for authentication, see the *Configure Single Sign-On* topic in the Axon Data Governance Administrator Guide.

The Axon installer assigns the following default port numbers for the Apache server:

- If you use HTTP authentication, the installer assigns 9999 as the default port number for the Apache server.

- If you use HTTPS authentication, the installer assigns 9443 as the default port number for the Apache server.

You can also enter a custom port number for the Apache server. Depending on whether you selected the default port number or entered a custom port number for the Apache server during installation, you must enter the correct port number in the browser address field.

1. Clear your Internet browser cache and cookies.
2. In the address field, type the fully qualified host name for the Axon login page in the following format: `http(s)://<host_name>:<9999_or_9443_or_custom_port_number>/`
3. From the Axon home page, on the top right corner of the toolbar, click **Login**.
4. Enter your login credentials and click Login. Use the same login credentials that you used for your previous version of Axon.
5. Axon refreshes the page and displays your username in the toolbar. This indicates that you have successfully logged in.

When you log in to Axon for the first time, Informatica recommends that you modify your login password for security purposes. The password must be at least eight characters long and contain at least one lowercase character, one uppercase character, one numeric digit, and one special character.

Manage Saved Searches

If you upgrade Axon from a version earlier than 5.2, the upgrade process migrates the previously saved searches of all Axon users.

If the search results of saved searches does not display the expected results. Informatica recommends that you verify the search results, and create new searches if required.

CHAPTER 5

Monitor and Troubleshoot

This chapter includes the following topics:

- Monitor Scheduled Jobs, 33
- Troubleshooting, 33
- Revert to an Earlier Version of Axon, 36

Monitor Scheduled Jobs

You can monitor the scheduled jobs created by the Jobber utility. You can view the details of scheduled jobs and the error messages for failed jobs.

See all scheduled jobs

To see the list of all jobs scheduled by Jobber, run the following command:

```
<UPGRADE_DIR>/axonhome/third-party-app/jobber/bin/jobber -sock=<UPGRADE_DIR>/
axonhome/third-party-app/config/jobber/jobber_daemon.sock -
user=<Axon_Administrator_non-root_user> -jobfile=<UPGRADE_DIR>/axonhome/
axon_scheduler/axon.jobs list
```

See email notification logs

The `<user_name>` file contains the error messages, if any, for the email notifications. To view the error messages, run the following command:

```
vi /var/spool/mail/<user_name>
```

Troubleshooting

Axon Does Not Load in the Browser

You can access Axon by typing the fully qualified host name in the address bar of a web browser. In the address field, type the fully qualified host name for the Axon login page in the following format: `http(s)://<host_name>:<port_number>/`

If Axon does not load in the browser, perform the following tasks:

Verify the Firewall Settings

You must enable the firewall of the machine where you installed Axon to allow requests for the Axon port.

Verify that the HTTPD Service is Running

To verify that the HTTPD service is running, go to the `<INSTALLATION_DIR>/axonhome/third-party-app/scripts` directory in the Linux environment, and run the following command:

```
sh httpd status
```

If the service is shut down, go to the `<INSTALLATION_DIR>/bin` directory, and run the following command to restart the Axon services:

```
sh startup.sh
```

Verify that the Unison Search Service is Running

To verify that the Unison Search service is running, go to the `<INSTALLATION_DIR>/axonhome/third-party-app/scripts` directory in the Linux environment, and run the following command:

```
sh axon_unison_microservice_init status
```

If the service is shut down, go to the `<INSTALLATION_DIR>/bin` directory, and run the following command to restart the Axon services:

```
sh startup.sh
```

Verify Log Files

Verify the following log files:

- `<INSTALLATION_DIR>/axonhome/third-party-app/httpd/logs/<hostname>-error_log` for HTTP authentication
- `<INSTALLATION_DIR>/axonhome/third-party-app/httpd/logs/<hostanme>-ssl_error_log` for HTTPS authentication
- `<INSTALLATION_DIR>/axonhome/axon/var/logs/prod.log`

Verify Your Axon License Validity

Check if your Axon license has expired. If your license expires, users cannot log in to Axon. Perform the following tasks if your Axon license expires:

1. Contact Informatica Global Customer Support to obtain a new license key.
2. In the Linux environment, replace the expired license key file with the new license key file in the following directory:

   `<INSTALLATION_DIR>/axonhome/axon/`

   Note: Make sure that the new license key file and expired license key file share the same name.

Note: When you clear the cache and restart the Axon services, the Axon web interface might be disrupted for some users that are logged into Axon. Informatica recommends that you update the cache after you save your changes in all the **System Settings** pages. Additionally, perform this action during a maintenance period when very few users are using Axon.

Verify Axon Settings and Parameters

Check if the Axon settings and **Admin Panel** parameters are correct. You can modify some of the **Admin Panel** settings from the Linux environment. You can run specific commands to display the current parameter values, reset the parameters to their default values, or enter new parameter values.

For more information, see the *Modify Admin Panel Settings from the Linux Environment* topic in the *Monitoring Axon* chapter of the Axon Data Governance Administrator Guide.

Incorrect Host Name

If you encounter an error with the host name during installation, verify that the host name has been configured with the correct IP address.

Run the following command to show the IP address of your host name:

```
hostname -i
```

Run the following command to show the fully qualified domain name of your host:

```
hostname -f
```

Validation Utility Errors

You might see errors relating to some package libraries when you run the validation utility.

Upgrade your version of OpenSSL to openssl-libs-1.0.2k if you see the following error when you run the validation utility:

```
Your system contains internal RPMs that are lower than the versions required for Axon.
Install the following internal RPM versions before you proceed: openssl-libs-1.0.2k
```

Cannot Log In to Axon

If your Axon license expires, users cannot log in to Axon. Logged in users automatically log out of Axon at the time of license expiry.

Perform the following tasks if your Axon license expires:

Verify that the PostgreSQL Database Service is Running

To verify that the PostgreSQL database service is running, go to the `<INSTALLATION_DIR>/axonhome/third-party-app/scripts` directory in the Linux environment, and run the following command:

```
sh postgresql status
```

If the service is shut down, go to the `<INSTALLATION_DIR>/bin` directory, and run the following command to restart the Axon services:

```
sh startup.sh
```

Note: Use the same commands to verify that the database services is running for the PostgreSQL database deployed on a different node and external nodes, such Amazon RDS and Microsoft Azure Database for PostgreSQL.

Replace Your Axon License Key

To replace your Axon license key, perform the following steps:

1. Contact Informatica Global Customer Support to obtain a new license key.
2. In the Linux environment, replace the expired license key file with the new license key file in the following directory:

   ```
   <INSTALLATION_DIR>/axonhome/axon/
   ```

   Note: Make sure that the new license key file and expired license key file share the same name.

Note: When you clear the cache and restart the Axon services, the Axon web interface might be disrupted for some users that are logged into Axon. Informatica recommends that you update the cache after you save your changes in all the **System Settings** pages. Additionally, perform this action during a maintenance period when very few users are using Axon.

Warnings in Configure.log Files

After you upgrade Axon, you might find a few warnings in the `Configure.log` file due to the previous RabbitMQ and Erlang versions.

You can stop running the previous versions of the RabbitMQ and Erlang libraries, or upgrade the shared libraries. If you plan to upgrade the shared libraries, use the following versions:

- rabbitmq_server-4.2.4
- erlang-27.3.4.8

Verify that the host name and IP addresses are configured correctly on the server.

Revert to an Earlier Version of Axon

If the upgrade process is interrupted and the upgrade is not complete, you can revert to an earlier version of Axon.

When you upgrade Axon, the installer preserves the files of the earlier Axon versions. If you have not deleted the installation directories of earlier Axon versions, you can launch an earlier version of Axon and the related services.

1. Go to the `<UPGRADE_DIRECTORY>/bin` location where you have upgraded Axon, and run the following command to shut down the Axon instance:

   ```
   sh shutdown.sh
   ```

   The system shuts down all the Axon services.
2. Go to the location of the earlier Axon version that you want to run, navigate to the `bin` directory, and run the following command to start Axon:

   ```
   sh startup.sh
   ```

   The system starts the earlier version of Axon and all the related services.

INDEX

A

Axon Agent
  configure 27

C

console upgrade 18

D

directories 14

E

email notifications
  configure 28
  daily 29
  monthly 30
  weekly 29

M

monitoring jobs 33

S

segmentation
  disable 27
  re-enable 27
services
  check status 23

U

upgrade modes
  console 18
  overview 18
upgrade path
  Axon 8
  Axon Agent 9

V

validation utility 15