How-To Library

Informatica

Deploy Axon Data Governance 7.2 on Kubernetes Using Axon Deployment Manager

© Copyright Informatica LLC 2021. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

This article describes how to install Axon Data Governance on Kubernetes from the Docker image using Informatica Axon Deployment Manager. This article also describes how you can use Informatica Axon Deployment Manager to manage an existing Axon Data Governance deployment on Kubernetes.

Supported Versions

- Axon Data Governance 7.2

Table of Contents

Overview. . . . 2
Axon Deployment Manager Process Checklist. . . . 3
Before You Begin. . . . 3
Verify System Requirements. . . . 3
Contact Informatica Global Customer Support. . . . 3
Access to Axon Installer. . . . 4
Verify the License Key. . . . 4
Access to Axon Deployment Manager 4
Verify Kubernetes Configuration. . . . 4
Use Docker Hub. . . . 4
Build the Docker Image. . . . 5
Step 1: Choose the Deployment Type. . . . 5
Step 2: Configure the Docker Image. . . . 5
Step 3: Configure the Axon Services. . . . 6
Run the Docker Image to Deploy Axon on Kubernetes. . . . 6
Step 1: Choose the Deployment Type. . . . 6
Step 2: Provide Axon Deployment Details. . . . 7
Step 3: Configure the Axon Services. . . . 8
Manage Axon. . . . 8
Frequently Asked Questions about Deploying Axon on Kubernetes. . . . 9

Overview

A Kubernetes engine is a cluster comprised of one or more master nodes and multiple worker nodes. The Kubernetes cluster master runs the Kubernetes control plane processes, including the Kubernetes API server, scheduler, and core resource controllers. The worker nodes run the workloads.

Use the Web-based interface in Informatica Axon Deployment Manager to quickly create standard Docker images and deploy using Kubernetes.

Docker is an open source platform that provides an isolated environment called containers to run applications. Docker allows independent containers to run within a single Linux instance. A Docker image is an executable package that can run an application, a code, run-time files, environment variables, or configuration files. A container is a run-time instance of an image.

Axon Deployment Manager Process Checklist

Perform the following tasks associated with the installation:

1. Verify the following prerequisites:
    a. Verify system requirements.
    b. Configure Docker engine.
    c. Access Axon Deployment Manager and extract the Axon installer `.tar` file.
    d. Verify the license key.
    e. Set up a repository to store Docker images.
    f. Set up the Kubernetes cluster.
2. Build the Docker image for Axon services with the Linux operating system.
3. Run the Docker image to deploy Axon using Kubernetes.
4. Manage Axon using Axon Deployment Manager to perform tasks, such as running the paramsync script and restarting the Axon services.

Before You Begin

Before you start using Axon Deployment Manager, verify that the machine meets the pre-installation requirements for the Axon installation.

Verify System Requirements

Verify that your environment meets the minimum system requirements for the installation process.

- Disk space of 50 GB in the Docker build directory.
- Disk space of 50 GB in the current working directory.
- Disk space of 50 GB in the Docker configuration directory.
- Supported image name or one of the following image names for the subscribed Linux operating system:

  ```
  registry.access.redhat.com/rhel7:7.8
  ```

  or

  ```
  centos:7
  ```
- Configure external storage and associate storage class with external storage.
- Disk space of 10 GB required for external storage.
- Master node configuration: 4 cores of 3 GHz with 24GB RAM
- Worker node configuration: 2 modules of 8cores of 3GHz with 24 GB RAM
- Register and subscribe to the machine where you build the docker images.

Contact Informatica Global Customer Support

When you initially contact Informatica Global Customer Support for Axon installation access, the Informatica Global Customer Support team initiates a shipping request. The shipping team sends the Axon installation link and license information to you.

You can contact Informatica Global Customer Support online for access to the following files:

- Axon installer `.tar` file

- License key
- Axon deployment `.zip` file

Access to Axon Installer

You require access to the Axon installer `.tar` file to install the product.

Download and extract the Axon installer from the Informatica Marketplace.

Contact the support team to access the Axon installer `.tar` file. You can then place the Axon installer `.tar` file on the machine where you build the image.

Verify the License Key

Before you install the software, verify that you have the license key available for the Axon installer.

The product is provided as Bring Your Own License (BYOL). Copy the license key file to a directory accessible to the user account that installs the product. You can use an existing Informatica license or contact Informatica Global Customer Support if you do not have a license key or if you have an incremental license key.

Access to Axon Deployment Manager

You require access to the `.zip` file to install Axon Deployment Manager and deploy Axon on Kubernetes.

Download and extract Axon Deployment Manager from the Informatica Marketplace.

Extract the `axon_isp_utility.zip` file to access Axon Deployment Manager and deploy Axon on Kubernetes.

Verify Kubernetes Configuration

Complete the following tasks on the machine where you run Axon Deployment Manager:

1. Install `kubectl`.
2. Ensure that the machine where the container utility runs can communicate with the Kubernetes cluster through the `kubectl cluster-info` command. The command displays information about the master and services that run in the cluster.

   For more information, see the Kubernetes documentation.

Use Docker Hub

You can use the Docker Hub to push the built image to your Docker repositories and use the image during the deployment instead of building the Docker image on every worker node.

If you want to pull an image from the Docker Hub or private registry, you must create a Kubernetes secret with the name `regcred` on each worker node. Run the following command to create the Kubernetes secret:

```
kubectl -n <namespace> create secret docker-registry regcred --docker-server=https://
index.docker.io/v2/ --docker-username=<username> --docker-password=<password>
```

Build the Docker Image

Build a Docker image for Axon. After you build the Docker image, Axon Deployment Manager uses the Docker image to run the Kubernetes pods. Ensure that the Docker image is stored in the local host or Docker registry before you install Axon in Kubernetes with Axon Deployment Manager.

To build the Docker image, perform the following tasks:

1. Choose the deployment type.
2. Build the Docker image.
3. Configure the Axon services.

Note: If you already have a built Docker image stored in the Docker registry, you can directly run the Docker image to deploy Axon on the Kubernetes. Refer to "Run the Docker Image to Deploy Axon on Kubernetes" on page 6.

Step 1: Choose the Deployment Type

On the **Deployment Type** page, select the deployment type and host instances to build the Docker image.

1. To launch Axon Deployment Manager, run the following command: `sh startup.sh`

   Axon Deployment Manager uses port 12104 by default. To specify a different port, add the required port number at the end of the startup command as shown in the following example:

   ```
   sh startup.sh <required port number>
   ```

   Note: If Axon Deployment Manager is already running, do not start it again.
2. On the **Home** page, select **Kubernetes**.
3. To build the Docker image, select **Build Image**.

   The **Deployment type** page appears.
4. On the **Deployment type** page, select the product to build the Docker image.

   Axon is selected by default.
5. Optionally, you can choose to configure SSL protocol for secure authentication to build the image or deploy the containers on the remote host.
   - If you do not want to build the image on the remote host, go to step 6.
   - If you want to build the image on the remote host, set the authentication type to **Password** or **Key**.
     - For password type authentication, enter the host name, user name, password, and port to connect to the host machine.
       The SSH connection uses port 22 by default.
     - For key type authentication, enter the host name, user name, path of the host authentication key, and port number.
6. Click **Next**.

Step 2: Configure the Docker Image

On the **Configure Docker** image page, enter the following information for the `.tar` file location and the images:

1. Specify the base operating system to build the Docker image.
   - To build the Docker image on CentOS, select `centos:7`.
   - To build the Docker image on RHEL, select `registry.access.redhat.com/rhel7`.
   - To build the Docker image on a custom operating system, select `Custom`, and enter the name of the valid operating system.

2. Enter the Axon installer `.tar` file path on the machine where you want to build the image.

   Axon Deployment Manager uses the tar utility to extract the installer server files to a directory on the machine.

3. Enter the working directory to build the Docker image.

   Default is `/root`.

4. Click **Next**.

   The **Configure Axon Services** page appears.

Step 3: Configure the Axon Services

On the **Configure Axon Services** page, specify the image name for Axon services that you want to include in the Docker image.

1. In the **Image Name** section, specify the name of the Docker image for the Axon services. You can specify the default image name for the required Axon services.
   For example, for the Notification service, you can specify the default image name `informaticaltd/axonk8s:notification` or a custom image name to build the Docker image.
2. Click **Build**.

   The process of building the image starts.

After the Docker image is built, you can view the status and name of the image, along with the tasks performed by the installer in the log summary.

Run the Docker Image to Deploy Axon on Kubernetes

Run the Docker image to deploy Axon Data Governance on Kubernetes.

To run the Docker image, perform the following tasks:

1. Choose the deployment type.
2. Provide Axon deployment details.
3. Configure the Axon services.

Step 1: Choose the Deployment Type

On the **Deployment Type** page, select the deployment type and host instances to run the Docker image.

1. To launch Axon Deployment Manager, run the following command: `sh startup.sh`

   Axon Deployment Manager uses port 12104 by default. To specify a different port, add the required port number at the end of the startup command as shown in the following example:

   ```
   sh startup.sh <required port number>
   ```

   Note: If Axon Deployment Manager is already running, do not start it again.
2. On the **Home** page, select **Kubernetes**.
3. To run the Docker image, select **Run Image**.
4. On the **Deployment type** page, select the product to build the Docker image.

   Axon is selected by default.
5. Optionally, you can choose to configure the SSL protocol for secure authentication to build the image or deploy the containers on the remote host.

- If you do not want to run the image on the remote host, go to step 6.
- If you want to run the image on the remote host, set the authentication type to **Password** or **Key**.
  - For password type authentication, enter the host name, user name, password, and port to connect to the host machine.
    The SSH connection uses port 22 by default.
  - For key type authentication, enter the host name, user name, path of the host authentication key, and port number.

6. Click **Next**.

Step 2: Provide Axon Deployment Details

In the **Docker information** page, provide the required information to connect to the Docker image and container.

1. In the **Docker and Kubernetes Information** section, configure the following fields:

Field	Description
Namespace	Enter lowercase alphanumeric characters and hyphen. The value must start and end with an alphanumeric character. Enter a maximum of 63 characters.
Storage Class	Specify storage class to manage external storage.
Informatica License Key	Enter the path and file name of the Informatica license key.
Working Directory	Enter the path to the directory where you want to install the utilities.

2. In the **Service configuration** section, configure the following options:
   - To view logs in the Admin Panel, select **Enable viewing of logs in the Admin Panel**.
   - For HTTP authentication, enter the port number in the range of 30000 to 32535.
     The HTTP authentication uses port 31511 by default.
   - To configure SSL authentication, select **Enable HTTPS authentication**. Enter the port number, SSL certificate, and SSL key details.
   - To connect Axon to Enterprise Data Catalog, select **Connect Axon to Enterprise Data Catalog**. Enter the following details:
     - Enterprise Data Catalog Host
     - Enterprise Data Catalog Port
     - Enterprise Data Catalog Server Login User Name
     - Enterprise Data Catalog Server Password
     - Enterprise Data Catalog Server Namespace
     - Enterprise Data Catalog Resource Name
   - To connect Axon to Data Privacy Management, select **Connect Axon to Data Privacy Management**. Enter the following details:
     - Data Privacy Management Host
     - Data Privacy Management Port

- Data Privacy Management Server Login User Name
- Data Privacy Management Server Password
- Data Privacy Management Server Namespace

3. Click **Next**.

Step 3: Configure the Axon Services

On the **Configure Axon Services** page, specify the image name for the Axon services that you want to deploy on Kubernetes.

1. In the **Image Name** section, specify the name of the Docker image for the Axon services. You can specify a default image name for the required Axon services.
   For example, for the Notification service, you can specify the default image name `informaticaltd/axonk8s:notification` or a custom image name to build the Docker image.
2. Click **Deploy**.

   The Docker image runs and deploys Axon on Kubernetes.

In the log summary, you can view the status and details of the deployment logs along with the tasks performed by the installer.

Manage Axon

You can restart Axon services using Axon Deployment Manager. You can take a backup of the database. You can also download logs to verify the status of your action.

1. To launch Axon Deployment Manager, run the following command: `sh startup.sh`

   Axon Deployment Manager uses port 12104 by default. To specify a different port, add the required port number at the end of the startup command as shown in the following example:

   ```
   sh startup.sh <required port number>
   ```

   Note: If Axon Deployment Manager is already running, do not start it again.
2. Click **Manage Axon**.

   Note: Steps 1 and 2 are not required if you are managing an existing deployment of Axon.
3. Optionally, if you want to remotely manage Axon that is deployed on Kubernetes, enable secure authentication, and set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the host name, user name, password, and port to connect to the host machine.

     The SSH connection uses port 22 by default.
   - For key type authentication, enter the host name, user name, path of the host authentication key, and port number.
4. In the **Action Information** section, enter the following details:

Property	Description
Namespace	Enter the same value that you used to run the Docker image to deploy pods in the Kubernetes environment.
Working directory	Specify the path to the existing working directory.

Property	Description
K8s Actions	You can choose one of the following options: • Reindex the database. • Run the `paramsync` script. • Restart the Axon services. • Back up the database. • Check the status of the Axon services.

Frequently Asked Questions about Deploying Axon on Kubernetes

Review the following frequently asked questions to understand the deployment of Axon on Kubernetes:

What happens if the Axon pod crashes or is deleted?

If the Axon pod crashes or is deleted, a new Axon pod is created and the old pod is terminated. The new Axon pod takes about 2 minutes to be up, but Axon Data Governance takes about 30 minutes to be up and running.

Where can I view the deployment logs?

You can view the logs in the working directory that you specified during the deployment of Axon on Kubernetes. The deployment log file name includes the latest timestamp. A sample deployment log file in the working directory is as follows:

```
/root/workingdirectory/logfile1619363942811.log
```

Where can I find the database backup?

You can access the database backup from the following location:

```
<Mount location for persistent volume>/<Shared volume pvc>/db_backup
```

A sample database backup directory is as follows:

```
/nfsshare/default-shared-volume-pvc-1510ff6b-8272-4334-9b7e-abaed1334720/db_backup
```

Is there a prerequisite for integration of products with Axon that is deployed on Kubernetes?

To integrate other products, such as Axon Agent, Enterprise Data Catalog, Informatica Data Quality, and Data Privacy Management, with Axon that is deployed on Kubernetes, add a DNS entry for the host name of the products. The server in which other products are installed can be resolved by using a fully qualified host name.

Which services are included in the Axon pod?

An Axon pod includes the following services:

- `Assetonboarder`
- `Ldapsynchronizer`
- `jobber`
- `daemontools`
- `apache`
- `odbconsumer`
- `php`
- `wkhtmltopdf`

How do I run the `php bin/console` commands in the Kubernetes environment?

To run the `php bin/console` commands, perform the following steps:

1. To log in to the Axon pod, run the following command:

   ```
   kubectl -n <namespace> exec -ti <axon_pod_name> /bin/bash
   ```

2. To change the user, run the following command:

   ```
   su nroot
   ```

3. Run the `php bin/console` commands by using the following syntax:

   ```
   export /home/nroot/exportEnv.sh;cd /home/nroot/axon;/home/nroot/php/bin/php bin/
   console <command>
   ```

Authors

Nidhi Jain

Vinita Arun