How-To Library

Informatica

Configuring Monitoring Parameters for Axon Data Governance

© Copyright Informatica LLC 2020, 2022. Informatica, the Informatica logo, and PowerCenter are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html

Abstract

This article describes how to configure the logging parameters in the PostgreSQL database to improve monitoring of Axon Data Governance.

Supported Versions

- Informatica Axon Data Governance 7.2

Table of Contents

Overview. 2
Configuring Log Connection and Disconnection Parameters. 2
Configuring Log Statements. 3
Confguring Log Duration. 3

Overview

When you install Axon on the PostgreSQL database, the parameters such as `log_connections`, `log_disconnections`, `log_statement`, and `log_duration`, are not enabled by default.

You can configure the following parameters in the PostgreSQL database:

`log_connections`

Logs each attempt made to connect to the PostgreSQL database and the successful completion of user authentication. The default value is `off`.

If you configure the `log_connections` parameter, you can monitor the database to see if a breach has occurred. You can then find the source of breach and confine the breach to a limited extent.

`log_disconnections`

Logs the end of each session and the session duration. The default value is `off`.

If you configure the `log_disconnections` parameter, you can view and examine the connections for failed attempts and duration of the logged-in session.

`log_statement`

Logs the type of SQL statements. The default value is `none`.

`log_duration`

Logs the duration of each completed SQL statement. The default value is `off`.

Use the log duration for statements to identify both non-performing and long-running queries.

Configuring Log Connection and Disconnection Parameters

Configure the `log_connections` and `log_disconnections` parameters in the PostgreSQL database to enable logs for login attempts and user authentication.

1. Navigate to the following directory:

   `<INSTALLATION_DIR>/axonhome/third-party-app/postgresql/data`

2. Open the `postgresql.conf` file and configure the following parameters:
   - Set the `log_connections` parameter value to `on`.
   - Set the `log_disconnections` parameter value to `on`.
3. In the Linux environment, run the following command to restart the PostgreSQL database server:

   ```
   sh <INSTALLATION_DIR>/axonhome/third-party-app/scripts/postgres restart
   ```

Configuring Log Statements

Configure the `log_statement` parameter in the PostgreSQL database to store the logs for the type of SQL statements.

1. Navigate to the following directory:

   ```
   <INSTALLATION_DIR>/axonhome/third-party-app/postgresql/data
   ```
2. Open the `postgresql.conf` file and set the `log_statement` parameter value to `ddl`.
3. In the Linux environment, run the following command to restart the PostgreSQL database server:

   ```
   sh <INSTALLATION_DIR>/axonhome/third-party-app/scripts/postgres restart
   ```

Confguring Log Duration

Configure the `log_duration` parameter in the PostgreSQL database to store the log duration for each SQL statement.

1. Navigate to the following directory:

   ```
   <INSTALLATION_DIR>/axonhome/third-party-app/postgresql/data
   ```
2. Open the `postgresql.conf` file and set the `log_duration` parameter value to `on`.
3. In the Linux environment, run the following command to restart the PostgreSQL database server:

   ```
   sh <INSTALLATION_DIR>/axonhome/third-party-app/scripts/postgres restart
   ```

Author

Vinita Arun Kumar

Acknowledgements

The author would like to acknowledge Beemaraj V, Principal Software Engineer, for his technical assistance.