How-To Library

Informatica

Install Axon Data Governance 7.2 on Docker with the Container Utility

© Copyright Informatica LLC 2020, 2021. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

Informatica provides the Informatica container utility to install Axon Data Governance quickly. This article describes how to install Axon and the Axon Agent from the docker image through the Informatica container utility.

Supported Versions

- Axon Data Governance 7.2

Table of Contents

Overview. . . . 3
Container Utility Process Checklist. . . . 3
Before You Begin 3
Verify System Requirements. . . . 4
Contact Informatica Global Customer Support. . . . 4
Generate CI/CD Content for Silent Input Properties File. . . . 4
Build the Docker Image. . . . 5
Step 1. Choose the Deployment Type. . . . 5
Step 2. Build the Docker Image. . . . 6
Step 3. Verify the Informatica Docker Image. . . . 6
Run the Docker Image. . . . 6
Step 1. Choose the Deployment Type. . . . 7
Step 2. Provide Docker Details. . . . 7
Step 3. Model Repository Service Credentials. . . . 8
Step 4. Data Integration Service Credentials. . . . 9
Step 5. Axon Service Credentials. . . . 10
Quick Deployment. . . . 10
Step 1: Choose the Deployment Type. . . . 10
Step 2. Provide Configuration Options. . . . 11
Configure the Docker Image in Silent Mode. . . . 11
Running the Silent Installer. . . . 11
Troubleshooting Docker. . . . 12
Appendix A: Sample Silent Properties for CI/CD for Build Image for Axon 13
Appendix B: Sample Silent Properties for CI/CD for Run Image for Axon 13
Appendix C: Sample Silent Properties for CI/CD for Build Image for Axon Agent. . . . 14

Appendix D: Sample Silent Properties for CI/CD for Run Image for Axon Agent. 14

Overview

With a web-based interface in the Informatica container utility, you can easily create standard docker images and create a container using docker.

Docker is an open source platform that provides an isolated environment called containers to run the applications. Docker allows independent containers to run within a single Linux instance. A docker image is an executable package that can run an application, a code, run-time files, environment variables, or configuration files. A container is a run-time instance of an image.

With the Informatica container utility, you can build or run the docker image with the silent installer. CI/CD or continuous integration and continuous delivery, is a practice that automates the integration and delivery operations in a CI/CD pipeline. Informatica automated the generation of the silent input properties. If you want to run the silent installer, you can choose to generate the properties when you go through the wizard steps, and then copy the properties directly into the silent install properties file.

The Informatica container utility provides quick and easy access to install and configure Docker for Axon or the Axon Agent. You can create standard docker images and create a container using Docker.

Container Utility Process Checklist

Perform the following tasks associated with the installation:

- ❑ Complete prerequisites:
  - Verify system requirements.
  - Configure docker engine.
  - Verify the license key.
  - Extract the Informatica container utility and access the Axon installer .tar file.
  - Set up repository databases.
  - Automate the generation of the silent input property file.
- ❑ Build the docker image with the base operating system.
- ❑ Run the docker image.
- ❑ Deploy the docker image quickly or download and run the default image.
- ❑ Build or run the docker image in silent mode with CI/CD content.

Before You Begin

Before you install the Informatica container utility, verify that the machine meets the pre-installation requirements for the Informatica product installation.

To meet the pre-installation requirements, perform the following tasks:

1. Verify system requirements.
2. Contact Informatica Global Customer Support.
3. Access to .tar file.
4. Verify the license key.

5. Generate CI/CD content for silent input properties File.

Verify System Requirements

Verify that your environment meets the minimum system requirements for the installation process:

- Supported image name or one of the following image names for the subscribed base operating system: `registry.access.redhat.com/rhel7 or centos:centos7`.
- Register and subscribe the machine where you build the docker images.
- If IPv4 forwarding is not enabled on your system, add the `net.ipv4.ip_forward=1` parameter in the following file: `/etc/sysctl.conf`.
  To restart the network service, run the following command:

  ```
  systemctl restart network
  ```

  To verify the system configuration, run the following command:

  ```
  sudo sysctl -p
  ```

Contact Informatica Global Customer Support

When you initially contact Informatica Global Customer Support for Informatica installation access, the Informatica Global Customer Support team initiates a shipping request. The shipping team sends the Informatica installation link and license information to you.

Access to .tar File

You require access to both the Informatica container utility and the Axon installer.tar file to install the product.

Download and extract the Informatica container utility installer files from the Informatica Marketplace. After you extract the informatica_container_utility_linux-x64.zip file, contact the support team to access the Axon installer .tar file. You can then place the Axon installer tar file on the machine where you build the image.

To gather inputs for the silent input properties files, launch the Informatica container utility and click **Generate silent properties for CI/CD**. You can then change the format of the properties file to UNIX before you run the silent installation.

Verify the License Key

Before you install the software, verify that you have the license key available for the Informatica product installer.

The product is provided as a Bring Your Own License (BYOL). Copy the license key file to a directory accessible to the user account that installs the product. You can use an existing Informatica license or contact Informatica Global Customer Support if you do not have a license key or if you have an incremental license key.

The volume directory is the directory where the Informatica license key and certificates are stored. You must have read, write, and execute permissions on the volume directory.

Note: You do not need a license for the Informatica container utility.

Generate CI/CD Content for Silent Input Properties File

CI/CD is a process of continuous integration, continuous delivery, and continuous deployment. With the CI/CD process available when you create or build the docker image in the Informatica Container Utility, you can generate property values to run the silent installer. Before you can run the silent installer, click **Generate silent properties for CI/CD** from

the Informatica container utility. Use the generated CI/CD values to replace the contents of the silent input properties file. You must convert the properties file to the UNIX format before you run the silent installer.

When you run the CI/CD process, you can copy all the user input values entered to build or run the docker image from the Informatica container utility from a single panel. The generated CI/CD contents are in the supported format of the silent install property files. Manually save the CI/CD contents into the silent input properties file located in the silent installation directory. Convert the properties file to the UNIX format before you run the silent installation.

Make sure to perform the tasks of build the docker image and run the docker image before you click **Generate Silent Input Properties File**.

Build the Docker Image

Build a docker image for Axon and Axon agent. After you build the docker image, the Informatica container utility uses the docker image to run on containers. Ensure that the docker image is stored in the local host or docker registry before you install Axon or Axon agent in the docker with the Informatica container utility.

To build the docker image, perform the following tasks:

1. Choose the deployment type.
2. Build the docker image.
3. Verify the docker image.

Step 1. Choose the Deployment Type

On the **Deployment type** page, you must select the deployment type and host instance to build the docker image.

1. Launch the Informatica container utility with the `sh startup.sh` command. By default, the utility uses port 12386.

   To specify the startup command with a different port number, enter the values in the following format: `sh startup.sh <required port number>`
2. To build the Informatica Docker image, select **Build the docker image**.

   The **Deployment type** page appears.
3. On the **Deployment type** page, enter the information for the deployment type.
   - Select Axon or Axon Agent for the product.
   - Choose to host on Amazon Web Services (AWS), Microsoft Azure, or on-premises.

   The build image uses Docker as the default deployment type.
4. Optionally, you can choose to provide secure authentication to build the image or deploy the containers on the remote host. If you do not want to set the secure authentication for the containers, go to step 6.
5. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connetcion uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
6. Click **Next**.

   The **Build the docker image** page appears.

Step 2. Build the Docker Image

On the **Build Docker Image** page, enter information for the tar file location and the images, or accept the default values to build the docker image.

1. Specify the base operating system path to build the docker image.
   - To build the docker image on CentOS, enter a value or select the default value of `centos:centos7`.
   - To build the docker image on RHEL, enter a value or select the default value of `registry.access.redhat.com/rhel7:7.8`.
     If you choose RHEL 7, use Docker 1.13 included with your RHEL distribution.
2. Enter the Axon installer tar file path on the machine where you build the image.

   The Informatica container utility uses the tar utility to extract the installer server files to a directory on your machine where you build the image.
3. Specify the docker base image name.

   Default is `axon:1.0`, where `1.0` is the tag name.
4. Enter the docker build directory.

   Specify the machine host directory to build the docker image.

   Default is `/user/home`.
5. If you select **Axon Agent** in the **Deployment Type** page, select the Informatica domain version for the Axon Agent.
6. Click **Build**.

   Optionally, you can choose to generate the silent properties for CI/CD. When you generate silent properties for CI/CD from the container utility, you can also copy all the installation options and the values specified in the container utility and later paste the contents into the property file for the silent installer.

Step 3. Verify the Informatica Docker Image

You can verify that the Axon image is present in the host specified while building the docker image.

To verify that the Axon docker image exists for Axon and Axon agent, enter the docker images command from the command prompt. Ensure that the values for the tag, image ID, created date, and size information appears for the Axon docker image

The following sample displays the result of the docker image command:

```
[root@irlcmg08 ~]# docker images
REPOSITORY                      TAG                 IMAGE ID            CREATED             SIZE
axon                            1.0                 ca557c023331        3 days ago          8.72 GB
```

```
[root@irlcmg08 ~]# docker images
REPOSITORY                      TAG                 IMAGE ID            CREATED             SIZE
agent                           1.0                 5e38f514fd45        5 hours ago         1.69 GB
```

Run the Docker Image

You can run the docker image to deploy Axon or Axon Agent containers on Amazon Web Services (AWS), Microsoft Azure, or on-premises

To run the docker image perform the following tasks:

1. Choose the deployment type.
2. Provide the docker details.
3. Configure Model Repository Service credentials.

4. Configure Data Integration Service credentials.
5. Configure Axon service credentials.

Step 1. Choose the Deployment Type

On the **Deployment type** page, you must select the deployment type and host instance to run the docker image.

1. Launch the Informatica container utility with the `sh startup.sh` command. Default port is 12386.

   To specify the startup command with a different port number, enter the values in the following format:

   ```
   sh startup.sh <required port number>
   ```

2. To run the Informatica Docker image, select **Run the docker image**.

   The **Deployment Type** page appears.

3. Enter the information for the deployment type.
   - Select one of the following options for the **Informatica Product** field:

     - Axon

     - Axon Agent
   - Choose to host on Amazon Web Services (AWS), Microsoft Azure, or on-premises.
   - The deployment type is Docker.
4. Optionally, you can choose to provide secure authentication to deploy the containers on the remote host. If you do not want to set the secure authentication for the containers, go to step 6.
5. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
6. Click **Next**.

   The **Docker information** page appears.

Step 2. Provide Docker Details

On the **Docker Information** page, provide the required information to connect to the docker image and container.

1. If you choose **Axon** for the **Informatica Product** field on the **Deployment Type** page, perform the following steps:
   a. In the **Docker configuration** section, enter the docker image name, container name, path and file name of the license key, and the volume directory. Enter the existing directory to create tmpfs volume. Verify that you specify different file paths for the volume directory and the license key directory.
   b. Optionally, enter the network name.
   c. In the **Service configuration** section, you can select the following check boxes:
      - To view logs in the Admin Panel, select **Enable viewing of logs in the Admin Panel**.
      - Select **Enable HTTPS authentication**. Enter the port number, SSL certificate, and SSL key detail.

- To connect Axon to Enterprise Data Catalog, select **Connect Axon to Enterprise Data Catalog**. Enter the following details:
  - Enterprise Data Catalog Host
  - Enterprise Data Catalog Port
  - Enterprise Data Catalog Server Login User Name
  - Enterprise Data Catalog Server Password
  - Enterprise Data Catalog Server Namespace
  - Enterprise Data Catalog Resource Name
- To connect Axon to Data Privacy Management, select **Connect Axon to Data Privacy Management**. Enter the following details:
  - Data Privacy Management Host
  - Data Privacy Management Port
  - Data Privacy Management Server Login User Name
  - Data Privacy Management Server Password
  - Data Privacy Management Server Namespace

d. Click **Deploy**.

2. If you choose **Axon Agent** for the **Informatica Product** field on the **Deployment Type** page, perform the following steps:

   a. In the **Docker configuration** section, enter the docker image name, and the volume directory. Enter the existing directory to create tmpfs volume. Make sure that you have read, write, and execute permissions on the directory.

   b. Optionally, enter the network name.

   c. In the **Service configuration** section, select the Informatica domain version for the Axon Agent.

   If you choose 10.2.2 Hot Fix 1, 10.4.0, 10.4.1, or 10.5 domain version, the page displays the option to run the data quality rules on Axon attributes.

   d. Enter connection name to run data quality rules.

   You can generate data quality scores in Informatica Data Quality and display the scores in Axon.

   e. Click **Next**.

   Make sure the domain version you choose during run the docker image for the Axon Agent must be similar to the domain version that you chose when you built the docker image for the Axon Agent.

Step 3. Model Repository Service Credentials

On the **Model Repository Service Credentials** page you can configure the Model repository properties. The page appears if you select **Axon Agent** for the **Informatica Product** field on the **Deployment Type** page.

1. Configure the following properties:

Property	Description
Domain Name	Name of the Model Repository Service (MRS) domain.
Node Port Name	Port number.

Property	Description
Host Name	Name of the host.
Node Name	Name of the node.
User Name	The database user name for the Model repository.
Password	Repository database password for the database user.
Service Name	Name of the service
Security Domain	Name of the security domain to which the domain user belongs.

2. Specify if the cluster is enabled for SSL authentication.

   Enter the path to the truststore file.
3. Specify if the cluster is enabled for custom SSL authentication.

   Enter the SSL password.
4. Click **Next**.

Step 4. Data Integration Service Credentials

On the **Data Integration Service Credentials** page you can configure the Data Integration Service properties. The page appears if you select Axon Agent for the **Informatica Product** field on the **Deployment Type** page.

1. Configure the following properties:

Properties	Description
Node Port Number	Port number.
Host Name	Name of the host on which the service runs.
Node Name	Name of the node on which the service runs.
User Name	The database user name for the Data Integration Service.
Password	The database password for the database user.
Service Name	Name of the service.
Security Domain	Name of the security domain to which the domain user belongs.

2. Specify if the cluster is enabled for the SSL authentication.

   Enter the path to the truststore file.
3. Specify if the cluster is enabled for the custom SSL authentication.

   Enter the SSL password.
4. Click **Next**.

Step 5. Axon Service Credentials

On the **Axon Service Credentials** page you can configure the Axon Service properties. The page appears if you select **Axon Agent** for the **Informatica Product field** on the **Deployment Type** page.

1. Configure the following properties:

Property	Description
URL	The URL on which the Axon service is hosted.
User Name	The user name for the Axon service.
Password	The password for the Axon service.
Port	The port number. Make sure the port number that you entered is available to run the Axon agent.

2. Specify if the `HTTPS` authentication is enabled for Axon.
3. Click **Deploy**.

Quick Deployment

With the quick deployment, you can download and run the Informatica docker image with a pre-built image of Axon Agent. The utility uses the PostgreSQL database and CentOS base operating system that are bundled with the docker image.

Step 1: Choose the Deployment Type

On the **Deployment Type** page, you must select the host instance to download and run the docker image.

1. Launch the Informatica container utility with the `sh startup.sh` command. Default port is 12386. To specify the startup command with a different port number, enter the values in the following format: `sh startup.sh <required port number>`.
2. To build and run the Informatica Docker image, select **Quick Deployment** in the Informatica container utility.

   The **Deployment Type** page appears.

   By default, the selected product is Axon with the Docker deployment type.
3. Choose AWS, Microsoft Azure, or on-premises in the **Deployment Service** field.

   By default, the selected deployment service is on-premises.
4. Optionally, you can choose to provide secure authentication to deploy the containers on the remote host. If you do not want to set the secure authentication for the containers, go to step 7.
5. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
6. Click **Next**.

   The **Configuration Options** page appears.

Step 2. Provide Configuration Options

On the **Configuration options** page, provide the required information to connect to the docker image and container.

1. In the **Quick Deployment** section, enter the file name of the license key.
2. Enter the volume directory. Enter the existing directory to create tmpfs volume.
3. Specify the docker registry from where you can download the docker image. You can select the local host machine, public registry, private registry, or Informatica private registry.

   The private registry or the Informatica private registry might require additional user login credentials to connect to the registry.
4. If you selected the Informatica private registry, review the terms and conditions to download the docker image in the **User Acceptance** dialog box. To proceed with the docker image download, select **Accept**.
5. Browse for the supported docker image for the selected product.

   The installer uses the following defaults for the container name and port configurations:
   Creates a container name that matches the image tag name.

   Port used in Axon: 9999.
6. Click **Deploy**.

Configure the Docker Image in Silent Mode

You can build or run the Docker image in silent mode after updating the required properties files with the generated CI/CD inputs from the Informatica container utility.

To run the Informatica container utility in silent mode, complete the following tasks:

1. Run the Informatica container utility and choose to generate CI/CD content.
2. Configure the silent input properties file and specify the installation options.

   When you generate silent properties for CI/CD from the Informatica container utility, you can copy all the installation options and the values specified in the Informatica container utility and paste the contents into the property file for the silent installer.
3. Save the properties file in the UNIX format to the file path that contains the silent installer.
4. Run the silent installer with the silent installation properties file.

If you want to run the utility for additional images, you must save each property file before every run of the silent installer.

Running the Silent Installer

Manually copy the generated CI/CD contents when you build or run the docker image from the Informatica container utility into the supported silent properties file. The customized `SilentInput_BuildImage.properties` or `SilentInput.properties` file has different content based on whether you run the silent installer to build or run the docker image. After you configure the properties file, open a command prompt to start the silent installation.

1. Run the Informatica container utility and choose to generate CI/CD content.
2. Copy the generated CI/CD contents from the Informatica container utility into the supported silent properties file when you build or run the docker image.
3. From the terminal, go to the root of the directory that contains the installation files. For build image, navigate to the following directory: `<user_home>/appconTemp/<image name>/Gutil`. For run image, navigate to the following directory: `<user home>/appconTemp/<image name>/Gutil`

4. Verify that the directory contains the customized `SilentInput_BuildImage.properties` or `SilentInput.properties` file based on whether you build or run the docker image.
5. From the terminal, run the dos2unix command to convert the silent input properties file to the Unix format.
6. Create a log directory: `mkdir logs`
7. Run sh silentInstall.sh >> logs/<debug configure>.log.

When the silent installation is complete, you can view the log file in the directory where you extracted the utility.

Troubleshooting Docker

I tried to build the docker image, but the build image fails.

If build image fails during installer tar file extraction or before the docker build image starts, verify that adequate disk space is available in the current working directory.

If the build image fails at the step `Copy/Binaries/home/Informatica` in the log file, then there is not enough disk space in the docker configuration directory. To find the docker configuration directory, run the docker info command.

You can also free up some space from the docker configuration directory when you delete a dangling image. When you create the new build of the image but do not specify a new name, you create a dangling image and the old image becomes the dangling image. Those old images remain untagged and display "<none>" as the name when you run the docker images command.

To delete the dangling images, complete the following steps:

1. To list all dangling images and to get the image ID, run the command: docker images -f dangling=true
2. To delete each dangling image, run the command: docker image rm -f <image id>

If the build image fails with the following error, you need to manually pull the docker image:

```
Sending build context to Docker daemon 25.75GB
Step 1/30: FROM registry.access.redhat.com/rhel7:7.7
Trying to pull repository registry.access.redhat.com/rhel7 ...
Installation Status:ERROR
```

To fix the issue, you can manually run the following command:

```
docker pull registry.access.redhat.com/rhel7:7.7
```

If the build image fails with the following error, the docker build script has failed to access the repository to download dependencies:

```
This system is not registered with an entitlement server.
```

To register and subscribe the machine where you build the docker image:

1. Run the yum repolist all command to see all the repositories.
2. Use the subscription-manager to register with the following command: subscription-manager repos --enable.
3. To enable custom repositories, run the command: yum-config-manager --enable

If the build image displays the authenticationrequired error when you run the docker pull command to pull the image from RHEL, the authentication with the docker authentication might have expired. Run the docker logout command and then pull the docker image. If the issue persists, try to pull the docker image from registry.redhat.io instead of registry.access.redhat.com. If any issue remains with RHEL, you could try to use Centos7 for proof of concept cases.

Appendix A: Sample Silent Properties for CI/CD for Build Image for Axon

The following example shows the contents of the file:

```
DOWNLOAD_AND_RUN=0
HubUserName=
IMAGE_NAME=testaxon:1.0
HubPassword=
OS_NAME=registry.access.redhat.com/rhel7:7.8
AGENT_VERSION=5
INFA_REPO=0
LICENSE_KEY_LOC=/data2/EDC_Resources/abdeic_1020_All_8850.key
PRIVATE_HUB=1
INSTALL_OPTION=1
AMBARI_FILE_LOC=/data2/1040_Binaries/ambaribinariesredhat7.tar.gz
INSTALL_DPM=0
SCANNER_FILE_LOC=/data2/1040_Binaries/ScannerBinaries.zip
DPM_TAR_FILE_LOC=/data2/1040_Binaries/10.4.0_DataPrivacyManagement_Installer_linux-
x64_Build_GA.tar
productType=AXON
TAR_FILE_LOC=/misc/infastore/Axon/7.1.0/pre-prod/aio-development/4594/Axon_7.1.0_linux-x64.tar
```

Appendix B: Sample Silent Properties for CI/CD for Run Image for Axon

The following example shows the contents of the file:

```
DIS_TRUSTSTORE_FILE_PATH=
CLOUD_SUPPORT_ENABLE=0
MRS_SERVICE_NAME=
ENABLE_KERBEROS=0
DIS_DOMAIN_HOST=inaxonqa001
ADVANCE_CONFIG_PAGE_STATUS=1
MRS_USER_NAME=Administrator
APP_HTTP_PORT=9001
UPG_BACKUP_DIR=/root/Informatica/DQAGENT_HOME
DIS_SERVICE_NAME=
DIS_SSL_CUSTOM_PASSWD=
SAML_AUTHENTICATION=false
INSTALL_TYPE=0
MRS_USER_PASSWD=Administrator
ADVANCE_PORT_CONFIG=0
MRS_IS_SSL_ENABLED=0
AXON_HTTPS_ENABLED=0
DIS_IS_SSL_ENABLED=0
AXON_AGENT_VERSION=1
USER_INSTALL_DIR=/home/Informatica
DIS_USER_NAME=Administrator
MRS_IS_SSL_CUSTOM=0
AXON_USERNAME=admin@informatica.com
RULE_AUTOMATION_ENABLED=0
MRS_NODE_NAME=Node01
DIS_IS_SSL_CUSTOM=0
MRS_DOMAIN_HOST=inaxonqa001
USER=
DOMAIN_NAME=Domain
UPGRADE_WITHOUT_PC=1
ENABLE_USAGE_COLLECTION=1
DIS_NODE_NAME=Node1
DIS_USER_PASSWD=Administrator
AXON_URL=http://10.65.145.214:9999
MRS_TRUSTSTORE_FILE_PATH=
DIS_NODE_PORT=6005
DIS_SECURITY_DOMAIN=1
MRS_SECURITY_DOMAIN=1
RULE_AUTOMATION_CONNECTION_NAME=
```

```
AXON_PASSWORD=Changeme@123
PASSWORD_COMPLEXITY=false
MRS_SSL_CUSTOM_PASSWD=
MRS_NODE_PORT=6005
```

Appendix C: Sample Silent Properties for CI/CD for Build Image for Axon Agent

The following example shows the contents of the file.

```
DOWNLOAD_AND_RUN=0
HubUserName=
IMAGE_NAME=testaxonagent:1.0
HubPassword=
OS_NAME=registry.access.redhat.com/rhel7:7.8
AGENT_VERSION=5
INFA_REPO=0
LICENSE_KEY_LOC=/data2/EDC_Resources/abdeic_1020_All_8850.key
PRIVATE_HUB=1
INSTALL_OPTION=1
AMBARI_FILE_LOC=/data2/1040_Binaries/ambaribinariesredhat7.tar.gz
INSTALL_DPM=0
SCANNER_FILE_LOC=/data2/1040_Binaries/ScannerBinaries.zip
DPM_TAR_FILE_LOC=/data2/1040_Binaries/10.4.0_DataPrivacyManagement_Installer_linux-
x64_Build_GA.tar
productType=AGENT
TAR_FILE_LOC=/misc/infastore/Axon/7.1.0/pre-prod/aio-
development/4594/Axon_7.1.0_linux-x64.tar
```

Appendix D: Sample Silent Properties for CI/CD for Run Image for Axon Agent

Enter a short description of the concept here (required).

```
CHANGE_REQUEST_PORT=5000
EIC_RESOURCE_NAME=
CLOUD_SUPPORT_ENABLE=0
ENABLE_KERBEROS=0
HTTPS_PORT=
MARKETPLACE_PWD=
UPG_BACKUP_DIR=/root/Informatica/Axon
DB_PWD=
EXTERNAL_EXSISTING_POSTGRES_CONNECT_STRING=
CHANGEREQUEST_DB_PWD=
VALUELIST_DB_PWD=
HTTPS_ENABLED=0
WORKFLOW_PORT=8081
ADVANCE_PORT_CONFIG=0
DOC_UPLOAD_DB_PWD=
BULK_UPLOAD_SERVICE_PORT=7000
BULK_UPLOAD_COMMITOR_PORT=7030
EXTERNAL_EXSISTING_POSTGRES_ADMIN_PASSWD=
VALUE_LIST_PORT=7060
EXTERNAL_EXSISTING_POSTGRES_STATUS=0
UNISON_PORT=7050
DOC_UPLOAD_PORT=4000
EIC_PORT=
SATS_USERNAME=
EXTERNAL_EXSISTING_POSTGRES_DIR=
UNISON_DB_PWD=
SEGMENTATION_PWD=
SSL_CERTIFICATE=
BULK_UPLOAD_VALIDATOR_PORT=7010
SEGMENTATION_PORT=7621
CUSTOM_DATABASE_PASSWD_STATUS=0
SATS_HOST=
```

```
EXTERNAL_POSTGRES_DIR=
EIC_HOST=
ADVANCE_CONFIG_PAGE_STATUS=1
SATS_CONFIGURATION_OPTION=0
SATS_PASSWORD=
MEMCACHE_PORT=11211
HTTP_PORT=9999
EIC_CONFIGURATION_OPTION=0
EIC_NAMESPACE=
EXTERNAL_EXSISTING_POSTGRES_PORT=
SAML_AUTHENTICATION=false
INSTALL_TYPE=0
SSL_KEY=
LICENSE_KEY_LOC=/data/axon/license.key
SATS_NAMESPACE=
MSG_BROKER_PORT=5672
INSTALL_OPTION=1
NOTIFICATION_DB_PWD=
MARKETPLACE_PORT=7704
SATS_PORT=
PROCESS_CONFIGURATION_PORT=2480
BULK_UPLOAD_PREVALIDATOR_PORT=7020
EIC_PASSWORD=
USER_INSTALL_DIR=/home/Informatica
PROCESS_CONFIGURATION_PORT2=2424
PROXY_HOST_NAME_OPTION=0
KEY_LIST_FILE_LOC=/home/Informatica/config/keyFile.txt
PROXY_HOST_NAME=
EXTERNAL_POSTGRES_DB_NAME=
EXTERNAL_POSTGRES_STATUS=0
BULKUPLOAD_DB_PWD=
USER=nroot
UPGRADE_WITHOUT_PC=1
ENABLE_USAGE_COLLECTION=1
EXTERNAL_POSTGRES_HOST=
EIC_USERNAME=
EXTERNAL_EXSISTING_POSTGRES_ADMIN_USER=
IS_POSTGRES_CONNECT_STRING=0
IS_LOGGING_ENABLED=0
NOTIFICATION_PORT=3000
EXTERNAL_POSTGRES_PASSWD=
PASSWORD_COMPLEXITY=false
```

Author

Vinita Arun