How-To Library

Informatica

Purging Profile and Scorecard Results from the Profiling Warehouse

© Copyright Informatica LLC , 2021. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

When you run a profile or scorecard, the profile and scorecard results are saved in the profiling warehouse. You can delete these results from the profiling warehouse. This article discusses how to purge the profile results and scorecard results from the profiling warehouse.

Supported Versions

- Data Quality 10.2

Table of Contents

Overview. 2
Purging Profile and Scorecard Results. 2
Purge. 3
Purge Orphan Results. 5
Purging Orphan Results. 5
detectOrphanResults. 6
purgeOrphanResults. 7

Overview

When you run a profile or scorecard, the profile results or scorecard results are saved in the profiling warehouse. The Analyst service or the Developer tool retrieves the results from the profiling warehouse and displays it in the Analyst tool or Developer tool. When you run a profile or scorecard multiple times, all the results are saved in the profiling warehouse. With time, the results occupy a lot of the available memory space in the warehouse resulting in performance issues. To address the possible performance issue, you can purge the profile or scorecard results. By default, the profiling warehouse does not purge the results.

You can use one of the following methods to delete the results from the profiling warehouse.

- Run the infacmd ps Purge command. The command purges all the profile and scorecard results except for the results from the latest profile or scorecard run.
- Delete the profile or scorecard. When you delete a profile or scorecard, the infacmd ps Purge command is triggered by the Data Integration Service. The Data Integration service queues the purge task as a low priority request. The purge task is initiated after the current profile, scorecard, drill-down, and export requests are processed, or when the Data Integration Service is in the idle state.

Sometimes, after you delete or purge a profile or scorecard, the profile results or scorecard results might persist in the profiling warehouse. These results are called orphan results. You can use the infacmd ps purge OrphanResults command to purge the orphan results.

Purging Profile and Scorecard Results

You can delete the profile results and scorecard results from the profiling warehouse. Based on your requirements, you can choose the options in the infacmd ps Purge command to delete a profile or scorecard, or multiple profiles or scorecards in the profiling warehouse.

1. Open the command prompt.

2. To run infacmd commands, navigate to the `<Informatica installation directory>/isp/bin` directory on the Informatica domain or the `<Informatica installation directory>/clients/DeveloperClient/infacmd` directory in the client machine.
3. To purge the profile results for profiles and scorecards, run the infacmd ps Purge command.

Purge

Purges profile and scorecard results from the profiling warehouse. The infacmd ps Purge command purges all the profile and scorecard results except for the results from the latest profile or scorecard run.

The infacmd ps Purge command uses the following syntax:

```
Purge
<-DomainName|-dn> domain_name
[<-Gateway|-hp> gateway_name]
[<-NodeName|-nn>] node_name
<-UserName|-un> user_name
<-Password|-pd> Password
[<-SecurityDomain|-sdn> security_domain]
<-MrsServiceName|-msn> MRS_name
<-DsServiceName|-dsn> data_integration_service_name
<-ObjectType|-ot> object_type
<-ObjectPathAndName|-opn> MRS_object_path
[<-RetainDays|-rd> results_retain_days]
[<-ProjectFolderPath|-pf> project_folder_path]
[<-ProfileName|-pt> profile_task_name]
[<-Recursive|-r> recursive]
[<-PurgeAllResults|-pa> purge_all_results]
```

The following table describes infacmd ps Purge options and arguments:

Option	Argument	Description
-DomainName -dn	domain_name	Required. The name of the Informatica domain. You can set the domain name with the -dn option or the environment variable INFA_DEFAULT_DOMAIN. If you set a domain name with both methods, the -dn option takes precedence.
-Gateway -hp	gateway_name	Optional if you run the command from the Informatica installation \bin directory. Required if you run the command from another location. The gateway node name. Use the following syntax: `[Domain_Host]:[HTTP_Port]`

Option	Argument	Description
-NodeName -nn	node_name	Required. The name of the node where the Data Integration Service runs.
-UserName -un	user_name	Required if the domain uses Native or LDAP authentication. User name to connect to the domain. You can set the user name with the -un option or the environment variable INFA_DEFAULT_DOMAIN_USER. If you set a user name with both methods, the -un option takes precedence. Optional if the domain uses Kerberos authentication. To run the command with single sign-on, do not set the user name. If you set the user name, the command runs without single sign-on.
-Password -pd	Password	Required if you specify the user name. Password for the user name. The password is case sensitive. You can set a password with the -pd option or the environment variable INFA_DEFAULT_DOMAIN_PASSWORD. If you set a password with both methods, the password set with the -pd option takes precedence.
-SecurityDomain -sdn	security_domain	Required if the domain uses LDAP authentication. Optional if the domain uses native authentication or Kerberos authentication. Name of the security domain to which the domain user belongs. You can set a security domain with the -sdn option or the environment variable INFA_DEFAULT_SECURITY_DOMAIN. If you set a security domain name with both methods, the -sdn option takes precedence. The security domain name is case sensitive. If the domain uses native or LDAP authentication, the default is Native. If the domain uses Kerberos authentication, the default is the LDAP security domain created during installation. The name of the security domain is the same as the user realm specified during installation.
-MrsServiceName -msn	MRS_name	Required. The Model Repository Service name.
-DsServiceName -dsn	data_integration_service_name	Required. The Data Integration Service name
-ObjectType -ot	-	Required. Enter profile or scorecard.
-ObjectPathAndName -opn *	MRS_object_path	Optional. Do not use with ProjectFolderPath or Recursive. The path to the profile or scorecard in the Model repository. Use the following syntax: `ProjectName/FolderName/.../{SubFolder_Name/ObjectName|ProjectName/ObjectName}`
-RetainDays -rd	results_retain_days	Optional. Specifies the time range for the profile and scorecard results to be eligible for retention in the profiling warehouse. The Data Integration Service purges the rest of the profile and scorecard results. For example, if you enter -rd 10, then the results from the current day and past nine days are retained and the rest of the results are purged from the profiling warehouse.

Option	Argument	Description
-ProjectFolderPath -pf *	project_folder_path	Optional. Do not use with ObjectPathAndName or ProfileTaskName. The names of the project and folder where the profile or scorecard is stored. Use the following syntax: `ProjectName/FolderName`
-ProfileName -pt *	profile_task_name	Optional. The name of the profile task that you want to purge. If a folder has only one profile, then you can use only the ProjectFolderPath option because the ProjectFolderPath includes the name of the profile that contains the profile task. If a folder has multiple profiles in a folder, then use the ProfileName option along with the ProjectFolderPath option to specify the profile name.
-Recursive -r	recursive	Optional. Do not use with ObjectPathAndName. Applies the command to objects in the folder that you specify and its subfolders.
-PurgeAllResults -pa	purge_all_results	Optional. Set this option to purge all results for the profile or scorecard object. Use with the -recursive option to apply the command to profile and scorecard results in the folder that you specify and its subfolders.
* To run the command, you need to specify ObjectPathAndName or ProjectFolderPath or ProfileTaskName.		

Purge Orphan Results

You can detect and purge the orphan results from the profiling warehouse with the infacmd commands.

After you run a profile, the profiling warehouse stores the profile results. When you delete a profile in the Analyst tool, the Analyst service deletes the profiling results from the profiling warehouse and the metadata from the Model repository. In the Developer tool, when you open a profile and then delete the profile, the Developer tool deletes the profile results from the profiling warehouse and the metadata from the Model repository. When you delete a profile before you open it, the Developer tool removes the profile and its metadata from the Model repository, but retains the profile results in the profiling warehouse. Use the infacmd ps detectOrphanResults command to detect the orphan results, and run the infacmd ps purgeOrphanResults command to delete the orphan profile results from the profiling warehouse.

Purging Orphan Results

After you detect the orphan profile results, you can remove the orphan profile results from the profiling warehouse.

1. Open the command prompt.
2. To run infacmd commands, navigate to the `<Informatica installation directory>/isp/bin` directory on the Informatica domain or the `<Informatica installation directory>/clients/DeveloperClient/infacmd` directory in the client machine.
3. To detect the orphan results, run the infacmd.bat ps detectOrphanResults -dn <domain_name> -hp <gateway_name> -un <user_name> -pd <password> -msn <MRS_name> -dsn <data_integration_service_name> > <file_name> command.

The profiling warehouse displays the profile ID or parent ID of the profile that has orphan results on the screen. The <file_name> file contains the list of profile IDs or parent IDs of the profiles that has orphan results.

4. To verify whether the correct profile ID or parent ID for the orphan profile results is stored in the file, run the Select * from MRX_PROFILE_SUMMARY query on the Model repository.

   The SQL query returns a list of all existing profile IDs and parent IDs and it does not include the profile ID or parent ID of the profiles with orphan profile results.

5. To purge the orphan profile results from profile warehouse, run the infacmd.bat ps purgeOrphanResults -dn <domain_name> -un <user_name> -pd <password> -fpn <filePathName> command.

   The message **Creating purge jobs for orphan profile results** appears, and the profiling warehouse purges the orphan profile results.

detectOrphanResults

Detects profile results in the profiling warehouse that do not have an associated profile in the Model repository. When you delete a profile before you open it, the Developer tool or the Analyst tool removes the profile and its metadata from the Model repository. The action results in orphan profile results in the profiling warehouse. To detect the orphan profile results, you can run the infacmd ps detectOrphanResults command. To save the command output to a file, run the `infacmd ps detectOrphanResults > <filename>` command.

The infacmd ps detectOrphanResults command uses the following syntax:

```
detectOrphanResults

<-DomainName|-dn> domain_name

[<-Gateway|-hp> gateway_name]

[<-NodeName|-nn>] node_name

<-UserName|-un> user_name

<-Password|-pd> Password

[<-SecurityDomain|-sdn> security_domain]

<-MrsServiceName|-msn> MRS_name

<-DsServiceName|-dsn> data_integration_service_name
```

The following table describes infacmd ps detectOrphanResults options and arguments:

Option	Argument	Description
-DomainName -dn	domain_name	Required. The name of the Informatica domain. You can set the domain name with the -dn option or the environment variable INFA_DEFAULT_DOMAIN. If you set a domain name with both methods, the -dn option takes precedence.
-Gateway -hp	gateway_name	Optional if you run the command from the Informatica installation \bin directory. Required if you run the command from another location. The gateway node name. Use the following syntax: `[Domain_Host]:[HTTP_Port]`

Option	Argument	Description
-NodeName -nn	node_name	Required. The name of the node where the Data Integration Service runs.
-UserName -un	user_name	Required if the domain uses Native or LDAP authentication. User name to connect to the domain. You can set the user name with the -un option or the environment variable INFA_DEFAULT_DOMAIN_USER. If you set a user name with both methods, the -un option takes precedence. Optional if the domain uses Kerberos authentication. To run the command with single sign-on, do not set the user name. If you set the user name, the command runs without single sign-on.
-Password -pd	Password	Required if you specify the user name. Password for the user name. The password is case sensitive. You can set a password with the -pd option or the environment variable INFA_DEFAULT_DOMAIN_PASSWORD. If you set a password with both methods, the password set with the -pd option takes precedence.
-SecurityDomain -sdn	security_domain	Required if the domain uses LDAP authentication. Optional if the domain uses native authentication or Kerberos authentication. Name of the security domain to which the domain user belongs. You can set a security domain with the -sdn option or the environment variable INFA_DEFAULT_SECURITY_DOMAIN. If you set a security domain name with both methods, the -sdn option takes precedence. The security domain name is case sensitive. If the domain uses native or LDAP authentication, the default is Native. If the domain uses Kerberos authentication, the default is the LDAP security domain created during installation. The name of the security domain is the same as the user realm specified during installation.
-MrsServiceName -msn	MRS_name	Required. The Model Repository Service name.
-DsServiceName -dsn	data_integration_service_name	Required. The Data Integration Service name

purgeOrphanResults

Purges the orphan profile results from the profiling warehouse. You can run this command after you run the infacmd ps detectOrphanResults command to detect the orphan profile results.

The infacmd ps purgeOrphanResults command uses the following syntax:

```
purgeOrphanResults
<-DomainName|-dn> domain_name
[<-Gateway|-hp> gateway_name]
[<-NodeName|-nn>] node_name
<-UserName|-un> user_name
<-Password|-pd> Password
```

```
[<-SecurityDomain|-sdn> security_domain]

<-MrsServiceName|-msn> MRS_name

<-DsServiceName|-dsn> data_integration_service_name

<-filePathName|-fpn> filePathName
```

The following table describes infacmd ps purgeOrphanResults options and arguments:

Option	Argument	Description
-DomainName -dn	domain_name	Required. The name of the Informatica domain. You can set the domain name with the -dn option or the environment variable INFA_DEFAULT_DOMAIN. If you set a domain name with both methods, the -dn option takes precedence.
-Gateway -hp	gateway_name	Optional if you run the command from the Informatica installation \bin directory. Required if you run the command from another location. The gateway node name. Use the following syntax: `[Domain_Host]:[HTTP_Port]`
-NodeName -nn	node_name	Required. The name of the node where the Data Integration Service runs.
-UserName -un	user_name	Required if the domain uses Native or LDAP authentication. User name to connect to the domain. You can set the user name with the -un option or the environment variable INFA_DEFAULT_DOMAIN_USER. If you set a user name with both methods, the -un option takes precedence. Optional if the domain uses Kerberos authentication. To run the command with single sign-on, do not set the user name. If you set the user name, the command runs without single sign-on.
-Password -pd	Password	Required if you specify the user name. Password for the user name. The password is case sensitive. You can set a password with the -pd option or the environment variable INFA_DEFAULT_DOMAIN_PASSWORD. If you set a password with both methods, the password set with the -pd option takes precedence.
-SecurityDomain -sdn	security_domain	Required if the domain uses LDAP authentication. Optional if the domain uses native authentication or Kerberos authentication. Name of the security domain to which the domain user belongs. You can set a security domain with the -sdn option or the environment variable INFA_DEFAULT_SECURITY_DOMAIN. If you set a security domain name with both methods, the -sdn option takes precedence. The security domain name is case sensitive. If the domain uses native or LDAP authentication, the default is Native. If the domain uses Kerberos authentication, the default is the LDAP security domain created during installation. The name of the security domain is the same as the user realm specified during installation.

Option	Argument	Description
-MrsServiceName -msn	MRS_name	Required. The Model Repository Service name.
-DsServiceName -dsn	data_integration _service_name	Required. The Data Integration Service name
-filePathName -fpn	filePathName	Required. The file path with the name of the file that contains a list of profile IDs. The profile IDs map to the orphan profile results that need to be purged.

Author

Lavanya S