How-To Library

Informatica

Reading NVARCHAR and NCHAR Data from SAP Tables with a JDBC Connection in Informatica Developer

© Copyright Informatica LLC 2018, 2021. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https:// www.informatica.com/trademarks.html.

Abstract

You can run a mapping that reads NVARCHAR and NCHAR data from SAP tables with a JDBC connection. Before you can run the mapping, you must configure properties for the Data Integration Service that runs the mapping in Informatica Administrator and configure properties for Informatica Developer (the Developer tool) in the `developerCore.ini` file. This article describes the configuration tasks that you must perform before you run the mapping.

Supported Versions

- Informatica Developer 10.2.1

Table of Contents

Overview. 2
Reading NVARCHAR and NCHAR Data from SAP Tables with a JDBC Connection in Informatica Developer. . . 2

Overview

You can run a mapping that reads NVARCHAR and NCHAR data from SAP tables with a JDBC connection.

Before you can run the mapping, you must update the properties on the Data Integration Service that runs the mapping, and you must update the `developerCore.ini` file in the Informatica installation. The updated properties enable the Data Integration Service to read the NVARCHAR data as VARCHAR data and the NCHAR data as CHAR data when you run the mapping.

You can update the Data Integration Service properties in Informatica Administrator.

Reading NVARCHAR and NCHAR Data from SAP Tables with a JDBC Connection in Informatica Developer

To read NVARCHAR and NCHAR data from SAP tables with a JDBC connection, update options in Informatica Administrator and in the `developerCore.ini` file.

1. Log in to Informatica Administrator.
2. Select the Data Integration Service that will run a mapping that reads data from the SAP tables.
3. Click the **Processes** tab, and click **Edit** in the **Advanced Properties** section.
4. Add the following properties in the **JVM Command Line Options** field:

   ```
   -Dmap.nvarchar.to.varchar=true -Dmap.nchar.to.char=true
   ```
5. Click **OK** to save the changes.
6. Recycle the Data Integration Service.
7. Open the following directory:

   ```
   <Informatica installation directory>\clients\DeveloperClient
   ```

   The directory contains the `developerCore.ini` file and the `run.bat` file.
8. Add the following properties to the `developerCore.ini` file, and save the file:

   ```
   -Dmap.nvarchar.to.varchar=true
   -Dmap.nchar.to.char=true
   ```

9. Double-click the `run.bat` file to launch the Developer tool.

   You must launch the Developer tool from the `run.bat` file to complete the configuration.

When you run a mapping to read NVARCHAR and NCHAR data from SAP tables, select the Data Integration Service for which you configured the JVM options in Informatica Administrator. The Data Integration Service reads the NVARCHAR and NCHAR columns in the SAP table as VARCHAR and CHAR columns, respectively.

Author

Anu Chandrasekharan

Acknowledgements

The author would like to acknowledge Sowjanya HJ, for her technical assistance.