How-To Library

Informatica

Install Data Quality on Kubernetes with Informatica Deployment Manager 10.5.3

© Copyright Informatica LLC 2022. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

Informatica Deployment Manager provides a quick and easy way to install and manage the Informatica domain. This article describes how to install Data Quality on Kubernetes from the Docker image using Informatica Deployment Manager. This article also describes how you can use Informatica Deployment Manager to manage an existing Data Quality deployment on Kubernetes.

Supported Versions

- Data Quality 10.5.2 and 10.5.3

Table of Contents

Overview. . . . 3
Informatica Deployment Manager Process Checklist. . . . 4
Before You Begin 4
Verify System Requirements. . . . 4
Set Up the Keystore and Truststore Files. . . . 5
Contact Informatica Global Customer Support. . . . 5
Set Up Databases. . . . 6
Configure the Azure Kubernetes Service (AKS) cluster for the Informatica domain. . . . 6
Verify Kubernetes Configuration 7
Generate Content for Silent Input Properties File. . . . 7
Build the Informatica Docker Image. . . . 7
Step 1. Choose the Deployment Type. . . . 7
Step 2. Configure the Docker Image. . . . 8
Step 3. Verify the Informatica Docker Image. . . . 9
Run the Informatica Docker Image to Create a Domain. . . . 9
Step 1. Choose the Deployment Type. . . . 10
Step 2. Provide Docker and Domain Configuration Repository Information. . . . 10
Step 3. Configure the Domain. . . . 11
Step 4. Configure the Model Repository Service. . . . 12
Step 5. Configure the Data Integration Service. . . . 13
Step 6. Configure the Content Management Service. . . . 13
Step 7. Configure the Profiling Warehouse Connection Database. . . . 14
Step 8. Configure the Workflow Database Connection. . . . 15
Step 9. Configure the Analyst Service. . . . 15
Step 10. Run the Docker Image. . . . 16
Build the Docker Image in Silent Mode. . . . 17
Running the Silent Installer. . . . 17
Complete the Post-Install Tasks. . . . 18
Complete the Domain Configuration. . . . 18

Complete the Domain Integration. . . . 18
Install the Developer Tool. . . . 19
Start and Stop the Informatica Services. . . . 19
About Managing Existing Deployments. . . . 20
Manage Domains. . . . 20
Update a Domain. . . . 20
Shut Down a Domain. . . . 20
Restart a Domain. . . . 21
Download Logs from Nodes. . . . 21
Manage Nodes. . . . 22
Run a Command on a Node. . . . 22
Update the Node Startup Commands. . . . 23
Shut Down Nodes. . . . 24
Restart Nodes. . . . 24
Update the Autoscaling Parameters. . . . 25
Set Environment Variables on Nodes. . . . 25
Manage Emergency Bug Fixes (EBFs). . . . 26
View the List of EBFs. . . . 26
Apply EBFs. . . . 26
Roll Back EBFs. . . . 27

Overview

Use the web-based interface in Informatica Deployment Manager to quickly create standard Docker images and a container using Docker.

Docker is an open source platform that provides an isolated environment called containers to run the applications. Docker allows independent containers to run within a single Linux instance. A Docker image is an executable package that can run an application, a code, run-time files, environment variables, or configuration files. A container is a run-time instance of an image.

You can configure Informatica Data Quality on Kubernetes to optimize resource management and enable load balancing for the Informatica domain within the containerized environment. You can also provide horizontal scaling of pods based on the load provided on the domain.

Note: Informatica Deployment Manager supports only Azure Kubernetes Service as the Kubernetes platform.

You can use Informatica Deployment Manager to build the Docker image. You can build the Docker image with the default base or custom operating system and Informatica product binaries. With Informatica Deployment Manager, you can create containers using this Docker image to configure the Informatica domain.

When you run the Docker image, you can install Informatica products and you can create a domain.

With Informatica Deployment Manager, you can build the Docker image with the silent installer. If you want to run the silent installer, you can choose to generate the silent input properties when you go through the wizard steps, and then copy the properties directly to the silent install properties file.

Informatica Deployment Manager Process Checklist

Perform the following tasks associated with the installation:

- ❑ Plan for all installation components within the domain, such as nodes and services. For more information, see the *Installation for PowerCenter and Data Quality* guide for the Data Quality version to install.
- ❑ Complete prerequisites:
  - Verify system requirements.
  - Configure Docker engine.
  - Set up keystore and truststore files.
  - Extract Informatica Deployment Manager and access the Informatica installer .tar file.
  - Verify the license key.
  - Set up the databases.
  - Prepare for Kubernetes configuration.
  - Automate the generation of the silent input property file.
- ❑ Build the Informatica Docker image with base operating system and Informatica binaries.
- ❑ Run the Docker image to configure the Informatica domain.
- ❑ Build the Docker image in silent mode.
- ❑ Complete the post-requisites:
  - Complete the domain configuration.
  - Create the application services.
  - Install the Developer tool.

Before You Begin

Before you install Data Quality, verify that the machine meets the pre-installation requirements for the Informatica product installation.

Verify System Requirements

Verify that your environment meets the following minimum system requirements for the installation process:

- Disk space of 75 GB in the Docker build directory.
- Disk space of 40 GB in the Docker image working directory.
- If you want to use a single directory as both root directory and working directory for Docker, ensure that you allocate a disk space of 100 GB in the directory.
- Register and subscribe the machine where you build the docker images.
- Temporary disk space and permissions.
- Patch requirements.
- Sizing requirements.

Note: For more information about the temporary disk space, permission, patch, and sizing requirements, see the *Installation for PowerCenter and Data Quality* guide for the Data Quality version to install.

Set Up the Keystore and Truststore Files

When you install the Informatica services, you can configure secure communication for the domain and set up a secure connection to Informatica Administrator (the Administrator tool). If you configure the security options, you must set up the keystore and truststore files. For more information, see the *Installation for PowerCenter and Data Quality* guide for the Data Quality version to install.

Contact Informatica Global Customer Support

When you initially contact Informatica Global Customer Support for Informatica installation access, the Informatica Global Customer Support team initiates a shipping request. The shipping team sends the Informatica installation link and license information to you.

You can contact Informatica Global Customer Support online for access to the following files:

- Informatica installer .tar file
- License key
- Informatica client installation

Access to the .tar File

You require access to both the Informatica Deployment Manager and the Informatica installer.tar file to install the product.

Download and extract the Informatica Deployment Manager installer files from Informatica Marketplace.

After you extract the informatica_1052_deployment_manager.zip file, contact the support team to access the Informatica installer .tar file. You can then place the Informatica installer tar file on the machine where you build the image.

Note: The name of the folder that contains the Informatica Deployment Manager installer files must not contain any space.

To gather inputs for the silent input properties files, launch Informatica Deployment Manager and click **Generate silent properties**. You can then change the format of the properties file to UNIX before you run the silent installation.

Verify the License Key

Before you install an Informatica product using Informatica Deployment Manager, ensure that you have the license key for the product.

The Informatica product is provided as a Bring Your Own License (BYOL). Copy the license key file to a directory accessible to the user account that installs the product. You can use an existing Informatica license or contact Informatica Global Customer Support if you do not have a license key or if you have an incremental license key.

Note: You do not need a license for Informatica Deployment Manager.

Access the Informatica Client Installation

Ensure that the Informatica Global Customer Support team has provided you with access to the Informatica client installation.

Before you install the Informatica clients, verify that the machine meets the minimum system and third-party software requirements. If the machine where you install the Informatica clients is not configured correctly, the installation can fail.

Set Up Databases

Before you install Data Quality, you must set up some databases for the repositories and application services associated with Data Quality. The databases store data, metadata, and run-time results of the repositories and application services.

When you set up a database, you must ensure that the required disk space is available on the database and create the database with parameters required by Data Quality. You must also create user accounts for the databases and install the database clients.

Note: For more information about the disk space, parameters, user accounts, and clients for the databases, see the *Installation for PowerCenter and Data Quality* guide for the Data Quality version that you want to install.

To install Data Quality with all its supported application services, you must set up the following databases:

Domain configuration repository database

The domain stores configuration and user information in the domain configuration repository. You can create the domain configuration repository on an Oracle, PostgreSQL, or Microsoft SQL Server database.

Model repository database

The Model repository stores information about the metadata for the data objects and mappings in a relational database.

Reference data warehouse database

The reference data warehouse stores the data values for reference table objects that you define in a Model repository. You can create the reference data warehouse on an Oracle, Microsoft SQL Server, or PostgreSQL database.

Profiling warehouse database

The profiling warehouse stores profiling and scorecard results for the Data Integration Service. You need a profiling warehouse to perform profiling and data discovery. You can create the profiling warehouse on an Oracle or Microsoft SQL Server database.

Workflow database

The workflow database stores run-time metadata for workflows using the Data Integration Service. You can use an Oracle or Microsoft SQL Server database as the workflow database.

Exception management database

The exception management database stores exception records for Data Quality. You can use an Oracle or Microsoft SQL Server database as the exception management database.

You can either create an on-premises database or use a managed database for each repository and application service. When you run the Docker image, you must provide information about the databases.

Configure the Azure Kubernetes Service (AKS) cluster for the Informatica domain

Before you install Data Quality, you must configure the Azure Kubernetes Service (AKS) cluster to deploy, scale, and manage Docker containers and container-based applications across a cluster of container hosts.

1. Create an AKS cluster.
2. Create a Microsoft Azure storage account.
3. Create a Microsoft Azure container registry.

Verify Kubernetes Configuration

Complete the following tasks on the machine where you run Informatica Deployment Manager:

1. Install kubectl.
2. Ensure that the machine where the Informatica Deployment Manager runs can communicate with the Kubernetes cluster through the kubectl cluster-info command. The command displays information about the master and services that run in the cluster.

For more information, see the Kubernetes documentation.

Generate Content for Silent Input Properties File

When you create or build the Docker image using Informatica Deployment Manager, you can generate the property values to run the silent installer. Before you can run the silent installer, click **Generate silent properties** in Informatica Deployment Manager. Use the generated values to replace the contents of the silent input properties file. You must convert the properties file to the UNIX format before you run the silent installer.

In Informatica Deployment Manager, you can use the option to generate the silent properties to copy all the user input values entered to build or run the Docker image from a single panel. The generated contents are in the supported format of the silent install property files. Manually save the generated contents into the silent input properties file located in the silent installation directory. Convert the properties file to the UNIX format before you run the silent installation.

Build the Informatica Docker Image

Build a Docker image for Informatica products. After you build the Docker image, Informatica Deployment Manager uses the Docker image to run the containers. Ensure that the Informatica Docker image is stored in the local host or Docker registry before you install Informatica products in Docker with Informatica Deployment Manager.

Step 1. Choose the Deployment Type

On the **Deployment type** page, select the Data Quality version to deploy. Additionally, you can choose to configure secure authentication to build the Docker image on a remote host.

1. Launch Informatica Deployment Manager. You can use the Secure Sockets Layer (SSL) protocol to launch Informatica Deployment Manager in a secure way. If you choose to use SSL, you can use a custom SSL certificate or the default Informatica SSL certificate.
   - To launch without SSL, run `sh startup.sh nonssl .`
   - To launch with the default SSL certificate, run `sh startup.sh .`
   - To launch with a custom SSL certificate, run `sh startup.sh SSL <certificate location> <certificate password>` . The password must be in single quotes.

   Note: By default, Informatica Deployment Manager uses four ports that are available within the port range of 12100 to 12200. To specify a different port range, add the first port number of the required port range at the end of the startup command as shown in the following example: `sh startup.sh SSL <certificate location> <certificate password> <port number>`
2. To build the Informatica Docker image, select **Build image**.

   The **Deployment type** page appears.
3. Select the Data Quality version to deploy.
4. Optionally, choose to configure Secure Shell (SSH) protocol for secure authentication to build the image on a remote host. If you do not want to set the secure authentication, go to step 7.

5. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
6. If you want to update an existing image by applying or rolling back Emergency Bug Fixes (EBF), select the **Update existing Informatica image** check box.
7. Click **Next**.

   The **Configure Docker image** page appears.

Step 2. Configure the Docker Image

On the **Configure Docker image** page, specify details of the Docker image. The fields on the **Configure Docker image** page vary depending on whether or not you selected the **Update existing Informatica image** check box on the **Deployment type** page.

1. If you did not select the **Update existing Informatica image** check box on the **Deployment type** page, perform the following steps:
   a. Specify the base operating system to build the Docker image. If you want to build the Docker image on a custom operating system, select `Custom`, and then enter the name of the operating system.
   b. Enter the path to the Informatica installer .tar file.

      The .tar file must be present on the machine where you want to build the image. The Informatica Deployment Manager uses the tar utility to extract the installer server files to a directory on the machine.
   c. Enter the name of the Docker image.

      Default Docker image name is `informatica<product_version>:1.0`, where `1.0` is the tag name.
   d. Enter the machine working directory to build the Docker image.

      Default is `/root`.
   e. Specify whether you want to install packages to integrate the Informatica domain with Hadoop or Databricks.

      Note: This step is applicable only for Informatica Deployment Manager v10.5.3.
   f. If you choose to install packages to integrate the Informatica domain with Hadoop or Databricks, select one or more integration packages.

      Note: The integration packages must be available in the directory that contains the Informatica installer file.
2. If you chose to update an existing Docker image, perform the following steps:
   a. Specify the base operating system to build the Docker image. If you want to build the Docker image on a custom operating system, select `Custom`, and then enter the name of the operating system.
   b. Enter the name of the Docker image that you want to update.
   c. Enter the name that you want to assign to the updated Docker image.

      The image name must be in the following format: `<image_name>:<tag_name>`
   d. Enter the machine working directory to build the Docker image.

      Default is `/root`.
   e. Specify whether you want to apply or roll back an EBF from the existing Docker image.

Note: You can apply or roll back multiple EBFs together.

f. If you choose to apply an EBF, perform the following steps:

   1. Enter the path to the folder that contains the .tar files of all the EBFs that you want to apply.
   2. If you want to apply multiple EBFs in a particular order, enter the EBF IDs in the order in which they must be applied. Ensure that you enter the EBF IDs as comma-separated values.
   3. Optionally, choose to delete the backup content for the EBFs. If you delete the backup content for an EBF, users cannot roll back the EBF after you apply it.
   4. If you choose to delete the backup content, enter the ID of the EBF for which you want to disable rollback support. To specify multiple EBF IDs, enter the IDs as comma-separated values.

g. If you choose to roll back an EBF, perform the following steps:

   1. Enter the path to the folder that contains the .tar files of all the EBFs that you want to roll back.
   2. If you want to roll back multiple EBFs in a particular order, enter the EBF IDs in the order in which they must be rolled back. Ensure that you enter the EBF IDs as comma-separated values.

3. Optionally, you can choose to generate the silent properties for silent installation.

   When you generate the silent properties from Informatica Deployment Manager, you can also copy all the installation options and the values specified in the deployment manager and later paste them in the property file for the silent installer.

4. Click **Build**.

   Informatica Deployment Manager starts to build the Docker image.

After the Docker image is built, you can view the status and name of the image, along with the tasks performed by the installer in the log summary.

Step 3. Verify the Informatica Docker Image

You can verify that the Informatica image is present in the host that you specified when you built the Docker image.

To verify that the Informatica Docker image exists, enter the docker images command from the command prompt. Ensure that the values for the tag, image ID, created date, and size information appears for the Informatica Docker image.

The following sample displays the result of the docker image command:

```
{root@master abc]#docker images
REPOSITORY                    TAG        IMAGE ID       CREATED       SIZE
informatica1052               1.0        f9923fb2cfa0   20 hours ago  17.7 GB
```

Run the Informatica Docker Image to Create a Domain

You can install Informatica products by running the Docker image.

Run the Docker image to create nodes in the Informatica domain. By default, Informatica Deployment Manager creates a domain when you run the Docker image. When the domain is created, the node that you create becomes a gateway node in the domain. The gateway node contains a Service Manager that manages all the domain operations.

Step 1. Choose the Deployment Type

On the **Deployment type** page, select the Data Quality version to deploy. Additionally, you can choose to configure secure authentication to run the Docker image and deploy the product on a remote host.

1. Launch Informatica Deployment Manager. You can use the Secure Sockets Layer (SSL) protocol to launch Informatica Deployment Manager in a secure way. If you choose to use SSL, you can use a custom SSL certificate or the default Informatica SSL certificate.
   - To launch without SSL, run `sh startup.sh nonssl .`
   - To launch with the default SSL certificate, run `sh startup.sh .`
   - To launch with a custom SSL certificate, run `sh startup.sh SSL <certificate location> <certificate password>` . The password must be in single quotes.

   Note: By default, Informatica Deployment Manager uses four ports that are available within the port range of 12100 to 12200. To specify a different port range, add the first port number of the required port range at the end of the startup command as shown in the following example: `sh startup.sh SSL <certificate location> <certificate password> <port number>`
2. To run the Informatica Docker image, select **Run image**.

   The **Deployment type** page appears.
3. Select the Data Quality version to deploy.
4. Optionally, choose to configure Secure Shell (SSH) protocol for secure authentication to deploy the containers on a remote host. If you do not want to set the secure authentication, go to step 6.
5. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
6. Click **Next**.

   The **Domain details** page appears.

Step 2. Provide Docker and Domain Configuration Repository Information

In the **Domain and Docker details** section of the **Domain details** page, provide the domain configuration repository database information and the information required to connect to the Docker image.

1. Specify the Docker image name, Informatica license key file, and path to the working directory.
2. Provide the following information about the Azure Container Registry that contains the Informatica Docker image:
   - Name of the server that hosts the Azure Container Registry.
   - Login credentials of the Azure Container Registry account.
3. Provide the following information about the Azure Storage account that you want to use as shared storage for the Informatica domain:
   - Name of the account.
   - Resource group of the cluster storage account in which the Azure Storage account is created.
4. Optionally, choose to enable autoscaling for Data Integration Service.

The Horizontal Pod Autoscaler scales the number of pods in a deployment or replica set based on the CPU utilization mentioned for the CPU load factor. Kubernetes creates horizontally scalable worker nodes that are added to the grid with the Data Integration Service and Content Management Service process enabled.

Note: If you enable autoscaling for the Data Integration Service, the Model Repository Service and Data Integration Service are automatically created when you deploy the Docker image.

5. If you choose to enable autoscaling, enter the worker node, CPU utilization, and memory utilization information to autoscale:
   - **Minimum number of nodes**. The minimum number of worker nodes to create in the domain. Default is 2.
   - **Maximum number of nodes**. The maximum number of worker nodes to create in the domain. Default is 4.
   - **CPU load factor**. Kubernetes autoscales the Informatica worker nodes after monitoring the worker node and when the worker node reaches the value set for the CPU percentage metrics. Default is 75 percent.
   - **Memory load factor**. Kubernetes autoscales the Informatica worker nodes after monitoring the worker node and when the worker node reaches the value set for the memory percentage metrics. Default is 80 percent.
6. Select the database to use for the domain configuration repository, and then enter the database user account, password, and the JDBC connection string to connect to the database.

   You can use the following syntax in the JDBC connection string:
   Oracle

   ```
   jdbc:Informatica:oracle://<host name>:<port number>;ServiceName=<service
   name>;EncryptionMethod=SSL;HostNameInCertificate=<database host
   name>;ValidateServerCertificate=<true or false>
   ```

   PostgreSQL

   ```
   jdbc:Informatica:postgresql://<host name>:<port number>;DatabaseName=<database
   name>;EncryptionMethod=SSL;HostNameInCertificate=<database host
   name>;ValidateServerCertificate=<true or false>
   ```

   Microsoft SQL Server

   ```
   jdbc:Informatica:sqlserver://<host name>:<port
   number>;SelectMethod=cursor;DatabaseName=<database
   name>;EncryptionMethod=SSL;HostNameInCertificate=<database host
   name>;ValidateServerCertificate=<true or false>
   ```

Step 3. Configure the Domain

In the **Domain configuration** section of the **Domain details** page, provide the Informatica domain details, connections details for Informatica Administrator, and whether to secure communication to the domain or not. You can also specify the application services that you want to deploy with the domain.

1. Specify the domain name, user name, password, port number, and the number of gateway nodes you want in the domain. The domain name must be in lower case.

   By default, Informatica creates two gateway nodes. If the master gateway node stops working, the other gateway node becomes the master gateway node.
2. If you want to specify the number of ports that application services can use, enable advanced port configuration.
3. By default, secure communication is enabled for the Informatica domain. However, you can choose to disable it. If secure communication is enabled for the domain, specify whether to use the default Informatica SSL certificates or to use your SSL certificates to secure domain communication.

4. If you choose to provide the SSL certificates, select the keystore and truststore files and enter their passwords.
5. By default, secure HTTPS connection is enabled for Informatica Administrator. However, you can choose to disable it. If HTTPS connection is enabled for Informatica Administrator, choose to use a default keystore or a custom keystore file.
   - If you use the default keystore, the installer creates a self-signed keystore file named Default.keystore in the following location:
     `<Informatica installation directory>/tomcat/conf/`
   - If you use a custom keystore, select the keystore file and enter its password.
6. By default, Informatica Deployment Manager is configured to create all the supported application services when it deploys the Docker image. However, you can run the image without creating any application service or with only specific application services. Perform one of the following steps based on whether you want to create the application services with the domain or later:
   - To create all the supported application services, click **Next**.
   - To create only specific application services, in the **Configure the Informatica application services and connections** section, clear the check boxes for the services that you do not want to create and click **Next**.
   - To deploy Data Quality without creating any application service, clear all check boxes in the **Configure the Informatica application services and connections** section, and click **Deploy**.

   Note: If you enabled autoscaling for the Data Integration Service, the Model Repository Service and Data Integration Service are created when you deploy the Docker image.

Step 4. Configure the Model Repository Service

The Model Repository Service manages the Model repository. The service receives requests from Informatica clients and application services to store or access metadata in the Model repository. On the **Model Repository Service** page, you can configure the database for the Model repository.

1. Enter a name for the Model Repository Service.

   Default value is mrs. If you want to specify a different name for the service, consider the following guidelines:
   - The name of the service must be unique within the domain and must be in lower case. It must not exceed 128 characters or begin with the special character `@`. It must also not contain spaces or the following special characters:
     `` ` ~ % ^ * + = { } \ ; : ' " / ? . , < > | ! ( ) ] [ ``
   - You cannot change the name of the service after it is created.
2. Select the database to use for the Model repository and specify the user ID and password for the database.
3. Enter the JDBC connection string.

   You can use the following syntax in the JDBC connection string to connect to a secure database:
   Oracle

   ```
   jdbc:Informatica:oracle://<host name>:<port number>;ServiceName=<service name>
   ```

   PostgreSQL

   ```
   jdbc:Informatica:postgresql://<host name>:<port number>;DatabaseName=<database name>
   ```

   Microsoft SQL Server

   ```
   jdbc:Informatica:sqlserver://<host name>:<port
   number>;SelectMethod=cursor;DatabaseName=<database name>
   ```
4. If you select Microsoft SQL Server, you can choose to enter the schema name for the database. If you select Oracle or PostgreSQL, the installer creates the tables in the default schema.

5. Specify whether the database is secure.

   If you select the secure database option, you need to provide inputs for the qualified path to the database truststore file, truststore password, and specify the secure JDBC Parameters. By default, the value for the secure JDBC parameters is

   ```
   EncryptionMethod=SSL;HostNameInCertificate=;ValidateServerCertificate=false;
   ```

6. Click **Next** to configure additional services, or run the Docker image on page 16.

Step 5. Configure the Data Integration Service

The Data Integration Service receives requests from Informatica client tools to run integration, profile, and data preparation jobs. The service writes results to different databases and writes run-time metadata to the Model repository. On the **Data Integration Service** page, you can configure the parameters for the Data Integration Service.

1. Enter a name for the Data Integration Service.

   Default value is dis. If you want to specify a different name for the service, consider the following guidelines:

   - The name of the service must be unique within the domain and must be in lower case. It must not exceed 128 characters or begin with the special character `@`. It must also not contain spaces or the following special characters:
     ```
     ` ~ % ^ * + = { } \ ; : ' " / ? . , < > | ! ( ) ] [
     ```
   - You cannot change the name of the service after it is created.

2. Specify the communication protocol for the Data Integration Service. Default value is http.
3. Based on the protocol that you select, enter the port number to use for the service.

   If you select the **http & https** protocol, you must enter both HTTP and HTTPS port numbers. Ensure that there are minimum three unused ports between the specified HTTP and HTTPS port numbers.

4. Specify whether to use the default Informatica SSL certificates or to use your SSL certificates to secure the communication for the service.

   Note: The option to choose the SSL certificates is available only if you selected **https** or **http & https** as the communication protocol.

5. If you choose to provide the SSL certificates, select the keystore and truststore files that contain the SSL certificates and specify the passwords for the files.
6. Click **Next** to configure additional services, or run the Docker image on page 16.

Step 6. Configure the Content Management Service

The Content Management Service manages reference data for data domains that use reference tables. The service uses the Data Integration Service to run mappings to transfer data between reference tables and external data sources. On the **Content Management Service** page, you can configure the parameters for the Data Integration Service. Additionally, you can configure the database for the reference data warehouse.

1. In the **Content Management Service parameters and database** section, enter a name for the Content Management Service.

   Default value is cms. If you want to specify a different name for the service, consider the following guidelines:

   - The name of the service must be unique within the domain and must be in lower case. It must not exceed 128 characters or begin with the special character `@`. It must also not contain spaces or the following special characters:
     ```
     ` ~ % ^ * + = { } \ ; : ' " / ? . , < > | ! ( ) ] [
     ```

- You cannot change the name of the service after it is created.

2. Specify the communication protocol for the service. Default value is http.
3. Based on the protocol that you select, enter the port number to use for the service.
4. Specify whether to use the default Informatica SSL certificates or to use your SSL certificates to secure the communication for the service.

   Note: The option to choose the SSL certificates is available only if you selected **https** as the communication protocol. You can use the default SSL certificates only if the Administrator tool is also configured to use the default SSL certificates.
5. If you choose to provide the SSL certificates, select the keystore file that contains the SSL certificates and specify the password for the keystore file.
6. Select the database to use for the reference data warehouse and specify the user ID and password for the database.
7. Specify the database parameters.
   a. If you selected **Microsoft SQL Server** or **PostgreSQL**, enter the schema name for the database. If you selected **Oracle**, the installer creates the tables in the default schema.
   b. Enter the JDBC connection string.

      You can use the following syntax in the JDBC connection string to connect to a secure database:
      Oracle

      ```
      jdbc:informatica:oracle://<host name>:<port number>;ServiceName=<service name>
      ```

      PostgreSQL

      ```
      jdbc:informatica:postgresql://<host name>:<port number>;DatabaseName=<database
      name>;EncryptionMethod=SSL;HostNameInCertificate=<database host
      name>;ValidateServerCertificate=<true or false>
      ```

      Microsoft SQL Server

      ```
      jdbc:informatica:sqlserver://<host name>:<port
      number>;SelectMethod=cursor;DatabaseName=<database name>
      ```
   c. Enter the data access connection string.
8. Click **Next** to configure additional services, or run the Docker imageon page 16.

Step 7. Configure the Profiling Warehouse Connection Database

The profiling warehouse stores profiling and scorecard results for the Data Integration Service. On the **Profiling Warehouse Connection** page, you can configure the database for the profiling warehouse.

1. In the **Profiling warehouse connection database information** section, select the database to use for the profiling warehouse and specify the user ID and password for the database.
2. Specify the database parameters.
   a. If you selected **Microsoft SQL Server**, enter the schema name for the database. If you selected **Oracle**, the installer creates the tables in the default schema.
   b. Enter the JDBC connection string.

      You can use the following syntax in the JDBC connection string to connect to a secure database:
      Oracle

      ```
      jdbc:informatica:oracle://<host name>:<port number>;ServiceName=<service name>
      ```

Microsoft SQL Server

```
jdbc:informatica:sqlserver://<host name>:<port
number>;SelectMethod=cursor;DatabaseName=<database name>
```

c. Enter the data access connection string.

3. Click **Next** to configure additional services, or run the Docker image on page 16.

Step 8. Configure the Workflow Database Connection

The Data Integration Service stores run-time metadata for workflows in the workflow database. On the **Workflow Connection** page, you can set up the workflow database and configure the connection for the Data Integration service to access the workflow database.

1. In the **Workflow connection database information** section, enter a name for the workflow database connection.

   When you specify the name for the connection, consider the following guidelines:

   - The name of the connection must be unique within the domain and must be in lower case. It must not exceed 128 characters or begin with the special character `@`. It must also not contain spaces or the following special characters:
     `` ` ~ % ^ * + = { } \ ; : ' " / ? . , < > | ! ( ) ] [ ``
   - You cannot change the name of the connection after it is created.

2. Select the database type for the workflow database and specify the user ID and password for the database.
3. Specify the database parameters.
   a. If you selected **Microsoft SQL Server**, enter the schema name for the database. If you selected **Oracle**, the installer creates the tables in the default schema.
   b. Enter the JDBC connection string.

      You can use the following syntax in the JDBC connection string to connect to a secure database:
      Oracle

      ```
      jdbc:informatica:oracle://<host name>:<port number>;ServiceName=<service name>
      ```

      Microsoft SQL Server

      ```
      jdbc:informatica:sqlserver://<host name>:<port
      number>;SelectMethod=cursor;DatabaseName=<database name>
      ```

   c. Enter the data access connection string.
4. Click **Next** to configure additional services, or run the Docker image on page 16.

Step 9. Configure the Analyst Service

The Analyst Service runs the Analyst tool and manages the connections between service components and the user that has access to the Analyst tool. On the **Analyst Service** page, you can configure the parameters for the Analyst Service. Additionally, you can enable exception record management for Data Quality.

1. In the **Analyst Service** section, enter a name for the Analyst Service.

   When you specify the service name, consider the following guidelines:

   - The name of the service must be unique within the domain and must be in lower case. It must not exceed 128 characters or begin with the special character `@`. It must also not contain spaces or the following special characters:
     `` ` ~ % ^ * + = { } \ ; : ' " / ? . , < > | ! ( ) ] [ ``

- You cannot change the name of the service after it is created.

2. Choose the protocol to use for communication between the Analyst tool and Analyst Service. Default value is http.
3. Based on the protocol that you choose, enter the port number to use for the service.

   For HTTPS protocol, you must enter both HTTP and HTTPS port numbers. Ensure that there are minimum three unused ports between the specified HTTP and HTTPS port numbers.
4. Specify whether to use the default Informatica SSL certificates or to use your SSL certificates to secure the communication for the service.

   Note: The option to choose the SSL certificates is available only if you selected **HTTPS** as the communication protocol.
5. If you choose to provide the SSL certificates, select the keystore file that contain the SSL certificates and enter the password for the keystore file.
6. On the **Log Level** drop-down, select the logging level for the service.

   The logging level determines the type of messages that the Analyst Service writes to the service log when the service runs the Analyst tool.
7. If you want to enable exception record management for Data Quality, select the **Enable exception management** check-box, and then perform the following steps:
   a. Enter a name for the connection to the database that stores the exception records.
   b. Select the database to use for storing the exception records and specify the user ID and password for the database.
   c. If you selected **Microsoft SQL Server**, enter the schema name for the database. If you selected **Oracle**, the installer creates the tables in the default schema.
   d. Enter the custom JDBC connection string.

      You can use the following syntax in the JDBC connection string to connect to a secure database:
      Oracle

      ```
      jdbc:informatica:oracle://<host name>:<port number>;ServiceName=<service name>
      ```

      Microsoft SQL Server

      ```
      jdbc:informatica:sqlserver://<host name>:<port
      number>;SelectMethod=cursor;DatabaseName=<database name>
      ```
   e. Enter the data access connection string.
8. Run the Docker image on page 16.

.

Step 10. Run the Docker Image

You can run the Docker image with the default YAML files that the installer generates or you can customize the YAML files and run the image with the customized YAML files. When you customize a YAML file, the installer validates the structure of the modified file but does not validate the values that you update in the file.

You can modify the following YAML files for your Docker image:

kubernetes_deployment_pvc.yaml

kubernetes_deployment_autoscale_statefulSet.yaml

kubernetes_deployment_storage_class.yaml

kubernetes_deployment_horizontal_pod_autoscaler.yaml

kubernetes_deployment_statefulSet.yaml

1. To run the Docker image with the default YAML files, click **Deploy**.
2. To run the Docker image with customized YAML files, click **Deploy with custom YAML**.
   a. On the **Configure YAML files** page, select the YAML file that you want to modify.
   b. Modify the content of the YAML file based on your requirements, and click **Save**.
   c. Repeat steps a and b for each YAML file that you want to modify.
   d. Click **Deploy**.

The Docker image runs.

Build the Docker Image in Silent Mode

You can build the Docker image in silent mode after updating the required properties files with the generated silent properties from Informatica Deployment Manager.

To run the installer in silent mode, complete the following tasks:

1. Run Informatica Deployment Manager and choose to generate the silent properties.
2. Configure the silent input properties file and specify the installation options.

   When you generate silent properties from Informatica Deployment Manager, you can copy all the installation options and the values specified in Informatica Deployment Manager. You can then paste the copied contents into the property file for the silent installer.
3. Save the properties file in the UNIX format to the file path that contains the silent installer.
4. Run the silent installer with the silent installation properties file.

If you want to run Informatica Deployment Manager for additional images, you must save each property file before every run of the silent installer.

Running the Silent Installer

Manually copy the generated silent properties when you build the Docker image from Informatica Deployment Manager into the supported silent properties file. After you configure the properties file, open a command prompt to start the silent installation.

1. Run Informatica Deployment Manager and choose to generate the silent properties.
2. Copy the generated silent properties from Informatica Deployment Manager into the supported silent properties file when you build the Docker image.
3. From the terminal, go to the root of the directory that contains the installation files. For build image, navigate to the following directory: `<working directory>/appconTemp/<image_name>`.
4. Verify that the directory contains the customized `SilentInput_BuildImage.properties`.
5. From the terminal, run the `dos2unix` command to convert the silent input properties file to the Unix format.
6. Create a log directory: `mkdir logs`
7. Run sh silentInstall.sh >> logs/<debug configure>.log.

   Note: If you want to generate the silent input properties to update an existing image, run the `silentinstallEBF.sh file`.

When the silent installation is complete, you can view the log file in the working directory.

Complete the Post-Install Tasks

After you deploy Data Quality, perform the post-installation tasks.

Complete the Domain Configuration

To complete the domain configuration after you install the Informatica services, perform the following tasks:

- Verify locale settings and code page
- Configure Informatica environment variables
- Configure the library path environment variables
- Configure locale environment variables

Note: For more information about how to perform the tasks, see the *Installation for PowerCenter and Data Quality* guide for the Data Quality version to install.

Complete the Domain Integration

Complete the following tasks:

Update the hosts file to access the Administrator tool through the browser.

To access the Administrator tool from the clients or to communicate to the Administrator tool from the node port, enter the node external IP and pod name in the hosts file:

1. To get the node name for the pod where you created the domain, enter the following command with the pod name:
   `kubectl get pod <pod name> -o wide`

   The output displays the node name on which the pod runs. Note the node name of the pod.
2. To get the node's IP address, enter the following command with the node name:
   `kubectl get node <node name> -o wide`

   The output lists the node and the corresponding external IP. Note the external IP address of the node that has the pod running.
3. On the Windows machine, add the following entry to the hosts file in the `C:\Windows\System32\drivers\etc\hosts` path, and save the file:
   `<Node external IP> <tab or space> <pod name>`

   For example: `37.100.167.23 infaserver`

Log in to Informatica Administrator.

To connect to the Administrator tool, get the node IP on which the infaserver runs and the NodePort of the pod. To access the Administrator tool in a browser, enter the pod name followed by the NodePort number in the following format:

`http://<pod name>:<node port>`

For example, http://new-infaserver:32005

Default Administrator tool node port number is 32008.

Create the application services if you did not create them during deployment.

Create the following services and connections:

- Model Repository Service
- Data Integration Service

- Content Management Service
- Analyst Service
- Profiling warehouse connection
- Workflow connection

Note: For more information about creating the services, see the *Installation for PowerCenter and Data Quality* guide for the Data Quality version to install.

Install the Developer Tool

You can copy the Developer tool installation binaries from the Akamai link that you received when you contacted Informatica Global Customer Support for the Informatica installation tar file. Copy the files to your installation directory and install the Developer tool.

You can install the client to create data objects, create and run mappings, and create virtual databases. To install the client, perform the following tasks:

Before you install the client.

Before you install the Informatica client, verify that the minimum installation requirements are met. If the machine where you install the Informatica client is not configured correctly, the installation can fail.

Install the client.

Use the Informatica client installer to install the Developer tool.

Install languages.

To view languages other than the system locale and to work with repositories that use a UTF-8 code page, install additional languages on Windows for use with the Informatica clients.

Configure the client for a secure domain.

When you enable secure communication within the domain, you also secure connections between the domain and Informatica client applications. Based on the truststore files used, you might need to specify the location and password for the truststore files in environment variables on each client host.

Start the Developer tool.

The first time you start the Developer tool, you add the domain and connect to a Model repository. To connect to the node, you can get the host name and port number from node present on the Administrator tool.

Note: For more information about how to perform the tasks, see the *Installation for PowerCenter and Data Quality* guide for the Data Quality version to install.

Start and Stop the Informatica Services

Run infaservice.sh to start and stop the Informatica daemon.

You can start the daemon with the infaservice.sh startup command. To stop the daemon, enter the infaservice.sh shutdown command. By default, infaservice.sh is installed in the following directory:

```
<Informatica installation directory>/tomcat/bin
```

Note: If you use a softlink to specify the location of infaservice.sh, set the INFA_HOME environment variable to the location of the Informatica installation directory.

About Managing Existing Deployments

In addition to deploying Informatica Data Quality, you can also manage existing deployments of Informatica Data Quality using Informatica Deployment Manager.

You can manage and update the domains and nodes associated with existing Informatica Data Quality deployments running on Kubernetes. If Informatica releases an Emergency Bug Fix (EBF) that is applicable for the deployed product, you can also apply the EBF using Informatica Deployment Manager.

Manage Domains

You can update, shut down, and restart Informatica Data Quality domains using Informatica Deployment Manager. You can also download the logs from the nodes in a domain.

Update a Domain

You can update the gateway count and pod resources of a domain.

1. On the Informatica Deployment Manager home page, select **Manage Domain**.

   The **Manage domain** window appears.
2. On the **Domain** panel, click **Update domain**.

   The **Update domain** page appears.
3. Optionally, you can choose to configure Secure Shell (SSH) protocol for secure authentication to update the domain on a remote host. If you do not want to set the secure authentication, go to step 5.
4. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path to the host authentication key, and port number.
5. In the **Domain information** section, enter the name and working directory of the domain that you want to update.
6. Optionally, choose to update the gateway nodes, and then specify the number of gateway nodes.
7. Optionally, choose to configure the pod resources, and then update the request and maximum limit values of CPU and memory resources available for the container.
8. Click **Update**.

   The domain update starts. You can view whether the domain is updated in the log summary.

Shut Down a Domain

To run administrative tasks on a domain, you can shut down the domain. When you shut down a domain, the Service Manager on the master gateway node stops all application services and Informatica services in the domain. Any service processes running on nodes in the domain are also aborted.

1. On the Informatica Deployment Manager home page, select **Manage Domain**.

   The **Manage domain** window appears.

2. On the **Domain** panel, click **Shut down domain**.

   The **Shut down domain** page appears.

3. Optionally, you can choose to configure Secure Shell (SSH) protocol for secure authentication to shut down the domain on a remote host. If you do not want to set the secure authentication, go to step 5.

4. If you enable secure authentication, set the authentication type to **Password** or **Key**.

   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.

5. In the **Domain information** section, enter the name and working directory of the domain to shut down.

6. Click **Shut down domain**.

   The Service Manager on the master gateway node stops the application services, Informatica services, and service processes on each node in the domain and shuts down the domain. You can view whether the domain is shut down in the log summary.

Restart a Domain

You can restart a domain running on Kubernetes using Informatica Deployment Manager. When you restart a domain, the application services, Informatica services, and service processes on the gateway and worker nodes in the domain are restarted.

1. On the Informatica Deployment Manager home page, select **Manage Domain**.

   The **Manage domain** window appears.

2. In the **Domain** panel, click **Restart domain**.

   The **Restart domain** page appears.

3. Optionally, you can choose to configure Secure Shell (SSH) protocol for secure authentication to restart the domain on a remote host. If you do not want to set the secure authentication, go to step 5.

4. If you enable secure authentication, set the authentication type to **Password** or **Key**.

   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.

5. In the **Domain information** section, enter the name and working directory of the domain to restart.

6. Click **Restart domain**.

   The domain and the application services, Informatica services, and service processes running on its nodes are restarted. You can view whether the domain is restarted in the log summary.

Download Logs from Nodes

You can use Informatica Deployment Manager to download the logs form the nodes in an existing domain.

1. On the Informatica Deployment Manager home page, select **Manage Domain**.

   The **Manage domain** window appears.

2. On the **Domain** panel, click **Download logs**.

   The **Download logs** page appears.

3. Optionally, you can choose to configure Secure Shell (SSH) protocol for secure authentication to download the logs from a node on a remote host. If you do not want to set the secure authentication, go to step 5.
4. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
5. In the **Domain information** section, enter the domain name and the working directory.
6. Click **Download logs**.

The logs are downloaded as a zipped file to the domain working directory. The zipped file contains the installer and node logs. If an EBF is applied on the domain, the EBF logs are also available in the zipped file.

Manage Nodes

Informatica Deployment Manager enables you to manage the nodes in existing Informatica Data Quality domains. You can run commands on the nodes and update the node startup commands. You can also shut down and restart the nodes.

Run a Command on a Node

You can run commands on any node in a domain. You can also preview the output of the command before running it.

1. On the Informatica Deployment Manager home page, select **Manage Domain**.

   The **Manage domain** window appears.
2. On the **Node** panel, click **Run command**.

   The **Run command** page appears.
3. Optionally, you can choose to configure Secure Shell (SSH) protocol for secure authentication to run the command on a remote host. If you do not want to set the secure authentication, go to step 5.
4. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
5. In the **Command details** section, choose the nodes where you want to run the command.

   You can run the command on one node, all nodes, all gateway nodes, or all worker nodes.
6. Enter the name and working directory of the domain associated with the nodes.
7. Enter the command that you want to run.

   You can preview the output of the command in the **Command preview** section.
8. Click **Run** to run the command on the specified nodes.

Update the Node Startup Commands

You can update the commands that run when a node starts in the domain. You can update the pre-startup or post-startup commands for the nodes.

1. On the Informatica Deployment Manager home page, select **Manage Domain**.

   The **Manage domain** window appears.

2. On the **Node** panel, click **Update startup commands**.

   The **Update startup commands** page appears.

3. Optionally, you can choose to configure Secure Shell (SSH) protocol for secure authentication to update the startup commands on a remote host. If you do not want to set the secure authentication, go to step 5.

4. If you enable secure authentication, set the authentication type to **Password** or **Key**.

   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.

5. In the **Command details** section, choose the nodes for which you want to update the startup commands.

   You can update the commands for one node, all nodes, all gateway nodes, or all worker nodes.

6. Enter the name and working directory of the domain associated with the nodes.

7. From the **Command type** list, select whether the command is a pre-startup or post-startup command.

8. Choose to run the command should run only once before or after the startup.

9. Specify the updated commands.

   a. Click **Add commands**.

      The **Commands** window appears.

   b. Click **New**.

      The **New Command** window appears.

   c. Enter the command.

      The command must contain its complete executable path. You can enter multiple commands and nodes names as comma-separated values. You can also enter a regular expression followed by an asterisk (*) to imply all occurrences of the regular expression.

   d. Click **OK**.

      The **Commands** window displays the command and its details.

   e. Repeat step b through d for each command to update.

   f. Click **OK**.

10. Click **Update**.

    The startup commands are updated for the node. The updated commands run when the pod is restarted. After the pod is successfully restarted, the pre-startup commands run before the node starts and the post-startup commands run after the node starts.

Shut Down Nodes

To run administrative tasks, you can shut down a node in an existing domain. When you shut down a node, you stop Informatica services and abort all application service processes and computations running on the node.

1. On the Informatica Deployment Manager home page, select **Manage Domain**.

   The **Manage domain** window appears.
2. On the **Node** panel, click **Shut down nodes**.

   The **Shutdown Nodes** page appears.
3. Optionally, you can choose to configure Secure Shell (SSH) protocol for secure authentication to shut down the nodes on a remote host. If you do not want to set the secure authentication, go to step 5.
4. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
5. In the **Node information** section, enter the name and working directory of the node that you want to shut down.
6. Click **Shut down nodes**.

   The application services, Informatica services, and service processes are stopped on the node and the node is shut down. You can view whether the node is shut down in the log summary.

Restart Nodes

You can restart a node in an existing domain using Informatica Deployment Manager. When you restart a node, the application services, Informatica services, and service processes running on the node are restarted.

1. On the Informatica Deployment Manager home page, select **Manage Domain**.

   The **Manage domain** window appears.
2. On the **Node** panel, click **Restart nodes**.

   The **Restart nodes** page appears.
3. Optionally, you can choose to configure Secure Shell (SSH) protocol for secure authentication to restart the nodes on a remote host. If you do not want to set the secure authentication, go to step 5.
4. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
5. In the **Node information** section, enter the name and working directory of the node that you want to restart.
6. Click **Restart nodes**.

   The node and the application services, Informatica services, and service processes running on the node is restarted. You can view whether the node is restarted in the log summary.

Update the Autoscaling Parameters

You can update the autoscaling parameters, such as the number of nodes, CPU load factor, and the CPU and memory resource for existing deployments to dynamically adjust the load to meet end user demand.

1. On the Informatica Deployment Manager home page, select **Manage Domain**.

   The **Manage domain** window appears.
2. On the **Node** panel, click **Update autoscale parameters**.

   The **Update autoscale parameters** page appears.
3. Optionally, you can choose to configure Secure Shell (SSH) protocol for secure authentication to restart the nodes on a remote host. If you do not want to set the secure authentication, go to step 5.
4. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
5. In the **Autoscale information** section, enter the name and working directory of the domain.
6. Optionally, choose to specify the node limit for autoscaling, and then enter the maximum and minimum number of nodes to scale.
7. Optionally, specify the CPU load factor.
8. Optionally, update the CPU limit, memory limit, CPU request, and memory request values for the pod.
9. Click **Update**.

Set Environment Variables on Nodes

You can set additional environment variables on the nodes of an existing Informatica Data Quality domain running on Kubernetes.

1. On the Informatica Deployment Manager home page, select **Manage Domain**.

   The **Manage domain** window appears.
2. On the **Node** panel, click **Set environment variables**.

   The **Set environment variables** page appears.
3. Optionally, you can choose to configure Secure Shell (SSH) protocol for secure authentication to restart the nodes on a remote host. If you do not want to set the secure authentication, go to step 5.
4. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
5. In the **Environment variable details** section, choose the nodes on which you want to set the environment variables.

   You can run the variables on all nodes, all gateway nodes, or all worker nodes together.
6. Enter the name of the domain.

7. Specify the name and value of the variables.
   a. Click **Add variables**.

      The **Environment variables** window appears.
   b. Click **New**.

      The **New environment variable** window appears.
   c. Enter the name and value of the variable that you want to set for the domain, and click **OK**.

      The variable name and value appears on the **Environment variables** window.
   d. Repeat steps b and c for each variable that you want to set. You must also repeat steps b and c for each environment variable that is already set for the nodes. This prevents the existing variables from getting deleted.
   e. Click **OK**.
8. Click **Apply changes**.

Manage Emergency Bug Fixes (EBFs)

Informatica releases Emergency Bug Fixes (EBFs) to provide fixes for critical issues that were found in previous releases. You can use the web-based interface in Informatica Deployment Manager to apply the EBFs on an Informatica Data Quality domain running on Kubernetes. You can also use interface to roll back EBFs that are already applied to the domain.

View the List of EBFs

You can use Informatica Deployment Manager to view the list of EBFs that apply to an Informatica Data Quality domain running on Kubernetes. The list includes the EBFs that are already applied on the domain.

1. On the Informatica Deployment Manager home page, select **Manage Emergency Bug Fix (EBF)**.

   The **EBF** page appears.
2. Optionally, choose to configure Secure Shell (SSH) protocol for secure authentication to deploy the EBF on a remote host. If you do not want to set the secure authentication, go to step 4.
3. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
4. In the **EBF details** section, choose to get the list of EBF.
5. Enter the name of the domain.
6. Click **Get EBF List**.

   The list of EBFs applied on the domain appears.

Apply EBFs

You can use Informatica Deployment Manager to apply an EBF on an Informatica Data Quality domain running on Kubernetes.

1. On the Informatica Deployment Manager home page, select **Manage Emergency Bug Fix (EBF)**.

   The **EBF** page appears.

2. Optionally, choose to configure Secure Shell (SSH) protocol for secure authentication to deploy the EBF on a remote host. If you do not want to set the secure authentication, go to step 4.
3. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
4. In the **EBF details** section, choose to apply EBF.
5. Enter the name and working directory of the domain.
6. Enter the path to the folder that contains the .tar file of the EBF.
7. Enter the ID of the EBF to apply. To apply multiple EBFs, enter the EBF IDs in the order in which they are present in the `EBFs` folder of shared volume.

   Note: If you want to enter multiple EBF IDs, enter the IDs as comma-separated values.
8. Click **Apply EBF**.

   You can view the status of the EBF in the log summary.

Roll Back EBFs

You can use Informatica Deployment Manager to roll back the EBFs that are applied on an Informatica Data Quality domain running on Kubernetes.

1. On the Informatica Deployment Manager home page, select **Manage Emergency Bug Fix (EBF)**.

   The **EBF** page appears.
2. Optionally, choose to configure Secure Shell (SSH) protocol for secure authentication to deploy the EBF on a remote host. If you do not want to set the secure authentication, go to step 4.
3. If you enable secure authentication, set the authentication type to **Password** or **Key**.
   - For password type authentication, enter the machine IP address or host name, user name, password, and port to connect to the host machine.
     By default, the SSH connection uses port 22.
   - For key type authentication, enter the machine IP address or host name, user name, path of the host authentication key, and port number.
4. In the **EBF details** section, choose to roll back EBF.
5. Enter the name and working directory of the domain.
6. Enter the path to the folder that contains the .tar file of the EBF.
7. Enter the ID of the EBF that you want to roll back.

   If you want to roll back multiple EBFs in a particular order, enter the EBF IDs in the order in which they must be rolled back. Ensure that you enter the EBF IDs as comma-separated values.

   Note: To obtain the IDs of the previously applied EBFs, view the list of EBFs on page 26 applied on the domain.
8. Click **Roll back EBF**.

   You can view the status of the EBF in the log summary.

Author

Manish Goswami