How-To Library

Informatica

MDM SaaS Business Event Payloads

© Copyright Informatica LLC 2023, 2024. Informatica LLC. No part of this document may be reproduced or transmitted in any form, by any means (electronic, photocopying, recording or otherwise) without prior consent of Informatica LLC. All other company and product names may be trade names or trademarks of their respective owners and/or copyrighted materials of such owners.

Abstract

When you run Publish Business Events jobs to capture actions on business entity records, such as create, update, and delete, business event payloads are generated in JSON format. This article helps you understand these event payloads and provides some examples of payloads.

Supported Versions

- MDM SaaS May 2024

Table of Contents

Introduction. . . . 2
Event payload metadata structure. . . . 3
Event payload parameters. . . . 4
Event type and related asset parameters. . . . 4
Event metadata parameters. . . . 5
Member parameters. . . . 6
Additional parameters. . . . 7
Event payload examples. . . . 7
Create a record example. . . . 7
Update a record example. . . . 8
Delete a record example. . . . 9
Merge records example. . . . 10
Unmerge records example. . . . 12

Introduction

To capture actions on business entity records, such as create, update, and delete, you can publish business events from MDM SaaS applications to targets that Cloud Data Integration supports. To publish events, you can run a Publish Business Events job that generates an event payload in JSON format.

The payload contains parameters that represent information related to the business events. You can use the event payload to audit, track changes, generate reports, or integrate with downstream systems.

For example, you can create records in Customer 360 SaaS and propagate the records with all or some fields to a downstream billing system. Also, when you merge and unmerge records in Customer 360 SaaS, you can capture these events for processing by downstream systems. You define and run Publish Business Events jobs to publish these events. These jobs generate event payloads that contain information related to events, such as event type, asset details, contributing source records, and event metadata.

Payloads are based on the mapping of incoming fields with target fields that you define in Cloud Data Integration mapping. The payload data varies based on the business entity and the related actions that you run Publish Business Events jobs for.

Event payload metadata structure

To understand data that's published in an event payload, review the metadata structure of a payload.

Payloads have the following metadata structure:

```
{
    "type": "object",
    "id": "new_org_created:Default",
    "properties": {
        "eventType": {
            "type": "string"
        },
        "entityType": {
            "type": "string"
        },
        "entityGuid": {
            "type": "string"
        },
        "userName": {
            "type": "string"
        },
        "sourceSystem": {
            "type": "string"
        },
        "changeListId": {
            "type": "string"
        },
        "meta": {
            "type": "any"
        },
        "members": {
            "type": "array",
            "items": {
                "type": "object",
                "id": "urn:jsonschema:com:informatica:mdm:bes:service:event:Member",
                "properties": {
                    "sourceSystemId": {
                        "type": "string"
                    },
                    "sourcePKey": {
                        "type": "string"
                    },
                    "businessId": {
                        "type": "string"
                    }
                }
            }
        },
        "parent": {
            "type": "object",
            "id": "urn:jsonschema:com:informatica:mdm:bes:service:event:Parent",
            "properties": {
                "internalId": {
                    "type": "string"
                },
                "businessId": {
                    "type": "string"
                }
            }
        },
        "softDeleteHint": {
            "type": "string",
            "enum": [
                "DELETED",
                "RESTORED"
            ]
        },
        "lineageHint": {
            "type": "string",
            "enum": [
```

```
                "MERGED",
                "ACTIVATED"
            ]
        },
        "data": {
            "type": "any"
        }
    }
}
```

Event payload parameters

Event payloads are in JSON format. These payloads include an event ID and timestamp that are for internal use only. The payload also includes the "handlerData" object that contains details related to events.

The id parameter is a unique identifier of the business event that consists of 24 alphanumeric characters. The timestamp parameter contains an epoch timestamp of when the event occurred.

The handlerData object includes information about the event type and the details of assets that the event payload was published for. Also, this object includes event metadata and information about members or contributing source records.

Event type and related asset parameters

The handlerData object contains details about the event and the asset that the event is triggered for.

The following table describes the high-level event parameters in event payloads:

Parameter	Data Type	Description
eventType	String	Type of event, such as create, update, or delete. The parameter can have one of the following values: - RECORD_CREATED. Indicates that a record was created. - RECORD_UPDATED. Indicates that a record was updated or deleted. See the softDeleteHint parameter to determine whether the record was deleted. - RECORD_DELETED. Indicates that a source record was unmerged from a master record. The RECORD_CREATED and RECORD_UPDATED events occur along with the RECORD_DELETED events. - RECORD_APPROVED_CREATED. Indicates that a created record went through an approval workflow and was approved. - RECORD_APPROVED_UPDATED. Indicates that an updated or deleted record went through an approval workflow and was approved. - RECORD_APPROVED_DELETED. Indicates that a record was unmerged to form new records. The original record that's unmerged is treated as deleted. These records went through an approval workflow and were approved.
entityType	Enum	Type of asset, such as a business entity. The supported value is BusinessEntity.
entityGuid	String	Unique identifier of the asset, such as a business entity. For example, the ID of the predefined Organization business entity in Customer 360 SaaS is c360.organization. Custom assets can have default or custom IDs, such as customer.
userName	String	User name of the user who triggered the event, such as john or john.smith@abc.com.

Parameter	Data Type	Description
sourceSystem	String	Internal ID of the source system where the event occurred. For example, if the event occurred in Customer 360 SaaS, the internal ID is c360.default.system.
changeListId	String	Unique identifier to track a set of changes or changes that are part of an approval workflow, such as 87698623465834e32af8. If changes to a business entity record don't go through an approval workflow, the value is null.

Event metadata parameters

The meta object in the JSON payload contains additional metadata about the event.

The following table describes the event metadata parameters in event payloads:

Parameter	Data Type	Description
businessEntity	String	Internal ID of the business entity that the event was triggered for. For example, if an event is triggered for the Organization business entity in Customer 360 SaaS, the value is c360.organization. A custom business entity, such as Location, might not be prefixed with the name of the MDM SaaS application.
id	String	Internal identifier of the business entity record. The identifier consists of 24 alphanumeric characters, such as 6242171e87eb93605aeb80e2.
createdBy	String	User name of the user who created the asset, such as john or john.smith@abc.com.
creationDate	String	Indicates when the asset was created. The date is in epoch format, such as 1648498462137.
updatedBy	String	Indicates who updated the asset, such as john or john.smith@abc.com.
lastUpdateDate	String	Indicates when the asset was last updated. If an asset creation event is published, the last updated date and the creation date are the same. The date is in epoch format, such as 1648498462137.
modelVersion	String	Version of the asset that's associated with the business event. For example, the version of a business entity associated with a record creation event is 3. Subsequent updates to this business entity increments the model version by 1. If another record creation event occurs following an update to the business entity, the version is incremented to 4.
states	Object	Lists the states of the record. The object can contain the following parameters: base, consolidation, createMode, searchIndex, validation, and xref_consolidation.
base	Enum	Indicates whether a record is in the active or deleted state. The parameter can have one of the following values: ACTIVE or DELETED
consolidation	Enum	For internal use only.
createMode	Enum	Indicates how a record was created. Currently, the value can only be REGULAR.
searchIndex	Enum	For internal use only.

Parameter	Data Type	Description
validation	Enum	Validation status of the record. If error handling isn't enabled for your environment, the status is PENDING. When error handling is enabled for your environment, the parameter can have one of the following values: - VALID. Record has no errors and is valid. - INVALID. Record has validation errors. - PENDING. Record is not validated or the record is pending validation.
xref_consolidation	Enum	For internal use only.
businessId	String	Unique identifier of the record, such as MDM00000016V7K.
status	Enum	Status of the record that indicates whether a record is active or inactive. For example, during a merge operation, two records are active, but after they merge, a new active record is created, and the existing records become inactive. The parameter can have one of the following values: ACTIVE or INACTIVE

Member parameters

The members object in the JSON payload contains details about contributing source records of the event. When multiple records merge, a new record is created. The event payload associated with the new record can have multiple contributing source records within the members object.

The following table describes the parameters related to contributing records in event payloads:

Parameter	Data Type	Description
sourceSystemId	String	Internal ID of the source system that the source record belongs to. For example, if the source system is Informatica Customer 360, the internal ID is c360.default.system. The source record can also be from a system other than the default source system with an internal ID, such as sfdc. The internal ID of source systems other than default source systems might not have the prefix c360.
sourcePKey	String	Primary key of the source record that was used to load the record into the MDM SaaS data store, such as 6242171e87eb93605aeb80e3.
businessId	String	Unique identifier of the source record, such as MDM00000016V7K.

Additional parameters

Additional parameter values are available for merge, unmerge, and delete operations.

The following table describes the additional event parameters in event payloads:

Parameter	Data Type	Description
parent	Object	An object with two record identifier parameters. When records merge, the new master record that's created becomes the parent of the contributing records. Records for which a create event is published don't have a parent and the parameter value is null. The parent object contains the following parameters of the parent record: - internalId. Internal identifier of the new master record that records merge into, such as 6242171e87eb93605aeb80e2. - businessId. Unique identifier of the new master record that records merge into, such as MDM00000016V7K.
softDeleteHint	Enum	Indicates whether a record is active or soft-deleted. You can restore soft-deleted records. The parameter can have one of the following values: DELETED or RESTORED For example, when you delete a record from an MDM SaaS business application, the record is soft-deleted and exists in the system. In this case, the value of the eventType parameter is RECORD_UPDATED and the value of the softDeleteHint parameter is DELETED.
lineageHint	Enum	Indicates whether lineage exists when merge or unmerge operations result in create, update, or delete events. The parameter can have the following values: - MERGED. Indicates that an update event merged a record with other records. The record is part of the lineage of another record it merged into. - ACTIVATED. Indicates that an update event unmerged a record from another record and activated the record as a separate record. When multiple records are merged, a new master is created. A create event is published for the new master record and update events are published for the records that are merged. The lineageHint parameter value for these update events is MERGED. When you unmerge a record, the original master record is hard-deleted, a new master record is created, and the original master record evolves into an updated master record. The lineageHint parameter value for the update event is ACTIVATED. The lineageHint parameter value for create and delete events is NULL indicating that these records don't have a lineage.
data	String	Contains all the field values of a business entity record.

Event payload examples

To understand the structure and content of event payloads that Publish Business Events jobs create, review the event payload examples for the create, update, delete, merge, and unmerge operations.

Create a record example

You create a record in MDM SaaS and add only one field value, ABC Inc. In the event payload, the event type is RECORD_CREATED. The record is assigned the business ID MDM00000016V7K and is active. The data object includes the only field value, ABC Inc, that the record contains.

The following sample shows the payload for a create event:

```
{
            "id": "6242171f87eb93605aeb80e7",
            "timestamp": 1648498463276,
            "handlerData": {
```

```
            "eventType": "RECORD_CREATED",
            "entityType": "BusinessEntity",
            "entityGuid": "c360.organization",
            "userName": "john",
            "sourceSystem": "c360.default.system",
            "changeListId": null,
            "meta": {
                "businessEntity": "c360.organization",
                "id": "6242171e87eb93605aeb80e2",
                "createdBy": "john",
                "creationDate": 1648498462137,
                "updatedBy": "john",
                "lastUpdateDate": 1648498462137,
                "modelVersion": "3",
                "states": {
                    "base": "ACTIVE",
                    "consolidation": "MATCH_DIRTY",
                    "createMode": "REGULAR",
                    "searchIndex": "SEARCH_DIRTY"
                    "validation": "PENDING",
                    "xref_consolidation": "MATCH_DIRTY"
                },
                "businessId": "MDM00000016V7K",
                "status": "ACTIVE"
            },
            "members": [
                {
                    "sourceSystemId": "c360.default.system",
                    "sourcePKey": "6242171e87eb93605aeb80e3",
                    "businessId": "MDM00000016V7K"
                }
            ],
            "parent": null,
            "softDeleteHint": null,
            "lineageHint": null,
            "data": {
                "name": "ABC Inc"
            }
        }
    }
```

Update a record example

You edit a record in MDM SaaS. In the event payload, the event type is RECORD_UPDATED. The record remains active and the business ID of the record remains the same. A patch record is added to reflect the edited data.

The following sample shows the payload for an update event:

```
{
            "id": "654ab4540b0f3029855d3895",
            "timestamp": 1699394644869,
            "handlerData": {
                "eventType": "RECORD_UPDATED",
                "entityType": "BusinessEntity",
                "entityGuid": "c360.organization",
                "userName": "john",
                "sourceSystem": "c360.default.system",
                "changeListId": null,
                "meta": {
                    "businessEntity": "c360.organization",
                    "id": "6242171e87eb93605aeb80e2",
                    "createdBy": "john",
                    "creationDate": 1648498462137,
                    "updatedBy": "john",
                    "lastUpdateDate": 1699394644659,
                    "modelVersion": "3",
                    "states": {
                        "base": "ACTIVE",
                        "consolidation": "MATCH_DIRTY",
```

```
                        "createMode": "REGULAR",
                        "searchIndex": "SEARCH_DIRTY",
                        "validation": "PENDING",
                        "xref_consolidation": "MATCH_DIRTY"
                    },
                    "businessId": "MDM00000016V7K",
                    "status": "ACTIVE"
                },
                "members": [
                    {
                        "sourceSystemId": "c360.default.system",
                        "sourcePKey": "6242171e87eb93605aeb80e3",
                        "businessId": "MDM00000016V7K"
                    },
                    {
                        "sourceSystemId": "c360.default.system",
                        "sourcePKey": "ex654ab42f0b0f3029855d388d",
                        "businessId": "MDM0000006JRNL"
                    }
                ],
                "parent": null,
                "softDeleteHint": null,
                "lineageHint": null,
                "data": {
                    "numberOfEmployees": 10000,
                    "name": "ABC Inc"
                }
            }
        }
```


Delete a record example

You delete a record in MDM SaaS. In the event payload, the event type is RECORD_UPDATED. The base state and the softDeleteHint parameters of the record are set to DELETED.

The following sample shows the payload for a delete event:


```
{
            "id": "654ab4ca0b0f3029855d38ad",
            "timestamp": 1699394762603,
            "handlerData": {
                "eventType": "RECORD_UPDATED",
                "entityType": "BusinessEntity",
                "entityGuid": "c360.organization",
                "userName": "john",
                "sourceSystem": null,
                "changeListId": null,
                "meta": {
                    "businessEntity": "c360.organization",
                    "id": "6242171e87eb93605aeb80e2",
                    "createdBy": "john",
                    "creationDate": 1648498462137,
                    "updatedBy": "john",
                    "lastUpdateDate": 1699394741476,
                    "modelVersion": "3",
                    "states": {
                        "base": "DELETED",
                        "consolidation": "MATCH_DIRTY",
                        "createMode": "REGULAR",
                        "searchIndex": "SEARCH_INDEXED",
                        "validation": "PENDING",
                        "xref_consolidation": "MATCH_DIRTY"
                    },
                    "businessId": "MDM00000016V7K",
                    "status": "ACTIVE"
                },
                "members": null,
                "parent": null,
                "softDeleteHint": DELETED,
```

```
                "lineageHint": null,
                "data": null
            }
        }
    }
```


Merge records example

You merge records with the business IDs MDM00000016V7K and MDM00000016V7L. When the records merge, a new record is created with the business ID MDM00000016V7K, and the existing records become inactive. If you configured Publish Business Events jobs for create and update events, a create event and two update events are published when the records merge. The create event is published for the new master record and the update events are published for each record that is merged.

The new master record is created with the business ID of the record that's considered the surviving record. The payload of this create event also contains the members object with the business ID, primary key, and source system ID of the two records that are merged.

The payload of the update events contains the business ID of the new master record, MDM00000016V7K, in the parent object. The lineageHint is set to MERGED.

The following sample shows the payload for the create event associated with a sample merge operation that results in a new master record:


```
{
            "id": "6242192587eb93605aeb80f6",
            "timestamp": 1648498981005,
            "handlerData": {
                "eventType": "RECORD_CREATED",
                "entityType": "BusinessEntity",
                "entityGuid": "c360.organization",
                "userName": "john",
                "sourceSystem": null,
                "changeListId": null,
                "meta": {
                    "businessEntity": "c360.organization",
                    "id": "6242192487eb93605aeb80ee",
                    "createdBy": "john",
                    "creationDate": 1648498979873,
                    "updatedBy": "john",
                    "lastUpdateDate": 1648498979873,
                    "modelVersion": "3",
                    "states": {
                        "base": "ACTIVE",
                        "consolidation": "MATCH_DIRTY",
                        "searchIndex": "SEARCH_DIRTY"
                    },
                    "businessId": "MDM00000016V7K",
                    "status": "ACTIVE"
                },
                "members": [
                    {
                        "sourceSystemId": "c360.default.system",
                        "sourcePKey": "6242171e87eb93605aeb80e3",
                        "businessId": "MDM00000016V7K"
                    },
                    {
                        "sourceSystemId": "c360.default.system",
                        "sourcePKey": "6242172d87eb93605aeb80e9",
                        "businessId": "MDM00000016V7L"
                    }
                ],
                "parent": null,
                "softDeleteHint": null,
                "lineageHint": null,
                "data": {
                    "name": "AMD Inc"
```

```
                }
            }
        }
```

The following table contains the payloads for the update events associated with a sample merge operation:

Contributor Record	Contributor Record

<pre>{
"id": "6242192587eb93605aeb80f8",
"timestamp": 1648498981634,
"handlerData": {
"eventType": "**RECORD_UPDATED**",
"entityType": "BusinessEntity",
"entityGuid": "c360.organization",
"userName": "john",
"sourceSystem": null,
"changeListId": null,
"meta": {
"businessEntity": "c360.organization",
"id": "6242172d87eb93605aeb80e8",
"createdBy": "john",
"creationDate": 1648498477789,
"updatedBy": "john",
"lastUpdateDate": 1648498979873,
"modelVersion": "3",
"states": {
"base": "ACTIVE",
"consolidation": "MATCH_DIRTY",
"searchIndex": "SEARCH_DIRTY"
},
"businessId": "MDM00000016V7L",
"status": "INACTIVE"
},
"members": [
{
"sourceSystemId": "c360.default.system",
"sourcePKey": "6242172d87eb93605aeb80e9",
"businessId": "**MDM00000016V7L**"
}
],
"**parent**": {
"**internalId**": "**6242192487eb93605aeb80ee**",
"**businessId**": "**MDM00000016V7K**"
},
"softDeleteHint": null,
"lineageHint": "**MERGED**",
"data": {
"name": "AMD Inc"
}
}
}</pre>
	<pre>{
	"id": "6242192587eb93605aeb80fa",
	"timestamp": 1648498981932,
	"handlerData": {
	"eventType": "**RECORD_UPDATED**",
	"entityType": "BusinessEntity",
	"entityGuid": "c360.organization",
	"userName": "john",
	"sourceSystem": null,
	"changeListId": null,
	"meta": {
	"businessEntity": "c360.organization",
	"id": "6242171e87eb93605aeb80e2",
	"createdBy": "john",
	"creationDate": 1648498462137,
	"updatedBy": "john",
	"lastUpdateDate": 1648498979873,
	"modelVersion": "3",
	"states": {
	"base": "ACTIVE",
	"consolidation": "MATCH_DIRTY",
	"searchIndex": "SEARCH_DIRTY"
	},
	"businessId": "MDM00000016V7K",
	"status": "INACTIVE"
	},
	"members": [
	{
	"sourceSystemId": "c360.default.system",
	"sourcePKey": "6242171e87eb93605aeb80e3",
	"businessId": "**MDM00000016V7K**"
	}
	],
	"**parent**": {
	"**internalId**": "**6242192487eb93605aeb80ee**",
	"**businessId**": "**MDM00000016V7K**"
	},
	"softDeleteHint": null,
	"lineageHint": "**MERGED**",
	"data": {
	"name": "ABC Inc"
	}
	}
	}</pre>

Unmerge records example

You unmerge a record with the business ID MDM00000016V7L that was previously merged into the master record with the business ID MDM00000016V7K. This action hard-deletes the original master record and the contributor record that you unmerge. The unmerge operation results in two master records with the business IDs MDM00000016V7L and MDM00000016V7K.

The creation of the master record with the ID MDM00000016V7L publishes a create event. The creation of the master record with the ID MDM00000016V7K publishes an update event. The new master record with the ID MDM00000016V7K doesn't have the record with the ID MDM00000016V7L as the contributor record.

Note: This example is for informational purposes only. We don't recommend the use of events related to unmerge operations for auditing this operation.

The following table contains the payloads for the delete events associated with a sample unmerge operation:

Original Master Record	Contributor to the Original Master Record

<pre>{
"id": "6242219d87eb93605aeb80ff",
"timestamp": 1648501149088,
"handlerData": {
"eventType": "**RECORD_DELETED**",
"entityType": "BusinessEntity",
"entityGuid": "c360.organization",
"userName": "john",
"sourceSystem": null,
"changeListId": null,
"meta": {
"businessEntity":
"c360.organization",
"id": "6242192487eb93605aeb80ee",
"createdBy": "john",
"creationDate": 1648498979873,
"updatedBy": "john",
"lastUpdateDate": 1648498979873,
"modelVersion": "3",
"states": {
"base": "ACTIVE",
"consolidation": "MATCH_DIRTY",
"searchIndex": "SEARCH_INDEXED"
},
"businessId": "**MDM00000016V7K**",
"status": "**ACTIVE**"
},
"members": null,
"parent": null,
"softDeleteHint": null,
"lineageHint": null,
"data": null
}
}</pre>
	<pre>{
	"id": "6242219d87eb93605aeb8101",
	"timestamp": 1648501149095,
	"handlerData": {
	"eventType": "**RECORD_DELETED**",
	"entityType": "BusinessEntity",
	"entityGuid": "c360.organization",
	"userName": "john",
	"sourceSystem": null,
	"changeListId": null,
	"meta": {
	"businessEntity":
	"c360.organization",
	"id": "6242172d87eb93605aeb80e8",
	"createdBy": "john",
	"creationDate": 1648498477789,
	"updatedBy": "john",
	"lastUpdateDate": 1648498979873,
	"modelVersion": "3",
	"states": {
	"base": "ACTIVE",
	"consolidation": "MATCH_DIRTY",
	"searchIndex": "SEARCH_INDEXED"
	},
	"businessId": "**MDM00000016V7L**",
	"status": "**INACTIVE**"
	},
	"members": null,
	"parent": null,
	"softDeleteHint": null,
	"lineageHint": null,
	"data": null
	}
	}</pre>

The following table contains the payloads for the create and update events associated with a sample unmerge operation:

New Master Record	Original Master Record with Updates

<pre>{
"id": "6242219d87eb93605aeb8103",
"timestamp": 1648501149461,
"handlerData": {
"eventType": "**RECORD_CREATED**",
"entityType": "BusinessEntity",
"entityGuid": "c360.organization",
"userName": "john",
"sourceSystem": null,
"changeListId": null,
"meta": {
"businessEntity":
"c360.organization",
"id": "6242219c87eb93605aeb80fc",
"createdBy": "john",
"creationDate": 1648501148633,
"updatedBy": "john",
"lastUpdateDate": 1648501148633,
"modelVersion": "3",
"states": {
"base": "ACTIVE",
"consolidation": "MATCH_DIRTY",
"searchIndex": "SEARCH_DIRTY"
},
"businessId": "**MDM00000016V7L**",
"status": "**ACTIVE**"
},
"members": [
{
"sourceSystemId":
"c360.default.system",
"sourcePKey":
"6242172d87eb93605aeb80e9",
"businessId": "**MDM00000016V7L**"
}
],
"parent": null,
"softDeleteHint": null,
"lineageHint": null,
"data": {
"name": "Banana Ltd"
}
}</pre>
	<pre>{
	"id": "6242219d87eb93605aeb8105",
	"timestamp": 1648501149521,
	"handlerData": {
	"eventType": "**RECORD_UPDATED**",
	"entityType": "BusinessEntity",
	"entityGuid": "c360.organization",
	"userName": "john",
	"sourceSystem": null,
	"changeListId": null,
	"meta": {
	"businessEntity":
	"c360.organization",
	"id": "6242171e87eb93605aeb80e2",
	"createdBy": "john",
	"creationDate": 1648498462137,
	"updatedBy": "john",
	"lastUpdateDate": 1648501148633,
	"modelVersion": "3",
	"states": {
	"base": "ACTIVE",
	"consolidation": "MATCH_DIRTY",
	"searchIndex": "SEARCH_DIRTY"
	},
	"businessId": "**MDM00000016V7K**",
	"status": "**ACTIVE**"
	},
	"members": [
	{
	"sourceSystemId":
	"c360.default.system",
	"sourcePKey":
	"6242171e87eb93605aeb80e3",
	"businessId": "**MDM00000016V7K**"
	}
	],
	"parent": null,
	"softDeleteHint": null,
	"lineageHint": "**ACTIVATED**",
	"data": {
	"name": "Apple Ltd"
	}
	}</pre>

Author

Documentation team