How-To Library

Informatica

# Using the Security Configuration Utility in Multidomain MDM

© Copyright Informatica LLC 2016, 2021. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html

# Abstract

You can use the security configuration utility to manage some of the security settings in an MDM Hub implementation. Use the utility to change the hashing algorithm used in the MDM Hub, change the certificate provider and reset the passwords of the MDM Hub users. You can also use the security configuration utility to update the customer hashing key, which is also called the pepper value. This article explains how to use the security configuration utility.

# Supported Versions

- Multidomain MDM 10.2
- Multidomain MDM 10.3

# Table of Contents

Overview. . . . . 2
Before You Run the Utility. . . . . 2
Changing the Hashing Algorithm. . . . . 3
Changing the Certificate Provider. . . . . 3
Updating the Customer Hashing Key. . . . . 4
Resetting a Password. . . . . 4

# Overview

Use the security configuration utility to manage some of the security settings in an MDM Hub implementation. The utility makes it easier for you to manage how users access the MDM Hub.

Use the security configuration utility to perform the following tasks:

- Change the hashing algorithm that is used for password hashing.
- Change the certificate provider that is used for authentication.
- Change the customer hashing key that is used to create the hashing algorithm.
- Reset a password for a user in the MDM Hub.

**Note:** After each task, restart the application server for the changes to take effect.

# Before You Run the Utility

To get the security configuration utility, contact Informatica Global Customer Support.

Before you run the security configuration utility for the first time, perform the following tasks:

1. Unzip the SecurityUtility.zip
2. Add the following Hub Server properties to the `cmxserver.properties` file:
   - mdm.mail.server.host=<smtp-host>
   - mdm.mail.server.port=<smtp-port>
   - mdm.mail.server.user=<adminuser@domain.com>
   - mdm.mail.server.password=*******

- mdm.mail.server.smtpauth=true
- mdm.mail.server.ttls=true

**Note:** For more information about Hub Server properties, see the *Informatica MDM Multidomain Edition Configuration Guide*.

3. If you add more custom properties to the `cmxserver.properties` file for a mail client, add the property with the following prefix:

   ```
   mdm.mail.server.props
   ```

4. Update the `securityConfig.properties` file. The securityConfig.properties file is in the following directory:
   `<MDM Hub installation directory>/server/resources`

   **Note:** If you want to skip the mail connection test when you start the utility, set the property `verify.mail.off` to `true` in the `securityConfig.properties` file. If you disable the property, it checks the email configuration is correct and sends a test mail to the user configured in cmxserver.properties.

# Changing the Hashing Algorithm

The MDM Hub uses a password hashing method to protect user passwords. How passwords are hashed depends upon the specified hashing algorithm and also requires a certificate provider. You can reconfigure the hashing algorithm that is used for password hashing in the MDM Hub. Reconfiguring the hashing algorithm automatically resets the passwords of all the MDM Hub users.

Before you implement a custom hashing algorithm, you must implement the Java abstract class `com.siperian.sam.security.hashing.algorithms.HashAlgorithm` in the `siperian-server-hash.jar` file, which is in the following directory:

```
<MDM Hub installation directory>/server/lib/hashing
```

1. In the security configuration utility, enter `2` to configure the hashing algorithm.
2. Enter the name of the algorithm to configure.

   For example, enter `SHA3`.
3. Enter the implementation class name, which is the canonical, or fully qualified, class name.
   For example, enter `$HASHING_CLASS_NAME$`.
4. Optionally, if you use a custom hashing algorithm, enter the file path location of the hashing algorithm archive.

   **Note:** The hashing algorithm archive must be a ZIP file. If the archive contains multiple JAR files and other supporting files, ensure they are all in the ZIP file.

The security configuration utility sends the new passwords to the associated email address of each user account. For more information about password hashing, see the *Informatica Multidomain MDM Security Guide* and the *Informatica Multidomain MDM Configuration Guide*.

# Changing the Certificate Provider

You can change the certificate provider that is used for authentication of trusted applications in the MDM Hub.

1. In the security configuration utility, enter `3` to change the certificate provider.
2. Optionally, if you use a custom implementation, enter the class name of the certificate.
3. Optionally, if you use a custom implementation, enter the file path location of the certificate provider archive.

   **Note:** The certificate provider archive must be a JAR file. If you use a custom certificate provider, ensure the `<MDM Hub installation directory>/server/resources/certificate` directory is empty.

The security configuration utility initializes the keystore and certificates for the trusted applications. To implement the provider, you must implement a `PKIUtil.java` interface in the `siperian-server-pkiutil.jar` file.

## Updating the Customer Hashing Key

You can use the security configuration utility to update the customer hashing key, also called the pepper value. Updating the hashing key automatically resets the passwords of all the MDM Hub users. Use a hashing key that contains a sequence of up to 32 hexadecimal characters with no delimiters.

1. In the security configuration utility, enter `4` to change the customer hashing key.
2. Enter a new value.

   **Important:** Protect the secrecy of the key. If the value of the custom hashing key is lost, you must reset all user passwords.

## Resetting a Password

You can reset the password for a user account in the MDM Hub.

In the Hub Console ensure that the user account associates with an email address before you reset the password.

**Note:** You must set the email address for the `admin` user account manually in the CMX_SYSTEM.C_REPOS_USER table of the database.

1. In the security configuration utility, enter `1` to reset a password.
2. To reset a password, enter the user name of the user whose password you want to reset. If you want to reset password for multiple users, enter the user names separated by commas.

   For example, to reset the passwords of users jsmith and bbecker, enter `jsmith,bbecker`.

The new passwords for the specified user accounts appear. The security configuration utility sends the new passwords to the associated email address of each user account.

## Author

**Documentation Team**