How-To Library

Informatica

Address Verification Best Practices for Israel

© Copyright Informatica LLC 2022. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

This document tells you how to connect the elements in an Israel address to the appropriate address elements in Informatica Address Verification. This document also describes best practices that you can implement when you verify addresses in Israel.

Supported Versions

- Informatica Address Verification 3.0 and 4.0
- Informatica Address Verification (On-Premises) 5.x

Table of Contents

Introduction. . . . 2
Process Modes. . . . 2
Character Set. . . . 3
Address Format and Address Structure. . . . 3
Key Address Elements. . . . 3
Mapping Input Address Data to Address Elements. . . . 3
Input and Result XML in Address Verification (On-Premises). . . . 4
Input and Result XML in Address Verification. . . . 5
Address Enrichments. . . . 6
Multilanguage Support for Israel Addresses. . . . 6
Frequently Asked Questions. . . . 7
Reference Address Databases. . . . 7
Additional Documentation Resources. . . . 8

Introduction

Informatica Address Verification can validate and enhance addresses in Israel. This how-to article provides you with configuration information and best practices that you can follow to get the most from the addresses. The best practices include advice on how to select the appropriate XML elements for Israel address data.

To verify the quality of an input address, Address Verification compares the address information to the data in one or more reference data files. You can configure Address Verification to analyze the different types of address information in the input data. You must map each item of address information to an appropriate element in Address Verification.

When you select the input address elements, you must ensure that the elements are correct for the different types of input information. The country that the address identifies determines the elements that you need.

Process Modes

Informatica Address Verification supports the following process modes for Israel addresses:

- BATCH
- COUNTRY RECOGNITION
- FAST COMPLETION

- INTERACTIVE
- PARSE

Character Set

Israel reference address databases store address data in the Hebrew, Latin, and Latin-1 scripts. By default, Informatica Address Verification returns the verified Israel addresses in the Hebrew script.

Address Format and Address Structure

You improve the performance of Address Verification when you define the input address in the format that the postal service expects.

The Israel postal service recognizes the following structure for a postal address:

```
Line 1: RECIPIENT OR CONTACT NAME
Line 2: [HOUSE NUMBER] STREET
Line 3: POSTAL CODE CITY
Line 4: COUNTRY
```

The following sample address shows the address in the Latin script:

```
Mr. Ploni Almoni
24, Jaffa
9414201 JERUSALEM
ISR
```

The following sample address shows the address in the Hebrew script:

```
מר פלוני אלמוני
24, יפו
9414201 ירושלים
ISR
```

Key Address Elements

Address Verification is unlikely to verify an address successfully if one of the following items is absent from the address:

- Locality
- Postal Code
- Street

Mapping Input Address Data to Address Elements

To verify an address, map the input address information to appropriate elements in Address Verification.

The following table shows how you can map the input address to the address elements:

Information Type	Address Information	Address Elements
Street Name	JAFFA	Street
House Number	24	HouseNumber

Information Type	Address Information	Address Elements
Postal Code	9414201	PostalCode
City	JERUSALEM	Locality
Country	ISRAEL	Country

Input and Result XML in Address Verification (On-Premises)

The following example shows how you can map the address information to the XML address elements in Address Verification (On-Premises).

You enter the following input address:

```
<InputData>
    <AddressElements>
        <Country Item="1" Type="NAME">ISR</Country>
    </AddressElements>
    <AddressLines>
        <FormattedAddressLine Line="1">24, JAFFA</FormattedAddressLine>
        <FormattedAddressLine Line="2">9414201 JERUSALEM</FormattedAddressLine>
    </AddressLines>
</InputData>
```

Informatica Address Verification (On-Premises) returns the following result:

```
<?xml version="1.0" encoding="UTF-16"?>

<!-- EngineVersion="5.16.2.60959" -->

<Result     ProcessStatus="V4"
     ModeUsed="BATCH"
     Count="1"
     CountOverflow="NO"
     CountryISO3="ISR"
     PreferredScript="DATABASE"
     PreferredLanguage="DATABASE">

<ResultData ResultNumber="1"
     MailabilityScore="5"
     ResultPercentage="100.00"
     ElementResultStatus="F0F000F0F000000000E0"
     ElementInputStatus="60600060600000000060"
     AddressResolutionCode="00000000000000000000"
     ExtElementStatus="00000000000000000000"
     ElementRelevance="10100010100000000010"
     AddressType="S"
     LanguageISO3="???">
    <AddressElements>
        <Country Type="NAME_EN" Item="1">Israel</Country>
        <Locality Item="1">Jerusalem</Locality>
        <PostalCode Item="1">9414201</PostalCode>
        <Street Item="1">Jaffa</Street>
        <Number Item="1">24</Number>
    </AddressElements>
    <AddressLines>
        <DeliveryAddressLine Line="1">24, Jaffa</DeliveryAddressLine>
        <CountrySpecificLocalityLine Line="1">9414201 Jerusalem</CountrySpecificLocalityLine>
        <FormattedAddressLine Line="1">24, Jaffa</FormattedAddressLine>
        <FormattedAddressLine Line="2">9414201 Jerusalem</FormattedAddressLine>
        <FormattedAddressLine Line="3">Israel</FormattedAddressLine>
    </AddressLines>
    <AddressComplete>24, Jaffa
9414201 Jerusalem
Israel</AddressComplete>
```

```
</ResultData>
</Result>
```

Note: Informatica provides separate reference databases for Israel addresses in each script. To verify addresses in the native script, install the native databases. To verify addresses in a Latin script, install the Latin databases.

Input and Result XML in Address Verification

The following example shows how you can verify an Israel address in a SOAP call to Address Verification.

You submit the following request:

```
<soap:Envelope xmlns:soap="http://www.w3.org/2003/05/soap-envelope" xmlns:v="http://
validator5.AddressDoctor.com/Webservice5/v4">
    <soap:Header/>
    <soap:Body>
        <v:Process>
            <v:login>****</v:login>
            <v:password>****</v:password>
            <v:parameters>
                <v:ProcessMode>BATCH</v:ProcessMode>
                <v:ServiceParameters></v:ServiceParameters>
                <v:ValidationParameters>
                    <v:PreferredLanguage>ENGLISH</v:PreferredLanguage>
                </v:ValidationParameters>
            </v:parameters>
            <v:addresses>
                <v:Address>
                    <v:FormattedAddress>
                        <v:string>24 Jaffa</v:string>
                        <v:string>9414201 JERUSALEM</v:string>
                        <v:string>ISR</v:string>
                    </v:FormattedAddress>
                </v:Address>
            </v:addresses>
            <v:enrichments>
            </v:enrichments>
        </v:Process>
    </soap:Body>
</soap:Envelope>
```

Informatica Address Verification returns the following response:

```
<soap:Envelope xmlns:soap="http://www.w3.org/2003/05/soap-envelope" xmlns:xsi="http://
www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
   <soap:Body>
      <ProcessResponse xmlns="http://validator5.AddressDoctor.com/Webservice5/v4">
         <ProcessResult>
            <StatusCode>100</StatusCode>
            <StatusMessage>OK</StatusMessage>
            <Results>
               <Result>
                  <ProcessStatus>V4</ProcessStatus>
                  <CountryISO3>ISR</CountryISO3>
                  <ResultDataSet>
                     <ResultData>
                        <ResultNumber>1</ResultNumber>
                        <MailabilityScore>5</MailabilityScore>
                        <ResultPercentage>100.00</ResultPercentage>
                        <ElementInputStatus>6060006060000000060</ElementInputStatus>
                        <ElementResultStatus>F0F000F0F000000000E0</ElementResultStatus>
                        <ElementRelevance>10100010100000000010</ElementRelevance>
                        <ExtElementStatus>00500000000000000000</ExtElementStatus>
                        <AddressResolutionCode>00000000000000000000</AddressResolutionCode>
                        <AddressType>S</AddressType>
                        <LanguageISO3>ENG</LanguageISO3>
                        <Address>
                           <Street>
                              <string>Jaffa</string>
                           </Street>
```

```
                        <HouseNumber>
                           <string>24</string>
                        </HouseNumber>
                        <Locality>
                           <string>Jerusalem</string>
                        </Locality>
                        <PostalCode>
                           <string>9414201</string>
                        </PostalCode>
                        <Country>
                           <string>ISRAEL</string>
                        </Country>
                        <DeliveryAddressLines>
                           <string>24, JAFFA</string>
                        </DeliveryAddressLines>
                        <CountrySpecificLocalityLine>
                           <string>9414201 JERUSALEM</string>
                        </CountrySpecificLocalityLine>
                        <FormattedAddress>
                           <string>24, JAFFA</string>
                           <string>9414201 JERUSALEM</string>
                           <string>ISRAEL</string>
                        </FormattedAddress>
                        <AddressComplete>24, JAFFA;9414201 JERUSALEM;ISRAEL</AddressComplete>
                     </Address>
                  </ResultData>
               </ResultDataSet>
            </Result>
         </Results>
      </ProcessResult>
   </ProcessResponse>
</soap:Body>
</soap:Envelope>
```

Address Enrichments

You can configure Informatica Address Verification to add the following enrichment to verified Israel addresses:

Enrichment Type	Description
Standard Geocoding	You can retrieve standard, interpolated geocoordinates for valid Israel addresses.

Multilanguage Support for Israel Addresses

You can configure Address Verification to return valid Israel addresses in English or in Hebrew. The default language is Hebrew.

To set the preferred language, configure the `PreferredLanguage` attribute of the Result element in `Parameters.xml`.

The following table describes the `PreferredLanguage` values that you can set for Israel address data:

Option	Description
DATABASE	Default value. Returns all address information in Hebrew.
ENGLISH	Returns all address information in English.
ALTERNATIVE_1	Returns all address information in Hebrew.

Option	Description
ALTERNATIVE_2	Returns all address information in English.
PRESERVE_INPUT	Returns the address information in the input language.

Note: If you select a Latin character set as the preferred script and you select Hebrew as the preferred language, Address Verification transliterates the Hebrew address into Latin characters. For optimal results in a Latin character set, consider selecting English as the preferred language.

Frequently Asked Questions

Can Address Verification (On-Premises) verify an Israel address in the Hebrew script?

Yes. Address Verification (On-Premises) can read and write Israel addresses in Hebrew or Latin scripts.

To set the preferred character set for the address data, configure the `PreferredScript` attribute of the Result element in `Parameters.xml`.

Can Address Verification return an address in the Hebrew script when you verify the address through the cloud interface?

No. When you verify an address through the cloud interface, Address Verification can return the address only in a Latin script.

Does the reference data for Israel contain building and sub-building data?

No. Israel reference data does not contain building or sub-building data.

What is the address format of an Israel address?

Address Verification reads each line of an Israel address from right to left. The street information line begins with the street name, and the house number follows to the left of the street name. Likewise, the locality line begins with the locality name, and the post code follows to the left of the locality name.

For example, consider the element order in the following address:

```
Line1: 23, רב אלוף דוד אלעזר
Line2: 6107000 תל אביב יפו
```

Reference Address Databases

Informatica updates the Israel reference address databases quarterly. You can download the latest database packages from the Informatica Database Download portal. For news about reference address databases and software updates for Address Verification, subscribe to the Informatica DaaS Newsletter from Informatica.

Informatica Address Verification provides the following reference databases for Israel addresses:

- `ISR5BI.MD`. Batch and interactive data.
- `ISR5FC.MD`. Fast completion data.
- `ISR5GC.MD`. Standard geocoding data.

Note: You download databases for Informatica Address Verification (On-Premises). You do not need to download databases for Informatica Address Verification, as Informatica Address Verification uses a cloud interface.

Selecting the Batch and Interactive Files for Your Installation

For Latin data:

Informatica delivers the current versions of the `ISR5BI.MD` and `ISR5FC.MD` files in zip files named `ISR5BI_01.zip` and `ISR5FC_01.zip` respectively. The database files in `ISR5BI_01.zip` and `ISR5FC_01.zip` include Latin script data.

For Hebrew data:

Informatica delivers the current versions of the `ISR5BI.MD` and `ISR5FC.MD` files in zip files named `ISR5BI_02.zip` and `ISR5FC_02.zip` respectively. The database files in `ISR5BI_02.zip` and `ISR5FC_02.zip` include native script data.

Additional Documentation Resources

To view the latest documentation for Informatica Address Verification, check the following help modules on the Informatica Documentation Portal:

- Address Verification (On-Premises) 5.x
- Address Verification 4.0

Author

Shahani Natalia Mendonca

Acknowledgements

The author would like to thank Amarpal Kaur Sohi, David Handy, Farhan Ashraf, and Xiayi Zhang for their assistance.