How-To Library

Informatica

Address Verification Best Practices for Ukraine

© Copyright Informatica LLC 2022. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

This document tells you how to connect the elements in a Ukraine address to the appropriate address elements in Informatica Address Verification. This document also describes best practices that you can implement when you verify addresses in Ukraine.

Supported Versions

- Informatica Address Verification 3.0 and 4.0
- Informatica Address Verification (On-Premises) 5.x

Table of Contents

Introduction. . . . 2
Process Modes. . . . 2
Character Set. . . . 3
Address Format and Address Structure. . . . 3
Key Address Elements. . . . 3
Mapping Input Address Data to Address Elements. . . . 3
Input and Result XML in Address Verification (On-Premises). . . . 4
Input and Result XML in Address Verification. . . . 5
Address Enrichments. . . . 6
Reference Address Databases. . . . 6
Additional Documentation Resources. . . . 7

Introduction

Informatica Address Verification can validate and enhance addresses in Ukraine. This how-to article provides you with configuration information and best practices that you can follow to get the most from the addresses. The best practices include advice on how to select the appropriate XML elements for Ukraine address data.

To verify the quality of an input address, Address Verification compares the address information to the data in one or more reference data files. You can configure Address Verification to analyze the different types of address information in the input data. You must map each item of address information to an appropriate element in Address Verification.

When you select the input address elements, you must ensure that the elements are correct for the different types of input information. The country that the address identifies determines the elements that you need.

Process Modes

Informatica Address Verification supports the following process modes for Ukraine addresses:

- BATCH
- COUNTRY RECOGNITION
- FAST COMPLETION
- INTERACTIVE
- PARSE

Character Set

Ukraine reference address databases store address data in the Cyrillic script.

The `PreferredScript` attribute determines the character set in which Address Verification returns the address data.

The following table shows how Address Verification returns address data for different `PreferredScript` settings in Ukraine:

DATABASE	POSTAL_ADMIN_PREF	POSTAL_ADMIN_ALT	LATIN	LATIN_ALT	LATIN_1
Cyrillic	Cyrillic	Cyrillic	ASCII	ASCII, transliterated to the Ukrainian BGN standard	ASCII, transliterated to the Ukrainian BGN standard

Address Format and Address Structure

You improve the performance of Address Verification when you define the input address in the format that the postal service expects.

The Ukraine postal service recognizes the following structure for a postal address:

```
Line 1: RECIPIENT OR CONTACT NAME
Line 2: STREET NAME HOUSE NUMBER [SUB-BUILDING INFORMATION]
Line 3: CITY
Line 4: POSTAL CODE
Line 5: COUNTRY
```

The following sample address shows the structure:

```
Вул. Сонячна 1
С. Липини
45601
UKR
```

Key Address Elements

Address Verification is unlikely to verify an address successfully if one of the following items is absent from the address:

- Locality
- Postal Code
- Street

Mapping Input Address Data to Address Elements

To verify an address, map the input address information to appropriate elements in Address Verification.

The following table shows how you can map the input address to the address elements:

Information Type	Address Information	Address Elements
Street Name	Вул. Сонячна	Street
House Number	1	HouseNumber

Information Type	Address Information	Address Elements
Postal Code	45601	PostalCode
City	С. Липини	Locality
Country	UKR	Country

Input and Result XML in Address Verification (On-Premises)

The following example shows how you can map the address information to the XML address elements in Address Verification (On-Premises).

You enter the following input address:

```
<InputData>
    <AddressElements>
        <Country Item="1" Type="NAME">UKR</Country>
    </AddressElements>
    <AddressLines>
        <FormattedAddressLine Line="1">Вул. Сонячна 1</FormattedAddressLine>
        <FormattedAddressLine Line="2">С. Липини</FormattedAddressLine>
        <FormattedAddressLine Line="3">45601</FormattedAddressLine>
    </AddressLines>
</InputData>
```

Informatica Address Verification (On-Premises) returns the following result:

```
<?xml version="1.0" encoding="UTF-16"?>

<!-- EngineVersion="5.16.2.60959" -->

<Result     ProcessStatus="V4"
     ModeUsed="BATCH"
     Count="1"
     CountOverflow="NO"
     CountryISO3="UKR"
     PreferredScript="DATABASE"
     PreferredLanguage="DATABASE">

<ResultData ResultNumber="1"
     MailabilityScore="5"
     ResultPercentage="100.00"
     ElementResultStatus="F0F088F0F000000000E0"
     ElementInputStatus="60600060600000000060"
     AddressResolutionCode="00000000000000000000"
     ExtElementStatus="00000000000000000000"
     ElementRelevance="10100010100000000010"
     AddressType="S"
     LanguageISO3="UKR">
    <AddressElements>
        <Country Type="NAME_EN" Item="1">Ukraine</Country>
        <Locality Item="1">с. Липини</Locality>
        <PostalCode Item="1">45601</PostalCode>
        <Province Item="1">Волинська</Province>
        <Province Item="2">Луцький</Province>
        <Street Item="1">вул. Сонячна</Street>
        <Number Item="1">1</Number>
    </AddressElements>
    <AddressLines>
        <DeliveryAddressLine Line="1">Вул. Сонячна 1</DeliveryAddressLine>
        <CountrySpecificLocalityLine Line="1">С. Липини</CountrySpecificLocalityLine>
        <FormattedAddressLine Line="1">Вул. Сонячна 1</FormattedAddressLine>
        <FormattedAddressLine Line="2">С. Липини</FormattedAddressLine>
        <FormattedAddressLine Line="3">45601</FormattedAddressLine>
        <FormattedAddressLine Line="4">Ukraine</FormattedAddressLine>
```

```
    </AddressLines>
    <AddressComplete>Вул. Сонячна 1
с. Липини
45601
Ukraine</AddressComplete>
</ResultData>
</Result>
```

Input and Result XML in Address Verification

The following example shows how you can verify a Ukraine address in a SOAP call to Address Verification.

You submit the following request:

```
<soap:Envelope xmlns:soap=http://www.w3.org/2003/05/soap-envelope xmlns:v=http://
validator5.AddressDoctor.com/Webservice5/v4>
<soap:Header/>
<soap:Body>
<v:Process>
<v:login>*****</v:login>
<v:password>*****</v:password>
<v:parameters>
<v:ProcessMode>BATCH</v:ProcessMode>
<v:ServiceParameters></v:ServiceParameters>
<v:ValidationParameters> </v:ValidationParameters>
</v:parameters>
<v:addresses>
<v:Address>
<v:FormattedAddress>
<v:string>Вул. Сонячна 1</v:string>
<v:string>С. Липини</v:string>
<v:string>45601</v:string>
<v:string>UKR</v:string>
</v:FormattedAddress>
</v:Address>
</v:addresses>
<v:enrichments> </v:enrichments>
</v:Process>
</soap:Body>
</soap:Envelope>
```

Informatica Address Verification returns the following response:

```
<soap:Envelope xmlns:soap=http://www.w3.org/2003/05/soap-envelope xmlns:xsi=http://www.w3.org/
2001/XMLSchema-instance xmlns:xsd=http://www.w3.org/2001/XMLSchema>
   <soap:Body>
      <ProcessResponse xmlns=http://validator5.AddressDoctor.com/Webservice5/v4>
         <ProcessResult>
            <StatusCode>100</StatusCode>
            <StatusMessage>OK</StatusMessage>
            <Results>
               <Result>
                  <ProcessStatus>V4</ProcessStatus>
                  <CountryISO3>UKR</CountryISO3>
                  <ResultDataSet>
                     <ResultData>
                        <ResultNumber>1</ResultNumber>
                        <MailabilityScore>5</MailabilityScore>
                        <ResultPercentage>100.00</ResultPercentage>
                        <ElementInputStatus>6060006060000000060</ElementInputStatus>
                        <ElementResultStatus>F0F088F0F000000000E0</ElementResultStatus>
                        <ElementRelevance>10100010100000000010</ElementRelevance>
                        <ExtElementStatus>00000000000000000000</ExtElementStatus>
                        <AddressResolutionCode>00000000000000000000</AddressResolutionCode>
                        <AddressType>S</AddressType>
                        <LanguageISO3>UKR</LanguageISO3>
                        <Address>
                           <Street>
                              <string>вул. Сонячна</string>
                           </Street>
```

```
                              <HouseNumber>
                                 <string>1</string>
                              </HouseNumber>
                              <Locality>
                                 <string>с. Липини</string>
                              </Locality>
                              <PostalCode>
                                 <string>45601</string>
                              </PostalCode>
                              <Province>
                                 <string>Волинська</string>
                                 <string>Луцький</string>
                              </Province>
                              <Country>
                                 <string>UKRAINE</string>
                              </Country>
                              <DeliveryAddressLines>
                                 <string>Вул. Сонячна 1</string>
                              </DeliveryAddressLines>
                              <CountrySpecificLocalityLine>
                                 <string>С. Липини</string>
                              </CountrySpecificLocalityLine>
                              <FormattedAddress>
                                 <string>Вул. Сонячна 1</string>
                                 <string>С. Липини</string>
                                 <string>45601</string>
                                 <string>UKRAINE</string>
                              </FormattedAddress>
                              <AddressComplete>ВУЛ. СОНЯЧНА 1;С. ЛИПИНИ;45601;UKRAINE</
AddressComplete>
                           </Address>
                        </ResultData>
                     </ResultDataSet>
                  </Result>
               </Results>
            </ProcessResult>
         </ProcessResponse>
      </soap:Body>
   </soap:Envelope>
```

Address Enrichments

You can configure Informatica Address Verification to add enrichments to verified Ukraine addresses.

The following table lists the types of enrichment that you can add to a Ukraine address:

Enrichment Type	Description
Standard Geocoding	You can retrieve standard, interpolated geocoordinates for valid Ukraine addresses.
Arrival Point Geocoding	You can retrieve arrival point geocoordinates for valid Ukraine addresses.

Reference Address Databases

Informatica updates the Ukraine reference address databases yearly. You can download the latest database packages from the Informatica Database Download portal. For news about reference address databases and software updates for Address Verification, subscribe to the Informatica DaaS Newsletter from Informatica.

Informatica Address Verification provides the following reference databases for Ukraine addresses:

- `UKR5BI.MD`. Batch and interactive data.
- `UKR5FC.MD`. Fast completion data.

- `UKR5GC.MD`. Standard geocoding data.
- `UKR5GCAP.MD`. Arrival point geocoding data.

Note: You download databases for Informatica Address Verification (On-Premises). You do not need to download databases for Informatica Address Verification, as Informatica Address Verification uses a cloud interface.

Additional Documentation Resources

To view the latest documentation for Informatica Address Verification, check the following help modules on the Informatica Documentation Portal:

- Address Verification (On-Premises) 5.x
- Address Verification 4.0

Author

Shahani Natalia Mendonca

Acknowledgements

The author would like to thank Amarpal Kaur Sohi, Pawan Nadig, and Xiayi Zhang for their assistance.