How-To Library

Informatica

Address Verification Best Practices for United Arab Emirates

© Copyright Informatica LLC 2022. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

This document tells you how to connect the elements in a United Arab Emirates street address to the appropriate address elements in Informatica Address Verification. This document also describes best practices that you can implement when you verify street addresses in the United Arab Emirates.

Supported Versions

- Informatica Address Verification 3.0 and 4.0
- Informatica Address Verification (On-Premises) 5.x

Table of Contents

Introduction. . . . 2
Process Modes. . . . 2
Character Set. . . . 3
Address Format and Address Structure. . . . 3
Key Address Elements. . . . 3
Mapping Input Address Data to Address Elements. . . . 3
Input and Result XML in Address Verification (On-Premises). . . . 4
Input and Result XML in Address Verification. . . . 5
Frequently Asked Questions. . . . 7
Address Enrichments. . . . 7
Reference Address Databases. . . . 7
Additional Documentation Resources. . . . 7

Introduction

Informatica Address Verification can validate and enhance addresses in the United Arab Emirates. This how-to article provides you with configuration information and best practices that you can follow to get the most from street addresses in the United Arab Emirates. The best practices include advice on how to select the appropriate XML elements for United Arab Emirates address data.

To verify the quality of an input address, Address Verification compares the address information to the data in one or more reference data files. You can configure Address Verification to analyze the different types of address information in the input data. You must map each item of address information to an appropriate element in Address Verification.

When you select the input address elements, you must ensure that the elements are correct for the different types of input information. The country that the address identifies determines the elements that you need.

Process Modes

Informatica Address Verification supports the following process modes for United Arab Emirates addresses:

- BATCH
- COUNTRY RECOGNITION
- FAST COMPLETION

- INTERACTIVE
- PARSE

Character Set

United Arab Emirates reference address databases store address data in the Latin-1 script.

Address Format and Address Structure

You improve the performance of Address Verification when you define the input address in the format that the postal service expects.

The address format of a street address in the United Arab Emirates contains address elements in the following order:

```
Line 1: RECIPIENT OR CONTACT NAME
Line 2: BUILDING INFORMATION [SUB-BUILDING INFORMATION]
Line 3: STREET NAME HOUSE NUMBER
Line 4: LOCALITY
Line 5: PROVINCE
Line 6: COUNTRY
```

The following sample address shows the structure:

```
VILLA 6
ZAGLABA ST 99
DUBAI
DUBAI
ARE
```

Note: The postal service in the United Arab Emirates delivers mail to post office boxes. Courier and parcel delivery services deliver mail to street addresses. For more information on post office box addresses, see "Frequently Asked Questions" on page 7.

Key Address Elements

Address Verification is unlikely to verify an address successfully if one of the following items is absent from the address:

- Locality
- Province
- Street

Mapping Input Address Data to Address Elements

To verify an address, map the input address information to appropriate elements in Address Verification.

The following table shows how you can map the input address to the address elements:

Information Type	Address Information	Address Elements
Street Name	ZAGLABA ST	Street
House Number	99	HouseNumber
Building Name	VILLA 6	Building

Information Type	Address Information	Address Elements
City	DUBAI	Locality
Administrative Region	DUBAI	Province
Country	ARE	Country

Input and Result XML in Address Verification (On-Premises)

The following example shows how you can map the address information to the XML address elements in Address Verification (On-Premises).

You enter the following input address:

```
<InputData>
    <AddressElements>
        <Country Item="1" Type="NAME">ARE</Country>
    </AddressElements>
    <AddressLines>
        <FormattedAddressLine Line="1">VILLA 6</FormattedAddressLine>
        <FormattedAddressLine Line="2">ZAGLABA ST 99</FormattedAddressLine>
        <FormattedAddressLine Line="3">DUBAI</FormattedAddressLine>
        <FormattedAddressLine Line="4">DUBAI</FormattedAddressLine>
    </AddressLines>
</InputData>
```

Informatica Address Verification (On-Premises) returns the following result:

```
<?xml version="1.0" encoding="UTF-16"?>

<!-- EngineVersion="5.16.2.60959" -->

<Result     ProcessStatus="V4"
     ModeUsed="BATCH"
     Count="1"
     CountOverflow="NO"
     CountryISO3="ARE"
     PreferredScript="PRESERVE_INPUT"
     PreferredLanguage="DATABASE">

<ResultData ResultNumber="1"
     MailabilityScore="5"
     ResultPercentage="100.00"
     ElementResultStatus="00F8F0F04000F00000E0"
     ElementInputStatus="00606060200060000060"
     AddressResolutionCode="00000000000000000000"
     ExtElementStatus="000000A0B00000000000"
     ElementRelevance="00101010000000000010"
     AddressType="B"
     LanguageISO3="XXX">
    <AddressElements>
        <Country Type="NAME_EN" Item="1">United Arab Emirates</Country>
        <Locality Item="1">Dubai</Locality>
        <Locality Item="2">Umm Suqeim</Locality>
        <Locality Item="3">Umm Suqeim 2</Locality>
        <Province Item="1">Dubai</Province>
        <Street Item="1">Zaglaba St</Street>
        <Number Item="1">99</Number>
        <Building Item="1">Villa 6</Building>
    </AddressElements>
    <AddressLines>
        <DeliveryAddressLine Line="1">Villa 6</DeliveryAddressLine>
        <DeliveryAddressLine Line="2">Zaglaba St 99</DeliveryAddressLine>
        <CountrySpecificLocalityLine Line="1">Dubai</CountrySpecificLocalityLine>
        <FormattedAddressLine Line="1">Villa 6</FormattedAddressLine>
```

```
        <FormattedAddressLine Line="2">Zaglaba St 99</FormattedAddressLine>
        <FormattedAddressLine Line="3">Dubai</FormattedAddressLine>
        <FormattedAddressLine Line="4">United Arab Emirates</FormattedAddressLine>
    </AddressLines>
    <AddressComplete>Villa 6
Zaglaba St 99
Dubai
United Arab Emirates</AddressComplete>
</ResultData>
</Result>
```

Input and Result XML in Address Verification

The following example shows how you can verify an United Arab Emirates address in a SOAP call to Address Verification.

You submit the following request:

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/" xmlns:v4="http://
validator5.AddressDoctor.com/Webservice5/v4">
   <soapenv:Header/>
   <soapenv:Body>
      <v4:Process>
         <v4:login>....</v4:login>
         <v4:password>.....</v4:password>
         <v4:parameters>
            <v4:ProcessMode>Batch</v4:ProcessMode>
            <v4:ValidationParameters>
            </v4:ValidationParameters>
         </v4:parameters>
         <v4:addresses>
            <v4:Address>
               <v4:Building>
                  <v4:string>Villa 6</v4:string>
               </v4:Building>
               <v4:Street>
                  <v4:string>Zaglaba St</v4:string>
               </v4:Street>
               <v4:HouseNumber>
                  <v4:string>99</v4:string>
               </v4:HouseNumber>
               <v4:Locality>
                  <v4:string>Dubai</v4:string>
               </v4:Locality>
               <v4:PostalCode>
                  <v4:string></v4:string>
               </v4:PostalCode>
               <v4:Province>
                  <v4:string>Dubai</v4:string>
                  </v4:Province>
               <v4:Country>
                  <v4:string>ARE</v4:string>
               </v4:Country>
            </v4:Address>
         </v4:addresses>
         <v4:enrichments>
         </v4:enrichments>
      </v4:Process>
   </soapenv:Body>
</soapenv:Envelope>
```

Informatica Address Verification returns the following response:

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/" xmlns:xsi="http://
www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
   <soap:Body>
      <ProcessResponse xmlns="http://validator5.AddressDoctor.com/Webservice5/v4">
         <ProcessResult>
            <StatusCode>100</StatusCode>
            <StatusMessage>OK</StatusMessage>
```

```
            <Results>
               <Result>
                  <ProcessStatus>V4</ProcessStatus>
                  <CountryISO3>ARE</CountryISO3>
                  <ResultDataSet>
                     <ResultData>
                        <ResultNumber>1</ResultNumber>
                        <MailabilityScore>5</MailabilityScore>
                        <ResultPercentage>100.00</ResultPercentage>
                        <ElementInputStatus>0060606020006000060</ElementInputStatus>
                        <ElementResultStatus>00F8F0F04000F00000E0</ElementResultStatus>
                        <ElementRelevance>00101010000000000010</ElementRelevance>
                        <ExtElementStatus>00000000B00000000000</ExtElementStatus>
                        <AddressResolutionCode>0000000000000000000</AddressResolutionCode>
                        <AddressType>B</AddressType>
                        <LanguageISO3>???</LanguageISO3>
                        <Address>
                           <Building>
                              <string>VILLA 6</string>
                           </Building>
                           <Street>
                              <string>Zaglaba St</string>
                           </Street>
                           <HouseNumber>
                              <string>99</string>
                           </HouseNumber>
                           <Locality>
                              <string>Dubai</string>
                              <string>Umm Suqeim</string>
                              <string>Umm Suqeim 2</string>
                           </Locality>
                           <Province>
                              <string>Dubai</string>
                           </Province>
                           <Country>
                              <string>UNITED ARAB EMIRATES</string>
                           </Country>
                           <DeliveryAddressLines>
                              <string>VILLA 6</string>
                              <string>Zaglaba St 99</string>
                           </DeliveryAddressLines>
                           <CountrySpecificLocalityLine>
                              <string>Dubai</string>
                           </CountrySpecificLocalityLine>
                           <FormattedAddress>
                              <string>VILLA 6</string>
                              <string>Zaglaba St 99</string>
                              <string>Dubai</string>
                              <string>UNITED ARAB EMIRATES</string>
                           </FormattedAddress>
                           <AddressComplete>Villa 6;Zaglaba St 99;Dubai;UNITED ARAB EMIRATES</
AddressComplete>
                        </Address>
                     </ResultData>
                  </ResultDataSet>
               </Result>
            </Results>
         </ProcessResult>
      </ProcessResponse>
   </soap:Body>
</soap:Envelope>
```

Note: Locality 2 and Locality 3 are not postally relevant elements according to local postal guidelines in the United Arab Emirates.

Frequently Asked Questions

How do I create an address for United Arab Emirates postal service delivery?

The postal service in the United Arab Emirates delivers mail to post office boxes.

The address format of a P.O. Box address in the United Arab Emirates contains address elements in the following order:

```
Line 1: RECIPIENT OR CONTACT NAME
Line 2: BUILDING INFORMATION [SUB-BUILDING INFORMATION]
Line 3: POST OFFICE BOX NUMBER
Line 4: PROVINCE
Line 5: COUNTRY
```

Does the reference data for the United Arab Emirates contain house number data?

No, United Arab Emirates reference data does not contain house number data. Address Verification copies the house number from the input to the output.

Is postal code information available for United Arab Emirates addresses?

No, postal code information is not available for United Arab Emirates addresses.

Should I include both locality and province information when I create a street address for delivery?

Yes, include the locality and province names even if both names are the same.

Address Enrichments

You can configure Informatica Address Verification to add the following enrichments to verified United Arab Emirates addresses:

Enrichment Type	Description
Standard Geocoding	You can retrieve standard, interpolated geocoordinates for valid United Arab Emirates addresses.

Reference Address Databases

Informatica updates the United Arab Emirates reference address databases quarterly. You can download the latest database packages from the Informatica Database Download portal. For news about reference address databases and software updates for Address Verification, subscribe to the Informatica DaaS Newsletter from Informatica.

Informatica Address Verification provides the following reference databases for United Arab Emirates addresses:

- `ARE5BI.MD`. Batch and interactive data.
- `ARE5FC.MD`. Fast completion data.
- `ARE5GC.MD`. Standard geocoding data.

Note: You download databases for Informatica Address Verification (On-Premises). You do not need to download databases for Informatica Address Verification, as Informatica Address Verification uses a cloud interface.

Additional Documentation Resources

To view the latest documentation for Informatica Address Verification, check the following help modules on the Informatica Documentation Portal:

- Address Verification (On-Premises) 5.x

- Address Verification 4.0

Author

Shahani Natalia Mendonca

Acknowledgements

The author would like to thank Amarpal Kaur Sohi, David Handy, Farhan Ashraf, and Atsuko Odermatt for their assistance.