How-To Library

Informatica

Address Verification 6.x Best Practices for Australia

© Copyright Informatica LLC 2023. Informatica, Informatica Cloud, and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

This document tells you how to connect the elements in an Australia address to the appropriate address elements in Informatica® Address Verification. This document also describes best practices that you can implement when you verify addresses in Australia.

Supported Versions

- Informatica Address Verification 6.0 and later
- Informatica Address Verification (On-Premises) 6.4.0

Table of Contents

Introduction. . . . 2
Process Modes. . . . 2
Character Set. . . . 3
Certified Mode Validation of Australia Addresses. . . . 3
Address Format and Address Structure. . . . 3
Key Address Elements. . . . 3
Mapping Input Address Data to Address Elements. . . . 4
Input and Result JSON in Address Verification (On-Premises). . . . 4
Input and Result JSON in Address Verification. . . . 5
Address Enrichments. . . . 7
Reference Address Databases. . . . 8
Additional Documentation Resources. . . . 8

Introduction

Informatica Address Verification can validate and enhance addresses in Australia. This how-to article provides you with configuration information and best practices that you can implement when you verify addresses in Australia. The best practices include advice on how to select the appropriate JSON elements for Australia address data.

To verify the quality of an input address, Address Verification compares the address information to the data in one or more reference data files. You can configure Address Verification to identify the different types of address information in the input data.

When you select the input address elements, you must ensure that the elements are correct for the different types of input information. The country that the address identifies determines the elements that you need.

You must map each item of address information to an appropriate element in Address Verification.

Process Modes

Informatica Address Verification supports the following process modes for Australia addresses:

- BATCH
- INTERACTIVE
- CERTIFIED

- QUICK CAPTURE
- GEOCODE TO ADDRESS

Character Set

Australia reference address databases store address data in the Latin-1 script. By default, Informatica Address Verification returns the verified Australia addresses in the Latin-1 script.

Certified Mode Validation of Australia Addresses

You can use certified mode to verify Australia addresses in accordance with the Address Matching Approval System (AMAS) guidelines of Australia Post. To verify Australia addresses in certified mode, you must install the latest certified data. The database file name includes the characters _CO1_, for example `AUS_ADV_VRF_C01_000_6_1_0.MD6`.

The file contains Postal Address File (PAF) data, which includes Australia Post's Delivery Point Identifiers (DPIDs).

Address Format and Address Structure

You improve the performance of Address Verification when you define the input address in the format that the postal service expects.

The Australia postal service recognizes the following structure for a postal address:

```
Line 1: RECIPIENT OR CONTACT NAME
Line 2: [SUB-BUILDING INFORMATION] HOUSE NUMBER STREET NAME STREET TYPE
Line 3: CITY PROVINCE POSTAL CODE
Line 4: COUNTRY
```

The following sample address illustrates the structure:

```
SHOP 7 208 ADELAIDE ST
BRISBANE CITY  QLD  4000
AUS
```

Key Address Elements

Address Verification is unlikely to verify an address successfully if one of the following items is absent from the address:

- Locality
- Postal Code
- Street

Mapping Input Address Data to Address Elements

To verify an address, map the input address information to appropriate elements in Address Verification.

The following table shows how you can map the input address to the address elements:

Information Type	Address Information	Address Elements
Street Name, Street Type	ADELAIDE ST	Street
House Number	208	HouseNumber
Apartment, Floor	SHOP 7	SubBuilding
City	BRISBANE CITY	Locality
State	QLD	AdministrativeDivision
Postal Code	4000	PostalCode

Input and Result JSON in Address Verification (On-Premises)

The following example shows how you can map the address information to the JSON address elements in Address Verification (On-Premises).

You enter the following input address:

```
{
  "Parameters": {
    "Mode": "Batch",
    "CountryDetermination": {},
    "DataSetDetermination": {}
},
  "IO": {
    "Inputs": [
      {
        "AddressElements": { "Country": "AUS" },
        "PreformattedData": {
          "PostalFormattedAdrressLines": [
           "WHITSUNDAY HARBOUR APARTMENTS", "U 156 4 ESHELBY DR"
        ]
       }
      }
    ]
}
}
```

Informatica Address Verification (On-Premises) returns the following result:

```
{
  "Parameters": {
    "Mode": "Batch",
    "CountryDetermination": {},
    "DataSetDetermination": {}
},
  "IO": {
    "Inputs": [
      {
        "AddressElements": { "Country": "AUS" },
        "PreformattedData": {
          "PostalFormattedAdrressLines": [
           "WHITSUNDAY HARBOUR APARTMENTS", "U 156 4 ESHELBY DR"
        ]
       }
      }
```

```
    ],
    "Outputs": [
      {
        "ResultInfo": {

          "ProcessStatus": "V",

          "ProcessModeUsed": "Batch",

          "DeliverAdditionalSuggestions": "No",

          "ResultCount": 1,

          "ResultCountOverflow": false,

          "ResultCountries": [ "AUS" ]
        },
        "Results": [
          {
          "Variants": [
            {
              "StatusValues": {
                "AddressType": "B",
                "LanguageISO3": "ENG",
                "UsedVerificationLevel": "All",
                "MatchPercentage": "100.00",
                "Script": "Native Primary",
                "AddressCount": "",
                "ResultQuality": 6
              },
              "AddressElements": {
                "Street": [{ "Value": "ESHELBY DR" }],
                "HouseNumber": [{ "Value": "4" }],
                "Locality": [{ "Value": "CANNONVALE" }],
                "PostalCode": [{ "Value": "4802" }],
                "AdministrativeDivision": [
                  { "Value": "QLD" }, {"Value": "QUEENSLAND" }
                ],
                "Country": [{ "Code": "AUS", "Name": "AUSTRALIA" }]
               },
               "PreformattedData": {
                 "PostalDeliveryAddressLines": [
                   { "Value": "WHITSUNDAY HARBOUR APARTMENTS" }
                 ],
                 "PostalFormattedAddressLines": [
                   { "Value": "WHITSUNDAY HARBOUR APARTMENTS" }, { "Value": "U 156 4 ESHELBY
DR" }
                 ],
                 "PostalLocalityLine": { "Value": "CANNONVALE QLD 4802" }
               }
              }
             ]
            }
           ]
          }
         ]
        }
```


Input and Result JSON in Address Verification

The following example shows how you can verify an Australia address in a REST call to Address Verification.

You submit the following request:

```
POST /AV6/v1/process HTTP/1.1
        Host: us-av.informaticadaas.com
        Content-Type: application/json
        {
        "Login": "***",
```

```
        "Password": "***",
        "CampaignId": "Campaign222",
        "UseTransactions": "TEST",
        "Request": {
         "Parameters": {
           "Mode": "Batch",
           "CountryDetermination": {},
           "DataSetDetermination": {},
           "CountrySets": [{
              "Process": {
              "AlternativeHandling": {},
              "VerificationLevel": {
              "PreferredVerificationLevel": "All",
              "MinimumVerificationLevel": "All"
            },
            "Geocode": {
            "SearchRadius": "50"
            },
            "Enrichments": {
             "Geocoding": {
              "Rooftop": false,
              "ArrivalPoint": false,
              "StreetCenter": false,
              "PostalCodeCenter": false,
              "LocalityCenter": false
             },
             "Global": false,
             "CountrySpecific": false,
             "CAMEO": false
            }
          }
         }
       ]
     },
     "IO": {
       "Inputs": [
         {
           "AddressElements": {
             "Building": [{ "Value": "WHITSUNDAY HARBOUR APARTMENTS" }],
             "SubBuilding": [{ "Value": "U 156" }],
             "Street": [{ "Value": "ESHELBY DR" }],
             "HouseNumber": [{ "Value": "4" }],
             "Locality": [{ "Value": "CANNONVALE" }],
             "PostalCode": [{ "Value": "4802" }],
             "AdministrativeDivision": [{ "Value": "QLD" }],
             "Country": "AUS"
           }
         }
       ]
     }
   }
}
```

Informatica Address Verification returns the following response:

```
{
           "Status": "Ok",
           "StatusDescription": "No error",
           "TransactionInfo": {
              "TotalTransactionsCharged": 1,
              "TransactionPools": [      {
                  "Type": "BATCH",
                  "TransactionsCharged": 1
            }]
     },
     "CampaignId": "Campaign222",
     "Response": [   {
        "ResultInfo":       {
          "ProcessStatus": "V",
          "ProcessModeUsed": "Batch",
          "ResultCount": 1,
```

```
        "ResultCountOverflow": false,
        "ResultCountries": ["AUS"]
    },
    "Results": [{"Variants": [    {
       "StatusValues":
          "AddressType": "B",
          "LanguageISO3": "ENG",
          "UsedVerificationLevel": "ALL",
          "MatchPercentage": "100.00",
          "Script": "Database",
          "AddressCount": "",
          "ResultQuality": 6
     },
     "AddressElements":            {
        "Street": [               {
           "Value": "ESHELBY DR",
        }]
        "HouseNumber": [          {
        "Value": "4",
        }]
        "Locality": [             {
           "Value": "CANNONVALE",
        }]
        "PostalCode": [           {
           "Value": "4802"
        }]
        "AdministrativeDivision":  [
                                   {
             "Value": "QLD",
        }]
        "Country": [              {
          "Code": "AUS",
          "Name": "AUSTRALIA"
        }]
      },
      "PreformattedData":          {
         "PostalDeliveryAddressLines": [{"Value": "WHITSUNDAY HARBOUR APARTMENTS"}],
         "PostalFormattedAddressLines":          [
            {"Value": "WHITSUNDAY HARBOUR APARTMENTS"},
            {"Value": "U 156 4 ESHELBY DR"}
         ],
         "PostalLocalityLine": {"Value": "CANNONVALE QLD 4802"}
      }
    }]}]
  }]
}
```


Address Enrichments

You can configure Informatica Address Verification to add enrichments to verified Australia addresses.

The following table lists the types of enrichment that you can add to an Australia address:

Enrichment Type	Description
CAMEO	You can retrieve CAMEO profiles as enrichments for valid Australia addresses. CAMEO profiles are consumer classification systems that provide socio-economic and demographic indicators about the residents at the address.
Standard geocoding	You can retrieve standard, interpolated geocoordinates for valid Australia addresses.
Arrival Point geocoding	You can retrieve arrival point geocoordinates for valid Australia addresses.
Rooftop geocoordinates	You can retrieve high-precision roof top geocoordinates for valid Australia addresses.

Reference Address Databases

Informatica updates the Australia reference address databases monthly. You can download the latest database packages from the Informatica Database Download portal. For news about reference address databases and software updates for Address Verification, subscribe to the SupportFlash newsletter from Informatica.

Informatica obtains its reference data for Australia from Australia Post, the national postal authority in Australia, and from other sources. In cases where a reference data file contains data from Australia Post, Informatica includes the characters _000_ in the database file name. When a reference data file contains data from another source, Informatica includes the characters _001_ in the database file name.

The following table lists the reference databases that Informatica provides for Australia addresses:

Database Name	Database Contents
AUS_ADV_ENR_CAM_000_6_1_0.MD6	CAMEO enrichments
AUS_ADV_ENR_GAP_000_6_1_0.MD6	Geocoding data, Arrival Point level
AUS_ADV_ENR_GAP_001_6_1_0.MD6	Geocoding data, non-postal Arrival Point level
AUS_ADV_ENR_GRT_000_6_1_0.MD6	Geocoding data, Rooftop level
AUS_ADV_ENR_GRT_001_6_1_0.MD6	Geocoding data, non-postal Rooftop level
AUS_ADV_ENR_GST_000_6_1_0.MD6	Geocoding data, Standard level
AUS_ADV_ENR_GST_001_6_1_0.MD6	Geocoding data, non-postal Standard level
AUS_ADV_ENR_EN1_000_6_1_0.MD6	Country-specific enrichments
AUS_ADV_RLK_GTA_000_6_3_0.MD6	Reverse lookup - geocode to address data
AUS_ADV_RLK_GTA_001_6_3_0.MD6	Reverse lookup - non-postal geocode to address data
AUS_ADV_VRF_BIA_000_6_3_0.MD6	Batch/Interactive verification data
AUS_ADV_VRF_BIA_001_6_3_0.MD6	Batch/Interactive non-postal verification data
AUS_ADV_VRF_QCP_000_6_3_0.MD6	QuickCapture verification data
AUS_ADV_VRF_QCP_001_6_3_0.MD6	QuickCapture non-postal verification data
AUS_ADV_VRF_C01_000_6_1_0.MD6	Certified verification data

Additional Documentation Resources

To view the latest documentation for Informatica Address Verification, click the following links:

https://network.informatica.com/community/informatica-network/products/data_quality/data-as-a-service/address-doctor

https://network.informatica.com/community/informatica-network/products/data_quality/data-as-a-service/address-doctor-cloud

Author

Dishari Dutta