How-To Library

Informatica

Address Verification 6.x Best Practices for Singapore

© Copyright Informatica LLC 2023, 2024. Informatica and the Informatica logo are trademarks or registered trademarks of Informatica LLC in the United States and many jurisdictions throughout the world. A current list of Informatica trademarks is available on the web at https://www.informatica.com/trademarks.html.

Abstract

This document tells you how to connect the elements in a Singapore address to the appropriate address elements in Informatica Address Verification. This document also describes best practices that you can implement when you verify addresses in Singapore.

Supported Versions

- Informatica Address Verification (On-Premises) 6.5
- Informatica Address Verification 6.5

Table of Contents

Introduction. . . . 2
Process Modes. . . . 2
Character Set. . . . 3
Address Format and Address Structure. . . . 3
Mapping Input Address Data to Address Elements. . . . 3
Input and Result JSON in Address Verification (On-Premises). . . . 3
Input and Result JSON in Address Verification. . . . 5
Address Enrichments. . . . 7
Reference Address Databases. . . . 7
Additional Documentation Resources. . . . 8

Introduction

Informatica Address Verification can validate and enhance addresses in Singapore. This how-to article provides you with configuration information and best practices that you can implement when you verify addresses in Singapore. The best practices include advice on how to select the appropriate JSON elements for Singapore address data.

To verify the quality of an input address, Address Verification compares the address information to the data in one or more reference data files. You can configure Address Verification to identify the different types of address information in the input data. You must map each item of address information to an appropriate element in Address Verification.

When you select the input address elements, you must ensure that the elements are correct for the different types of input information. The country that the address identifies determines the elements that you need.

Process Modes

Informatica Address Verification supports the following process modes for Singapore addresses:

- BATCH
- GEOCODE TO ADDRESS
- INTERACTIVE
- QUICK CAPTURE

Character Set

Singapore reference address databases store address data in the Latin-1 script. By default, Informatica Address Verification returns verified Singapore addresses in the Latin-1 script.

Address Format and Address Structure

You improve the performance of Address Verification when you define the input address in the format that the postal service expects.

The Singapore postal service recognizes the following structure for a postal address:

```
Line 1: RECIPIENT OR CONTACT NAME
Line 2: [BLOCK NUMBER, HOUSE NUMBER, OR BUILDING NUMBER] STREET
Line 3: [SUB-BUILDING INFORMATION][BUILDING INFORMATION]
Line 4: CITY POSTAL CODE
Line 5: COUNTRY
```

The following sample address illustrates the structure:

```
528 ANG MO KIO AVENUE 10
FLOOR 01 UNIT 2385 CHENG SAN CENTRE
SINGAPORE 560528
SGP
```

Mapping Input Address Data to Address Elements

To verify an address, map the input address information to appropriate elements in Address Verification.

The following table shows how you can map the input address to the address elements:

Information Type	Address Information Example	Address Elements
Street Name, Street Type	ANG MO KIO AVENUE 10	Street
House Number	528	HouseNumber
Postal Code	560528	PostalCode
City	SINGAPORE	Locality
Building Name	CHENG SAN CENTRE	Building
Floor	FLOOR 01	Sub-building 1
Apartment	UNIT 2385	Sub-building 2

Input and Result JSON in Address Verification (On-Premises)

The following example shows how you can map the address information to the JSON address elements in Address Verification (On-Premises).

You enter the following input address:

```
{
  "Parameters": {
    "Mode": "Batch",
    "CountryDetermination": {},
    "DataSetDetermination": {}
  },
```

```
  "IO": {
    "Inputs": [
      {
        "AddressElements": {
          "Street": [ { "Value": "MARINA SOUTH DRIVE" } ],
          "HouseNumber": [ { "Value": "51" } ],
          "Locality": [ { "Value": "SINGAPORE" } ],
          "PostalCode": [ { "Value": "018930" } ],
          "Country": "SGP"
        }
      }
    ]
  }
}
```

Informatica Address Verification (On-Premises) returns the following result:

```
{
  "Parameters": {
    "Mode": "Batch",
    "CountryDetermination": {},
    "DataSetDetermination": {}
  },
  "IO": {
    "Inputs": [
      {
        "AddressElements": {
          "Street": [ { "Value": "MARINA SOUTH DRIVE" } ],
          "HouseNumber": [ { "Value": "51" } ],
          "Locality": [ { "Value": "SINGAPORE" } ],
          "PostalCode": [ { "Value": "018930" } ],
          "Country": "SGP"
        }
      }
    ],
    "Outputs": [
      {
        "ResultInfo": {
          "ProcessStatus": "V",
          "ProcessModeUsed": "Batch",
          "DeliverAdditionalSuggestions": "No",
          "ResultCount": 1,
          "ResultCountOverflow": false,
          "ResultCountries": [ "SGP" ]
        },
        "Results": [
          {
            "Variants": [
              {
                "StatusValues": {
                  "AddressType": "S",
                  "LanguageISO3": "ENG",
                  "UsedVerificationLevel": "All",
                  "MatchPercentage": "100.00",
                  "Script": "Native Primary",
                  "AddressCount": "",
                  "ResultQuality": 6
                },
                "AddressElements": {
                  "Street": [ { "Value": "MARINA SOUTH DRIVE" } ],
                  "HouseNumber": [ { "Value": "51" } ],
                  "Locality": [ { "Value": "SINGAPORE" } ],
                  "PostalCode": [ { "Value": "018930" } ],
                  "Country": [ { "Code": "SGP", "Name": "SINGAPORE" } ]
                },
                "PreformattedData": {
                  "PostalDeliveryAddressLines": [
                    { "Value": "51 MARINA SOUTH DRIVE" }
                  ],
                  "PostalFormattedAddressLines": [
                    { "Value": "51 MARINA SOUTH DRIVE" }, { "Value": "SINGAPORE 018930" }
```

```
                    ],
                    "PostalLocalityLine": { "Value": "SINGAPORE 018930" }
                  }
                }
              ]
            }
          ]
        }
      ]
    }
  }
```

Input and Result JSON in Address Verification

The following example shows how you can verify a Singapore address in a REST call to Address Verification.

You submit the following request:

```
{
  "Login": *****,
  "Password": *****,
  "CampaignId": "Campaign222",
  "UseTransactions": "TEST",
  "Request": {
    "Parameters": {
      "Mode": "Batch",
      "CountryDetermination": {},
      "DataSetDetermination": {},
      "CountrySets": [
        {
          "Process": {
            "AlternativeHandling": {
              "OutdatedAddresses": { "Match": "Off", "GetNewAddress": false },
              "AliasAddresses": { "Match": "Off" }
            },
            "VerificationLevel": {
              "PreferredVerificationLevel": "All",
              "MinimumVerificationLevel": "All"
            },
            "Geocode": { "SearchRadius": "50" },
            "Enrichments": {
              "Geocoding": {
                "Rooftop": false,
                "ArrivalPoint": false,
                "StreetCenter": false,
                "PostalCodeCenter": false,
                "LocalityCenter": false
              },
              "Global": false,
              "CountrySpecific": false,
              "CAMEO": false
            }
          }
        }
      ]
    },
            "IO": {
    "Inputs": [
      {
        "AddressElements": {
          "Street": [ { "Value": "MARINA SOUTH DRIVE" } ],
          "HouseNumber": [ { "Value": "51" } ],
          "Locality": [ { "Value": "SINGAPORE" } ],
          "PostalCode": [ { "Value": "018930" } ],
          "Country": "SGP"
        }
      }
    ]
  }
```

```
  }
}
```

Informatica Address Verification returns the following response:

```
{
    "Status": "Ok",
    "StatusDescription": "No error",
    "TransactionInfo": {
        "TotalTransactionsCharged": 1,
        "TransactionPools": [
            {
                "Type": "BATCH",
                "TransactionsCharged": 1
            }
        ]
    },
    "CampaignId": "Campaign222",
    "Response": [
        {
            "ResultInfo": {
                "ProcessStatus": "V",
                "ProcessModeUsed": "Batch",
                "DeliverAdditionalSuggestions": "No",
                "ResultCount": 1,
                "ResultCountOverflow": false,
                "ResultCountries": [
                    "SGP"
                ]
            },
            "Results": [
                {
                    "Variants": [
                        {
                            "StatusValues": {
                                "AddressType": "S",
                                "LanguageISO3": "ENG",
                                "UsedVerificationLevel": "All",
                                "MatchPercentage": "100.00",
                                "Script": "Native Primary",
                                "AddressCount": "",
                                "ResultQuality": 6
                            },
                            "AddressElements": {
                                "Street": [
                                    {
                                        "Value": "MARINA SOUTH DRIVE"
                                    }
                                ],
                                "HouseNumber": [
                                    {
                                        "Value": "51"
                                    }
                                ],
                                "Locality": [
                                    {
                                        "Value": "SINGAPORE"
                                    }
                                ],
                                "PostalCode": [
                                    {
                                        "Value": "018930"
                                    }
                                ],
                                "Country": [
                                    {
                                        "Code": "SGP",
                                        "Name": "SINGAPORE"
                                    }
                                ]
                            },
```

```
                "PreformattedData": {
                    "PostalDeliveryAddressLines": [
                        {
                            "Value": "51 MARINA SOUTH DRIVE"
                        }
                    ],
                    "PostalFormattedAddressLines": [
                        {
                            "Value": "51 MARINA SOUTH DRIVE"
                        },
                        {
                            "Value": "SINGAPORE 018930"
                        }
                    ],
                    "PostalLocalityLine": {
                        "Value": "SINGAPORE 018930"
                    }
                }
            }
        ]
    }
]
}
```


Address Enrichments

You can configure Informatica Address Verification to add enrichments to verified Singapore addresses.

The following table lists the types of enrichment that you can add to a Singapore address:

Enrichment Type	Description
CAMEO	You can retrieve CAMEO profiles as enrichments for valid Singapore addresses. CAMEO profiles are consumer classification systems that provide socio-economic and demographic indicators about the residents at the address.
Geocoding	You can perform geocoding for Singapore addresses to the ArrivalPoint level of precision only.

Reference Address Databases

Informatica updates some of the Singapore reference address databases quarterly and some twice a year. You can download the latest database packages from the Informatica Database Download portal. For news about reference address databases and software updates for Address Verification, subscribe to the Informatica DaaS Newsletter from Informatica.

Informatica Address Verification provides the following reference databases for Singapore quarterly:

- `SGP_ADV_VRF_BIA_000_6_x_0.MD6`. Batch and interactive data.
- `SGP_ADV_VRF_QCP_000_6_x_0.MD6`. QuickCapture data.

Informatica Address Verification provides the following reference databases for Singapore twice a year:

- `SGP_ADV_RLK_GTA_000_6_x_0.MD6`. GeocodeToAddress data.
- `SGP_ADV_ENR_GAP_000_6_x_0.MD6`. ArrivalPoint geocoding data.
- `SGP_ADV_ENR_GST_000_6_x_0.MD6`. Standard geocoding data.

Note: You download databases for Informatica Address Verification (On-Premises). You do not need to download databases for Informatica Address Verification, as Informatica Address Verification uses a cloud interface.

Additional Documentation Resources

To view the latest documentation for Informatica Address Verification, click the following links:

https://docs.informatica.com/data-as-a-service/address-verification-(on-premises)/6-4-0.html

https://docs.informatica.com/data-as-a-service/address-verification/6-4-0.html

Author

Dishari Dutta